

I N D E X

	Page
Absolute Sensitivity, Tests for	8, 15
Accumulator Operation, Receiver for (see under Receiver)	
Air Cell, Operation, Dual Wave Receiver for	69
Receivers, Valves for	25
Resistors for use with	96
Valve Combinations for	27
Amplified A.V.C.	56
Amplifiers, Class AB, Operation of Push-Pull Triode	64
Class B, Matching for	8
Multi-Stage	27
Pentode, Resistance Coupled	37, 50, 87
Pentode, Resistance Coupled, By-pass Condensers in	39
Triode, Operating Conditions for	78
Triode, Push-Pull, Part I—Theoretical	64
Triode, Push-Pull, Part II—Graphical Application	78
Triode, Push-Pull, Power Output and Optimum Load for	65
7 Watt, Fidelity (A115)	45
13.5 Watt, Fidelity (A120)	53
30 Watt Transformer Coupled 6L6G, with Negative Feedback	43
Attenuation Function of Stage	89
Automatic Volume Control	47
Diode Load	86
Distortion with	55
Filter Circuits, Design of	86
Filter, Purpose of	86
Operation of Converter or I.F. Stage with	86
Special Arrangement to Avoid Overloading	69
System, Time Constant of	86
Balanced Tone	6
Band Width, Variable	90
Barretter 302, Application of	67, 80
Bass Boosting	5, 14
Battery, B, Conditions for Lower Drain	61
B Class Amplifier (See under Amplifiers)	
Blocking, Grid, in Battery Receivers	59
Broadcast Band, Operation of 1C6 on	63
Coils for Operation of 1C6 on	63
Buffer I.F.	90
By-pass Condensers in Resistance Coupled Pentode Amplifiers	39
Cathode Ray Oscillograph for Testing	2, 15, 35, 42
Cathode Resistor, Prediction of, for Push-Pull Triode Amplifiers	64
Characteristic Curves, Operating Conditions Calculated from	64
Dynamic, Drawing of	78
Dynamic, for Zero Plate Circuit Distortion	74
Coils for Battery Amateur Receiver (A73)	84
Operation on Broadcast Band	63
Short Wave 1C6 Operation	63
Primary High Impedance	93
Coil Winding Data for Amateur Receiver	34
Computation of Third Harmonic	78
Conversion A.C./D.C. using 866	9
Converter, Operation of, with A.V.C.	86
Converter Valves, Difficulty in lining up	60
I.F. Sensitivity Measurement	10
Testing while oscillating	10
Cross Modulation	56
Crystal Bridge Circuit	32
Decoupling with Multi-Stage Amplifiers	28
Degeneration, Harmonic Distortion reduced by	93
Design of A.V.C. Filter Circuits	86
Detector, High Impedance Reflex	93
See also under Diode, etc.	
Differential Loading, Distortion due to	56
Diode Detectors, Compensated Circuit for	21
Distortion in	11, 20
Need high input voltage	58
Diode, Load, A.V.C.	86
Load Resistance, A.C. Shunting of	11
Separate, for A.V.C.	60
Dissipation, Plate and Screen, in Tetrodes and Pentodes	76
Distortion, Criterion of	78
Determination of, and Power Output	75
Determining Power Output, when negligible	74
Dynamic Characteristics for Zero Plate Circuit	74
Effect of Speaker Resonance on	3
Graphical Determination of	78
Harmonic, Measurement of	2-3
Harmonic, reduced by Degeneration (see also under Inverse Feedback)	93
In Diode Detectors	11, 20

	Page
In Resistance Coupled Pentode Amplifiers	39
Prediction of, in Push-Pull Triode Amplifiers	64
With A.V.C.	55
Dropping Resistors, Voltage Dividers and	95
Dynamic Characteristic, Drawing of	78
For Zero Plate Circuit Distortion	74
Resistance	90
Feedback, No Instability caused by, from a Push-Pull Stage	65
Fidelity, Amplifier Single 2A3 (D41 Receiver)	5
Amplifier, 7 Watt 2A3 (A115)	45
Amplifier, 13.5 Watt 2A3 (A120)	53
Receiver, Testing for	2-3
Filament Circuit Regeneration	83
Filter Circuits, Design of A.V.C.	86
Purpose of A.V.C.	86
Time Constant of	86
Frequency Characteristics of Tuned Circuits	89
Response, Resistance Coupled Pentode Amplifier	38
Graphical Method, Push-Pull Triode Amplifiers, Part I—Theoretical	64
Push-Pull Triode Amplifiers, Part II—Application	78
Grid Bias, Graphical Prediction of, for Push-Pull Triode Amplifiers	64, 78
Blocking, Battery Receivers	59
G Series, Radiotron	88
Handbook 464	25
Harmonic Analysis, Value of Plate Current in	75
Components of Plate Current	75
Distortion (See under Distortion)	
Third, Computation of	79
High Impedance Primary Coils	93
Reflex Detector	93
Hum from poor filtering	28
Injection	27
I.F., Amplifier, A.V.C. applied to	86
Buffer	90
Sensitivity, Reading of	10
Input Capacity due to Miller Effect	13
Inverse Feedback, Resistance Coupling Applied to 1D4	7
Series	18, 58
Series, applied to 43 in 5-6 valve A.C./D.C. Receiver (E51)	67
Series, applied to 6V6G	81-82
Series, Arrangement (D42), (D43). Equivalent Circuit for	19, 36, 82, 87
Series, applied to 1D4 and 1F4	70
Series, Reduction of Effective Load by	87
Series, See-saw Voltage Effect	87
Series, Why a Pentode First Stage is necessary with	87
Transformer Coupling Applied to 1D4	7
30 Watt 6L6G Push-Pull Amplifier Transformer Coupled	43
Level Indicator using Radiotron 6G5	77
Load, Change of Power with	74
Diode, A.V.C.	86
Optimum, and Power Output for Push-Pull Triode Amplifiers	64
Optimum, for Pentodes, Determining of	74
Optimum, for Triodes	75
Reduction of Effective, by Series Inverse Feedback	87
Resistance Calculations, Plate to Plate	17
Resistance, Diode, A.C. Shunting of	11
Resistance, Prediction of, for Push-Pull Triode Amplifiers	64
Load Line	72
Operating A.C.	74
Plate to Plate, used as Basis for Calculations	64
Position, Approximation to	75
Shifting of, for Improved Accuracy in Calculation	75
Loud Speaker, Loading, Effect of Variation in, on Tetrodes and Pentodes	76
See under Speaker	
Magic Eye Tuning Indicator	68, 77, 82, 95
Matching of Output Valves	8
Mercury, Vapour Rectifier (See under Rectifier)	
Miller Effect	13, 90
Modulated Amplifier (See under Series or Plate Modulation)	
Modulation, by Ripple Voltage in Class AB, operation	64
Rise	55
Series	51
Plate	59
Negative Feedback (See Inverse Feedback)	
Noise Silencer	33
Operating Conditions, Calculated from Characteristic Curves	64
For Push-Pull Triode Amplifiers	79
Oscillation in Power Valves	60
Oscillograph for Testing Absolute Sensitivity	15
913 and Corrected Circuit	35, 42
Output Valves, Matching of	8
Pass Band Response	90
Pentode Amplifiers (See under Amplifiers)	
Pentodes, Determining Optimum Load for	74
Effect of Variation in Loudspeaker Loading on Tetrodes and	76
Plate and Screen Dissipation in	76

	Page
Power, Matching	8
Resistance Coupled, in Multi-Stage Amplifiers	27
Self Compensating	23
Use of Zero Bias Characteristics of	76
Photo Tube Types	17
Plate, Current, D.C. Compensating for Rise in	75
Current, Harmonic Components of	75
Current, Value of, in Harmonic Analysis	75
Dissipation in Tetrodes and Pentodes	76
Family Characteristics in Valve Output Calculations	72
Modulated Amplifier	59
Regulation, Effects of	76
Power, Alternating, in Load	74
Delivered to Plate Circuit	76
Output and Distortion, Determination of	75
Output and Optimum Load for Push-Pull Triode Amplifiers	65
Output Calculations, Use of the Plate Family for	72
Output, Change in, with Load	74
Output, Determining, when Distortion is negligible	74
Output, Maximum, Class AB ₁ Conditions necessary for	64
Output, Maximum, Determination of Working Constants for	78
Output, Prediction of, by graphical means for Push-Pull Triode Amplifiers	64
Power, Peak Alternating, in Load	74
Power Supply Resistance, Effects of	76
Power Valves, Oscillation in	60
See also under Pentodes and Triodes	
Primary Coils, High Impedance	93
Problem of Variable Selectivity	89
Push Pull Stage, No instability caused by Feedback from	64
Triode Amplifiers (See under Amplifiers)	
Q Factor of Coupled Circuits	90
Radiotron G Series	88
Receiver, Air Cell, Valves for	25
Amateur	16
Amateur Battery Receiver (A73)	83
Amateur Junior (C71)	33
Amateur Senior (C111)	30
T.R.F. High Quality Output (D71)	92
5 valve A.C. Fidelity (D41)	3, 10
5 Valve A.C. with Inverse Feedback (D42)	19, 36
5 Valve A.C. with Series Inverse Feedback using 6V6G (D43)	82
5-6 Valve A.C./D.C. with Series Inverse Feedback (E51)	67
5 Valve Battery (A55)	26
5 Valve Dual Wave, for Accumulator, Air Cell, or Vibrator Operation (A56) and (A57)	69
Rectifier, High Voltage, 866	9
Mercury Vapour	57
Reflex Detector, High Impedance	93
Regeneration, Filament Circuit	83
Regulation, Effects of Plate and Screen	76
Regulator, Voltage	94
Resistance, Coupled Pentode Amplifier	37, 50, 87
Coupling, Shunt Feedback with 1D4	7
Resistors for Air Cells	96
Response, Pass Band	90
Ripple Voltage, Effects of, reduced by Push-Pull Operation	65
Modulation by, in Class AB ₁ Amplifiers	64
Rise in D.C. Plate Current, Compensating for	75
Screen Dissipation in Tetrodes and Pentodes	76
Dropping Resistor gives Compensation with Pentodes	23
Regulation, Effects of	76
Supply for Resistance Coupled Audio Amplifiers	95
Supply for Converter Valves	95
Supply for I.F. Amplifiers	95
Supply for R.F. Amplifiers	95
See-saw Voltage Effect with Series Inverse Feedback	87
Selectivity, Problem of Variable	89
Self Bias, Compensation with Pentodes	23
Operating Conditions for Push-Pull Triodes	78
Sensitivity, Absolute Tests for	8, 15
I.F.	10
Series Inverse Feedback (See under Inverse Feedback)	
Series Modulation	51
Series Operation, Heating Time with	10
Short Wave Operation, 1C6	61
Coils for	63
Shunt Feedback with Resistance Coupling	7
Signal Generator, Reading Sensitivity with	10
Speaker Resonance, Effect of, on Distortion	3
Stable D.C. Voltage for Oscillators	94
Stability in Multi-Stage Amplifiers	28
Stability, 6D6, Improved	67
Tapped Volume Control for Tone Compensation	5
Testing for Fidelity	2-3
Tetrodes, Plate and Screen Dissipation in	76
Third Harmonic, Computation of	78

	Page
Tone Compensation	5, 22
Transformer Coupling, Inverse Feedback with Design	7
Input, to Class AB ₁ Amplifiers	57
Output, Air Gap in	58
Power, Current Rating of	60
Triode Amplifiers (See under Amplifiers)	58
Triodes, Power, Operating Data on	57
Tuned Circuit, Form of Attenuation Function of	89
Frequency Characteristic of	89
Tuner, R.F.	92
Tuning Indicator, Magic Eye	68, 77, 82, 95
U.H.F., Water Cooled Valves for	71
Variable Band Width	90
Variable Selectivity, Problem of	89
Vibrator, Operation, 5 valve Dual Wave Receiver for	69
Sets, High Output from 1D4	56
Voltage Dividers and Dropping Resistors	95
Voltage Regulator	94
Volume Control (See under A.V.C.)	
Tapped, for Tone Compensation	5
Water Cooled Valves for U.H.F.	71
Wave Analyser	2
Working Constants for Maximum Power Output, Determination of	78
Zero Bias Characteristics of Pentode, Use of	76
Bias, Improved Conditions for 1C6	61
1C6 Operation on Broadcast Band	63
1C6 Short Wave Operation, Coils for	63
1C6 Short Wave Operation, Improved Conditions for Zero Bias	61
1D4 With Series Inverse Feedback	18
1D4 With Shunt Inverse Feedback	7
1D4 With Transformer Coupling and Inverse Feedback	7
2A3 As Fidelity Amplifier	3
2A3 Matching	8
2A3 T.R.F. Receiver (D71)	92
2A3 Voltage Regulator	94
2A3 3.5 Watt Single Amplifier (D41)	5
2A3 7 Watt Fidelity Amplifier (A115)	45
2A3 13.5 Watt Fidelity Amplifier (A120)	53
6AC5G Announcement	96
6C6 For Tone Compensation	6, 22
6D6 Greater Stability of	67
6D8G Announcement	57
6G5 Applications	68, 77, 82, 95
6G5 Level Indicator using	77
6L5G Announcement	57
6L6G 30 Watt Amplifier with Negative Feedback	43
6N5 Announcement	57
6S7G Announcement	57
6T7G Announcement	57
6V6G Data	57
6V6G Application	81, 82
6V6G In Class AB ₁	81
6V6G Use of in Public Address Amplifier	81
6V6G With Inverse Feedback (See also under Inverse Feedback)	81, 82, 87
6V6G 30 Watt Amplifier with Negative Feedback	43
6ZY5G Announcement	96
42 With Series Inverse Feedback (See also under Inverse Feedback)	18-19, 36
50 Matching	8
75 Inability to give High Voltage Output	13
302 Barretter, Announcement	67, 80
806 Data	24
807 High Ratings for	85
808 Data	16
833 Announcement and Data	85
845 Dynamic Characteristics of	66, 78
845 Matching of	8
845 Self Bias Operating Conditions for	79
866 High Voltage Rectifier	9
868 Photo Tube	17
887 Announcement—Data	71
888 Announcement—Data	71
913 Application to Oscillograph	35, 42
921 Announcement and Data	79
922 Announcement	79
1603 Announcement	80
1603 Less Microphonic than 6C6	81
1608 Announcement, Data	79
1609 Announcement, Data	79
1610 Announcement, Data	79
1612 Announcement	96
1800 Announcement	96
1801 Announcement	96