

Abstracts and References

Compiled by the Radio Research Board and reproduced by arrangement with the Department of Scientific and Industrial Research

For the information of new readers it is pointed out that the length of an abstract is generally no indication of the importance of the work concerned. An important paper in English, in a journal likely to be readily accessible, may be dealt with by a square-bracketed addition to the title, while a paper of similar importance in German or Russian may be given a long abstract. In addition to these factors of difficulty of language and accessibility, the nature of the work has, of course, a great influence on the useful length of its abstract.

	PAGE		PAGE
Propagation of Waves	499	Directional Wireless	509
Atmospherics and Atmospheric Electricity	501	Acoustics and Audio-Frequencies .	509
Properties of Circuits	501	Phototelegraphy and Television ...	511
Transmission	503	Measurements and Standards ...	514
Reception	504	Subsidiary Apparatus and Materials	516
Aerials and Aerial Systems ...	506	Stations, Design and Operation ...	521
Valves and Thermionics	507	Miscellaneous	521

PROPAGATION OF WAVES

3219. OBSERVATIONS OF FREQUENCY-MODULATION PROPAGATION ON 26 MEGACYCLES [Simplified Analysis showing Distortion occurring with Two-Path Transmission consists of Introduction of New Modulation Frequency which is Frequency-Modulated and is Not Harmonically Related to Fundamental Modulation Frequency: Riverhead Observations from W₉XA, Kansas City (1150 Miles)].—M. G. Crosby. (*Proc. I.R.E.*, July 1941, Vol. 29, No. 7, pp. 398-403.)
3220. FURTHER COMPARISONS OF METEOROLOGICAL SOUNDINGS BY RADIO WAVES WITH RADIOSONDE DATA [and the Effects of Water Vapour & Condensed Drops].—A. W. Friend. (*Bull. Am. Meteorol. Soc.*, Feb. 1941, Vol. 22, No. 2, pp. 53-59: Discussion pp. 59-61.)

For a previous report see 3728 of 1940. "By radiosonde comparisons and improved operating techniques it has been found possible to make the older equipment [7 of 1940: "older" in comparison with new apparatus not yet in regular use] yield many more data. . . . The weaker tropospheric radio-wave reflections from discontinuities in upper air regions are made observable only because of a continuous background of radio-wave pulse reflection [reflection coefficient around 10^{-6} to 10^{-7}] of sufficient magnitude to cause an observable rise in the interference background amplitude level. . . . It is believed possible to detect ["in many cases before visible clouds are formed": cf. 964 of March] by means of radio-wave echoes the approximate heights of most cloud formations. . . ." [especially of clouds formed by convection under a temperature-inversion boundary]. The wavelength used was 123 m. For another summary see *Sci. Abstracts*, Sec. B., Aug. 1941, Vol. 44, No. 524, pp. 161-162.

3221. THE EFFECT OF THE DIELECTRIC CONSTANT OF THE AIR ON THE FREQUENCY STABILITY OF OSCILLATING CIRCUITS [Investigation of Influence of Temperature, Relative Humidity, & Pressure on the Dielectric Constant].—Volpert. (*See* 3292.)
3222. MEASUREMENTS OF THE DELAY AND DIRECTION OF ARRIVAL OF ECHOES FROM NEAR-BY SHORT-WAVE TRANSMITTERS.—C. F. Edwards & K. G. Jansky. (*Proc. I.R.E.*, June 1941, Vol. 29, No. 6, pp. 322-329.) A summary was dealt with in 1292 of May.
3223. AN AUTOMATIC IONOSPHERE STATION.—F. Ya. Zaborshchikov, D. N. Krasnolobov, & A. I. Fomina. (*Elektrousyaz* [in Russian], No. 1, 1941, pp. 18-30.)

A description of the equipment developed in Russia for automatic recording of the frequency/height characteristics of the ionosphere. Pulses of continuously varying frequency are radiated at a rate of 50 per second and the delay between the sending and receiving of the impulses is registered on a film by a cathode-ray oscillograph. The main characteristics of the equipment are as follows—(1) The frequency range is 1.5 to 15 Mc/s. (2) A complete frequency/height characteristic can be taken in 5 minutes. (3) The transmitter and receiver are synchronised by a common oscillator. (4) The output circuit of the transmitter serves also as the input circuit of the receiver. The equipment is described in detail, and several circuit diagrams are included. A station of this type has already been in regular service for six months.

3224. DISTRIBUTION OF ATMOSPHERIC OZONE [New Theory for Greater Amount of Ozone in Polar Regions & consequently in High-Level Currents of Polar Origin: Ozone Distribution as Index of Changes in Circulation].—O. R. Wulf. (*Bull. Am. Meteorol. Soc.*, Feb. 1941, Vol. 22, No. 2, p. 78: summary only.)

3225. REPORT OF COSMIC RAY OBSERVATIONS MADE ON THE U.S. ANTARCTIC EXPEDITION IN COOPERATION WITH THE BARTOL RESEARCH FOUNDATION.—S. A. Korff & E. T. Clarke. (*Journ. Franklin Inst.*, Nov. 1940, Vol. 230, No. 5, pp. 567-581.)
3226. OBSERVATIONAL CLUE TO THE SIZE OF METEORS [Evidence in Favour of Relatively Large Size].—M. A. R. Khan. (*Nature*, 27th Sept. 1941, Vol. 148, p. 372.)
3227. BRIGHT METEOR FOLLOWED IMMEDIATELY BY AURORAL DISPLAY.—C. W. Gartlein. (*Sci. News Letter*, 2nd Aug. 1941, Vol. 40, No. 5, p. 72.)
3228. CAUSE OF NIGHT GLOW OF SKY IS MAGNETIC ACTIVITY [Lick Observatory Measurements show Direct Relationship].—D. R. Barber. (*Sci. News Letter*, 2nd Aug. 1941, Vol. 40, No. 5, p. 78; *Science*, 25th July 1941, Vol. 94, Supp. p. 8.)
3229. SUNSPOT AND MAGNETIC STORM OF SEPTEMBER 18TH-20TH.—(*Nature*, 27th Sept. 1941, Vol. 148, p. 368.)
3230. SIX PERIODIC FLUCTUATIONS IN SOLAR CONSTANT [apparently Components of the 11-Year Sunspot Cycle].—Harvard University. (*Journ. Franklin Inst.*, Nov. 1940, Vol. 230, No. 5, p. 654: summary only.)
3231. PROPOSED STANDARD SOLAR-RADIATION CURVES FOR ENGINEERING USE.—P. Moon. (*Journ. Franklin Inst.*, Nov. 1940, Vol. 230, No. 5, pp. 583-617.)
3232. THE SOLAR CORONA [with Special Attention to Edlén's Researches].—D. H. Menzel. (*Nature*, 13th Sept. 1941, Vol. 148, p. 312: summary only.) See also 2348 of September.
3233. THE ABUNDANCES OF MOLECULES IN THE SOLAR REVERSING LAYER.—R. H. Lyddane, F. T. Rogers, Jr., & F. E. Roach. (*Phys. Review*, 1st Aug. 1941, Vol. 60, No. 3, pp. 281-282.)
3234. PROPAGATION OF RADIO WAVES ROUND THE EARTH [General Account].—T. L. Eckersley. (*Nature*, 27th Sept. 1941, Vol. 148, pp. 364-366.)
3235. THE EFFECT OF THE EARTH'S CURVATURE ON GROUND-WAVE PROPAGATION.—G.W.O.H.: Burrows & Gray. (*Wireless Engineer*, Oct. 1941, Vol. 18, No. 217, pp. 393-395.) Editorial on the paper dealt with in 1834 of July.
3236. WAVE PROPAGATION OVER TWO PARALLEL WIRES: THE PROXIMITY EFFECT—INDUCTANCE.—C. M. Hebbert. (*Bell S. Tech. Journ.*, July 1941, Vol. 20, No. 3, pp. 325-330.) Appendix to a paper on the "Transmission Characteristics of Toll Telephone Cables at Carrier Frequencies."
3237. ANGULAR DISTRIBUTION OF LIGHT SCATTERED IN LIQUIDS [Centres scatter in Manner of Particles small compared with λ , with Additional Scattering independent of Direction & of Polarisation State].—L. H. Dawson & E. O. Hulburt. (*Journ. Opt. Soc. Am.*, Aug. 1941, Vol. 31, No. 8, pp. 554-558.)
3238. THE MEASUREMENT OF THE REFRACTING POWER OF ABSORBING LIQUIDS.—H. Littmann. (*Physik. Zeitschr.*, 1st Oct. 1940, Vol. 41, No. 19, pp. 442-447.)
A previous paper (30 of January) derived theoretically and experimentally the intensity characteristic of light reflected from an absorbing medium, and showed the likelihood that the measurement of the refracting power of such a medium by means of total reflection would be subject to systematic errors. This point is investigated in the present paper by means of two methods of measuring the refracting power which are unaffected by absorption.
3239. SCATTERING OF LIGHT BY PIGMENT PARTICLES [and the Derivation of an Empirical Equation for Scattering as Function of Particle Size, over Wide Range of Sizes & Indices of Refraction].—D. H. Clewell. (*Journ. Opt. Soc. Am.*, Aug. 1941, Vol. 31, No. 8, pp. 521-527.)
3240. PENETRATION OF FOG BY LIGHT FROM SODIUM AND TUNGSTEN LAMPS.—M. Lucikiesh & L. L. Holladay. (*Journ. Opt. Soc. Am.*, Aug. 1941, Vol. 31, No. 8, pp. 528-530.)
3241. A NEW EXPERIMENT ON THE INTERFERENCE OF DIVERGING LIGHT RAYS [Limitations of Fresnel's Two-Mirror Arrangement avoided by Use of Mica Sheet, giving Patterns on Large Screen].—R. W. Pohl. (*Physik. Zeitschr.*, 15th Nov. 1940, Vol. 41, No. 21/22, pp. 498-499.)
3242. ON THE PHENOMENON OF "FRINGES" IN A PURELY CORPUSCULAR THEORY OF LIGHT.—S. T. Serghiesco. (*Journ. Opt. Soc. Am.*, Aug. 1941, Vol. 31, No. 8, pp. 550-554.) For previous work see 1529 of May.
3243. THE VELOCITY OF ACOUSTICAL AND ELECTROMAGNETIC WAVES [Refutation of Stratton's Objection to Einstein's Second Postulate (c Independent of Motion of Source) by Consideration of Doppler Effect, etc.].—G.W.O.H. (*Wireless Engineer*, July 1941, Vol. 18, No. 214, pp. 205-266.) Criticism of views in "Electromagnetic Theory" (1819 of July).
3244. A NEW WAY OF MEASURING THE VELOCITY OF LIGHT.—R. A. Houstoun. (*Proc. Roy. Soc. Edinburgh*, Sec. A, Part 1, Vol. 61, 1941, pp. 102-114.) See 42 of 1939. The quartz plate, oscillating in a 100 Mc/s field, acts as an intermittent grating to light passing through it, parallel to the optical axis.

ATMOSPHERICS AND ATMOSPHERIC ELECTRICITY

3245. CATHODE-RAY-OSCILLOGRAPHIC INVESTIGATION OF A LIGHTNING STROKE [Records of Two Strokes whose Effects are Known ("Cold" Lightning splitting Tree, No Burning; "Hot" Lightning with Fatal Effect & Burning: Influence of Duration of Main Discharge: Implications for Protective Devices].—H. Norinder. (*E.T.Z.*, 10th July 1941, Vol. 62, No. 28, pp. 617-621.)
3246. THUNDERSTORM PROBLEMS [Summary of Discussion].—F. J. W. Whipple. (*Nature*, 13th Sept. 1941, Vol. 148, pp. 305-307.)
3247. "PHYSICS OF THE AIR" [Book Review].—W. J. Humphreys. (*Proc. Phys. Soc.*, 1st Sept. 1941, Vol. 53, Part 5, No. 299, pp. 624-625.) For a paper by the same writer see 2915 of 1940.
3248. FORMATION OF CLOUD AND RAIN [Survey], and SEA-SALT AND CONDENSATION NUCLEI.—G. C. Simpson. (*Sci. Abstracts*, Sec. A, Aug. 1941, Vol. 44, No. 524, p. 225; p. 225.)
3249. TURBULENCE AND THE GROWTH OF CLOUD DROPS.—D. Arenberg. (*Sci. Abstracts*, Sec. A, Aug. 1941, Vol. 44, No. 524, p. 225.)
3250. GROUNDING ELECTRIC CIRCUITS EFFECTIVELY: PART III—GROUND SYSTEM REQUIREMENTS.—J. R. Eaton. (*Gen. Elec. Review*, Aug. 1941, Vol. 44, No. 8, pp. 451-456.)
3251. ELECTRETS MADE FROM DRY-MIXED COMPONENTS, and EFFECT OF PRESSURE ON THE SURFACE CHARGE OF AN ELECTRET.—W. J. Dodds & J. D. Stranathan: G. E. Sheppard & J. D. Stranathan. (*Phys. Review*, 15th Aug. 1941, Vol. 60, No. 4, p. 360; pp. 360-361.) For previous work on electrets see 1961 of 1940 and back reference.

PROPERTIES OF CIRCUITS

3252. A STABILISED FREQUENCY DIVIDER [for Frequency-Measuring Equipment, Wire-Line Carrier Systems, etc.: Relaxation Oscillator stabilised by Selective Feedback, and synchronised as Frequency Divider at High Orders of Division: High Degree of Independence of Operating Conditions: etc.].—G. Builder. (*Proc. I.R.E.*, April 1941, Vol. 29, No. 4, pp. 177-181.)
3253. THEORY AND APPLICATION OF RESISTANCE TUNING [Special Suitability of Transitron (Reverse-Transconductance) Oscillator (2296 of 1939): Frequency Variations of 50:1 if Good Wave-Form is Not Essential: Linear R/f Relation for 1.5:1 Variation (with Resistance Change in Both Arms): Applications to Laboratory Oscillator, Frequency-Modulation, & Industrial (Temperature, Pressure, Humidity, etc.) Measurements].—C. Brunetti & E. Weiss. (*Proc. I.R.E.*, June 1941, Vol. 29, No. 6, pp. 333-344.)
3254. MEASUREMENTS OF SHOT AND THERMAL NOISE: THE LINEAR RECTIFIER AS INDICATOR.—Bell. (See 3353.)
3255. ERRORS IN THE CALIBRATED LOSSES OF SYMMETRICAL RESISTANCE NETWORKS [with Equations & Curves for Corrections when Terminations differ from Assumed Values].—A. W. Melloh. (*Proc. I.R.E.*, July 1941, Vol. 29, No. 7, pp. 387-390.)
3256. REGULATING METHODS IN CONTROLLABLE ELECTRICAL SYSTEMS AND THE CRITERIA FOR THEIR STABILITY [Theoretical Investigation with Practical Conclusions: The Conflicting Demands of Precise Regulation and Short Regulating Time, in Direct & Indirect Control Methods: the Advantages of a Combined Method: etc.].—W. Artus. (*E.N.T.*, Oct. 1940, Vol. 17, No. 10, pp. 231-244.)
3257. THE CROSLY CONTRAST EXPANDER: AN ANALYSIS OF THE CIRCUIT [Bridge Circuit with Two Metal-Filament Lamps].—Amos. (See 3396.)
3258. THE SOLUTION OF A.C. CIRCUIT PROBLEMS [Method using Matrix Multiplication].—Pipes. (See 3554.)
3259. THE RESPONSE OF ELECTRICAL NETWORKS TO NON-SINUSOIDAL PERIODIC WAVES [Direct Method of Attack yielding Accurate Equation of Final Current Shape].—N. Marchand. (*Proc. I.R.E.*, June 1941, Vol. 29, No. 6, pp. 330-333.)
3260. NATURAL AND RESONANT FREQUENCIES OF COUPLED CIRCUITS.—G.W.O.H. (*Wireless Engineer*, June 1941, Vol. 18, No. 213, pp. 221-223.)
Extension of writer's previous method (*Elec. World*, 1916) to study of resonant frequencies when one circuit only is excited: for low resistances there are 3, including the antiresonance (rejector resonance) frequency: this remains unchanged as the resistances are progressively increased, while the other two approach, coalesce, and vanish: the surviving frequency is no longer that of rejector resonance but of acceptor resonance.
3261. COUPLING CIRCUITS AS BAND-PASS FILTERS: PARTS I, II, & III [Television & Other Techniques demand Precision Method of Design, provided by Straight Filter Theory: Formulae for Double-Parallel, Single-Parallel, & Series-Parallel Tuned Mutual Coupling Circuits, Tapped-Inductance Circuit, etc.: Design Charts].—E. K. Sandeman. (*Wireless Engineer*, Sept., Oct., & Nov. 1941, Vol. 18, Nos. 216, 217, & 218, pp. 361-367, 406-415, & 450-454.) For the final part see this issue (December).
3262. UNDERCOUPLING IN TUNED COUPLED CIRCUITS TO REALISE OPTIMUM GAIN AND SELECTIVITY.—Adams. (See 3310.)
3263. A COAXIAL FILTER FOR VESTIGIAL-SIDEBAND TRANSMISSION IN TELEVISION.—Salinger. (See 3411.)

3264. CONCENTRIC LINES AS BAND-PASS FILTERS: NEW DEVELOPMENTS.—R.C.A. Laboratories. (*E. & Television & S.W.W.*, Jan. 1941, Vol. 14, No. 155, p. 28.)

3265. A BAND FILTER WITH VERY STEEP ATTENUATION RISE AT ONE FLANK [Combination of Quartz Filter & Input Network].—H. Rupp. (*E.N.T.*, Dec. 1940, Vol. 17, No. 12, pp. 275-280.)

Primarily for the distortion-measuring equipment dealt with in 3400, below, but of interest also for high-fidelity carrier systems (for broadcast programmes, etc.). It has an attenuation rise of 6.3 nepers in an interval of 35 c/s at the lower cut-off frequency of 49.5 kc/s, and a pass-band of 20 kc/s.

3266. STRAY CAPACITANCES: THEIR INFLUENCE ON THE EFFECTIVE INDUCTANCE OF A COIL IN A METAL CONTAINER [measured by Resonance Method and Unbalanced & Balanced Transformer Bridge Methods, for Various Connections of Metal Container: Effects in Constant- K Band-Pass & Band-Pass Crystal Lattice Filters, and Methods of Overcoming Them].—L. I. Farren' & R.S. Rivlin. (*Wireless Engineer*, Aug. 1941, Vol. 18, No. 215, pp. 313-323.) From the G.E.C. laboratories.

3267. THE BAND-PASS EFFECT [Transformation of Low-Pass & High-Pass Sections into Band-Pass "Ampli-Filters," in Certain Conditions]: ITS NATURE IN ELECTRIC WAVE-FILTERS TERMINATED IN NEGATIVE IMPEDANCE.—S. P. Chakravarti. (*Wireless Engineer*, March 1941, Vol. 18, No. 210, pp. 103-111.) Further development of the work dealt with in 1720 of 1936, 3495 of 1938, and 51 of January (for later work see 1032 of April).

3268. THE FOUNDATIONS OF FILTER THEORIES, AND THEIR APPLICATIONS.—H. Epheser & H. Glubrecht. (*E.N.T.*, Aug. 1940, Vol. 17, No. 8, pp. 169-192.)

It is understandable that the practical engineer may find even Piloty's comprehensive papers (2477 of 1937 and 2226 of 1938) too mathematical for him, but even the admirably practical work of Jacoby & Schmidt ("Reactance Quadripole as Filter": *Siemens-Veröff. a.d. Nachrichtentech.*, Vol. 2, 1932, p. 279 onwards) did not lead to a wide spreading of filter theory. This is probably because the technician loses interest when a treatment becomes too full and complicated and the particular application he has in his mind is obscured. The writers have set out to produce a complete and unified presentation of the fundamentals which shall be comprehensible without previous acquaintance with the subject and which shall serve as an easy path to the utilisation of Cauet's important papers and books (20 references are given to these, many of which have been dealt with in past Abstracts: see for example 1932 Abstracts, p. 537—a paper in English which is marked as specially important; 1013 of 1935; 3915 of 1939; 2539 of 1940. For later papers, not mentioned, see 1627 of June and 3017 of November).

Part A of the present paper deals with the prop-

erties of the linear network and the dipole, Part B with quadripoles. Part C gives a development of filter circuits by Cauet's method (including both the Tschebyscheff and Jaumann methods of determining the parameters: see 1933 Abstracts, p. 443, and back references). Part D deals with the actual carrying out of the design of appropriate circuits, and with the effects of matching errors and losses: an appendix gives a proof of the reactance law.

3269. CANONICAL NETWORK CIRCUITS FOR REACTANCE QUADRIPOLES WITH PREDETERMINED CHARACTERISTICS.—H. Piloty. (*T.F.T.*, Sept., Oct., & Nov. 1940, Vol. 29, Nos. 9, 10, & 11, pp. 249-258, 279-290, & 320-325.) For earlier work see 959 (and 958) of 1940, and cf. 3272, below.

3270. ON THE THEORY OF INSERTION LOSSES.—E. V. Zelyakh. (*Elektrosvyaz* [in Russian], No. 1, 1941, pp. 62-68.) A number of practical problems concerning insertion losses in complex circuits are presented in the shape of five theorems, the proofs of which are given.

3271. STANDARDISED CURVE TABLES FOR THE CALCULATION OF THE WAVE TRANSMISSION EQUIVALENTS OF BAND-PASS FILTER SECTIONS [m -"T" and m -"Pi" Sections of Zobel Band-Pass Network: Band-Pass "X" Section of Series Oscillatory Circuits, and of Parallel].—R. Feldtkeller. (*T.F.T.*, July 1940, Vol. 29, No. 7, pp. 201-206.)

3272. THE CALCULATION OF FILTER CIRCUITS FROM THEIR OPERATIVE ATTENUATION.—R. Feldtkeller & W. Rheinhard. (*T.F.T.*, Nov. 1940, Vol. 29, No. 11, pp. 313-320.)

"For a low-pass X-circuit with two attenuation peaks in the suppression region, and for the filter circuits derived from this by equivalence considerations and simple frequency transformations the circuit elements are calculated in an elementary, partly graphical method from the requirements of the operative attenuation": the method of Piloty (959 of 1940 [see also 958]) is considered to be too complicated mathematically for the practical man.

3273. OPERATIVE TRANSMISSION EQUIVALENT [Betriebsmass] AND ECHO EQUIVALENT OF SYMMETRICAL LOSS-FREE QUADRIPOLES [Establishment of Relation, with Help of Reactance Angle: Graphical Representation, leading to Determination of Operative Attenuation & Echo Attenuation (due to Reaction of Quadripole on Transmitter through Its Impedance): etc.].—R. Feldtkeller. (*T.F.T.*, Nov. 1940, Vol. 29, No. 11, pp. 339-341.)

3274. BUILDING-UP PROCESSES IN OSCILLATORY CIRCUITS [Treatment applicable to Exploring-Note Sound Analysis, Amplifiers with Several Mutually Detuned Circuits, etc.].—Feldtkeller. (See 3417.)

3275. SOME NOTES ON LINEAR AND GRID-MODULATED RADIO-FREQUENCY AMPLIFIERS.—Terman & Buss. (See 3298.)

3276. HIGH-GAIN WIDE-PASS-BAND AMPLIFIER DESIGN [for Minimum Number of Valves: by Use of Couplings with Complementary Frequency-Response Curves], and NEUTRALISING WIDE-BAND AMPLIFIERS.—R.C.A. Laboratories. (*E. & Television & S-W.W.*, Jan. 1941, Vol. 14, No. 155, pp. 12-14; Feb. 1941, No. 156, pp. 84 and 86.)
3277. ELIMINATING PEAKS IN AMPLIFIER RESPONSE CURVES.—R.C.A. Laboratories. (See 3418.)
3278. VALVE ADMITTANCE CORRECTION CIRCUITS [for Neutralisation of Negative Input Conductances arising at Ultra-High Frequencies].—R.C.A. Laboratories. (*E. & Television & S-W.W.*, May 1941, Vol. 14, No. 159, p. 208.)
3279. REDUCING PHASE SHIFT IN NEGATIVE-FEEDBACK AMPLIFIERS [by Sandwiched Tertiary Winding for Feedback Voltage, giving Tight Coupling & Reduced Leakage Inductance].—R.C.A. Laboratories. (*E. & Television & S-W.W.*, Feb. 1941, Vol. 14, No. 156, p. 75.)
3280. EQUIVALENT CIRCUITS OF THE FEEDBACK AMPLIFIER ["Constant Voltage" & "Constant Current" Equivalent Circuits of Simple Amplifier, of Proved Utility, re-drawn for Feedback Amplifier by Artifice of replacing Forward & Feedback Paths by Equivalent Forward Path utilising a Hypothetical Valve: Application to Cathode-Coupled Amplifier].—A. Fairweather. (*Wireless Engineer*, April 1941, Vol. 18, No. 211, pp. 151-153.)
3281. THE THEORY OF SELF-BALANCING PHASE-INVERSION CIRCUITS.—A. A. Rizkin. (*Elektrosvyaz* [in Russian], No. 1, 1941, pp. 39-46.)
- Phase-inversion circuits used for the transition from single-valve to push-pull operation are discussed, and the defects of the self-balancing circuit described by Lorenzen (Fig. 1: see 1431 of 1939) are pointed out. A symmetrical self-balancing circuit (Fig. 2) which is free from these defects is proposed by the author. The main feature of this circuit is the introduction of a negative feedback to the main branch of the push-pull circuit. The operation and design of this, and of the more general circuit with independent feedback to both valves (Fig. 4), are discussed. A symmetrical self-balancing circuit in which the source of excitation can be earthed is also considered. The discussion is illustrated by numerical examples, and in conclusion a few critical remarks are made on the circuit (Fig. 7) proposed by Terman & others (64 of 1940), which came to the author's knowledge after this paper had been completed.
3282. A NEW TYPE OF DIRECT-CURRENT AMPLIFIER [for Measuring & Control Purposes].—Eberhardt, Nüsslein, & Rupp. (See 3588.)
3283. NON-LINEAR DISTORTION IN AMPLIFIER VALVES AND LOW-FREQUENCY TRANSFORMERS.—Kettel. (See 3357.)
3284. LOAD CURRENTS IN TRANSFORMERS WITH SEVERAL SECONDARY WINDINGS [as in Mains Units for Wireless Apparatus: Dependence of Current in One Winding on Load on Another (Development of Formulae): Determination of Constants by Open-Circuit & Short-Circuit Measurements: Example].—H. H. Wolff. (*E.N.T.*, Sept. 1940, Vol. 17, No. 9, pp. 209-213.)
3285. THE DESIGN OF THE UNIVERSAL WINDING [for Max. Inductance in Min. Volume].—Hershey. (See 3460.)
3286. REDUCING LOSS IN H.F. COUPLINGS [e.g. between Balanced Two-Wire Line and Earthed, Unbalanced Concentric-Line Resonator].—R.C.A. Laboratories. (*E. & Television & S-W.W.*, Jan. 1941, Vol. 14, No. 155, pp. 31-32.)
3287. THE CALCULATION OF CAPACITANCES FOR CABLES OF SIMPLE CROSS SECTION [Comparison of Methods used by Breisig, Kaden (Electrical Images: 68 of 1936 and 1879 of 1937), Kaden (Potential of Line Multiple Sources), & Meinke (3081 of 1940)].—F. Sommer. (*E.N.T.*, Dec. 1940, Vol. 17, No. 12, pp. 281-294.) For previous work see 4070 of 1939.
3288. CIRCUIT-DESIGNATION METHOD [New System of Circuit-Wiring Representation showing Paths of Various Types of Current].—O. H. Caldwell. (*Proc. I.R.E.*, May 1941, Vol. 29, No. 5, pp. 289-290.)

TRANSMISSION

3289. THE GENERATION OF HIGH POWERS ON SHORT WAVES [10 m: 220 W Output for 850 W Input] WITH QUENCHED SPARK GAPS.—W. Schönfeld. (*E.T.Z.*, 26th June 1941, Vol. 62, No. 26, p. 598: summary of 1938 Dresden Dissertation.)

A ten-gap discharger is used: it has in parallel with it an auxiliary LC circuit (450 kc/s in the best conditions), every half-wave of which shock-excites the short-wave circuit afresh. Conditions for the best results are given.

3290. BEAM POWER TETRODES AS NEGATIVE-RESISTANCE OSCILLATORS.—H. L. Krauss. (*Proc. I.R.E.*, March 1941, Vol. 29, No. 3, p. 141: summary only.)
3291. THE PIERCE PIEZOELECTRIC OSCILLATOR: ANALYSIS FOR THE DESIGN OF CRYSTAL- AND LINE-CONTROLLED APPARATUS.—Jefferson. (See 3439.)
3292. THE EFFECT OF THE DIELECTRIC CONSTANT OF THE AIR ON THE FREQUENCY STABILITY OF OSCILLATING CIRCUITS.—A. R. Volpert. (*Elektrosvyaz* [in Russian], No. 1, 1941, pp. 31-38.)
- It is pointed out that the frequency stability of an oscillating circuit is affected by the humidity of the air no less than by temperature, the humidity acting (a) directly by changing the dielectric constant ϵ of the air, and (b) indirectly by affecting

the properties of the insulating materials. Changes occurring under heading (a) only are dealt with in the present paper.

Formula 8 is derived for determining $\epsilon - 1$ of humid air. In this formula p is the total pressure of the air and water vapour (in mm Hg), T the absolute temperature, and $k = e/p$, where $e = p_2$, the water-vapour pressure. A family of curves $\epsilon - 1$ calculated from (8) for different temperatures and relative humidities g is shown in Fig. 1. In Fig. 2 experimental curves are plotted showing the variation of t (in degrees C), g , and q (absolute humidity) with time in a thermostatic oven, and also a calculated curve $\epsilon - 1$. A modified formula (13) is then derived in which k is replaced by $gE/100p$ (from eqn. 10): this gives $\epsilon - 1$ in terms of T , g , p , and E (saturated vapour pressure at a given temperature). Using this formula, the effects of t , g and p on ϵ are investigated separately by determining the corresponding coefficients of ϵ , i.e. relative increases in ϵ for a unit change in each of the above factors. Formulae 14, 15, and 16 for calculating these coefficients are derived, and curves are plotted in Figs. 3, 5, and 6 showing their variation with t .

Curves showing the variation of the temperature coefficient at various constant temperatures when g is varied are also plotted (Fig. 4). The effect of altitude on ϵ is also investigated, and it is shown that for a change of ± 100 m ϵ is changed by $\mp 9 \times 10^{-6}$.

The curves prove that humidity may affect considerably the frequency of an oscillating circuit, and it is therefore suggested that deliquescent materials, such as calcium chloride, should be used in thermostatic ovens.

3293. EFFECT OF TEMPERATURE ON FREQUENCY OF 6J5 OSCILLATOR [for Television & F.M.].—(See 3303.)
3294. DRIFT ANALYSIS OF THE CROSBY FREQUENCY-MODULATED TRANSMITTER CIRCUIT [Crosby A.F.C. Circuit, with Proper Attention to Design and Choice of Frequency Multiplications, provides Stability of Same Order as Crystal: etc.].—E. S. Winlund. (*Proc. I.R.E.*, July 1941, Vol. 29, No. 7, pp. 390-398.)
3295. A NOTE ON AMPLITUDE, PHASE, AND FREQUENCY MODULATION [Mathematical Analysis & Vector Diagrams].—H. D. Bickley. (*P.O. Elec. Eng. Journ.*, April 1941, Vol. 34, Part I, pp. 42-45.)
3296. THEORY AND APPLICATION OF RESISTANCE TUNING [Special Suitability of Transitron Oscillator: Applications to Laboratory Oscillator, Frequency-Modulation, etc.].—Brunetti & Weiss. (See 3253.)
3297. THE SOLUTION OF UNSYMMETRICAL-SIDE-BAND PROBLEMS WITH THE AID OF THE "ZERO-FREQUENCY CARRIER" [with Combined Amplitude & Angle Modulation, a Concept derived from Consideration of the "Vector Envelope": Solution yields directly the Modulation Envelope of Output Signal].—H. A. Wheeler. (*Proc. I.R.E.*, Aug. 1941, Vol. 29, No. 8, pp. 446-458.)
3298. SOME NOTES ON LINEAR AND GRID-MODULATED RADIO-FREQUENCY AMPLIFIERS.—F. E. Terman & R. R. Buss. (*Proc. I.R.E.*, March 1941, Vol. 29, No. 3, pp. 104-107.) A summary was dealt with in 3794 of 1940.
3299. THE MEASUREMENT OF MODULATION DEPTH [Method comparing Modulation Amplitude with Mean Carrier Amplitude, Electrically, before applying Result to Indicating Circuit: applied in Peak Programme Meter for B.B.C. Monitoring].—H. D. McD. Ellis. (*Wireless Engineer*, March 1941, Vol. 18, No. 210, pp. 99-102.)
3300. THE MEASUREMENT OF MODULATION IN CARRIER AMPLIFIERS.—J. P. Kinzer. (*Bell Lab. Record*, Aug. 1941, Vol. 19, No. 12, pp. 374-378.)
Particularly for the modulation product $2P - Q$, which is usually in phase for all the amplifiers in tandem, so that the total power is proportional to the square of the number of amplifiers.
3301. HALF-WAVE MODULATION [Intelligibility of Speech Not Seriously Depreciated by Transmission of One Half Only of Wave-Form: for Given Communication Requirement, limited in Range by Effect of Noise on Intelligibility, Design of Transmitter to transmit Half the Speech Wave gives 44% Saving in Power, 17% in Peak Emission, & Omission of Much Apparatus].—C. E. G. Bailey. (*Wireless Engineer*, July 1941, Vol. 18, No. 214, pp. 279-282.)

RECEPTION

3302. DIODE AS RECTIFIER AND FREQUENCY-CHANGER [Usefulness of Diode as Frequency-Changer when Transit-Time Effects would be Troublesome in Multi-Electrode Valves: etc.].—Bell. (See 3343.)
3303. EFFECT OF TEMPERATURE ON FREQUENCY OF 6J5 OSCILLATOR [Compensation of Frequency Drift during Warming-Up Period: for Television & F.M.].—(*Sci. Abstracts*, Sec. B, Aug. 1941, Vol. 44, No. 524, p. 163.) From *Radiotronics*, Bull. No. 110.
3304. TEMPERATURE AND FREQUENCY-DRIFT [Observations on a Television Receiver].—R.C.A. Laboratories. (*E. & Television & S-W.W.*, April 1941, Vol. 14, No. 158, pp. 182-183.)
3305. VIBRATOR UNITS WITH ULTRA-HIGH-FREQUENCY RECEIVERS [Suitability of "Vibra-packs"].—S. L. Robinson. (*E. & Television & S-W.W.*, Feb. 1941, Vol. 14, No. 156, p. 96.)
3306. IMPROVEMENTS IN B-BATTERY PORTABILITY [Package Size per Unit of Capacity reduced by about 50%: Design of "Minimax" Types].—H. F. French: Ever-Ready Company. (*Proc. I.R.E.*, June 1941, Vol. 29, No. 6, pp. 299-303.) See also 1062 of April.

3307. SAFETY REQUIREMENTS FOR MAINS-OPERATED WIRELESS APPARATUS [Notice of Specification B.S. 415-1941].—British Standards Institution. (*Wireless Engineer*, May 1941, Vol. 18, No. 212, p. 197.)
3308. RECEIVER AERIAL COUPLING CIRCUITS.—Sturley. (See 3334.)
3309. MEASUREMENT OF LOOP-ANTENNA RECEIVERS.—Swinyard. (See 3450.)
3310. UNDERCOUPLING IN TUNED COUPLED CIRCUITS TO REALISE OPTIMUM GAIN AND SELECTIVITY [Mathematical Analysis to obtain Optimum Coupling in Practical Design of I.F. Transformers for Superheterodyne Receivers: Existence of a Non-Critical Optimum Coupling below the Critical Value].—J. J. Adams. (*Proc. I.R.E.*, May 1941, Vol. 29, No. 5, pp. 277-279.)
3311. D.C. AMPLIFIED A.V.C. CIRCUIT TIME CONSTANTS [Examination of Statement (Kellogg & Phelps, 2100 of 1937) that Total Time Constant of Two RC Circuits separated by a Valve is Sum of Individual Time Constants: Influence of Comparative Values of These: Practical Errors due to Variations of Valve Slope Resistance & Amplification Factor: a More Correct Formula].—K. R. Sturley & F. Duerden. (*Wireless Engineer*, Sept. 1941, Vol. 18, No. 216, pp. 353-360.)
3312. SOME NOVEL AUTOMATIC-FREQUENCY-CONTROL CIRCUITS [especially the Use of Thyrite Resistances], and IMPROVED DISCRIMINATOR CIRCUIT for AUTOMATIC FREQUENCY CONTROL.—Anon: R.C.A. (*E. & Television & S.W.W.*, Feb. 1941, Vol. 14, No. 156, pp. 82 and 84; March 1941, No. 157, p. 141.)
3313. FURTHER NOTES ON GANGING SUPERHETERODYNE RECEIVERS [Derivation of Formulae for Direct Calculation of Circuit Components & Fault Factor: with Curves for Quantities involved].—M. Wald. (*Wireless Engineer*, April 1941, Vol. 18, No. 211, pp. 146-150.) Further development of the work dealt with in 1839 of 1940.
3314. THE SUPERHETERODYNE RECEIVER AS A SOURCE OF H.F. INTERFERENCE.—R. Moebes. (*T.F.T.*, July 1940, Vol. 29, No. 7, pp. 196-199.)

Most modern broadcast receivers employ an i.f. between 468 and 475 kc/s (but see later) and the oscillator frequency is by that amount higher than the signal frequency. The amplitude of the oscillator-frequency oscillations varies according to the mixing valve used, the frequency, and the supply voltages, and ranges between 5 and 15 V_{eff} . The amplified i.f. voltage at the rectifier is generally also around 10 v. Such voltages demand a careful screening of the oscillatory circuit, particularly the coils, if a radiation of these frequencies is not to occur and cause effects in the receiver itself or in neighbouring receivers. The metal cases employed in commercial receivers are out of the question for broadcast receivers using the cabinet as their loudspeaker baffle, and in practice the ordinary receiver of this type allows the hetero-

dying and i.f. oscillations to be detected (by a small frame and a sensitive receiver) in its immediate neighbourhood; in certain cases, probably as the result of resonance effects, the i.f. radiation may interfere with neighbouring sets. As a rule, however, the direct radiation does not have this effect, even when, to save metal, the metal of the chassis is replaced by a synthetic material. The screening cans of the oscillator and band-filter circuits ought not, however, to be dispensed with.

But more serious than the direct radiation is the possibility of the action of the oscillator circuit on the input circuit, by which voltages of the heterodyning frequency may appear at the aerial terminals and cause interference. Such action may be direct (when the design is unfortunate and the components' screening inadequate) or through the mixing valve: for the majority of receivers still have no h.f. input stage, and even those that have an input band-filter usually convert this, on the short-wave band, into a simple circuit. The magnitude of the heterodyning voltages likely to be thus produced at the input-circuit terminals through the mixing valve is here examined theoretically and, on certain assumptions, found to be 7-10 mv on the medium band, 2-3 mv on the long waves, and as much as 75 mv on the short. The direct action of the oscillator circuit on the input circuit is likely to add still more: confirmatory tests on a number of 6- and 7-circuit receivers showed good agreement with theory on the medium and short waves (suggesting that here the indirect action is predominant) but gave values much higher than those calculated on the long waves where, presumably, the direct action is more serious: the measured voltages ranged from 20-30 mv and even, in certain cases, to 80 mv. Seven-circuit sets with band-filter input on the medium and long waves gave voltages usually under 1 mv; but on the short waves, as predicted above, they yielded values around 100 mv.

The remainder of the paper discusses the effects of these voltages in actual practice, particularly with community-aerial systems; the comparatively small number of complaints received seems to require explanation, and some suggestions are made. Among these, it is pointed out that with the usual i.f. of about 470 kc/s most of the heterodyning frequencies lie outside the broadcast band: lately, however, certain receivers have been brought out with an i.f. of about 129 kc/s, and here the danger of interference is increased in more than one way: this was confirmed by experiment. The general conclusion reached is that as the superheterodyne receiver becomes more widely used, the short-wave band becomes more popular, and community-aerial systems are extended to deal with it, this type of interference will increase in seriousness: steps should therefore be taken now to reduce its dangers.

3315. ULTRA-SHORT-WAVE ANTI-STATIC AERIALS [for Near-By Interference (e.g. Ignition)].—R.C.A. Laboratories. (See 3327.)

3316. COMPULSORY [Ignition] INTERFERENCE SUPPRESSION [Letter urging Suitability of Present Moment for Its Introduction].—(*Wireless World*, Oct. 1941, Vol. 47, p. 268.) Cf. Morgan, *Elec. Review*, 24th Oct., p. 433.

3317. INTERFERENCE PROBLEMS IN FLUORESCENT LIGHTING [Interference (originating chiefly at Cathode) arrives by Direct Radiation from Bulb, from Power Line, and by Propagation over Common Line: Noise Frequencies: Suppression].—E. S. Mills & J. H. Campbell. (*Proc. I.R.E.*, March 1941, Vol. 29, No. 3, p. 141: summary only.)
3318. PROGRESS IN THE DEVELOPMENT OF INSTRUMENTS FOR MEASURING RADIO NOISE [with 21 Literature References].—C. M. Burrill. (*Proc. I.R.E.*, Aug. 1941, Vol. 29, No. 8, pp. 433-442.)
Including the Burrill-Morgan logarithmic-scale peak-reading meter RCA TMV-141A, with excellent performance. It is suggested that indicators of the rapid-response/slow-recovery type should be called "quasi-peak" indicators: "a thorough and well-planned programme of research ought to be undertaken by someone," to determine the time constants for these indicators more directly and promptly so as to arrive at the best values for them. For previous work see 1356 of May.
3319. "HILFSBUCH FÜR RUNDUNKENTSTÖRER" [Text Book for Interference-Suppressing Technicians: Book Review].—W. Schulz. (*T.F.T.*, Aug. 1940, Vol. 29, No. 8, p. 248.) Published for the German P.O.
3320. THE USE OF HEADPHONES WITH COMMUNICATION RECEIVERS. — (*E. & Television & S-W.W.*, March 1941, Vol. 14, No. 157, p. 105.)
3321. SERVICING EQUIPMENT AND ITS USES: PART IV—SPECIAL TOOLS AND APPLIANCES. (*Wireless World*, Oct. 1941, Vol. 47, No. 10, pp. 265-267.)
3322. A FIVE-BAND RECEIVER FOR AUTOMOBILE SERVICE.—Little & Rettenmeyer. (*See* 3543.)
3323. AVIATION PORTABLE ["Learavian" Receiver covering Aeronautical & Medium-Wave Broadcast Frequencies, with Intercommunication 'Phone System].— (*Wireless World*, Oct. 1941, Vol. 47, No. 10, p. 251.)
3324. SCOTT HIGH-FIDELITY RECEIVERS.—E. H. Scott. (*Proc. I.R.E.*, June 1941, Vol. 29, No. 6, pp. 295-299.)
3325. EUROPEAN LISTENERS [Note on Recent U.I.R. Synoptic Chart].—(*Wireless World*, Oct. 1941, Vol. 47, No. 10, p. 258.)
- AERIALS AND AERIAL SYSTEMS**
3326. THE APPROXIMATE REPRESENTATION OF THE DISTANT FIELD OF LINEAR RADIATORS [Résumé of General Theory: Field of a Conducting Thread: Equivalent Length of a Conducting Thread: "Effective Length" of a Driven Antenna (Approximate Formulae obtained from Leading Term in Fourier Series): Distant Field of Two Crossed Antennas (as in "Turnstile" U.H.F. Aerial): etc.].—R. King. (*Proc. I.R.E.*, Aug. 1941, Vol. 29, No. 8, pp. 458-463.)
3327. ULTRA-SHORT-WAVE ANTI-STATIC AERIALS [Signals on Horizontal Aerial vary approx. Linearly with Height above Ground: Near-By Interference (e.g. Ignition) practically Constant over Wide Variation of Height: System of Two Aerials, One close to Ground, Other Raised, with Outputs Opposed].—R.C.A. Laboratories. (*E. & Television & S-W.W.*, April 1941, Vol. 14, No. 158, pp. 183 and 187.)
3328. THE BEHAVIOUR OF WIDE-BAND CABLES WITH STYROFLEX INSULATION IN THE DECIMETRIC-WAVE BAND.—H. Kaufmann. (*T.F.T.*, Nov. 1940, Vol. 29, No. 11, pp. 325-326.)
Up to a few Mc/s, the attenuation characteristic of such cables depends almost entirely on resistance loss, which is here proportional to the square root of the frequency: but since the leakage loss increases about in proportion to the frequency, at extremely high frequencies it must finally exceed the resistance loss. The writer calculates the attenuation characteristic for two types of ordinary Styroflex-insulated wide-band cable, for frequencies up to 2000 Mc/s, from the equations (1-3) valid for a homogeneous line provided that the loss-angle of the dielectric is small compared with unity. Eqn. 3 involves this loss angle, for the air-Styroflex combination, and in order to calculate it (by Kaden's approximation, eqn. 4) it was necessary to extend Kebbel's centimetric-wave loss-angle measurements on Trolitul (2444 of 1939) to the decimetric region: the full characteristic is given in Fig. 1. Measurements at 20 cm and 50 cm of the complete attenuation characteristic, by the resonance method already described (2681 of 1940), show that the calculating technique still gives sufficiently accurate results in the decimetric-wave region.
3329. A FLEXIBLE LOW-ATTENUATION TRANSMISSION LINE [Continuously Moulded Polystyrene Embedment in Ribbon Form].—R.C.A. Laboratories. (*E. & Television & S-W.W.*, March 1941, Vol. 14, No. 157, pp. 135-136.)
3330. THE ATTENUATION AND IMPEDANCE OF SINGLE COAXIAL CABLES.—Brockbank. (*See* 3419.)
3331. SOME PROPERTIES OF AN AERIAL SYSTEM BUILT OF DIPOLES [Four Vertical Dipoles, at Corners of a Square: Various Radiation Characteristics obtainable: Reduced Vertical & Increased Horizontal Radiation: Vertical Stacking of Such Systems].—G. Rutelli. (*Sci. Abstracts*, Sec. B, Aug. 1941, Vol. 44, No. 524, p. 164.) From *Zeitschr. f. tech. Phys.*, No. 7, Vol. 21, 1940, p. 140-148.
3332. RHOMBIC TRANSMITTING AERIAL: INCREASING THE POWER EFFICIENCY [Use for High-Power Transmission hitherto limited by Terminating-Resistance Difficulties: Derivation of Practical Formula for Efficiency, leading to Conclusion that Parallel Arrangement of Such Aerials provides Effective Means for Increased Efficiency].—L. Lewin. (*Wireless Engineer*, May 1941, Vol. 18, No. 212, pp. 180-187.)

3333. ON THE IMPEDANCE OF RECEIVING AERIALS.—A. Heilmann. (*T.F.T.*, Dec. 1940, Vol. 29, No. 12, pp. 357-360.)
Fränz (761 of March) has recently pointed out the error of the idea that the impedance of an aerial is different according to whether it is used as a transmitting or a receiving aerial [*cf.* also Magnus & Oberhettinger, 2121 of August]. The following proof of the equality of receiving and transmitting impedance should appeal particularly to technicians in telephony: it is based on the law of the 'equivalent current source.' This states that in any linear network in which electromotive forces are acting at any points, the current in a resistance branch R_n can be calculated as if this resistance were fed from an equivalent current source with e.m.f. \mathcal{E}_i and internal resistance R_i , where \mathcal{E}_i is the open-circuit voltage (across the terminals a and b left open when R_n is removed) and R_i is equal to the resistance of the network at the terminals a, b when all voltage sources are short-circuited." In the course of his argument the writer deals with Wilnotte's conclusions and with those of Niessen & de Vries, explaining in each case the cause of error.
3334. RECEIVER AERIAL COUPLING CIRCUITS [Analysis of Problem of obtaining Highest Transfer Voltage Ratio with Minimum Reduction of Selectivity and Minimum Mistuning: Generalised Formulae: Experimental Verification].—K. R. Sturley. (*Wireless Engineer*, April & May 1941, Vol. 18, Nos. 211 & 212, pp. 137-146 & 190-197.)
3335. GROUNDING ELECTRIC CIRCUITS EFFECTIVELY: PART III—GROUND SYSTEM REQUIREMENTS.—J. R. Eaton. (*Gen. Elec. Review*, Aug. 1941, Vol. 44, pp. 451-456.)
3336. THE MATHEMATICS OF ICE LOADING EFFECT ON DESIGN OF OVERHEAD LINES.—J. McCombe. (*Distribution of Elec.*, Oct. 1941, Vol. 14, No. 144, pp. 480-483.) See also *Elec. Review*, 10th Oct. 1941, pp. 371-373.
3337. NOMOGRAMS FOR THE SOLUTION OF SPHERICAL TRIANGLES.—J. B. Friauf. (*Journ. Franklin Inst.*, Aug. 1941, Vol. 232, No. 2, pp. 151-174.)
- VALVES AND THERMIONICS**
3338. LARGE-SIGNAL HIGH-FREQUENCY ELECTRONICS OF THERMIONIC VACUUM TUBES [Mathematical Treatment (with Solution degenerating into Space-Charge-Limited Operation at Low Frequencies) based on Division of Multielectrode Valve into Several Diode Sections: Cases of Plane Diode with Cathode of Infinite Emission Capacity (Zero Initial Velocity), and with Periodic Injection of Electrons: Velocity-Modulated Valves & Their 58% Efficiency Limitation: Possible Improvement of Conventional Power Valves].—C. C. Wang. (*Proc. I.R.E.*, April 1941, Vol. 29, No. 4, pp. 200-214.)
3339. VELOCITY-MODULATED VALVES: MODERN TRENDS IN TUBES FOR U.H.F. OPERATION.—(*Wireless World*, Oct. 1941, Vol. 47, No. 10, pp. 248-251.)
3340. CALCULATING CONDUCTANCE [due to Electron Beam traversing a Transverse Alternating Field: Correction], and THE DEFLECTING CONDENSER.—S. Rodda: W. E. Benham. (*Wireless Engineer*, April 1941, Vol. 18, No. 211, p. 154; July, No. 214, pp. 277-278.) See 1077 of April. For Recknagel's paper see presumably (the reference given in the first letter is incorrect) 2257 of 1938.
3341. ON THE INDUCED CURRENT AND ENERGY BALANCE IN ELECTRONICS [U.H.F. Results (particularly with Velocity Modulation) point to Necessity for Fundamental Revision of Ordinary Concept of Current: Generalised Theory: Ramo's Work (131 of 1940): Treatment including Effects of Space Charge & Changing Electrode Potentials, and Balancing of Energy Relations: Application to U.H.F. Parallel-Plane Valves & Klystron], and ON THE ENERGY EQUATION IN ELECTRONICS AT ULTRA-HIGH FREQUENCIES.—C. K. Jen. (*Proc. I.R.E.*, June 1941, Vol. 29, No. 6, pp. 345-349; Aug., No. 8, pp. 464-466.) See also 3342, below.
3342. FIELD PROPAGATION TIME WITHIN A VALVE SYSTEM AT QUASI-OPTICAL FREQUENCIES [above Present Ultra-High Range: Electron-Transit Time may drop to Minor Rôle, Field-Propagation Time predominating].—C. K. Jen. (In second paper dealt with in 3341, above.)
3343. DIODE AS RECTIFIER AND FREQUENCY-CHANGER [Usefulness of Diode as Frequency-Changer when Transit-Time Effects would be Troublesome in Multielectrode Valves: when Difference-Frequency Output must be Linearly Proportional to Smaller of Input Voltages & Independent of Other Input, etc.: in Measuring Equipment & as Limiter: Theoretical Investigation of Effect of Imperfect Rectification, Signal/Noise Ratio of Frequency-Changer, etc.].—D. A. Bell. (*Wireless Engineer*, Oct. 1941, Vol. 18, No. 217, pp. 395-404.) From the Cossor laboratories.
3344. CERAMICS IN VALVE CONSTRUCTION [particularly German Work on Low-Loss Ceramic Seals for U.H.F. Valves].—R. Howard. (*Electronic Engineering* [formerly *E. & Television & S.W.W.*], Aug. 1941, Vol. 14, No. 162, pp. 343-344 and 376.)
3345. A NEW FREQUENCY CHANGER [with Electron-Multiplication: Particularly Suitable for U.H.F.].—(*E. & Television & S.W.W.*, Feb. 1941, Vol. 14, No. 156, p. 59.)
3346. SILVER-MAGNESIUM ALLOY AS A SECONDARY ELECTRON EMITTING MATERIAL [and Activation Methods: Suggested Explanation of Behaviour].—V. K. Zworykin, J. E. Ruedy, & E. W. Pike. (*Journ. Applied Phys.*, Sept. 1941, Vol. 12, No. 9, pp. 696-698.)
3347. A STUDY OF THE SECONDARY EMISSION FROM CUPROUS OXIDE, PURE OR TREATED WITH ALKALI METALS.—A. I. Frimer. (*Journ.*

of *Tech. Phys.* [in Russian], No. 5, Vol. 10, 1940, pp. 394-401.)

A report is presented on experiments with pure Cu_2O (prepared in two different ways) and Cu_2O treated with caesium, potassium, and rubidium. The apparatus used is described and a number of experimental curves are shown. The main conclusions reached are as follows:—(1) The secondary emission σ from Cu_2O is lower than from Cu (σ is 1.17 for Cu_2O and 1.35 for Cu) but it increases considerably (up to 6) when an alkali metal is deposited. (2) The absorption of gas by Cu_2O increases σ . (3) Heating of Cu_2O up to 400°C does not increase σ . (4) The energy distribution of secondary electrons from Cu_2O does not differ much from that in the case of Cu. If, however, Cu_2O is treated with an alkali metal the predominance of slow electrons becomes very prominent. A theoretical interpretation of the results is given.

3348. ON THE DEPENDENCE ON ANGLE OF THE SECONDARY-ELECTRON EMISSION FROM INSULATORS.—Salow. (See 3432.)

3349. THE DEPENDENCE OF THE SECONDARY ELECTRON EMISSION PRODUCED BY GAMMA RADIATION UPON THE DIRECTION OF THE RADIATION [in Radiation Therapy].—C. W. Wilson. (*Proc. Phys. Soc.*, 1st Sept. 1941, Vol. 53, Part 5, No. 299, pp. 613-623.)

3350. EFFECTS OF HEAT TREATMENT ON FIELD EMISSION FROM METALS [Anomalous F.E. (due to Surface Electropositive Impurities) removed by Heating, except from Nickel: Investigation using Martin's Cylindrical Electron Projector Tube].—J. H. Daniel. (*Journ. Applied Phys.*, Aug. 1941, Vol. 12, No. 8, pp. 645-652.) See Martin, 3351, below.

3351. THE CYLINDRICAL ELECTRON PROJECTOR TUBE IN THE STUDY OF THERMIONIC AND FIELD EMISSION.—Martin. (See Daniel, 3350, above). The tube was described by Martin in his paper dealt with in 619 of 1940.

3352. REDUCTION OF MAGNESIUM OXIDE BY TUNGSTEN IN VACUUM [Method of calculating Rate: Experimental Confirmation: of Interest in connection with Oxide-Coated Cathodes and with Use of Magnesia as Insulator].—G. E. Moore. (*Bell T. System Tech. Pub.*, Monograph B-1296, 12 pp.)

3353. MEASUREMENTS OF SHOT AND THERMAL NOISE: THE LINEAR RECTIFIER AS INDICATOR [applicable to Noise Measurement by Substitution Methods but Not by Absolute Methods].—D. A. Bell. (*Wireless Engineer*, March 1941, Vol. 18, No. 210, pp. 95-98.) For criticism (W. H. Aldous & E. G. James) and reply see July & Aug. issues, Nos. 214 & 215, pp. 278 & 323.

3354. THE SHOT EFFECT IN A SATURATED DIODE [Campbell's and Schottky's Theorems, based on Entirely Different Physical Considerations, shown by Heaviside Analysis to lead to Same Result in calculating Shot Noise

in External Circuit consisting of Lumped Impedances].—N. R. Campbell & V. J. Francis. (*Phil. Mag.*, Sept. 1941, Vol. 32, No. 212, pp. 239-244.)

3355. CORRECTION, AND EXTENSION TO CYLINDRICAL ELECTRODE SYSTEMS (AS IN LARGE TRANSMITTING TRIODES) OF "A THEORY OF THE PRACTICAL TRIODE."—I. A. Harris. (*Wireless Engineer*, April 1941, Vol. 18, No. 211, pp. 153-154.) See 1080 of April.

3356. ON THE THEORY OF TUBES WITH TWO CONTROL GRIDS [Inadequacy of Published Data: Some Characteristics, & Practical Method of Calculating the Performance: Pentagrid Heptode as Amplifier, as Modulator, & as Heterodyne Detector].—A. H. Wing. (*Proc. I.R.E.*, March 1941, Vol. 29, No. 3, pp. 121-136.)

3357. NON-LINEAR DISTORTION IN AMPLIFIER VALVES AND LOW-FREQUENCY TRANSFORMERS.—E. Kettel. (*E.T.Z.*, 3rd July 1941, Vol. 62, No. 27, p. 614: summary, from *Telefunken-Röhre*, No. 18, 1940, pp. 1-32.)

A quasi-linear system is defined as one which must be regarded as non-linear towards the fundamental and linear towards the harmonics. The "klirr" factor K (governing harmonic production) and modulation factor m (governing combination-tone formation) are used as measures of the distortion.

The former (root of the sum of the squares of the percentages of the various harmonics in comparison with the fundamental) and the latter (defined as $m = (S_{\max} - S_{\min}) / (S_{\max} + S_{\min}) \times 100\%$) have simple relations to one another only when only the 2nd and 3rd harmonics are in evidence: for the square-law characteristic the calculated relation is $m_2 = 4K_2$. For every point on the characteristic of an amplifier value $\mu = SR_i$. The writer calculates μ and K for three cases: where $\mu = \text{const.}$, $S = f(V_o, V_a)$ ("slope" distortions): $S = \text{const.}$, $\mu = f(V_a)$; ("amplification-factor" distortions: this term includes the true "Durchgriff" distortions and the "current-division" distortions): and $S = f(V_o, V_a)$, $\mu = f(V_a)$ (as in highly modulated pentodes: both types of distortion occur). Low-frequency triodes and pentodes are considered in these calculations, and then the writer deals with the various forms of "slope" distortion (namely modulation distortion, cross-modulation, and hum-modulation) occurring in h.f. pentodes with high internal resistance and small anode-voltage modulation.

Finally, "iron" distortions are considered, arising from the non-linear relation between B and H , and thus given by the hysteresis curve. Without magnetic bias the curve is symmetrical and the distortions contain only odd (principally the 3rd) harmonics. Introduction of bias makes the curve asymmetrical and adds some even harmonics: as the bias is increased the distortions diminish. The no-load "klirr" factor and the voltage and current "klirr" factors for a load R_i are calculated, and a simple method of measuring the first is given (not in the summary). The "klirr" factor in the absence of magnetic bias,

and the "iron" distortions in a push-pull output stage and in a single-valve output stage, are calculated at the end of the full paper.

3358. THE FIGURE OF MERIT OF H.F. VALVES [Suggested "F.O.M." Rating for guiding Choice of Suitable Valve for a Particular Wide-Band Amplifier Circuit: Derivation for Four Types of Circuit].—C. Lockhart. (*E. & Television & S-W.W.*, March 1941, Vol. 14, No. 157, pp. 106-110.)
3359. GAS-FILLED TRIODES AND THEIR PRACTICAL USE [in Laboratory & in Industry].—G. Windred. (*E. & Television & S-W.W.*, Jan., Feb., & March 1941, Vol. 14, Nos. 155/157.) Concluding the series dealt with in 4279 of 1940 and 861 of March.
3360. VALVE ELECTRODE ASSEMBLY: A NEW METHOD.—R.C.A. Laboratories. (*E. & Television & S-W.W.*, Jan. 1941, Vol. 14, No. 155, p. 19.)
3361. ALTERNATIVES IN VALVE REPLACEMENT.—L. A. Moxon. (*E. & Television & S-W.W.*, May 1941, Vol. 14, No. 159, pp. 201-203.)

DIRECTIONAL WIRELESS

3362. MEASUREMENTS OF THE DELAY AND DIRECTION OF ARRIVAL OF ECHOES FROM NEAR-BY SHORT-WAVE TRANSMITTERS.—Edwards & Jansky. (See 3222.)
3363. LONG-DISTANCE POSITION-FINDING BY D.F. [Extension of Simple Method of Calculating the Great-Circle Bearing between Two Stations, to give Latitude & Longitude of Distant Station].—F. Addey. (*P.O. Elec. Eng. Journ.*, July 1941, Vol. 34, Part 2, pp. 94-95.) See 3478 of 1939.
3364. NOMOGRAMS FOR THE SOLUTION OF SPHERICAL TRIANGLES.—J. B. Friauf. (*Journ. Franklin Inst.*, Aug. 1941, Vol. 232, No. 2, pp. 151-174.)
3365. AEROPLANE LOCATION RECORDER [with Large Motor-Driven Frame Aerial for Short-Wave Signals from Aeroplane: Automatic Indication].—United Air Lines. (*E. & Television & S-W.W.*, May 1941, Vol. 14, No. 159, p. 218.)
3366. ECHO SOUNDER FOR AIR DEFENCE [using 50 cm Waves: on Principle of Western Electric "Absolute Altimeter" (1892 of 1940) but with Focused Beam].—(*Journ. Roy. Aeron. Soc.*, Sept. 1941, Vol. 45, No. 369, p. 268: abstract only.) Based on U.S. Patent Office publications.
3367. "AIR NAVIGATION" [Book Review].—F. G. Brown. (*Engineering*, 26th Sept. 1941, Vol. 152, p. 244.)

ACOUSTICS AND AUDIO-FREQUENCIES

3368. THE LOUDNESS GAIN BY BINAURAL HEARING, AND ITS SIGNIFICANCE [Binaural Telephones give 1 Neper Gain (owing to "Square-Root" Sensitivity Law of Ear): Neglect

hitherto due to General Erroneous Belief in "Square" Law: Application to improve Transmission Efficiency or to allow Increased Line Attenuation].—K. Braun. (*T.F.T.*, Dec. 1940, Vol. 29, No. 12, pp. 343-345.)

3369. HALF-WAVE MODULATION [Intelligibility of Speech Not Seriously Depreciated by Transmission of One Half Only of Wave-Form].—Bailey. (See 3301.)
3370. ON THE AUDIBILITY OF ECHO AND ITS INFLUENCE ON THE INTELLIGIBILITY OF SPEECH.—A. Rabinovich. (*Journ. of Tech. Phys.* [in Russian], No. 8, Vol. 10, 1940, pp. 605-616.)
3371. A NEW REFERENCE-ATTENUATION METER WITH OBJECTIVE EXCITATION AND INDICATION [including Use of Loudspeaker, excited by Speech Spectrum from Beat-Note Generator, as "Artificial Mouth," and Ballistic Galvanometer (with Rectifier) as "Ear"].—K. Braun. (*T.F.T.*, Aug. 1940, Vol. 29, No. 8, pp. 223-227.) Further development of the work dealt with in 54 of 1940 and 1105 of April.
3372. AUDIO-FREQUENCY MICROVOLTER [combining with an A.F. Oscillator to give Accurately known Continuously Variable Voltages 1.0 μ V to 1.0 V].—General Radio. (*Review Scient. Instr.*, Aug. 1941, Vol. 12, No. 8, p. 415.)
3373. A NEW TYPE OF AUDIO-FREQUENCY OSCILLATOR [Resistance-Tuned, with Regeneration through Selective RC Network].—(*E. & Television & S-W.W.*, Jan. 1941, Vol. 14, No. 155, pp. 14 and 21.)
3374. SOUND-INTEGRATING MACHINE [for Rapid Plotting of Sound-Field of Ringer or Loudspeaker].—(*Bell Lab. Record*, July 1941, Vol. 19, No. 11, p. 342.)
3375. THE ELECTRICAL BREAKDOWN OF ROCHELLE SALT.—B. V. Gorelik. (*Journ. of Tech. Phys.* [in Russian], No. 5, Vol. 10, 1940, pp. 369-375.)
Experiments were conducted to investigate the reasons for the abnormally low electrical breakdown of Rochelle salt. Comparative tests with crystals of rock salt, alum, and naphthalin were also made.
3376. RECENT RESEARCH AND ITS EFFECT UPON LOUDSPEAKER DESIGN [including Box Baffles and a "Vented Acoustic Chamber": Importance of Correct Vent Area: etc.].—(*E. & Television & S-W.W.*, April 1941, Vol. 14, No. 158, pp. 174-176.)
3377. THE POST OFFICE AND PUBLIC ADDRESS [from 1928 onwards].—E. J. Casterton. (*P.O. Elec. Eng. Journ.*, April 1941, Vol. 34, Part 1, pp. 26-30.)
3378. THE CALCULATION OF CAPACITANCES FOR CABLES OF SIMPLE CROSS SECTION.—Sommer. (See 3287.)

3379. SOUND PROPAGATION IN THE OPEN AIR, AND ITS DEPENDENCE ON METEOROLOGICAL CONDITIONS [Theoretical Treatment of Effects of Wind & Temperature Gradients: Experimental Confirmation (Minimum Attenuation for 250-4000 c/s is 1 db/100 m): Differing Effects of Nearness to Ground on High & Low Frequencies, etc.].—H. Sieg. (*E.N.T.*, Sept. 1940, Vol. 17, No. 9, pp. 193-208.) With 30 literature references.
3380. THE PROPAGATION OF PRESSURE FLUCTUATIONS OF LARGE AMPLITUDE IN AIR COLUMNS [Experimental Investigation].—L. J. Kastner. (*Phil. Mag.*, Sept. 1941, Vol. 32, No. 212, pp. 206-224.)
3381. BELL SOUND DETECTOR [Use of Line Microphones (3600 of 1939) for Ground Defences].—Bell Tel. Laboratories. (*Journ. Roy. Aeron. Soc.*, Sept. 1941, Vol. 45, No. 369, p. 268: abstract only.)
3382. AEROPLANE "SPOTTING" BY ELECTRO-ACOUSTICAL METHODS.—Benjamin Electric. (*E. & Television & S-W.W.*, April 1941, Vol. 14, No. 148, pp. 153-154.) Commercial development of the system referred to in 790 of March.
3383. ON THE PREPARATION OF A THERMAL LIGHT-SOURCE WHICH CAN BE MODULATED AT NOTE FREQUENCIES.—Lattman. (See 3608.)
3384. THE TECHNIQUE OF THE COMMERCIAL GRAMOPHONE-DISC RECORDING PROCESS [including Test Methods (Advantages of Measurement of Quadratic & Cubic—Asymmetrical & Symmetrical—Distortions over Measurement of "Klirr" Factor: etc.): a Compressed Survey].—W. A. Günther. (*Bull. Assoc. suisse des Elec.*, 4th July 1941, Vol. 32, No. 13, pp. 291-296: in German.)
3385. RE-COATING RECORDING BLANKS [Description of Operation], and RECORDING BLANKS.—W. H. Pierce: D. W. Aldous. (*Wireless World*, Sept. 1941, Vol. 47, No. 9, pp. 242-243: Oct. 1941, No. 10, pp. 269-270.)
3386. A VARIABLE-SPEED TURNTABLE UNIT [Friction Wheel-&Cone Drive].—(*E. & Television & S-W.W.*, March 1941, Vol. 14, No. 157, p. 110.)
3387. MAGNETIC RECORDING AND SOME OF ITS APPLICATIONS IN THE BROADCAST FIELD [with 29 Literature References].—S. J. Begun. (*Proc. I.R.E.*, Aug. 1941, Vol. 29, No. 8, pp. 423-433.) A summary was referred to in 1395 of May.
3388. THE SYNTHETIC PRODUCTION AND CONTROL OF ACOUSTIC PHENOMENA BY A MAGNETIC RECORDING SYSTEM [Survey of Previous Proposals for "Synthetic Reverberation": Magnetic-Tape System re-designed by Brush Company: Applications to Other Purposes (Study of Sound-Decay Curves, of Space-Phasing for Improving Naturalness of P.A. Systems, etc.)].—S. K. Wolf. (*Proc. I.R.E.*, July 1941, Vol. 29, No. 7, pp. 365-371.)
3389. THE ABSORPTION OF SOUND BY MEANS OF A THREE-LAYER RESONANCE SYSTEM.—V. Nesterov. (*Journ. of Tech. Phys.* [in Russian], No. 8, Vol. 10, 1940, pp. 617-626.)
3390. THE "ACOUSTIC ENVELOPE": NEW DEVELOPMENT TO AID VOICE PRODUCTION [employed by Paul Robeson in touring Halls of Widely Varying Characteristics].—H. Burris-Meyer. (*Wireless World*, Sept. 1941, Vol. 47, No. 9, p. 233.) For other work by Burris-Meyer see 2440 of September.
3391. SYNTHESIS OF MUSICAL SOUNDS BY THE TOOTHED-WHEEL GENERATOR [Discrepancies between Tone of Electrical Musical Instruments & Their Mechanical Prototypes: Investigation, with View to eliminating These, of Toothed-Wheel Generator, with Magnetic or Electrostatic Pick-Up: Effects of Variation of Gap, Tooth Form, etc.].—K. H. Kleine. (*Physik. Zeitschr.*, April 1941, Vol. 42, No. 6, pp. 111-116.)
3392. TESTS AT THE NATIONAL INSTITUTE OF ELECTROACOUSTICS TO ARRIVE AT AN OBJECTIVE ESTIMATE OF THE ACOUSTICAL QUALITY OF SOME VIOLINS.—G. Pasqualini. (*La Ricerca Scient.*, Sept. 1940, Vol. 11, No. 9, pp. 622-639.) Beginning with a survey of previous work in various countries.
3393. NEGATIVE CHARACTERISTIC OF THE PIPE REED.—Zahradníček & Nesper. (*Physik. Zeitschr.*, Sept. 1940, Vol. 41, No. 17/18, pp. 419-421.)
3394. MOTION OF THE WALLS OF A CORNET [studied with Piezoelectric Pick-Up].—H. P. Knauss. (*Phys. Review*, 1st July 1941, Vol. 60, No. 1, p. 65: summary only.)
3395. THE COMMA IN MUSIC [Suggestion of New Comma, between Those of Pythagoras & Didymus, as Integer (53 Commas in Octave)].—A. F. Dufton. (*Phil. Mag.*, Sept. 1941, Vol. 32, No. 212, pp. 259-261.)
 "Although a gamut with 54 notes to the octave may appear to be unsuitable for a manual keyboard, the development of mechanically played music must not be ignored."
3396. THE CROSLY CONTRAST EXPANDER: AN ANALYSIS OF THE CIRCUIT [Bridge Circuit with Two Metal-Filament Lamps].—S. W. Amos. (*Wireless Engineer*, June 1941, Vol. 18, No. 213, pp. 237-239.)
 The improvement in contrast is not proportional to the original contrast, but "even this kind of expander is well worth including in receivers, owing to its simplicity."
3397. DESIGN FOR A SUPER-QUALITY 12-WATT AMPLIFIER.—J. C. C. Gilbert. (*E. & Television & S-W.W.*, Feb. & March 1941, Vol. 14, Nos. 156 & 157, pp. 72-75 & 111-116.)
 For a further note see April issue, pp. 184-185: here a defect (attenuation of the very low and very high audio-frequencies) of the Carpenter paraphase circuit employed is discussed, and a change suggested to O. H. Schmitt's circuit (2024 of 1938),

the claims for which have been verified experimentally: the paper incorrectly gives the name as Schmidt.

3398. THE CALCULATION OF FREQUENCY RESPONSE OF AUDIO-FREQUENCY AMPLIFIERS [and the Influence of the Miller Effect on the Higher Frequencies].—(*E. & Television & S.W.*, April 1941, Vol. 14, No. 158, p. 167.)
3399. NON-LINEAR DISTORTION IN AMPLIFIER VALVES AND LOW-FREQUENCY TRANSFORMERS.—Kettel. (*See* 3357.)
3400. A MEASURING EQUIPMENT WITH DIRECT INDICATION FOR THE DETERMINATION OF THE "KLIRR" FACTOR AND INDIVIDUAL HARMONICS.—H. Rupp. (*E.N.T.*, Nov. 1940, Vol. 17, No. 11, pp. 247-261.)

To obtain an accurate knowledge of the transmission properties of amplifiers, lines, etc., it is necessary to know how the "klirr" factor (non-linear distortion factor: sometimes translated as "blurr" or "rasping" factor: defined by Küpfmüller as

$$k = \sqrt{(A_2^2 + A_3^2 + \dots) / (A_1^2 + A_2^2 + \dots)},$$

but often given as

$$k' = \sqrt{(A_2^2 + A_3^2 + \dots) / A_1^2},$$

in which case $k = k' / (1 + k'^2)$: (*cf.* Kettel, 3357) varies not only with the frequency but also with the transmission level. With the usual methods of measuring this factor, such a process would take a great deal of time, since the circuit would require balancing before each reading. The method here developed allows the factor to be read directly off an indicating instrument: if desired, the "klirr" factor characteristic could be recorded automatically. By a change of circuit the individual harmonics can be measured: in this way the detection of the part of the transmission circuit which is causing the distortion is made easy—an advantage not possessed by previous techniques. The equipments described cover a frequency range of 50 to 10 000 c/s; the smallest "klirr" factor measurable is 0.4%, the accuracy is within 6-7% of the factor value.

The principle of the "klirr" factor measurement is that the variable test frequency f_1 is passed through the circuit under investigation and leaves it as $f_1 + nf_1$: it is then acted on (in the "modulator" M in Fig. 4) by an auxiliary frequency f_2 which is automatically regulated so that the sum (or the difference) of f_1 and f_2 is constant. Beyond M there appear, therefore, the two fundamental frequencies f_1 and f_2 , and in addition the frequencies $f_2 + (f_1 + nf_1)$ and $f_2 - (f_1 + nf_1)$. If f_2 is so regulated that the sum frequency $f_2 + f_1$ remains constant, and if the mixture is acted on by a high-pass filter S , only $f_2 + nf_1$ will emerge from S and reach the indicating instrument K , which will therefore measure the "klirr" frequencies of the original test frequency: the same will occur when it is the difference frequency which is kept constant, a low-pass filter being used in this case for S . The automatic adjustment of the auxiliary frequency is accomplished purely electrically by the system of multiple modulation included in the complete scheme, Fig. 5: the three generators G_1 ,

G_2 , & G_3 produce frequencies f_1 , f_2 , & f_3 , of which the first and last are fixed while f_2 is variable over a certain range. The modulators M_1 & M_2 produce $f_1 - f_2$ and $f_2 - f_3$, respectively, which are freed from the fundamentals and other modulation frequencies by filters S_1 & S_2 . The frequency $f_1 - f_2$ forms the variable test frequency, the original " f_1 " dealt with above, while $f_2 - f_3$ forms the auxiliary frequency (" f_2 " above) which acts on the test frequency in a third modulator M_3 after that frequency has passed through the circuit under investigation. The sum of the fundamental frequencies arriving at M_3 is thus $f_4 = f_1 - f_2 + (f_2 - f_3) = f_1 - f_3$: since f_1 and f_3 are both constant, f_4 is also constant, whatever the test frequency $f_1 - f_2$ may be, which is what was required.

The scheme shown in Fig. 6 and discussed more fully on pp. 259-260 is a simplified version of the above, requiring rather less apparatus but lacking certain advantages. In either case, the performance of the final filter (S in Fig. 4) in front of the indicating instrument is the chief factor in determining the accuracy obtainable: the lower-frequency flank of its characteristic must be very steep, and it therefore takes the form of a crystal bridge filter (*see* 3265, above). The circuit used when it is required to measure individual harmonics is shown in Fig. 8 and discussed more fully on p. 260.

3401. SOLID CARBON DIOXIDE AS AN EXCITER OF VIBRATIONS [and Some Applications].—Mary D. Waller. (*Nature*, 16th Aug. 1941, Vol. 148, pp. 185-187.)
3402. ON ACOUSTICALLY EFFECTIVE VORTEX MOTION IN GASEOUS JETS.—P. Savic. (*Phil. Mag.*, Sept. 1941, Vol. 32, No. 212, pp. 245-252.)
3403. PAPER ON THE VELOCITY OF ACOUSTICAL WAVES IN PETROLEUM FRACTIONS.—Matte-son & Vogt. (*See* 3511.)
3404. SUPERSONIC-WAVE ABSORPTION IN LIQUIDS, MEASURED OPTICALLY [by Practical Application of Grobe's Method (2860 of 1938)].—A. Lindberg. (*Physik. Zeitschr.*, 15th Oct. 1940, Vol. 41, No. 20, pp. 457-467.)
3405. SUPERSONIC-WAVE DISPERSION AND THE VELOCITY OF FRACTURE [with Photographs of Glass Fractures].—A. Smekal. (*Physik. Zeitschr.*, 15th Oct. 1940, Vol. 41, No. 20 pp. 475-480.)

PHOTOTELEGRAPHY AND TELEVISION

3406. "SCRAMBLED" TELEVISION. — Scopphony, (*Wireless World*, Oct. 1941, Vol. 47, No. 10, pp. 272-273.) British Patent 530 776.
3407. TELEVISION TRANSMISSION [Experiments with 441-Line, 30-Frame Interlaced Transmission over Coaxial Cable & Other Telephone Facilities].—M. E. Strieby & C. L. Weis. (*Proc. I.R.E.*, July 1941, Vol. 29, No. 7, pp. 371-381.) A summary was dealt with in 1936 of July.

3408. SOME OBSERVATIONS RELATING TO REPORTS OF COLOUR TELEVISION IN AMERICA, and J. L. BAIRD'S NEW COLOUR TELEVISION SYSTEM.—P. Nagy; J. L. Baird. (*E. & Television & S.W.W.*, Feb. 1941, Vol. 14, No. 156, pp. 60-62 and 95, 96; pp. 69-70.)
3409. FILM SCANNER FOR USE IN TELEVISION TRANSMISSION TESTS [Advantages of Farnsworth Image Dissector as Pick-Up: Use of Special Film "stretched" to give 60 Frames: Vertical Scanning by Continuous Motion of Film, Horizontal by Electronic Line Sweep in Dissector Tube].—A. G. Jensen. (*Proc. I.R.E.*, May 1941, Vol. 29, No. 5, pp. 243-249.)
3410. A PHASE-CURVE TRACER FOR TELEVISION [Phase Curve of Any Network shown on C.R.O. Screen, on Linear Frequency Scale from 0.1-5 Mc/s].—B. D. Loughlin. (*Proc. I.R.E.*, March 1941, Vol. 29, No. 3, pp. 107-115.) A summary was referred to in 1937 of July.
3411. A COAXIAL FILTER FOR VESTIGIAL-SIDEBAND TRANSMISSION IN TELEVISION.—H. Salinger. (*Proc. I.R.E.*, March 1941, Vol. 29, No. 3, pp. 115-120.) A summary was dealt with in 1846 of July. Cf. Brown, 3088 of November.
3412. BRIGHTNESS DISTORTION IN TELEVISION.—D. G. Fink. (*Proc. I.R.E.*, June 1941, Vol. 29, No. 6, pp. 310-321.) A summary was dealt with in 1430 of May.
3413. VERSATILE MULTI-CHANNEL TELEVISION CONTROL EQUIPMENT.—D. E. Norgaard & J. L. Jones. (*Proc. I.R.E.*, May 1941, Vol. 29, No. 5, pp. 250-265.) A summary was referred to in 1938 of July.
3414. NEW DESIGNS OF TELEVISION CONTROL-ROOM EQUIPMENT.—J. D. Schantz. (*Proc. I.R.E.*, June 1941, Vol. 29, No. 6, pp. 303-309.) From the Farnsworth Corporation.
3415. PHOTOELECTRIC CONDUCTIVITY OF ZINC-SULPHIDE/COPPER PHOSPHORS UNDER THE ACTION OF ALPHA RAYS.—F. R. Lappe. (*Ann. der Physik*, 14th June 1941, Vol. 39, No. 8, pp. 604-618.)
- The writer begins by stressing the importance of investigating the mechanism of phosphors by electrical methods (*cf.* Ruffler, 2517 of September). These are often easier, quicker, and more sensitive than optical methods, and conclusions as to optical behaviour can be drawn from them. Thus Goos, by experiments with ZnS₂Cu phosphors disintegrated by alpha rays, found among other things that this disintegration produced a linear increase in the extinction effect, already particularly pronounced in this particular phosphor (2714 of 1940 and back reference): he used, instead of optical measurement, the change of dielectric constant in a h.f. oscillatory circuit as a measure of the effect of illumination.
- It has been suggested that the "secondary current," *i.e.* the conductivity under an applied voltage, on illumination, would show a similar variation, and the present work examines this suggestion. The phosphor was spread in a very fine layer on a metal plate in a "conductivity cell" so that its electrical behaviour could be followed, both before and after the action of alpha rays, under the influence of the exciting light and of the red and infra-red light for producing the extinction effect (Fig. 1). The highly insulating phosphor under test shows a conveniently measurable "secondary current" on illumination only if the film is so thin that the incident light can excite it all through: Lenard gives a thickness of 0.014 mm at most for full excitation, and the film here used was of about that thickness, giving secondary currents about 1000 times as great as the "dark" current, with comparatively low voltages.
- Among the results obtained, and summarised on pp. 617-618, are the following:—the extinction effect in a continuously "blue"-excited phosphor (curve a, Fig. 3), measured as a "secondary-current" decrease, shows a marked inertia, as does the rise which occurs at the end of the extinction ("Rot aus"). If, on the other hand, the "blue" excitation is cut off, the current falls in the normal decay mode (curve b): the introduction of the extinguishing radiation ("Rot belichtet") causes an immediate but small rise in the current, followed by a more rapid decay. The small rise indicates the occurrence of a slight luminosity produced by the long-wave radiation, side by side with the extinction effect. Curve c represents the case when the red radiation is applied directly the blue is cut off: the current sinks much more quickly, practically reaching its "dark" value within 6 minutes, compared with over 10 minutes. The first apparent action of alpha rays is to behave as a short-wave exciting radiation, but simultaneously the destruction of the active centres has set in. The extinction effect as shown by the "secondary current" increases linearly with the destruction process, so that Goos's results are confirmed by this new method. A considerable variation of the "secondary current" with gas pressure was found, both dark and illuminated currents increasing rapidly with decreasing pressure: the extinction effect decreased, not so markedly, with decreasing pressure.
3416. THE RESPONSE OF ELECTRICAL NETWORKS TO NON-SINUSOIDAL PERIODIC WAVES.—Marchand. (*See* 3259.)
3417. BUILDING-UP PROCESSES IN OSCILLATORY CIRCUITS [Treatment based on Equivalent Circuit containing only Distortion-Free Lines: Stationary Oscillations: Building-Up Process outside Resonance: with Continually Varying Frequency (*e.g.* in Exploring-Note Sound Analysis): Technique applicable to Amplifiers with Several Mutually Detuned Circuits, etc.].—R. Feldtkeller. (*T.F.T.*, Dec. 1940, Vol. 29, No. 12, pp. 353-356.) For different treatments *cf.* Wheeler, 3642 of 1939, and Strecker, 447 of February.
3418. ELIMINATING PEAKS IN AMPLIFIER RESPONSE CURVES [at High-Frequency End of Video-Amplifier Range, due to Reactive Elements

- in Anode Circuit of One Valve].—R.C.A. Laboratories. (*E. & Television & S.W.W.*, May 1941, Vol. 14, No. 159, pp. 215 and 217.)
3419. THE ATTENUATION AND IMPEDANCE OF SINGLE COAXIAL CABLES [with Air-Space and Solid Polythene Dielectrics: Benefits obtainable from Standardisation of Characteristic Impedance: 75 Ohms as Suitable Value].—R. A. Brockbank. (*P.O. Elec. Eng. Journ.*, July 1941, Vol. 34, Part 2, pp. 66-71.)
3420. THE BEHAVIOUR OF WIDE-BAND CABLES WITH STYROFLEX INSULATION IN THE DECIMETRIC - WAVE BAND.—Kaufmann. (*See* 3328.)
3421. A FLEXIBLE LOW-ATTENUATION TRANSMISSION LINE [Continuously Moulded Polystyrene Embedment in Ribbon Form].—R.C.A. Laboratories. (*E. & Television & S.W.W.*, March 1941, Vol. 14, No. 157, pp. 135-136.)
3422. KERR EFFECT AND MOLECULAR STATE IN HIGHLY COMPRESSED GASES AND LIQUIDS.—E. Kuss & H. A. Stuart. (*Physik. Zeitschr.*, April 1941, Vol. 42, No. 6, pp. 95-105.)
3423. HALF-TONE REPRODUCTION IN PICTURE-TRANSMISSION APPARATUS USING GAS-FILLED LAMPS FOR POSITIVE RECORDING.—E. L. Orlovski. (*Journ. of Tech. Phys.* [in Russian], No. 4, Vol. 10, 1940, pp. 274-294.)
- A detailed discussion is given of the mathematical relationship between the optical density D' of the picture element to be transmitted and the optical density D_r of the corresponding recorded element when positive recording of the received picture is employed. It is shown that considerable distortion of half-tones occurs in picture transmission by apparatus of Soviet manufacture. Accordingly, the optimum operating conditions of the positive rectifier in the recording apparatus are established and a correcting circuit (lower half of Fig. 18) is proposed. Experiments with this circuit have shown that a great improvement is obtained thereby. Theoretical considerations are also put forward indicating that the photocurrent amplifier at the transmitting or receiving station can be so designed as to ensure distortionless transmission of half-tones. Another advantage of such amplifiers would be a rise in the permissible interference level.
3424. FUNDAMENTALS OF PHOTOTELEGRAPHY TECHNIQUE: PARTS I AND II.—H. Bitter. (*T.F.T.*, Aug. & Sept. 1940, Vol. 29, Nos. 8 & 9, pp. 215-223 & 270-276.) The third and final part was dealt with in 1444 of May.
3425. THE HANDLING OF TELEGRAMS IN FACSIMILE.—R. J. Wise & I. S. Coggeshall. (*Proc. I.R.E.*, May 1941, Vol. 29, No. 5, pp. 237-242.) A summary was dealt with in 1947 of July.
3426. THE RCA-931 MULTIPLIER PHOTOTUBE.—(*Review Scient. Instr.*, Aug. 1941, Vol. 12, No. 8, p. 416.)
3427. A REVIEW OF THE DEVELOPMENT OF SENSITIVE PHOTOTUBES [with over 80 Literature References].—A. M. Glover. (*Proc. I.R.E.*, Aug. 1941, Vol. 29, No. 8, pp. 413-423.)
3428. ON THE THEORY OF THE PHOTOEFFECT IN SEMICONDUCTORS [where Sommerfeld's Free-Electron Theory is No Longer Adequate].—V. F. Weisskopf & L. W. Apker. (*Phys. Review*, 15th July 1941, Vol. 60, No. 2, p. 170: summary only.)
3429. THE CRYSTAL PHOTOEFFECT IN *d*-TARTARIC ACID [Examination of Brady-Moore Current-Reversal Phenomenon].—C. K. Lui. (*Phys. Review*, 15th July 1941, Vol. 60, No. 2, pp. 160-161: summary only.)
3430. A NOTE ON THE DEMONSTRATION OF THE PHOTOEFFECT WITH A GLOW-DISCHARGE LAMP [and Some Applications].—Metzger. (*See* 3604.)
3431. A STUDY OF THE SECONDARY EMISSION FROM CUPROUS OXIDE, PURE OR TREATED WITH ALKALI METALS.—Frimer. (*See* 3347.)
3432. ON THE DEPENDENCE ON ANGLE OF THE SECONDARY-ELECTRON EMISSION FROM INSULATORS.—H. Salow. (*Physik. Zeitschr.*, 1st Oct. 1940, Vol. 41, No. 19, pp. 434-442.)
- For previous work, in connection with television pick-up tubes, *see* 1995 & 4025 of 1939 and 1881 of 1940. The present paper deals with measurements on mica, glass, and zinc sulphide. The characteristic of the s.e. coefficient between incident angles 0° to 70° and potentials 100 to 4000 v is a smooth curve following the same law as that for the angle-dependence of s.e. from metals. On the assumption of the validity of the Widdington-Thomson law for the energy dissipation of the primary electrons, and assuming a secondary-electron absorption proportional to the path, a formula is derived which represents the important features of the experimental results as regards potential and angle dependence. The sudden change in the s.e. from insulators at definite angular values, assumed to exist by Wehnelt and his school, is traced to the special measuring technique employed: the "jump" effect occurring in the collector current in this technique happens when the s.e. coefficient of the insulator reaches unity, and must not be regarded as a sudden change in the secondary emission.
3433. THE DRIFT OF THE SELENIUM BARRIER-LAYER PHOTOCCELL [Survey of Conflicting Reports: Measurements on Photronic, German, & Other Types].—R. A. Houstoun. (*Phil. Mag.*, June 1941, Vol. 31, No. 209, pp. 498-506.)
3434. A BIBLIOGRAPHY RELATING TO BARRIER-LAYER PHOTOELECTRIC CELLS.—(*Science Library Bibliogr. Series*, No. 558, 1941, 3 pp.)

MEASUREMENTS AND STANDARDS

3435. A NEW METHOD FOR MEASURING THE DIELECTRIC CONSTANTS AND LOSS FACTORS OF INSULATING MATERIALS IN THE CENTIMETRIC WAVE BAND.—F. Borgnis. (*Naturwiss.*, 22nd Aug. 1941, Vol. 29, No. 34, pp. 516-517.)

The ordinary h.f. methods become so difficult at these micro-wave frequencies that optical methods have been tried (Baz, 3695 of 1939; Kebbel, 2444 of 1939). Recently the distribution of the electric field of standing waves produced in a hollow tube of rectangular section, with a plate of the material at its closed end, has been employed for the purpose (Roberts & von Hippel, 3508 of 1940; Fejér & Scherrer, 3436, below). The present letter describes a method using a cylindrical cavity resonator of radius R , the test specimens taking the form of cylindrical rods of radius ρ , easy to prepare and economical in material: the electromagnetic relations in the resonator are exactly defined, are unaffected by edge effects and external disturbances, and permit an accurate theoretical treatment to be applied.

The cavity is excited in its electrical fundamental (Borgnis, 905 of 1940 [for later work see 61 of January and cross references]). The electric field strength has only one component E_z parallel to the cylinder axis, the magnetic field strength has a circular component H_ϕ . The resonance wave, whatever the height of the cylinder, is given by $\lambda = 2.61R$. If the rod of material is introduced centrally in the cavity, the essential character of the field remains unchanged: the presence of the rod modifies only the radial course of the electric and magnetic fields. The resonance wavelength λ is increased by $\Delta\lambda$, and for thin rods $\epsilon - 1 = 0.538(R/\rho)^2 \cdot \Delta\lambda/\lambda$, from which ϵ is obtained easily. The loss factor is measured by plotting the resonance curves of the resonator without and with the rod: if d and d' are the corresponding half-value breadths, then $\tan \delta = (0.269/\epsilon)(R/\rho)^2(d' - d)$. Average values for ϵ on a 14 cm wavelength, for Trolitul, Calit, and amber, were 2.32, 5.30, and 2.30 respectively, while the corresponding values for $\tan \delta \times 10^4$ were 5.7, 19, and 70. Control tests showed complete agreement between theory and experiment. The limit of error varies with different materials: it may rise to about 10%.

3436. PAPER ON THE MEASUREMENT OF DIELECTRIC CONSTANT AND LOSS FACTOR FOR CENTIMETRIC WAVES, BY INTERFEROMETRIC METHOD.—G. Fejér & P. Scherrer. (*Helvetica Phys. Acta*, Vol. 14, 1941, p. 141 onwards.) Referred to by Borgnis, 3435, above.
3437. THE OSCILLATING HIGH-FREQUENCY AMMETER [for Ultra-High Frequencies: Editorial on American Development, 3724 of 1938 and 819 of March].—G.W.O.H. Michel & Meahl. (*Wireless Engineer*, March 1941, Vol. 18, No. 210, pp. 93-94.)
3438. THE EFFECT OF THE DIELECTRIC CONSTANT OF THE AIR ON THE FREQUENCY STABILITY OF OSCILLATING CIRCUITS.—Volpert. (See 3292.)

3439. THE PIERCE PIEZOELECTRIC OSCILLATOR: ANALYSIS FOR THE DESIGN OF CRYSTAL AND LINE-CONTROLLED APPARATUS [Fresh Analysis to help in Design of Oscillator with Frequency Variable over Maximum Range compatible with Control by Single Crystal, and with Constant Amplitude: Extension to Line-Stabilised U.H.F. Oscillators].—H. Jefferson. (*Wireless Engineer*, June 1941, Vol. 18, No. 213, pp. 232-237.) From the Marconi laboratories.

3440. CONTOUR-MODE VIBRATIONS IN Y-CUT QUARTZ-CRYSTAL PLATES [Theory & Experiment: Conclusion that Principal Contour-Mode Responses are due to Coupling between Shear and Second Flexure & Its Harmonics: Extensional & First Flexural Modes occur only with Special Electrode Arrangements].—G. Builder & J. E. Benson. (*Proc. I.R.E.*, April 1941, Vol. 29, No. 4, pp. 182-185.)

3441. OSCILLOSCOPE PATTERNS OF DAMPED VIBRATIONS OF QUARTZ PLATES, AND Q MEASUREMENTS WITH DAMPED VIBRATIONS [including a Method using a "Momentary Contactor," sometimes employed in Determination of Alternator Wave-Form].—H. A. Brown. (*Proc. I.R.E.*, April 1941, Vol. 29, No. 4, pp. 195-199.) A summary was referred to in 3519 of 1940.

3442. PIEZOELECTRIC CRYSTALS [Correspondence on Notation of Quartz Crystals].—R. L. Smith-Rose: Mason & Willard. (*Proc. I.R.E.*, July 1941, Vol. 29, No. 7, p. 405.) See 501 of February.

3443. REFRACTION PATTERNS OF THE SURFACES OF OPAQUE AND TRANSLUCENT SOLIDS [Extension of Method (previously applied to Quartz) by Use of 'Diakon' Casts].—R. S. Rivlin & W. A. Wooster. (*Nature*, 27th Sept. 1941, Vol. 148, p. 372.) See 2774 of October.

3444. A QUARTZ-CRYSTAL CUTTING AND LAPPING MACHINE [Simplified Design, retaining Essentials for Accurate & Controlled Cutting], and THE PREPARATION OF PIEZOELECTRIC QUARTZ PLATES.—F. Butler. (*E. & Television & S.W.W.*, May 1941, Vol. 14, No. 159, pp. 204-207 and 211; *Electronic Engineering* [new form of above], June 1941, Vol. 14, No. 160, pp. 252-254 and 281.)

3445. SOME ANALYSES OF WAVE SHAPES USED IN HARMONIC PRODUCERS [in the Heterodyne Method of Frequency Comparison: Fourier Analyses of Sinusoidal, Rectangular, & Trapezoidal Pulses, and of Multivibrator Waves: Method of Modulation with Submultiple to increase Harmonic Content].—F. R. Stansel. (*Bell S. Tech. Journ.*, July 1941, Vol. 20, No. 3, pp. 331-339.)

3446. A STABILISED FREQUENCY DIVIDER [for Frequency-Measuring Equipment, etc.].—Builder. (See 3252.)

3447. SOME OBSERVATIONS ON AN A.C. RESONANT PENDULUM [Pendulum Bob of Iron swinging into Air-Core Coil tuned by Condenser to 60 c/s: Measurements on Current & Voltage, to determine Nature of Driving Force].—D. K. Weimer. (*Phys. Review*, 1st July 1941, Vol. 60, No. 1, p. 65: summary only.)
3448. WIRE-BROADCASTING MEASURING TECHNIQUE [developed by German P.O. & Industry].—Eisele. (*See* 3544.)
3449. SIGNAL GENERATORS ON THE H.F. MODULATION PRINCIPLE [particularly for Testing the Sensitivity & Selectivity of Receivers].—H. Nitsche. (*E.N.T.*, Nov. 1940, Vol. 17, No. 11, pp. 262-268.)

From the Rohde & Schwarz laboratories. If a h.f. generator for sensitivity measurements generates a h.f. voltage around 50-100 v and this has to be reducible by a voltage-dividing device to perhaps 1 μ v, screening attenuation necessary to keep interfering voltages down to 10% of the reduced test voltage must be of the order of 10³. This by no means easy problem has been solved satisfactorily for frequencies up to 300 Mc/s and over, but many attempts have been made to circumvent the necessity for such careful screening. A reduction of the full generator voltage, by the use of space-charge-grid valves or special regulating circuits, has the defect that if this is done, the reaction of the voltage divider on the frequency cannot be nullified, as is usually the case, by the use of very loose couplings. The employment of harmonics, with amplitudes about 1-2% of the fundamental, is another possible way of reducing the screening by about two orders of magnitude, but the obtaining of a harmonic voltage which will keep a constant ratio to the fundamental over a range of frequencies (a condition necessary for a direct calibration) is a difficult task. The use of sideband frequencies ("h.f. modulation principle") offers definite advantages: a h.f. carrier (*e.g.*, $f = 50$ Mc/s) is modulated by a h.f. voltage of lower frequency (*e.g.*, $f_1 = 500$ kc/s), to yield a sideband frequency of $f \pm f_1$ which can be given a note modulation by modulating f_1 , so that the modulation percentage remains constant. Then the production of small voltages $U_{f \pm f_1}$ is not dependent on the screening of the short-wave oscillator, since larger voltages of the required frequency do not occur if the weakening takes place on the modulating voltage U_{f_1} . Moreover, very small changes in the frequency of $f \pm f_1$ can be performed simply, by varying the comparatively low modulating frequency: a 10⁻³ change of f_1 (*i.e.* a change of 500 c/s in the case taken above) would give a detuning $\Delta f/f = 10^{-5}$ in the sideband frequency $f \pm f_1 = 50.5$ Mc/s.

An equipment developed on these principles was constructed and showed a number of interesting properties: the writer, however, emphasises that it was required for a distinctly special purpose (not specified) and that it is not recommended for general purposes or as a basis for mass production: it involves a large outlay and (in spite of careful design with an eye to simplicity in working) a complicated procedure. On the other hand, if the principle is used only for the advantage which it offers in the matter of very fine frequency adjustment for the

measurement of band-widths (the defects of the usual methods, electrical and mechanical, of obtaining such an adjustment are discussed in section II on p. 265), the equipment can be made very much simpler and more convenient, and forms a useful auxiliary to an ordinary signal generator.

3450. MEASUREMENT OF LOOP-ANTENNA RECEIVERS [and the Introduction of the Measuring Signal by a Transmitting Loop: Designs of Latter, including Shielding: Derivation of Formulae concerned: etc.].—W. O. Swinyard. (*Proc. I.R.E.*, July 1941, Vol. 29, No. 7, pp. 382-387.)
3451. PROGRESS IN THE DEVELOPMENT OF INSTRUMENTS FOR MEASURING RADIO NOISE.—Burrill. (*See* 3318.)
3452. THE MEASUREMENT OF MODULATION DEPTH [Method used in Peak Programme Meter for B.B.C. Monitoring].—Ellis. (*See* 3299.)
3453. A MEASURING EQUIPMENT WITH DIRECT INDICATION FOR THE DETERMINATION OF THE "KLIRN" FACTOR AND INDIVIDUAL HARMONICS.—Rupp. (*See* 3400.)
3454. A "TROUGH" VOLTMETER FOR MEASURING THE MINIMUM VALUE OF A UNIDIRECTIONAL UNDULATING VOLTAGE.—F. C. Williams & A. Fairweather. (In paper dealt with in 3478, below.)
3455. DESIGN FOR MAGIC-EYE VALVE VOLTMETER.—J. C. G. Gilbert. (*E. & Television & S.W.W.*, May 1941, Vol. 14, No. 159, pp. 212-214.)
3456. AN IMPULSE GENERATOR [for Impulse Transmission Testing & Other Purposes: giving Continuous Series of Impulses or Cyclic Repetition].—B. M. Hadfield & W. W. Chandler. (*P.O. Elec. Eng. Journ.*, April 1941, Vol. 34, Part 1, pp. 31-35.) The impulsing speed can be varied without affecting the percentage break, and *vice versa*.
3457. THE USE OF REPEATERS AS IMPEDANCE METERS [in Small Repeater Stations lacking Other Instruments: Repeater Itself used as Bridge].—K. Oettl. (*T.F.T.*, July 1940, Vol. 29, No. 7, pp. 192-196.)
3458. STRAY CAPACITANCES: INFLUENCE ON EFFECTIVE INDUCTANCE OF COIL IN METAL CONTAINER [measured by Resonance Method and Transformer Bridge Methods].—Farren & Rivlin. (*See* 3266.)
3459. THE BRIDGED-T METHOD OF MEASURING THE CONSTANTS OF A COIL [Extension of Editorial on Honnell's Method (3111 of 1940) to Inductance & Effective Resistance].—G.W.O.H. (*Wireless Engineer*, April 1941, Vol. 18, No. 211, pp. 135-136.)
3460. THE DESIGN OF THE UNIVERSAL WINDING [for Max. Inductance in Min. Volume: Gear-Ratio Formula and Tables & Curves for Its Application].—L. M. Hershey. (*Proc. I.R.E.*, Aug. 1941, Vol. 29, No. 8, pp. 442-446.)

3461. A.C. IMPEDANCE OF CHOKES AND TRANSFORMERS: A MEASURING INSTRUMENT FOR PRODUCTION CHECKS [Objections to Established Methods (Volt-Ammeter, Comparison): Development of Practical Instrument largely overcoming These, based on Comparison by Valve-Voltmeter Method].—T. J. Rehfisch & H. T. Bissmire. (*Wireless Engineer*, July 1941, Vol. 18, No. 214, pp. 266-270.) From the Murphy laboratories.
3462. MEASUREMENT OF IRON CORES AT RADIO FREQUENCIES [Method of measuring Effective Permeability & Loss Factor: Derivation of Expressions for predicting Coil Characteristics from These Constants: Examples (Variation of Q with Frequency & with Coil Diameter, Core/Coil Capacitance Effects, etc.): Corrections for Internal Resistance: etc.].—D. E. Foster & A. E. Newlon. (*Proc. I.R.E.*, May 1941, Vol. 29, No. 5, pp. 266-276.)
3463. TESTING SMALL SAMPLES OF TRANSFORMER IRON.—G.W.O.H.: Lamson. (*Wireless Engineer*, Aug. 1941, Vol. 18, No. 215, pp. 307-309.) Editorial on the method dealt with in 2180 of August.
3464. MECHANICAL RECTIFIERS AND THEIR USE IN MEASURING TECHNIQUE.—W. A. E. Peters. (*E.T.Z.*, 3rd July 1941, Vol. 62, No. 27, pp. 606-610.)

Disadvantages of simple dry-plate rectifiers (variations with current, voltage, and temperature: ageing: unsuitability for small voltages and therefore for null methods): two can be used in a bridge circuit to form a phase-sensitive rectifier, but they must be carefully matched. Advantages and requirements of the mechanical rectifier.* The rotating rectifier (Pfaffenberger: using a synchronous-clock movement). The vibrating-reed rectifier, simple type and type with adjustable contact-pause (Froböse), using a rotating-field device working off the mains: the excellent properties of this latter type for measuring purposes. The use of the mechanical rectifier for measuring voltage, current, and power: for point-by-point curve plotting: for the measurement of capacitance and of iron losses.

3465. A NEW TYPE OF DIRECT-CURRENT AMPLIFIER [for Measuring & Control Purposes].—Eberhardt, Nüsslein, & Rupp. (See 3588.)
3466. CIRCULAR-CHART RECORDING POTENTIOMETER WITHOUT GALVANOMETER [primarily for Temperature Recording].—Brown Instrument. (*Review Scient. Instr.*, Aug. 1941, Vol. 12, No. 8, pp. 413-414.)
3467. ELIMINATION OF THE EFFECT OF THE COLD ENDS IN THERMOELECTRIC TEMPERATURE MEASUREMENT [Various Methods, including Use of OKL ("without-Cold-Soldered-Junction") Elements].—A. Kuntze. (*Zeit-schr. V.D.I.*, 16th Aug. 1941, Vol. 85, No. 33, pp. 703-705.)

3468. A VACUUM-TUBE CURRENT INTEGRATOR [for Currents of about 0.04-0.9 μ A].—G. J. Perlow. (*Review Scient. Instr.*, Aug. 1941, Vol. 12, No. 8, pp. 412-413.) Cf. Watt, 3119 of November.
3469. MEASUREMENT OF PRE-BREAKDOWN CURRENTS IN DIELECTRICS WITH A CATHODE-RAY TUBE [Currents around 10^{-8} A: Equipment & Results].—H. H. Race. (*Gen. Elec. Review*, Aug. 1941, Vol. 44, No. 8, pp. 445-450.)
3470. PEAK-FACTOR MEASURING BRIDGE FOR HIGH VOLTAGES.—H. Warnecke. (*Arch. f. Elektrot.*, 15th April 1941, Vol. 35, No. 4, pp. 229-244.)
3471. ELECTROLYTIC CONDENSER TEST SET: A SIMPLE CAPACITY-MEASURING BRIDGE: TESTING FOR LEAKAGE.—F. A. Boyer. (*Wireless World*, Oct. 1941, Vol. 47, No. 10, pp. 254-255.)
3472. STANDARDISED CONDENSERS: MORE EFFICIENT PRODUCTION [Note on War Emergency Specification No. BS 271-1941].—(*Wireless World*, Oct. 1941, Vol. 47, No. 10, p. 251.)
3473. A.S.T.M. STANDARDS IN THE RADIO INDUSTRY [List of Specifications & Test Methods covering General Purpose Materials].—(*ASTM Bulletin*, Aug. 1941, No. 111, p. 60.)

SUBSIDIARY APPARATUS AND MATERIALS

3474. CALCULATING CONDUCTANCE [due to Electron Beam traversing a Transverse Alternating Field: Correction], and THE DEFLECTING CONDENSER.—Rodda: Benham. (See 3340.)
3475. ADDITION TO MY PAPER "ON THE APPLICATION OF ELECTRIC AND MAGNETIC FIELDS IN ELECTRON-OPTICS."—Brüche. (*T.F.T.*, Dec. 1940, Vol. 29, No. 12, p. 373.) See 2665 of 1940.
3476. THE FIELDS OF ELECTRIC SYSTEM WITH NARROW SLITS ACTING AS CYLINDRICAL ELECTRON LENSES.—Strashkevich. (*Journ. of Tech. Phys.* [in Russian], No. 2, Vol. 10, 1940, pp. 91-111.)

A detailed theoretical investigation of the electric fields formed at the slits in charged conductors, which can be used as electron lenses. A brief survey of the literature on the subject is given, and systems consisting of one or several parallel planes and of one or several coaxial cylinders are considered. The distribution of potential in the field of such system is discussed and their electron-optical properties are examined. Methods are indicated for determining the trajectory of the electron beam. A theoretical proof is given of the experimental formula (2) due to Davisson and Calbick (see 1933 Abstracts, p. 224) for determining the focal length in the case of a plane with a single slit, and formula (28) and (29) are derived for calculating the focal length of a "weak" lens. Certain necessary corrections in the existing theory of the lenses are pointed out.

3477. THE CALCULATION OF THE MAGNETIC FIELD OF A DIHEDRAL ANGLE.—Gubanov. (*Journ. of Tech. Phys.* (in Russian), No. 5, Vol. 10, 1940, pp. 376-394.)
The boundary between two media of magnetic permeability μ_1 and μ_2 is in the shape of a dihedral angle (Fig. 1): a current flows along a conductor N parallel to the edge of the angle, and it is required to determine the magnetic field at any point P of the space. An exact solution is given.
3478. INDUCTANCE-LINEARISED TIME BASE [Circuit where Charging Current returns to Initial Value just before Discharge, and remains Constant during Discharge: Theory, Experiment, & Design: Advantage of High Voltage-Utilisation Factor: useful for Special Purposes].—Williams & Fairweather. (*Wireless Engineer*, June & July 1941, Vol. 18, Nos. 213 & 214, pp. 224-231 & 271-276.) Chard's description of the operation of a similar circuit (3843 of 1937) is condemned. For a correction see August issue, No. 215, p. 312.
3479. POTENTIAL DIVIDERS AND RETARDING CABLES IN THE OSCILLOGRAPHIC RECORDING OF RAPID TRANSIENT PHENOMENA [Theoretical & Experimental Investigation of Factors influencing Accuracy of Resulting Records: Rôle of Cable Resistance is Predominant, of Dielectric Loss usually Negligible: Design of Practical Retarding Cable: etc.].—Angelini, Merega. (*Bull. Assoc. suisse des Elec.*, 18th July 1941, Vol. 32, No. 14, pp. 305-315: in French.)
3480. A PHASE-CURVE TRACER FOR TELEVISION [Phase Curve of Any Network shown on C.R.O. Screen].—Loughlin. (See 3410.)
3481. SECONDARY EMISSION: SOME EFFECTS ON DEFLECTOR-PLATE CHARACTERISTICS OF CATHODE-RAY TUBES [Hard, Sealed, Low-Voltage Type: Experimental Investigation of Effects of Secondary Electrons returning from Screen & intercepted by Deflector Plates: of Secondary Electrons produced by Primary Electrons grazing the Plates & the Splitter Plate in Double-Beam Tubes: Interaction between X & Y Plates—"Pimple Effect": etc.].—Moss. (*Wireless Engineer*, Aug. 1941, Vol. 18, No. 215, pp. 309-312.)
3482. EFFECTS OF HEAT TREATMENT ON FIELD EMISSION FROM METALS.—Daniel. (See 3350.)
3483. THE CYLINDRICAL ELECTRON PROJECTOR TUBE IN THE STUDY OF THERMIONIC AND FIELD EMISSION.—Martin. (See 3351.)
3484. ON THE QUESTION OF THE SPACE CHARGE IN A CATHODE-RAY BEAM [and the Influence of the Hot-Cathode Temperature].—Reusse & Ripper. (*T.F.T.*, July 1940, Vol. 29, No. 7, pp. 199-201.)
Recent researches have shown that the electrical charges in a focused beam of electrons are distributed more or less according to a Gaussian curve of errors, with maximum density at the beam axis. The form of the curve is a function of the current strength in the beam and of the velocity of the carriers. Occasionally the "centre of gravity" of the charge is more or less displaced with respect to the axis. These researches (3626 of 1939 and 3366 of 1940: also Jacob, 3625 of 1939) also showed that in certain conditions the charge distribution may display inhomogeneities, which are explained on optical lines by the combined actions of the two lenses of which the focusing system generally consists.
Another important question is the influence of the cathode temperature. The theory of the focused beam shows that even if complete geometrical and electrical constancy of the focusing system is assumed, this influence must have its effect: the a in Law's expression for the distribution of charge density in the cross section of the beam (3802 of 1937) involves the absolute temperature T of the emitting surface, and Fig. 3 shows the calculated curves giving the ratio (density i at distance r from the beam axis)/(total emission) as a function of r for various temperatures. A rise from 1000° to 1250° K produces only a small change in the curve, but a rise of 2000° gives a quite different appearance to the charge distribution. Experimentally, this point has hitherto been neglected: Jacob found that a rise of 165° produced no noticeable effect, but this is only to be expected. The experiments here described, with results illustrated by the two $i \cdot r$ curves of Fig. 6 (for a final electron velocity of 4 kv), showed that at 2050° the maximum i ordinate is lower than that at 1070° , while the breadth of the curve along the r abscissa axis is greater. The surfaces enclosed by the two curves are about equal (equal total ray current). For the oxide cathodes at present used, with their limited temperature range, the effect can generally be neglected.
3485. CATHODE-RAY TUBE ELECTRODE MOUNTING: also SIMPLE ELECTRODE ASSEMBLY FOR CATHODE-RAY TUBES GIVING EASE OF ASSEMBLY AND IMPROVED RIGIDITY & ALIGNMENT: and OPERATING A CATHODE-RAY TUBE WITH EARTHED SECOND ANODE.—Anon: R.C.A. Laboratories. (*E. & Television & S.W.W.*, Jan. 1941, Vol. 14, No. 155, pp. 27 and 43; May, No. 159, p. 214: and April, No. 158, p. 150.)
3486. "10 JAHRE ELEKTRONENMIKROSKOPIE" [Book Review].—AEG Research Institute. (*Schweizer Arch. f. angew. Wiss. u. Tech.*, July 1941, Vol. 7, No. 7, p. 212.)
3487. RECENT DEVELOPMENTS IN THE ELECTRON MICROSCOPE [leading to Description of the New R.C.A. Instrument (Resolving Power from 100×10^{-7} mm to 30×10^{-7} mm) of Compact Design, with New Stabilised Power Supply].—Hillier & Vance. (*Proc. I.R.E.*, April 1941, Vol. 29, No. 4, pp. 167-176.)
3488. ELECTRON-MICROSCOPY, A NEIGHBOURING FIELD TO TELEVISION TECHNIQUE [Short Survey of Development in Instrument Design and Operating Technique].—von Ardenne. (*T.F.T.*, Dec. 1940, Vol. 29, No. 12, pp. 367-371.)

3489. THE OBJECT-CARRIER VIBRATOR, A NEW AUXILIARY FOR ELECTRON-MICROSCOPY AND MICROSCOPY [for Uniform Distribution of Particles over the Carrier-Foil].—von Ardenne. (*Kolloid-Zeitschr.*, No. 11, 1940.) Mentioned in 3488, above.
3490. A 200 KV UNIVERSAL ELECTRON-MICROSCOPE WITH OBJECT-SHADOWING DEVICE [for Living Substances].—von Ardenne. (*Zeitschr. f. Phys.*, Vol. 117, 1941, p. 657 onwards.) Quoted in von Ardenne's paper, 3595, below.
3491. PAPERS ON ELECTRON-MICROSCOPY OF LIVING SUBSTANCES AND THE PREPARATION OF SPECIAL OBJECT-CARRYING FILMS FOR SUCH PURPOSES.—von Ardenne: Hass & Kehler. (See 3595 & 3596.)
3492. NEW TECHNIQUE FOR MAKING THIN TARGETS [Thicknesses down to 10^{-6} cm, Area 10 cm^2 : backed only by Thin Cellulose-Acetate Films].—Pockman & Webster. (*Review Scient. Instr.*, Aug. 1941, Vol. 12, No. 8, pp. 389-392.)
3493. PHOTOELECTRIC CONDUCTIVITY OF ZINC-SULPHIDE/COPPER PHOSPHORS UNDER THE ACTION OF ALPHA RAYS.—Lappe. (See 3415.)
3494. A SUPERSONIC-CELL FLUOROMETER [particularly suitable for "Fast" Phosphors: Some Results].—Briggs. (*Journ. Opt. Soc. Am.*, Aug. 1941, Vol. 31, No. 8, pp. 543-549.) A summary was dealt with in 1177 of April.
3495. TANTALUM AND ITS USES [in Transmitting Valves, particularly U.H.F.: Thermionic & Secondary Emission: Balkite Rectifier: Support & Conductor for Anodes (using Its Insulating Oxide Film): Mechanical Properties: etc.].—(*Review Scient. Instr.*, July 1941, Vol. 12, No. 7, pp. 374-375.) Cf. Kobayashi & Harashima, 1894 of July.
3496. CONSTRUCTION OF GLASS BELLOWS.—Pompeo & Meyer. (*Review Scient. Instr.*, July 1941, Vol. 12, No. 7, pp. 368-369.)
3497. CEMENTS FOR GLASS INSERTS IN ELECTRICAL APPARATUS.—Paton. (*Engineering*, 26th Sept. 1941, Vol. 152, p. 245.) Summary of E.R.A. Report Ref. G/T. 131.
3498. GLASS-TO-METAL SEALS: II [especially the Properties of Fernico: "42 Alloy" (Nickel-Iron), matching Special "1075" Glass: Chrome-Iron & Iron Seals: Strength of Seals].—Hull, Burger, & Navias. (*Journ. Applied Phys.*, Sept. 1941, Vol. 12, No. 9, pp. 698-707.) For I see 1184 of 1935.
3499. HIGH-VACUUM PUMPS AND PUMPING: AN OUTLINE OF MODERN APPARATUS AND METHODS [including Vacuum Measurement].—Edwards & Company. (*E. & Television & S.W.W.*, Feb. 1941, Vol. 14, No. 156, pp. 55-59.)
3500. ON THE OUTGASSING OF X-RAY TUBES AND KENOTRONS.—Popov & Bazykina. (*Journ. of Tech. Phys.* [in Russian], No. 4, Vol. 10, 1940, pp. 323-331.)
An experimental investigation of the outgassing of metallic and glass parts of X-ray tubes and kenotrons during various stages of the manufacturing process: practical suggestions are made.
3501. THERMOELECTRIC VACUUM METER [Limitations of Usual Hot-Wire Device with Temperature estimated by Resistance-Measurement or Thermoelement: Six-Fold Increase of Effect at Low Pressures obtained by Special Arrangement].—Moll & Burger. (*Zeitschr. f. tech. Phys.*, Vol. 21, 1940, p. 199 onwards: summary in *E.T.Z.*, 5th June 1941, Vol. 62, No. 23, p. 528.)
3502. AN IONISATION GAUGE CIRCUIT [Pressures 10^{-3} to 10^{-7} mm Hg and below] WITH A "MAGIC EYE."—Parkins & Higinbotham. (*Review Scient. Instr.*, July 1941, Vol. 12, No. 7, pp. 366-367.) With "certain advantages" over Ridenour's circuit (2211 of August).
3503. THE IONIC DENSIMETER.—Michelson & Sena. (*Journ. of Tech. Phys.* [in Russian], No. 3, Vol. 10, 1940, pp. 257-262.)
A device has been developed for measuring the density of gas or vapour in such apparatus as mercury-vapour rectifiers. The device is based on the following principle. If a grid D and a collector P parallel to it (Fig. 1) are placed in the gas or vapour whose density δ it is desired to measure, and an ion stream is passed through the grid, then the relationship between the ion current flowing onto P when this is at a negative potential with respect to D and that flowing when P is at a positive potential will be determined by a number of factors of which δ is one. This relationship is represented by formula (1), from which formula (2) is derived for determining δ . The accuracy of the method is discussed and it is shown that satisfactory results are obtained when the range of measurements (in the case of mercury vapour) extends over densities corresponding to pressures from 10^{-4} - 10^{-3} mm to 10^{-2} - 10^{-1} mm.
3504. ON STARTING AN ELECTRIC SPARK BY INTENSE IONISATION OF THE SPARKING SPACE [Use as Electric Relay, etc.].—Shimiza & Hirata. (See 3587.)
3505. THE BREAKDOWN OF COMPRESSED GASES AT A HIGH PRESSURE AND WITH SMALL SEPARATION BETWEEN THE ELECTRODES.—Blokhintsev, Vul, & Parnas. (*Journ. of Tech. Phys.* [in Russian], No. 5, Vol. 10, 1940, pp. 357-368.)
The breakdown voltage U of nitrogen was measured under pressures up to 90 kg/cm^2 . With a distance of 0.3 mm between the electrodes, values of U of the order of $1.5 \times 10^6\text{ v/cm}$ were obtained. The effect of the cathode material on U was also investigated, and methods are indicated for calculating U .
3506. MEASUREMENT OF PRE-BREAKDOWN CURRENTS IN DIELECTRICS WITH A CATHODE-RAY TUBE.—Race. (See 3469.)

3507. INVESTIGATION OF THE RELAXATION TIME IN MIXTURES OF POLAR AND NON-POLAR LIQUIDS [Nitrobenzol, and Chlorbenzol, in Benzol: Measurements at 13.65 Mc/s: Discussion of Results on Basis of Kronig's Unified Theory of Acoustic, Electric, & Magnetic Relaxation Phenomena].—Spengler. (*Physik. Zeitschr.*, 15th June, 1941, Vol. 42, No. 7/8, pp. 134-143.) For Kronig's work see 2573 of 1938 and 1715 of 1939.
3508. CONDUCTION OF ELECTRICITY BY DIELECTRIC LIQUIDS AT HIGH FIELD STRENGTHS.—Plumley. (*Phys. Review*, 15th Jan. 1941, Vol. 59, No. 2, pp. 200-207.) See 1501 of May, and cf. Dornte, 2541 of September.
3509. DISCHARGES IN INSULATION UNDER ALTERNATING-CURRENT STRESSES [Theoretical & Experimental Study of Internal Discharges in Insulation & in Model Circuits].—Austen & Whitehead. (*Journ. I.E.E.*, March 1941, Vol. 88, Part III, No. 1, pp. 18-22.)
3510. CORRELATION BETWEEN ELASTIC MODULI AND VISCOSITY OF LIQUIDS AND PLASTICS [Theory & Applications].—Gemant. (*Journ. Applied Phys.*, Sept. 1941, Vol. 12, No. 9, pp. 680-685.) Prompted by the experimental results of Matteson & Vogt and Davies & Busse (3511 & 3512, below).
3511. PAPER ON THE VELOCITY OF ACOUSTICAL WAVES IN PETROLEUM FRACTIONS [found to be Function of Density & Viscosity].—Matteson & Vogt. (*Journ. Applied Phys.*, Vol. 11, 1940, p. 658 onwards.) Referred to in Gemant's paper, 3510, above.
3512. DIELECTRIC PROPERTIES OF PLASTICISED POLYVINYL CHLORIDE.—Davies & Busse. (*American Chemical Society* paper, referred to in Gemant's paper, 3510, above.)
3513. CONTRIBUTION TO THE THEORY OF ANOMALOUS DISPERSION AND DIELECTRIC LOSS IN SOLID BODIES [Polyvinyl Products, etc.].—Holzmüller. (*Physik. Zeitschr.*, 15th Nov. 1940, Vol. 41, No. 21/22, pp. 499-508.)
For practical work by the same writer see 2481 of September and back reference. Author's summary:—"The occurrence of dielectric loss in polar solids is traced to alteration of the equilibrium setting of the polar groups in the molecule to the individual minima of potential energy. It is shown that in the electric field the number of dipole moments at levels of higher potential energy is larger than when the field is removed. Since the new setting of the dipole moment past an energy threshold can only occur as the result of the combined action of strong heat pulses and electric field, this setting is dependent on time. By the introduction of one or more relaxation times the observed dependence of the dielectric constants and loss angles on frequency and temperature is explained. It is shown how the quantities important for the determination of the internal forces of cohesion in the molecule can be calculated from measurements of dielectric constant and $\tan \delta$.
- "Since at present the calculations are limited to the establishment of equilibrium in the orientation of dipoles, and its dependence on the forces present, nothing can yet be said about the connection between viscosity and dielectric loss. An investigation in view, on the influence of intermolecular forces in movements of translation, promises to relate viscosity and ionic conductivity to place-interchange processes in solids, and to establish a connection between these different phenomena." Experimental confirmation of the theoretical work dealt with above has already been carried out and will be reported soon.
3514. POLYSTYRENE AND THE ELECTRICAL INDUSTRY: A SHORT REVIEW OF MODERN DEVELOPMENTS [particularly "Distrene" Brand].—Yarsley. (*Electrician*, 10th Oct. 1941, Vol. 127, pp. 203-204.)
3515. ELECTRICAL PARTS FROM POLYSTYRENE.—Plax Corporation. (*Review Scient. Instr.*, Aug. 1941, Vol. 12, No. 8, p. 417.)
3516. DIELECTRIC CONSTANTS AND LOSS FACTORS OF TROLIUL, ETC., FOR 14 CM WAVES.—Borgnis. (See 3435.)
3517. THE ANNEALING OF PHOTOELASTIC BAKELITE AND THE RESULTING EFFECT ON ITS PHYSICAL AND OPTICAL PROPERTIES.—Lee & Goldstein. (*Journ. Applied Phys.*, Aug. 1941, Vol. 12, No. 8, pp. 623-624: summary only.)
3518. CERAMICS IN VALVE CONSTRUCTION [particularly Ceramic Seals for U.H.F. Valves].—Howard. (See 3344.)
3519. LOW-LOSS CERAMICS FOR RADIO-FREQUENCY USE [Development, Manufacture, & Use: including Construction of Trimmer Condensers, High-Stability Inductances, etc.].—Britton. (*E. & Television & S.W.W.*, March & April, 1941, Vol. 14, Nos. 157 & 158, pp. 102-105 & 158-162 [with Corrections], and *Electronic Engineering* [new form of above], July 1941, Vol. 14, No. 161, pp. 301-303, 318.) From Steatite & Porcelain Products, Ltd.
3520. THE ELECTRICAL PROPERTIES OF HIGH-FREQUENCY CERAMICS.—Rosenthal. (*Electronic Engineering* [formerly *E. & Television & S.W.W.*], Sept. & Oct. 1941, Vol. 14, Nos. 163 & 164, pp. 388-390 & 438-441.) "Much of the data in this article has not been hitherto published."
3521. INVESTIGATIONS ON PHENOPLASTICS: PART 3—THE DIELECTRIC PROPERTIES.—Stäger & others. (*Schweizer Arch. f. angew. Wiss. u. Tech.*, July 1941, Vol. 7, No. 7, pp. 201-208.) Final part of the paper mentioned in 3144 of November: the previous chapters dealt with the mechanical properties.
3522. DIFFUSION CALCULATIONS: INTERRELATION BETWEEN TWO SOLUTIONS OF THE FOURIER EQUATION [primarily in connection with Plasticiser Losses].—Liebhafsky. (See 3552.)

3523. LAMINATED IMPREGNATED PLASTICS [including "Permalin" & "Pyram"].—Yarsley. (*Electrician*, 12th Sept. 1941, Vol. 127, p. 152.) Also "Jicwood," a special laminated wood "of extraordinary strength yet lighter by bulk than metal."
3524. THE ELECTRICAL BREAKDOWN OF ROCHELLE SALT.—Gorelik. (See 3375.)
3525. MIDGET TUBULAR OIL-FILLED CONDENSERS [0.006–0.5 μ F: up to 2000 V].—Aerovox Corporation. (*Review Scient. Instr.*, Aug. 1941, Vol. 12, No. 8, p. 416.)
3526. MECHANICAL RECTIFIERS AND THEIR USE IN MEASURING TECHNIQUE.—Peters. (See 3464.)
3527. THE INFLUENCE OF OXYGEN CONCENTRATION IN OXIDISING AND TEMPERING STOVES ON THE DIRECT AND REVERSE CURRENTS OF CUPROUS-OXIDE RECTIFIERS.—Tuchkevich. (*Journ. of Tech. Phys.* [in Russian], No. 9, Vol. 10, 1940, pp. 747–751.)
3528. HALL-EFFECT MEASUREMENTS ON SELENIUM.—Eckart & Kittel. (*Naturwiss.*, 13th June 1941, Vol. 29, No. 24/25, p. 371.)
- Selenium is generally assumed to be an oxidation ("deficiency") semiconductor because in a selenium rectifier the pass direction is the same as in a cuprous-oxide rectifier, but hitherto no quantitative results have been reported to confirm this character and to give data on the mobility of the deficiency electrons in selenium. Now, however, the writers have succeeded in demonstrating an anomalous (positive) Hall effect in a specially highly conductive sample. The measurements yield a value for the mobility of the deficiency electrons (Hall constant \times conductivity) of about 1 cm²/sec./volt/cm.
3529. A METHOD FOR CALCULATING THE EQUIVALENT NOISE VOLTAGE AND FOR DESIGNING THE SMOOTHING CHOKE FOR AN AUTOMATIC GRID-CONTROLLED MERCURY RECTIFIER OPERATED WITH A FLOATING BATTERY.—Gubanov. (*Elektrosvyaz* [in Russian], No. 1, 1941, pp. 47–54.)
- An analysis is given of the harmonic content of the rectified voltage as determined by the angle ψ at which the arc strikes (Fig. 1). The maximum value of ψ for a given mains-voltage variation is found, and methods are indicated for calculating the equivalent noise voltage and for designing the smoothing choke. Experiments have confirmed the validity of the methods proposed.
3530. IMPROVEMENTS IN B-BATTERY PORTABILITY [Package Size per Unit of Capacity reduced by about 50%: Design of "Minimax" Types].—French: Ever-Ready Company. (*Proc. I.R.E.*, June 1941, Vol. 29, No. 6, pp. 299–303.) See also 1062 of April.
3531. THE PRODUCTION OF THIN METAL WIRES.—Makovski. (*Journ. of Tech. Phys.* [in Russian], No. 4, Vol. 10, 1940, pp. 342–343.)

A small piece of metal is placed inside a glass tube which is then heated (Fig. 1) and extended to

obtain a wire of the desired thickness. Wires down to 0.001 mm diam. were thus obtained, even from brittle metals.

3532. "ELECTROLYTISCHE WANDERUNG IN FLÜSSIGEN UND FESTEN METALLEN" [Electrolytic Migration in Liquid & Solid Metals: Book Review].—Schwarz. (*Physik. Zeitschr.*, March 1941, Vol. 42, No. 4/5, p. 81.)
3533. MODERN MATERIALS IN TELECOMMUNICATIONS: PART IV—MAGNETIC MATERIALS: PART V—METALLIC CONDUCTORS.—Radley & others. (*P.O. Elec. Eng. Journ.*, April & July 1941, Vol. 34, Parts 1 & 2, pp. 19–25 & 72–78.) For previous parts see 1210/11 of April.
3534. LOAD CURRENTS IN TRANSFORMERS WITH SEVERAL SECONDARY WINDINGS.—Wolf. (See 3284.)
3535. MEASUREMENT OF IRON CORES AT RADIO FREQUENCIES.—Foster & Newlon. (See 3462.)
3536. FERROCART [Complete Disintegration of Sample Core supplied in 1933 (Schneider, 1933 Abstracts, p. 403): Enquiry for Other Experiences with This Material].—G.V.O.H. (*Wireless Engineer*, Sept. 1941, Vol. 18, No. 216, p. 352.)
3537. THE MANUFACTURE AND PROPERTIES OF COMPRESSED-POWDER PERMANENT MAGNETS.—Dehler. (*E.T.Z.*, 3rd July 1941, Vol. 62, No. 27, pp. 601–606.)

The writer begins with information about the improved permanent-magnet steels developed during the past ten years, and then discusses their limitations, such as the tendency to form cracks under severe vibration, lack of homogeneity, and general intractability (for any but the simplest designs). He then reviews briefly the recent promising development of sintered materials, both the Japanese "oxide magnets" and the aluminium-nickel-iron materials (*e.g.* Ritzau, 2878 of October), with a possible admixture of cobalt or copper: the objection is their expense. The use of powder contained in permanent containers of the desired shape has been tried, but has its defects: for instance the container is inclined to increase the air-gap undesirably.

The rest of the paper describes the preparation of compressed-powder magnets with synthetic-resin binders. Such materials are produced under the name of Tromalit (German Patent 656 966, Baermann). The circular-sectioned coaxial magnet shown in Fig. 11, with diameter 12 mm and air-gap 1.5 mm, gave a max. gap flux density of 2260 gauss when made of cast Oerstit and of 1720 gauss when made of the powder material: this represents a drop of nearly 25% for the latter, but the difference would decrease with increase of air-gap or with decrease in the size of the core, and in many cases would be eliminated altogether by the possibilities offered by the powder material of special shapes unattainable with the cast material. The saving in labour is very great. The paper includes a number of patent and literature references, some of the latter being to metallurgical journals not dealt with in these Abstracts.

STATIONS, DESIGN AND OPERATION

3538. OBSERVATIONS OF FREQUENCY-MODULATION PROPAGATION ON 26 MEGACYCLES.—Crosby. (See 3219.)
3539. RADIO TELEPHONE SERVICE IN CHESAPEAKE BAY, and RADIO EQUIPMENT FOR THE CRISFIELD PROJECTS [Ultra-Short-Wave Link between Islands & Mainland].—Taylor : Bailey. (*Bell Lab. Record*, Aug. 1941, Vol. 19, No. 12, pp. 358-362 : pp. 363-366.)
3540. AUTOMATIC RELAY STATIONS TO INCREASE RANGE OF TRANSMITTERS FOR FOREST FIRE-FIGHTING PARACHUTISTS.—(*Sci. News Letter*, 21st June 1941, Vol. 39, No. 25, p. 398.)
3541. RADIO EQUIPMENT FOR AN UNMANNED WEATHER STATION.—Pear. (*Sci. Abstracts*, Sec. B, Aug. 1941, Vol. 44, No. 524, p. 164.) Cf. Diamond & Hinman, 4463 of 1940.
3542. SOME CONSIDERATIONS OF FIGHTER-AIRCRAFT RADIO.—Cannell. (*E. & Television & S-W.W.*, May 1941, Vol. 14, No. 159, p. 203.)
3543. A FIVE-BAND RECEIVER FOR AUTOMOBILE SERVICE [and the Suggestion that Short Waves (in International S.W. Band) should be used for the Many Sections of U.S.A. which are without Adequate Daylight Broadcasting Service].—Little & Rettenmeyer. (*Proc. I.R.E.*, April 1941, Vol. 29, No. 4, pp. 151-166.)
3544. WIRE-BROADCASTING MEASURING TECHNIQUE [developed by German P.O. & Industry : Selective Measurement of Carrier Voltages : Monitoring of Quality (Modulation Factor, Frequency Characteristic, Contrast, Distortion Factor, Non-Linear Cross-Talk, Interference) : Line Attenuation, Input Impedance, Characteristic Impedance : Test Truck for Special Measurements].—Eisele. (*E.T.Z.*, 5th June 1941, Vol. 62, No. 23, pp. 513-519.)
3545. THE HIGH-FREQUENCY DISTORTIONS IN WIRE BROADCASTING [Non-Linear Distortion More Serious than in A.F. Technique : Amplitude Distortion fundamentally Less Serious, but actually Important owing to Use of Existing Telephone System : Its Production (& Counter-Measures)—Attenuation Distortion, Matching Distortion, Terminal Distortion, Cross-Over Distortion on Overhead Lines].—Klein. (*T.F.T.*, Nov. 1940, Vol. 29, No. 11, pp. 331-334.)
3546. MATCHING PROBLEMS IN WIRE-BROADCASTING LINE MATERIAL [Trunk Lines, Subscriber's Line, Special H.F. Connections, etc.].—Klein. (*T.F.T.*, Dec. 1940, Vol. 29, No. 12, pp. 363-367.)
3547. FUTURE OF EUROPEAN BROADCASTING : SOME TECHNICAL ASPECTS OF CHANNEL ALLOCATION.—Brailard. (*Wireless World*, Oct. 1941, Vol. 47, No. 10, pp. 252-253.) Discussion of Brailard's paper in *Journ. des Télécommunications*.
3548. THE TERMINAL EQUIPMENT OF THE BERNE NEW YORK WIRELESS TELEPHONE LINK.—Jacot. (*E.T.Z.*, 19th June 1941, Vol. 62, No. 25, pp. 579-580 : summary only.)
3549. MEDIUM-FREQUENCY TELEGRAPHY SYSTEM (MFS) ON OPEN LINES (Frequencies 3-8 kc/s, giving up to Six Additional Channels, in Gap between L.F. and Carrier-Frequency Telephony Channels).—Füllung & Pretzsch. (*T.F.T.*, Dec. 1940, Vol. 29, No. 12, pp. 345-353.)

MISCELLANEOUS

3550. A SIMPLE INTRODUCTION TO THE USE OF STATISTICS IN TELECOMMUNICATIONS ENGINEERING : Part I—SAMPLES OBEYING THE NORMAL PROBABILITY LAW : PART II—ANALYSIS OF SMALL SAMPLES [and the Nomographic Use of Fisher's "t" Test].—Doust & Josephs. (*P.O. Elec. Eng. Journ.*, April & July 1941, Vol. 34, Parts 1 & 2, pp. 36-41 & 79-84.)
3551. INDUSTRIAL MATHEMATICS [Mathematical Specialists in Industry : Present & Future Utilisation of Mathematics in Communications, Electrical Manufacturing, & Other Industries].—Fry. (*Bell S. Tech. Journ.*, July 1941, Vol. 20, No. 3, pp. 255-292.)
3552. DIFFUSION CALCULATIONS : INTERRELATION BETWEEN TWO SOLUTIONS OF THE FOURIER EQUATION [Sine-Series Solution (Slab with Sealed Periphery) & Error-Function Solution (for Semi-Infinite Body) : leading to Simplification in Calculation of Diffusion Constants].—Liebhafsky. (*Journ. Applied Phys.*, Sept. 1941, Vol. 12, No. 9, pp. 707-710.)
Primarily for the evaluation of measured losses of plasticisers from polyvinyl-chloride plastics, but applicable to other cases of flow governed by the fundamental Fourier equation $\partial c/\partial t = D\partial^2 c/\partial x^2$.
3553. AUTOMATIC INTEGRATION OF LINEAR SECOND-ORDER DIFFERENTIAL EQUATIONS BY MEANS OF PUNCHED-CARD MACHINES.—Feinstein & Schwarzschild. (*Review Scient. Instr.*, Aug. 1941, Vol. 12, No. 8, pp. 405-408.)
3554. THE SOLUTION OF A.C. CIRCUIT PROBLEMS [Method depending chiefly on Matrix Multiplication (simply performed by Calculating Machine) and avoiding Complex Numbers].—Pipes. (*Journ. Applied Phys.*, Sept. 1941, Vol. 12, No. 9, pp. 685-691.)
3555. "FOUR-FIGURE TABLES WITH MATHEMATICAL FORMULAE" [Book Review].—Plummer. (*Phil. Mag.*, June 1941, Vol. 31, No. 209, p. 510.) The collection of formulae is expanded from that originally prepared by C. S. Wright.
3556. "A BIBLIOGRAPHY OF ORTHOGONAL POLYNOMIALS" [Book Review].—Shohat & others. (*Phil. Mag.*, June 1941, Vol. 31, No. 209, p. 507.)

3557. "MECHANICAL VIBRATIONS: SECOND EDITION" [Book Review].—Den Hartog. (*Engineering*, 26th Sept. 1941, Vol. 152, pp. 243-244.)
3558. CYCLES PER SECOND [Editorial on Discussion dealt with in 1813 of June].—G.W.O.H. (*Wireless Engineer*, May 1941, Vol. 18, No. 212, p. 179.)
3559. CIRCUIT-DESIGNATION METHOD [New System].—Caldwell. (See 3288.)
3560. NEW-STYLE JAMMING: IMAGINATION IN WIRELESS WARFARE [Editorial on the Deutschlandsender "Voice," etc.].—(*Wireless World*, Oct. 1941, Vol. 47, No. 10, p. 247.) Development of 3161 of November.
3561. RAID WARNING BY RADIO [RCA Alert Receiver automatically Switched-On by Special Inaudible Signal].—(*Sci. News Letter*, 16th Aug. 1941, Vol. 40, No. 7, p. 99; for comments see *Wireless World*, Nov. 1941, p. 284.)
3562. CENTRALISED REMOTE CONTROL [for A.R.P. Work, etc.]: DETAILS OF A NEW RIPPLE-CONTROL (LOW-TENSION SYSTEM) EMPLOYING MAINS WIRING.—General Electric. (*E. & Television & S-W.W.*, April 1941, Vol. 14, No. 158, pp. 165-167.) Cf. 260 of January.
3563. THE DETECTION OF INCENDIARY BOMBS BY ELECTRICAL, ELECTRONIC, THERMOSTATIC, AND RADIO-ACTIVE DEVICES.—I.E.E. Committee. (*E. & Television & S-W.W.*, May 1941, Vol. 14, No. 159, pp. 198-200 and 238: abstract.) Cf. 3198 of November.
3564. THE "SUPPLY" OF PHYSICISTS [and the National Roster of Specialised "Personnel"].—(*Journ. Applied Phys.*, Sept. 1941, Vol. 12, No. 9, pp. 655-657.)
3565. TECHNICAL EDUCATION IN NEW SOUTH WALES.—Riddell. (*Journ. Inst. Eng. Australia*, June 1941, Vol. 13, No. 6, pp. 139-145.)
3566. PRESENT-DAY SCIENCE AND TECHNOLOGY IN THE U.S.S.R.—Bernal. (*Nature*, 27th Sept. 1941, Vol. 148, pp. 360-361.)
3567. THE BRITISH ASSOCIATION: CONTRIBUTION OF SCIENCE TO WORLD ORDER: INTERNATIONAL CONFERENCE IN LONDON.—(*Electrician*, 3rd Oct. 1941, Vol. 127, p. 189.) See also *Nature*, 4th & 11th Oct. 1941, pp. 388-393 & 424-427: also 18th & 25th October.
3568. A SCIENTIFIC PRESS BUREAU [Plea for].—Johnston. (*Nature*, 27th Sept. 1941, Vol. 148, p. 375.) See also Evans, *ibid.*, 11th Oct., p. 434.
3569. SUMMER CONVENTION, JUNE 23RD TO 25TH, 1941, AT DETROIT: SUMMARIES OF PAPERS, and ADDRESS OF PRESIDENT TERMAN AT THE SUMMER CONVENTION BANQUET.—(*Proc. I.R.E.*, April 1941, Vol. 29, No. 4, pp. 220-229; July, No. 7, pp. 400-408.)
3570. REGIONAL DIRECTORS PROPOSED IN NEW I.R.E. CONSTITUTIONAL AMENDMENT [with Discussion].—Terman. (*Proc. I.R.E.*, July 1941, Vol. 29, No. 7, pp. 408-411.)
3571. RADIO PROGRESS DURING 1940 [Electronics, Transmitters (& Aerials), Receivers, Frequency Modulation, Television & Facsimile, Electroacoustics, Propagation].—(*Proc. I.R.E.*, March 1941, Vol. 29, No. 3, pp. 89-103.)
3572. REVIEW OF PROGRESS IN ELECTRONICS: I.—INTRODUCTION AND GENERAL BIBLIOGRAPHY.—Windred. (*E. & Television & S-W.W.*, April 1941, Vol. 14, No. 158, pp. 151-152 and 154.) Beginning of a series.
3573. A THYRATRON-CONTROLLED ANNEALING FURNACE.—Tarnopol. (*Review Scient. Instr.*, July 1941, Vol. 12, No. 7, pp. 367-368.) Control better than $\pm 0.03^\circ\text{C}$ (at 1000°C) for any required long period.
3574. AN INTEGRATOR FOR SMALL CURRENTS [Neon Tube, Amplifier, & Mechanical Counter Combination].—Watt. (See 3119 of November.) See also 3468, above.
3575. THE DEAD-TIME OF A GEIGER COUNTER [Direct Measurements: about 10^{-4} Sec. for 1"-Diam. Counter], and CIRCUIT INDEPENDENCE OF CHARGE IN FAST COUNTER PULSES.—Stever. (*Phys. Review*, 15th Jan. 1941, Vol. 59, No. 2, p. 219; 15th July 1941, Vol. 60, No. 2, p. 160: summaries only.)
3576. TIME LAGS IN GEIGER-MÜLLER COUNTER DISCHARGES.—Montgomery & Montgomery. (*Phys. Review*, 15th June 1941, Vol. 59, No. 12, p. 1045.)
3577. THE HARMONIC ANALYSIS OF GEIGER-COUNTER PULSES.—Shankland & Blythe. (*Phys. Review*, 1st July 1941, Vol. 60, No. 1, pp. 64-65: summary only.)
3578. ELECTRONIC CUP-ANEMOMETER [Rotation of Perforated Disc interrupts Oscillator].—Gurley. (*Review Scient. Instr.*, July 1941, Vol. 12, No. 7, p. 373.) Cf. Goncharski, 2005 of July.
3579. EPICYCLIC GEAR TRAINS FOR DIFFICULT RATIOS.—Boys. (*Journ. of Scient. Instr.*, Oct. 1941, Vol. 18, No. 10, pp. 195-200.) Complementary to Clay's paper, 1990 of July.
3580. QUARTZ INDICATOR WITH HIGH NATURAL FREQUENCY [for I.C. Engines, etc.: Ordinary Quartz Pick-Up unsuitable for Knock Investigations: Development of Type with Natural Frequency as high as 100 kc/s].—Schmidt. (*Zeitschr. V.D.I.*, 19th July 1941, Vol. 85, No. 29, p. 644: summary only.) See also 2810 of 1940.
3581. MEASUREMENT OF THE NATURAL FREQUENCY OF PIEZOELECTRIC PRESSURE-MEASURING DEVICES [and the Advantages of the Steel-Ball Impact Method].—Gohlke. (*Zeitschr. f. Instr.-kunde*, June 1941, Vol. 61, No. 6, pp. 197-198: summary only.)
3582. THEORY AND APPLICATION OF RESISTANCE TUNING [Special Suitability of Transitron Oscillator: Applications to Industrial (Temperature, Pressure, Humidity, etc.) Measurements].—Brunetti & Weiss. (See 3253.)

3583. THE MEASUREMENT OF VARIABLE STRESSES BY A STRING METHOD.—Sobolev. (*Journ. of Tech. Phys.* [in Russian], No. 4, Vol. 10, 1940, pp. 309-315.)

A wire is stretched between two points on the object under investigation and excited into oscillations by two electromagnets spaced apart along the wire and fed respectively from the input and output of a 3-valve amplifier (Fig. 4). The resulting oscillations are frequency-modulated by the periodic movement of the supports. The output of the amplifier is used to pull a second oscillator into synchronism. The coupling circuit will then contain the modulating frequency, *i.e.* the oscillation frequency of the object, which is rectified and recorded on sensitised paper.

3584. INVESTIGATIONS ON ELECTRODYNAMIC TESTING [of the Mechanical Strength of Conductors subject to Short-Circuit Currents, etc.: Tests with Square-Wave Pulses, & Detection of Movement by Capacity-Change Method].—Aebi. (*Schweizer Arch. f. angew. Wiss. u. Tech.*, July 1941, Vol. 7, No. 7, pp. 185-195.)
3585. VELOCITY MEASUREMENT OF TRANSIENT MECHANICAL MOTIONS [of Cam Mechanisms, Triggers, etc.: using a Mirror Oscillograph].—Keilien. (*Journ. Applied Phys.*, Aug. 1941, Vol. 12, No. 8, pp. 634-637.)
3586. EDDY-CURRENT INDUCTION APPLIED TO THE DETERMINATION OF ACCELERATIONS [and Possible Applications of the New Principle, including to Motor Speed Control].—Forbes. (*Review Scient. Instr.*, Aug. 1941, Vol. 12, No. 8, pp. 398-401.)
3587. ON STARTING AN ELECTRIC SPARK BY INTENSE IONISATION OF THE SPARKING SPACE [One Electrode hollowed, with Thin Metal Window and High-Vacuum Cathode-Ray (Triode) Generator: Critical Potential reduced by 30%, Spark Time Lag less than 10^{-7} Sec.: Use as Electric Relay, Light Source for Instantaneous Photography, Chronograph for Short Time Intervals].—Shimizu & Hirata. (*Journ. Roy. Aeron. Soc.*, Oct. 1941, Vol. 45, No. 370, pp. 346-347: abstract only.)
3588. A NEW TYPE OF DIRECT-CURRENT AMPLIFIER [for Measuring Purposes, Supervision & Control of Processes, etc.].—Eberhardt, Nüsslein, & Rupp. (*E.T.Z.*, 29th May, 1941, Vol. 62, No. 22, pp. 493-497.)

Authors' summary:—"After a short survey of the previous development of d.c. amplifiers for measuring purposes, culminating in the photocell-compensator [Gilbert's "photoelectric potentiometer," 1651 of 1936], fundamental considerations on opposed-coupling d.c. amplifiers are discussed.

"A practically useful d.c. amplifier for process measurements, possessing a constant amplification in face of supply-voltage fluctuations and the ageing of valves, and in addition a constant zero point, can be developed by the following combination:—transformation of the d.c. voltage under measurement, as it enters the amplifier, into an alternating voltage: amplification of this, followed by rectifica-

tion by a phase-sensitive rectifier: compensation of the input voltage by opposed coupling of the output voltage [theoretical scheme Fig. 1]. By special design of the opposed-coupling channel [insertion of a suitable RC element], the effect of an 'elastic lead-back' can be obtained which will reduce the response time of the indicating or controlling instrument connected to the output terminals. The employment of non-linear elements in the opposed-coupling channel gives the amplifier a definite non-linear relation between input and output values, so that the characteristic of a non-linear pick-up device or receiver can be compensated. . . ." The elimination of a sensitive control-galvanometer renders the apparatus insensitive to vibrations (in railway trains, etc.) and the circuit enables it to stand practically any overload.

3589. REGULATING METHODS IN CONTROLLABLE ELECTRICAL SYSTEMS AND THE CRITERIA FOR THEIR STABILITY.—Artus. (*See* 3256.)
3590. GAS-FILLED TRIODES AND THEIR PRACTICAL USE [in Laboratory & in Industry].—Windred. (*See* 3359.)
3591. MAGNETIC METHODS USED FOR TESTING INDUSTRIAL GOODS [Survey].—Grigorov. (*Journ. of Tech. Phys.* [in Russian], No. 6, Vol. 10, 1940, pp. 441-458.)
3592. ULTRASONICS [with Particular Attention to Metallurgical Applications].—(*See* 3079 of November.)
3593. DETECTION AND EXAMINATION OF THE PROTECTING PASSIVE OXIDE LAYERS FORMED ON IRON, WITH THE HELP OF THE ELECTRON SCANNER [which brings out the Varying Secondary Emission].—Knoll. (*Physik. Zeitschr.*, 15th June 1941, Vol. 42, No. 7/8, pp. 120-122 and Plate.) *See* 4111 of 1939.
3594. SURFACE STUDIES WITH THE ELECTRON MICROSCOPE [of Standard "Transmission" Type, by preparing Suitable Replicas: Special Techniques].—Zworykin & Ramberg. (*Journ. Applied Phys.*, Sept. 1941, Vol. 12, No. 9, pp. 692-695.) Pending, perhaps, the full development of the electron-probe scanning method.
3595. ELECTRON-MICROSCOPY OF LIVING SUBSTANCES, and THE GERMINATION OF SPORES OF *Bacillus Vulgatus* AFTER PREVIOUS OBSERVATION IN THE 200 kV UNIVERSAL ELECTRON-MICROSCOPE.—von Ardenne: von Ardenne & Friedrich-Freksa. (*Naturwiss.*, 29th Aug. 1941, Vol. 29, No. 35, pp. 521-523: pp. 523-528.)

The conclusions reached in the writer's paper (4108 of 1939) on the possibility of such a technique have been applied to the design of the special Universal electron-microscope with "object-shadowing" device (3490, above). It was then found that the advantages of the recommended increase in accelerating potential had been underestimated, since it not only decreased the number of electrons necessary for blackening the photographic plate but also diminished the sensitivity of the living material to damage by the electrons; it is estimated that the "loading conditions" of

the living substance improve with the 2.5th power of the accelerating potential, so that the change from the usual 60 kv to 200 kv improved these conditions in the proportion of about 1:20. Further, the increased potential rendered the object-carrier (Hass & Kehler's aluminium-oxide foil—3596, below) completely transparent, so that the safety factor of 10 allowing for the attenuation due to the carrier could be omitted, thus improving the ratio to about 1:200 compared with the original estimate. These facts, combined with the "object-shadowing" device, have enabled the new instrument to take the first electron-microscope records of living processes, examples of which are reproduced in the second of these two papers: loadings around 10^{-6} coulomb/cm² are estimated. The first paper quotes (from the complete account of the apparatus, *loc. cit.*) a general expression for the highest resolving power possible for the photographic recording of the images of living substances, and applies this to the present conditions and future possibilities; it then concentrates on the design and use of the "object-shadowing" device (with the refinements necessary for its successful adjustment) by which the object is protected against the electrons except during the critical moment of exposure.

3596. A TEMPERATURE-RESISTANT AND DURABLE CARRIER-FILM FOR ELECTRON-INTERFERENCE RECORDING AND ELECTRON-MICROSCOPIC INVESTIGATIONS [Aluminium-Oxide Film].—Hass & Kehler. (*Kolloid-Zeitschr.*, No. 1, Vol. 95, 1941, p. 26 onwards.) Quoted in 3595, above.
3597. THE GENERATION OF HIGH POWERS ON SHORT WAVES WITH QUENCHED SPARK GAPS.—Schönfeld. (*See* 3289.)
3598. LOW-FREQUENCY ["Shock"] THERAPY: A NEW TECHNIQUE IN THE TREATMENT OF MENTAL DISEASES, and DESIGN FOR 3-METRE RADIO-THERAPY APPARATUS.—Edison-Swan: Clark. (*E. & Television & S.W.W.*, Feb. 1941, Vol. 14, No. 156, pp. 71 and 95; April, No. 158, pp. 155-157.)
3599. THE DEPENDENCE OF THE SECONDARY ELECTRON EMISSION PRODUCED BY GAMMA RADIATION UPON THE DIRECTION OF THE RADIATION [in Radiation Therapy].—Wilson. (*Proc. Phys. Soc.*, 1st Sept. 1941, Vol. 53, Part 5, No. 299, pp. 613-623.)
3600. PRODUCTION AND USE OF NEUTRONS.—Heyn. (*E. & Television & S.W.W.*, April 1941, Vol. 14, No. 158, pp. 171-173 and 186, 187.) From the Philips laboratories.
3601. JUNIOR ELECTROENCEPHALOGRAPH [Rugged & Simple: Instantaneous Dry-Tape Recording: Sensitivity $\frac{1}{2}$ mm/ μ V].—Electro-Medical Laboratory. (*Review Scient. Instr.*, Aug. 1941, Vol. 12, No. 8, p. 414.)
3602. ELECTRETS MADE FROM DRY-MIXED COMPONENTS, and EFFECT OF PRESSURE ON THE SURFACE CHARGE OF AN ELECTRET.—Dodds, Stranathan, Sheppard. (*See* 3251.)
3603. CONTACT ELECTRIFICATION OF SOLID PARTICLES [and Fleming's Results].—Schnurmann. (*Proc. Phys. Soc.*, 1st Sept. 1941, Vol. 53, Part 5, No. 299, pp. 547-553.) *Cf.* 1001 of March.
3604. A NOTE ON THE DEMONSTRATION OF THE PHOTOEFFECT WITH A GLOW-DISCHARGE LAMP [and the Possibility of using a Modern 110 V Lamp (with Barium-treated Electrodes) to replace a Photocell in Various Applications, particularly for Demonstrations].—Metzger. (*Physik. Zeitschr.*, 15th Nov. 1940, Vol. 41, No. 21/22, pp. 508-510.)
Although the decrease in ignition voltage occurring in a glow-discharge lamp on irradiation will increase the relaxation-oscillation frequency of a suitable circuit, such an arrangement cannot be used for photometric measurements because there is no simple relation between the voltage-reduction and the intensity of illumination. The writer, however, has found that the Osram "Beehive" glow-discharge bulbs for 110 volts (not those for 220 volts), having barium-treated electrodes, display a photoeffect resulting not only in the decrease of ignition voltage but also in a photocurrent capable of working a relay. The max. sensitivity is around 420-530 m μ , but there is a certain amount of response in the red region: the photocurrent for daylight is 3 or 4 times larger than for the light of an incandescent bulb. For voltages at least 30% below the ignition voltage the photocurrent/illumination curve is linear.
3605. A REVIEW OF THE DEVELOPMENT OF SENSITIVE PHOTOTUBES [with over 80 Literature References].—Glover. (*Proc. I.R.E.*, Aug. 1941, Vol. 29, No. 8, pp. 413-423.)
3606. THE TREND TOWARDS ELECTRONICS IN ENGINEERING [including Use of Photocells, etc., in Industry].—Langford Smith. (*Journ. Inst. Eng. Australia*, June 1941, Vol. 13, No. 6, p. 147: summary only.)
3607. PHOTOCCELL CONTROL OF WATER CHLORINATION [with Help of Ortho-Tolidine as Indicator].—Harrington. (*E.T.Z.*, 10th July 1941, Vol. 62, No. 28, p. 630: summary of Canadian paper.)
3608. ON THE PREPARATION OF A THERMAL LIGHT-SOURCE WHICH CAN BE MODULATED AT NOTE FREQUENCIES.—Lattmann. (*Schweizer Arch. f. angew. Wiss. u. Tech.*, Aug. 1940, Vol. 6, No. 8, pp. 212-224.)
Concluded from a previous issue. Conversion of elder pith into a carbon cellular structure, into a tungsten structure, and into a tantalum carbide structure: the construction of experimental tubes for heating these structures by electron bombardment, controlled by a grid: tests on modulation: etc. "Modulation factors at the higher note frequencies can be attained such as have never previously been possible with thermal modulation. Since it is possible by this method easily to prepare luminous surfaces of high light density, it is quite particularly suitable for the construction of a radiator for optical telephony." The previous instalment deals with the theoretical treatment of the problem: its results are confirmed by these tests.

INDEX

VOL. XVIII.

The Wireless Engineer

1941

	PAGE		PAGE
A.C. Impedance of Chokes and Transformers, A Measuring Instrument for Production Checks of the, T. J. Rehfish and H. T. Bissire	266	Effect of the Earth's Curvature on Ground-Wave Propagation, The (<i>Editorial</i>)	393
A.V.C. Circuit Time Constants, D.C. Amplified, K. R. Sturley and F. Duerden	353	Effective Inductance of a Coil in a Metal Container, The Influence of Stray Capacitances on the, L. I. Farren and R. S. Rivlin	313
ABSTRACTS AND REFERENCES (<i>see special Index published separately, priced 2s. 6d.</i>)		Efficiency of the Rhombic Transmitting Aerial, Increasing the Power, L. Lewin	180
Acoustical and Electromagnetic Waves, The Velocity of (<i>Editorial</i>)	265	Electromagnetic Waves, The Velocity of Acoustical and (<i>Editorial</i>)	265
Admiralty Handbook of Wireless Telegraphy, The (<i>Editorial</i>)	481	Electron Beam Traversing a Transverse Alternating Deflecting Field, Impedance of an (<i>Correspondence</i>)	64, 154
Aerial Coupling Circuits, Receiver, K. R. Sturley	137, 190	Equivalent Circuits of the Feedback Amplifier, Alan Fairweather	151
Aerial, Increasing the Power Efficiency of the Rhombic Transmitting, L. Lewin	180	Feedback Amplifier, Equivalent Circuits of the, Alan Fairweather	151
Aerials, Noise in Receiving (<i>Correspondence</i>)	405	Ferrocarril. A phenomenon of Time	352
Ammeter, The Oscillating High-Frequency (<i>Editorial</i>)	93	Frequencies of Coupled Circuits, Natural and Resonant (<i>Editorial</i>)	221
Amplified A.V.C. Circuit Time Constants, D.C., K. R. Sturley and F. Duerden	353	Frequency versus Amplitude Modulation (<i>Editorial</i>)	1
Amplifier, Equivalent Circuits of the Feedback, Alan Fairweather	151	Frequency-Changer, Diode as Rectifier and, D. A. Bell	395
Amplitude Modulation, Frequency versus (<i>Editorial</i>)	1	Frequency Modulated Systems, Interference in Relation to Amplitude, Phase and, O. E. Keall	6, 56
Amplitude, Phase and Frequency Modulated Systems, Interference in Relation to, O. E. Keall	6, 56	Ganging Superheterodyne Receivers, Martin Wald	146
Analysis of the Ionosphere (<i>Editorial</i>)	43	Ground-Wave Propagation, The Effect of the Earth's Curvature on (<i>Editorial</i>)	393
Anode Dissipation in Anode-Modulated Class C Amplifiers, R. G. Mitchell	443	Half-Wave Modulation, C. E. G. Bailey	279
Automatic Tuning and Measurement of Modulation, The Locked-in Oscillator and, S. Byard and W. H. Eccles	2	High-Frequency Ammeter, The Oscillating (<i>Editorial</i>)	93
Band-Pass Effect in Electric Wave-Filters Terminated in Negative Impedance, The Nature of, S. P. Chakravarti	103	Impedance of Chokes and Transformers, A Measuring Instrument for Production Checks of the A.C., T. J. Rehfish and H. T. Bissire	266
Band-Pass Filters, Coupling Circuits as, E. K. Sandeman	361, 406, 450, 492	Impedance of an Electron Beam Traversing a Transverse Alternating Deflecting Field (<i>Correspondence</i>)	64, 154
Books:		Inductance of a Coil in a Metal Container, The Influence of Stray Capacitances on the, L. I. Farren and R. S. Rivlin	313
E.R.A. Reports:—		Inductance Linearised Time Base, F. C. Williams and Alan Fairweather	224, 271
The High Frequency Properties of Various Forms of Wire Specimens, G. G. Sutton	415	(<i>Correction</i>)	312
Radio Interference from Thermostats in Refrigerators and Irons, S. F. Pearce and S. Whitehead	415	INDUSTRY, THE:—	
Geomagnetism, Sydney Chapman and Julius Bartels	17	Brimar Rectifier Type 25Z4G	64
Radio-Frequency Measurements by Bridge and Resonance Methods, L. Hartshorn	63	British Insulated Cables, Ltd.: Leaflet NSG0 on Pernax Insulating Tape	187
Bridged-T Method of Measuring the Constants of a Coil, The (<i>Editorial</i>)	135	Cossor, Ltd.: Instruction Manuals Issued, A.C. Impedance Bridge Model 3389	64
British Standards Specifications: No. B.S. 415-1941 "Safety Requirements of Mains-operated Wireless Apparatus," and No. B.S. 951-1941 "Earthing to Water Mains" and No. B.S. 933-1941 "Magnetic Materials for Use Under Combined D.C. and A.C. Magnetisation"	197	Double Beam Cathode-Ray Oscillograph Model 3339	111
	491	Eddystone: Change of Address	111
Cathode-Ray Tubes, Some Effects of Secondary Emission on Deflector Plate Characteristics of, Hilary Moss	309	Loose-leaf Folder with Technical Leaflets Issued	456
Chokes and Transformers, A Measuring Instrument for Production Checks of the A.C. Impedance of, T. J. Rehfish and H. T. Bissire	266	Edwards and Co.: "Vacustat" Vacuum Gauge	64
Coil Constants, The Twin-T Method of Measuring (<i>Editorial</i>)	441	Catalogues of High-Vacuum Diffusion Pumps	456
Coil in a Metal Container, The Influence of Stray Capacitances on the Effective Inductance of a, L. I. Farren and R.S. Rivlin	313	Expanded Rubber Co., Ltd.: Brochure on Gas-Expanded Rubber and Ebonite Cellular Materials	456, 491
Condenser, The Deflecting (<i>Correspondence</i>)	277	Holsun Batteries, Ltd.: Change of address	187
Constants of a Coil, The Bridged-T Method of Measuring the (<i>Editorial</i>)	135	Multicore Solders, Ltd.: "Ersin" Lead-Free Solder	456
Constants, The Twin-T Method of Measuring Coil (<i>Editorial</i>)	441	Pernax Insulating Tape, Leaflet on	187
Constrast Expander Circuit, An Analysis of the Crosley, S. W. Amos	237	Salford Electrical Instruments, Ltd.: Quartz Crystal Calibrator Type BW.200	5
Coupled Circuits, Natural and Resonant Frequencies of (<i>Editorial</i>)	221	Sloan Electrical Co., Ltd.: Change of Address	187
Coupling Circuits as Band Pass Filters, E. K. Sandeman	361, 406, 450, 492	Standard Telephones and Cables, Ltd.: Brimar Rectifier Type 25Z4G	64
Crosley Contrast Expander Circuit, The, S. W. Amos	237	Catalogue Describing Type E.S.4. S.W. Transmitter	491
Cycles per Second (<i>Editorial</i>)	179	Stratton and Co., Ltd.: Change of Address	111
D.C. Amplified A.V.C. Circuit Time Constants, K. R. Sturley and F. Duerden	353	Loose-leaf Folder with Technical Leaflets Issued	456
Deflecting Condenser, The (<i>Correspondence</i>)	277	Taylor Electrical Instruments, Ltd.: Catalogue	64
Dimensions of Physical Quantities, The (<i>Editorial</i>)	351		
Diode as Rectifier and Frequency-Changer, D. A. Bell	395		

	PAGE
INDUSTRY, THE (continued):—	
Tin Research Institute: Publications Issued:	
No. 102 "Hot Tinning"	111
No. 105 "Spectrographic Methods of Determining Impurities in Lead-Tin Solders"	456
White Co., The S. S.:	
Treatise and Supplements on Remote Control Issued	64, 187
Wright and Weaire Ltd.: Director's Resignation	491
Interference in Relation to Amplitude, Phase and Frequency Modulated Systems, O. E. Keall	6, 56
Ionosphere, Analysis of the (Editorial)	43
Iron, Testing Small Samples of Transformer (Editorial)	307
L inearised Time Base Inductance, F. C. Williams and Alan Fairweather	224, 271
(Correction).....	312
Linear Rectifier as Indicator of Measurements of Shot and Thermal Noise, The, D. A. Bell	95
(Correspondence)	278, 323
Line-Controlled Apparatus, Analysis for the Design of Pierce Piezo-Electric Oscillator, The, H. Jefferson	232
Locked-In Oscillator and Automatic Tuning and Measurement of Modulation, The, S. Byard and W. H. Eccles.....	2
M agnetron, Theory of Short-Wave Oscillations with the Measurement of Modulation, The Locked-in Oscillator and Automatic Tuning and, S. Byard and W. H. Eccles	2
(Correspondence)	404
Measurement of Modulation Depth, The, H. D. McD. Ellis	99
Measurements of Shot and Thermal Noise, The Linear Rectifier as Indicator of, D. A. Bell	95
(Correspondence)	278, 323
Measuring Coil Constants, The Twin-T Method of (Editorial)	441
Measuring the Constants of a Coil, The Bridged-T Method of, (Editorial)	135
Modulated Class C Amplifiers, Anode Dissipation in Anode, R. G. Mitchell.....	443
Modulated Systems, Interference in Relation to Amplitude, Phase and Frequency, O. E. Keall.....	6, 56
Modulation, The Locked-In Oscillator and Automatic Tuning and Measurement of, S. Byard and W. H. Eccles	2
Modulation Depth, The Measurement of, H. D. McD. Ellis	99
Modulation, Frequency versus Amplitude (Editorial).....	1
Modulation, Half-Wave, C. E. G. Bailey	279
N atural and Resonant Frequencies of Coupled Circuits (Editorial)	221
Negative Impedance, The Nature of the Band-Pass Effect in Electric Wave-Filters Terminated in, S. P. Chakravarti	103
Noise, The Linear Rectifier as Indicator of Measurements of Shot and Thermal Noise, D. A. Bell	95
(Correspondence)	278, 323
Noise in Receiving Aerials (Correspondence)	405
Nomenclature, Slovenly Tendencies in (Editorial)	179
O scillating High-Frequency Ammeter, The (Editorial)	93
Oscillations with the Magnetron, Theory of Short-Wave (Correspondence)	404
Oscillator, The Pierce Piezo-Electric, H. Jefferson	232
P hase and Frequency Modulated Systems, Interference in Relation to Amplitude, O. E. Keall	6, 56
Physical Quantities, The Dimensions of (Editorial)	351
Pierce Piezo-Electric Oscillator, The, H. Jefferson	232
Power Efficiency of the Rhombic Transmitting Aerial, Increasing the, L. Lewin	180
Practical Triode, The, I. A. Harris	45
(Correspondence)	153
Propagation, The Effect of the Earth's Curvature on Ground-Wave (Editorial)	393
R eceiver Aerial Coupling Circuits, K. R. Sturley	137, 190
Receiving Aerials, Noise in (Correspondence)	405
Rectifier and Frequency-Changer, Diode as, D. A. Bell	395
Relaxation Amplifier, The, Martin Wald	483
Replacement Valves, B.V.A. List of	491
Resonant Frequencies of Coupled Circuits, Natural and (Editorial)	221
Rhombic Transmitting Aerial, Increasing the Power Efficiency of the, L. Lewin	180

	PAGE
Secondary Emission on Deflector Plate Characteristics of Cathode-Ray Tubes, Some Effects of, Hilary Moss	309
Shot and Thermal Noise, The Linear Rectifier as Indicator of Measurements of, D. A. Bell	95
(Correspondence)	278, 323
Short-Wave Oscillations with the Magnetron, Theory of (Correspondence)	404
Slovenly Tendencies in Nomenclature (Editorial)	179
Stray Capacitances on the Effective Inductance of a Coil in a Metal Container, The Influence of, L. I. Farren and R. S. Rivlin	313
Superheterodyne Receivers, Ganging, Martin Wald	146
T esting Small Samples of Transformer Iron (Editorial)	307
Theory of the Practical Triode, A, I. A. Harris	45
(Correspondence).....	153
Theory of Short-Wave Oscillations with the Magnetron (Correspondence)	404
Thermal Noise, The Linear Rectifier as Indicator of Measurements of Shot and, D. A. Bell	95
(Correspondence)	278, 323
Time Base, Inductance Linearised, F. C. Williams and Alan Fairweather	224, 271
(Correction).....	312
Transformer Iron, Testing Small Samples of (Editorial)	307
Transformers, A Measuring Instrument for Production Checks of the A.C. Impedance of Chokes and, T. J. Rehfish and H. T. Bissmire	266
Transmitting Aerial, Increasing the Power Efficiency of the Rhombic, L. Lewin	180
Triode and Its Application to Valve Design, A Theory of the Practical, I. A. Harris	45
(Correspondence)	153
Tuning and Measurement of Modulation, The Application of the Locked-in Oscillator to Automatic, S. Byard and W. H. Eccles	2
Twin-T Method of Measuring Coil Constants, The (Editorial)	441
V alve Design, A Theory of the Practical Triode and its Application to, I. A. Harris	45
(Correspondence)	153
Valves, B.V.A. List of Replacement	491
Velocity of Acoustical and Electromagnetic Waves, The (Editorial)	265
W ave-Filters Terminated in Negative Impedance, The Nature of the Band-Pass Effect in Electric, S. P. Chakravarti	103
Wave Propagation, The Effect of the Earth's Curvature on Ground- (Editorial)	393
Waves, The Velocity of Acoustical and Electromagnetic (Editorial)	265

INDEX TO AUTHORS

	PAGE
AMOS, S. W.	237
BAILEY, C. E. G.	279
BELL, D. A.	95, 395
BISSMIRE, H. T. and REHFISCH, T. J.	266
BYARD, S. and ECCLES, W. H.	2
CHAKRAVARTI, S. P.	103
DUERDEN, F. and STURLEY, K. R.	353
ECCLES, W. H. and BYARD, S.	2
ELLIS, H. D. MCD.	99
FAIRWEATHER, ALAN	151
FAIRWEATHER, ALAN and WILLIAMS, F. C.	224, 271
FARREN, L. I. and RIVLIN, R. S.	313
HARRIS, I. A.	45
JEFFERSON, H.	232
KEALL, O. E.	6, 56
LEWIN, L.	180
MCD. ELLIS, H. D.	99
MITCHELL, R. G.	443
MOSS, HILARY	309
REHFISCH, T. J. and BISSMIRE, H. T.	266
RIVLIN, R. S. and FARREN, L. I.	313
SANDEMAN, E. K.	361, 406, 450, 492
STURLEY, K. R.	137, 190
STURLEY, K. R. and DUERDEN, F.	353
WALD, MARTIN	146, 483
WILLIAMS, F. C. and FAIRWEATHER, ALAN	224, 271

mg