RADIO ELECTRONICS

ELECTRONICS FOR HOME INDUSTRY AND LABORATORY





"EXPLOR AIR" 4-BAND DERENVAR DATE



19 H 0905 See page 64

LAFAYETTE **ALL-TRANSISTOR CB** "WALKIE-TALKIE"



ATAYETTE BINDOGLARS



LAFAYETTE SOLID STATE AUTOMATIC STEREO PHONOGRAPH



orn, i



LAFAYETTE "MIGHTY 9" 9-TRANSISTOR **RADIO**

See page 103

99 H 3513L See Page

POLARIS HEFRACTOR



STEREO RECEIVER



99 H 7035

FAYETTE "THY 6" TRANSISTOR RADIO



17 H 6900L

COMPLETE AM-FM



TRIPLE TURRET ELECTRIC EYE MOVIE CAMERA





FOR EASY PAY INFORMATION See Center Insert A

> For INDEX See Page 3

Christmas

Catalog

No. 651

LAFAYETTE

MAIL ORDER & L. I., SALES CENTER 111 JERICHO TURNPIKE (West of So. Oyster Bay Rd.)

SYOSSET.

L. I., N. Y. 11791

Shop-by-Phone Dept. 516 Walnut 1-7500

Other Departments

516 WAInut 1-7700

Other Stores BRONX BROOKLYN

MASS.

JAMAICA

NEW YORK SCARSDALE

> BOSTON NATICK

NEWARK

PARAMUS PLAINFIELD

FOR COMPLETE

AODRESSES AND STORE HOURS

See Page 3 FOR LAFAYETTE

ASSOCIATE STORE"

See Page 93

NEW LOCATIONS: MID-TOWN MANHATTAN AND BROOKLYN

NEW! LAFAYETTE MODEL LR-800 70-WATT COMPLETE AM-FM STEREO RECEIVER



 Nevistor "Front-end" with 1.5 μν Sensitivity Circuitry-Signals Presence of Stereo Broadcasts • Complete Preamplifier Control Facilities-70-watt Amplifier • Variable ACC control • Front Panel Bar-Type Tuning Indicator for AM and FM

AS LOW AS S9 monthly

The deluxe Model LR-800 contains on one compact chassis all the electronics necessary for a superb complete home music system. Just add speakers to enjoy the magnificent fidelity of FM, FM Stereo or high quality standard AM broadcast. Addition of a phono or tape transport completes your high fidelity system. Features: Extremely sensitive 'Nuvistor' front end pulls in FM stations free of noise and spurious signal interference. Amazing "Stereo Search" circuit pinpoints stereo stations quickly and positively with a tone signal heard through your loudspeakers. Bar-type electron-ray tuning Indicator and large easy-to-read slide rule dial, with flywheel tuning action make tuning FM or AM a pleasure. Variable AFC controls "locks-in" stations. Powerful 70-watt stereo amplifier reproduces all program material with clean sound even with inefficient speaker systems. The audio control center features separate friction-lock bass and 3reble controls for each channel, balance control, rumble and FM noise controls for each channel, balance control, rumble and FM noise filter; loudness switch and front panel stereo headphone iack/ speaker "off" switch for private listening. Tape monitor lets you evaluate recorded material as you tape it. Separate Mode selector

SPECIFICATIONS

Tuner Section—FM Sensitivity: 1.5 μv for 20 db quieting MPX Separation: 37 db @ 400 cps Frequency Response: FM Mono—20-20,000 cps ±1db, FM Stereo 50-15,000 cps ±1db. Harmonic Distortion: Less than 0.5% @ 1 KC. Amplifier Section—Power Output: 35 watts per channel Music Power, Hum and Noise: 55 db low level, 80 db high level. Harmonic Distortion: 1% at full output. Output Impedances: 8 & 16 ohms, switch selected Equalization: RIAA (Mag), NAB (tape Head). Tubes: 24 inclu. EM-84 tuning eye, 9 diodes, 1 selenium rectifier. 2 AC receptacles, 1 switched.

AFAYETTE 70-WATT STEREO TURING MODEL LR-800 AM-FM



SK-300 DECORETTE V

- Lafayette LR-800 70 Watt AM-FM Stereo Receiver Garrard Model AT60 4 Speed Record Changer Pickering V15/AT-1 Diamond Needle Cartridge*
- Wood Base for Changer (Specify Oiled Walnut
- or Mahogany)
 2 Lafayette SK-300 "Oecor-ette V" 5-Speaker Slim Speaker Systems (Oiled Walnut).

Above stereo system with your *choice of Pickering V15/AT-1, Shure M7/N21D, or Empire 880 diamond needle carridge; complete with all necessary cables and instructions, Shpg. wt., 96 lbs.

Same as above except with 2 Lafayette famous SK-58 12" Free Edge Coaxial Speakers instead of SK-300 "Decgrette V" Speaker systems. Shpg. wt., 84 lbs. 21 H 9753CWX Net 278.50

Same as 21 H 9753CWX plus 2 Lafayette famous patented Eliptoflex enclosures. Shpg. wt., 132 lbs. (Specify Oiled Walnut or Mahogany). 21 H 9754CWX

Same as 21 H 9746CWX except with 2 Lafayette superb SK-270 Decor-ette II 5-speaker slim speaker systems (oiled walnut) instead of Decor-ette V speaker systems. Shpg. wt., 110 lbs. Net 340.50

PRINTED IN U.S.A. . ENTIRE CONTENTS COPYRIGHTED 1964 BY LAFATETTE RADIO ELECTRONICS CORPORATION . SYDSSET, L. I., N. Y.

You Can Depend On LAFAYETTE

Mail Order Division

Our modern Mail Order Headquarters, located on over 8 acres of land, includes expanded warehouse facilities plus the most modern handling equipment to give you quicker service. Within 24 hours after receipt, most orders are processed, picked, wrapped and shipped on their way.

Retail Store Division 12 Convenient Locations

Visit any Lafayette store and see a wide assortment of merchandise from this catalog as well as many non-catalog items. Also be sure to see the custom-designed Sound Studios and Lafayette's Ham Shack, Trained, courteous sales personnel will help you with your For Associate Store Locations See Page 93

OUR 2 NEWEST STORES

Mail Order and Sales Center SYOSSET, L. I., N. Y.

111 Jericho Turnpike

(West of So. Oyster Bay Rd.) Shop By Phone Dept.

516 WAinut 1-7500

All Departments 516 WAInut 1.7700

Open Mon., Thurs. & Fri. 'til 9:30 P.M.

Special Xmas Hours starting Nov. 30 Open Weekdays 'til 9:30 P.M.

NEW YORK - 45th St.

71 West 45 St. (between 5-6 Aves.) Phone 212 757-3121

Open Thurs. 'til 9:00 P.M. Special Xmas Hours starting Nov. 30 Open Weekdays 'til 9:00 P.M.

BROOKLYN, N.Y.

2265 Bedford Avenue (cor. Snyder Ave.) 212 IN 9-8900

Open Mon., Wed., Thurs., Fri. 'til 9:30 P.M. Special Xmas Hours starting Dec. 7 Open Weekdays 'til 9:30 P.M.

SCARSDALE, N.Y. 691 Central (Park) Ave. (1/2 mile north of Ardsley Rd.) 914 GR 2-2700 Open Mon. Thurs., Fri. 'til 9:30 P.M. **Special Xmas Hours** Starting Nov. 30 Open Weekdays

til 9:30 P.M.

100 Sixth Avenue (1 block north of Canal St.) 212 WO 6-5300 Open Thurs. 'til 8:45 P.M. Special Xmas Hours starting Dec. 14 Open Weekdays

NEW YORK, N.Y.

JAMAICA, N.Y. 165-08 Liberty Avenue. (off Merrick Rd.) 212 AX 1-7000 Open Mon., Thurs., Fri. 'til 8:45 P.M. Special Xmas Hours starting Dec. 7 Open Weekdays

til 8:45 P.M.

542 E. Fordham Road (3 blocks east of Webster Ave.) 212 FO 7-8813 Open Thurs. 'til 8:45 P.M. Special Xmas Hours starting Dec. 14 Open Weekdays til 8:45 P.M.

BRONX, N.Y.

NATICK, MASS. 1400 Worcester Street (Rt. 9 opposite Shopper's World) Phone: 617 875-6146 Open Wed., Thurs., Fri. 'til 9:30 P.M. Special Xmas Hours starting Nov. 30 Open Weekdays til 9:30 P.M.

BOSTON, MASS. 584 Commonwealth Ave. (1/2 block above Kenmore Sq.) Phone: 617 267-8900 Open Mon. thru Fri. 'til 9:00 P.M. Special Xmas Hours starting Nov. 30 Open Weekdays til 9:30 P.M.

NEWARK, N.I. 24 Central Avenue (just west of Broad St.) 201 MA 2-1661 Open Wed. 'til 8:45 P.M.

Special Xmas Hours starting Dec. 7 Open Weekdays til 8:45 P.M.

til 8:45 P.M. PLAINFIELD, N.J. 139 W. 2nd Street (1 block E. of Front St.) 201 PL 6-5100 Open Thurs. 'til 8:45 P.M. Special Xmas Hours starting Dec. 7 Open Weekdays til 8:45 P.M.

PARAMUS, N.J. 182 Route 17 (1 mile north of Garden State Plaza) 201 CO 1-8800 Open Mon., Wed., Fri. 'til 9:30 P.M. Special Xmas Hours starting Nov. 30 Open Weekdays 'til 9:30 P.M.

INDEV

Amateur Gear Amplifiers, Hi-Fi Kits Antennas, TV and FM ASSOCIATE STORE AL	122-125
Amplifiers Hi.Fi	6.13 10.21
Kits	0.13, 10.21
Antennas TV and EM	00 00
ASSOCIATE STORE AP	NOTECOEO, 03
AUTO ADDOCUTE AL	INKE22F2 33
Batteries & Chargers	80, 81, 87
Below Cost Specials	70. 71
Cahinets, Hi.Fi	26.20
Cameras and Accessori	95 74-79
Carringes Milei	42
CITIZENS BAND EQUIPMENT Drafting & Drawing EASY PAY PLAN CEI	
FOLLOWENT	100 100
Destina & Destina	126-139
niatting & niaming ""	101
EASY PAY PLAN CEI	NTER INSERT A
coucational Kits	67-69
Experimenter Specialtic	es 72, 73, 99
HeadDhones, Steren	42
Hearing Aids, Earphone	- 100
wing! raibilone	3 106

INDEX
HI-FIDELITY SYSTEMS
AND COMPONENTS 2, 4-22, 54, 55
Intercoms 90, 92
Intercoms 90, 92 Lamps & Electrical Accessories 109
Meters 125
Microphones 14, 65
Microscopes 104, 106
Microscopes 104, 106 Movie Cameras 76, 78, 78A
wuititesters 116
Musical Instruments
& Accessories62, 63
RADIOS
Auto 82, 83 Clock 57
Clock
Table
Table 57, 61 Receivers, Special Purpose 121
Receivers, 5tereo 2, 4, 5, 16, 19-22
Record Changers 40 41
Remote Control Equipment 64, 65

			_
Phonographs Needles		See Insert	53
Shortwave R	adios	61, 6	:7
SPEAKERS A	IND SPE	AKFR	
SYSTEM	S	23-3 44-48, 14	35
Tape Record	ers	44-48, 14	10
Accesso	ries	49, 5	50
researcones, s	Binocular	3 102 10	13
I EFEA1210M	3E13	10	17
Timers & Co.	ent	115-12	0
Tools Chd 8	unters	······· <u></u>	п
Tours, 510. &	rower	86, 94-9	8
Toys, Models			4
TRANSISTOR	RADIOS	58, 59, 6	1
Tuners		14, 15, 18-2	2
Turntables		4	2
WALKIE-TALK	IES	131-13	4

Industrial **Electronics** Division

Industrial, Institutional and Government Agency Buyers **NEW JERSEY**

NEW ENGLAND

1400 Worcester St., Natick, Mass. Phone: 617 875-1358

24 Central Ave., Newark 2, N. J. 201 Mitchell 3-6868

METROPOLITAN NEW YORK-LONG ISLAND

165-08 Liberty Ave., Jamaica 33, N. Y. 212 Olympia 8-5050

ABC

International Sales Division ERVICES BUYERS WORLDWIDE. SERVICES WRITE TO:

International Sales Division Lafayette Radio Electronics Corporation P.O. Box P Syosset, L.I., N.Y., U.S.A.

LAFAYETTE'S NEW 1965 CATALOG No. 650 Over 500 Pages

Featuring Everything in Electronics for Home • Industry • Laboratory

from the

"World's Hi-Fi & Electronics Center"

44 Years of Dependable Service at Lafayettes' Traditionally Low. Low Prices.

If you do not have the FREE Lafayette Catalog 650, or if you want a copy for a friend, fill out and mail the coupon now!

Lafayette Cat. No. 651

EXPORT TERMS

Full payment must accompany the order. Enclose check or draft; or remit international Postal Money Order or confirmed, irrevocable Letter of Credit, All payments should be in U.S. Doliars payable at U.S. Bank, Include 20% above merchandise value to cover international postage, insurance, consular fees and other export shipping costs. Overpayments are promptly refunded. All prices F.O.B. our warehouses and subject to change without notice.



LAFAYETTE

ELECTRONICS Dept. 651, P. O. Box 10

Syo55et, L. I., N. Y. 11791

Send the FREE 1965 Lafayette Catalog No. 650

Name	Please Print
Addre	ss
City	StateZip

LAFAYETTE MODEL LA-230 24-WATT COMPLETE AM-FM STEREO RECEIVER



COMPLETE RECEIVER! \$7.00 monthly

16 Tubes plus 6 Diodes

- 24-Watt Fully Integrated Stereo Amplifier Stereo "Searcher" for Locating Stereo Stations
- Front Panel Stereo Headphone Jack
- FM Stereo Noise Filter
- AM/FM Tuning Meter
- Complete Stereo Preamp Facilities

JUST ADD SPEAKERS FOR A COMPLETE STEREO SYSTEM


The ideal heart for your stereo system, all on one compact chassis, Connect two speaker systems, turn on and in moments you're enjoying the static-free reception of music broadcast in FM stereo multiplex. The LA-230 utilizes an advanced design stereo "Search" circuit which takes the guesswork out of finding FM stereo stations. While tuning for stereo, a continuous note is heard through your loudspeakers when a stereo station is on the air. Wide bandwidth gives excellent response. The addition of a tape recorder or record player will bring you recorded music to enjoy as well. Contributing to the high quality sound of this four-in-one unit are complete stereo preamp facilities and a 24-watt stereo push-pull amplifier with a response of 20-20,000 cps. Controls include: variable AFC; Power off/on concentric volume, bass, treble, selector (AM, FM Stereo "search"; FM MPX Phono, Aux.), amplifier (L, R, B, L-+R, Rev. Mono) Tuning. Loudness on/off and FM Multiplex Noise filter switch. The ideal heart for your stereo system, all on one com-

The LA-230 also offers the convenience of a front panel stereo headphone jack for your private listening pleasure and a speaker on/off switch. Rear Panel controls include hum balance and 8-16 ohm speaker impedance switch.

- SPECIFICATIONS -

TUNER: FM 88-108MC, AM 535-1600 KC; SENSITIVITY: 3 μν for 20 db S/N ratio: FM SEPARATION: 25 db @ 400 cps; FREQUENCY RESPONSE: 20-20,000 cps ±2 db; AMPLIFIER: OUTPUT: 12-watts per channel (music power); EQUALIZATION: RIAA; HUM & NOISE: Mag. Phono —55 db. Aux., —68db; TUBES: 16 tubes, 6 diodes.

MATCHED STEREO SYSTEMS with MODEL LA-230 AM-FM STEREO RECEIVER



Garrard Model 50

Pickering V-15/AT-1

CHOICE OF STEREO CARTRIDGE Empire Shure M7/N21D



2-SK-180



2-SK-270

Lafayette LA-230 24-Watt AM-FM Multiplex Stereo Tuner-Amplifier

Garrard Model 50 4-Speed Record Changer Pickering Model V15/AT-1. Diamond Needle

Cartridge' Wood Base for Changer (specify oiled

walnut or mahogany)
2 Lafayette SK-300 "Decor-ette V" 5-Speaker Slim Speaker System (Oiled Walnut)

Above hI-fi stereophonic system with a choice of Pickering V15/AT-1, Shure M7/N21D, or Empire 880 diamond needle cartridge complete with all necessary cables and instructions. Shg., wt., 79 lbs.

21 H 9721CWX Net 215.50

2—Eliptoflex

ALTERNATE SYSTEMS

Enclosure	Garrard		Speaker/ * Speaker Speaker					
System R		Changer	Cartridge	Base	System	Cabinet	Wt. Lbs.	Net
21 H 9723CWX L 21 H 9724CWX L 21 H 9726CWX L	LA-230 LA-230 LA-230 LA-230 LA-230	AT60 50 AT60 50 50	Choice of Pickering V15/AT-1 Shure M7/N21D or Empire 880	+++++	2 SK-270	Decor-ette V‡ Decor-ette II‡ Decor-ette II‡ 2 Eliptoflex * *	81 93 95 61 109	226.50 272.50 283.50 214.50 272.50

†Specify oiled walnut or mahogany #Oiled walnut only **Specify oiled walnut, walnut, or mahogany

LAFAYETTE MODEL LA-215 COMPLETE **AM-FM STEREO RECEIVER**

ONLY \$9.00 monthly



• 15 Tubes plus 6 Diodes • Front Ponel Stereo Headphone Jock • Complete Stereo Preomp Focilities • 11 Front Panel Controls • Just Add Speakers for Complete Stereo System

A Fine AM-FM Tuner with Built-in-Multiplex plus a 12-WATT COMPLETELY INTEGRATED STEREO AMPLIFIER

A complete stereo control center with AM/FM tuner with built-in multiplex and a 12-watt stereo amplifier. FM section features advanced stereo "Search" circuit which introduces a tone when a multiplex signal is tuned in Changing the selector switch from stereo search to FM stereo permits normal MPX reception, AFC assures low drift FM reception, MPX noise filter eliminates unwanted station noise. AM section features superhet circuit and a wanted station noise. AM section features superhet circuit and a built-in antenna, Front panel controls; power on/off; concentric volume/balance; master bass; master treble; 6-position selector switch (AM, FM, Stereo Search, Stereo FM, Phono, Aux.); tuning, stereo-mono mode switch; MPX noise filter on/off; AFC on/off; speakers on/off. Rear panel has speaker phase switch and

8 & 16 ohm impedance selector; stereo inputs for mag phono,

- SPECIFICATIONS -

TUNER FM Sensitivity: 3µv for 20 db S/N ratio—Frequency Response: FM, 20-20.000 cps ±2 db; FM Stereo, 50-15,000 cps ±2 db—Harmonic Distortion: FM, less than 1% @ 400 cps; FM Stereo. less than 2% @ 400 cps—FM Stereo Separation: 25 db

0 400 cps.

AMPLIFIER Power Output: 6 watts music power per channel—
Sensitivity: Mag. Phono, 3.5 mv @ 4.5 watts output Crystal, 30

mv @ 4.5 watts output—Hum and Noise—55 db for low level input -75 db for high level input-Output Impedance: 8 & 16 ohms switched--Phono Equalization: RIAA.

LAFAYETTE COMPLETE STEREOPHONIC HI-FI SYSTEMS

FEATURING THE LA-215 12-WATT AM-FM STEREO RECEIVER

Lafayette LA-215 12-watt AM-FM Stereo Tuner-Ampli-

Lafayette-Webcor Model PK-770 4 Speed Automatic Record Changer with Astatic Turnover Cartridge and Diamond LP Stylus.

Wood Base for Changer (Oiled Walnut). 2 Lafayette SK-265 "Slenderette III" 2-Speaker Slim Speaker Systems with all necessary cables and instructions.

Complete system as above. Shpg. wt., 75 lbs. 21 H 9956WX

Net 159.50

Same as above except with Garrard Model 50 4 speed changer with choice of Pickering V15/AT-1, Shure M7/N2ID or Empire 880 diamond stylus cartridge instead of Lafayette-Webcor Model PK-770 changer. Shpg. wt., 75 lbs.

21 H 9957WX

Same as 21 G 9956WX except with 2 Lafayette SK-123 Ultra-Compliance speaker system (oiled walnut finish) instead of SK-265 speaker systems. Shpg. wt., 75 lbs. 21 H 9958WX

Same as 21 H 9957WX except with 2 Lafayette SK-123 ultra—Compliance speaker system (oiled walnut finish) instead of SK-265 speaker systems. Shpg. wt., 75 lbs. Net 180.90 21 H 9959WX

Same as 21 H 9957WX except with 2 Lafayette famous SK-58 12" free-edge coaxial speakers instead of SK-265 "Slenderette 11!" speaker systems. Shpg. wt., 65 lbs. Net 189.50 Net 189.50


Same as 21 H 9962WX plus 2 Lafayette famous patented Eliptoflex speaker enclosures (specify oiled walnut, wal-Eliptoflex speaker enclosures (specif nut, or mahogany). Shpg. wt., 112 lbs.

Net 247.50 IIi-Fi Systems are Available on Easy Pay Plan-See Center Insert A




Lafayette Cat. No. 651 5

LAFAYETTE 44-WATT ALL-TRANSISTOR STEREO AMPLIFIER MODEL LA-200



\$9 monthly

19 Transistors Silicon Diodes



SPECIFICATIONS

IHFM Music Power: 44 watts; 22 watts per channel; IMFM Music Power: 44 watts; 22 watts per channel; 18 watts continuous sine wave power per channel. Frequency Response ± 1 db, 20-20,000 cps. Harmonic Dist.: 1%. Hum & Noise: Tuner, —74 db; Mag. Phono, —54 db. Tone Controls: ± 10 db. Imputs: (Spairs); Tape Head; Mag. Phono; Cer. Phono; Tuner; Aux. Outputs: Tape Recorder, 4 ohms (also) for 8 and 15 chempets: 16 ohm speakers).

 Complete Stereophonic Control Facilities
 Modern Styling, Compact Size • Cool Running, Reliable Transistor Circuitry • 20-20,000 cycles ± 1 db • Smooth, Fast Transient Response • Freedom From Hum and Noise • Instantaneous Warmup

YEARS AHEAD FEATURES

- Switches
- 2 Front Panel Stereo Phone Jack 3 Oversize Electrolytic Capacitors for Better Power Supply Filtering, and Longer Life
- 4 Military-type Terminal Boards Give Greater Reliability 5 Heat Shield for extra component
- protection
- 1 Smooth Positive Action Controls and 6 Massive Heat Sink to Insure Cool operation of Power Transistors Speaker Phase Switch
 - 8 2 AC Convenience Outlets, One Switched 9 Fused AC Line
 - 10 Massive Power Transformer
 - 11 Complete Overload or Short Circuit Protection
 12 19 Transistors, 5 Silicon Diodes

The LA-200 combines a complete stereophonic preamplifier and a dual channel 44-watt power amplifier on one compact chassis. All-transistor circuit offers advantages not found in tube sets. The initial performance level is maintained for years without adjustments when operated properly, features including Front panel stereo headphole receptacle, scratch and rumble filters, separate on-off power switch, bass and treble controls for each channel, 4-position mode switch, volume, balance and 5-position input selector switch, speaker on/off switch. Phase switch on rear panel; 2 AC convenience receptacles, one switched; pilot light. Operates with 4, 8 or 16-ohm speakers. Brown textured finish case, gold finish aluminum panel and knobs. For 105-125V 50/60 cycles AC. Size: 13Wx 4%, Hx9°D (with legs). Shpg. wt., 15 lbs. Imported.

44-WATT HI-FI STEREO SYSTEMS WITH LAFAYETTE MODEL LA-200 ALL-TRANSISTOR STEREO AMPLIFIER



Lafayette LA-200 44-Watt All-Transistor Stereo Amplifier

Garrard Model 50 4-Speed Stereo Changer Pickering V15/AT-1 Diamond Needle

Cartridge* Wood Base for Changer (Oiled Walnut or Mahogany)

2-Lafayette SK-300 "Decor-ette V" 5-Speaker Slim Speaker System (Oiled Walnut)

Complete system as above plus all necessary cables and instructions. Shpg. wt., 64 lbs. 21 H 9701CWX

Same system as 21 G 9701CWX except with Garrard Model AT60 record changer instead of model 50. Shpg. 66 ths

21 H 9702CWX Net 199.50 Same as 21 H 9701CWX except with 2 Lafayette SK-180 10" Trihelix⊕three way speakers instead of Decor-ette V speaker systems. Shpg. wt., 46 lbs.

21 H 9707CWX Net 187,50 Same as 21 H 9707CWX plus 2 Lafayette famous paten-

ted Eliptoflex speaker enclosures (specify oiled walnut, walnut, or mahogany). Shpg. wt., 94 lbs.

Specify your choice of Pickering V15/AT-1, Shure M7/N21D or Empire 880 diamond needle cartridge.

NEW! LAFAYETTE 40-WATT ALL-TRANSISTOR STEREO AMPLIFIER MODEL LA-340

- Big 40 Watts of Music Power (IHFM)
- Extremely Cool Running
- Instant Warm Up—Plays **Immediately**
- Tape Recording Outputs
- Transformerless Output Circuit For Lower Distor-
- 19 Transistors, 4 Diodes
- Slim-Modern Styling

Low in cost, high in performance! If you wanted the thrilling sound of transistor amplification but found it too expensive -the Lafayette LA-340 is your answer. New slim styling with virtually no heat production lets you place it anywhere in the room. Full range sound is achieved with a frequency response of 30-20,000 cycles. Five pairs of stereo inputs accommodate a tuner, phono using magnetic or ceramic cartridges, tape recorder and auxiliary sources. Accepts 4, 8 or 16 ohm speakers. Terminal board wiring assures mechanical stability. Other features include, front panel stereo headphone jack and switch to silence loudspeakers, and concentric volume control, 2 AC receptacles for convenience in connecting other components. Beautiful gold panel and matching knobs. Size: 1134Wx334Hx10½" deep inclu. knobs and dark brown metal case. For 117V 50/60 cycles AC. Shpg. wt., 10 lbs. Imported Net 79.95



SPECIFICATIONS

Power Output: 40 Watts IHFM; 20 watts IHFM music power per channel. 12 watts continuous sine wave power per channel. Frequency Response: ±1 db 30-20,000 cps. Harmonic Distortion: 1% Hum and Noise: —70db on Tuner, Aux., —56 db Magnetic Phono, Tape Head. Cross talk: 52 db @ 100 cps. Sensitivity: Tuner 0.25 volts, .75 volts Aux. Inputs: 5 pairs—Tape Head, Magnetic Phono, Ceramic Phono, Tuner, Auxiliary. Outputs: 4, 8, 16 ohm, two high impedance for tape recording; Front panel stereo headphone jack. Equalization: NAB; RIAA. Controls: Switches — Power on/off. spkr./Phone, Bass, Treble, Mode (Left, Right Stereo, Rev). 2 AC receptacles, one switched

LAFAYETTE 40-WATT STEREO SYSTEMS WITH MODEL LA-340 ALL-TRANSISTOR STEREO AMPLIFIER

2 ELIPTOFLEX

ENCLOSURES

Lafayette LA-340 40-Watt All-Transistor Stereo Ampli-

Garrard Model 50 4-Speed Record Changer

99 H 0011WX Model LA-340

Wood Base for Changer (Specify oiled walnut or Mahogany)

Pickering V15/AT-1 Diamond Needle Cartridge*
2 Lafayette SK-300 "Decor-ette V" 5 Speaker Slim

Speaker System (oiled walnut)

Complete 40 watt stereo system as above with choice of Pickering V15/AT-1, Shure M7/N21D, or Empire 880 diamond needle cartridge; and with all necessary cables and instructions. Shpg. wt., 64 lbs.

21 H 9785CWX

Same as above except with Garrard AT60 4 speed record changer instead of Garrard Model 50 record changer. Shpg. wt. 66 lbs. 21 H 9786CWX

Same as 21 H 9785CWX except with 2 Lafayette famous SK-58 12" free edge coaxial speakers in 2 Lafayette patented Eliptoflex speaker enclosures. (Specify oiled walnut, walnut or mahogany) instead of 2 Decorette V speaker systems. Shop, wt., 100 lbs.
21 H 9790CWX Net 224.95

Same as 21 H 9790CWX except with Garrard AT60 instead of Garrard Model 50 record changer. Shpg. wt., 102 lbs. 21 H 9792CWX Net 235.50

For Additional Hi-Fi Equipment See Pages 2 & 4-43





Lafayette Cat. No. 651

LAFAYETTE MODEL LA-224 24-WATT STEREO AMPLIFIER



- Stereo Headphone Jack
- Independent Concentric Bass & Treble Controls For Each Channel
- Concentric Volume/Balance Control

FIRST RATE—a Brilliant Stereo Performer . . an amplifier with wide-range frequency response, low distortion, low hum and noise characteristics you can expect of a quality hi-fi amplifier designed for placement anywhere in your home. A full range of control facilities have been provided to assure complete Stereo capability and flexibility. Two dual concentric Bass and Treble controls provide separate and individual tone controls for each channel. A dual concentric volume control acts as an independent level control for vide separate and individual tone controls for each channel. A dual concentric volume control acts as an independent level control for each channel and allows precise channel balancing. Fast, easy operation between Stereo, Reverse Stereo, Monophonic Left channel and Monophonic Right channel is furnished by a Mode switch. A selector Switch furnishes switching from Aux, Tuner or Phono music sources. In addition slide switches are included for: Rumble Filter (off-on) Phase (normal-reverse) and to take full advantage of the front panel Headphone jack a switch is provided for speaker oppone operation. Paired inputs located on the rear panel accomor phone operation. Paired inputs located on the rear panel accommodate any of the ordinary stereo sound sources—inputs are included for magnetic, crystal or ceramic cartridges; Tuner, tape or auxiliary (high output) plus Tape Out jacks for recording through

- Frequency Response: 20-25,000 CPS ± 1 db at 1 Watt
- Hum & Noise—73 db Below Rated Output
- High Sensitivity Allows Use With All Stereo Cartridges

SPECIFICATIONS

Power Output: 12 watts per channel stereo. 24-watts monaural operation. Frequency Response: 20-25,000 CPS ± 1 db at 1 watts. 50-20,000 CPS ± 2db at 12 watts. Hum and Noise: Mag Phone—56db below rated output. Tuner—73db below rated output. Distortion: less than 1% total harmonic distortion at 12 watts (IKC), less than 25% total harmonic distortion at 1 watt (IKC). Sensitivity: Low Level (Mag Input) 5mv at full output, High Level. 6v at full output. Outputs: Dual 8 and 16-ohm impedance speaker outputs. Dual Tape outputs. Tube. Complement: Total of 8, 3-12AX7, 4-6GWB, 1-5AR4.

WATT MATCHED STEREO PHONO LAFAYETTE 24 SYSTEMS WITH LA-224 STEREO AMPLIFIER



Lafayette Model LA-224 24-watt Stereo Amplifier. Garrard Model 50 4-speed Record Changer. Pickering V15/AT-1 Diamond Needle Cartridge*. Wood Base for Changer (Specify Giled Walnut or Mahogany).

2 Lafayette Model SK-265 "Slenderette III" 2-Speaker Slim Speaker Systems. (Oiled

Walnut).

* Specify choice of Pickering V15/AT-1, Shure M7/N21D, or Empire 880 Cartridge.

NEW! LAFAYETTE MODEL LA-260 40-WATT

STEREO AMPLIFIER

\$7.00 Monthly

Concentric Volume, Bass & Treble

 Less Than 1% Harmonic Distortion At Rated Output

• Frequency Response: ± 1 db 40-20,000 @ Rated Output

Front Panel Stereo Headphone and **Tape Output Jacks**

High Sensitivity — Will Accept Majority of Stereo Cartridges

If you are interested in owning an outstanding high fidelity system, then the heart of it should be the Model LA-260. 40 big watts of output gives you full bass, solid midrange and brilliant treble response — even with popular low efficiency speakers. Complete master control facilities include concentric bass, treble and volume controls to customize the sound to suit your taste and listening area. Low cut rumble filter eliminates possible annoving rumble from record players; selector switch gives choice of phono, tuner, tape head and auxiliary program sources. Mode switch (Left, Right, Stereo



SPECIFICATIONS

Music Power Output: 40 watts, 20 watts each channel. Harmonic Distortion: Less than 1% at rated output. Frequency Response: Distortion: Less than 1% at rated output, rrequency response, ±1 db 40-20,000 cps. Hum and Noise: Tuner —75 db; Magnetic phono —58 db. Sensitivity: For full output—Mag Phono 4.5 my; High level: 5 v. Inputs (5 pairs): Tape Head, Mag Phono, ceramic phono, Tuner, Aux. Outputs: 2-pair tape recorder, stereo head-phone jack, 8 and 16-ohm per channel speaker impedance, Tubes: (3) 12AX7, (2) 6BL8, (4) 6BQ5, 5AR4, G234, rectifier.

& Rev) positions. Panel Speaker-Phonesswitch for choice of headphone or loudspeaker listening. Phase switch corrects speaker
phasing without changing wires. In addition tape recorder outputs
are provided on front and rear panels for your convenience. Tape
head inputs permit direct playback from your recorders tape heads.
AC outlet. Ivory and Gold front panel with case. For 115V 60 cycle
AC. Size: 149/4Wx51/aHx11"D. Shpg. wt., 301/2 lbs. Imported.
Net 73.85

LAFAYETTE 40-WATT MATCHED STEREO PHONO SYSTEMS WITH MODEL LA-260 STEREO AMPLIFIER

GARRARD

17450

MODEL 50 ON BASE

- Lafayette LA-260 40-Watt Stereo Amplifier
- Garrard Model 50 4-Speed Record Changer
- Wood Base for Changer (Specify oiled walnut or mahogany)
- Pickering V-15/AT-1, Diamond Needle Cartridge*
 2 Lafayette SK-300 "Decor-ette V" 5-Speaker Slim Speaker Systems (oiled walnut)

Complete featured stereo system above with all necessary cables and instructions plus * choice of Pickering V-15/AT-1, Shure M7/N21D, or Empire 880 diamond needle cartridge. Shpg. wt., 80 lbs.

21 H 9742CWX Same as above but with Garrard Model AT60 4 speed record changer

instead of Garrard Model 50 changer. Shpg. wt., 82 lbs. Net 186.50 21 H 9730CWX

Same as 21 H 9742CWX except with 2 Lafayette SK-180 10" Trihelix 3 way speakers instead of SK-300 speaker systems. Shop wt. 62 lbs. Net 170.50 21 H 9737CWX

Same as 21 H 9737CWX plus 2 Lafayette patented Eliptoflex speaker enclosures. (specify oiled walnut, walnut, or mahogany). Shpg. wt., 110 lbs Net 227.75

Same as 21 H 9738CWX except with Garrard Model AT-60 4 speed record changer instead of Garrard Model 50 changer. Shpg. wt., 112 lbs.



CHOICE OF STEREO CARTRIDGE



Decor-ette V Shure M7/N21D 2 SK-180



GARRARD AT 60 ON BASE

V-15/AT-



Lafayette Cat. No. 651

Lafayette Model LA-250A 50-Watt Stereo Amplifier



FNGINFERED FOR SUPREMACY

ONLY

• 50 WATTS MONAURAL — 25 WATTS EACH STEREO CHANNEL • RESPONSE 15-40,000 ± .5 DB (at normal listening level) • UNIQUE "SEPARATION" CONTROL • PREMIUM CPUT TUBES • SEPARATE BASS & TREBLE CONTROLS • CLUTCH-TYPE VOLUME-BALANCE RESPONSE 15-40,000 CPS . PREMIUM OUT-• 3rd CHANNEL OUTPUT

breathtaking performance

The Stereo 250A . . . a stereo high fidelity amplifier with a high quality of reproduction, remarkable versatility and new distinctive styling—worthy of a place in the finest stereo hi-fi music system. A full range of controls enables system. A full range of controls enables you to enjoy the utmost in listening pleasure in any situation. A unique "blend" control which provides continuously variable channel separation—from full monaural to full stereo—may be used to eliminate the exaggerated channel separation found in some stereo source material. Included is a clutch-type Volume-Balance control for independent or simultaneous control of both channels, concentric Bass and Treble controls which provide inde-pendent tonal control of each channel and a 4-position switch which selects phono, tuner, auxiliary or tape head stereo inputs. Simple slide switches channel reversal and phase reversal-or you can reproduce either

channel through both amplifiers. loudness switch permits the volume-balance control to function as a com-pensated loudness control. The LA-250A also features a 3rd channel out put which may be used to feed a 3rd single channel amplifier and speaker single channel amplifier and speaker to provide a wider sound spread, a Tape Output jack for recording purposes, plus dual terminations for 4, 8 or 16 ohm speakers. Advanced circuitry includes DC operated preamp and tone control tube filaments for humfree operation, 6CW5/EL86 push-pull output tubes, individual bias and balance adjustments on each channel and hum balance control. a hum balance control.

a hum balance control.
Attractive beige vinyl laminated steel case. Handsomely designed gold anodized extruded front panel. Dimensions with legs and knobs. 14½WX 12¾Dx5½"H. Shpg. wt., 28 lbs.
Not 89 SO. 21 H 0901WX Net 89.50 **SPECIFICATIONS**

POWER OUTPUT & DISTORTION: watts—25 per channel ± 1 db at less than 1% Total Harmonic Distortion at 1 KC. Less than 0.5% Total Harmonic Distortion at 1 KC at normal listening level (1 watt); less than 0.5% IM distortion at normal listening level.

FREQUENCY RESPONSE: 15-40,000 cps ± 0.5 db at normal listening level.

HUM & NOISE: 70 db below rated outtust at max volume (bligh level innuts) HUM 2 NOISE: 70 db below rated output at max. volume (high level inputs). SENSITIVITY: for full output high level inputs). SENSITIVITY: for full output high level inputs 0.5V; Mag. Phono 3.5 MV at 1 KC. CHANNEL SEPARATION: Greater than 55 db at 1 KC; greater than 45 db from 20-20,000 cps. IMPEDANCE: 4, 8 and 16 ohms per channel. POWER: 200 watts 110-125 V AC 50-60 cycles.

LAFAYETTE 50 WATT STEREO SYSTEMS FEATURING **MODEL LA-250A 50 WATT STEREO AMPLIFIER**



CARRARD MODEL 50 ON BASE



Empire 880





As Little As \$9.00 Monthly



Garrard Model SO 4-Speed Record Changer

Wood Changer Base (Specify oiled walnut or mahogany)

Pickering V-15/AT-1 Diamond Needle Cartridge 2 Lafayette SK-58 Famous Free-Edge 12" Coaxial Speakers

Complete system as above with choice of Pickering V-15/AT-1, Shure M7/N21D, or Empire 880 diamond needle cartridge. Includes all necessary cables and full instructions. Shpg. wt.,

65 lbs. 21 H 9772CWX

2 SK-58

COAXIAL



..... Net 179.95

ALTERNATE SYSTEMS

Same as 21 H 9772CWX plus 2 Lafayette patented Eliptoflex speaker et (specify oiled walnut, walnut or any). Shpg. wt., 113 lbs. 21 H 9773CWX enclosures

Z1 H 9773CWX Net 238.50 Same as 21 H 9773CWX except with Gar-rard Model AT60 4-speed record changer instead of Garrard Model 50 changer, Shpg. wt. 115 lbs. Net 248.75

SYSIEMS
Same as 21 H 9772CWX except with 2
Lafayette SK-270 Decorette II 5-speaker
slim style speaker (oiled walnut) instead
of 2 SK-58 speakers. Shpg. wt., 91 lbs.
Net 242.75
Net 242.75 Net 242.75
Same as 21 H 9778CWX except with Garrard
Model AT60 changer instead of Garrard
Model 50. Shpg. wt., 93 lbs.
21 H 9779CWX Net 253.50





NEW! LAFAYETTE 70-WATT STEREO AMPLIFIER

MODEL LA-350

Only S8 monthly



Six Pairs of Stereo Inputs For All Sources

Handsome Extruded Aluminum Front Panel

DC On Preamp Filaments For Minimum Hum

Tape Monitor Switch

Stereo Headphone Jack On Front Panel

Separate Channel Tone Controls

The deluxe Lafayette LA-350 is packed with power, features and handsome styling. 70 watts of sonic power produces tonal beauty to match its good looks. Delivers plenty of reserve power to drive even inefficient speakers to full listening levels. Eleven comprehensive front panel controls provide utmost flexibility—assures
"custom" sound reproduction in your home. Six position program
selector enables instant selection of music sources including tape
head inputs for direct playback of tapes from a stereo tape recorder.
Mode switch provides choice of laft or right channels, mix, stereo and reverse channels. Separate bass and treble controls are friction-locked and are adjustable independently or simultaneously. Friction-locked balance controls adjusts each stereo channel for perfect separation. Separate volume control and power switch makes possible undisturbed control settings — simplicity of

operation. Also features: tape monitor switch which lets you listen operation. Also features: tape monitor switch which lets you listen to tapes while recording, rumble filter, loudness switch and a convenient front panel stereo headphone jack with a switch to silence speakers for real private listening. Rugged construction and quality components will provide years of dependable performance. DC on preamplifier filaments and hum adjust controls on both DC and AC filament lines minimizes hum to extremely low levels. Two AC convenience outlets on rear panel apron permits simple connection of tuner and phono AC line. Handsome brushed gold extruded aluminum front panel and knobs with contrasting case fits in any decor. 14% WX51/4HX10"D. For 117V, 60 cycles AC. Imported. Shgs. wt., 30 lbs.

Net 99.50

SPECIFICATIONS

Power Output: 70 watts Music Power: 28 watts per channel continuous, Frequency Response: ±1 db 15 to 30,000 cps at normal listening level. Harmonic Distortion: Less than 1%. Hum and Noise: 55 db down and Phono inputs, 76 db down on auxiliary inputs. Channel Separation: 50 db at 1KC. Inputs and Sensitivity: Tape Head and Phono 1,1.5 my: Phono 2, 6 my: Tuner, 200 my; Auxiliary 1, 10 my; Aux. 2, 750 my. Output Impedances: 8 and 16 ohms, Tape Outputs: 2 pair, Tubes: (3) 12AX7/EGC83, (2) 6ANB, (4) 7198A; 5 diodes. 2 AC Outlets, 1 switched.

LAFAYETTE 70-WATT MATCHED STEREO SYSTEMS WITH MODEL LA-350 STEREO AMPLIFIER

AS LOW AS

17450

GARRARD MODEL 50 ON BASE

Lafayette LA-350 70 Watt Stereo Amplifier Garrard Model 50 4-Speed Record Changer Wood Base for Changer (Specify oiled walnut or mahogany) Pickering V15/AT-1 Diamond Needle Cartridge*

2 Lafayette SK-300 "Decor-ette V" 5 Speaker Slim Speaker Systems (Oiled Walnut)

Complete featured system as above with your * choice of Pickering V15/AT-1, Shure M7/N21D, or Empire 880 diamond needle cartridge. and with all necessary cables and instructions. Shpg. wt., 30 lbs. 21 H 9601CWX Net 184.50

ALTERNATE SYSTEMS

	Garrard Chang-				Speaker/ Speaker	Speaker	Wt.	
System	Amp	er	Base	Cartridge	System	Cabinet	Lbs.	Net
21 H 9602CWX	LA-350	AT60	+	Choice of	2 SK-300	Decor-ette V*	81	194.50
21 H 9604CWX	LA-350	50	+	Pickering	2 SK-58		67	174.50
21 H 9605CWX	LA-350	50	+	V15/AT-1	2 SK-58	2 Eliptoflex‡	115	232.25
21 H 9606CWX	LA-350	AT60	+	or Shure	2 SK-58		69	184.50
21 H 9607CWX	LA-350	AT60	+	M7/N21D	2 SK-58	2 Eliptoflex‡	117	242.95
21 H 9613CWX	LA-350	50	+	or Empire	2 SK-275	Decor-ette III*	115	259.50
21 H 9614CWX	LA-350	AT60	†	880	2 SK-275	Decor-ette III*	117	269.95

Specify oiled walnut or mahogany. Oiled Walnut, walnut or mahogany.

Oiled walnut only.

Any of above systems with addition of Lafayette MODEL LT-250 FM Multiplex Stereo Tuner add \$74.25 to price of system and 13 lbs to shpg. wt. Any of above systems with addition of Lafayette MODEL LT-325 AM-FM Multiplex

Stereo Tuner add \$82.50 to system price and 17 lbs. to shpg. wt.

Hi-Fi Systems are Available on Easy Pay Plan-See Center Insert A



GARRARD MODEL

AT 60 ON BASE

2 SK-300

11

LAFAYETTE 10-WATT STEREO AMPLIFIER MODEL LA-214



- 5 Watts of Power Each Channel
- Frequency Response 50 to 20,000 cps
- Front Panel Stereo Phone Jack
- **Dual Concentric Bass and Treble Controls**
- Rumble Filter
- Inputs for Ceramic and Crystal Phono, Tuner, High Level Tape
 Beautifully Styled

The Lafayette model LA-214 is a complete amplifier/preamplifier in a highly styled metal cabinet. It will faithfully reproduce such program sources as stereo or monophonic record changers, tuners, and stereo tape player. Features concentric bass and treble controls, rumble filter and front panel jack for stereo headphones. Other controls include Power/on; Volume, Mode selector (4 positions); 3-position program selector and Speaker/Phone switch. On rear panel 8 or 16 ohm speaker impedances may be selected and there is a handy speaker phase switch. Also included are a hum adjust and Acconvenience outlet. Rugged hand wired circuit is fused for maximum component protection. Power output: 5 watts music power each stereo channel or 10 watts if used monophonically. The amplifier is compact enough to fit in any convenient location such as a shelf, table or bookcase. For 105-125 volts 50/60 cycles AC only. Tube complement: 2-6805, 12AX7, 6CA4. Imported. Size 124/2Wx5Hx734"D. (with legs). Shpg. wt., 15 lbs.

10-WATT MATCHED STEREO PHONO SYSTEMS with LA-214 AMPLIFIER



COMPLETE SYSTEM As low

Lafayette LA-214 10 Watt Stereo Amplifier

Lafayette-Webcor 4-Speed Record Changer with Wide-Range Ceramic Turnover Cartridge with Synthetic Sapphire Stylus and LP Diamond Stylus Wood Base for Changer (Specify Mahogany or Walnut) Two Lafayette SK-181 "Minuette" Speaker Systems (Walnut)

Complete system above with all necessary cables and interconnecting instructions. Shpg. wt., 43 lbs. 21 H 9927CWX

Same system as above except with two Lafayette oiled walnut finished Minuette speaker systems instead of walnut Minuette systems. Shpg. wt., 43 lbs. Net 90.50

Same as above except with two Lafayette SK-265 SLENDERETTE III oiled walnut 2-speaker 2-way slim speaker systems instead of Minuette speaker systems. Shgg. wt., 62 lbs.

21 H 9929CWX Net 96.50

LAFAYETTE 15-WATT MONAURAL HI-FI AMPLIFIER



- Hum & Noise 75 db Below Rated Output
- Power Output 15-Watts
- Sensitivity: 3 mv. Magnetic Phono
- 5 Input Selections
- Frequency Response: 30-20,000 cps ±1.5 db At Normal Listening Level

The New Lafayette LA-218 is a perfect combination of outstanding performance, beautiful styling, and low price. It can easily be integrated into a fully equipped hi-fi system utilizing the 5 input selections. Because of its high input sensitivity, either magnetic or ceramic cartridges may be used, achieving full power output. A tape deck, even without playback preamplifiers, may be used in direct recording through tape output jack and in playing back through tape-head input. Also may be used with AM, FM or TV tuner music sources. A loudness control compensates for the loss of low frequencies when listening at low levels—you do not have to listen at high volume level to achieve full tonal quality. A scratch filter is useful in reducing noise of dusty or damaged records. Headphone jack is provided for private listening. Individual bass and trebte controls each provide a boost of 10 db and cut of 14 db for adjusting to individual listening areas and tastes. Full 15 watts is sufficient power to adequately drive most speaker systems. Perfect for use as a second amplified a converting to secret of the starting out monophonically and adding stereo at a later date. Engineered to include every practical feature at a low price. Beautifully styled in popular low silhouette enclosure and will add beauty to any room decor. Size: 124/4Wx51/4Hx81/4*D. Shpg. wt., 18 lbs. Imported.

Net 44.50

SPECIFICATIONS:

Power Output: 15-watts; Frequency response: 30-20,000 cps ±1.5 db (at normal listening level). Input Sensitivity: High level .23V, level). Input Sensitivity: High level .23V, Magnetic phono 3 mv. Hum and Noise Level: Volume control at maximum—High level inputs 75 db below rated output, Magnetic phono and tape head inputs 58 db below rated output. Harmonic distortion: less than 1% at full power output. Outputs: 8 and 16 ohm impedance speaker outputs: tape output The complement: 2-12°27, 2-6805. 1-12AU7 1 6CA4.

AFAYETTE 15-WATT MATCHED HI-FI PHONO SYSTEMS

Lafayette LA-218 15-Watt Complete Integrated Monaural Amplifier.

Garrard Model 50 4-Speed Record

Wood Base for Changer (Specify Mahogany or Oiled Walnut).

Pickering V-15/AT-1 Diamond Needle Cartridge

Lafayette SK-265 SLENDERETTE III, 2-Speaker 2-Way Slim Speaker System (oiled walnut).

Above system complete with choice of Pickering V15/AT-1. Shure M7/N21D, or Empire 880 diamond needle cartridge plus interconnecting cables and necessary instructions. Shpg. wt., 50 lbs.

21 H 9930CWX Net 99.95

Same as 21 H 9930CWX system except with Lafayette SK-300 Decorette V 5-Speaker Slim Speaker System (oiled walnut) instead of SK-265 speaker system. Shpg. wt., 52 lbs. 21 H 9931CWX Net 114.95

Same as 21 H 9931CWX except with Lafayette famous 12" Free-Edge Coaxial Speaker SK-58 instead of SK-300 speaker system. Shop. Wt., 46 lbs.

21 H 9932CWX Net 109.95

21 H 9933CWX

Same as 21 H 9932CWX system above plus Lafayette patented Eliptoflex speaker en-Lafayette patented Eliptoflex speaker en-closure (specify oiled walnut, walnut, or mahogany), Shpg. wt., 70 lbs. Net 138.95

CHOICE OF STEREO CARTRIDGE **Pickering** Empire Shure M7/N21D V-15/AT-1 880 GARRARD MODEL 50 AS LOW AS SK-58 SK-265 Slenderette III SK-300 **ELIPTOFLEX®** Decor-ette V

LAFAYETTE AM/FM STEREO TUNER

Model LT-325



Features New Audible Tone Stereo Search System. Two 3-Gang Tuning Condensers With added Tuned RF Stage For Superb Sensitivity and Selectivity.

93°5

\$8.00 Monthly

● 20-TUBE PERFORMANCE—12 TUBES PLUS TUNING EYE AND RECTI-FIER AND 9 DIODES ● MPX SEPARATION 38 DB @ 400 CPS ● LESS THAN 1% DISTORTION ● DUAL TUNED CASCADE LIMITERS AND WIDE BAND RATIO DETECTOR ● GROUNDED GRID RF FRONT END FOR LOW NOISE ● YARIABLE AFC CONTROL ● FLYWHEEL TUNING ● STEREO NOISE FILTER SWITCH ● AUTOMATIC STEREO MODE INDICATOR

Simplicity, Flexibility and Superb Styling have been carefully integrated in this quality tuner. Offering unlimited versatility, the LT-325 features new Automatic Stereo Monitor which shows automatically when you are tuned to a stereo broadcast. Tuning eye helps to tune all stations accurately. New "Stereo Search" circuitry provides an audible signal through both left and right channel speakers to let you know when you have tuned to a station broadcasting in FM stereo multiplex. Its new low silhouette enclosure can be placed proudly on ar open bookshelf or custom installation anywhere in your home. On the front panel there is a mode selection

PECIFICATIONS

Frequency Response: FM and FM stereo 15-15.000 cps ± 1 db. FM Stereo Separation: more than 38 db @ 400 cps. Harmonic Distortion: FM and FM Stereo less than 1% @ 400 cps. MPX Noise Filter: —7db @ 10KC. SCA Rejection: better than 50 db. Tuner Sensitivity: FM 2 μν for 20 db of

S/N. Variable FM AFC lock control, stereo tone search. Tubes: 6BE6, (3) 6BA6, (3) 6AU6, EM84, 6AV6, 6X4, 6BL8/ECF80, (2) 6A08/ECC85, 12AX7/ECC83, Power: 117V 50/60 cps AC, 60 watts. Dimensions: 143/4Wx476Hx91/2"D. Legs add 3/4" to height. \$hpg. wt., 171/-

LAFAYETTE FM STEREO TUNER Model LT-250



 New Audible Stereo Search System To Locate Stations Broadcasting In FM Multiplex Stereo
 3-Gang Tuning Condenser Provides A Tuned RF Stage For Excellent Sensitivity and Selectivity.

8395

\$7.00 Monthly

● STEREO SEARCH SYSTEM ● MPX NOISE FILTER ● BUILT-IN MUL-TIPLEX CIRCUIT WITH 38 DB SEPARATION @ 400 CPS. ● RATIO DE-TECTOR AND DUAL TUNEO LIMITERS ● AFC SWITCH ● STEREO MODE INDICATOR ● FREQUENCY RESPONSE 20-20,000 CPS ±1 DB ● LOW SILHOUETTE STYLING

TRULY remarkable, quality performance and styling that will delight both your eye and your ear. Features the new stereo search control. When this circuit is energized by a station broadcasting in FM multiplex stereo, it sends an audible signal through both the left and the right channels. Tuning eye facilitates accurate tuning of all signals with pin point sharpness. Automatic stereo indicator lights when control is set to the FM stereo position. Engineered to provide high-quality FM and FM stereo reception, the LT-250 has a grounded grid low noise front end. The multiplex circuit provides a stereo separation of 38 db at 400 cps. with less than 1% distortion. Front panel controls consist of the Mode selector: (mono, stereo search,

FM stereo, FM stereo noise filter); see-saw AFC and power switches, and main tuning. Stereo dimension control to custom blend stereo reception (in-rear). Flywheel tuning control gives velvet smooth tuning action. Two stereo output jacks on rear panel. Tube complement: (2) 6BA6, (3) 6AU6, EM84, 6AV6, 6BL8/ECF80, (2) 6AU6/ECC85, 12AX7/ECC83 and 6X4. Seven Germanium diodes and one Silicon diode. Gold finish extruded aluminum front panel with complementary case and metal knobs. Complete with cage and legs. Dimensions: 1234Wx47/aHx91/2"D, For 117V 50/60 cps AC. Imported.
99 N 0002WX Shpg. wt., 13 lbs. Net 83.95

NEW! LAFAYETTE AM/FM TUNER MODEL LT-100



Carefully designed and engineered for outstanding performance, the new LT-100 offers many fine features including an FM multiplex output jack for connection to a multiplex adapter and smooth, easy-to-use flywheel tuning. Front Panel Controls: 4-position selector switch including FM AFC; Tuning. Has built-in AM ferrite loop antenna and rear apron terminals for external AM and FM antennas. Large, Illuminated slide rule dial is easy-to-read for accurate tuning. FM Specifications: Sensitivity, 3-µv; Frequency Response, 20-20,000

cps ± 1 db; Harmonic Distortion, less than 1% @ 400 cps. Attractively styled low silhouette metal enclosure has brown finish to contrast with gold front panel with brown knobs. Complete with cage and legs. Overall Dimensions: 12%Wx4%Hx9½"D. For 110-125 volts, 50/60 cps AC. Power consumption 40 watts. Shpg. wt., 15 lbs Imported.

• 10-Tube Performance—7 Tubes (3 Dual Purpose) • Attractive Low

99 H 0006WX AM-FM Tuner

re Lt-80B FM Tuner

Silhouette Styling-Complete with Case.



A BUDGET PRICED TUNER PACKED WITH FEATURES

Armstrong Circuit Foster-Seeley Discriminator and Dual Tuned Limiters • AFC • AFC Defeat • Extremely Sensitive — 1.5 µv for 20 DB Quieting • 10-Tube Performance — 8 Tubes (2-Dual Purpose) • 20-20,000 Cycles ± ½ DB • Superb Low Silhouette Styling • 3-Gang Tuning Condenser • Tuned Grounded Grid RF Stage

\$5 monthly

WITH MULTIPLEX JACK FOR MULTIPLEX ADAPTER

Designed and constructed of the finest components, with jewel like precision (each unit is hand wired). Engineered to provide maximum FM versatility, the LT-80B is provided with a multiplex output jack to accept a stereo FM multiplex adapter. Flywheel action tuning control. Tube complement consists of 2-5AQ8, 2-5BA6, 2-6AU6, 1 each 6AL5 and 6X4. Handsome low silhouette enclosure will do Justice to any decor. Beautifully finished in gold and white with contrasting black dial face. Complete with case and legs. Dimensions: 1136Wx8Dx456Th. Imported. 99 H 0050WX Stereo Tuner

MODEL KT-220



Separation 30db at 400 cycles

 Self-powered
 Ideal for Lafayette tuners equipped with MPX output jacks

Enjoy thrilling FM Stereophonic sound from any recent Lafayette Tuner or any other quality wide-band FM or FM-AM tuner equipped with Multiplex jacks by simply adding this low-cost Lafayette Multiplex adapter kit. Engineered for anyone to build and operate, the KT-220 is easily connected to your tuners built-in multiplex output and special instructions are provided for connection to tuners without MPX output jacks. Coils are pre-aligned and only minimum adjustments are necessary. Self-powered, the unit may be hidden out of sight or installed remotely from your tuner.


Specifications: Separation—30db at 400 CPS. Distortion—below 1%. Centrels: Noise filter on-off, power on-off with pilot light, separation control (rear). Front panel is finished in beige and ivory trim with contrasting beige and brown cabinet. Size 8½/2Wx4%/2Dx4%/2H for 110-125 voits, 60 cycle AC.

Net 19.50

19 H 0907 Shpg. wt., 4 lbs.

..... Net 19.50

FISHER 500B 65 WATT FM STEREO RECEIVER



This magnificent FM Stereo Receiver has complete facilities for handling every possible stereo and monophonic program source through its stereophonic master control center, powerful 55 watt stereo amplifier, and super sensitive FM Stereo Multiplex Tuner. Features Stereo Beam, an exclusive Fisher invention that tells you instantly whether or not an FM Station is broadcasting in stereo multiplex. Completely eliminates the "try and find" stereo multiplex broadcast problem. A switchable filter reduces hiss and and ind" stereo multiplex broadcast problem. A switchable filter reduces hiss and background noise on stereo programs without affecting the frequency response. SPECI-FICATIONS: Amplifier distortion less than 0.5%. Frequency response 25-25,000 cps ± 1.5 db; FM sensitivity 0.7 μ into 72 ohm load; IHFM sensitivity 2.2 μ V. S/N & hum 70 db. IF bandwidth 190 Kc; channel selectivity 52 db; FM response 30-15,000 cps; Tubes: 4-ECC85, 6-6AU6, 4-12AX7. 2-7591, 2-EM84A, IN-542, plus special multiplex tubes. Size: 174/2Wx5%Hx1344"D. Shpg. wt., 35 lbs.

21 H 3651WX

Walnut Wood Cabinet for Model 500B, Shpg. wt., 6 lbs.

Net 234.95

Net 22.45.

NEW Low Price

Check These Outstanding Features and Technical Specifications.

● Exclusive Stereo Beam ● Tuning Indicator ● Linear Logging Scale ● CONTROLS: MPX Filter, Station Selector, Dual Bass and Treble, Six-Position Selector (Tape Head, Phono, MPX Stereo, FM, Aux, Tape), Balance, Volume. SWITCHES: High Filter, Low Filter, Tape Monitor, Mono-Stereo, Channel Reverse, Loudness Contour ● Low-level audio tube filaments heated by a separate DC supply ● Magnificent architectural brass-finish control panel. FM TUNER Wide-band design. Sensitivity: 0.7 micro-

rm turker wide-band design. Sensitivity: U.7 microvolts (72 ohms, 20 db. quieting), 2.2 microvolt (IHFM Standard.) Four IF Stages. FM-Stereo separation, 35 db. AMPLIFIER: Power output, 65 Watts. Harmonic Distortion, 0.5%. Hum and Noise, —85 db. RIAA sensitivity, 3.3 mv. Aux. Sensitivity, 230 mv. Output Impedances: 4 8 and 16 ohms. Impedances: 4, 8 and 16 ohms.

65 WATT FM STEREO PHONO SYSTEMS FEATURING "FISHER 500B"







FAMOUS SELLING STEREO SYSTEM

Now everybody can enjoy the thrill of beautiful Now everybody can enjoy the thrill of beautiful music reproduction at only a moderate cost with this outstanding FM Stereo Phono System. System includes: Fisher 500B 65 watt FM Stereo Receiver less case, Garrard Model 50 4 speed automatic Turntable with eil walnut wood base, choice of Pickering W45/AT-1, Empire 880 or Shure M7/N21D stereo cartridge, and lastly, 2 of Lafayette's best selling speaker systems—the Decorette V—featuring 5 specially engineered speakers designed to achieve optimum performance in a thin type enclosure only 416 performance in a thin type enclosure only 41/2 inches in thickness.

21 H 9625WX Shpg. wt., 82 lbs. Net 314.95 Same system as above but with Garrard AT60 4 speed Automatic Turntable in place of Garrard Model 50, Shpg. wt., 85 lbs.

21 H 9626WX

CUSTOM STEREO SYSTEM

Now for the audio enthusiast who desires to mount his components in a custom cabinet— Lafayette offers this exciting FM Stereo System. System includes Fisher 500B 65 watt FM Stereo Receiver less case, Garrard Model AT60 4 speed automatic Turntable with oil walnut wood base, choice of Pickering V15/AT-1, Empire 880, or Shure M7/N210 stereo cartridge, and 2 famous Lafayette SK 210 3 way speakers with 21/4 lb. magnet.

DELUXE STEREO SYSTEM

For the audio enthusiast who wants a deluxe For the audio enthusiast who wants a deluxe FM Stereo-Phono System. System includes Fisher 500B-65 watt FM Stereo Receiver, Superb Garrard Model A70 4 speed automatic Turntable with oil wainut wood base, choice of new Pickering V15/AM-1 or Empire 880P Stereo cartridge and 2 of Lafayette's finest Bookshelf speaker systems—the Decorette III which features a 12" polysfam woofer with 1 lb magnet 8" mid poly-foam woofer with 1 lb. magnet, 6" mid range, and 3½ super tweeter mounted in a specially engineered "Tuned" enclosure with Tube-Type Duct. Enclosures are finished in oil walnut Shpg. wt., 128 lbs. 21 H 9629CWX

FISHER X-101-C 60 WATT STEREO AMPLIFIER



This deluxe 60 watt Stereophonic Master Audio Control Amplifier features the exclusive "New Look" by Fisher, an elegantly styled, functional, operational, panel. Only the Program Selector, Mode Selector and Volume control are in view. The other infrequently used controls are hidden behind a pull-down panel. Offers 30 Watts of music power output per channel, center channel, output, 14 inputs (2 phonos), output selector switch, front panel jack, loudness control, jack for "SpaceXpander." Exclusive Fisher Direct-Tape-Monitor, 10 tubes, 2 silicon rectifiers. Response 20-20,000 cps ±1 db. Hum and noise 88 db below rated output. Harmonic distortion, 5% at rated output. 1% intermodulation @ rated power. Size 1546Wx41% Hx1242"D. Less cabinet. Shpg. wt.,

21 H 3603WX \$7 monthly 21 H 3609W MC-2 Metal Cabinet for X-101-C. Shpg. wt., 9 lbs, 21 H 3610W Walnut Wood Cabinet for X-101-C. Shpg. wt., 7 lbs.

Net 14.36 22,46

A Deluxe 60 Watt Stereophonic Master Audio Control -Amplifier at only

139⁵⁰

OUTSTANDING FEATURES

- 60 Watts Power Output
- Beautiful Styling
- **Oirect Connection of Center** Channel or Extension Speaker

60 WATT STEREO-PHONO SYSTEMS FEATURING FISHER X-101-C

SHELF SYSTEMS—As Low As 206.50



MODEL SK270 DECORETTE II

System I—A moderately priced 60 watt Stereo-Phono system enhanced by the elegant styling of the Fisher X-101-C 60 watt stereo amplifier. The other fine components which complete this system are: Garrard Model 50 4-speed automatic turntable with oil walnut base, choice of Pickering V-15/AT-1, Shure M7/N21-D, or Empire 880 stereo cartridge, and a pair of Lafayette Slenderette III slim. type, 2-speaker-2-way systems with oil coat finish. Shpg. wt., 55 lbs.

ATBO

21 H 9634CWX As little as \$10 monthly . Net 206.50 System II—Same as above except with Garrard AT60 4-speed auto-matic turntable in place of Garrard 50. Shpg, wt., 57 lbs.

matic turntable in place of Garrard 50. Snpg, w., 57 18 21 H 9635CWX As little as \$10 monthly Net 219.50 System III—Same as 21 H 9634CWX except with a pair of Lafayette Decorette II, 5-speaker—3-way systems with oil walnut finish in place of Lafayette Slenderette III speaker system. Shpg. wt., 63 ibs. As little as \$14 monthly. Net 286.50 wt., 64 lbs. Net 299.50

Lafayette Ili-Fi Systems Are a Sound Investment

CUSTOM SYSTEMS—as low as 232.50



SK58 CHOICE OF STEREO CARTRIOGE



Net 139.50






Garrard Model AT60

OPTIONAL COMPONENTS





System I-A superb custom 60 watt stereophonic system featuring the Fisher X-101-C 60 watt stereo amplifier, Garrard Model AT60 4-speed automatic turntable with oil walnut base, choice of Pickering V-15/AT-1, Shure M7/N21-D, or Empire 880 stereo cartridge, and lastly, a pair of world-famous Lafayette SK-58 12" coaxial speakers with 146 lb. magnet. Shpg. wt., 63 lbs.


21 H 9638CWX As little as \$11 monthly. Net 232.50
System II—Same as above except with deluxe Garrard type A70
4-speed automatic turntable in place of Garrard AT60. Shpg. wt., 70 lbs.

21 H 9639CWX As little as \$12 monthly Net 252.50
System III—Smae as 21 H 9638CWX but with SK-58 speakers mounted in a pair of patented Lafayette Elliptoflex enclosures with oil walnut finish. Shpg. wt., 111 lbs.
21 H 9640CWX As little as \$14 monthly Net 292.50
System IV—Same as 21 H 9640CWX except with deluxe Garrard type

A70 4-speed automatic turntable in place of Garrard AT60. Shpg. wt., 118 lbs.

21 H 9641CWX As little as \$15 monthly Net 312.50

FISHER Model X100 40 Watt Stereo Amplifier



LOOK AT OUR LOW, LOW, PRICE

OUTSTANDING **FEATURES**


The X100 40 watt stereo integrated amplifier is an excellent buy for the audio enthusiast with a limited budget. This fine stereo amplifier offers simplicity of operation and a full complement of control facili-ties for maximum flexibilities. OUTSTANDING TEATURES Controls: Balance, Dual Bass and Treble, Five-Position Mode Selector, Five-Position input Selector including two positions for magnetic cartridges, High and Low Filter Switches and Loudness Contour. SPECI-FICATIONS: Power Output 40 watts. Harmonic distortion 0.5%. Hum and noise 90 ob before rated output. Frequency Response 20-20,000 cps, within 1 db. Sensitivity (low level inputs) 3.5 my, (high level inputs) 180 mv. High filter 12 db/octave above 5 Kc. Low filter 12 db/octave below 50 cps. 11 tubes. DIMENSIONS: 1546Wx41% Hx11% D. Shpg.

wt., 22 lbs. less cabinet 21 H 3652WX Model X100 21. H 3609W Metal Cabinet for X100 Net 14.36 Oil Walnut wood cabinet for X100

Front panel has sixteen controls and switches to permit wide flexibility in either monophonic or stereophonic operations

- Power output—40 watts
- Center channel output
- Full Tape Recording Facilities

40 Watt Stereo Phono System Featuring the Fisher X100







SYSTEM I—A complete 40 watt stereo phono system for the music lover at so little in price—System includes Fisher X100 40 watt stereo integrated amplifler, Garrard Model 50 4 speed automatic turntable with oil wainut wood base, choice of Pickering V15/AT-1 Empire 880, or Shure M7N21D Stereo cartridge, and lastly, a pair of famous Lafayette "Slenderette" III Slim 2-speaker 2 way speakers systems with oil wainut finish on 4 sides.

Net 164.50 21 H 9511CWX Shpg. wt., 66 lbs.

SYSTEM II-same as above except with Garrard Model AT60 automatic Turntable in place of Garrard Model 50.

21 H 9512CWX Shpg. wt., 68 lbs. SYSTEM III—same as 21 9511CWX except with a pair of Lafayette Decorette V speaker systems in place of Lafayette Slenderette III Speaker Systems. 21 H 9513CWX Shpg. wt., 78 lbs.

Net 194,50 SYSTEM IV—same as 21 9513CWX except with Garrard Model AT60 automatic Turntable in place of Garrard Model 50. Net 209.50

21 H 9514CWX Shpg. wt., 80 lbs. .../..... 18 Lafayette Cat. No. 651

CUSTOM SYSTEMS as low as 18450










M7/N21D OPTIONAL COMPONENTS

X100 (less cabinet)





SYSTEM I—A popular priced 40 watt stereo phono system for custom installations features the Fisher X100 40 watt stereo integrated amplifier, Garrard Model 50 4 speed automatic turntable with oil walnut wood base, choice of Pickering V15AT-1, Empire 880, or Shure M7N21D stereo cartridge, and lastly a pair of the world famous Lafayette SK58 12" coaxial speakers with 1¼ magnets.

21 H 9515CWX Shpg. wt., 61 lbs. Net 184.50 SYSTEM II—same as above except with Garrard Model AT60 automatic Turntable in place of Garrard Model 50.

21 H 9516CWX Shpg. wt., 63 lbs. SYSTEM III—same as 21 9515CWX but with SK58 speakers mounted

in a pair of 2 famous Lafayette patented Eliptoflex Enclosures with Oil Walnut finish. 21 H 9517CWX Shpg. wt., 131 lbs.

SYSTEM IV—same as 21 9516CWX but with SK58 speakers mounted in a pair of 2 famous Lafayette patented Eliptoflex Enclosures with Oil Walnut finish. 21 H 9518CWX Shpg. wt., 133 lbs. ..

Hi-Fi Systems are Available on Easy Pay Plan-See Center Insert A

QUALITY 80-WATT FM STEREO PHONO SYSTEMS FEATURING THE SHERWOOD S-8000 IV FM STEREO RECEIVE




CHOICE OF STEREO CARTRIOGE


Pickering Empire 880

Shure M7/N210

OPTIONAL SPEAKER SYSTEM



COMPLETE SYSTEM AS LOW AS





Complete system includes: the excellent Sherwood S-8000 IV 80-watt stereo receiver which features 40-watts output from each stereo channel. The S-8000IV combines a powerful Stereo amplifier-preamp and FM Stereo Tuner on one complete chassis. System also includes the famous Garrard AT60 4-speed automatic stereo record changer with an oiled wainut base and your choice of one of the following deluxe stereo cartridges with .7 mil diamond needle—Pickering V-15/AT-1, Empire 880, or Shure M7/N21D. A magnificent pair of Lafayette Decorette V slim speakers completes the system. The Decorette V speaker systems features 3 perfectly matched speakers offering brilliant sound reproductioun—housed in a superbly styled oil wainut veneer enclosure with a decorative wainut picture frame molding bordering a fine cane grille. Shop, wt. 84 lbs.

a fine cane grille, Shpg. wt., 84 lbs. 21 N 9985CWX System Same quality system as above except with 2-speaker systems featuring the world famous Lafayette SK-58 12" coaxial speakers in patented oiled walnut Lafayette Eliptoflex enclosures in the place of the decorette V speaker systems. Shpg. wt.,

21 H 9984CWX

Net 459.65

NEW SHERWOOD S-9000 150-WATT SOLID STATE STEREO INTEGRATED AMPLIFIER



As Low As \$14 monthly

- Transformerless Outputs
- 150 Watts (75 Each Stereo Channel)

A new 150-watt solid state integrated stereo amplifier provides audio A new 150-wart solid state integrated stereo amplifier provides audio power output on one compact chassis. Special circuitry prevents damage to costly transistor components due to a shorted output or overheating. Silicon transistors mounted on glass-epoxy. Circuit boards are used throughout the audio stages. Output circuits are transformerless for optimum transient response and overall stability. Transformeriess for optimum transient response and overall stadinty. Front-panel controls and switches include ganged stereo bass, treble, loudness, balance, selector, mode, phono level, scratch filter, rumble filter, loudness contour, phase, tape monitor, and headphone jack, Frequency response: 20 to 20,000 cps \pm 0.5 db at 50 watts per channel. Num and noise down 80db below 50-watt output. Output impedance: 4 and 16 ohms. Inputs: 2 phono, 2 tape head, 2 aux., 2 tuner. Less cabinet. Size 14x4x12½". Shpg. wt., 26 lbs.

Net 299 50

MCINTOSH PROFESSIONAL MODEL MR67 STEREO FM TUNER

- Nuvistor RF, 4 IF Stages
- and 2 Limiters
 "Panloc" For Professional Built-in Installation



Signal Strength/Multipath Distortion Indicator

For superb monophonic or stereo FM reception. Features "Panloc" system for a professional built-in installation with ease of operation and maintenance. Highly sensitive circuitry offers cascode (2 tube) RF amplifier with high gain 6054 nuvistor in first stage. 4 IF stages and 2 limiter stages with AGC used to insure limiting only in the limiter stages. High (2.5 µV) sensitivity reduces adjacent station interference. Switchable front panel indicator is used for both precise tuning control and Indication of multipath distortion which

may occur in some locations.

Response 20-20,000 cps. Distortion: less than 0.5% at 100% modulation. Hum: 70 db down. For 105-125V 50/60 cycles AC. 16Wx 5%,HX13"D. Less cabinet. Shpg. wt., 33 lbs.

21 H 5107WX Net 299.00

Wood Cabinet for MR-67, Oiled walnut. Shpg. wt., 11 lbs.


Michigan Model Ma-230 Dual 30-Watt Stereo Integrated Amplifier **FEATURES**

Exclusive McIntosh Silicon Planar Solid State Preamplifier

Superb Dual 30-Watt Stereophonic Tube Power Amplifier

True musical enjoyment is yours with this professional quality combination preamplifier and power amplifier. Exclusive silicon planar pre-amplifier uses 12 solid state devices mounted on military spec, printed amplifier uses 12 solid state devices mounted on military spec. printed circuit board. Mas only 1/10 of 1% distortion. Power amplifier features 30 watts per channel continuous or 44 watts IHFM music power. Distortion is less than 0.5% at rated output. Response: -0.5 db 20-20,000 cycles. Hum and Noise: 75 db down on high level inputs. 65 db down on low level inputs. Controls include: dual concentric bass and treble; volume, balance, 6 position input selector. Mode selector. Switches: Equalization. Tape monitor, Phase, Speaker on-off, power on-off, Low and High frequency filters and loudness. Also features exclusive "Panloc" system for custom mounting, permits unit to slide in or out with safety lock. 2 convenient front panel stereo headphone jacks for private siereo listening. Size: 16Wx57%Hx15W. Anodized gold and black finish. For 105-125V. 60 cycles AC. Shpg. wt., 56 lbs.

21 H 5115WX Model MA 230 Net 349.00 21 H 5116W Cabinet Oiled Walnut for MA 230, 11 lbs. Net 29.00



NEW MA-230 less case

DELUXE SCOTT STEREOPHONIC AMPLIFIERS

NEW SCOTT MODEL 233 66-WATT STEREO INTEGRATED AMPLIFIER



 Quality Sound—Modest Price 5995 • Front Panel Stereo Headphone Jack • Center Channel Output • Subsonic Filter

Has quality and dependability equal to Scott's best, but lower power at a moderate price. Heavy-duty output transformers provide superb bass response with the majority of inefficient speaker systems. Outstanding features and specifications include: Alf-aluminum chassis and DC operated heaters for lowest hum. Mode Selector for monophonic, stereo, reverse stereo and left or right Selector for monophonic, stereo, reverse stereo and left of right channel; Equalizer Switch for tape or RIAA; Scratch Filter; Separate Bass and Treble Tone Controls for each channel; Loudness/Volume Control; Speakers/ Earphones Jack and switch to turn off speakers for private listening; High and Low Magnetic Phono Input; Tape Head Input; Center Channel Power Output drives speaker directly; Speaker Phase Switch. Response ±1db, 20-20,000 cps. Power output: 66 watts (IHFM). Harmonic Distortion: 0.8%. Hum and Noise: —80 db. Size: 15wx43/Hx131/4"D. Shpg. wt., 26 lbs. 21 H 6040WX Less Case Net 159 95

Metal Enclosure for 233. Shpg. wt:, 5 lbs. Net 12.50 21 H 6009W

Walnut Wood Case for 233D. Shpg. wt., 6 lbs. Net 22.50 21 H 6024W

STEREO SYSTEMS FEATURING SCOTT 233



COMPLETE SYSTEM AS LOW AS

CHOICE OF STEREO CARTRIDGE


Empire

Pickering

V15/AT-1



OPTIONAL SPEAKERS



2 SK-58 Speakers

Shelf System consisting of Scott 233, 33 watt stereo integrated amplifier, less case, quality Garrard Model 50, 4 speed automatic changer with oil walnut wood base. Choice of one of three deluxe stereo cartridges Pickering V15/AT-1, Empire 880, or Shure M7/N210 Stereo Cartridge; a pair of Lafayette Slenderette III slim 2-speaker 2-way systems in oil walnut enclosures.


Shure

M7 N21D

21 H 9976CWX Shpg. wt., 68 lbs. Custom Stereo System-same system as above except 2 famous Lafayette SK-58 12" coaxial speakers in place of Lafayette Stenderette HI Shelf speakers.

21 H 9977CWX Shpg. wt., 64 lbs.

SCOTT MODEL 299D 80-WATT STEREO INTEGRATED AMPLIFIER



5 • Frequency Response 20-20,000 cps ±1db • Front Panel Stereo Headphone Jack • Center Channel Output • Subsonic Filter

Combines the ultimate in Scott quality, dependability and per-formance. Important specifications and features include: Pickup Switch allows choice between two magnetic pickups or pickup and Switch allows choice between two magnetic pickups or pickup and tape head; Tape Monitor; Scratch and Rumble Filters on all inputs; Phase Reversal; Equalization for microphone, NAB tape and RIAA records; Stereo Headphones Output with Speakers/Earphones Switch; Derived Center Channel; Center Channel Power Output to drive 3rd loudspeaker directly; Separate Bass and Treble Controls on each channel; Input Selector Switch for Microphone, Stereo, Stereo Reverse and Left or Right Channel; Volume/Loudness Circuit and Control; All-Aluminum Chassis and DC heater Supply for inaudible hum. Signal lights show mode of operation at a glamce. Power Output: 40 watts each channel (IHFM); Frequency Response: 20 to 20,000 cps 11 db; Harmonic Distortion: 0.8%; IM Distortion: 0.5%; Hum and Noise: —80 db. Terminals for 4, 8 or 16-ohm speakers. Uses 11 tubes including 4-7591 outputs plus rectifiers. Size 15Wx4496Hx13Va**D. Shpg. wt., 30 lbs. 15Wx43/8Hx131/4"D. Shpg. wt., 30 lbs.

Size 15Wx4+8Hx13-74 0 21 H 6014WX Less Case Net 194.95 Metal Enclosure for 299D. Shpg. wt., 5 lbs.

Net 12.50 21 H 6009W Walnut Wood Case for 299D. Shpg. wt., 6 lbs.

Net 22.50 21 H 6024W

STEREO SYSTEM FEATURING SCOTT 229D



AS LOW AS



CHOICE OF STEREO CARTRIDGE Shure M7/N21D Pickering V15/AT-1

OPTIONAL GARRARD A-70

Quality Stereo System consisting of Scott 2990 80-watt stereo integrated amplifier less case. Garrard AT-60 4-speed automatic changer with an oil walnut wood base. Choice of one of the three deluxe stereo cartridges, Pickering V15/AT-1, Empire 880, or Shure M7/N210 Stereo cartridge; A pair of Lafayette "Decorette V" 5-speaker slim-type speaker systems in a beautiful oil walnut enclosure. Shop, wt., 84 lbs.
21 H 9978CWX

21 H 9978CWX Deluxe Stereo System same system as above except famous Garrard Model A-70 4-speed record changer in place of Garrard A-60 record changer. Shpg. wt., 90 lbs.


21 H 9979CWX Net 299.95

NEW TRANSISTORIZED HI FI COMPONENTS

SCOTT MODEL 344 TRANSISTORIZED 50 WATT STEREO TUNER/AMPLIFIER

CHECK THESE **OUTSTANDING FEATURES:**

- PLATED, FOUR NUVISTOR FRONT END AS-HIGH SENSITIVITY AND CROSS MODULATION REJECTION
- SERIES GATE. TIME-SWITCHING MULTIPLEX CIRCUITRY GIVES SEPARATION IN EXCESS OF 35 DB.
- AUTO-SENSOR CIRCUIT AUTOMATICALLY A LENTLY SWITCHES TO STERED MODE WHEN TO STERED BROADCAST TUNED
- LOUDNESS COMPENSATION ASSURES FULL TONAL QUALITY AT LOW VOLUME LEVELS
- DUAL BASS AND TREBLE CONTROLS UTILIZED IN SCOTT'S MONOSPAN FOR STEREOPHONIC SIMULA-TION OF MONOPHONIC RECORDS
- FRONT PANEL LOW LEVEL DUTPUT FOR MONITORING WITH STEREO HEADPHONES
- SEPARATE PRECISION TUNING METER FOR ACCURATE FM TUNING
- FLYWHEEL BALANCED AND BALLBEARING MOUNTED TUNING CONTROL FOR SMOOTH OPERATION



Scott's all-new 344 solid-state tuner/amplifier integrates the deluxe Model 312 Tuner section and a new 50 watt transistorized stereo amplifier on one compact, lightweight chassis, SPECIFICATIONS: FM sensitivity 2.2 _w; Separation, 35 db; Amplifier frequency response, 20 to 20,000 cps ±1 db, Size: 15½wx13½Dx5½"H, 21 H 6042wX Shpg. wt., 16½ lbs. Net 364.95 Metal Case, simulated leather, for 344 21 H 6009w Shpg. wt., 5 lbs. Net 12.50

HARMAN-KARDON SR-900 SOLID STATE 75-WATT FM STEREO RECEIVER

The SR-900 features a virtually distortionless seventy-five-watt stereo amplifier engineered to drive even the most efficient speakers. The frequency response of the SR-900 is flat from below 5 cps to beyond 300,000 cps. Features a stereo control-center preamplifier which offers simple, easy-to-operate controls. The all solid-state FM tuner offers extreme sensitivity, excellent capture ratio, outstanding cross-talk characteristics. Stereo multiplex separation exceeds 35 db with less than 0.5% distortion. Also utilized is a solid state stereo logic circuit which instantly switches the receiver to stereo the moment an FM station begins to broadcast multiplex. SPECIFICATIONS. Distortion: less than 5% from 20,000 cps. Damping factor: 40:1 down to 10 cps. Rise time: 1.3 μ sec. Minimum volume hum down 95 db. Impedance output: 4 to 16 ohms. FM sensitivity: 1.85 μ HFF. Multiplex separation: better than 40 db. Size: 16Vax5x113%. Shpg. wt., 28 lbs. 21 H 4243WX Model SR-900 Net 395.00 Net 395.00 21 H 4244W Wood cabinet for above. Oiled walnut The SR-900 features a virtually distortionless seventy-five-watt

......

The SR900 features a 75-watt solid state stereo integrated amplifier—37.5 watts per channel-and a solid state FM stereo tunerall on one complete chassis.

NEW BOGEN AT600 60 WATT SOLIO STATE STEREO AMPLIFIER-PREAMPLIFIER



17995

- All Transistor 60-Watt Amplifier
- Frequency Response 25 to 50,000 cps
- Handsome Brushed Gold Front Panel

A new, solid state, 60-watt amplifier (30 watts per channel iHF music waveform). The AT600 features long life, instant warm-up, absence of noise, and advanced transistor circuitry. All the power is available to drive even the lowest efficiency speakers. Frequency response ±1 db, 25 to 50,000 cps; IM distortion less than 1%. Headphone outlet for private listening. Noise and Humicrelative to full output) Tuner, —65 db; Auxiliary, —65 db; Phono mag., —60 db; Tape, —55 db. Channel cross-talk: —50 db @ 1,000 cps. Output impedance 4/8/16 ohms. Power consumption. 110 watts full power both channels. Front panel controls: Selector switch; mode switch; output switch; stereo switch; loudness switch; volume control; balance control; bass control; troble control; power switch. Inputs: phono mag; tape head; auxiliary; tuner. Outputs: speaker; tape; head phones. Lustrous brushed gold front panel. Less cabinet. Size: 15x10x45/6". Shpg. wt., 15 lbs. 21 H 1719WX Model AT600. Less cabinet Net 179.95 New Begen FT-60 Solid State FM Stereo Tuner. Features Stereo "Minder Light."

21 H 1716WX Shpg. wt., 11½ lbs. Cabinet, walnut for AT600, FT-60. Shpg. wt., 8 lbs. Net 187.95 Net 22.35

See Our Catalog 650 For Additional Hi-Fi Equipment

OELUXE 60 WATT STEREO PHONO SYSTEM FEATUR-ING BOGEN AT600 SOLIO STATE STEREO AMPLIFIER



This deluxe stereo system includes: The Bogen solid-state AT600 60-watt stereo amplifier-preamplifier, Garrard model 50 4-speed automatic record changer on a beautiful oited walnut base. Your choice of one of three following deluxe stereo cartridges: Pickering V-15/AT-1, Shure M7-N21D, or Empire 880. And lastly, a magnificent pair of Lafayette Decorette V Slim Type speaker systems. The Decorette V system features 5 perfectly matched speakers offering brilliant sound reproduction and housed in a superbly styled referring brilliant sound reproduction and housed in a superbly styled oiled walnut veneer enclosure with a decorative walnut picture frame moulding bordering a fine cane grille. Spp. wt., 72 lbs. 21 H 9632CWX Complete system. Specify cartridge Net 267.50

FAMOUS NAME HI FIDELITY KITS




DYNAKIT "PAS-3" STEREO PREAMPLIFIER KIT

TOP-performing stereo preamp for use with high quality basic amplifiers includes two independent high gain, low noise preamplifier-control channels. All critical circuitry is pre-assembled on 2 printed circuit boards. Features "Opna-Blend" For variable channel separation, DC heated tube filaments. Inputs: 3 stereo low level and 4 stereo high level. Frequency response: ±0.5 db 10-40,000 cps. Distortion: less than 0.5%. Noise: less than 2 µv. Gain, 60 db at 1000 cps on RIAA, 20 db on high level. For 110-120V., 50/60 cycles AC. Deluxe gold panel. Size: 13x8x4". Shpg. wt., 11 lbs. 21 H 2301WX PAS-3 Kit. \$6 Monthly.

Net 62.95 21 H 2302WX PAS-3A Wired. \$7 Monthly.

Net 93.45

* SCOTT MODEL LK-48B **48-WATT STEREO AMPLIFIER KIT**



This popular amplifier kit gives a clean 24 watts output per channel—enough power for virtually any music system. Completely versatile, effering phono, tuner, extra, and tapehead inputs. Features a powered center channel output for three-channel stereo or for extension speakers without the need of an additional amplifier. A tape monitor switch permits integration with a three-head tape deck in direct monitoring of recordings. Front panel stereo earphone jack and speaker "on-off" switch facilitates private earphone listening. SPECIFICATIONS: Power Output: 24 watts/channel IHFM standard. Frequency Response: 20-20,000 cps ±1 db. Harmonic distortions: 0.8%. Hum Level: —80 db. Sensitivity: phono, 3 mv. tape head, 9 mv. Dimensions: 15½Wx5¼4Hx13¼**D. Shpg. wt., 35 lbs. (less case). 21 H 6037WX Net 114.95

Leatherette Metal Case for LK-48B. Shpg. wt., 2 lbs. 21 H 6009W Net 12.50 Wooden Walnut Case for LK-48B. Shpg. wt., 7 lbs. 21 H 6024W 22.50



EICO ST-70K 70 WATT STEREO INTEGRATED AMPLIFIER KIT

INTEGRATED AMPLIFIER KIT

Consists of 2-35 watt amplifiers and a complete stereophonic hi-fi
control center on one chassis. Stereo inputs in switched sets including: 2 magnetic phono (one for turntable, one for changer); tape
head, preamplified tape, FM-AM stereo tuner, FM-FM Multiplex, and
Auxiliary. Controls: Level with balance check swich and loudness/
level switch; bass, treble, six-position mode selector, blend, tape
speed, tape monitor, scratch, and rumble. Output: 4, 8, and 16 ohm
speaker. Third channel output available. Specifications: IM distortion —2% at 70-watts. Harmonic Distortion —1/2% at 70 watts.
Frequency response—±1/2 db, 20-20,000 cps. Shpg. wt., 35 lbs.
21 H 2508WX Model ST-70K

Net 99.95

Model ST-70 as above, but factory wired Net 149.95 21 H 2509WX



2095 KIT

DYNAKIT "STEREO 70" 70-WATT STEREO BASIC AMPLIFIER KIT

The stereo 70 provides outstanding reproduction, firm bass, and smooth natural highs. Delivers 35-watts per channel, Frequency response: ±0.5 db from 10 cps to 40,000 cycles. IM distortion: less than 1% at 35 watts. Sensitivity 1.3 volts rms input for 35 watts output. Hum and Noise: better than 90 db below rated output. Output impedance: 4, 8 and 16 ohms. Nickel-finished chassis; vinyl-coated charcoal brown cover. For 110-120V 50/60 cycles AC. Size 9Wx64/2Mx 1370 Show at 32 Ms have the sense of 13"D. Shpg. wt., 32 lbs. 21 H 2303WX Stereo 70/A Kit. \$8 Monthly 21 H 2304WX Stereo 70/A Wired. \$9 Monthly

Net 110.45 SCOTT MODEL LT-110B

WIDE BAND FM STEREO TUNER KIT



This popular FM stereo tuner kit boasts beautiful new styling, refined scott performance, and extremely easy to follow building methods. Critical multiplex section and silverplated front end are wired and pre-tested at the factory. You need only align the tuner's wide-bandpass IF's and detector stage using the meter on the tuner itself. SCOTT's sonic monitor eliminates guesswork in identifying FM Stereo broadcasts. Features also include precision front panel tape output, stereo subchannel filter, stereo noise filter and precision tuning meter. Newly restyled to match all Scott amplifiers and amplifier kits. SPECIFICATIONS: Sensitivity: 2.2 microvolts. Frequency response: 30-15.000 cps. Signal-to-Moise Ratio 60 db. Separation: better than 30 db. Uses 8 tubes, 11 diodes plus rectifier. Size: 15Wx4436HX10°D. Shpg. wt., 20 lbs. Less case.

Net 124,95 This popular FM stereo tuner kit boasts beautiful new styling, refined 21 H 6036WX Net 124.95

Leatherette metal case for LT-110B. Shpg. wt., 2 lbs. 21 H 6009W Net 12.50

Wooden Walnut Case for LT-110B. Shpg. wt., 7 lbs. 21 H 6024W



Critical Circuits Pre-aligned

Net 22.50

EICO MODEL 2536 FM STEREO RECEIVER SEMI-KIT

A complete 36-watt stereo amplifier and superb FM stereo tuner on one compact chassis. Features ready-to-use component assemblies both prewired and prealigned for ease of construction and best performance. Other features include, precise rotary tuning dial, bartype electron-ray tuning indicator and stereo defeat switch. Amplifier output: 36-watt (IHFM music power); Harmonic distortion: 0.5% at 10 W per channel, IM distortion 0.25% at 1-watt. Separate hum balance and Bass and Treble controls for each channel, Balance control; Blend: Tape Monitor switch and Tape Output. 4 inputs. Tuner: 3_W IHFM useable sensitivity; Channel separation, 30 db. Extruded aluminum panel matches other classic units. For 115V 60 cycles AC. Size: 15½wyx554bx133%*0. Shpg. wt., 25 lbs. 21 H 2515WX Model 2536 Semi-Kit Net 208.95 A complete 36-watt stereo amplifier and superb FM stereo tuner on

21 H 2516WX Above, factory wired and tested Net 209.95 21 H 2528W Metal cover for 2536-Wt. 3 lbs. .

7,50 21 H 2530W Walnut wood case for 2536-Wt. 6 lbs. . Net 19.95

FAMOUS LAFAYETTE "SLENDERETTE III" SLIM 2-SPEAKER 2-WAY SYSTEM


Fine Speaker Performance Offering Rich Clean Sound At Lafavette's Low, Low Price

- · Ideal Choice for Floor, Shelf or Wall Mounting
- Perfect for low cost Stereophonic or
- Monophonic Systems
 Improves Fidelity of Phonographs, TV Sets, **AM and FM Radios**
- Room-Filling Music Everywhere In Your

2-for- 38.50

The Lafayette Slenderette III is the ideal choice as a floor, shelf, or wall type speaker system for low-cost stereo or monophonic systems, and for top quality extension speaker use. Can be used for improving fidelity of existing TV sets, AM and FM radios, tape recorders, and phonographs. Enjoy smooth, wide-range sound in every room of your house. The slim styling enhances the decor of your room. Contains a special 6½" high compliance woofer and a matched 2½" cone tweeter with crossover network. Offers fine speaker performance — clear natural bass, full midrange reproduction, and wide-dispersion of high frequencies. The speakers are mounted in a superbly constructed and finished oil walnut cabinet. Oil walnut finish is on all four sides. With walnut picture frame molding. Measures 12x18 inches with a depth of 5½ inches. Freq. response—50-10,000 cps. Impedance 8 ohms. Shpg. wt., 15 lbs. Imported.

Net 19.50 Net 19.50 2 for 38.50



SELECT "SLENDERETTE II" SLIM 3-WAY 3-SPEAKER SYSTEM

Featuring Jensen Speakers and Universal Woodcrafters Cabinet at Lafayette's Low, Low Price

- 3-Speaker 3-Way System
 Utilizes Jensen 8" High Compliance Woofer, Jensen 6" Mid-Range Driver & Jensen 3" Tweeter
- For Shelf, Floor or Wall
- Beautifully Styled Cabinet Finished on all 4 Sides in Finest Genuine Walnut Veneer With Cane Grille & White Enamel Border

The "Sienderette II" is an outstanding system offering superb styling and rich, deep sound. Incorporates the latest advanced acoustic design at Lafayette's low, low, price. Contains a 3-speaker 3-way system engineered by Jensen with newly developed Jensen components. Utilizes a Jensen 8" high compliance woofer with rubber suspension for extra wide excursion, a Jensen six-inch midrange driver in rubber suspension, and a special Jensen 3-inch tweeter. Woofer electric crossover at 2000 cycles, midrange electric crossover at 2000 cycles. Power capacity: 18 watts continuously, 36 watts peak. Superbly styled cabinet finished on all 4 sides in finest genuine walnut veneer with protruding cane grille 8 white enamel border. Ideal for shelf, floor or wall mounting. Includes wall bracket. Impedance 8 ohms. 211/4Wx141/4Nx41/4"D. Shpg. wt., 22 lbs.

Net 28.85 21 H 0101WX



LAFAYETTE "MINUETTE" HIGH-FIDELITY SPEAKER SYSTEM 2350 TWO FOR

1250

Shelf Size — 8¼Dx15¾Lx5¾"H

Genuine Walnut Finish on 4 Sides

Complete with 6' Extension Cable and



Net 23,50 Set of two for Stereo—Save 1.50 Net 13.95 Set of two for Stereo-Save 1.40 Net 26.50

Lafayette Cat. No. 651 23

Take Advantage of Lafayette's Low Speaker System Prices

THE 5 MOST IMPORTANT SPEAKERS YOU MAY EVER OWN ARE IN . .



Lafayette's decor-ette V" **SLIM 5-SPEAKER SYSTEM**

Four Specially Engineered 612-inch Low Resonance Speakers—One 212-inch Cone Type Tweeter Designed to achieve optimum performance in a new type audiopanel enclosure of only 4¼ inches in thickness.

A superbly styled oil walnut veneer enclosure with magnificent walnut picture frame molding, bordering a fine decorative Cane Grille.

Freq. response 50-18,000 cps
Power handling Canacity continuous 15 watte near

Power handling Capacity continuous 15 watts, peak level power—30 watts. Crossover Electrical 2,500 Cycles

Impedance-8 ohms


Lafayette is proud to offer a dazzling 5-speaker system—magnificently styled and engineered. The "Decorette V" incorporates a specially designed audio panel speaker system consisting of four 6½" low resonance speakers, and one 2½" cone tweeter mounted in a flat enclosure of only 4¼ inches thickness. The results achieved are remarkable; clean natural bass response, smooth midrange and pure, rich highs. These are mounted in a superbly styled oil walnut veneer enclosure with magnificent walnut picture frame molding, bordering a fine decorative cane grille. Ideal for floor mounting, bookshelf mounting, or wall mounting. Can even be used as a room bordering a fine decorative cane grille. Ideal for floor mounting, bookshelf mounting, or wall mounting. Can even be used as a room divider. Overall frequency response 50-18,000 cps. Power handling capacity 15 watts, peak load power—30 watts. Complete with decorator styled legs. Impedance 8 ohms—size 2134Mx414Dx1736°W. Shpg. wt., 17 lbs. Imported.

99 H 0008WX Model SK-300 Decorette Speaker System Net 39.95

Net 39.95 2 for 78.50

Only \$5 monthly

\$7 monthly



DELUXE LAFAYETTE decor-ette IIT. SLIM **5-SPEAKER 3-WAY SYSTEM**



SK-270 DECORETTE II

\$6.00 Monthly



FEATURING.

31/2" Dome Lens Compression Tweeter

8" Woofer with 1/2 lb. magnet

31/2" Cone Tweeter

6" Mid-Range Driver

8" Woofer with 1/2 lb. magnet

 Custom Assembled in a Genuine Hand-Rubbed Oiled Walnut Veneer Cabinet of Extra Heavy 3/4" Stock

Frequency Response, 40-20,000 cps

Power Handling Capacity, Continuous 30 Watts; Instantaneous Peak Load Power, 60 Watts

Impedance 8 Ohms

specially designed 6" mid-range open back driver provides uniform response from 500 to 7500 cycles. The 3½" cone type tweeter gives wide dispersion of the mid-highs smoothly from 1000 to 10,000 cycles. The dome lens type compression tweeter response is from 5000 to 35,000 cycles. Omni-directional, this tweeter gives 360° sound dispersion to add overall brilliance to the system. RC electrical crossover frequency is 5000 cps. Instantaneous peak load power, 60 watts. Impedance, 8 ohms. Size: 25"Hx17"Lx434"W. Supplied with 4 1" round walnut decorator legs which can be mounted on the cabinet for either vertical or horizontal placement. Shpg. wt., 24 lbs. 21 H 0106WX SK-270 Decorette II Net 5

Designed by Lafayette engineers—built by the foremost English Hi-Fi Speaker manufacturer to Lafayette's rigid specifications.


Designed by Lafayette engineers—built by the foremost English Hi-Fi Speaker manufacturer to Lafayette's rigid specifications. The genuine, hand-rubbed oiled walnut veneer cabinet with smart ebony black and gold picture frame molding, has been designed and styled or either vertical or horizontal placement. A real space-saver, it is slim in appearance and can be placed on a bookshelf, mounted on the floor, used as a room divider or hung on the wall. The "decorette II" is a 5-speaker 3-way system utilizing the latest advanced acoustic designs. Two 8" woofers with ½-lb. magnets incorporate a "Rig'dflex" Floating Piston Hyperbolic Cone resulting in a free floating cone rim and a completely rigid cone center to provide maximum distortionless bass from 500 cycles down to 40 cycles. The Lafayette Cat. No. 651

Deluxe LAFAYETTE "Decorette III" 3 Speaker 3-Way System

Designed by Lafayette engineers — built by the foremest English Hi-Fi Speaker manufacturer te Lafayette's

Features.

- Newly Developed 12" Poly-Foam Woofer with 1 lb. magnet and A Free-Air Response of 35 cps.
- 6" Closed-Back Mid-Range
- 31/2" Sealed Cone-Type "Super" Tweeter
- Specially Engineered "Tuned" **Enclosure with Tube-Type Duct** For Superior Bass Response
- Smooth Overall Response From 30 to 30,000 cps
- Crossover At 5,000 cps
 Power Rating—Up To 25 Watts Continuous, 50 Watts Instantaneous Peak
- Nominal 8 ohms Impedance



Designed by Lafayette engineers—built by the foremost English HI-Fi Speaker manufacturer to Lafayette's rigid specifications, the Dec-orette III employs three separate speakers to provide smooth, realistic musical reproduction over the entire audible range—you'll hear deep effortless bass . . . clear precise mid-range . . . shimmering highs.

Model SK275

Decorette III

The particularly low bass response of this bookshelf system is achieved by means of a specially engineered enclosure and the use of a newly-developed 12" low-resonance woofer which covers the range of 30 to 2000 cycles. The 6" mid-range Speaker and the 3½"


"Super" tweeter act as direct radiators and provide smooth repro-

- SYSTEM DESIGN -

The enclosure is a bass reflex design using a ducted port of the tube type which is proportioned to provide correct acoustic "tuning" of the enclosure. This arrangement provides a special path for the sound waves radiated from the rear of the woofer so that they emerge "in-step" with those radiated from the front of the woofer. This provides a substantially greater bass sound power from the system. Solid 34" wood construction, internally braced, plus the liberal use of sound absorbent material, ensures an extremely rigid enclosure, free of undesirable resonances. A

special 12" woofer covers the range to 2,000 cycles and employs a foam-treated cone that contributes greatly to the efficient, distortion-free bass reproduction. A 6" midrange speaker covers the 2000 to 5000 cycle range and is of the closed back type to prevent interaction with the woofer. A 3½" cone-type "Super" tweeter, also with closed back, provides coverage from 5000 cycles to beyond audibility (30,000 cps). All three speakers are acoustically matched and provide a well-balanced and smooth sound output over the entire range of the system.

LAFAYETTE'S **ULTRA-COMPLIANCE 2-WAY** SPEAKER SYSTEM



These Ultra-Compliance 2 Way Systems feature a unique dual cone speaker with heavy magnet structure, employed in a specially designed tuned ducted port enclosure. Both tweeter and woofer "float" on flexible, corrugated edges, with the outer edge of the tweeter cone attached to the mid-section of the woofer. This results in a mechanical crossover so that both cones operate in phase at low frequencies, but only the tweeter cone radiates high frequencies. The same type of wide-range frequency response as found in true coaxial or multiple speaker systems is achieved in these unique "Ultra-Compliance" Speaker Systems. Frequency response is 40-16,000 cps—Impedance: 8-16 ohms.

VERY SMALL IN SPACE—LESS THAN 1 CU. FT.

- Frequency Response 40-16,000 cps
- Especially Designed Vented, Tuned Duct Type Enclosures
- Unique Mechanical 2-Way Speaker With Heavy Magnet
- Enclasure Finished on 4 Sides Excellent For Stereo

FULL SIZE PERFORMANCE—These outsanding Lafayette Ultra-Compliance 2-way speaker Systems achieves a purity of sound and musical quality that is astounding from a speaker system occupying less than one cu. ft. of space. A perfect speaker for use anywhere in your home or office ... makes ideal extension units or use in pairs for stereo.

Available in rich mahogany or walnut. Finished on four sides it horizontally on its side or vertically on its base. Easily adapts to bookshelf placement or modular use. Dimensions are only 103/6Hx 18%,6Lx8%"D Shpg. wt., 15 lbs. Imported.

99 H 0039WX Model SK-124 Mahogany Set of Two Speaker Systems 99 H 0040WX Model SK-123 Oiled Walhut Set of Two Speaker Systems

DELUXE LAFAYETTE ELIPTOFLEX® ENCLOSURE

FINISHED ON 4 SIDES Adapts to any room arrange-ment. Place horizontally on shelves or vertically on the floor.

As Low As

The "Eliptoflex"....

- Meets space requirements of stereo.
- Utilizes the full advantages of efficient 12" speaker performance.
- Provides optimum performance without use of large wattage, expensive amplifiers.

The "Eliptoflex" utilizes a unique elliptical port which broadens frequency response and provides better transient response. A specially engineered diffracting ring eliminates cancellation effects between front and rear radiation. These engineering advances when coupled with the famous Lafayette free-edge SK-58 12" coaxial speaker with 3" cone type tweeter, 114 lb. TSK-5 high flux density magnet, — special 34" wide sheepskin cone-edge suspension and built-in crossover network level control offer a magnificent speaker system. (See listing below). system. (See listing below).


"Eliptoflex" achieves a degree of natural smoothness, low-distortion "Eliptoriex" achieves a legiee of indular simulation and rich robust bass hitherto found only in large enclosure speaker systems or inefficient bookshelf speakers requiring high powered ampliflers. Due to its highly efficient design characteristics the "Eliptoflex" does not require costly high wattage amplification.

The "Eliptoflex" speaker system is beautifully finished on 4 sides in a variety of hardwood veneers for attractive room placement either horizontally or vertically. Dimensions are 14Hx23% Wx13% "D. Shpg. wt., 35 lbs.

ELIPTOFLEX ENCLOSURE LESS SPEAKER - FINISHED ON 4 SIDES

20 H 0127WX 20 H 0128WX	"Eliptoflex"	Enclosure—Mahogany	36.50 36.50
20 H 0129WX	"Eliptoflex"	Enclosure—Oiled Walnut I	36.50 29.50

PHENOMENAL ELIPTOFLEX PERFORMANCE




The loudspeaker is mounted on a baffle recessed in the cabinet shell The loudspeaker is mounted on a battle recessed in the cabinet shell with the front-plate extending partially across the front surface of the baffle forming ducts or tubes from the port openings to the outside air. The elliptical cutout changes the effective length of the duct across its area. This variation in path lengths provide an extremely smooth transition from duct to free air; broadens the frequency response and provide better transient response. A triangular shaped diffracting ring mounted on the front of the baffle board virtually eliminates undesirable cancellation effects normally produced by close coupling of front and rear cone radiation. This poard virtually eliminates undestraine canceriation effects formally produced by close coupling of front and rear cone radiation. This results in a "lens" effect, changing relative particle velocities and consequently, phase relationships so as to produce a smooth transition from front to rear radiation. Comparative laboratory and listening tests indicate that "Eliptoflex" performance is demonstratively unarrical throughout the contraction. stratively superior throughout the audio spectrum.

LAFAYETTE ELIPTOFLEX with FAMOUS SK-58 12" COAXIAL SPEAKER with 1 LB. MAGNET

no si nationisti cirit Audiouti Montonio - Africano.


AS LOW



Superb performance from a speaker system featuring the famous Lafayette SK-58 12" coaxial speaker with 2-3" cone type tweeters and 1½4 lb. magnet mounted in the patented Lafayette Eliptoflex enclosure. Enclosure comes finished on 4 sides. Eliptoflex/SK58 Speaker System Net 64.50

21 H 0115WX Mahogany 21 H 0116WX Walnut 21 H 0112WX Oil Walnut 21 H 0117WX Unfinished Birch Net 64.50 Net 64.50 See Page 27 For Full description of SK-58

LAFAYETTE ELIPTOFLEX with SK-180 10" TRIHELIX 3-WAY SPEAKER



An ideal combination of speaker and enclosure that furnishes optimum 3-way speaker performance. Eliptoflex enclosures are finished on all four sides for vertical or horizontal placement. Shpg, wt., 32 lbs.

EIII	ptoriex/SK.	180 Speaker System		
21	H 0118WX	Mahogany	. Net	66.50
		Walnut		
		Oiled Walnut		
21	H 0114WX	Unfinished Birch	. Net	61.50

See Page 27 For Full description of SK-180

THE WIDELY ACCLAIMED LAFAYETTE® SK-58°12" COAXIAL SPEAKER

SUPERB PERFORMANCE GUARANTEED*... OR YOUR MONEY BACK!

- 11/4 LB. MAGNET WEIGHT
- RESPONSE 30-15,000 CPS SHEEPSKIN "FREE EDGE" CONE MOUNTING
- 3" COAXIALLY MOUNTED TWEETER
- **BUILT-IN LC NETWORK**
- **RATED AT 20 WATTS CONTINUOUS POWER**

The World Renowned Original Lafayette SX-58

Lafayette's exclusive 12" coaxial is a precision-made high fidelity loudspeaker, universally acclaimed by music lovers, hi-fi enthusiasts and professional experts alike. It provides a truly faithful reproduction of sound without any "coloration" or distortion, its excellence being responsible for its use in innumerable high fidelity music systems today. The SK-58 incorporates such features as heavy, high flux density TSK-5 magnets for high efficiency; %" wide sheepskin cone-edge suspension and special composition fibre cone material, specially treated for ultra-linear, distortion-free response; heavy rugged cast metal frame for freedom from resonances and for greater rigidity. The coaxially-monted 3" coneresonances and for greater rigidity. The coaxially-mounted 3" cone-type tweeter has a bell shaped mounting for maximum dispersion of high frequencies with no back radiation. With the built-in

3000 cps crossover network it contributes its share to the smooth 3000 cps crossover network it contributes its share to the smooth delivery of the overall wide range response of 30-15,000 cps. Woofer resonance in free air is 40 cps. Speaker power handling capacity is 20 watts continuous sine wave, 35 watts peak program material. Impedance of the voice coil is 8 ohms, connections being made to chromeplated screw terminals. Finished in gray-brown opelescent enamel, the speaker is supplied complete with "brilliance" level control. Shpg. wt., 11 lbs. Imported.

99 H 0019W SK-58 12" Coaxial Speaker

*Try your SK-58 at home. If for any reason you are dissatisfied, you may return it at once and your money will be refunded (less transportation charges).

LAFAYETTETRIHELIX®

3 COMPLETELY INDEPENDENT SPEAKERS WITH 3 SEPARATE VOICE COILS IN A SINGLE 10" COMPACT UNIT

 Frequency Response 20 to 20,000 cps (30-18,000 cps ± 3 db) • Revolutionary Conical Stiffener" • Eccentric Baffle Mounting of Midrange & Tweeter Eliminates Interaction Between Speaker Cones . Built-in Crossover Network and Brilliance Control . Extremely Efficient . High Excursion Woofer . Ideal For Stereo

Recreates The Entire Audio Spectrum With Concert Hall Faithfellows—The Lafayette "Trihelix." Fresh engineering concepts have resulted in a single 10-inch speaker designed expressly for use in bookshelf size enclosures. The "Trihelix" is in effect a complete three-way high-fidelity speaker system, with three mechanically and electronically independent speakers mounted within a single 10-inch frame. Although they are individual units the 2-inch tweeter and 5-inch midrange speakers have been especially designed to compliment the woofer. Special freatment of the cones and cone edges with polyester resins provides an even distribution of mid and high frequencies without peaks or resonances. To minimize interaction between the three cones both the midrange and tweeter units are mounted eccentrically or off center in relation to the woofer and are completely enclosed by a specially designed baffle. These unusual design features result in effectively eliminating intermodulation distortion—a common fault in conventionally designed 3-way speakers. The specially treated woofer cone employs a revolutionary "conical stiffener" located at the apex of the cone in order to stiffen the diaphragm and eliminate "breakup," thus

\$5.00 Monthly

providing a true piston action. This carefully designed conestiffening procedure, in addition to its very high compliance, enables the woofer to deliver a smooth, crisp, solid bass that balances naturally against a crystal clear midrange and natural treble. A built-in electrical crossover network with crossover points at 1500 cps and 5000 cps, allows each speaker to reproduce its portion of the audio range smoothly and efficiently. An adjustable brilliance control permits matching of sound to room acoustics. SPECIFICATIONS: Overall Response 20-20,000 cps (30 to 18,000 cps ± 3 db). Free Air Resonance 35-55 cps. Impedance 16 ohms. Power Rating: 20 watts Average Program Material. Crossover Points: 1500 & 5000 cps. Overall Diam: 10°. Overall Depth: 7°. Baffle cut-out: 8½°°. Screw type terminals are color coded for quick easy connection of amplifier leads. Shpg. wt., 8 lbs. Imported. Imported.

99 H 0020W SK-180 10" Trihelix Speaker

20 H 0109W Adaptor Board To Fit above to 12" cetout Net .88

Lafayette Hi-Fi Provides Quality and Performance




Engineered to satisfy the most discriminating listener, the 210 achieves full 3 speaker preformance through its advanced 3-way design. Woofer, midrange radiator and tweeter are all axially mounted within a single rigid, unitized die cast frame to provide an integrated, efficient wide range speaker system. Construction features incorporate a 3 inch voice coil with an exclusive "Rigidfiex" cone-bonding and cone-edge treatment process to form a virtually free-edged cone suspension. All irregularities of the audible frequency spectrum are smoothed out with standing waves and surround resonances eliminated. High efficiency and low distortion are further assured by use of a specially designed 2½ lb. ceramic magnet.

Frequency response is 30-20,000 cps with a free-air woofer cone

resonance of 35 cps. Bass response is tight and solid without boom or hangover to achieve phenomenal realism. At 2000 cps, frequencles are channeled into a stiff-coned midfrequency radiator by means of a smooth mechanical crossover. High frequencies are reproduced with a silkiness and naturalness to beyond the limits of human hearing by means of a compression driver tweeter. This superb new tweeter incorporates a rigid, die-cast, flared, hyper-elliptical horn, a 1" diameter aluminum voice coil and diaphragm in a self-aligning assembly with air chamber and phase equalizer. A built in crossover allows the tweeter to take over at 5,000 cps and is provided with a high-frequency L-pad level control with attractive escutcheon and knob. Shpg. wt., 15 lbs.

Net 42,50

LAFAYETTE ELIPTOFLEX® with SK-210 SOVEREIGN 12" 3-WAY SPEAKER



AS LOW AS

\$7 monthly

PERFORMANCE MATCHED—Lafayette's famous Eliptoflex bookshelf enclosure matched with the exceptional SK-210 Sovereign 12" 3-way speaker with 2½ b. ceramic magnet. The unique Eliptoflex design, featuring an elliptical port for broader frequency response, plus the famous Lafayette SK-210 3-way speaker combine to provide to-day's discriminating stereo enthusiast with superb performance throughout the audio spectrum. See above for individual component description. Size: 14Hx2378Wx1376"D. Shpg. wt., 39 lbs. 21 H 0122WX SK-210 & Eliptoflex Mahogany

Net 74.50 Net 74.50 21 H 0123WX SK-210 & Eliptoflex Walnut Net 74.50 21 H 0124WX SK-210 & Eliptoflex Oiled Walnut 21 H 0125WX SK-210 & Eliptoflex in Unfinished Birch Net 67.50

LAFAYETTE Griterion **ELIPTOFLEX® SPEAKER CABINET** with the SK-210 SOVEREIGN 12" SPEAKER





only **98**50

\$8 monthly

Now Lafayette's renowned Eliptoflex enclosure in a new decorator inspired form. Incorporates the same inner construction and acoustic principles that have made Eliptoflex performance famous. The SK-210 is packaged separately, and can easily be mounted in the Criterion enclosure in a matter of minutes. Size: 32½Hx18Dx16"W. Wt. 65 lbs. Criterion Eliptoflex Walnut finish with SK-210.

Net 98.50 21 H 0126WXM Criterion Eliptoflex Oiled Walnut finish with SK-210.

21 H 0127WXM

Criterion Eliptoflex Mahogany finish with SK-210. 21 H 0128WXM

Net 98.50

Net 98.50

DELUXE LAFAYETTE MODEL SK-215 3-WAY 15 INCH HIGH FIDELITY SPEAKER



Free-Edged Cone Suspension

12 OB/Octave Cross-over Network with High Frequency Level Control

Precision Pressure-Oriven Horn-Loaded Tweeter with Aluminum Oiaphragm & Coil

Massive 5-lb. Ceramic Magnet

3-inch Main Voice Coil

Overall Frequency Response: 20-20,000 cps

Cone Resonance Frequency: 25 cps

Power Capacity—50 Watts Impedance—16 Ohms

Lafayette combined the finest British craftsmanship and advanced acoustic design to bring you this outstanding 3-way 15" speaker. The SK-215 utilizes a patented concentric twin-gap magnetic system with a massive 5 lb. super efficient double duty cylindrical ceramic magnet. Woofer, mid-range radiator and compression tweeter are axially mounted to achieve outstanding, efficient wide-range speaker performance. With a cone resonance of 25 cps, the woofer section is vacuum constructed by an exclusive process and features a virtually free-edged cone suspension that eliminates standing waves and surround resonances. An automatic mechanical crossover separates bass and mid-range frequencies at 2000 cps to a highly stable mid-range radiator. A 12 db per octave LC crossover network provides smooth transition at 5000 cps from mid-range to a precision pressure-driven horn-loaded tweeter employing an aluminum diaphragm and coil in a self-aligning assembly with air chamber and phase equalizer, This crossover has a high frequency constant impedance L-pad level control for matching of sound to room acoustics and individual listening tastes. SPECIFICATIONS: Cone Resonance. 25 cps; Overall Frequency Response, 20-20,000 cps; Magnet Weight, 5 lbs.; Magnetic Flux Density, over 250,000 Maxwells: Crossover Frequencies, 2000 and 5000 cps; Power Capacity, 50 watts; Woofer Voice Coil Diameter, 3 inches Tweeter Voice Coil Diameter, 1 inch; Impedance, 16 0hms, Dimensions: 6½" overall leath; 15½" diameter Shar with 20 lbs. Diameter, 1 inch; Impedance, 16 Ohms, Dimensions: 61/2" overall depth: 151/4" diameter. Shpg. wt., 30 lbs. 21 H 0130WX Net 64.50

Lafayette Model SK-216 3-way 12" Hi-Fi Speaker

DELUXE LAFAYETTE SPEAKER SYSTEM featuring Lafayette "Universal" Bass Reflex Enclosure and Lafayette SK-215 3-Way 15" Speaker



A superb speaker system featuring the Lafayette SK-215 3-way speaker (see description above) and the beautifully styled Lafayette "Universal" Bass Reflex Enclosure. Solidly constructed of ¾" stock, this fine enclosure is designed to achieve optimum performance from a separate 12" or 15" full range. 3-way speaker. Provides rich, robust bass. The enclosure comes with a cutout for the SK-215, and is lined internally with acoustical material. Finished walnut and mahogany models are of genuine veneer and acoustically correct flakecore. Dim. 28%x23½x16"D. Note: The SK-215 is packed separately and can easily be mounted in the "Universal" Enclosure in a matter of minutes. Shpg. wt., 84 lbs.

"Universal" Base Reflex Walnut Enclosure and SK-215 Speaker


21 H 9618WX Net 11
"Universal" Base Reflex Mahogany Enclosure and SK-215 Speaker 21 H 9619WX Net 117.00

"Universal" Base Reflex Walnut Enclosure only. Shpg. wt., 54 lbs. 20 H 0131WX Net 52.50 "Universal" Base Reflex Mahogany Enclosure only. Shpg. wt., 54 lbs.

LAFAYETTE "UNIVERSAL" BASE REFLEX ENCLOSURE AND LAFAYETTE 5K-216 3-WAY SPEAKER. Outstanding Lafayette Speaker System fea-turing same Lafayette "Universal" Bass Reflex Enclosure listed above with Lafayette SK-216 3-Way 12" Speaker, Shpg. wt., 79 lbs. "Universal" Base Reflex walnut enclosure and SK-216 speaker. 21 H 9616WX

"Universal" Bass Reflex mahogany enclosure and SK-216 speaker 21 H 9617WX Net 107.00

LAFAYETTE'S Popular MINI-DUCT®





LOW AS

Mounting boards accept all types of tweeters

LAFAYETTE SK-98® 8" DUO-CONE HI-FI SPFAKER

Mechanical 2-Way Design

Overall Response 40-16,000 Cps. Large Magnet Structure Patented Cone Construction and

Material High Excursion Weefer

The dual-cone construction used in these high quality 8" speakers, provides the same type of wide-range response normally found in provides the same type of wide-range response normally found in true coaxial speakers or multiple speaker systems. The woofer and tweeter cones "float" on flexible corrugated edges. This mounting results in true mechanical crossover, so that both cones operate at low frequencies, but only the tweeter cone operates at high frequencies. This gives improved high frequency directional characteristics and minimum distortion. Patented cone materials provide extremely smooth response over the range of 40-16.000 cps. Magnets are large and heavy, with a flux density of 10.500 gauss and total flux of 56,000 maxwells. Terminals are screw-type for solder-less connections. Sensitivity is 99.5 db/watt; free air resonance is 55-70 cps; voice coil impedance is 8 ohms. Size is 8" diam., 414" deep and requires 634" diam. baffle opening. Shpg. wt., 5½ lbs. imported. Imported. 99 H 0027 8" 2-WAY SPEAKER Net 9.95 Net 18.95

MINIDUCT® SPEAKER ENCLOSURE WITH LAFAYETTE SK-98 8" PATENTED DUAL CONE SPEAKER



A PERFECT COMBINATION: The "Mini-Duct" enclosure and the famous Lafayette SK-98 8" mechanical 2-way speaker with patented dual cone construction. This speaker combined with the Lafayette "Mini-Duct" enclosure will give the wide-range frequency response (40-16,000 cps) normally found in the coaxial speakers or multiple speaker systems. Shpg. wt., 291/2 lbs.

Combination unfinished "Mini-Duct" enclosure with SK-98 Speaker 21 H 9990WX Combination mahogany "Mini-Duct" enclosure with SK-98 Speaker 21 H 9991WX Net 34.25 Combination walnut "Mini-Duct" enclosure with SK-98 Speaker

21 H 9992WX Combination oiled walnut "Mini-Duct" enclosure with SK-98 Speaker 21 H-9993WX

SPEAKER ENCLOSURE

A universal ducted-port bookshelf enclosure engineered for use with 1, 2 or 3-way speaker systems.

SOLIDLY CONSTRUCTED OF 34" WOODS START WITH A SINGLE SPEAKER AND BUILD INTO 2- OR 3-WAY SYSTEM LATER ACOUSTICALLY LINED THROUGHOUT AVAILABLE IN A VARIETY OF 4-SIDED FINISHES

Now limited space need not necessarily mean limited sound. The Lafayette Mini-Duct is acoustically designed to achieve smooth, distortion-free reproduction with a remarkably full, clean extended bass response that gives no indication as to its small size. Reducing boards are supplied so that the Mini-Duct will accept an 8" Woofer. 6" Mid-Range and a variety of tweeters. This versatility makes it possible to start with an 8" speaker and eventually build into a 2-way or 3-way speaker system. Solidly constructed build woods the Mini-Duct is beautifully finished in a variety of fine veneers on 4 sides. Designed for attractive horizontal or vertical placement anywhere in your home with dimensions 23Wx115-Mx

veneers on a sides. Designed for attractive norizontal or vertical placement anywhere in your home with dimensions 23Wx11½Hx 11½*D. Shpg. wt., 23¾ lbs.
20 H 0123WX WALNUT Net 24.95
20 H 0124WX MANGGANY Net 24.95
20 H 0125WX OILED WALNUT Net 24.95 Net 24.95 Net 24.95 20 H 0126WX UNFINISHED BIRCH

LAFAYETTE SK-130 8" WIDE-RANGE

HI-FI SPEAKER Made In England To Our Own Rigid


Specifications CHECK THESE PHENOMENAL SPECIFICATIONS

- Frequency Response: 40-18,000 cps Flux Density: 13,500 Maxwells Pewer Handling Capacity: 15 Watts Magnet Weight: 1 lb. High Efficiency
- Cone Resonance: 55 cps
- Veice Ceil: 1-Inch
 Impedance: 16 Ohms
 Alcomax Magnet

ASTONISMING FIDELITY from a speaker of this size and modest price. Designed and finished with typical British craftsmanship, the SK-130 features an especially designed hyperbolic cone with a plastic surround suspension for wide compliance performance. Bass response is robust and full bodied, while the midrange and highs are virtually transparent, with never a trace of shrillness or harshness. The excellent wide-range response of the SK-130 make it ideal for stereo when used in pairs or perfect for use as a high quality extension speaker. Overall Diam. 8½°X4° Deep. Baffle cutout 7½°. Rigid vibration-free frame is equipped with screw type terminals. Imported. 21 H 0113 Shpg. wt., 3 lbs. Net 12.95

FAMOUS LAFAYETTE MINI-DUCT® BOOKSHELF ENCLOSURE WITH SK-130 8" WIDE-RANGE SPEAKER

As low as



A combination that rivals the performance of much larger speaker systems. This fine enclosure assures optimum performance from the SK-130. Only 23Wx11½Hx11½***D—ideal for mounting in a bookcase or record shelf. Finished on 4 sides in a variety of fine furniture finishes. Shpg. wt., 27 lbs.

21 H 9994WX Mahogany 21 H 9995WX Walnut 21 H 9996WX Oiled Walnut 21 H 9997WX Unfinished Net 36.95 Net 36.95 36,95


Lafayette Supplies Fine Speaker Systems at Low Cost

2 FOR STEREO

LAFAYETTE ULTRA-LINEAR SK-128° FULL RANGE 8-Inch BIAXIAL SPEAKER with Acoustic Tweeter Baffle Design

The SK-128 combines the best features of a multiple speaker system in one compact and economical unit. It offers full, even coverage of the entire audible range, with no distortion or coloration to mar your listening pleasure. The specially treated woofer cone has a unique "Conical Stiffener" at the apex which, coupled with its high compliance, enables the cone to operate in a piston-like manner—delivering a clean, powerful bass response. The 2-inch tweeter has its own voice coil and magnetic field. Special treatment of cone and cone edge provides even distribution of the high frequencies, with no peaks or resonances. The unusual off-center mounting of the tweeter and its eliptical baffle minimizes interaction between tweeter and woofer and insures an overall response free of intermodulation distortion. Electrical crossover from the woofer cone to the tweeter unit is provided by a built-in network. An adjustable brilliance contrel permits matching of sound to room acoustics. Efficiency of the speaker is such that it will operate from any amplifier with as output of I watt or more. Installed in a bass-reflex type of enclosure, it performs outstandingly, and is recommended for all high-quality music systems—whether monaural or stereophonic. SPECIFICATIONS: Overall Response: 20-20.00 cps. (40-16,000 cps. ± 3 db). Free air Resonance: 45-65 cps. Impedance: 8 ohms. Power Rating: 20 watts intgrated Program Material. Crossover: 2,500 cps. Overall Diam. 8%." Overall Depth: 51%." Baffle cut-out: 7%.2" Rugged, vibralion-free speaker frame with color-coded screw-type terminals for quick, easy connection of amplifier leads. Shpg. wt., 5 bs. Imported. 99 H 0032 Full Range 8" Biaxial Speaker Net 19.50


1950 2 for 38.95







Eccentric Tweeter Mounting & Unique Elliptical Baffle Completely Eliminates Interaction Between Woofer & Tweeter



■ 20 TO 20,000 CPS (40 TO 16,000 CPS ± 3 DB) ■ HIGH EFFICIENCY ■ HIGH EXCURSION WOOFER WITH UNIQUE "CONICAL STIFFENER" ■ HANDLES HEAVY BASS PASSAGES WITHOUT "DOUBLING"

LAFAYETTE MINI-DUCT® BOOKSHELF ENCLOSURE WITH SK-128® 8" ULTRA-LINEAR SPEAKER

The perfect answer for those who demand realistic sound reproduction even where space is limited. Two of these systems are ideal for stereo. Beautifully finished on all 4 sides for horizontal or vertical placement. Shpg. wt., 28 lbs.

21 H 0109WX 21 H 0110WX	Speaker Speaker	System System	in in	Oiled Walnut Ne Mahogany Ne	t	39.50 39.50 39.50
21 H 0111WX	Speaker	System	in	Unfinished Birch Ne	t	37.50



LAFAYETTE'S WORLD FAMOUS

15" COAXIAL HI-FI SPEAKER



- 30-20.000 CPS—35 Watts Peak
- Large 13 oz. Ceramic Magnet

A high quality, budget priced speaker system consisting of specially designed 15" woofer with a full 5" high-frequency tweeter coaxially mounted with a 1½" voice coil. SPECIFICATIONS: Frequency response, 30-20,000 cps. Crossover frequency, 3500 cps 3500 cps. Cone resonance, 45 cps. Power handling capacity, 20 watts continuous and 35 watts peak, Impedance, 8 ohms. Rugged, lasting seamless cone. Has 4-way binding posts for easy installation. Shpg. wt., 12 posts

Net 17.95 21 H 4711W

12" WIDE-RANGE HI-POWER HI-FI SPEAKER



● 11/4 lb. Ceramic Magnet ● Rated at 30 Watts ● Response 20-14,000 CPS • Seamless Cone

Special Heavy-Duty
Construction Ideal

This wide-range 12" FM high fidelity speaker is rated at 30 watts and is excellent for use with any hi-fi system. Voice coil impedance 8 ohms. Outside diameter 121%". depth 634". Color-coded 4-way binding-post terminals. Shpg. wt., 8 lbs. 21 H 4712

Net 14.95

12" THREE-WAY HI-FI SPEAKER



10 oz. Ceramic Magnet 20 Watts Power Capacity Frequency Response 35-17,500 cps

Features a 10 oz. ceramic magnet, and when correctly baffled, will reproduce bass notes down to 35 cps. A special eliptical tweeter extends response to 17,500 cps and gives improved sound dispersion over the usual cylindrical types. Voice coil diameter is 1½". Impedance is 8 ohms. Power Capacity is 20 watts. Plated steel frame finished in brown baked enamel. Has 8 lbs. Net 11.95 4-way binding posts. Shpg. wt., 21 H 4714

ECONOMY 12" COAXIAL SPEAKER



Frequency Response 40-15,000 cps Voice Coil Diameter 1"

An economical way to improve the sound of existing inexpensive hi-fi consoles or portables or as the main speaker system of a budget priced high-fidelity system. A a budget priced night-ridelity system. A built-in filter correctly divides the frequency spectrum and distributes the different frequencies to the woofer and tweeter. Power rating: 12 watts. Impedance: 8 ohms, Shpg. wt., 5½ lbs.

15" HI-FI WOOFER



- Alnico Magnet
- 20 to 5000 Cycles Peak Watts-Watts

Efficient 15" woofer with 2 lb. Alnico V magnet, Ideal for 2- and 3-way speaker magnet. Ideal for 2- and 3-way speaker systems. Handles 35 watts of audio power. Frequency response ±2 db 20 CPS to 1000 CPS, and ± 5 db from 20 CPS to 5,000 CPS with proper baffling. Voice coil dia. 2", impedance 8 ohms. Finished in beautiful brown enamel. Has 4-way binding posts. Shpg. wt., 131/4 lbs. Cone resonance 45 cycles. 21 H 4719W

12" HI-FI WOOFER WITH 2 LB. MAGNET



- 30 Watts 20-2500 Cps 2" Voice Coil Diameter
- Cone Resonance at 30 Cps

This sturdily constructed This sturdily constructed 12" Woofer is rated at a full 30 watts audio power. Frequency response from 20 to 2500 cps with the speaker resonant frequency at 30 cps. Heavy 2 lb. Alnico V magnet and 2" diameter voice coil. Plated steel frame finished in brown baked enamel. Has 4 way binding coats 8 obs. immediate Short with 1014 lbs. posts. 8 ohm impedance. Shpg. wt., 101/2 lbs. 21 H 4720 Net 22.95

12" HI-FI WOOFER WITH 11/4 LB. MAGNET



- 25 Watt Power Capacity
- Response 30-9,000 Cps 11/2" Voice Coil
- Diameter Cone Resonance 50 Cps

Ideal for assembling 2- and 3-way speaker systems at a budget price. Enclosed magnet structure — completely dust-proof. Compli-ance of outer cone and inner spider carefully

calculated for best bass response. 134 lb. ceramic magnet, 8 ohm impedance. Has 4-Way binding posts. Cone Resonance 50 cycles. Shpp. wt., 8 lbs.

21 H 4716 Net 15,50

INCH WOOFER



Magnet

35 to 7500 cps Free Edge Cone High Compliance

This 8" woofer is an ideal choice for use in 2 or 3 way speaker systems where space is of great importance. The 11/4 lb. ceramic or great importance. The 14s in the low end. A free-edge, high compliance cone is utilized for high efficiency. Power handling capacity is 25 watts peak. Voice coil diameter 1½". Cone resonance is 50 cycles. 8 ohm impedance. Has 4-way binding capacity for a control of the low of the lo posts for simple installation. Shpg. wt., 6 lbs. 21 H 4721 Net 10.65

MID-RANGE SPEAKER



25 Watts Capacity Response 350-14,000 cps **Enclosed Back**

Capable of reproducing virtually undistorted sound from 350 to 14,000 cps, the recommended crossover frequencies are at 350 cps and 5,000 cps. Power handling capacity: 25 watts. Cone Resonance: 150 cps. Impedance: 8 ohms. 10 oz. ceramic magnet. Voice coil diameter: 1". Plated steel frame finished in brown baked enamel. Has 4-way binding posts. Shpg. wt., 4½ bs.
21 H 4718 Net 6.50

Lafayette Supplies Fine Speakers at Low Cost

BUDGET PRICED HI-FI SPEAKERS

ROYAL DANISH 12" DUAL CONE SPEAKER



- Frequency Response 45 to 14,000 cps 1" Diameter Voice C
- **High Flux Density**

You will be pleasantly surprised at the quality of this fine speaker which Lafayette brings you at this low price. An exclusive, special formula cone rim treatment eliminates cone rim resonance and distortion. Overall depth, 5½°. Completely enclosed. 1" diameter voice coil with an impedance of 8 ohms. Shpg. wt., 6 lbs. Imported. 12" Dual Cone Hi-Fi Speaker 21 H 7101 Net 7.95

21 H 7101

Net 7.95

61/2" COAXIAL HI-FI SPFAKER

- Overail Response
- 50-16,000 Cps. Space Saving
- **Economical For** Stereo Built-in L C Network Large, Heavy

Magnets



An excellent speaker with all the best features of coaxial design. 6½" woofer is equipped with large, heavy magnet for maximum efficiency and low distortion. 2" tweeter is a separate speaker coaxially mounted in a housing which completely seals off back radiation. Voice coil impedance, 8 ohms. Requires 5½" diam. cutout. Size is 6½" diam., 34" deep. Shpg. wt., 3½ lbs. Imported

99 H 0028 61/2" Coaxial Speaker Net Net 12.95

LAFAYETTE 61/2" THINLINE SPEAKER



Frame ideal for Economy Music Systems or Extension Speaker Use



Low-cost, 3-way, full-range speaker with 3 diaphragms performing as woofer, mid-range and tweeter. Its small size, only 2" deep, makes it excellent for use in a wide variety of space-saving applications. Frequency response, 75-12,000 cps. Power handling capacity, 3 watts of program material. Impedance 3 obms. Shore the 216 them. pedance, 8 ohms. Shpg. wt., 21/2 lbs. imported. 99 H 0031

Net 4 95

LAFAYETTE 6"x9" WIDE RANGE SPEAKER

High Sensitivity

Magnetic Circuit

55 to 14,000 cps



Space Saver Construction This hi-fi extended range speaker is defi-This hi-fi extended range speaker is definitely a must for add-on stereo application and lends itself to many new applications such as adding hi-fi to autos, TV, radio sets, and also where space limitations are paramount. It has an outside diameter of 6%x 9%;" Mtg. hole dimensions are 4%x6%;" Depth is 3%;". Mas 4-way binding posts.
21 H 4799 Shpg. wt., 2 lbs. Net 4.95

LAFAYETTE COMPRESSION TWEETER



000 Cycles Response

Nandles 20 Watts

of Power

Phasing Plug for Uniform Sound

Oispersion

Die-Cast Aluminum Construction . High Efficiency

This unit offers amazing clarity and brilliance of sound. Built-in basing plug insures uniform sound output. Low end cut-off 1500 cycles; high range extends to 20,000 cycles. Handles up to 20 watts of power. Recommended crossover frequency 2500 cycles or higher. Dimensions: 5½" long, mounts in 3½" dia. hole. Impedance 16 ohms. Imported. Shog, wt., 2 lbs.

99 H 6250 Tweeter Net 9.95

DELUXE LAFAYETTE-GOODMAN "DOME LENS" LITTA HIGH FREQUENCY COMPRESSION **TWEETER**





and 4 way systems Handles up to 30 watts of power.

Offers 360° sound dispersion, quality high frequency response of sharp transients. Capable of handling frequencies from 5000 cps. to beyond the limits of human audibility. Has built in crossover at 5000 cps. Voice coil impedance 8-16 ohms. Dimensions: 4D x2½" length. Shpg. wt., 1½ lbs. Imported from England.

LAFAYETTE LOW COST HI-FI TWEETER



Frequency Response 3,000-16,000 Cps.

Reproduces high frequencies without losing clarity and volume. Even sound dispersion is insured by use of a round cone. Metal cased with completely sealed rear housing. Frequency response 3,000-16,000 cps. Diameter 2¾ inches. Depth 1¾ inches. Voice coil impedan-3 & ohms. Shpg. wt., 1 lb. Imported.
99 H 0117 Net 2.25

AND 3-WAY L/C



- 4 crossover frequencies: 350, 700, 2000-3000, 5000 cycles

 6 crossover combinations
 Built-in brilliance and presence centrols
This versatile unit can be used either as a Inis versatile unit can be used either as a 2-way or 3-way 6 db per octave network. For 8-16 ohm speakers. Suitable for mounting inside enclosure or leaving out in the open. Brilliance and Presence controls — are mounted on the front panel. If desired, these level controls may be removed acceptable. level controls may be removed, escutcheon plate, for external mounting; controls are wired with 3-foot long leads. Shpg. wt., 6 lbs. imported. 99 H 0022 Net 14.95

LAFAYETTE 2-WAY CROSSOVER NETWORK



Adjusts to Either 2500 or 5000 cps Crossover Freg.

Has a built-in continuously variable high-frequency "Brilliance" level control. Control has a 2½ ft. cable to mount on rear or side of speaker cabinet, and a long shaft for thick wood panels. For use with 8-16 ohm speakers. Easily accessible screw terminals. Metal case 576Lx256Hx236"D. Shpg. wt., 5 lbs. Imparted ibs. Imported. 99 H 0021 Net 7.95

LAFAYETTE 3-WAY 12 INCH "SLENDER-LINE" HI-FI SPEAKER





2 for 38.95

 Only 3½" depth — can be mounted in virtually any "thin-type" cabinet Special low-resonance woofer cone
 Independent horn type super tweeter for wide dispersion of highs . Frequency response 30-18,000 cps . Heavy duty die cast frame • Complete with brilliance level control.

This new superb 3-way "slender-line" 12" high fidelity speaker incorporates the latest advanced techniques in speaker design. Constructed to Lafayette rigid specifications, the Lafayette SK-260 is an unbelievable value offering rich, brilliant sound reproduction. Engineered to faithfully reproduce the complete audio spectrum from 30 to 18,000 cps, this fine speaker is but 3½" in depth, can be mounted in virtually any thin-type cabinet or shelf type enclosure. Incorporates a special low-resonance woofer cone, for clean natural bass response without boom, mechanical mid-range, and independent horn-type tweeter for wide dispersion of highs. Offers full-bodied mid-range and quality high frequency response enabling you to hear all the fine transients and high notes of the higher frequencies. Features heavy duty die-cast frame. Built-in mechanical crossover at 1,800 cps and electrical crossover at 5,000 cps. Power handing capacity 20 watts, peak 40 watts. Complete with brilliance level control. Impedance 8 ohms. Shpg. wt., 10 lbs. Imported.

99 H 0029

Net 19.95 2 for 38.95

LAFAYETTE 2-WAY 12-INCH "SLENDER-LINE" HI-FI SPEAKER



 Dual Cone Construction ◆ Heavy Duty Magnet ◆ 2" Edgewound "Voice Coil" • Frequency Response: 20-13,000 cps • Shallow Depth for Custom Mounting

for 26.95

Here is a high quality, low cost, dual-cone speaker featuring outstanding sound and a heavy-duty die cast frame to permanently center the sound reproducing elements. This insures low distortion for the life time of the speaker. The shallow frame design of the SK-255 permits simple custom installation in walls, "thin-type" enclosures, ready-made consoles or wall baffle extension speaker use. The big 12" high compliance woofer delivers plenty of solid bass while the upper audio spectrum. Other features are 2" edgewound voice coil assembly and a built-in mechanical crossover at 1800 cycles. Has convenient binding post terminals for fast, easy connections to any amplifier.

SPECIFICATIONS—Frequency Response: 20-13,000 cycles. Power Handling Capacity: 20 watts, 40 watts peak. Voice Coil impedance: 8 ohms. Cone resonance: 45 cps ± 10 cps. Voice Coil Diameter: 2 inches. Size: 1214" diameter x 3½" deep. Shpg. wt., 7 lbs. Imported.

Net 13.95 2 for 26.95

Net 13.95 2 for 26.95

LAFAYETTE REVERBERATION **AMPLIFIER & SPEAKER SYSTEM**

Creates Realism of **Concert Hall Sound!**

- Ideal for Stereo or Mono Systems
- Does Not Affect **Fidelity**
- **Self-Contained** Amplifier/Speaker System with Built-in Power Supply



99 H 0030

The Lafayette SK-256 is a compact, space saving self-contained reverberation amplifier speaker system that works with your existing component Hi-Fi system, AM or FM radio, tape recorder to bring the realism of concert hall sound to your listening area. 3-tube amplifier delivers 2½ watts to a 6½" PM speaker. Inputs provided are stereo/mono high level and stereo/mono lovelevel. Front mounted control is push-pull on-off/volume. For 110-117 volts, 50-60 cps AC. Oiled walnut cabinet measures 111% WX 7% HX-5%"D. Shpg. wt., 7 lbs. imported SK-256

FIBRE GLASS INSULATION



Excellent sound absorbing material. For lining interiors of speaker cabinets, consoles, phonos, TV's, etc. 9 sq. ft., 1" thick with glue and applicator. Shpg. wt., 1 lb.


DELUXE BASS REFLEX KIT: 20 square feet, 16x16x

Bonded fibre-glass. Shpg. wt., 2 lbs.


JENSEN speakers + UNIVERSAL WOODCRAFTERS cabinet + LAFAYETTE low prices







. Jensen 12" Woofer, 8" Midrange Driver, 31/2" Enclosed Tweet



ENTI CUSTOM QUALITY SPEAKER SYSTEMS

DUTTON DELUXE BOOKSHELF SPEAKER SYSTEM MODEL DLS-529

Frequency Response: 40 to 15,000 cps Wide-Angle Dispersion

Excellent for Stereo

An ingenious adaptation of the much more expensive EMI professional studio monitor speaker. This 2-cubic foot bookshelf speaker system combines a wide frequency range with superb transient response and relatively low distortion. It is capable of such faithful musical reproduction throughout the whole audio spectrum that any defects in the equipment used with it will be immediately and blatantly revealed. The woofer is EMI's exclusive, handmade 134x84/" elliptical driver with aluminum cone and special plastic superposed. There are two 316 the transients are the superposed with current nanomade 1.342849" elliptical driver with aluminum cone and special plastic suspension. There are two 342" tweeters, specially designed with curved diaphragms. High precision crossover network designed to operate tweeters at 4500 cycles and upwards. Driver and tweeters completely and separately enclosed in a chamber with 34" reinforced walls. Cabinet is 24" wide x 13" high x 124s" deep. Interior is designed to damp out standing waves and other spurious vibrations. Includes a carefully selected metal front grille. Impedance of system is 4 ohms. Shpg. wt., 50 lbs.

21 H 5901WX Hand-Rubbed Diled Walnut 21 H 5902WX Hand-Rubbed Satin Walnut


Net 159.00 Net 159.00

NEW MODEL 812 COMPACT SYSTEM


An exceptionally fine low cost, compact 2-way loudspeaker system designed for small living areas. Suitable for floor or bookshelf Installation. The model 812 uses a 6½" hand-made wooder with a ceramic_magnet, and a 3½" tweeter with covered diaphragm and ceramic magnet specially designed for this system. Features low distortion and full frequency response. The fine wood cabinet is finished in oiled walnut. The speaker grill is made of the same woven metal as used on the more expensive EMI speaker systems. Dimensions: Width 10½", Depth 9", Height 14½". Impedance 8 ohms. Shpg. wt., 17 lbs.

21 H 5908WX Oiled Walnut

Net 49,95



IMPORTED FROM ENGLAND



Model 812

NEW MAXIMUS 1 SPEAKER SYSTEM by GOODMANS

IMPORTED FROM ENGLAND

One Of The Smallest, True High Fidelity Speaker Systems In The World! Actual Size 101/2x51/2x71/4"

- Sufficient Handling Capacity-With Ease
- Crisp Voice Articulation—Natural Presence .
- Real Treble, Solid Bass
- Unusual Compactness—Fits Anywhere

The MAXIMUS 1 is only 103/2x51/2x71/4" and fits everywhere—book shelf, end table, or wall. Inside each miniature mastercrafted oiled walnut enclosure are precision direct-radiator drive units with specially designed crossover networks to give uniform response from 45 to 20,000 cps. Exceptionally smooth bass is achieved by the utilization of a massive magnet in the woofer section. Power handling capacity is 15 watts, making it compatible with most amplifiers. A uniquely designed 1-crossover network transfers power at 900 cps to a newly developed backloaded mid-range/high frequency mit Shog wt 11 like. backloaded mid-range/high frequency unit. Shpg. wt., 11 lbs. 21 H 8301WX Walnut Finish

Net 59.50



MAXIMOS 1 A Speaker System Developed by the UTC Sound Division, Garden City, New York

s6 monthly

EMPIRE GRENADIER **MODEL** 8000 DIVERGENT LENS SPEAKER SYSTEM

Designed and Engineered for Stereophonic Sound . . . Three Acoustic Lenses allow you to enjoy phenomenal Stereo separation of full frequency response anywhere in the room . Speaker Placement is Nen-Cytical Non-Critical.

high compliance woofer with 12" high compliance woofer with 4" voice coil and 18 lb. ceramic magnet that feeds through a front loaded horn with 3500" radiation for full sound dispersion and prevention of standing waves. Full presence mid-range direct radiator and a low-mass domed tweeter. Rigid, totally damped columnar speaker enclosure cabinet is wranged in satin walnut lamination. damped columnar speaker enclosure capitet is wrapped in satin walnut laminate with mar and stain proof surface. Frequency response: 30-20,00D cps. Mandles up to 100 watss. Impedance: 8 ohms. Dimensions: 15¼" dia. x 29" high. Shpg. wt. 68 lbs. 21 H 3420WX

Net 149.95

NEW ECONOMY 3-WAY SPEAKER SYSTEM KIT

Ideal for the "do-it-vourself" audio Enthusiast. Features Matched 8" woofer, 5" mid-range, and 2" Tweeter.

Only

A 3 way speaker system, consisting of an 8" Woofer, with 10.7 oz. magnet, 5" mid-range 2" tweeter, and crossover network completely wired and mounted on a front panel and covered with attractive grey grill cloth. Specifications: Frequency range—35-18,000 cps, Crossover frequency 4,000 cps, Impedance 8 ohms, Front panel. Size: 20x8½". Power rating 15 watts. Shop. wt., 10 lbs.
21 H 7102W Net 32.75



"BUILD-YOUR OWN"

EASY-TO-ASSEMBLE HI-FI **ENCLOSURE KITS**

LAFAYETTE UNIVERSAL HI-FI BASS REFLEX ENCLOSURE KITS



All pleces of these carefully designed bass reflex high fidelity speaker enclosures are accurately precut of \(\frac{4}{\chick} \) Plywood to fit snugly together and eliminate spurious resonances. Surface is white birch veneer. Front panels have picture-frame moulding and plastic acoustic grilles to blend with any finish and room decor. Tapered offset legs are protected by brass ferrules. Acoustic lining material prevents reverberation and cabinet resonance. Cutouts are provided for 15" speaker plus adapter for 12", \(8\frac{1}{2}\) or 8" midrange plus adapter for 5" and blank wood block if no midrange speaker is used; cutout with adapter boards for 2 sizes of rectangular and 3 sizes of round compression horn tweeters plus blank block if no tweeter used. Kits are supplied unfinished, smoothly sanded and ready for finishing. The lowboy-style cabinet dimensions are (less legs) \(28\frac{1}{2}\) \(\frac{1}{2}\) \(\frac{1}{2}\ All pieces of these carefully designed bass reflex high fidelity speaker enclosures are

20 H 0121WX Unfinished Highboy Enclosure Kit 20 H 0122WX Unfinished Lowboy Enclosure Kit

Net 29.95 Net 29.95

Use this professional walnut oiling kit to achieve a beautiful oil finish on all unfinished walnut furniture. Materials are identical to those used by professional finishers; kit contains walnut oiling mixture, walnut paste wax, sandpaper and instructions. Shpg. wt., 2 lbs. 13 H 1801

OILEO WALNUT STAIN FOR LIGHT WOODS.
To be used with MS-592 for an attractive walnut-colored finish on lightcolored woods, such as birch, etc.

13 H 1802 Shpg. wt., 1 lb.

Net .89

Lafayette BASS REFLEX SPEAKER BOOKSHELF **ENCLOSURE KIT FOR 8" or 6" SPEAKERS**

AS LOW AS

Assembles In Less Than 30 Minutes!

Smooth Sanded Ready for a Fine Finish Entire Cabinet

Precision Cut - Fits Together Smoothly

Adapts For 8" or 6" Speakers

Easy To Follow Pictorial Instructions

Versatile - Use As Floor or Bookshelf Enclosure

BUILO IT YOURSELF . . . Expensive woodworking equipment isn't needed each cabinet component has been precision cut and fits together perfectly. There's nothing else to buy . . . acoustic padding, grill cloth and hardware are provided. Use any 8" or 6" speaker, the mounting board has been precut for 8" speakers and an adapter is supplied for 6" speakers.

for 6" speakers.

Designed for horizontal placement in a bookshelf, along a wall, etc. Constructed of veneers on 3 sides with handsome picture frame molding. (See Lafayette's professional finishing kits). Dimensions: 23x9½x11". Available in either birch or walnut unfinished veneers.

20 H 0112WX Birch Kit. Shpg. wt., 15 lbs.

Net 10.95

20 H 0113WX Walnut Kit.

Speakers for Lafayette Cabinet Kit (above). Lafayette 8" Duo-Cone Speaker; 40-16,000 cps response. 99 H 0027 Shpg. wt., 5½ lbs. Net 9.95

Lafayette 61/2" Coaxial Speaker; 50-16,000 cps response.

99 H 0028 Shpg. wt., 31/2 lbs. Net 6.95

Not 1/2" But 34" Furniture Grade White Birch Plywood or Walnut Veneer on Flaked Core Plywood

Built-in Picture Frame Moulding Adapter For 6" Speaker recut For 8' Interior Speaker Acoustic Padding Decorative Acoustic Grill Cloth Carefully Designed **Bass Reflex Port**

The Letter X in Stock Number Indicates Shipped Express Only

THE FAMOUS LAFAYETTE ELIPTOFLEX SPEAKER CABINET Ready-To-Finish, Easy-To-Assemble KIT FORM




HERE IS THE **FLIPTOFLEY** COMPLETELY

U.S. PATENT NO. 3089562

ASSEMBLEO



EASY TO ASSEMBLE!



A Bookshelf-Size Enclosure Engineered by Lafayette Research—ASSEMBLE IT, FINISH IT, and SAVE!

 The Same Speaker Cabinet That Set A New Standard of Excellence
 Utilizes the Full Advantages of Efficient 12" Speaker Performance • Provides Optimum Performance Without Use of Expensive Large Wattage Amplifiers • 3 Sides Prepared For Finishing. For Horizontal Placement

AS LOW AS

This is the same Lafayette Eliptoflex Speaker Cabinet that set a new standard of speaker enclosure excellence—now available in ready-to-finish easy-to-assemble kit form. The easy-to-follow instruction sheet, with large pictures, guide you step-by-step for easy assembling. When completely assembled and highlighted with your favorite finish—you'll be amazed at the professional looking results.


You'll also appreciate the engineering excellence of this speaker cabinet. The Eliptoflex utilizes a unique elliptical port which broadens frequency response and provides better transient response. A specially engineered diffracting ring eliminates cancel-

lation effects between front and rear radiation. The "Eliptoflex" achieves a degree of natural smoothness, low distortion and rich robust bass. Due to its highly efficient design characteristics, costly high wattage amplification not required. The Kit is available in either ready-to-finish birch or in ready-to-finish genuine walnut veneer. Assembled the "Eliptoflex" measures 14Hx23%wx13%6"D. Shgs. wt., 24 lbs.

20 H 0110WX Ready-To-Finish Kit in Birch ... Net 21.50 Ready-To-Finish Kit with Walnut Veneered Acoustically Correct Flake Core.

20 H 0111WX Net 24.50

ELEGANT MULTI-PURPOSE EQUIPMENT CABINET



ONLY

\$8 monthly

Add elegant charm to your decor with this beautiful "American Contemporary" multipurpose equipment cabinet crafted in fine woods, and finished beautifully in walnut. This spaclous cabinet will hold all of your Hi-Fi equipment in an ideal arrangement for your pleasure and convenience. The cabinet has 6 roomy compartments. The top three are 9¼4Mx13½"D. Each lower side compartment is 19¼4Wx13¼"H. The lower center compartment is 18¼4Wx13¼"D. Overall dimensions: 60Wx29Hx18"D, Three sculptured sliding doors make access to com-Three sculptured sliding doors make access to com-ponents easy without taking up space in your room. Shpg. wt., 110 lbs. 20 H 3809WX Walnut Finish

Net 99.50



... to decorate your home with music

Interior Dimensions Tambour Equipment Cabinet

each upper compartment 10"Hx191/2"Wx151/2" D

each lower compartment 12% "Hx19 1/2 Wx16 1/4"D



LAFAYETTE'S CRITERION LINE-The standard of construction and design by which all others are judged.

> TAMBOUR EQUIPMENT CABINET ONLY \$8.00 Monthly



THE Priterion TAMBOUR EQUIPMENT CABINET

Classic simplicity and elegance together with truly functional design characterize this new equipment cabinet. "Component Engineered" by Lafayette's audio experts to provide ample, convenient, well-ventilated accommodations for all of your components. When matched with its companion Criterion Eliptofiex speaker enclosure (described below) if forms a complete music center and perfectly matched furniture ensemble. The construction and design reflect the quality contained in these units: cabinets employ rigid tongue and groove construction of '34," lumber core woods throughout, with matched veneers inside as well as out. Smartly styled with tambour sliding doors and tapered legs for graceful, decorative harmony, as well as for room space saving. Four compartments provide space for housing turntable or changer, amplifier, tuner, etc., with room for record storage. Each upper compartment is 10Hx19½Wx15½°D; each lower compartment is 12½,Hx19½Wx16¾°D. Available in your choice of three finishes. Overall Dimensions: 44Wx18Dx32½°H including legs. Shpg. wt., 70 lbs. 20 H 0101WX Walnut 20 H 0102WX Oiled Walnut Net 89.50

20 H 0103WX Mahogany

Net 89.50 Net 89.50

THE Priterion ELIPTOFLEX SPEAKER CABINET

The same graceful, timeless styling and fine construction as the CRITERION equipment cabinet, which it matches. Designed to accommodate any 12" speaker, this enclosure incorporates the inner construction and acoustic principles of the famous Lafayette "Eliptoflex" enclosure. A specially designed elliptical port with diffracting ring broadens frequency response, increases transient response and eliminates cancellation effects between front and rear radiation. This results in low distortion, natural smoothness and unequaled performance in the low ranges. Constructed of 1%6" lumber core woods with hand-rubbed natural wood veneers. Smartly styled with matching grille cloth, decorative tambour borders, and tapered legs. Overall Dimensions: 32½4x18Dx16"W. Shpg. wt., 50 lbs.

20 H 0104WX Walnut 20 H 0105WX Oiled Walnut 20 H 0106WX Mahogany

AFAYETTE HI-FI COMPONENT SHELF/CONSOLE



DIMENSIONS Top Shelf 11"Hx16"Dx31\/2"W Lower Shelf 1544"Hx1542"Dx3142"W

Speaker Compartments 27"Hx16"Dx1434"W **Overall Dimensions** 3334"Hx16"Dx621/2"W (including 5" legs)

Decorator Inspired!!

\$5 monthly

OILED WALNUT FINISH

UNFINISHED

Room For All Your Components . Sturdy 34" Wood Non-Warp Construction . Holds Over 150 Records . An Attractive Addition To Any Home-Place Along A Wall Or Use As A Room Divider

The ideal answer to your Hi-Fi Stereo component placement problems—measures 62½" long, yet holds over 150 records with more than enough room for your amplifier, turntable or record changer, tape deck and stereo speakers. Veneered rear panel, finished on both sides, permits its use as a room divider. Speaker compartments spaced to achieve proper separation for stereo. Shipped knocked down—Assembles in minutes. Shps. wt., 65 lbs.


Oiled Walnut Finish on Genuine Walnut; Veneered Flake Core 20 M NO14 AT 50

20 H 0114WX Net 47.50 20 H 0115WX Unfinished Flake Board Net 28.95

Sce Page 3 for Lafayette Addresses and Store Hours

DELUXE HI-FI CABINETRY

CONTEMPORARY "ALL-IN-ONE" STEREO EQUIPMENT CABINET



Beautiful and functional design-removable center partition and adjustable shelf

A handsome equipment cabinet with same interior and overall dimensions as above cabinet. The removable center partition and adjustable shelf give you the necessary flexi-bility in installing your components. May be arranged to house most turntables, ampliflers, tuners, and tape recorders. Long length of 72 inches is both attractive and func-tional for speaker separation. Walnut finish. Shpg. wt., 165 lbs.

20 H 3802WX


Net 159.50


Contemporary All-In-One Stereo Equipment Cabinet

Elegantly Styled and -Crafted

AT ONLY

As Little as \$7 Monthly





This beautifully styled 70" cabinet has been designed with everything you need in utility as well as the finest appearance in contemporary simplicity. The meticulous custom craftsmanship, rich, matched mature wood veneers and custom hand-rubbed finish will please the most discriminating taste. Includes dual 12" speaker enclosures, with baffle plates, 2 sliding doors, sliding changer

carriage, record partition and equipment section. Overall size: 70Wx180x33%" H. Leg 1042". Inside speaker compartment: 1542"x 20"H. 2 Equipment sections, 1 blank panel, 1 shelf: 1744Wx742Hx 151/2"D. Record storage section. Shpg. wt., 160 lbs.

20 H 6101WX

STEREO EQUIPMENT CABINET SPANISH MOTIF



20 H 3810WX Shpg. wt., 150 lbs. Net 199.50

As Little as \$9 Monthly Truly outstanding in appearance, this beautifully designed and constructed cabinet will add Spanish elegance for any period to any room. Its rich appearance is equally matched by its versatility. Moveable shelves and partitions adapts this cabinet to an infinite variety of combinations of audio components. Carefully constructed with the finest of hard woods, the cabinet is superbly finished in Pecan, easily maintained to a high lustre. Overall size: 72" wide x 18" deep x 29" high.

---------23 23 23 231 23

Use Lafayette's Easy Pay Plan-See Center Insert A

Deluxe LAFAYETTE/WEBCOR Automatic Record Changer



 Automatic 4-Speed Changer Plays 16²/₃,
 33¹/₃, 45 and 78 RPM Records Automatically or Manually • Outstanding For Either Stereo or Monaural Use • Intermixes Records of the Same Speed • Heavy Duty 4-Pole 4-Coil Motor • Ribbed Rubber Turntable Mat Prevents Slippage, Cushions Records • Jam-Proof Tone Arm Mechanism • Oie-Cast Aluminum One-Piece Tone Arm . Automatic Shut-off After the Last Record has Been Played • Astatic Turnover Cartridge with .7 Mil Diamond Stylus for Microgroove Records, 3 mil Synthetic Sapphire Stylus For 78 RPM Records

A Superb Automatic 4-Speed Record Changer Made for Lafayette by Webcor



COMPLETE WITH .7 MIL DIAMOND NEEDLE

A superb 4-speed automatic record changer made for Lafayette by Webcor, an outstanding leader in the development and manufacturing of top quality record changers in the United States. This Lafayette/Webcor automatic record changer has been designed to give a very high standard of performance and dependability. Plays stereo or monaural records superbly. Plays 1626, 3334, 45 and 78 RPM records automatically or manually. Intermixes a one-inch stack of 7 and/or 12-inch standard hole records of the same speed. Utilizes dynamically balanced 4-pole 4-coil motor. Mainplate has scientifically constructed ribs that absorb vibration, reducing rumble. The heavy turntable has an extra long turntable bearing that also virtually eliminates rumble and wow. Spindle prevents double record drop; enlarging of record hole. On-off reject switch permits manual record play without causing an automatic change cycle. Changer A superb 4-speed automatic record changer made for Lafayette by

automatically shuts off after last record has played. Jam-proof tone-arm. "Torsion Spring" action permits moving tone-arm at any time without damaging changer. Adjustable stylus set-down comes equipped with Astatic turnover stereo cartridge with .7 mil diamond stylus for microgroover records, and 3 mll synthetic sapphire tip for 78 RPM records. Minimum mounting dimensions: 1434" wide, 131/2" deep, 51/2" above and 41/4" below mounting board. With 2—36" connector cables. Attractive finish in charcoal gray, aluminum and black. For 110-120 V., 60 cycles AC. Shpg. wt., 11 ibs.

21 H 0102W less base 21 H 0103 d5 RPM spindle-for above 24 H 0112W Oil walnut recessed base for above 24 H 0113W Mahogany recessed base for above 24 H 0113W Unfinished mtg. board for above 2.50 3.95

Made By ADMIRAL for LAFAYETTE The Admiral ENSIGN



• 4-Speed—16¾, 33⅓, 45 and 78 RPM • Plays Stereo or Monaural Records • Quality Ceramic Turnover Stereo Cartridge • Single Knob Speed/Function Control • Automatic 3-Way Shut-Off . Intermixes Records of Same Speed . Heavy-Duty, Constant-Speed Motor

The Admiral "Ensign" is a fine 4-speed automatic record changer made by Admiral for Lafayette offering outstanding performance at a low, low price. Built for compatibility with both stereophonic and monaural records. The balanced featherweight tone arm operates at only 5.7 grams of needle pressure to minimize record wear. Arm is equipped with Filip-type Ronette ceramic stereo cartridge. Heavy precision turntable delivers no noticeable hum, rumble, or wow. Drive wheel disengages in neutral position, thus preventing rumble producing flat spots. Plays 1624, 3344, 45 and 78 RPM records. Intermixes 10" & 12" records of the same speed. Plays records manually if desired. Single knob speed/function control. Automatic 3-way shut-off after last record. 117VAC, 60 cycles. Compact and exceptionally functional, only 1342x12x742". 3" below and 542" above mounting board. Beautiful brown & gold finish. Shpg. wt., 12 lbs.

21 H 0104W	Admiral "Ensign" less base	Net	19.95
24 H 0107W	Walnut Base for above	Net	3.95
24 H 0108W		Net	
24 H 0109W	Mounting Board for above	Net	1.10
21 H 0105	45 RPM Spindle for above	Net	1.65

NEW Garrard AUTOMATIC TURNTABLES

PLUS Your Choice Of Famous Stereo Cartridges For Only



Shure



plus choice of PICKERING, SHURE, EMPIRE CARTRIDGE

PICKERING SHURE, EMPIRE CARTRIDGE

A 51

PICKERING SHURE, EMPIRE CARTRIDGE

PICKERING SHURE, EMPIRE CARTRIDGE

A 52

PICKERING SHURE, OR adjustable with audible/visual guide. Bias compensator cancels out tone arm skating force. Features integral cueing device, automatic shut off, heavy 12" balanced cast non-magnetic turntable, and advanced Garrard Lab series 4-pole shaded motor. Stereow wired. For 110-130V—17x1434" less base. Shpg. wt., 22 lbs. imported from England.

21 H 3715WXM Lab 80 with Pickering V-15/AT-1 21 H 3716WXM Lab 80 with Empire 880P Cartridge 21 H 3717WXM Lab 80 with Shure M7/N21D Cartridge 21 H 3705WX Lab 80 less cartridge Net 99.51 Net 99.51 Net 99.51 Net 99.50

NEW GARRARD TYPE A70 AUTOMATIC TURNTABLE

plus choice of PICKERING, SHURE, EMPIRE CARTRIDGE

Successor to the world-famous "A" the 4-speed A70 automatic turntable features a completely new dynamically balanced tone arm. Bullt-in bias compensator—enables arm to track even the lightest and most compliant cartridges accurately, without distortion. Other outstanding features include: double shielded Lab Series 4-pole shaded motor, full-sized heavy balanced cast "sandwich" turntable. Stereo wired. Size: 16%4"x141%". For 110-130%, 60 cycles AC. Less base. Shpg. wt., 20 lbs. Imported from England.

21 H 3718WXM A70 with Pickering V-15/AT-1 Cart. 21 H 3719WXM A70 with Empire 880 Cartridge 21 H 3720WXM A70 with Shure M7/N21D Cartridge 21 H 3706WX A70 Less Cartridge Net 84.51 Net 84.51 Net 84.51 Net 84.50

GARRARD TYPE AT60 AUTOMATIC TURNTABLE

plus choice of PICKERING, SHURE, OR EMPIRE CARTRIDGE

The AT60 combines turntable performance with record changer convenience. Plays all 4-speeds: 16%; 33%; 45 and 78 rpm. Automatic intermix operation when desired. Features a heavy cast, oversized turntable (formally exclusive to the type A) . . dynamically balanced and non-magnetic. The tone arm is the tubular, counterweight adjusted, dynamically balanced design with built-in stylus pressure gauge legible from the top. Stereo wired. Size 15%1x 13%*D. For 110-130V, 60 cycles AC. Less base. Shpg. wt., 13 ibs. Imported from England imported from England.

21 H 3721WM AT60 with Pickering V-15/AT-1 cartridge 21 H 3722WM AT60 with Empire 880 cartridge 21 H 3723WM AT60 with Shure M7/N210 cartridge 21 H 3707W AT60 less cartridge Net 59.50

NEW GARRARD MODEL 50 AUTOMATIC TURNTABLE

plus choice of PICKERING, SHURE, OR EMPIRE CARTRIDGE

Quality in the Garrard tradition at a modest price. Features the same oversized turntable and handsome mat styling of the renowned AT-6. New counter-weighted cast aluminum tone arm with finger-touch stylus pressure adjustment. Convenient plug-in head. 4-pole shaded motor provides 4 accurate speeds: 16²4, 33⁴5, 45 and 78 rpm. Smooth changer mechanism offers automatic intermix operation. Size: 14⁴4kx12⁴/2*D. Stereo wired. Less base and 45 rpm spindle. For 110-130 volts, 60 cycles AC. Shpg. wt., 11 lbs. Imported from Finland.

ibs. Imported from England. Model 50 with Pickering V-15/AT-1 cart... Net 44.51 Model 50 with Empire 880 cartridge Net 44.51 Model 50 with Shure M7/N21D cartridge Net 44.51 Model 50 less cartridge Net 44.54 21 H 3724WM 21 H 3725WM 21 H 3726WM 21 H 3708W

ACCESSORIES FOR GARRARD AUTOMATIC TURNTABLES



45 RPM AUTOMATIC SPINOLES (FIG. A) 45 RPM AUTOMATIC SPINOLES (FIG. A)
Avg. wt., 10 oz.
21 N 3709 For Lab 80 3.80
21 N 3710 For A70 and A 3.80
21 N 3711 For A760 and 50 3.80
21 N 3712 For AT6 3.80
21 N 3713 For Autoslim 3.80
OUST COVERS (FIG. 8)
Molded of clear sparkling vinyl to fit contours of Garrard changers. Shpg. wt., 1½
the lbs. 21 H 3732 For Lab 80 Met 4.95 21 H 3733 A70 and A Net 4.95 21 H 3734 For AT-60, 50 and AT-6 Net 4.95 21 H 3735 For Autoslim Net 4.95



(FIG. 0)



GARRARD PRESSURE GAUGE (FIG. C) Model SP63. Insures correct pressure. Large, legible scale with widely spaced, easy-reading ½-gram markings. Swiveling balance scale pan. With 5-gram brass weight "standards" to check accuracy. Shpg. wt., 6 oz.

21 W 3731 Net 2.95

LAFAYETTE MOUNTING BOARDS (FIG. 0) Unfinished, smooth sanded. Shpg. wt., 11/2 24 H 1207W For LAB 80 24 H 1208W For A70 and A For A760, 50, A76; Autoslim 24 H 1209W 1.10 1.10 1.10

LAFAYETTE RECESSED WOOD BASES (FIG. E) Sturdy, recessed, finely finished. Shpg. wt., 4 lbs. For Models

Stock No. Finish 24 H 1201W Oil Walnu 24 H 1202W Mahogany Oil Walnut 24 H 1203W Oil Walnut 24 H 1204W Mahogany 24 H 1205W Oil Walnut 24 H 1206W Mahogany

Net A70 and A 3.95 A70 and A 3.95 Lab 80 3.95 Lab 80 3.95 AT60, 50, AT6 and Autostim 3.95 AT60, 50, AT6 and Autostim 3.95

All Prices and Specifications Subject to Change Without Notice

STEREO INTEGRATED TURNTABLES

RENOWNED AR 2-SPEFD STEREO TURNTABLE

Complete With Precision Tone Arm. **Biled Wal** nut Base. and Transparent **Dust Cover**



Only

WITH CHOICE OF STEREO CARTRIDGE

\$7 Monthly






An outstanding turntable featuring a precision arm, oil walnut base An outstanding turntable featuring a precision arm, oil walnut base and transparent dust cover in one compact unit. The rugged 3.3 lb. balanced aluminum platter is belt driven from synchronous motors operating at 33½ and 45 RPM. Turntable and arm are shockmounted from the top plate eliminating vibration. Tone arm floats down to the record if dropped, but dampening mechanism is disengaged as soon as the needle touches the record. Meets NAB specifications for broadcast equipment on wow, flutter and speed accuracy. Also includes cables, overhang adjustment device and needle force gauge. Size with cover—12¾x16¾x5¼". Shpg. wt 18 lbs

wt., 18 lbs. 21 H 7201WX	Net	78.00
AR Turntable plus Empire 880P stereo cartridge 21 H 7202WXM	Net	78.01
AR Turntable plus Pickering V15/AM-1 stereo cartridge	Net	78.01

WEATHERS "TOWNSEND 82" STEREO TURNTABLE



And Oil Walnut Base

Only

WITH CHOICE OF STEREO CARTRIDGE







Encased in walnut, the slim and compact Weathers "Townsend 82" is a low contour 33½ rpm stereo turntable, 17½" wide by 14½" deep by 5¼" high, including oil walnut tone arm. The arm will accept any standard cartridge and is adjustable to the stylus pressure and tracking angle recommended for each cartridge, Incorporates a 12 pole synchronous motor to achieve wow and flutter of less than 0.065%. Rumble is —50 db. "Delta shaped platform" suspension system isolates the turntable from floor-bounce shocks or acoustic feedback. Aluminum turntable platter. Shpg. wt., 12 lbs. 14 h6904WX Model 82 Turntable Model 82 Turntable plus Empire 880P Stereo Cartridge

Model 82 Turntable plus Empire 880P Stereo Cartridge Net 59.96 21-6908WXM Model 82 Turntable plus Pickering V15/AM-1 Stereo Cartridge Net 59.96

BENJAMIM MIRACORD

STUDIO 10H **AUTOMATIC TURNTABLE**



Only

S8 monthly

WITH CHOICE OF STEREO CARTRIDGE







Pickering V15/AM-1

The Miracord Studio 10H features a hysteresis motor, the famous "magic wand" spindle and a rectangular mass-suspended tone arm with interchangeable plug in cartridge head. Tracks and trips as low as 1 gram. Push-buttons select automatic or manual operation at any speeds playing all records including the new 33½ 7" type. at any speeds playing all records including the new 331/3 Satin chrome finish on all machined parts. Imported from W.

21 H 1601WX Model 10H less bass and cartridge Model 10H plus Empire 880P stereo cartridge Net 99 50 21 H 1606WXM Net 99.51 Model 10H plus Pickering V15/AM-1 Stereo cartridge Net 99 51 21 H 1620WXM ACCESSORIES for MIRACORD TURNTABLES 21 H 1603W Oiled Walnut Wood Base. Shpg. wt., 4 lbs. 21 H 1604W Unfinished Wood Base. Shpg. wt., 4 lbs. 21 H 1626 Automatic 45 RPM Spindle. Shpg. wt., 1 lb. Net 9.95 Net 8 95 Net 5.00 Oil Walnut Integrated Base with Plastic Dust Cover. Net 19.95 21 H 1628W

DUAL 1009 AUTOMATIC TURNTABLE



S8 monthly

WITH CHOICE OF STEREO CARTRIDGE





PICKERING V15/AM-1 Empire 880P

deluxe automatic turntable which features a seven pound plus A deluxe automatic turntable which reatures a seven pound pius dynamically balanced non-ferrous platter. Precision, high torque, 4-pole motor resists variations in line voltage up to ±10%. A unique three point suspension system provides acoustic isolation that is virtually impervious to mechanical vibration or acoustic feedback. Dynamically balanced professional tone arm. Dimensions: 127%" † ½" width*, depth 103%" † ½", above top of motor board 6½" below top of motor board 3½". Shpg. wt., 19¼ lbs. Imported. *Additional ½" allows for counterweight clearance in cabinet installation. stallation

21 H 6500WX Dual 1009 Net 99.50 1009 plus Empire 880P stereo cartridge Net 99.51 21 H 6506WXM Model 1009 plus Pickering V15/AM-1 Stereo cartridge Net 99.51 21 H 6514WXM ACCESSORIES 21 H 6525 Model AS-6 45 RPM spindle Net 4.80 Oil walnut base for dual 1009. Shpg. wt., 3 lbs. Net 9.95 21 H 6501W

FAMOUS LAFAYETTE F-767 STEREO HEADPHONES





25 FT. UNIVERSAL STEREO HEADPHONE



Listen to the finest high fidelity stereophonic sound reproduction through your favorite stereo headphone anywhere in the room, Ideal for use with Lafayette, Koss, Superex, Jensen, Sharpe and many other headsets. Flexible 3-conductor cable, grey vinyl jacket, 25 ft. in length. With ¼4" 3-circuit plug on one end and a 3-circuit jack on the other end. Shpg. wt. 1 lb. Imported.

99 H 0118

Net 2.29 Net 2.29

FAMOUS SHURE STEREO CARTRIDGES



M7/N21-D



21 H 6206L

M-44-5 with diamond stylus 21 H 6215L

M-44-7 with diamond stylus 21 H 6216L

OUR Best Buy in Stereo Headphones

 Air-Cushioned Headband
 Soft Foam Rubber Ear Cushions for Maximum Comfort and Bass Response . High Sensitivity

Maximum Comfort and Bass Response • High Sensitivity

The headband is covered with an air-filled vinyl bag which serves as a gentle air cushion, eliminating discomfort. Vinyl bag can be deflated, removed for washing and re-inflated. Soft foam rubber ear pads keep out external noise, provide maximum bass response and make these headphones extremely comfortable to wear. Sensitivity is very high — a signal power of 1 to 2 mw will produce adequate listening volume. Frequency response, 30-15,000 cycles. Impedance, 8 ohms per phone. Supplied with cylindrical overload control box for connection of the head phones to equipment that does not have stereo headphone jacks. Phones plug into box and two pairs of leads from the box connect to speaker output terminals; may also be attached to two separate extension speaker jacks for stereo. This headphone and control box not recommended for transistor amplifiers that do not have a stereo headphone jack.— use Model FA-60 headphone set (below) in such cases. F-767 supplied com-Model FA-60 headphone set (below) in such cases. F-767 supplied complete with attached stereo phone plug, overload junction box and in-structions. Imported

99 H 0035 Shpg. wt., 21/2 lbs.

NEW MOOEL FA-60 STEREO HEAOPHONES

For Use With Transister Amplifiers That Do Not Have A Stereo Headphone Jack

Same quality headphones as above, but comes with 4 separate leads terminated in spade lugs, plus over-load junction box with 4 screw-type input terminals and 4 output leads (all 4 leads isolated). Designed for connection to speaker terminals of transistor amplifiers or whenever complete isolation of all four wires is desired. Imported.

99 H 0048 Shpg. wt., 21/2 lbs.

STEREO HEAOPHONE CONTROL BOX

F-641 stereo control box is designed to connect F-767 stereo headphones to an existing system without the need of continually disconnecting speakers (cannot be used with FA-60). Impedance 4-16 ohms. Mas separate earlyhone jacks for stereo or monaural, separate volume controls for each side of the headset, and a speaker on-off switch. 434Wx1%HX 134"D. Imported.

99 H 0036 Shpg. wt., 11/4 lb.

DELUXE LAFAYETTE F-770 STEREO-PHONES



- Private Listening
 No Space Problem
 Exceptionally Fine Quality . Stereo and Monaural
- Actually 2 High Fidelity Oynamic Speakers Soft Foam Rubber Ear Pads Frequency Response 25 to 15,000 Cycles

The Lafayette F-770 combines broad frequency response and faithful reproduction with a comport-oriented design to make listening with them a real pleasure. The Stereophones are actually two 2½" high fidelity dynamic speakers with a frequency response range of 25 to 15,000 cycles. Perfect for stereo and monaural operation, the headphones are rated at ½ watt maximum input; impedance, 8 ohms per phone. The soft foam rubber ear pads provide extremely comfortable listening, help to keep out noise and maintain an excellent bass response. Imported.

99 H 0034 Shpg. wt., 2 lbs.

Pickering V15/AME-1


Elliptical

Control Box for F-770

Permits flexible one-switch change-over from speakers to Stereo phones. Imported 99 H 0037 Net 4.95

connector for connecting 2 or more sets of headphones to a single source. Net 2.45

UP DATE YOUR HI FI SYSTEM WITH THESE FINE PREMIUM HI FI STEREO CARTRIDGES COMPLETE WITH DIAMOND STYLUS



ADC-660 21 H 1307L 1995 Empire 880 21 H 3401L 21 H 5344L Elliptical Hand Polished Diamond Stylus replacement for EMPIRE 880P 21 H 3413L

14.95

880PE

21 H 3412L

MAGNIFICENT LAFAYETTE MODEL RK-600A 4 TRACK STEREO TAPE RECORDER



Completely Self-Contained

Sound-with-Sound

PLAYS-4-Track Stereo Tapes, 2-Track Stereo Tapes, Monaural 2-Track Tapes, Monaural Full Track Tapes

RECOROS-4-Track Stereo. 4- Track Monaural.

Two Speeds: 3¾ & 7½ ips 2 6x4" Hi-Fi Speakers

7" Empty Reel

Patch Cords

SUPERBLY STYLED ... WITH THESE DELUXE FEATURES

Heads — Separate record/playback and erase heads, mu-metal shielded.
INDIVIDUAL CHANNEL RECORD BUTTONS—
Permit sound-with-sound recording.
INDIVIDUAL CHANNEL VOLUME, CONTROLS
— Provide volume adjustment on playback, act as input level controls during recording.

ing.
POSITIVE-ACTION CONTROL LEVER — Assures easy control of rewind, fast forward and record/playback functions.
2 SPEEDS — Choice of 7½ ips or 3¾ ips by means of simple capstan adjustment.
PAUSE CONTROL — Provides safe, instant stop for editing. Control is self-holding.
SOUND DEFLECTOR SIDE PANELS — Let you deflet speaker sound for hest staren afdeflect speaker sound for best stereo ef-

fect. HI and LO LEVEL INPUTS - Stereo inputs MI and LO LEVEL IMPUTS — Stereo inputs for recording from microphones, FM stereo tuners, stereo amplifier, radios, etc. MONITOR OUTPUTS — For playback through stereo amplifier, or for headphone monitoring during recording.

INDIVIDUAL RECORDING LEVEL INDICATORS — Provide indication of correct volumers.

ume adjustment on record.

The RK-600A is a complete 4-track, 2-speed stereo tape recorder . . needs no extra amplifiers or speakers. Plug in

speed stereo tape recorder . . . needs no extra amplifiers or speakers. Plug in the microphones supplied and make "live" stereo recordings anywhere play the tape back and hear your recording in full-dimension stereo—you'll be amazed how wonderfully easy it is! RK-600A also has inputs for recording from radios, FM tuners, Hi-Fi amplifiers, etc. Simply connect the patch cords supplied to your program source and follow the simple recording procedure, either in stereo or monaural . . lets you keep a permanent recording of your favorite musical programs, etc. The recorder also makes "soundwith-sound" recordings—a feature that allows you to accompany yourself in a duet, add your voice to pre-recorded music, etc. And, "sound-with-sound" rape allows you to re-record one track if you SPECIFICATIONS

are dissatisfied with it moving the recording on the other

Other features include fast-forward and fast-rewind facilities, simple tape threading arrangement, individual neon recording level indicators, a hito tone switch, speaker muting switch, plus extension speaker outputs. The RK-600A is housed in a smart vinyl covered case with handle and is supplied complete with 2 dynamic microphones, patch cords and empty 7" reel. For 117V. 60 cycles AC. Dimensions: 161/2W x 11D x 71/2"H. Imported. Shpg. wt., 31 lbs. wt., 31 lbs.

Model RK-600A Stereo Tape Recorder 99 H 1506WX Net 129.50

7" reel of 1200 ft. Lafayette Recording Net 1,59

SPECIFICATIONS

Frequency Response: 40-15,000 cps at 7½ lps, 40-9,000 cps at 3¾ ips. Stereo Separation: .45 db. Wow & Flutter: As low as 0.25%. S/N Ratio: 45 db. Reel Capacity: 7" reel. Speakers: (2) built-in 4" x 6" oval. Audio Output: 1.5 watts per channel. Erase Frequency: 80 kc. Heads: 4 track—separate record/playback and erase heads, mu-metal



\$6.00 Monthly

Takes up to 7" Reels

95 TAKES REELS UP TO 7" • WITH RECORDING LEVEL INDICATOR • ½-TRACK DOUBLES PLAY AND RECORD TIME . TWO SPEEDS-34 OR 71/2 IPS 4x6" SPEAKER FOR FINE TONAL REPRODUCTION . PROVISION FOR EXTERNAL SPEAKER . PERMITS DIRECT RECORDING FROM RADIO OR PHONO

Perfect for home, school or office. At home, the RK-142 proves ideal for parties or recording your favorite musical performance. Handy fool-proof operation has been provided by a specially designed lever type record switch which completely eliminates the chance of accidential erasure. At 3¾ ips., the RK-142 provides more than 4 hours recording on long play ½ mil 2400 ft. tape reel. A special 4x6 inch heavy-duty permanent magnet speaker furnishes an exceptionally fine tonal quality. Record level indicator facilitates recording by showing you when the volume control is correctly set. Jacks provided for microphone, phono and extension speaker (special alligator clip cord is supplied). Complete with sensitive dynamic microphone. Finished in attractive scuff-resistant material. Dimensions: 11¾x97xx 7½°, For 110 volts, 60 cycles. Imported.

98 H 1512WX Model RK-142 Deluxe Tape Recorder.

99 H 1512WX Model RK-142 Deluxe Tape Recorder

Lafayette Cat. No. 651

SPECIFICATIONS—Tape speed: 7.5 and 3.75 ips in two speeds. S/N ratio: —42 db or better at 7.5 ips tape speed. Rewind time: 3 min. for 7" reel. Fast Take up Time: 3 min. for 7" reel. Response: Record-playback response essentially flat with table. Wime-Entitler.

with tone at max. treble. Wow-Flutter: 0.2% or better at 7.5 ips; 0.3% at

Take Advantage of Lafayette's Low Tape Recorder Prices

NEW LAFAYETTE RK-675 DELUXE PUSHBUTTON 4-TRACK STEREO RECORDER

DESIGNED TO RECORD FM MULTIPLEX BROADCASTS!

Records 4-Track Stereo, 4 Track Monaural

Plays 4 and 2-Track Stereo and 4-Track Monaural 6 Pushbutton Controls • 2 Speeds

Sound-with-Sound

Automatic Shut-off of Tape Transport Wide Frequency Response for "Life-Like" Reproduction Heavy duty 4 pole Capacitor Start Motor Individual Channel Volume Controls

Separate Interlocking Record Buttons
Magnificent Tone From 2 Full Range Self-Contained
Matched Hi Fi Speakers
Pause Control Provides Instant Stop for Editing

2 Individual Record Level Meters

Digital Tape Counter

An extraordinary self-contained portable tape recorder with professional quality features. Records and plays back 4-track stereo and monophonic tapes at 2 speeds, 7½ and 3¾ ips. Records from any source-radios, FM tuners. Hi-Fi stereo amplifiers or "live" from the quality dynamic microphones supplied. Make sound-with-sound tapes . . accompany yourself in a duet or add your voice to prerecorded music. The rugged tape mechanism features a heavy duty 4-pole canacitar start motor. Gives emocht tangent and the features are leaved to the control of the second tangent and tangent and tangent and tangent and tangent according to the second tangent and tangent capacitor-start motor. Gives smooth tape run low flutter and wow. Automatic shut-off of entire transport at end of tape . . . disengages controls to neutral position . . prevents tape spillage. Easy-to-use push-buttons provide positive control of tape motion. Has separate interlocking record buttons. Magnificent tone is assured with 2 big terlocking record buttons. Magnificent tone is assured with 2 Dig 6x4" full tone speakers and side flaps for better stereo separation. Other features include digital tape counter, pause control for editing, 2 record level meters, and individual channel volume controls. Complete with luxurious simulated leather case, 2 dynamic microphones, cables and take-up reel. For 105-125V 60 cycles AC. Size: 161/aWx7Hx121/a"0. Shpg. wt., 35 lbs. Imported.

98 N 1504WX Model RK.675.

Net 179.95 99 H 1504WX Model RK-675 Net 179.95 28 H 0101 7" Reef of Lafayette Recording Tape ...

SPECIFICATIONS

Net

Frequency Response, Record/Playback: 40-18,000 cps @ 71/2 ips; 40-12,000 cps @ 334 ips. Audio Output: 3-watts per channel, Signal-te-Neise Ratio: —45 db. Interchannel Separation: 45 db or better; Wow & Flutter: 0.2% @ 7½ ips, 0.25% @ 34 ips. Bias & Erase; 80KC; Rewind Time: Less than 4 minutes for 1200 ft. of tape. Speed Accuracy: 98%.

LAFAYETTE RK-137A TAPE RECORDER

Featuring 4-Track Stereo Playback*
with 4-Track Monaural Record/Playback

e Two Speeds — 3¾ & 7½ lps e Pause Lever Provides Instant Stop for Editing e Record — Erase Safety Switch e Fast, Rugged Shift Lever Control e Extension Speaker Jack e High Impedance Monitoring Jack e VU Meter Recording Level Indicator e Electronic Track Selector Switch e Specially Oesigned Heavy-Outy 6x4" PM Speaker e Separate Erase and Record Heads

Speaker • Separate Crase and Record Heads

The RK-137A Tape Recorder contains a fine, quality constructed, smooth tape mechanism. Engineered to provide virtually every wanted tape recorder feature, the RK-137A performs brilliantly, with facilities for 4-track monaural record/playback and 4-track playback (when used with a second channel containing a tape head input such as found in a component Hi-Fi system). Controls are completely functional and are designed and arranged to make the RK-137A a genuine pleasure to use. Features include: a rugged, easy to use shift lever for fast rewind, fast forward, play and record functions; a special push-button safety record switch assures against accidental erasure of tapes; velvet-smooth volume and on-off tone controls; a pause lever instantly stops tape in motion, especially useful for editing; track switch provides fast, dependable electronic switching between tape tracks 1-4 and 3-2. In addition a VU recording level meter has been incorporated to indicate correct volume-setting for recording. Speeds are adjustable from 344 to 74½ inches per second by means of a simple capstan adjustment. From a standard 7" 1200 ft. reel the RK-137A provides over 2 hours monaural record/playback time at 74½ ips and over 4 hours at 334 ips. Jacks are furnished for microphone input, High impedance Radio-Phono Input, Extension Speaker Output, Monitor Output and Stereo Head Output for playback of 2nd stereo channel. Shps. wt., 22 lbs. Imported.

99 H 1511WX Model RK-137A Tape Recorder Net 89.50
7" reel of 1200 ft. Lafayette Recording Tape

reel of 1200 ft. Lafayette Recording Tape

See Our Catalog 650 For Additional Tape Recording Equipment

\$9 monthly Pause Control Two Level Meters Digital Tape Counter Matched Stereo Speakers 2 dynamic mikes

CARRYING CASE

COMPLETE WITH Carrying case, 2 dynamic mikes, autput cables, and 7-inch empty tape



Includes Lightweight carrying case, dy-namic microphone, autput cable, 7 inch empty tape reel.

and erase heads.

sa monthly

RESPONSE: 40-15 000 cps at 7½ ips. 40-9,000 cps at 3¾ ips. S/N RATIO: 40 db. WOW/FLUTTER: less than 0.3%. CHANNEL SEPARATION: 45 db. INPUTS: Radio, Mic. OUTPUTS: Stereo Tape Head, External Spkr. Monitor. AMPLIFIERS: Single Channel; tube-type preamp and power amp. TAPE HEADS: 4-Track Stereo record/playback and grase heads:

SPECIFICATIONS

Lafayette Cat. No. 651 45

LAFAYETTE MODEL RK-650 PROFESSIONAL 4-TRACK STEREO RECORD & PLAYBACK TAPE DECK



- **Deluxe Pushbutton Operation**
- Complete with Built-in Transistorized Record & Playback Preamps
- Automatic Cut-off Switch Stops Recorder at End of Tape or When Tape Breaks
- Separate Record/Play and Erase Heads Smooth, 4-Pole Capacitor—Start Motor 2 Level Indicator Meters

The RK-650 abounds in professional-type features making it suitable to meet every stereo and monophonic recording situation. Tape transport and electronic components are integrated into one lighttransport and electronic components are integrated into one light-weight unit, for use in either a portable carrying case or a hand-some built-in home installation. Has an ultra quiet 4-pole heavy duty, low slip capacitor-start motor and belt-drive for double flutter filtering. Automatic tape and machine stop at end of the tape or during a break in the tape. The Pause control assists in making "pro" recordings by stopping the tape momentarily for editing. Separate channel recording permits sound-with-sound. Clear FM multiplex recording is assured by high (80 KC) bias operation. The second PROFESSIONAL

OPERATING FEATURES TAPE REELS-TAKE UP TO 7" SIZE AUTOMATIC TAPE CUT-OFF

- SWITCH
- C. HEADS—SEPARATE RECORD/
 PLAY & ERASE
 O. TAPE POSITION INDICATOR
 E. INPUT SELECTOR SWITCH
 F. SPEED SELECTOR/POWER ON-OFF
- **RECORO LEVEL METERS** INDIVIOUAL VOLUME CONTROLS
- MASTER VOLUME CONTROL SEPARATE CHANNEL RECORD RUTTONS
- K. PAUSE CONTROL 4 PUSHBUTTON TAPE MOTION CONTROLS
- M. ON-OFF PILOT LIGHT

All tape transport and electronic controls are located on the top panel for easy access. Has positive action pushbutton motor control. For 117V, 60 cycles AC. Tape Deck is complete with preamps, 4 connecting cables and empty reel. Shpg. wt., 20 lbs. Less Case and Microphones. Size: 15VeWx644Hx11½°D. Imported.

99 N 1502WX Model RK-650 Net 109.95

Model RK-650	with deluxe carrying case		
99 H 1503WX		Net	124.95
99 H 1510W	Oiled Walnut base for RK-650	Net	6.95
99 H 4502	Dynamic Microphone for RK-650 Net	ea.	4.75
	,	2 fo	r 8.95

SPECIFICATIONS

Frequency Response, Record/Playback: 40-18,000 cps @ 7½; 40-12,000 cps @ 3¾ ips. 4 transistors, 4 tubes; 1 full-wave bridge rectifier. Audio Output: .8 volts per channel. Signal-to-Noise Ratio:

-45 db. Interchannel Separation: 45 db or better; Wow & Flutter: 0.2% @ 7½ ips, 0.25% @ 3¾ ips. Bias & Erase: 80KC; Outputs: 2 audio, 2 monitor. Imputs: 4.

LAFAYETTE 2-SPEED STEREO PLAYBACK TAPE DECK

99 H 1515W



Model RK141

\$6 monthly

SPECIFICATIONS

Frequency Response: @ 7½ IPS, 50-18,000 CPS ± 1.5 db; @ 3¾ IPS, 50-9,000 CPS ± 2 db. Wow & Flutter: 15% @ 7½ IPS, 0.2% @ 3¾ IPS. Cross Talk & Stereo Channel Separation: 50 db. Signal To Noise Ratio: 50 db. Playback Output: with Built-in Stereo Playback Preamplifiers 0.5V. Power: 110-120V 60 cycles AC operation. PLAYS BACK

- Stereo 1/4-Track: 1/2-Track
- Monaural 1/2-Track; Full-Track

Dual NAB Equalized Transistorized Stereo Playback Preamps Allows-Use With Virtually Any Stereo Amplifier • Frequency Response: 50-15,000 cps @ 7½ ips • Accepts Full-Size 7-inch Reels • Automatic Shut-Off At End Of Tape

Precision engineered to satisfy the most discriminating music listener, the RK-141 will playback with upcompromising fidelity ½-track and ½-track stereo tapes plus ½-track and full-track monaural tapes. The RK-141 is equipped with its own built-in 6-transistor dual stereo playback preamplifiers equalized for the NA8 tape curve . . . allows use with virtually any stereo amplifier by merely connecting to the auxiliary, tuner, or hi-level tape inputs. Precision laminated playback head. Automatic shut-off at the end of the tape. The 4-pole, heavy-duty, constant speed induction motor has front panel speed selector switch. In addition, two rugged lever-action controls provide for Rewind, Off, Play and Fast Forward functions. Accepts all size tape reels up to and including 7". Measures 10½DX14½WX5"H. Complete with shielded book-up cables. Shpg. wt.. 17 lbs. Imported.

99 H 1513WX Model RK-141 Stereo Playback Tape deck Net 59.50 Furniture Grade Walnut Base for RK-141, Shpg. wt., 4 lbs.

Furniture Grade Walnut Base for RK-141, Shpg. wt., 4 lbs. 99 H 1514W Not 695 Portable Carrying Case for RK-141. Shpg. wt., 5 lbs.

5 TRANSISTOR PORTABLE PUSHBUTTON TAPE RECORDER



Small, Compact—weighs only 2 lbs.

Uses 2-Track System—Doubles Recording Time Operates on Two 11/2V "C" Batteries

Takes 3" Reels

e Takes 3" Reels

A deluxe, miniature 2-track tape recorder measuring only 7½x6%x 2¾6" and weighing a mere 2 lbs. Records and plays up to 20 minutes (both tracks) on a 300 ft. 3" reel. Special switch on the sensitive microphone lets you stop or start reels remotely—makes the unit ideal for dictating purposes. Has simple push-button operation for Record, Play, Rewind and Stop functions. Circuit is completely transistorized and has push-pull audio output with bullt-in speaker.

offers clear, crisp sound reproduction. Special earphone receptacle for monitoring during recording or for private listening during playback. Uses only 2 inexpensive 1½y² "C" batteries for complete operation. Special design allows recorder to be operated with cover closed...lets you record or play with the unit in any position—even while walking! Housed in a high-impact plastic cabinet in black and gray with silver trim and colored push-buttons, carrying handle. Supplied complete with remote control microphone, earphone, 3" reel of tape, empty reel, batteries. Imported.

earphone, 3" reel of tape, empty reel, batteries. Imported.

27 H 1101 Shpg. wt., 3 lbs. 32 H 4801 Extra 'C' cell battery (2 required)

NORELCO MODEL 101

TRANSISTORIZED

PORTABLE RECORDER

Net 19.95 Net ea.

FAMOUS Wollensak T-524 **4-SPEED TAPE RECORDER**



\$8 monthly Records Up to 3 Hours

1%" Constant Speed Capstan Drive Recording and Battery Condition Indicator

As simple to operate as a portable radio.
Carry it everywhere. Works on six ordinary
flashlight batteries. Push two buttons,
you're recording up to 3 hours on a 4"
reel of tape. Push one button you're playing
back. Dial your favorite bass or treble tone. back, Dial your favorite bass or treble tone. Special speaker provides big clear sound. Rewinds in seconds. High quality dynamic microphone picks up sound from the far-thest points in a room. Constant speed cap-stan drive lets you play tapes on any 17½" 2-track recorder with no loss in sound quality. Record and battery life meter shows recording level plus exact battery condition. Frequency response: 80-8,000 cps. S/N ratio: better than 45 db. Complete with transparent cover, mike cables. Size: 11Wx 8Hx3¾"D. Shpg. wt., 8½ lbs. Imported. 27 H 4801WX Net 99.50

'D' cell batteries for "101" (6 Required) CC-86 Texon Carrying Case for Model "101" Net 7.95

- 4-Speeds; $7\frac{1}{2}$, $3\frac{3}{4}$, $1\frac{7}{6}$, $1\frac{5}{6}$ ips Push-button Operation
- Instant Pause Control
- **Tone Control**
- **Neon Record Level Indicators**
- Records/Plays---2-Track Mono

DELUXE 6 TRANSISTOR PUSHBUTTON TAPE RECORDER



6 Transistors: 1 Diode, 1 Thermistor 334 & 1% ips—Capstan Driven for Constant Speed

Up To One Hour Recording Time Without Turning Tape Over

Takes 3¼" Reels

New 6-transistor tape recorder features capstan drive with governored motor for accurate and constant speed. 3% or 1% ips, allows a full recording time of up to two hours on 600 foot tape—one hour without stopping to turn tape over. Equipped with record level meter without stopping to turn tape over, Equipped with record level meter and battery strength indicator to prevent recording errors. Features sensitive dynamic microphone with remote control switch making a perfect unit for dictation and speech practicing purposes. Also records directly from radio, TV, phonograph, telephone, or other tape recorder. Specially designed "dashboard type" push-buttons give speedy yet accurate operation. Battery life: 10 hours under continuous use. Complete with remote-control dynamic microphone, magnetic carphone, tape, empty reel and batteries. Size: 9%Wx8%Dx2½"H. Shpg. wt., 5 lbs. Imported.

27 H 1001

Net 39.95

27 H 1002 AC Power Pack for above tape recorder 32 H 4801 Extra "C" Cell Battery (4 required) Net 12.95 Net ea.

NEW CONCORD 330 VOICE OPERATED PORTABLE RECORDER



950 Automatic Voice Operation—Sound Starts

-Sound Stops It! Automatic Slide Advance For Unattended Slide Projector Operation Automatic Movie Sync—Synchronize Sound With Movie Projector

Automatic Tape Threading Fully Transistorized—Runs on Flashlight Batteries

The New Concord Model 330 is a fully automatic voice operated portable tape recorder matic voice operated portable tape recorder incorporating many deluxe features. Automatic voice operation provides almost unlimited recording applications — the 330 starts recording whenever a sound is present and stops during silent periods. Frequency response is 50 to 10,000 cps for excellent musical reproduction. Takes up to 5 inch reels and operates at both 1% and 3% lps. Complete with dynamic microphone, earphone, empty reel, sensing tape, and slide projector plug. Uses 6 size "D" cells. Dimensions: 12Wx8¾Dx3¾"H. Shpg. wt., 6 lbs.

27 H 3502WX Model 330 AC Adaptor for 330 Net 12.95

WORLD FAMOUS TAPE RECORDERS

SONY "905" BATTERY OPERATED VOICE ACTIVATED TAPE RECORDER



- Solid State Circuitry . Rechargeable Battery Power
- **Voice Activated Operation**
- A.G.C. Automatically Sets Record Level

The New Sony "905" incorporates several computer-type electronic achievements in this deluxe portable tape recorder. Literally operates at the sound of your voice—simply speak and the "905" instantaneously starts recording! The A.G.C. (automatic gain control) automatically adjusts to changes in recording level completely eliminating recording errors due to very loud or soft voices. Separate detachable recording units and matching amplifier/speaker base which automatically recharges the four penlight batteries. Recording unit weighs only 4½ lbs. and may be used separately or with AC power matching base for full fidelity playback. Speeds: 3¼ and 1½ lps. Reel Size: Up to 3¼ inch. Dimensions: 8½Wx6½Dx 6½7H. Shpg. wt., 8 lbs.
Complete with Matching Amplifier/Speaker System, Dynamic Microphone, Leather Carrying Case, and 4 Nickel Cadmium Rechargeable Satteries.

Batteries. 27 H 6001WX

NEW Wollensak MODEL 1280 4-TRACK STEREOPHONIC TAPE RECORDER



- 4-Track Stereo or Mono Play and Record
- Detachable Wing Speakers
- Automatic Head Demagnetizer

• Automatic Head Demagnetizer

A quality recorder combining exciting features with deluxe styling. Records and plays 4-track stereophonic and monophonic tapes at 2 speeds,7½2 and 3¾ ips with superb fidelity. Has separate detachable wing speakers with big 5x7 speakers which can be placed at optimum distance for best stereo effect. Independent volume and tone controls adjust response to your taste. Features easy-to-use tab controls to control off/speed selector, individual channel record/play and stop functions. Also has reverse/fast forward, index counter, 2 VU meters, automatic head demagnitizers and automatic stop at end of tape. Frequency response: ±3 db 50-17,000 cps ② 7½ ips; 50-8,000 cps ③ 3¼ ips. S/N ratio: 45 db. With 2 microphones, patch cords, reel of tape and take-up reel. Size: 10¾4 with speaker cover x 17½2wx 14″D. For 110-120V, 60 cycles AC. Shpg. wt., 33 lbs.

Net 199.00

DELUXE CONCERTONE MODEL 801 STEREO TAPE RECORDER



featuring

- **Automatic Reversing** for Playback or Recording
- Solid State Circuitry
- 3 Motors
- **Push button Controls**

\$19 monthly

The New Concertone 801 is one of the most advanced stereo recorder — reproducers available today for the serious hobbyist. Offers extreme versatility by employing six heads—two play, two record, two erase—arranged symmetrically on both sides of the center capstan. This ½4 track stereo Bi-Directional recorder allows continuous playback or recording in either direction without reel turnover thus permitting an entire evening of uninterrupted music. SPECIFICATIONS: Two Speeds: 3¾ and 7½ ips. Frequency Response: 30-18,000 cps @ 7½ ips and 40-12,000 cps @ 3¾ ips. Wow and Flutter: Less than .2% at 7½ ips. Signal to Noise Ratio: 50 db. Three Motors. Rewind time: 1200 feet in 45 sec. Output level 1.0 volt. Completely self contained portable with integrated speakers, monitor amplifiers, dynamic microphones, and handsome two-tone carrying case. Size 19¼4Hx14¼Wx85%*D. Shpg. wt., 49 lbs.

Net 397.46

DELUXE Wollensak T-1580 STEREOPHONIC TAPE RECORDER



2 & 4 Track Stereo or Mono Record/Playback

Sound-on-Sound

A superb 2 and 4-track stereo or mono tape recorder plays at 3¾ and 7½ ips. Features sound-on-sound recording. PA voice over play-back, separate volume control on each stereo channel, precision index counter for accurate monitoring, and a balance tone control on each channel. An instant stop switch is provided for precise editing while an automatic shut-off instantly turns the mechanism off when the end of the reel is reached. Incorporated is an automatic head demagnetizer and a self-adjusting breaking system. Specs—13 db at 3¾ ips; Play time: up to 8 hours on 4-track mono, up to 4 hours on 4-track stereo; Power output: 11 watts per stereo channel (22 watts mono); Wow and Flutter: less than 3% each speed; Signalto-Noise ratio: greater than 48 db; Power consumption: 110 volts AC only; Inputs: mike, phono-radio, and preamp. Complete with 2 mikes, vinyl cover, and accessories cables. Size: 6½xx10¼xx11¾". Shpg. wt., 26 lbs. 26 lbs. 27 H 7001WX \$15 monthly Net 319.00

LAFAYETTE RECORDING TAPES

LAFAYETTE'S FAMOUS MONEY-BACK GUARANTEE YOU BE THE JUDGE!

Lafayette's tape is made by outstanding nationally known manufacturers. It is first quality, splice free, red oxide coated, with full frequency response, uniform output and no "drop-outs." Resistant to moisture, heat, cold and abrasion.

We guarantee absolute satisfaction or your money back. If for any reason you are dissatisfied, return the tape at once and we will refund your money less only transportation charges. You are the sole judge.

LAFAYETTE ACETATE BASE RECORDING TAPE

LAFAYETTE

ELECTRONICS

Acetate base magnetic recording tape with uniform standard red oxide coating provides wide range high fidelity response over the audio spectrum. Features poise free reproduction, low abrasion and uniform output. In 1 mil and 1½ mil thickness,

	_				Net Per Reel		
Stack No.	Feet	Reel	Mils	Wt. Lbs.	1-4	5-24	25 Up
28 H 0102 28 H 0103 28 H 0101 28 H 0104	600 900 1200 1800	5" 5" 7" 7"	1½ 1 1½ 1½	1/2 3/4 1 1 1/4	.99 1.20 1.59 1.98	.90 1.10 1.49 1.88	.85 .99 1.35 1.79

LAFAYETTE MYLAR BASE RECORDING TAPE

Mylar base is especially strong, durable and break resistant, and is virtually impervious to heat, cold or humidity. All in clear plastic reels, individually boxed.

					Net Per Reel			
Stock No.	Feet	Reel	Mils	Wt. Lbs.	1-4	5-24	25 Up	
28 H 0105	1200	5"	1/2	3/4	1.75	1.58	1.42	
28 H 0106 28 H 0107	1800 2400	7"	1 1/2	11/4	2.49 3.10	2.25 2.79	2.13 2.51	
20 11 0.07	2400	,	72	474	3.10	2.75	2.31	

LAFAYETTE TENSILIZED MYLAR TAPES




These tapes are of the same high quality as the standard acetate and mylar Lafayette tapes with the added advantages of the tensilized mylar base. Super-strong mylar is prestretched and is highly resistant to breakage, moisture, heat, cold, and humidity. Highly polished, splice-free, quiet, non-abrasive finish. Smooth output throughout the entire audio spectrum. Tensilized mylar gives you the most permanent type of base and is therefore ideal for your most treasured recordings. All are 1/2 mil, thus permitting the maximum amount of footage per reel. Individually boxed.

_		REEL	WT.,	NET PER REEL		
STOCK NO.	FEET	SIZE	LBS.	1-4	5-24	25-UP
28 H 0109	300	3″	1/2	.69	.63	.59
28 H 0110	600	31/4"	1/2	1.00	.90	.80
28 H 0111	1200	5″	1/2	2.25	2.03	1.83
28 H 0108	2400	7"	1/2	3.69	3.39	3.05

NEW KINEMATIX "VOICE-MATIC" VOICE ACTUATED CONTROLS

Model KX5000



Made in U.S.A.

- Converts your Battery operated Tape Recorder to a Voice-Actuated Tape Recorder
- Sound Starts your Tape Recorder—Absence of Sound stops your tape Recorder
- No tools needed—no soldering required

Model KX4000—A new concept in a tape recording accessory. Contact board of KX4000 is inserted between contacts and battery of your present battery operated tape recorder. No soldering required—no tools needed. Now your tape recorder will start whenever a sound is present. The recorder will stop when sound source stops. Has .5amp switching capacity. Complete with sensitivity control which permits you to operate, a recorder from as far away as 15 feet. Requires 2 standard 9 volt batteries (not supplied with KX4000). Dim. 3½"x1"x2¼". Shpg. wt., 1 lb.

28 H 3101L Net 19.95

Model KX5000—Deluxe Version of Model KX4000—Switching capacity—2amp. 2 controls—Sensitivity control and adjustable Pause control which keeps recorder from turning off immediately during pauses between sentences. Includes input jack for external mike—and accessory input jack for use with various household appliances enabling you to turn these appliances on and off.

28 H 3102 L Net 29.95

LAFAYETTE RECORDING ACCESSORIES

LAFAYETTE BULK TAPE ERASER AND DEMAGNITIZERS

- Completely Erases Tape
- Two Erasing Coils
- Erases up to 1" Tapes
- Erases 1/4" Tapes in One Operation-No Reversing
- For 3", 5", 7" or 10½" Reels

Standard Model

Professional Model



A carefully designed and precisely manufactured tape "degausser" for complete erasing of A carefully designed and precisely manufactured tape "degausser" for complete erasing of tapes. Just place the tape reel on spindle of demagnetizer, slowly rotate 2 or 3 turns, take off, and that's all. Reduce tape hiss to the level of new "virgin" tape. Two completely separate coils are used for doubly-effective erasures, even of large, 10½" reels. Will erase 1" wide tape. An extra powerful unit for heavy-duty use—draws over 9 amoeres. Can be used to demagnetize tape, magnetically stripped film, plus tools and watches. Has a heavy, custom finished case, a rugged non-magnetic top, heavy duty on-off switch and power cord. Has built-in fuse. Pilot light prevents accidentally leaving it turned on. Size 6¼x7½x3½". 105-125V Govela Sher wit 14 lb Importable. 125V, 60 cycle. Shpg. wt., 14 lbs. Imported. 99 H 1516 Professional Model

STANDARD MODEL

Similar to professional model for all size reels but handles only standard size ¼" tapes or smaller and reel must be turned over once. Has separate spindle positions for 10½" and 3, 5, and 7" reels; non-magnetic bakelite plate for reel rest. One powerful coil consumes 5 amps. Metal case 7½x44x3½". Shog. wt., 9 lbs. Imported.

LAFAYETTE TAPE HEAD DEMAGNETIZERS



Has 3 complete sets of removable pole pieces: straight, 45° and 90° for quick easy use with any tape head. Removes magnetism that accumulates in every tape head insuring optimum signal-to-noise ratio. For 110 Volt 60 cycle. Shpg. wt., 1 lb. . Net 3.95

24 H 0901

ECONOMY MODEL

Features very strong field with a single probe. Its thin cross-sectional size allows it to be used on all heads. For 110V 60 cycle. Shpg. wt., 12 oz. Imported.

Net 2.89

Net 1.49

Net

REEL LOCKS



Set of Two

Holds tape recorder reel in place by locking spindle to reel. Especially useful if recorder is in vertical position. Will not interfere with normal operation of reels. Easily removable. Shpg. wt., 6 oz. Imported.

99 H 1519 Set of two

TWIST-LOCK YRENE CANS



Buy the Set - save and GET THE CHEST FREE!

dust-free, moisture-proof unbreakable to usterize, mosture-proof untreakable styrene tape cans in storage chest. Can has foolproof twist lock feature and is ribbed for convenient stacking. Center locking stud prevents reel movement on all 7" reels and most 3" and 5" reels. Shpg. wt., 6 lbs. 28 H 6510 Net 4.75

TWIST LOCK CANS ONLY
28 H 6511 Lots of 6 ea. .40 Single ea. .45 Lafayette Cat. No. 651

TAPE CLEANER



Tape is impregnated with special formula cleaner. Simply run through like regular roll of tape. Entire job done in 2 minutes. Can be reused many times. 100' roll on 5" reel. Shpg. wt., 8 oz.

28 H 2001 28 H 2002 3" Ree!





METAL STORAGE CANS

Cans are ribbed for easy storage. Precision Cans are ribbed for easy storage, Precision fit. Finished in grey. Av. shgp, wt., 8 ozs. 28 H 6305 3" can lots of 6, Ea. .18 Singly, Ea. .20 lots of 6, Ea. .27 Singly, Ea. .30 Lots of 6, Ea. .36 Singly, Ea. .30 Singly, Ea. .39

CLEAR PLASTIC REELS

Individually boxed plastic reels for recording tape. Av. shpg. wt., 4 oz. singly. 28 H 2903 31/4" real Intend 6 Fa

20	п	2303	344	ree	: 10 t5 01 0, E	340
					Singly, Ea	26
28	Н	2904	5"	reel	Singly, Ea	26
					Singly, Ea	29
28	н	2905	7"	reel	lots of 6. Ea	38
					Singly, Ea	45

TELEPHONE PICKUP FOR RECORDING TELEPHONE CONVERSATIONS



Induction telephone pickup, Telephone conversations can now be picked up with no tapping of wires or special telephone circuits. Simply place the phone base, either cradle or upright type, on the pickup plat-form and connect the leads to the high impedance input of any medium gain audio amplifier, or directly to any tape, disc or wire recorder. Shpg. wt., 8 ozs.

Net 1.95

TELEPHONE PICKUP COIL



Designed to feed into the microphone input of either a tape recorder or any high gain amplifier. Easily attached to the telephone by suction rubber type attachment. The coil is electrostatically shielded to minimize hum pick-up. When properly positioned on telephone handset, the output of this device is more than adequate for a fully modulated tape recording. Complete with 5' shielded cable. Shpg. wt., 6 ozs. 99 H 6197 Imported



Handy 6 ft. lead has insulated alligator clips Handy 6 ft. lead has insulated alligator clips at one end and RCA phono plug at the other. Supplied with shielded phono plug adapter to adapt the RCA phono plug to standard phono plug if necessary. Attach alligator clips to speaker terminals and simply plug other end into tape recorder. Ideal for recording from Radio, Phono or TV. Shpg. wt., 8 or Imported. 8 oz. Imported. 99 H 1517 Net .67

METAL TAPE STORAGE CHEST

STANDARD CASE: Sturdy all steel carrying case. Holds 12 7" or 5" reels and cons. Twin snap locks. Platinum gray hammerloid finish. Metal separators. Includes index cords. Shpg. wt., 5 lbs. 28 H 1501

TAPE HEAD CLEANER




HC-2 HEAO CLEANER. Removes grime and accumulated oxides from tape heads. 2 oz. bottle has applicator cap. Wt. 4 oz 26 H 6031

See Our Catalog 650 For Additional Tape Recording Accessories

ELEGANT HOLIDAY GIFT SELECTIONS

NEW SLIM TYPE "CONSOLLETTE" HIFI MUSIC CENTER

- FM---AM Radio
- FM Stereo Radio
- Stereo-Monaural Phonograph
- Stereo Lite Indicates FM Stereo When FM Stereo Broadcasts Are Being Received



A beautifully integrated AM-FM, Stereophonic FM radio, and a deluxe phonograph in a slim, gracious cabinet with "Triplex" design. This elegant consolette can be placed on a table or wall mounted. Also mounts on optional Grand Stand. Each cabinet contains on a table or wall mounted. Also mounts on optional Grand Stand, Each cabinet contains one 8" woofer, one 4" tweeter, and crossover network. Brilliant sound reproduction. Automatic record changer plays 16, 33, 45 LP and 78 RPM records. Intermixes all sizes of same speed automatically. Automatic shut off, Stereo cartridge has turnover diamond and synthetic sapphire needles. Compatible for standard LP's and 78. Deluxe 15 watt stereo amplifier. Stereo lite indicates when FM stereo broadcasts are being received. 5 controls: balance/AFC, dual tone/on-off, dual loudness, Selector for AM-FM, FM stereo and for phonograph tone range. 25Wx13%DX14¾"H. U/L approved 110-120V; 60 cps AC. Shpg. wt., 44 lbs.

Grand Stand for above phono-Add decorator accent to any room. In brushed chrome with smart black satin finish square base. Shpg. wt., 8 lbs. 7.95 24 H 4903WX

Grand Stand

Optional

FISHER MODEL 50 30-WATT TRANSISTORIZED PORTABLE STEREO SYSTEM



\$11 monthly

30 Watt Transistorized Stereo Master Control Amplifier

Garrard 4-Speed Automatic Record Changer Pickering Magnetic Cartridge With Clamend

The Model 50 is a true high fidelity system in a "suitcase"—combines the high quality of a Fisher 30 watt solid state amplifier, a Garrard 4-speed automatic turntable and a Pickering magnetic cartridge. The speaker system utilizes two 6" woofers and two 2½" tweeters which may be placed up to 20 feet apart. Six controls and switches, including a Speaker On-Off switch, provide complete control of the volume, balance and tonal characteristics of program material, and a front-panel headphone jack facilitates private listening with headphones. Both a tuner and tape recorder, or other highlevel source can be played through the Model 50 by connecting them to the two pairs of high-level inputs provided on the rear of the case. The turntable, which can intermix a stack of 7, 10 and 12 inch records, shuts the entire system off automatically after the last record has been played. Power Requirements: 105-120 VAC. 50/60 cps. Size: 244/s/x144/s%". Shpg. wt., 35 lbs. The Model 50 is a true high fidelity system in a "suitcase"-

Net 229.50 24 H 5601WX FISHER MODEL 75-Same as above except the components are mounted in an elegant walnut wood cabinetry.

Net 269.50 Take Advantage of Lafayette's Low Phonograph Prices

COLUMBIA MASTERWORK M-4500 DELUXE SOLID STATE STEREO COMPONENT SOUND SYSTEM



\$9 monthly

Handsome three-piece system is enclosed in Justrous hand-rubbed hand crafted oil walnut hardwood

Features Precision engineered Carrard AT-6 automatic intermix record changer — with magnetic cartridge and diamond stylus 11 Transister solid state steree Powerful amplifier

A splendid stereo masterpiece highlighting convenience, flexibility, and performance. Efficient design and solid state circuitry are combined to produce a truly superb sound system. The amplifier, stereo cartridge, record changer, speakers, and cabinetry are carefully matched to provide faithful frequency response. The heart of this superb system consists of a powerful solid state 30 watt peak power stereo amplifier featuring absence of heat and noise, instant warm-up, and amazingly clean output. The two speaker enclosures each contain one 6½" woofer and one 3½" tweeter combined to offer stirring "highs" and clean resonant "lows". The Garrard AT-6 automatic intermix changer plays all sizes and all speeds. Tone arm has built-in stylus pressure gauge. Ultra-sensitive magnetic stereo cartridge contains a long life precision ground and polished diamond needle. Controls: Volume with loudness compensation, Balance, Bass, Treble, on-auto/off, Mono/stereo Selector, and Aux/Phono Selector. Auxiliary inputs for use with AM tuner, FM tuner, or tape recorder. Ut Approved. For 110-120V 60 cps AC. Size: 18½"Wx8½zHx14¼"D. Each Speaker Encl. 17½wx 10Hx6"D. Shpg. wt., 54 lbs.

THE IDEAL HOLIDAY GIFT - A POPULAR PRICED LAFAYETTE PHONOGRAPH



For the young. Plays all records, all speeds

24 H 6101

Plays up to 12" monaural records at 162/3, 331/3, 45 or 78 RPM. A Plays up to 12" monaural records at 10-9, 3343, 45 of 78 KPM. A single lever selects any speed. The lightweight pickup arm is equipped with a single all-purpose needle for all records. Has volume control with on-off switch. Retractable 45 RPM chuck. Fine quality Alnico V PM speaker. Attractive 2-tone leatherette covered case. For 110-120 volts, 60 cycles. Size: 11-4/4Wx104/2Dx54/2"H. Shpg. wt., 8 lbs

Net 14.95



QUALITY LAFAYETTE 4 Speed MANUAL PHONO

Full Size Case; Plays 12" Records with Lid Closed
 Separate Tone and Volume Controls

With this portable phonograph you can play any record up to 12" size at 1645, 3345, 45 or 78 RPM with the lid closed. Has retractable 45 RPM chuck. A single lever selects any speed. The lightweight pickup RPM chuck. A single lever selects any speed. The lightweight pickup arm is equipped with a turnover cartridge with dual synthetic sapphire styli. Has both tone control and volume control with on-off switch. Fine quality Alnico V PM speaker. Attractive 2-tone wedgewood blue and white case; decorative escutcheon plate is chrome finished. For 110-120 volts, 60 cps, AC. Dimensions: 13Wx12½Dx 6¾/H. Shpg. wt., 10 ibs.

24 H 4204

Net 19.95



DELUXE LAFAYETTE AUTOMATIC 4 SPEED PORTABLE PHONOGRAPH

Features Deluxe "Maestro" 4 Speed Automatic Record Changer

•

Plays 1645, 331/3, 45, and 78 RPM Records
Intermixes Different Size Records of the Same Speed

Automatic Shut-Off After Last Record

A deluxe automatic phonograph in a beautiful two-tone interlaced blue and white case. Plays 16/3, 33/3, 45, and 78 RPM records. Intermixes different size records of the same speed. Automatic shut-off after last record has been played — motor shuts off and arm returns to rest position automatically. Separate tone and volume controls, on-off reject switch. Fine Alnico V PM speaker for magnificent sound reproduction. Turnover cartridge with dual synthetic sapphire stylus. For 110-120 volt 60 cycle AC. Size: 15x14x7". Shpg. wt., 15 lbs.

24 H 4201W 45 RPM Spindle for above phonograph. 24 H 4203 Shpg. wt., ½ lb.

Net 1.49

NEW LAFAYETTE SOLID STATE AUTOMATIC STEREO PHONOGRAPH



New Tilt-Down Stereo Phonograph-Solid State Circuitry -2 Removable Wing Speakers

- Deluxe "Maestro" 4 Speed **Automatic Intermix Changer**
- 6 Transistors—2 Silicon Diodes
- Instantaneous-Warm-Up
- 4 Controls
- Compatible—Plays Stereo and Monaural

MONAUFAI

A handsome new solid state stereo phonograph with drop lid design and detachable wing speakers. Equipped with deluxe "Maestro" 4-speed automatic intermix changer with turnover stereo cartridge and dual synthetic sapphire stylus. Plays all size records and all speeds. Automatic shutoff after last record. Front slide speed selector and record size selector. Precision built solid state stereo amplifier features 6 transistors and 2 silicon diodes. 4 controls — channel 1 volume, channel 2 volume; channel 1 tone, channel 2 tone. Heavy duty 5* Alnico V PM speaker in each wing department. Beautifully styled all wood case is covered in rich charcoal grey and white trim with silver overlay. For 110-125V 60 cycle AC. Dim.: 24½x14½x8¼x.

24 H 4202WX Shop wt. 24 lbs. Nat 57 es.

Net 57.95 Net

LAFAYETTE'S FINEST SOLID STATE HI-FIDELITY STEREO PHONOGRAPHS

LAFAYETTE SOLID STATE PORTABLE STEREO PHONO

- Garrard 4-Speed Intermix Automation Changer Solid State Stereo Amplifier—6 Transistor, 2 Sili-
- con Diode Full Wave Rectifiers Instantaneous Warm Up
- Diamond Stylus
- Compatible—Plays Stereo and Monaural

A beautifully designed solid state stereo phonograph. Features famous Garrard 3-speed Intermix automatic changer that will handle all sizes and all speeds of both stereo and monaural records and will intermix different size records of the same speed. Automatic shut off after last record of the same speed. Automatic solution and the last lead that has been played. Contains on-off and reject switch. Deluxe stereo amplifier features 6 transistors and 2 silicon full wave rectifiers. Equipped with heavy "Power transformer," 3 stages of amplification—3 audio control functions—separate full range compensated loudness and balance controls. plus dual channel tone controls. Each detachable speaker wing contains a high efficiency 5" extended range speaker with 1.47 oz. magnet. Turnover ceramic cartridge with synthetic sapphire and diamond stylus—attractive charcoal black case. For 110-120VAC. 60 cycle. Size 174/2x13x94/2". Shpg. wt., 24 lbs.

24 H 0206WX Net 69.95 21 H 3713 45 RPM Spindle for Garrard changer Net 3.80



STATE PORTABLE STEREO PHONO DELUXE LAFAYETTE SOLID

- Solid State Circuitry 8 transistors 2 silicon diode full wave rectifiers
 Garrard 4-speed Intermix Automatic Changer
 4 Speakers—4 Controls—Superb tone

- Diamond Stylus
 Drop Lid Construction

● Drop Lid Construction

A superb solid state Lafayette Portable stereo phono with outstanding tone quality. Powerful push-pull 8-transistor amplifier circuit produces 20 watts peak music output, Amplifier is equipped with heavy duty Power transformer. 4 Controls: loudness, balance, bass, treble. Each detachable wing has one 8" heavy duty extended range speaker and one 3" tweeter plus a built in 8-ft. extension cord for wall-to-wall full dimensional sound realism when separating speakers. Wide range turnover stereo cartridge is equipped with a diamond stylus for LP and stereo records and a synthetic sapphire stylus for standard 78 RPM record. The famous Garrard 4-speed Intermix Automatic changer will handle all sizes and all speeds of both stereo and mono records. Intermixes different size records of the same speed. Automatic shut off. Housed in beautifully styled all-wood Automatic shut off. Housed in beautifully styled all-wood case with charcoal gray covering and fine white backing. Dim. 23x16¹/₄x8¹/₄" for 110-120V 60 cps AC. Shpg. wt., 34 lbs.

21 H 3713 45 RPM Spindle for Garrard changer Net 3.80 afay ette

MAGNIFICENT LAFAYETTE SOLID STATE "TABLE TYPE" PHONO

- Powerful 24-watt amplifier 10 Transistors, 2 Silicon Diode Full Wave Rectifiers
- 2 Deluxe Separate Matching Speaker Systems with high Efficiency 8" Extended Range Speakers for Rich Brilliant Sound Reproduction

An elegantly styled Solid State Stereo "Table Type" phonograph which will enhance the decor of any room. Offers rich brilliant sound reproduction. The control center consists of a 10-transistor integrated amplifler which produces 24 watts peak music output—amplifier features push-pull output, heavy duty power transformer. Four audio control functions heavy duty power transformer. Four audio control functions—separate variable bass and treble, loudness, and balance. 2 separate matching speaker systems feature high efficiency 8" extended range speakers. Famous Garrard "AT5" 4-speed precision automatic turntable plays 7". 10", and 12" records in all 4 speeds. Intermixes different size records of the same speed. Wide range turnover stereo cartridge is equipped with a diamond stylus for LP and stereo records, and a synthetic sapphire-stylus for standard 78 RPM records. The phonograph and matching speakers are housed in Genuine walnut wood cabinets with beautiful all walnut finlsh. Dimensions: Cabinet 19½x14x8". Speaker Encl. 13½ x10x4". For 110-120V 60 cycle AC. Shpg. wt., 40 lbs.


Net 119.95 21 H 3712 45 RPM Spindle for Garrard AT5 Net

Famous Garrard AT-5 4-Speed precision automatic Turntable



SELECTED PHONO ACCESSORIES

LAFAYETTE DIAMOND **NEEDLES**



OUR TOP SELLING DIAMOND NEEDLE DOZEN

STOCK NO.	FIG.	FIT CARTRIOGE NO.
24 H 0179	1	All Ronette, Astatic & BSR Monaural
24 H 0136	2	GE-"A" Series
24 H 0137	3	GE 4G Series VRII
24 H 0146	2 3 4	Sonotone 2T, 5T & 7T Series
24 H 0150	- 5	E-V 21 & 26 Series
24 H 0153	6	Ronette BF40, OV Series, Admiral Ensign
24 H 0154	7	Sonotone 8T & 8TA
24 H 0157	8	RCA 106770, A, 106771, A.
24 H 0158	9	Monarch (BSR)
24 H 0161	10	GE VR-227
24 H 0164	11	Astatic 17 & 17D
24 H 0172	12	Sonotone 16T Series

RECORD CLEANING KIT



Deep clean your records the modern way. Specially prepared detergent anti-static record cleaning fluid protects your valuable records as it cleans. Just a few drops on new velvet-foam rubber applicator mitt will give your records a professional cleaning job. Supplied with anti-static fluid, velvet applicator mitt and polyurethene pad. 24 H 8502 Shpg. wt., 10 oz. Net 1.29



TONE ARM

Ends groove and stylus damage caused by accidental dropping of tone arm onto record, greatly extending record life. Accurately and smoothly lowers tone arm into run-in groove and lifts arm off record at end of play, Ideal for "cueing," Designed to fit practically every known turntable arm as well as record changer with manual features. For temporary and permanent installation. Shpg. wt., 6 oz. Imported.

RADIO BROADCASTER/PHONO OSCILLATOR



2 TUBE AMPLIFIER WITH TUBES

(Fig. A) Uses a 50L6 and 35Z5 rectifier tube. Has volume control with switch and tone control. Chassis size: 2½x3½". For 110 125V, AC or DC. With cord and plug, tubes, diagram but less output transformer. Shpg. wt., 3 lbs. 24 H 1302

THREE TUBE AC-OC PHONO AMPLIFIER

(Fig. B) Equipped with a variable tone control and a separate volume control with off position. Delivers up to two watts output. Phonograph motor connects to the amplifier. Uses 3 tubes: 12AV6, 50C5, and 35W4 rectifier. For 110-125V AC or DC. 21/8x41/2" steel chassis. With cord and plug, schematic, but less tubes and output transformer. Shpg. wt. 2 lbs. 24 H 1303 Net 3.75 (Fig. C) OUTPUT TRANSFORMER matches output tube to 3-4 ohm voice coil. Shpg. wt., ½ lb. 24 H 8401 Singly ea. .49 In lots of 5 ea.

STEREO/MONAURAL PICKUP



Employs a high-output crystal turnover cartridge for either stereo or monaural aperation. Frequency response, 20-18,000 cycles; output, 1 volt per channel. Crosstalk between channels is 15 db or more down. Each channel has a separate shielded output cable. Travel lock arm rest prevents accidental damage to records. The pickup arm is designed to be mounted in a single, circular hole, $\frac{1}{2}$ in diameter. Equipped with side attachment for easy lifting and setting down. Durable plastic construction. Shop, wt. 7 oz. Durable plastic construction. Shpg. wt., 7 oz. Imported. 99 H 1024

Net 1.95 Synthetic Sapphire LP replacement needle for above 99 H 1027 Net .49 Synthetic Sapphire STD replacement needle 98 H 1028 Net 49



LAFAYETTE STEREO AUDIO CABLES

Two shielded insulated cables, of different color tones, for easy identification of chan-nels) inside a common chrome grey plastic jacket, providing two completely isolated channels. Avg. shpg. wt., 6 oz. Imported.

Length		Net
36"	Phono pin'	1,17
6′	plugs at	1.3
10'	all ends.	1.62
	36" 6'	6' plugs at

THE "DUST BUG"



Automatically removes dirt and dust on each playing. Light plastic arm mounts by suction cup. Can be permanently mounted by rubber cement. The bottle of antistatic cleaning fluid has a built-in wick for application to a brush and pad at the end of arm. Shpg. wt., 6 oz.

24 H 2501 Standard model (A) Imported Net 5.95 CHANGER DUST BUG (B). The tuft and pad assembly clips onto arm of changer. Per-

forms the same as the standard model. Shpg. wt., 4 oz.

24 H 2502 Changer model (B)

imported Net 4.95 DISPENSER OF ACTIVATING FLUID. For Dust Bugs. 24 H 2504

24 H 2503 Replacement Plush Pad and Nylon Brush Net 1.50

RECORD STATIC and DUST ELIMINATOR




Sprays a fine mist which keeps your record clear of surface noise created by static (com-mon to all vinyl records) and clean of dust attracted by the

static charge. Prevents groove and needle wear caused by static-dust and keeps records lustrous. Extends their life. Two applications a year is sufficient. Enough for hundreds of records. Shpg. wt., 8 oz. 24 #6601

PHONO AND HI FIDELITY ACCESSORIES

ROBINS PHONO ACCESSORIES



(A) RB-88 CLEAN-SWEEP. Genuine Camel's Hair Brush sweeps entire tracking surface of records (up to 12") with each revolution. Removes dust and other particles from sound grooves. Pressure sensitive adhesive pad on machined aluminum base permits, easy secure mounting on any phono equipment. Can be swung out of the way when not in use. Complete with instructions for assembly and use. Wt. 8 oz.

24 H 8001 Net 3.60

(B) NB-1 "KLEENEEDLE" AUTOMATIC CHANGER BRUSH, Removes "dust-blob" each time arm passes over brush. Adjustable height.
Pressure sensitive base for easy mounting on any changer. Wt. 4 oz.

24 H 8004 Net .93 (C) E-15S ROUND BOTTOM 12" RECORD COV-ERS. Package of 15. Keeps records free from dust and moisture. Wt. 7 oz.

(D) EJ-15S SQUARE COVERS FOR STANDARD 12" RECORD JACKETS. Package of 15. Wt., 7 oz.

24 H R012



HI-FI STOP-O-MATIC FOR HI-FI TEMS. Automatically turns off amplifier and changer when last record has played. You can fall asleep to your favorite music without fear of "burning up" your equipment. Has switch permitting use of amplifier without changer. Two models. Size 6x2x11/2".

Wt., 2 lbs. HFS-1 for European changers. Garrard, Collaro. Thorens, etc. 24 H 8023

Net. 5.50 HFS-2 for U.S. made changers, Webcor, etc. 24 H 8024 Net 5.50

(F) CHANGER COVERS—Soft durable plastic Fits most changers. Protects changer from

dust, moisture, etc. Type CC-5S 17×15x8¾". Wt. 8 oz. 24 H 8025 Net .98 Type CC-2 121/2×15×8". Wt., 7 oz. 24 H 8026 Type CC-1 13x131/2x8". Wt. 7 oz. 24 H 8027 Net 1.17

(F) TURNTABLE COVERS-CC-3S 22x161/2x9". Wt., 6 oz. 24 H 8028 Net 1.25 CC-4 171/4x171/2x9". Wt., 6 oz. 24 H 8029

CC-678 Rigid, collapsible, 12x1542x5' Net 2.94

STYLOGRAPH STYLUS INSPECTOR

A real boon to record collectors. Helps protect your records and insure continued quality reproduction. An invaluable aid to inspect other small pointed objects too. Shows a large illuminated silhouette on a 1x1½" ground glass screen. Easy to use, needle cartridge need not be removed from tone arm. Complete with on/off switch, bulb and two penlight batteries. Size: 5\%x 1\5\x1\5\%\. Shpg. wt., 8 oz. Imported. 99 H 1032 Net 3.29

32 H 4802 Extra bat. for above, ea. Net .13




LAFAYETTE STYLUS PRESSURE GAUGE

Lafayette's stylus pressure gauge is an accurate device that allows you to read with the pickup in normal playing position. Range, 0-30 gm. No spring and minimum moving parts. Shpg. wt., 1 lb. Imported, Net 99 H 1011

HIGH FIDELITY ACCESSORIES

LAFAYETTE MULTIPLE **6 SPEAKER SWITCHES**





Multiple Speaker Switch Constant impedance device for controlling any 6 remote speakers; up to 63 different combinations. Wall mounting with brass plate. Shop, wi 10 oz. With instructions and hardware.

99 H 0054 Imported Multiple Speaker Switch Net 2.10 Identical to above but mounted on flat, gold-embossed plate for mounting on flat panel. 31/2×25/6". Shog. wt., 10 oz. Imported.



PERMITS REMOTE SELECTION OF ANY 3 PAIRS OF SPEAKERS

(Fig. A) A constant impedance speaker se-(rig. A) A constant impedance speaker se-lector switch for multiole-speaker Steren Mi-Fi. Selects 3 sets of speakers in any combination, with up to 60 watts of audio power. Mounted on an attractive, gold-fin-ished steel electric outlet olate. 23%x4½". Shpg. wt., 1 lb. Imported. Stereo Speaker Selector Switch.

99 H 0098 Net 1.59 (Fig. B) As above in enclosed case 2Hx4Wx 3"D.

99 H 010 1 Net 2.10

STEREO LEVEL BALANCE CONTROL



Logarithmic Curve

Provides individual level control for stereo speakers. Varies "brilliance" or "presence"
Controls stereo extensions without mis-Controls stereo extensions without matching. Dual control mounted on concentric shart. Gold-finished brass plate and attractive black knobs with gold trimming. L pad for 8 ohm circuits. Plate is 21/8" across: overall depth 31/4". Shpg. wt., 10 oz.

99 H 6140 Level Control Net 2.89

DELUXE STEREO LEVEL BALANCE CONTROL 395



• Dual Concentric 8 ohm L Pads

 Logarithmic Curve Two phono jacks enable you to plug in extension or monitoring speakers from the front. Screw terminals in the rear provide for a simple, permanent

for a simple, permanent hookup. Control mounted on concentric shaft. Brushed brass plate with attractive black with gold-trim knobs. Concentric 8 ohm L pads. Use it to control volume on a second set of speakers. Plate is 4½x2¾"; from front of knob to plate 1"; Overall depth 3¾". Shpg. wt., 1 lb. Imported. 99 H 6141 Deluxe Level Control ... Net 3.95

BALL BEARING HEAVY DUTY SLIDES

Drawer slides made of 16 gauge steel. Supports 50 lbs. Ball bearing, double-extension type, drawer slides. Length 15" travel length 11", extended 22". Shpg. wt., 5 lbs. 20 H 5201 per pair Net 1.75 11", extended 22". Snpg. Wt., 3 IUS.
20 H 5201 per pair Net 1.75
SHORT TYPE. Same construction as above but 13" long; travels 9"; extends to 22".
20 H 5202 per pair Net 1.50

LAFAYETTE L PADS

L pads for use as "bril-liance" controls to vary tweeter level, or as "presence" controls to

vary midrange speaker level. Both wire-wound elements are concentrically mounted within one plastic housing. With gold-finished metal escutcheon plate, mtg. screws, and attractive black knob. Size: 1½" dia., 7½" deep (less shaft), 2½" deep overall. Shpg. wt., 6 oz. Imported.

pad for 8 ohm circuits 99 H 6134 L pad for 16 ohm circuits

Net 1.39 Net 1.39

LAFAYETTE T PADS



99 H 6135

T Pads Constant impedance control to adjust speaker vol-ume. With brass satin plate for wall mounting. With all parts and instructions. Shpg. wt., 10 8 ohm T Pad. Imported.

8 Onm 1 7 See No. 1 No.

LAFAYETTE REMOTE SPEAKER **FADERS**

Remete Speaker Fader Provides adjustable volume level for Radlo. TV, Hi-Fi and remote speaker. Gradually increases volume on one speaker while diminishing volume on the other. May also be used to adjust volume for 1 speaker. Gold plate for front panel mounting. With Instructions, 99 N 6138 Shpg. wt., 6 oz. Imported. Net . 89 Remote Speaker Fader. Same as above ex-

cept for wall mounting. 99 H 6139 Shpg. wt., 6 oz. Imported.Net .89

See Our Catalog 650 For A Complete Listing of Hi-Fi Installation Accessories

PHONO AMPLIFIERS AND HI-FI ACCESSORIES

Toward Stereo/8 AMPLIFIER



Compact Low Silhouette Styling!

- Separate Stereo Volume-Balance Controls
- Variable Tone Control With On-Off Switch
- Front-Panel Phono-Tuner Switch for Selection of Phono or Tuner
- Selector Switch for Monaural or Stereo Operation


Ideal for that low cost stereo system you are planning for your living room, den, bedroom or business. It's petite size lends itself easily to any location—it's attractive low silhouette styling will blend beautifully with the furniture decor in any room of your home or business. Excellent for converting your present monaural console or portable to stereo.

or portable to stereo.

Controls include separate Left Channel and Right Channel Volume-Balance Controls, Stereo/Monaural Mode switch, Variable Tone control with On-Off switch, Phono/Tuner Selector switch; 4 jacks in rear for stereo tuners and stereo crystal or ceramic phono cartridges; 2 pair of 4-ohm output terminals accept most speakers. Tubes and components mounted horizontally for compactness. Complete with case. Tube complement: 1-12AX7, 2-35C5, and 1-35W4. Size: 7½WX2%4X55%"D. Imported.

99 H 0047 Shpg. wt., 6 lbs. Net 17.95

STEREO/5 AMPLIFIER



- Individual Stereo Volume-Balance Controls
 - For Both Stereo and Monaural
- Fully Wired-Ready For Stereo

A stereo amplifier priced to fit everyone's purse. This rugged, precision made dual channel stereo amplifier will amaze you with its fine quality. . Ideal for that low cost stereo system you're planning for your home or business. Perfect for converting your present console or portable to stereo. Controls include separate left channel and right channel volume controls, stereo-monaural mode switch, tone control switch and on-off switch. Provision for crystal or ceramic cartridge. 4-ohm output terminals accept most speakers. Tube complement: 2-35C5, 1-35W4 and 1-12AX4. Size: 4½Hx5½WX 4½°D. 115 volt 60 cycles. Shpg. wt., 5 lbs. Imported.

99 H 0046 A stereo amplifier priced to fit everyone's purse. This rugged, pre-

COMPLETE STEREO PHONO SYSTEMS

Featuring Lafayette/Webcor 4-Speed 4-Pole Automatic Changer

Complete system consists of Trutest Stereo/8 Stereo Complete system consists of Irutest Stereo/8 Stereo
Amplifier, Lafayette—Webcor Automatic 4-speed Record Changer with wide-range stereo turnover cartridge, with diamond stylus. 2 Lafayette SK-109
Miniature Speaker Systems in Attractive Mahogany
veneer finish, Above system supplied complete with
25' speaker cable for each speaker, less changer base.
Shog. wt., 26 lbs.
99 H 9902WXM

Net 62.50

Same system as above except with Stereo/5 stereo amplifier instead of Stereo/8 stereo amplifier.

99 H 9903WXM Shog, wt., 25 lbs. Net 57.50 99 H 9903WXM Shpg. wt., 25 lbs. 24 H 1210W Mahogany base for changer

AS LOW AS

\$6 Monthly





ROTRON WHISPER FAN

- Super Silent, Compact
- **Reduces Service Costs**
- Ideal For Cooling Hi-Fi Equipment

The ideal fan for cooling hi-fi equipment. Extremely quiet, introduces no distortion, yet it moves 60 cubic feet of cool air per minute. Lets your equipment last up to 40% longer! Compact in design, easily installed in any position. Airflow is reversible. Advanced heavy system; slow speed, and prelubrication will provide years of maintenance-free operation. For 115VAC, 60 cps. 7 watts. Size: 1½" deep and 41%," square.

24 H 7501 Shpg. wt., 1 ib.

Net 14.85



MULTI-INPUT SELECTOR CONTROL

Connects any one of 5 inputs to 1 output AM, FM. phono, tape, aux. Completely shielded to prevent hum. Complete with mounting hardware. 5 phono jacks input, 1 phone jack output. Shpg. wt., 1 lb.

99 H 1029 Multi Input Selector

Net 1.76

lafayette® STEREO VU **BALANCE METER**



Balances Stereo Systems

Ends the problem of balancing your stereo system. Two precisely damped loudness meters provide a continuous comparison of speaker levels. Scales calibrated in "Volume Units" and percent. 1.2 volts input sensitivity for 0 VU or 100 percent indication. The special calibrating switch and 20 db attenuation controls permit exact matching of channels. Greater than 8,000 ohm impedance permits connecting to output circuits without loading. The entire unit is housed in an attractive plastic case 6 Wx344Hx276"D. Imported. 99 H 5038 Shpg. wt., 3 lbs. Stereo Balance Meter Net 11.95

FAMOUS QUALITY LAFAYETTE FM/AM TABLE RADIOS

NEW! QUALITY FM/AM TABLE RADIO


Distinctive Styling

Rich Tone 4" Speaker

Effective AFC For Stable FM Reception

Built-in Ferrite Rod AM Antenna

Smartly styled table-top or shelf radio which receives rich, static-free FM and quality AM broadcasts. Completely self-contained, requires no external FM or AM antennas. These are built-in for superb reception. Powerful 4" speaker offer full-bodied FM sound and clear AM broadcasts. Ef-fective AFC circuit keeps FM stations tuned-in with low drift; enjoy many hours of pleasant, re-laxed listening. AVC prevents blasting, keeps sound level relatively even. Handsome, easy-toread slide rule dial has precision vernier control for simpler tuning. Superheterodyne circuit has 6 tubes, 2 diodes. Stylish hi-impact plastic cabinet finished in ivory and gold. Imported. Size: 91/8Wx 61/8Hx51/2"D. For 110-120 volts 50/60 cycles AC. Shpg. wt., 5 lbs. Imported. 17 H 3002



DELUXE FM/AM DUAL SPEAKER TABLE RADIO

Two 4-Inch PM Speakers for Full Dynamic Range

External 300-0hm Antenna Input Terminals

Greater Sensitivity

• Provision for Extension Speaker

AFC for Low Drift FM

High Fidelity FM/AM table radio. Fine furniture styling. Dual 4-inch PM speakers, in an acoustically correct cabinet, produce rich full-frequency sound on both FM and AM. Features improved AFC action which "locks-in" FM stations. A supersensitive AM antenna brings in distant stations clearly while reducing unwanted noise. An FM wire antenna is provided to assure clear FM reception. An external 300-ohm FM antenna can be attached to built-in input terminals for improved reception of distant stations. Beautifully finished Oiled Walnut cabinet and easy-to-read slide rule dial with an on off neon indicator light Meets FCC requirements for radiation shielding. A receptacle on the rear of the radio allows easy, quick addition of an extension speaker. For 110-120 volts, 60 cps AC or DC. Size: 17½Wx7¾6Hx5¾6"D. Shpg. wt., 8 lbs. Imported. 99 H 3502

Net 39.50

Magnificent Rich Tone!

\$5.00 Monthly



Beautifully Styled Oil Walnut Cabinet

MAGNIFICENT FM/AM CLOCK RADIO

Automatic Telechron Clock

Wake-to-Music Plus Alarm

Sleep-Switch-Lulls you to Sleep


Powerful Alnico 5 PM Speaker

Loudness Control

Combines a fully automatic Telechron clock with luminous hands and a superb FM/AM radio. Handy sleep-switch permits you to slowly drift-off to dreamland while the radio shuts itself off at a preset time. Beautiful AM or FM music awakens you pleasantly. Optional buzzer alarm also includ-ed. In addition to a standard AM broadcast radio, a quality FM radio, with AFC will expand your listening pleasure. FM antenna is built into line cord. External FM antenna terminals built-in for fringe area use. Slide rule dial for easier tuning. Beautiful molded plastic cabinet in antique white and gray with silver trim. Tubes: 50C5, 12AV6, (2) 12BA6, 12BE6, 12D18 plus selenium rectifier. Size: 13½Wx7Hx 5½"D. For 110-120 volts, 60 cps AC only.

Take Advantage of Lafayette's Low Radio Prices

\$5.00 Monthly



FAMOUS LAFAYETTE TRANSISTOR PORTABLE RADIOS



LAFAYETTE "TINY 6" **6-TRANSISTOR RADIO**

Sensational "Pull-In" Power . . . Clean Crisp Tone

- Sensitive Superheterodyne Circuit
- Vest Pocket Size Built-In High-Gain Ferrite Antenna
- Economical—Uses Only One


LAFAYETTE "MIGHTY 9" 9-TRANSISTOR RADIO

- Compact, Shirt-Pocket Size Powerful Superheterodyne Circuit
- Clear, Crisp Tone
- Includes Leather Case, Earphone and Battery

Precision-made and handsomely styled, this feature-packed transistor radio uses 9 transistors in a powerful superheterodyne circuit with built-in ferrite antenna to really pull in those AM Stations. Push-pull audio output circuit with 2½" speaker assures exceptionally clear, crisp tonal quality. Automatic volume control circuit minimizes fadeout and sudden blasts of volume. Slim & compact, it can easily be slipped into pocket or purse—it's an ideal traveling companion wherever you go. Has handy thumbwheel controls, easy-view dial window, earphone jack, and operates on a single low-cost 9-volt battery. Comes complete with leather case, earphone (for private listening), and 9-volt battery. Shpg. wt., 1 b. Imported. 98 H 35131. 99 H 3513L 99 H 6021 Extra Battery, Shpg. wt., 2 oz.



10 TRANSISTOR TWIN SPEAKER RADIO



includes Leather Case, Earphone and Ratteries



Separate Twin Speaker Design Offers Magnificent Full Fidelity

- 10 Matched Transistors, 1 Diode **Varistor**
- Sensitive Superheterodyne Circuit

Push-Pull Power Amplifier

A superbly designed high quality AM portable radio. Twin speakers act together to combine hi and low tones into a magnificent full fidelity sound. Powerful 10 transistor, 1 diode, 1 varistor superhet circuit is equipped with an automatic gain control stage. Virtually eliminates blasting and fading. Powerful push-pull amplifier delivers 180 mw of power. Super sensitive built-in ferrite core antenna assures greater sensitivity and selectivity. Easy to use magnified stide rule tuning is incorporated in the beautiful golden metal panel. Plays for hours on 4 penlite cells. Tuning range, 535-1605KC. Fine quality leather cases are included for the radio and separate earphone. Complete with batteries and earphone. Size: 634Wx334HX 154°0. Shog. wt., 1½ lbs. Imported.

17 H 34031.

Net 19.95
28 H 4802 Extra Battery for above (4 required)

Net . 13

32 H 4802 Extra Battery for above (4 required) A Lafayette Gift Certificate Solves Your Christmas Gift Problems

NEW LAFAYETTE 10 TRANSISTOR AM/FM PORTABLE



MAGNIFICENT TONE QUALITY

- Big Set Performance Telescoping FM antenna
- 2 Band Stide Rule Diat
- Adjustable tone control

Tubeless, cordless static-free FM are yours with this thrilling performer. High efficiency true-tone 2½x3½" oval dynamic speaker and push-pull audio output deliver a full range of sound on FM or AM to enhance your radio listening pleasure. FM drift is virtually eliminated. Super-powered circuit employs 10 transistors, 1 thermistor and 3 diodes, AVC. Only 4½x8½x2". It offers undreamed of convenience—take it anywhere. Features: precision vernier dial tuning, builtin ferrite AM antenna. chrome plated telescoping 27" FM whip antenna, earphone jack for private listening. Operates on 4 inexpensive penlite cells. Low current drain gives long battery life. Complete with batteries, leather case and earphone. Imported. Shpg. wt., 3½ lbs.

17 H 6802L Net 24.95 Net 24.95

32 H 4802 Extra batteries. Uses 4. Wt., 2 oz.

14-TRANSISTOR 3-BAND FM/AM/SW PORTABLE RADIO

CONVERTIBLE/PORTABLE WITH 2 SEPARATE DIALS FOR USE AS A PORTABLE OR TABLE MODEL





Tunes 540-1600 KC, 4-12 MC, 88-108 MC

DELUXE 15 TRANSISTOR 3 BAND FM/AM/SW PORTABLE RADIO



Complete with batteries and earphone.

\$5 monthly

- Tunes 590-1600KC, 3.5-10MC, 88-108MC. Effective Automatic Frequency Control
- Operates as an Audio Amplifier
- Low Current Drain

A hi-quality portable receiver which not only performs as a radio, but also operates as an audio amplifier for you to play your records through. Advanced audio output circuit is coupled directly to the speaker for better overall frequency response. This direct coupling and a large 4x6" PM dynamic loudspeaker combine to deliver excellent tonal quality. 15 transistors plus 5 diodes assure high sensitivity. Automatic frequency control is incorporated for stable performance. The large "easy to read" dial is controlled by a 12:1 tuning ratio drive. Easy positive dial settings. Covers 3 Bands—540-1600KC (Standard Broadcast). 3.5-10 mc (shortwave), and 88-108MC (FM). Auxiliary input for multiple adapter—expandable circuitry. Complete with 4 standard D-cell batteries. earphones and vinyl leather case. Size 7.4Hx11Wx3.4"). Case covered with vinyl leather. Shpg. wt., 7 lbs. Imported.

17 H 0104L

28 H 48M6 Batteries for shore (4 convicted). 32 H 4804 Batteries for above (4 required)

Net ea.

59

DELUXE NEW LAFAYETTE 9-TRANSISTOR VHF AIRCRAFT AND BROADCAST PORTABLE RECEIVER

Tunes: 535-1605KC and 110-135MC

Powerful 9-transistor superheterodyne circuitry

Separate VHF RF Amplifier Stage

Thermistor To Compensate for Temperature Changes



superbly engineered and crafted portable receiver.

\$5.00 Monthly

QUALITY 8-TRANSISTOR AM-MARINE BAND PORTABLE RADIO



Complete with Leather case, earphones, and battery

- Covers AM and Marine Bands
- Highly Sensitive Rod-Antenna Plus Built-In Ferrite Core Antenna

32 H 4802 Extra Z cells for above

Net ea. .13 AM-SW 8-TRANSISTOR PORTABLE RADIO Same deluxe circuitry as above but covers AM (530-1600 KC) and the 3.9-12MC band for short-wave listening.

POWERFUL 9-TRANSISTOR AM PORTABLE and TABLE RADIO

• 9 Transistors, 1-Diode, 1-Thermistor

• Big Tone 31/2" PM Speaker

Precision Vernier Tuning

Genuine Top Grade Cowhide Cabinet

Receive top performance and glorious tone from this highly attractive portable radio. Entire cabinet is made of genuine top grain cowhide. 3½" PM speaker gives "big-set" tone even in noisy outdoor areas. Superior tone and cabinetry make this deluxe set ideal for use annywhere in your home. Powerful 9-transistor circuit really pulis in stations. Uses six readily obtainable flashlight batteries. Features, vernier tuning for easy station selection, built-in ferrite rod antenna, earphone, integral leather case with handle, and batteries. Dimensions: 734Wx514Hx212"D. Shpg. wt., 5 lbs.

29 H 3504 Imported

32 H 4801 Extra "C" batteries, (use 6) wt., 2 oz.

ea. Net .13

FULL RICH TONE





THE TRANSCONTINENTAL "SOLID STATE" 11 BAND AM-FM SHORTWAVE PORTABLE

SUPERB PERFORMANCE MAGNIFICENT TONE

16 Transistors

8 Diodes

Super Sensitive Tuner

Variable Selectivity

Automatic Frequency Control

— 11 BANDS: —

MW 540-1600Kc SW 20.5-22.5Mc LW 150-400Kc FM 66.5-72.5Mc 2-4Mc FM 78-88Mc 4-9Mc 88-108Mc SW 9-12Mc FM 118-132Mc



SW 14.5-18.5Mc



Complete With Earphone and Batteries

only

The TRANSCONTINENTAL is an extremely versatile multiband portable radio receiver and offers 11 reception bands making it useful anywhere in the world. Besides the standard Medium and Long Wave bands, the four FM bands can be used for standard FM broadcast and as a monitor four FM bands can be used for standard FM broadcast and as a monitor for airdrome control towers. The five short wave bands include ship-to-ship, marine, weather, amateur and international broadcasts. Features special module components which can be easily replaced in the event of set failure. Three major circuit boards are designed for easy, immediate replacement. A single tuner is used in the LW, MW, and FM bands to eliminate duplication and simplify service. FM circuit can be locked for stable operation with switchable AFC. Selectivity can be

switched for improved audio reproduction and extended side band reception. Large ferrite bar antenna for LW and MW bands, and 5.6 foot multi-section whip antenna for SW and FM broadcasts. A 2-Way speaker system consisting of a 4" woofer and 1½" tweeter offers excellent reproduction. Separate jacks for external antenna, earphone, speaker, and microphone/phonograph. Uses six 1.5 volt batteries. Shpg. wt., 12 lbs. Imported.

17 H 6903WX

Net 99.50

Extra Size "C" Flashlight Batteries. (6 required) 32 H 4801

NEW! LAFAYETTE 10-TRANSISTOR AM PORTABLE RADIO

only



- Compact, Shirt-Pocket Size
- 10 Transistors, Diode Thermistor
- Geared Vernier Dial For Precision
- Big 2½" Dynamic Speaker
- Includes Leather Pouch, Earphone and Battery

A full 10 Transistor shirt-pocket portable masterfully styled and engineered. High quality 2½" dynamic speaker provides rich tone which is truly impressive. Vernier tuning is smooth, accurate, large direct reading circular dial lets you pinpoint stations without fuss or magnification. Precise front panel thumbwheel control adjusts volume, turns set off. Built-in ferrite bar antenna and powerful superheterodyne circuit pulls in stations near and far. High import plastic case is finished in black with silver aluminum front panel. Earphone jack for personal listening. Complete with leather case, earphone and single low cost 9-volt battery. Size: 4%HX 2%WX18½"D. Shpg. wt., 1½ lbs. Imported.

17 H 01021 Net 12.68
SS H 8021 Extra 9-volt battery Net .21

PANASONIC R-8 MINIATURE SOLID STATE AM TABLE RADIO



6 Transistor — 1 Oiode Circuit Only 7x3x3"

Battery Powered

A finely engineered miniature table radio. Use anywhere you want to enjoy your favorite programs. Advanced 6 transistor—1 diode circuit delivers full size table radio sound. Operates on 3 economical penilite batteries. Does not require an external power source. Convenient compartment for cigarette clips, pins, etc. Small size won't

17 H 3006 Shpg. wt., 4 lbs. Imported

PANASONIC 777 FM/AM FM-STERED



Precision circuit has 11 tubes and 9 diodes. Two full range 61/2' Precision circuit has 11 tubes and 9 diodes. Two full range 642"
PM speakers in swing up or swing out enclosures for best channel separation. AFC control and Monaural FM blocking switch combine with convenient stereo tuning eye to assure stable stereo reception. Has variable tone and balance controls, Built-in AM and FM antenna. 1½ watts audio output per channel. Walnut finish cabinet and 2 speaker extension cables, Dimensions: 35½x7¾x6¾" (opened). For 110-120V, 60 cycles AC. Shpg. wt., 22 lbs. Imported 17 H 3004WX

AMPLIVOX T.M. ALL-TRANSISTOR SPFAKER-AMPLIFIER



- Cabinet Coupled Bass Oriver
- 2 Speakers For Full Instrument Range
- Molded Royalite Case

new 5-watt all transistorized audio amplifier. Features 2 HI-Fi speakers with cabinet coupled bass driver for full instrument range. Three instrument inputs allows use with bass Three instrument inputs allows use with bass as well as standard guitar or accordion. Features advanced, up-to-date solid state circuitry which assures utmost reliability. No warmup necessary; ready to use instantly. Custom designed cabinet. Separate volume and tone controls. Acoustical case of handsome molded Royalite (used in finest luggage) for durability. Controls are located at the top for convenient adjustment. 117V AC Powered. Size: 10x14x5". Shpg. wt., 8 lbs. 13 H 8201WX



5-WATT TREMOLO

A complete 5-watt amplifier with exciting tremolo control, UL approved. Has Hi-Fi speaker for faithful sound reproduction. One speed and one strength control for tremolo. Case covered with silver and tan tweed keratol. Control panel in black and gold with large matching black and gold control knobs.
For 115V 60 cps, AC. Size: 19x16x6". Shpg.
wt., 18 lbs.
41.50

5-WATT SPFAKER **AMPLIFIER**



Features 8" speaker for faithful reproducreatures o speaker in faithin reproduc-tion. Top-mounted control panel has tone and volume control and inputs for three instruments. Three-tube chassis. Housed in 2-tone cabinet with attractive lattice-work grille cloth. Case size: 16Wx6Dx13"H. AC-DC 60-cycle operation. Shpg. wt., 18 lbs. 13 H 8718WX Net 29.95 **NEW! The "BIG BEAT".**

> **Exclusive with Lafayette Built in-Completely Transistorized Amplifier!**

Double Cut Away Solid Mahogany Body

3 Piece Laminated Neck With Adjustable Truss Rods

Rosewood Fingerboard With 10 Position Markers

Individual Machines With White Markers

• Individual Machines With White Markers
• Precision Fretted-Uniform "FEEL"

An Exceptionally fine guitar with a "Show-Stopper" finish, PLUS a built in specially designed and engineered miniature transistorized amplifier! A new concept incorporating all the fine professional features; lucid, sparkling tone; easy action; up to date styling; sleek, slim, double cut-away design; powerful magnetic pick-up; separate tone and volume controls; exciting "sparkling burgundy" finish; blonde maple neck, hand rubbed and polished; auditorium size, 40¼"x13½" The self contained amplifier affords perfect portability with the tone range and volume of "stationary" amplifier did not self contained amplifier affords perfect portability with the tone range and volume of "stationary" amplifier units. May also be used with any external guitar amplifier. Equipped with external jack and cord. Shpg. wt., 15 lbs.

79.95

Batteries for above (2 required)

99 H 9058WX

99 H 6021

LAFAYETTE PROFESSIONAL CUTAWAY ELECTRIC GUITAR

Net ea.

.21

Imported

Auditorium Size-421/2"x171/2" • Dual Adjustable Pickups

Five Controls—including Solo/Rhythm Switch

Laminated Arched Top and Back e Laminated Arched Top and Back
Grand auditorium size—plus professional design—engineered for professional performance. Laminated maple neck with oval rosewood fingerboard. Six large inlaid position markers and nickel sliver frets. White, pin-striped celluloid binding on top and back edges. Nickel plated hardware, deluxe machine heads, two sensitive pickups with individually adjustable pole pieces. Five controls permit choice of units, vary tone and volume, select between bridge pick-up for solo and forward pick-up for rhythm work. Arched laminated top and back in a shaded walnut finish with golden sunburst. Size 42½x17½x3½² Less case. Shpg. wt., 18 lbs. Imported.

Net 59.95

GUITAR-AMPLIFIER COMBINATION

Consists of 99 H 9058WX guitar, 99 H 9078WX 20-watt amplifier, and 99 H 9043 Tremolo foot switch. Shpg. wt., 50 lbs. 99 H 9901WXM

LAFAYETTE MODEL LA-75 20-WATT MUSIC AMPLIFIER

Inputs
Delivers 20 watts of clean power, to a built-in 12" heavy-duty 20-watt speaker or to an external 4, 8 or 16-ohm speaker. 3 inputs: two instrument inputs and one microphone input for voice. Frequency response: ± 3 db from 33 cycles to 20Kc on voice input: ± 3 db from 33 cycles to 15Kc on instrument inputs. Mike input sensitivity is 9 my RMS. 6 tubes. 153%"H (including rubber feet) x 191/6Wx81%", D. Carrying handle. Imported. Shpg. wt., 30 lbs.

99 H 9078WX

Net 89.50

Net 89.50

99 H 9078WX
FOOT SWITCH to remotely control the tremolo in the LA-75. Equipped with cable terminated in standard phone plug to fit corresponding jack on 1A-75. Shpg. wt. 1½ lbs.
Net 5.95

LAFAYETTE® DOUBLE CUTAWAY—DUAL PICKUP **ELECTRIC GUITAR with Tremolo Tailpiece**

• 2 Adjustable Pickups • Individual Tone and Volume Controls

 Individual Rocker Switches
 Solid Mahogany Body—3 Piece Laminated Neck Elegant double cutaway design features tremolo tailpiece and detachable stell reinforced warpproof neck. Solid Mahogany Gleaming, hand rubbed finish body. Rosewood fingerboard with 8 white inlaid markers and 20 frets. 2 microphone pickups each adjustable for tone and volume balance. Separate tone and volume controls. Sensitive pickups have individual adjustment screws for each string. Chrome plated guard plate. Highly polished shaded mahogany finish. Size 39Lx12Wx111/4"D. Less case. Shpg. wt., 10 lbs. Imported. 99 H 9060WX Carrying Case

13 H 8713WX Shpg. wt., 3 lbs.

GUITAR-AMPLIFIER OUTFIT

Consists of above Guitar, 5 watt amplifier with 8" speaker, tone and volume controls and carrying case. Shpg. wt., 35 lbs.

79.95

"VALUE" ELECTRIC GUITAR

Magnetic Pick-up • Individual Adjusting Screws

Individual Tone and Volume Controls

The perfect instrument for the budget-minded musician. Features double cut-away solid body construction for that true, "twangy" electric guitar sound and rugged dependability. Other features are a sensitive magnetic pick-up with individual adjusting screws, individual tone and volume controls, 20 fretts with 6 marked positions. Comes complete with connecting cord with standard plugs on each end. Deep mahogany color with sunburst. Shpg. wt., 12 ibs. Imported

99 H 9022WX GUITAR OUTFIT: Includes 99 H 9022WX guitar, 13 H 8718 amplifier, and 13 H 8712WX case. Shpg. wt., 35 lbs. 13 H 9003WX

CARRYING CASE ONLY. Shpg. wt., 3 lbs. 13 H 8712WX

Net 8.95





OUTSTANDING MUSICAL INSTRUMENTS

DELUXE DUAL PICKUP GUITAR/AMPLIFIER COMBINATION

An outstanding double cutaway guitar in mahogany solid body with hand rubbed finish. Reinforced steel neck, oval rosewood rinish. Reinforced steel neck, oval rosewood fingerboard, 20 frets, Inlaid pearl markers. Dual magnetic pickups with Individual string adjustment. Controls: 2 volume, 1 tone, 2 selector switches. Also LA-75 20-watt hi-fi amplifier with heavy-duty 12" speaker. Shpg. wt., 45 lbs. Imported. Guitar Case and Amplifier 13 H 9001WX. Net 159.95

Deluxe Guitar only. Wt., 15 lbs. 13 H 8714WX .. Net 89.95

Carrying Case only, Wt., 3 lbs. 13 H 8715WX

TRIPLE PICK-UP DOUBLE-CUTAWAY **ELECTRIC GUITAR COMBINATION**

A 3-piece outfit featuring Triple-pickup professional guitar in double-cutaway style. Maple reinforced neck with adjustable steel rod and 2 parallel truss rods. Adjustable bridge. 3 magnetic pickups, individual adjustments, 3 volume, 1 tone control, selector switch. LA-75 20-watt hi-fi amplifier with heavy-duty 12" speaker. Shpg. wt., 48 lbs. Imported. Guitar, case and Amplifier

Guitar, case and Amplifier. 13 H 9002WX Net 179.95 Guitar only. Shpg. wt., 15 lbs. Net 109.95 13 H 8718WX

Case only, Shpg. wt., 3 lbs. 13 H 8717WX

COMPLETE ELECTRIC ACOUSTIC **GUITAR OUTFIT**

This complete 7-piece guitar outfit features a standard-size electric acoustic guitar that can be used with or without amplifier. Outfit includes 5-watt speaker/amplifier, imitation guitare generalisk neckstrap, con-Case only; wt., 3 lbs.

7 PIECE "ECONOMY" OUTFIT

Net 7.95

6-piece special guitar outfit with beginner's record course. You get: guitar, guitar bar, record course, 3 guitar picks, extra set of strings, neck cord. Guitar has hardwood body and steel reinforced neck. Imported Complete Outfit. 13 H 8723WX Shpg. wt., 9 lbs.... Net 21.95 Gultar Only, 13 H 8724WX Shpg. wt., 7 lbs..... Net 18.88-

ARCHED TOP GUITAR

AKUNEU IUF QUITAN
A grand concert size, F hole guitar with
glossy mahogany finish. White celluloidbound ebony finish fingerboard. Has adjustable bridge and nickel-plated adjustable
tall-place. Heavy gauge shell celluloid pick
guard and nickel-plated machines with
white buttons. Shpg. wt., 7 lbs.
13 H 8728WX

Net 18.95

FOLK GUITAR

CLASSIC SPANISH GUITAR

OLASSIC STANISM GUIIAR

A carmencita classic-type guitar combining outstanding craftsmanship and materials. Back, sides and neck are of genuine mahogany and top is of spruce. Steel reinforced neck and nylon strings. Top edge is bound with heavy sparkling brown celluloid. Slotted headplece, white button machines. Shpg. wt., 11 ibs. imported.

13 H 8729WX Net 32.95

Case for above 13 H 8720WX Shpg. wt., 4 lbs.....Net 8.95

Musical Instruments are Available on Easy Pay Plan-See Center Insert A

Highly polished mahogany back, sides and neck. Inlaid pearl position markers, white patent pegs, white bone nut. Strings are carefully gauged nylon. Sound hole bound with black and white celluloid and decorated with iniaid purfling. Gives the warmh of tone and ease of response to satisfy any player. Shpg. wt., 4 lbs. imported.

Net 14.95

ELECTRIC BASS

Deep-voiced bass tones with quick, easy response. Contour-cut solid body and 30-piece adjustable steel reinforced neck. Rosewood fingerboard with 20 frets. Heavy duty pickup with individual tuning screw for each string. 45" long, 1234" wide. Polished, hand rubbed finish. Shpg. wt., 15 lbs. Imported

DRUM COMBO OUTFIT

14x20" single-tension bass drum with tomtom and cymbal holders. 14x51/2" tom and cymbal holders. 14x5½" snare drum with separate tension, flanged hoop, metal snare, professional throw-off, 12x8" matching tom-tom with separate tension, flanged hoops. Accessories include a 12" cymbal, drum pedal with adjustable beater and springs, disappearing spurs, sturdy snare-drum stand, holder for tom-tom and eticks lengthed. sticks. Imported. 13 H 8701WX Shpg, wt., 45 lbs... Net 109.95

PROFESSIONAL TUNABLE BONGOS

Pure white perfect calfskin heads for best rhythm effect. Sparkling color finish. Sturdy construction with heavy plated hardware. Four tuning lugs on each bongo, Head sizes 734" and 645". Overall 7" deep. Complete with Tuning Key. Shpg. wt., 5 lbs. Imported. 13 H 8704 Net 15.95

ELECTRONIC METRONOME

A smart, modern electronic metronome that A smart, modern electronic metronome that uses transistors and is battery operated. Features a bright neon light which flashes in synchronization with an audible beat. Dial also provides adjustment for suitable tempo (40-208). Battery lasts almost indefinitely. 6" high and 7" wide at base. Shpg. wt., 2 lbs. Imported. 99 H 9083 ... Net 14.95

SNARE DRUM

An exciting 14x5½" separate tension snare drum with metal snares, tone modulator, heavy-duty throw-off, flanged hoops, rolled rims, nickel plated hardware. Bright sparkle finish. Complete with norwood metal stand, sticks, brushes, instruction book. Shgg. wt. 15 lbs. imported.

13 N 8705WX Net 34.85 An exciting 14x51/2" separate tension snare

"RENE DUVAL" CLARINET OUTFIT

Quality clarinet made entirely of selected grenadilla wood. Tuned for the key of Bb, Boehm system, 17 keys, 6 rings. Mouth-plece, cap, ligature, reed, music lyre, swab, grease cup and quality case of plush-lined fabric covered veneer. Shpg. wt., 8 lbs. Imported.

13 H 8710WX .. Net 89.95

TRUMPET OUTFIT

An outstanding trumpet with beautiful pro-fessional styling with nickel-silver tubing and trim. Valves feature nickel silver conand trim. Valves reature nickel silver con-struction with top springs and slotted no-twist guides. Body is of brass, clear lac-quered finish. With mouthplece, music lyre and plush-lined case with large accessory compartment. Shpg. wt., 14 lbs. imported. 13 N 8709WX. Net 79.95

"RENE DUVAL" ALTO SAX OUTFIT

professional instrument with smooth, A professional instrument with smooth, light key action and rich, full tone. Integral one-piece tone holes, drawn from the body. Has removable key guards, genuine mother-of-pearl-fingertips on keys, and extra-heavy reinforced bottom guard. Equipped with popular C#, Bb, C# with articulated G and automatic high F key. Bb, C# and C keys located on right side are facing forward to prevent contact with clothing. Gladstone type case with silk plush lining. Shpg. wt., 20 lbs.

13 H 8711 Imported. Net 159.95 **NEW "ARTISTRY"** CLASSIC GUITAR

 Violin Finish Maple True Classic Design **Superior Materials Used Throughout** \$6 monthly

The "Artistry" classic guitar features two-piece violin finish maple back and sides with narrow grained spruce top. Excellent tonal qualities meet the critical demands of the most discriminating classic guitarist. Fan braced with steel reinforced maple neck. All edges bound to the control of the control to the control t

> METHOD FOR GUITAR By JOE FAVA



As low as 149

A contemporary approach towards comprehensive mastery of the guitar written in a clear concise manner by a professional. The strings are learned in order of their difficulty with musical arrangements for study. Profusely il-

13 H 8706 Book (1st position) 40 pages Net 1.49 13 H 8707 Book II (2nd position) 40 pages Net 1.49

(Higher positions) 48 pages . Net 1.98

HOW TO PLAY THE GUITAR

Famous "Music Minus One" Records!



The easy way to learn all the chords and rhythms on your guitar. Has vocal accompaniment; ballad styles; folk, country and western; rhythm and blues; shuffle beats. Features guitar demonstration and text by George Barnes, spoken commentary by Bob Mersey.

24 H 4508 Shpg. wt., 1 lb. Net 3.50

Interested in Electronics? The Ideal Gift For Young and Old!

LAFAYETTE "EXPLOR-AIR" 4-BAND RECEIVER KIT

4 Bands for Total Coverage

550KC-1600KC 1650KC-5.5MC 5.5MC-16MC 16MC-30MC

Covers 10, 15, 20, 40, 80, 160 Meter Amateur Bands Tunes International Broadcast, Citizens Band, Maritime, Aeronautical and WWV Time Signals • Complete Band Switching from Front Panel • Bandspread Tuning Built-in 4" Speaker

e Built-in 4" Speaker

Lafayette's sensational shortwave receiver kit is a complete shortwave and standard broadcast set which covers the entire region from 550 kilocycles to 30 megacycles. Four whole bands of fascinating programming. Perfect for language students and shortwave listeners.

Only a regenerative circuit can offer such amazing performance and yet be so simple to build. Building this fine kit is an absolute pleasure—it's so well designed you can't go wrong. Kit includes all the parts you need, and the detailed step-by-step instruction book with its glant pictorial drawings shows you just how to put them together. One front panel knob does all the bandswitching, immediately taking you from band to band. All colis are prewound for greater accuracy.



Made In U.S.A.

Complete 4 band coverage of broadcast stations, international broadcast bands, amateur, maritime, and WWV time signals. Big 4" speaker and sensitive circuit with 50C5 output stage and 12AT7 regenerative detector and amplifier stages give you all the volume you want. Phone Jack for privacy automatically disconnects speaker. All controls are on the front panel: On-Off Volume, Main Tuning, Band Spread, Bandswitch, Antenna Tuning, and Regeneration. 110 volt 50-60 cycle AC-DC power supply. Size: 10x7x5".

Size: 10x/x5".

18 H 0905 (Less Cabinet) wt., 5 lbs. 22.95
Leatherette covered Wooden Cabinet for above. 1 lb.
Net 2.85

TUNE IN THE WORLDI

LAFAYETTE SUPER-TROLTM R/C **TRANSMITTER**

*MEETS FCC REGULATIONS

Assembled-tested-guaranteed.
Crystal controlled with .01% tolerance crystal as per FCC regulations. Range approximately one mile. Will operate any 27.255 MC R/C receiver. Only 8½x2¾x3¾x*. Includes antenna, tube, crystal, and instructions. FCC license applications enclosed — no examination required. Less batteries. Shpg. wt., 2½ lbs. Imported Net 14.95

SUPER-TROLTM. R/C RECEIVER

Completely wired and tested receiver—extremely sensitive and stable. Completely enclosed—ideal in boats—or case may be removed if desired. Ingeniously constructed to withstand vibration and shock. Features external fine tuning—antenna "snap" lead—plug for power and actuator connections. Requires one 1.5V battery and one 67.5 Volt battery. Size determined by use. Measures only 3x294x11/2". Complete with tube and instructions. Less batteries. Shpg. wt., 8 oz. imported **Imported**

99 H 9028 BATTERIES REQUIRED:

SPECIAL COMBINATION OFFER

99 H 9032M Consists of R/C Transmitter and R/C Receiver — Combination 22.90

MULTI-PURPOSE ELECTRO SERVO MECHANISM



 Powerful, Motor Driven R/C Actuator

Operates with any single channel R/C receiver and transmitter. Requires 3 volts. Provides for steering and automatic return to neutral. Single pulse operation. Only 2½x2x1¾" overall. Includes instructions and liberage to extend a structor with the second of the second linkage to extend actuator arm. Shpg. wt., 8 oz. Imported

ideal for transceivers, miniature portable and transistor radios, wireless broadcasters. 5-section antenna of chrome-plated brass screws jack supplied. Measures 38" fully extended, 9" closed with plastic case. **Imported**

98 H 4001



27.255 CRYSTAL .005% TOLERANCE!



etc., as well as on channel 23 of class "D" Citizens Band Equipment. Type HG-6/U holder; Pin spacing .493; Pin dia. .050". Designed for use in R/C

CRYSTAL SOCKET

R/C ESCAPEMENT



A sturdy 2 arm self neutralizing escapement. Converts electrical impulses from remote control receiver to mechanical motion. Four 90°

R/C ENGINE ESCAPEMENT



Self-neutralizing remote engine control. Varies engine speed of your model. Neutral speed of your model. Neutral position of one arm is low speed, neutral position of 2nd arm is high speed, activated position of either arm (armature activated) stops motor. Only %4 oz. Requires 1½ volt battery. Size: 1%x1x 1%4". Shpg. wt., 5 oz. Imported an 49n38 Net 2.45

COMPOUND R/C ESCAPEMENT



One pulse, right turn; two pulses, left turn. Three pulses closes circuit for supplementary control. The rudder returns to neutral position when transmitter keying

ratchet governor. Uses 1½ volt battery. Welghs
1½ oz. Size: 2%Lx1%," overall. Shpg. wt., 6 oz. Imported 99 H 9036

..... Net .59 Lafayette is Headquarters For the Experimenter and Builder

Citizen-Ship R/C Transmitters, Receivers and Accessories

MODEL TTX TRANSISTORIZED TONE TRANSMITTER



2650 SINGLE CHANNEL 27.255 mc

This popular, efficient single channel tone transmitter measures 34/x55/2x17%" and weighs only 12-02. with battery, it is 100% collector modulated (no reduction of RF signal with modulation). In addition it features a high efficiency externally loaded antenna and printed circuit chassis. It operates on 9 volts; requires no license. Operates R/C pack with SE-2 Escapement below. Shog. wt., 2 lbs. Also available in 26.995, 27.045, 27.045 on special order (4 weeks delivery). 42 H 1906 Less Battery (Surgess 2N6). Net 28.50 42 H 1906 Less Battery
32 H 4806 9-Volt Battery (Burgess 2N6)

MODEL RSH SINGLE CHANNEL RELAYLESS SUPERHETERODYNE RECEIVER



• Only 2x1½x¾"
• Requires Only 2 Pengelis

This 7 transistor receiver reliably

This 7 transistor receiver reliably operates escapements directly from a powerful output transistor, with no intervening relay, to give rudder or rudder and motor control. Excellent with Model TTX transmitter as excommodates complete installation. Its supersensitivity permits flying to limit of controllable visibility. Its excellent selectivity permits flying with up to five modelers, using other FCC frequencies, without interference. Epoxy glass printed circuit board. Crystal controlled—change frequency by simply changing crystals. No overload at any distance. Idle 5 Ma delivers 2.8 volts to escapement. Especially efficient with Citizenship SE-2 and PSN-2 escapements. Requires only 2 pen cells. Weighs only 1¼ oz. Shgg. wt., 8 oz. Less batteries. For 27.145 MC Also available in 26.955 MC, 27.045 MC, 27.095 MC and 27.195 MC on special order (4 weeks delivery). 42 H 1910 For 27.145 MC


MODEL TCB TRANSISTORIZED CAM ACTION SERVO



 First Servo to Give Variable Ratio Ideal for

Contest Work

PACK WITH SE-2 ESCAPEMENT



Single Channel 27.255 mc

Completely wired R/C unit for INSTANT model plane or boat Instal-

MODEL SE-2 ESCAPEMENT Smallest Size Compound or Selective Type Sensitive Escapement

MODEL SL-6 SIX CHANNEL ALL-TRANSISTORIZED HIGH POWER TONE TRANSMITTER



(27.145MC)

Operates RL-6 Reed Receiver, and all single channel receivers on this page. Features RF output from silicon fransistor and center loaded antenna; "contest type" lever switches, 4-transistor temperature—compensated circuit for tone stability. Six adjustable tone frequencies from 350-650 cps. Battery drain 50 MA. Anodized aluminum case with rubber feet. 6/8x559x2-4". Weight 234 lbs. with battery. Complete with antenna, less pattery. Available in 26.995, 27.045, 27.095, 27.195 and 27.255MC on special order (4 20.535, 27.053, 27.054, 27.155


MODEL RL-6 SIX-CHANNEL ALL-TRANSISTORIZED RELAYLESS SUPERHET REED RECEIVER

(27.145MC)

\$5 monthly

Especially designed for use with the Citizen-Snip SL-6 transmitter, the combination is ideal for Rudder (class I), intermediate (class II), and Pylon racing. Receiver operates 3 separate servos (rt., ift.; up, down; high and low motor). 6 transistors, crystal controlled. Change frequency by changing crystals. High selectivity permits flying up to 5 different models simultaneously without interference. Current drain: 5 MA signal cff, 15MA signal on. Weighs only 3½ cz. Slze: 27ex1¾x1". Less battery. Available in 26.995, 27.045, 27.095, 27.195 and 27.255MC on special order (4 weeks delivery). weeks delivery).
42 H 1905 Net 45.75
32 H 4807 9-volt battery for above Net .48

MODEL MDL SINGLE CHANNEL RELAYLESS TONE RECEIVER



Subminiature, super-regenerative relayless tone receiver that operates from any tone transmitter. Designed for perfect unit operation with powerful SE-2 escapement. Virtually crash proof. Requires 3 voits (2 sencell batteries). Size with plastic cover: 7exix1%6". Weighs

Net 19.95



5-CHANNEL RESONANT REED HOBBY RELAY

TUNED TO FREQUENCIES:

266.0 CPS, 280.8 CPS, 313.0 CPS, 349.0 CPS

A compact, reliable 5 channel resonant reed frequency selective relay. Frequency tolerance ± 1%. Especially adaptable to 5 channel remote control hobby tone receivers and Citizens Band tone signaling receivers. Can also be used as high stability, resonant reed oscillator control. Features low tuning error, good temperature stability, and low driving requirements. Reed response approx. 75 milliseconds; contact rating 100-ma at 48 VOC, 15 ma at 100 VDC, 1 ma at 150 VDC. Orive power varies from 1 milliwatt at 100 cpt 50 milliwatts at 800 cps. Weight 1 oz. 1½/13/13/13/4". Mounts by two 6/32" tapped-holes on back and bottom. Shpg. wt., 8 oz.

Net 7.95

LAFAYETTE KITS EASY-TO-BUILD-ENJOYABLE-TO-USE

LAFAYETTE KT-92 5-WATT PUSH-PULL **AMPLIFIER** Made in U.S.A.

 Push-Pull Audio Output Stage
 Inverse Feedback Circuit Separate Volume, Bass & Treble Controls • AC er DC Operation

Uperation

Here in kit form is an AC-DC hi-fi amplifier that presents defuxe features despite its amazingly low price. The separate bass and treble controls permit adjustment of both low and high frequency response and balance. Works equally well with both crystal or ceramic cartridges. Tube line-up consists of a 12AX7 amplifier and phase inverter, a pair of 35C5's in push-puil, having a power-packed low-distortion output plus a 35W4 rectifier. The circuit utilizes an inverse feedback loop to reduce the level of hum and distortion. Kit is complete containing all essential parts, tubes and detailed instruction manual showing pictorial and schematic diagrams. Shops. Wf Albs. wt., 4 lbs.

COMPLETE MONAURAL PHONO SYSTEM KIT



For those who prefer a monaural system, this package consists of the Lafayette KT-92 push-pull amplifier kit, the Lafayette-Ensign 4-speed automatic record changer complets with stereo-monaural car-tridge and the Lafayette SK-124 2-way speaker system. When erder-ing specify mahogany or walnut finish, less base. Shpg. wt., 28 lbs.

..... Net 47.50 21 H 9797WX Walnut Base for changer Net
Mahogany Base for changer 24 H 0107 24 H 0108


12-WATT HI-FI AMPLIFIER KIT with BUILT-IN PRE-AMPLIFIER



ONLY

FEATURES: Separate full-range bass boost and controls. 4, 8 and 16 ohms speaker output. Amplifier, pre-amplifier and power supply on single open pre-punched chassis for the easiest construction. 4 input connections located at rear of chassis for magnetic phono or tape, crystal phono, tuner/radio, and mike or auxiliary. Self-balance phase inverter system and full range tone control amplifier. Inverse phase inverter system and full range tone control amplifier. Inverse feedback circuit. Removable front panel for professional appearance in custom installations. Amplifier can be used with electric guitar, etc., or in a Public Address System. Frequency Respense: 1 db 20 to 20,000 cycles; Distertion: 194 at rated output; Hum: Tuner/Crystal Phono 80 db below 12 watts; Magnetic Phono/Tape 60 db below 12 watts. Sensitivity: Magnetic Phono/Tape 3mv. Crystal Phono 0.5 volt. Tuner/Radio 0.5 volt. 4 Centrels; Function, Loudness, Bass, Treble/Power Switch; Tube Cemplement: 12AX7/EC63 Preamp; 12AT7 Phase Inverter; Tone Control Amplifier; 2-6V6 Push-pull Beam Power Amplifier; 1 Rectifier. Complete with 24-page Instruction book complete with diagrams, illustrations and step-by-step construction details. Baked Hammertone. Golden Brown Finish Chassis. 11Wx7Dx 57H. Power Consumption 55 watts; 117 VAC; 50-60 cycles.

STEREO 30-WATT WILLIAMSON TYPE DUAL AMPLIFIER/PREAMPLIFIER KIT



A Complete Steree Controi Center • 15 Watts Each Channel, 30 Watts Monaural • Easy To Build

only 2650

A Stereophonic 30-Watt Williamson Type Dual Amplifier/Preamplifier Kit. FEATURES: Stereo Inputs for Tepe/Low Level Phono, High Level Phono, FM/AM Tuner, High Level Tape/Auxillary. Dual tape outputs. Output Impedances: 4, 8 and 16 ohms. 3rd channel output. Equalization: (Tape) NAB; (Phono) RIAA. Separate full-range bass boost and treble controls for each channel. Frequency Response: ±1 db 20 to 20,000 cps. Distertion: Less than 1% harmonic distortion. Humm: Tuner/Hi Phono/Aux. 70 db below 15 watts, Low Phono 60 db below 15 watts; Tape 55 db below 15 watts. 9 Frent Panel Controls: Function, Loudness, Balance, Treble A/Off, Treble B, Bass A, Bass B, Equalization, Mode. Tubes: 2-12AX7/ECC83, 2-12AT7/ECC81, 4-7408, 1-5U4. Operates on 117 volts, 50-60 cps AC. Baked Hammertone, Golden Brown Finish Chassis. Complete with "Foolproof" instruction book having diagrams, illustrations and step-by-step construction details. Size: 15Wx6Hx8"D. Shpg. wt., 18 lbs.

FM-AM TUNER KIT

Pre-wired and Pre-aligned Front End

Automatic Frequency Control



Features smooth counter-weight tuning with built in AFC defeat switch, advanced AFC circuitry that prevents drift as it locks in your station after selection, and special temperature-compensated oscillator circuit as additional aid in preventing drift. The powerful 7 tube tor circuit as additional aid in preventing drift. The powerful 7 tube circuit Plus Selenium Rectifier has an Armstrong FM Circuit ... with ratio detector, and a low noise FM pre-wired and pre-aligned front end, and offers a 20-20,000 cps. response. The AM section features a Superheterodyne Circuit with AVC and a powerful Ferrite Loopstick Antenna with multiplex stereo output Jack. SPECIFICA-TIONS: Frequency response: FM ± ½ db. 20-20,000 cps. FM drift ± 5 KC Maximum. Sensitivity: FM 5µv for 30 db. Quieting; AM 25µv. Distortien: Less than 1% on FM. Hum Level: 60-db. Controls (2): Off—AM-FM, tuning with AFC incorporated. Power Drain: 30 watts at 105-125 voits AC. Size: 12" wide — 6" deep. Shgg. wt., 15 ibs. Front panel finish: Mahogany, Ivory, and Gold. TUBE COMPLEMENT: 1-6BE6, 1-6BA6, 2-ECC85, 1-6AL5, 2-6AU6, 1-rectifier. Cover for AM-FM Tuner. Shpg. wt., 3 lbs. ... Net 5.95

FM TUNER KIT

Same as FM-AM Tuner Kit less AM circuitry and less 6BE6. Shpg. wt., Cover for FM Tuner Kit, Shpg. wt., 3 lbs. ... Net 5.95 19 H 4003W 19 H 4006

Take Advantage of Lafayette's Low Kit Prices.

LAFAYETTE EASY TO BUILD EDUCATIONAL KITS

20-IN-1 TRANSISTOR EXPERIMENTERS KIT

MADE IN H.S.A.

FUN TO BUILD-EDUCATIONAL and ALL 20 projects result in a useful working instrumently

PROJECTS YOU BUILD

1. TRANSISTOR TESTER 2. VOICE ACTU-ATED ALARM 3. PHOTO TIMER 4. AUDIO AMPLIFIER 5. CRYSTAL SET 6. SOLAR RADIO 7. RAIN ALARM 8. TIMER 9. ONE TRANSISTOR RECEIVER 10. CODE PRAC-TICE OSCILLATOR

11. METROPHONE 12. TWO TRANSISTOR RECEIVER 13. ELECTRONIC RELAY 14. HOME BROAD-CASTER 15. PHOTO ELECTRIC RELAY 18. BURGLAR ALARM 17. WIRELESS TRANSMITTER 18. HEGENERATIVE RECEIVER 19. CITIZENS BANO MONITOR 20. AUDIO OSCILLATOR Excellent for beginners as well as advanced experimenters, this kit enables you to build and learn about 20 interesting and useful transistor circuits. By utilizing "Breadboard" construction, each project can be built by simply inserting a few preassembled component blocks and interconnecting leads between them. A soldering iron is only required for the basic wiring and not for subsequent projects. All wiring is covered in a step-by-step manner by the instruction manual. Each of the 20 projects is clearly presented with step-by-step instructions, large easy-to-read pictorial wiring diagrams, schematic diagrams, and an explanation of the circuit behavior. The kit is complete with perforated mounting board, 2-transistors, 1-diode, earphone, and all other parts required for construction. The detailed 28-page instruction manual contains a wealth of information about each project. Less batteries and tools. Net 16.95 Net 16.95

19 H 0902 Complete. Shpg. wt., 6 lbs. 32 H 4802 Z Cell Battery for Kit projects ... 32 H 4803 221/2 Volt Battery for Kit projects

Net .13 Net 1.61

99 H 4503

SHORTWAYE AND SUPERHET BROAD-CAST RADIO KIT



2 bands cover both standard broadcast 540-2 bands cover both standard broadcast 540-1700 KC and shortwave 5.8-18 MC which in-cludes international broadcast, 40 and 20-meter ham bands and same of the aeronau-tical and marine bands. Superheterodyne cir-cuit has high gain IF's. builf-in broadcast band loop antenna. Cornes complete with wainut cabinet, 4" PM speaker, tubes (12SA7, 12SK7, 12SQ7, 5016 plus 3525 rectifier) and all parts. Easy to follow step-by-step instruc-tions. Shortwave band requires external an-tenna (not supplied). Size 934Wx6flx54/2"D. tenna (not supplied). Size 936Wx6Hx51/2"D. For 110V AC or DC. Shpg. wt., 6 lbs. 19 H 4001

LAFAYETTE WIRELESS BROADCAST/AMPLIFIER



1925

Use it either as a

Wireless Broadcaster or AM Audio Amplifier!

- CLEAN, MODERN STYLING . POWERFUL SIGNAL
- WORKS WITH ALL CRYSTAL AND MAGNETIC
- MIKES AND PHONO CARTRIDGES
- THROUGH ALL AM RADIOS PLAYS

Treat yourself and your family to hears of fun with this Treat yourself and your family to he.rs of fun with this Lafayette Kit. Make your own radio programs, announcements, etc., through AM radios anywhere in the house, without wires or extra gadgets. Designed for easy construction by youngsters or adults, it compines in one compact unit a powerful 3-tube wrietess brostcaster and an audio amplifier. Clearly written instructior manual makes it a cinch to build. Operates on any frequency between 900 and 1600 kilocycles on your radio dial. It will accept any crystal or magnetic microphone. In addition, it may be used directly as a phono or microphone amplifier. No external preamp is required. Simple silde switch permits either form of operation. Just connect it to a PM speaker (4-16 ohms). Conforms to FCC regulations and is designed to provide high quality voice or record broadcasts. voice or record broadcasts.

No license or permit is necessary. Complete with crystal clear instruction manual. Less Mike. For 105-125V AC or DC. Attractively styled metal cabinet. Siza 4Hx8Wx4¾°D. Shpg. 19 H 0903

Same as above, but factory wired & tested

.. Net 14.95

Crystal microphone for above. Desa or hand held, 8 ft. cable. Shpg. wt., 1 lb.

.... Net 2.95

COMPLETELY WIRED INCLUDES



LAFAYETTE SUPER-SENSITIVE PHOTOCELL ELECTRONIC

CLAIREX CADMIUM SULPHIDE PHOTOCELL & ADJUSTABLE SUPER SEN-SITIVITY—WORKS WITH JUST A FLASHLIGHT AT 250 FEETI • NEEDS NO SPECIAL HIGH-INTENSITY LIGHTS • INSTANTA-NEOUS OR SUSTAINED OPERATION ON THE FLIP OF A SWITCH!

Ideal for sustained operation required for burglar alarms, door buzzers and for instantaneous on-off operation required for counters, packaging, door opening, motor activation plus countless industrial applications. Switch converts unit from instantaneous "on-off" to sustained "on" operation. "RESET" switch opens the external circuit and turns off the alarm. The unit operates on 110 voits AC and incorporates the efficient 5823 cold cathode tube. A simple change in wiring (in instructions), as well as convenient input terminals, enables you to supply the external circuit with any desired voltage. Relay contacts rated at 3 amps permitting up to 300 watts external load on 110 Voits AC. Complete with all parts, photocell, tube chassis, silkscreened metal cabinet and easy-to-follow illustrated instructions. Size: 3x4x5". Shpg. wt., 3 lbs.

19 H 0904 Complete Kit ACCESSORIES FOR ABOVE 99 H 9023 Electric Beli, 110V AC. Shpg. wt., 2 oz. 99 H 9024 Electric Buzzer, 110V AC. Shpg. wt., 10 oz. 99 H 9011 6-Digit Electric Counter. Shpg. wt., 1½ lbs. 1.29 Net Net

Net 12.95

with AC line cord and plug. Will actuate the relay at 70 feet w/o red filter, up to 30 feet with red filter. Remcvable red filter makes light beam invisible by day and very difficult to detect at right. Metal case. Size 54x3x4". For 110V 60 cycle AC. Shpg. wt., 4 lbs. Imported. Net 7.50 99 H 9026 Replacement Bulb for above. Net .21 99 H 9027

Completely wired and assembled light source

LIGHT SOURCE

FOR ELECTRONIC RELAY KIT

Lafauette is Headquarters for Experimenter's Specialties

Lafayette Cat. No. 651 67

BASIC EDUCATIONAL COMPUTER KITS

GENIAC PORTABLE MEMORY CARD FILE



How to file a card in 25 places simultaneously.

only

For the busy scientist, engineer, teacher, businessman or student who must keep basic information on file. NOW the Geniac Portable Memory Unit, (PMU), a low cost Information retrieval system can conservatively sort 400 cards per minute—using no electrical parts or gadgets. Sorting is by rods. Information is coded into the cards by matching prepunched holes around the edge of the card. No previous knowledge is necessary. Once coded the card is filed at random and will automatically appear during sorts for the various categories. Serves as a useful adjunct to company integrated information systems. The basic PMU contains a matching hand punch, sorting rods and 300 cards.

cards. Net 17.96 19 H 3801 Shpg. wt., 6 lbs. Additional Cards, pkg. of 100

Not 3.92

GENIAC® COMPUTER KITS



Over 800 Parts For Schools, For Science Fairs, For **Advanced Experimenters**

- COMPUTES, REASONS, PLAYS
- GAMES

 COMPOSES MUSIC, FORE-CASTS WEATHER
- DESIGN YOUR OWN COMPUTERS
- OVER 400 PARTS AND COMPONENTS

DOUBLE GENIAC

The newest kit in famous Geniac® series!
The "Double" Geniac contains over 800 parts, Two of everything in the Standard model. Offers the advanced experimenter a far wider range of activities. Perfect for school demonstration. Multiple setup is idea! for Science Fair projects—submit one or more designs, Build "electric trains" that test intelligence—code and decode—add,

subtract, multiply and divide-solve puzzles subtract, multiply and divide—solve puzzles
—play games—forecast weather—reason in
syllogisms—information and logic circuits.
No soldering required. Easily assembled and
operated. 64 page guide and reference book,
beginners manual, wiring diarrams and many
extra pamphiets outlining projects and methods. Complete with mounting rack and batteries. Shog. wt., 12 ibs.

19 H 3803

STANDARD GENIAC

Make Them," "Symbolic Analysis of Relay and Switching Circuits," "Beginner's Man-ual, Machine to Compose Music. Wiring Dia-grams, etc. Complete with battery. 1642x grams, etc. Complete 1134". Shpg. wt., 6 lbs.

ANALOG COMPUTER KIT



- Ideal Introduction to Basic Elements
- of Analog Computers
 Work Over 50 Experiments
 Easy-to-Assemble with Screwdriver and Pilers
- the Way to Sound Scientific Learn the Knowledge

The latest Analog Computer Kit offering a basic introduction to computer theory—gives accurate answers to practical problems. Perform over 50 experiments—multiplication, division, powers, square roots, rocketry, interest, radio-active decay, light, kinetic energy, etc. Level of accuracy better than 5%. The computer consists of a masonite, solid instrument panel, kits, potentiometers, meter, specially calibrated scales, guide and operating booklet. Easy-to-assemble. 19 M 3805 Shpg. Wt., 6 lbs. ... Net 8.95 19 H 3805 Shpg. wt., 6 ibs. Net 9.95



Your Rewarding Introduction to the Exciting Computer Field — Performs Functions of Full Size Computer — Solves Scientific & Business Problems

The 601 demonstrates how computers operate, what they can and cannot do by simulating computer applications in business, ing computer applications in business, science and military. It can learn, remember, calculate, and make decisions. Indispensable to teachers, businessmen who need to keep up with modern technology, a first hand opportunity to explore space are techniques and experimentation. A set of six comprehensive manuals are provided with each Minivac 601. These provide step-by-step experiments demonstrating how computers do arithmetic, use logic, provide automatic control, and language translation . . . It even plays rames as an opponent, partner or referee. The Minivac is ready to use the moment you unpack if Operates on a law 12-volt avenue unpack if Operates on a law 12-volt avenue unpack if Operates on a law 12-volt avenue. calculate, and make decisions. Indispensable you unpack it. Operates on a low 12-volt system—It is safe to use as an electric train.
Minivac consists of a 24" console with 12

indicator lights. 1 circuit breaker; 6 DPDT memory storace relays; 6 secondary memory storace switches; 6 data input push buttons; 16-position switch (motor driven); pame matrix; 194 dual terminals and 100 program wires. The console measures 24x13x5½"H. Shpg. wt. 17 lbs. Power input 110V AC.

MINIVAC 6010. A deluxe version of the 601 which is capable of handling a larger variety of more advanced computer programs. Ideal for industrial use. A seventh capacitor/resistor manual will accompany the 6010. Now with the additional features of individual protective dust covers for relays, improved silds switches and push-buttons for tighter specs and greater reliability. 19 H 8102WX ...

Lafayette is Headquarters For the Electronic Hobbuist

SCIENCE AND TECHNOLOGY KITS

INTERNATIONAL RECTIFIER **EDUCATIONAL SCIENCE KITS**



SOLAR ENERGY AND TRANSISTOR ELECTRONICS LAB 1 KIT

e More than 30 Fascinating Projects

Designed to acquaint the Junior Scientist with basic electronic circultry. Master control panel features indicator scope, galvanometer, signal buzzer, and push button selector. Builds projects in elecsignat buzzer, and push button selector, buttons projects in let-tronic circultry including two different radios, code practice set, sun operated "Wake Up" alarm, phone and telegraph broadcast transmitters. Completely safe, no soldering, no special tools re-quired. Complete with easy-to-follow instruction manual. Solar power will operate most experiments; battery power optional on ali experiments. Size 16%xx1136x3.

Net 14.66 19 H 2905 Shpg. wt., 3 lbs.

SOLAR ENERGY AND TRANSISTOR ELECTRONICS LAB 2 KIT

• Over 50 Basic and Intermediate Projects in This Advanced Kit.

Features magnificent master control panel with speaker, par-phone jacks, additional push button switches and electronic circuit elements. Builds Solar Powered satellite type "beep" transmitter, electronic light indicators, burglar and fire alarm systems, radios, transistorized broadcast transmitter. Completely safe, no soldering, no special tools required. Complete with easy-to-follow instruction manual. Solar power will operate most experiments: battery power power and particularly services. optional on all experiments. Size 16%,x16x3".

... Net 22.01 ... Net 16.00 19 H 2906 Shpg. wt., 5 lbs. Lots of 3 ea.

SOLAR ENERGY AND TRANSISTOR ELECTRONICS LAB 3 KIT

e Builds Over 70 Different Projects and Experiments

This unit includes all of the exclusive features of the other Interna-tional Rectifier Electronic Labs, plus the components to build an amplifier, public address system, inter-com, telephone pickup, electronic timer, and many more circuits simulating those in missile guidance, computers, etc. Every component is of the professional quality used in commercial and industrial equipment. This advanced quality used in commercial and industrial equipment. This advanced lab is as simple to assemble as the basic unit. Completely safe, no soldering, no special tools required. Complete with easy-to-follow instruction manual. Solar power will operate most experiments; battery power optional on all experiments. Size 16%,x16x3".

Net 24.00

NOVATRON

A SCIENTIFIC INSTRUMENT FOR THE EXPERIMENTERS

- POWERFUL 110 VOLT AC/DC MOTOR MINIATURE ATOM SMASHER PRODUCES 75,000 VOLTS ABSOLUTELY SAFE

COMPLETELY WIRED (NOT A KIT)

In no sense of the word a toy or gadget. This machine is a scientific instrument capable of producing 75,000 volts—makes sparks up to 2" long—yet it is absolutely safe because the current is infinitesimal. The science teacher—science lover—or hobbyist can perform sprantage to a com-

Lafayette is Headquarters For the Electronic Hobbyist

GENERAL ELECTRIC 5-TRANSISTOR PORTABLE RADIO KIT



An authentic G.E. Portable Radio. Well engineered electronic components have been pre-assembled into 3 factory-tested sub-units for quick, easy soldering to the printed circuit board. Kit includes 5 transistors plus diode, pre-aligned IF's, ferrite antenna, G.E. 314" magnetic speaker, textron carrying case and all parts. Operates on 9 volt battery (not supplied). Complete Instruction manual. Shpg. wt., 3 lbs. 19 H 2703



PHILMORE DUAL BAND BROADCAST SHORTWAVE RADIO KIT

- 3 Tuess Including
- Rect fler e 2 Barnds
- 550-1850 KC. 3-13MC

This radio covers the standard broadcast band from 550 to 1650 This radio covers the standard broadcast band from 550 to 1650 kc, and a shortwave band from 3 to 13 Mc. Modern circuitry with enough audio to drive a built-in 3½ inch speaker. Be rewarded with the saitsfaction of having built a radio which will actually pull in standard broadcast, amateur and other shortwave stations. Includes punched chassis, grey hammartone panel, 3½" speaker, pictorial and schematic diagrams, and easy-to-follow instructions. Complete with all hardware: less solder, were and tubes. Tubes required: 1—35W4, 1—50C5 and 1—12AUE, For 105-125 volts. AC or DC. AC or DC.

19 H 5801 MODEL 7001CR. Shpg. wt., 4 lbs.

MAGIC-GLO BLACK LIGHT

TEKNIKIT®

Learn Invisible Detection

Write Secret Messages

Educational—Scientific Enjoyable—Interesting

The Black Light Kit enables you to see the invisible. Guaranteed completely safe and harmless. This kit allows children to study the phenomena of fluorescence and phosphorescense. Set contains black light, socket and cord, laboratory lamp stand, 4 jars of fluorescent paint, invisible ink, invisible crayon, trace: powder, 3 fluorescent mineral specimens, phosphoragram, optical black, brushes and pen, and a box of fluorescent specimens. Enables the student to perform endless numbers of fascinating experiments. The amply illustrated 48 page booklet "The Story of Black Light—The Unseen World Around Us," explains the use of black light in file 6s such as mineralogy, electronics, crime detection, medicine, stamp collecting, and many others. Shpg. wt., 4 lbs.

19 H 1301

REVELL PORTABLE WEATHER RESEARCH LABORATORY UNIT



A PRACTICAL AND ATTRACTIVE KIT FOR THE STUDY OF WEATHER CONDITIONS

A completely portable, efficient weather Fesearch Laboratory Kit assembled in a Deluxe plastic console storage and carrying case with handle. Extremely easy to assemble, is so efficient that it can be used by professional forecasters—yet simple to operate and understand. Includes professional Amerold barometer with completely assembled mechanism. Also, professional style anemote observation. Instruments and equipment include nephoscope, relative humidity calculator, temperature humidity index calculator, compass, compass rose (for use in conjunction with included wind vane and nephoscope) rain gauge, sling psychrometer with two 5 inch thermometers, wind and gust indicator and cloud chart. Also includes U. S. Weather hap, weather recording forms, and scientific booklet.

18 H 5701 Shpg. wt., 3 lbs.

Net 7.50

EVERY ITEM ON THIS PAGE IS BEING OF-FERED AT A PRICE BELOW OUR ACTUAL COST. QUANTITIES LIMITED-ORDER NOW!

DELUXE HI-FI KITS - FIRST SERVED

EVERY ITEM ON THIS PAGE IS BEING OF-FERED AT A PRICE BELOW OUR ACTUAL COST. QUANTITIES LIMITED-ORDER NOW!

FAMOUS LAFAYETTE KT-236 36-WATT STEREO AMPLIFIER KIT



Fine wide range stores reproduction

Built-in dual preamps

Dual concentric controls for easy and smooth operation

SPECIFICATIONS: Power output: 36 watts—18 watts per channel ±1 db. Frequency Response: 15-30,000 cps ±1 db at normal levels. Sensitivity: Full output; High level inputs 0.5v; Mag. Phono 3 mv. Sensitivity: Full output; High level inputs 0.5v; Mag. Phono 3 mv. Distortion: Harmonic less than 0.15% at normal level; IM, less than .3%. Hum and Neise: (at full volume) High inputs 70 db below rated output, Mag. Phono 53 db below rated output. Channel Separation: 50 db. Output Impedance: 8 and 16 ohms. Inputs: (total 4) Dual Aux., Dual Tuner, Crystal Phono, Dual Mag. Phono. Outputs: (total 4) Dual main speaker output, dual tape outputs. Tubbes: 4-EL84, 2-7199, 3-12AX7, plus 2 silicon diodes. Attractive beige vinyl laminated steel cabinet. Handsomely designed hass anodized aluminum front near Supplied with

LAFAYETTE Griterion® KT 600A STEREO PRE-AMPLIFIER MASTER CONTROL CENTER



Response 5-40,000 cps Four auxiliary AC Outlets Versatility of a Studio Control Console

The KT-600A has a total of 12 input jacks (6 stereo pairs) for program sources of any type and level. Separate turnover and roll-off switches provide 24 positions of correct equalization—independent for each channel. A Bridge Control provides continuously variable channel separation. Low impedance Plate Follower outputs are used, and a host of many other professional type features, W.Case, KT-800AWX Stereo Preamp Kit. Shpg, wt., 16 lbs. Net 52.50

SPECIFICATIONS

SPECIFICATIONS

Frequency Response: 5-40,000 cps ±1 db. Olstertien: Less than 0.05% IM at 2-volts out; less than 0.1% Harmonic, at 2 volts out. Sensitivity: Low Level 2.2 mv for 1 volt out; high level 94 mv for 1 volt out; Tape Head inputs 1.8 mv for 1 volt out. Hum and Noise: High level inputs better than 80 db below 2.0 volts: low inputs better than 62 db below 2.0 volts. Input Impedance: High level—250K ohms: Mag—96K ohms; Ceramic—96K ohms in series with 68 uuf; Tape Head—470K ohms. Tone Control Range: Bass ±15 db at 30 cps; Treble ±15 db at 10Kc. Auxiliary AC Outlets: 4. Tubes: 7-7025, 2-Selenium Rectifiers. Power Requirements: 35 Watts. 105-125 volts AC. 50/60 cycles: Size: 14Wx4¹½₆Hx11½²D, not including projections. including projections.

FAMOUS LAFAYETTE KT-250A 50 WATT STEREO AMPLIFIER KIT



Total of 9 Tubes and 3 Silicon Diodes DC Applied to Preamp and Tone Tube Heaters May be Paralleled For 50 Watt Mono Operation

SPECIFICATIONS: (All relative figures at normal listening levels). Power Output: 50 Watts, 25 Watts per channel ±1 db. Distortion: Harmonic, ±1 db at less than 1% at 1 kc (1 watt), IM less than 1%. Frequency Response: 15-40,000 cps ±.5 db, 25-50,000 ±1 db at rated output. Hum and Noise: 77 db below rated output at zero watter with bight inputs. at rated output. Hum and Nelse: 77 db below rated output at zero volume, max. vol. hum is 70 db below output with high inputs, Mag. phono inputs 50 db below output. Sensitivity for full output (high level inputs) .5 v; (mag. phono) 3.5 mv at 1 kc. Channel separation 55 db at 1 kc and 45 db at 20-20,000 cps. Switched Aux. AC outlet. Speaker phase switch. One loudness switch for compensated listening. Impedance: 4, 8, and 16 ohms. Tubes, 4-6CW5/E186, 2-7199, 3-12AX7, 3 silicon diodes. Pewer: 200 watts at 117vac, 50-60 cps. Designed for ease of construction. Assembly manual contains detailed step by step instructions. Size: 14½x 5½x1234".

KT-250AWX Shpg. wt., 28 lbs. ..

LAFAYETTE @riterion^o 100 WATT STEREO BASIC AMPLIFIER



Conservatively Rated at 50 watts per channel Frequency Response: 2-100,000 cps at 1 Watt Unmeasurable Distortion!

Handsomely finished in contrasting brown and beige with control panel finished in brass. Complete with all components including attractive beige finish steel cover, with built-in handles and step-by-step instruction manual. 171/4Wx12½0x81/4"H. For 110-125V 50/60 cycle operation, Shpg. wt., 60 lbs. KT-550WX Net 89.50


LA-550WX Same as above but wired ... Net 116.50

TECHNICAL SPECIFICATIONS

Power Output: 50 watts RMS per channel from 20-20,000 cps; Harmenic Distertion: .15% at 1.000 cycles at 50 watts, 0.75% from 20-20,000 cps at 50 cps at 50 watts, IM Distertion: Less than 0.5% at 50 watts, 60 & 7,000 cps, 4:1 ratio, 0.15% at 10 watts, Frequency Response: 14-45,000 cps, +0—1 db at 50 watts; 2-100,000 cps. +0—1 db at 1 watt. Sensitivity: 1.0 voit RMS input for 50 watts output, Damping Factor: 15 at 1 kc—26 ohms. Feedback: Over 50 db, Hum and Neise: —90 db. Output Impedance: 4.8 and 16 ohms. Single AC outlet. Centrales: A Bias Controls 2 AC 4, 8 and 16 ohms Single AC outlet. Controls: 4 Bias Controls. 2 AC Balance Controls. Meter Selector Switch and Power On/Off Switch. Tube Complement: (Total of 10) 4-7027A, 4-6CL6, 2-6BR8A plus 5 Silicon Diodes.

FAMOUS LAFAYETTE HE-20C **Deluxe Citizens-Band Transceiver**

EXCELLENT FOR BUSINESS. FARM, INDUSTRY, CAR, BOAT, PERSONAL AND SPORTS USE



Tuncable Receiver over all 23 channels Illuminated Direct Reading "S" Meter for Relative RF Power Output, and Receiver "S" Readings Oependable Push-To-Talk Ceramic Microphone

Illuminated Dial Spatting Switch for Positive Frequency Location on Tuneable Receive Highly Effective Automatic Series Gate Noise Limiter Built-in 12 or 6-voit Power Supply for Mobile Use Complete with channel 8 Transmit & Receive Crystals

Adjustable Squeich Control Receive Tuneable or Fixed Crystal Selector Switch

14-Tube Performance, 2 Giodes, 3 Rectifiers 8 Crystal-Controlled Transmit Positions 8 Crystal-Controlled Receive Positions

Illuminated Dial

13 Dependable Relay Switching

NEW LOW PRICE

AMAZING

was 109.50 Catalog 644

June 1964

HE-20cl



- 8 CRYSTAL TRANSMIT POSITIONS . SPOTTING SWITCH for Positive Frequency Location on Tuneable Receive
- BUILT-IN SELECTIVE CALL CIRCUITRY AND SOCKET!

DEPENDABLE RELAY SWITCHING

Not A Kit! COMPLETELY WIRED!

.... Net 99.50 2.25 2.25

POWERFUL 12-TRANSISTOR 4-BAND

PUSHBUTTON SW/AM PORTABLE

FABULOUS 12-TRANSISTOR 3-BAND FM/AM-SW PORTABLE



BELOW Your Choice



FM/AFC—Locks-in Stations Tuned RF Stage

Hi-Q Long Range Antennas Optional AC Operation Plays Hundreds of Hours on 6 Flashlight Batteries

Tone Control plus AGC

Triple your listening pleasure with a 4-12 megacycle shortwave band which can pick up amateur (40 Meters), Police, Aeronautical and Foreign stations, plus static-free FM programs providing life-like music and voice. Receives AM too, gets excellent reception where lesser portables fall. The 12-Transistor 4-diode plus varistor superhaterodyne circuit with 7-section 29½" monopole FM antenna has extra sensitivity to bring in those distant stations. Heavy magnet 3x5" speaker provides rich full tone. FM circuit has AFC switch to "lock-in" stations. Tone Control switch provides desired listening quality. Economical to operate—plays on 6 standard "C" cells or AC with adapter (optional at slight extra cost). Includes earphone and batteries. "1¾4Wx51¾4Kx2¾"D. Shpg. wt., 5½ lbs. Imported. FS-2511.

32 H 4801 "C" cell, Additional Batteries for above. 6 required. Net ea. .13 F\$-255 117V AC Adapter for above. Wt., 2½ lbs. Imported Net 4.89

Everything In Electronics From One Dependable Source

Made In U.S.A.

2 Speakers
Fine Tuning Centrol
3 Built-in Antennas • 4 Bands { 540—1600N 1.6—4.5MC **Tene Centrel**


Tuned RF Stage Complete with Batteries and Dynamic Earphone Big Easy-Te-Read Slide Rule Dial Extraordinary Tone Quality

A really superb shortwave portable with more sensitivity and pulling power than many table model SW receivers. Four bands: Pushbutton selected AM Broadcast and 3 Shortwave Bands. Listen to Police, Maritime, Mobile Phone. WWY, 75, 40, 20 and 15-meter Amateur, Aircraft and all the exciting and informative international Shortwave broadcasts from most anywhere in the world! Uses 12 Transistors, 2 diodes and a varistor. Two dynamic speakers (3½" and 2") give you rich table-model tone, plenty of volume. Fast pushbutton band selection for all four bands. Includes 7-section 29½" chrome shortwave monopole antenna, ferrite AM antenna, ferrite booster antenna, earphone for private listening and six "C" batteries. Can also be run on standard AC house current (117v, 60 cycles) when used with FS-255 Adapter. Size: 10Wx4¼Hx2¾"D. Shpg. wt., 5 lbs. Imported.

32 H 4801 Additional Batteries For Above

SPECIALTIES FOR HOBBYIST and EXPERIMENTER


NEW! 1-WATT 4-TRANSISTOR PUSH-PULL AUDIO AMPLIFIER



Our most powerful miniature amplifier. It has many direct uses in audio frequency applications for tuners, test equipment, etc. Pushpull circuit is very sensitive and has an output of 1-watt! Using only 4 transistors, it requires a 12-voit source supplied by Standard 'D' cells in series. Outputs from record players with magnetic cartridge, tape heads, microphones, etc. (not exceeding 20 millivoits) can be connected directly. Higher output devices may be easily connected with a resistor in series. Components are neatly layed out on a printed circuit board with pre-drilled holes for mounting the entire unit in a vertical or horizontal position. Bullt-in leads are supplied for a volume control, on-off switch, battery and 8 ohm loudspeaker. Dimensions: 476Lx1½Hx244"W. Shpg. wt., 12 ozs. Imported. Our most powerful miniature amplifier. It has many direct uses in ozs, Imported.

99 H 9038	Net	6.95
ACCESSORIES FOR ABOVE		0.00
32 H 4804 8 "D" Cells Required	et ea.	.13
99 H 6019 5K ohm Volume control w/switch, Shog, wt., 2 o	7 Net	69
32 H 2405 Miniature Knob for above	Net	.09

3-TRANSISTOR SUBMINIATURE




FOR THE EXPERIMENTER, HOBBYIST BUILDER! . PRINTED CIRCUIT . COMPLETE WITH **TRANSISTORS**

Here is an amazing little audio amplifier with a multitude of challenging applications; i.e., subminiature phono amplifier, tape recorder amplifier, hand-held public address amplifier, telephone pick-up amplifier, etc. Output sufficient for average listening. Has leads for any one of the following inputs: Tape recorder record/playback heads, radio-tuner, crystal or ceramic phono cartridge, and crystal or ceramic microphone. Has lead terminations for ON-OFF switch, Volume Control, 4 to 10 ohm speaker, and leads terminating in clips for a 9-volt miniature battery. Size: 21%x11/4x34". Can be readily mounted on chassis. Shpg. wt., 8 oz. Imported.

99 H 9039 99 H 6021 9-Volt Battery	Not 24
99 H 6019	wt., 2 oz.
Miniature Crystal Microphone 11/6" Diam, x 1/6" Deep. Shpg. 99 H 4509	wt 6 07
Miniature Speaker 2½" Diam. 10 ohms Voice Coil Impeda	nce. Shpg.
wt., 8 oz. 99 W 609 7	Net 1.49

3-TRANSISTOR SUBMINIATURE AM BROADCAST TUNER



RADIOS! AN OUTSTANDING AM BROADCAST RADIO WHEN CONNECTED TO ANY TRANSISTOR AUDIO AMPLIFIER ON THESE PAGES OR ELSEWHERE!

FEATURES COMPLETELY WIRED

PRINTED CIRCUIT BOARD.

deluxe 3-transistor subminiature AM broadcast tuner that features

A deluxe 3-transistor subminiature AM broadcast tuner that features 3 dependable transistors, 3 IF plus 1 oscillator transformer, and ferrite antenna in an efficient, completely wired superheterodyne circuit on a sturdy printed-circuit board.

Now you can build your own highly efficient broadcast receiver by simply adding this exceptional tuner to any of the transistor audio amplifiers listed. The long tuner leads for connecting to external amplifier and/or to a separate 9-volt battery, makes this easy as ple. Also features a large clearly visible calibrated tuning dial. The printed circuit board layout permits either vertical or horizontal mounting. Supplied complete with mounting brackets and detailed instructions. Size: 4x134x2"H with brackets. Shpg. wt., 8 oz. Imported.

99 H 9040

Net 7.95

An Exclusive Lafavette Publication



TRANSISTORIZED MINIATURE AMPLIFIER AND TUNER **APPLICATIONS**

IMPORTED

By Rufus P. Turner

Many original Applications Not Found Elsewhere!

96 Pages . . . Over 61 Circuits . . . 60 Illustrations . . . 6-Chapters-Audio, Amateur & Citizens Band, Controls, Test Instruments, Tuners, Hearing Aids, Intercoms, Etc.

An inspiring new book written by a registered Professional Engineer and author of 13 technical books and of more than 2000 magazine articles. Deals primarily with over 60 challenging and interesting applications, many of them original, of the Lafayette transistorized miniature amplifiers and tuners described on these pages. Consists of 6 latareties about 19 pages. of 6 Interesting chapters.

1. Audio Applications—Amplifiers, Preamplifiers, Modular Amplifiers.

Stereo Amps, etc.

Stereo Amps, etc.

Ham Radio and Citizens Band-Selective Call Alarms, Speech Clipper, Speech Amplifier Modulator, etc.

Control—AM RF Relay, Capacitance Relay, Sound Operated Relay,

3. Control—AM RF Relay, Capacitative neigh, Control—AM RF RElay, Capacitative neigh, Control—AM RF RF Signal Tracer, Percent Modulation Meter, 4. Test Instruments—AF RF Signal Tracer, Percent Modulation Meter, AF Watt-meter, Sound Level Meter, etc.

5. Tuners—No License Radio Communication System, Broadcast/Short-Wave Tuner, etc.


6. Miscellaneous—Hearing Alds, Intercoms, Electronic Stethoscopes, Light Beam Transmitter & Receive, Gleger Counter, Electronic Announcer, etc.

An excellent source of information for the kit builder, experimenter and for workers in various areas of electronics.

Net 1.50

EXPERIMENTER'S AND HOBBYIST'S SPECIALTIES

5-TRANSISTOR PUSH-PULL **AUDIO AMPLIFIER**




- 360 MW DUTPUT COMPLETELY WIRED
- . DIRECT WIRING

ONLY 31/4" x 11/4" x 11/4"

A more powerful and more sensitive version of the 4-transistor amplifier on right, this amplifier employs 3 stages of audio driving a push-pull output stage. Power output is 360 mw, designed for speakers with a voice coil impedance of 8-11 ohms. Low impedance input has sensitivity of 300 microvolts. Input transformer for matching high impedance to the amplifier input available as an accessory (see below). Comes with leads for low impedance input, speaker, volume control/on-off switch. Battery clips and leads supplied for 9 volt miniature battery (one required). Shpg. wt., 5 oz. Imported. 5 oz. Imported.

	Net	6.95
	Net	.21
10,000 ohm volume control w/switch. Shpg. wt., 2 oz.		.69
99 H 8032 8 ohm 3" speaker. Shpg. wt., 10 oz. 99 H 8038 8 ohm 2" speaker. Shpg. wt., 8 oz. Input transformer for matching high impedance	Net	1.49 1.49
(mike, etc.) to amplifier. 99 H 6034	Net	.89

4-TRANSISTOR SUBMINIATURE **AM/SW TUNER WITH** VERNIER TUNING DIAL



Makes Superb Sup-erhet AM/SW Radio with Any Transistor Audio Amplifier

• 2 Bands-530-1600 KC. 4.5-12 MC

• Completely Wired Printed Circuit Board • 4 Transformers: 3 IF Plus 1 Oscillator, for Fine Superheterodyne Performance

Vernier type tuning mechanism makes precise AM/SW tuning a cinch with this extremely powerful and sensitive 4-transistor tuner. Outstanding features include: completely wired printed circuit board, 3 IF and 1 oscillator transformers for exceptional sensitivity and selectivity, built-in ferrite antenna for both AM & SW reception, superhet circuit with BC & SW band switch. S/N Ratio: 14 db on AM; 20 db on SW. Supplied complete with 3 long leads for connecting to external amplifier and/or to a separate 9v battery (only 3 ma. drain), mounting brackets and operating instructions. Overall Dimensions: 61/8Wx31/4Dx211/4"H. Shpg. wt., 1 lb. Imported.

Net 14.95 99 H 9041

4 TRANSISTOR SUBMINIATURE **PUSH-PULL AUDIO AMPLIFIER**



OUTPUT 100-MW TERRIFIC FOR THE EXPERIMEN-TER, HOBBYIST AND KIT BUILDER!

COMPLETELY WIRED, NOT A KIT! . PRINTED CIRCUIT BOARD . COMPLETE WITH TRANSISTORS

A tiny, transistorized push-pull audio amplifier with a multitude of applications. Only 3" x 1½" x 1½" it can be mounted inside other equipment to serve as a subminiature phono amplifier, tape recorder, amplifier, etc. Can be the complement of a homebuilt project which needs only an audio amplifier to make it complete and self-contained. Two stages of audio are followed by a push-pull output stage designed to deliver 100 mw to an 8-11 ohr impedance. Low impedances input, with a sensitivity of 0.9 mv. input transformer for matching high impedances to the amplifier available as an accessory (see below). Includes leads for input, speaker, and volume control/on-off switch. Battery clips and leads supplied for 9-volt miniature battery (one required). Shpg. wt., 5 oz. imported.

99 H 9042

	Net	4.95
ACCESSORIES FOR ABOVE		
99 H 6021 9-volt battery. Shpg. wt., 2 oz	Net	.21
50K ohm volume control w/switch. Shpg. wt., 2 oz.		
		.69
99 H 6032 8 ohm voice coil speaker. Shpg. wt., 10 oz	Net	1.49
99 H 8036 8 ohm voice coil speaker. Shpg. wt., 8 oz	net	1.49
Input transformer for matching high impedance		
(mike, etc.) to amplifier.	Net	.89
99 H 6034	Har	

"MITY-AMP" POWERFUL 2-WATT **AUDIO AMPLIFIER MODULE**



With Applications Booklet and Schematics

Completely Encapsulated


Specifically designed to offer compactness, versatility and quality. Adaptable to hundreds of audio applications. Full 2-watt power yet fits in the palm of your hand. Completely encapsulated in high quality epoxy—will not be affected by high humidity or salt con-tent in air: water-proof and shock-proof. Frequency Response: 20 cycles to 15KC ± 2 db at 1 watt. Input Impedance: 45 ohms to 50K ohms; Output Impedance: 3.2 ohms to 45 ohms; Power Requirements: 6 to 12 volts at 300 to 700 ma. Overall 2x31/2x7/6". Shpg. wt., 10 oz. 19 H 4401

Net 8.45

OLYMPUS PEN "F" SINGLE LENS REFLEX With Interchangable

Automatic Lens


Automatic F/1.8 Lens • Single Frame—Twice the Number of 35 mm Exposures Solid Titanium High Speed Rotary Shutter • Weighs only 18 oz.!



A complete compact single lens reflex camera only 5 inches long and 2½ high. Using standard 35 mm film you get twice as many exposures as standard double frame 35's. Features bright through the lens view finder, a rotary-type focal plane shutter which allows full flash sync with bulb and electronic flash up to 1/500 sec.! Standard lens is fully automatic F 1.8 with instant-reopen diaphram and preview button for depth-of-field check. Also features double stroke rapid wind lever, instant return mirror and double exposure prevention. One-step havenet Pen lens mount quickly accepted interstroke rapid wind lever, instant return mirror and double exposure prevention. One-step bayonet Pen lens mount quickly accepts interchangeable accessory lens listed below. Shutter speed dial couples to accessory CdS meter. Shgg. wt., 2 lbs. imported.

15 H 7601L Pen F Less case Net 139.95
15 H 7602L Case For Pen F Net 9.95
CdS Meter for Pen F Couples to Shutter Speed Dial

15 H 7604L 100mm Auto TF/3.5 lens 15 H 7605L 25mm Auto W F/4 99.95



MINIMATIC-C AUTO "35"

- Automatic Exposure, ASA 10 to 400 45mm YASHINON f/2.8 Lens View rangefinder—Automatic Parallax

Correction



LYNX-5000 35mm

- All-in-one Finder
- Sharp, Super-fast f/1.8 lens Shutter Speeds to 1/1000 Sec. Two-Stage CdS Meter

Set the needle in the finder and SH007! To assure you of fine 35mm prints or slides every time the LYNX-5000 combines an easy-

MIRANDA "F" 35 MM SLR



- Speed to 1/1000th Second
 Internally Coupled f/1.9 Lens
- A deluxe 35 mm single lens reflex camera which features a sharp, fast f/1.9 lens internally coupled and interchangeable with every other lens in the extensive Miranda system, plus lens of most other 35's. Pentaprism is interchangeable too with other types of finders and the new brilliant viewfinder brings out details even in the dimmest light. Shutter speed ranges from 1/1000 to 1 sec. Multigrid center spot permits precise focusing to as close as 17". The "F" also has instant return mirror, depth-of-field preview button, single-action rapid advance lever and many other features. Complete with case. Shgg. wt., 5 bs. Imported. 5 lbs. imported. 15 H 3704L

DROPFRONT "PRO" BAG

A heavy-duty professional bag. Zippered for easy access. Styled for easy hand or over-the-shoulder carrying. Removable, adjustable straps. Chrome plated snap-lock, feet and hardware. Handsome, heavy black simulated cowhide with leather and corduroy lining. Front tripod carrying straps. Meesures 13" long x 7" wide and 9½" high. Shpg. wt., 3 lbs. All Imported.

Net 9 85

15 H 3413 "PRO" II Net 9.95

Same as above except measures 11x61/4x83/4". Shpg. wt., 3 lbs. SUPER-PRO 16". Same as above measures 16x73/4x11". Shpg. wt., 4 lbs

..... Net 13.95

KALIMAR CdS-430 EXPOSURE METER

- **ON/OFF Push-Button**
- to Conserve Battery ASA Scale 6 to 12,000
 - (DIN Scale 9-42) f/1 to f/32 Lens **Aperture Scale**

extremely sensitive Cadmium Sulfide photoelectric exposure An extremely sensitive Cadmium Sulfide photoelectric exposure meter. Perfect for still or movie photography either indoors or outdoors. Designed to be used either as a hand meter or can be mounted to the accessory shoe of still cameras. Has EV indicator for Polaroid and other cameras equipped with LVS numbers. Uses readily obtainable mercury battery. Measures reflected or incident light; supplied with incident light attachment. Lightweight and very compact. Measures only 1x11/x11/3". Complete with mercury battery and leather carrying case. Shpg. wt., 1/2 lb. imported.

GENUINE PIGSKIN GADGET BAG



REMOTE SHUTTER RELEASE

20 Ft. Long

NEW-COMBO-GRIP FLASH BRACKET \sim

Firm Grip for Any Camera
 Provides Mount for Accessories
 Pistel Quick Use of Camera

This new combination grip and utility bracket is better than a third hand. Molded pistol grip provides solid grip for any camera. Particularly useful for SLR's and twin lens reflex. Accessory bracket provides mount for flash guns, meters and strobe lights. Affords ultra safe carry for valuable cameras and accessories. Shpg. wt., 1 lb. 99 H 7162

Lafavette Cat. No. 651

Lafayette Offers VALUE - VARIETY - VERSATILITY

15 H 2501



NEW! KODAK INSTAMATIC 150 OUTFIT

This complete foto outfit is 2295 perfect for the casual photographer who desires professional quality pictures.

Spring wound auto-advance winds film; instant no-thread winds film; instant no-thread the film in the professional part of the professional p winds film; instant no-urreau loading; built in pop up flash holder are among the features of this versatile camera. Preset, fixed-focus lens with choice of 2 shutter speeds allow simple operation. Uses popular AG-1 buils and size "126" film. Outfit comes with carrying case for camera and access. case for camera and accessories. Shpg. wt. 5 lbs.

15 H 2628L Net 22.95

The perfect electronic flash unit for the all around camera man. Small, lightweight,



CAMERA

COLOR OR BLACK AND WHITE

Priced Low Enough Fer Kids Good Enough Fer

Ideal for Use at the World's Fair, at Camp, on the Beach, etc. For Indoor and Outdoor Use Takes up to 16 Color or Black/White Pictures

An amazing camera offer from Lafayette—a snapshot camera that An amazing camera order from Larayette—a snapshot camera full looks like an expensive 35 mm camera, yet sells for a sensational low price. Has three adjustments for close-up to infinity. Takes 16 color black/white pictures on standard roll of 120 film. With lens cover and strap. Shpg. wt., 1 lb.

FILM FOR ABOVE

Pkg. of 2 rolls, 16 exposures each. 120 B & W. Wt. 2 oz. 15 H 1812

BROWNIE SUPER 27 DUTFIT



PRE-VIEWER 8MM MOVIE VIEWER

Ultrablitz MONOVET M

ELECTRONIC FLASH GUN

era man. Small, lightweight, it fits all cameras. Features guide No. 50 for Kodachrome II, even light over wide 70° angle; rechangeable nicad battery with AC adapter which fits any 110-220 volt wall outlet. Flash duration of 1/1000 sec. "freezes" fastest action. Transistorized monitor relay maintains constant light output for 70-80 flashes per charge. Has retractable PC shutter cord. Size: 49sx 27%x136". Shpg. wt., 1½ lbs. Imported. 15 H 3705




Ideal for on-the-spot viewing of 8mm home novies. Lightweight, only 14 oz. Just insert movies Lightweight, only 14 oz. Just insert movie film in viewer and turn crank. Eye level viewing iens provides 20X magnification. Built-in illumination using inexpensive pen wt., 1 lb.

..... Net 6.95 1.5 volt batteries for above ea. ... Net .13

New Dynachrome II

COLOR FILM WITH PROCESSING

- Beats the High Cost of Color Film
- Same Fine Pictures Processing Included Direct To Your Home



your home
15 H 1808 8mm, 25 ft. Daylite ASA 25 Net 2.48
15 H 1808 8mm, 25 ft. Indoor ASA 40 Net 2.48
15 H 1810 35mm 20 Exp. Daylite ASA 25 Net 2.18
15 H 1811 35mm 36 Exp. Daylite ASA 25 Net 3.11

NEW! DYNAPAN—BLACK & WHITE ROLL FILM

Migh quality black & white film for all your snap shot requirements.

2 Rolls of fine grain, fast black & white film per pkg.

15 H 1812 120, 2 rolls per pkg.

15 H 1913 127, 2 rolls per pkg.

Net .59

15 H 1814 620. 2 rolls per pkg.

Net .59

"PRO" ELEVATOR TRIPOD

Holds Heaviest Equipment

Velvet Smooth Panning Action Extends to 461/2"-

Elevator Adds 10"-Closes to 22"



All aluminum construction. Gear drive elevator with positive lock. Large, cushioned pan head fits any camera. Mead ans 3600—tilts 180°. Legs lock at any height. Lock and unlock with a half twist. Completely rigid, even when fully extended. Long section construction for maximum stability. Oversize thumb locks and handle for ease of use. Velvet smooth action in all planes of motion. Positive leg stops prevent overspread. Rubber tipped feet for solid footing on any surface. Satin black and aluminum finish—chrome trimmed. Shpg. wt., 4 lts. imported. Net 11.85

8mm PROJECTOR SCOPE





Films

Fits Most 8mm Projectors

The projectionists friend . . .
The HPI Projector-Scope attachment lets you preview films as soon as you get them. Can be attached easily to most 8mm projectors by simply removing the original lens. Large 45%x3½" screen with a 6-element lens lets you see or show sharp movies without darkening room or setting up a screen. Edit films right on the projector. Can not be used with Basken and Kcdak Brownie models A10 and A15, Includes handy frame marker for easier editing. Shpg. wt., 1 ib.

15 H 3427 Net 5.33

Lafavette Cat. No. 651 75

See Our Catalog 650 For Additional Photographic Equipment

OUTSTANDING 8MM MOVIE CAMERAS & PROJECTORS

NEW! VERNON 8mm CdS YASHICA YASHIMAT ZOOM REFLEX/ZOOM MOVIE CAMFRA



Penlight cells (4 req.) 32 H 4802

Net as.

monthly

REFLEX 8

Fully Automatic CdS Exposure System Film Footage Counter Built-in "A" Type Filter

Zoom Lens

Amazingly compact, the new Yashimat Zoom combines most of the features of top quality full-size 8mm zoom movie cameras in a body small enough to fit in the pocket. Complete with reflex viewing and focusing, It has fully automatic CdS exposure control, electric motor drive and precision 11-element zoom lens with a 3:1 ratio. Only 1½ lbs., the Yashimat Zoom includes such advanced features as a bullt in type A filter, auto-resetting footage counter constantly visible in the finder, battery check meter and 3-way shutter release with safety lock. Reflex viewing through the lens ends parallax error, lets you focus to 3.5 feet without fear of cutting off the top of the subject. Shpg. wt., 3 lbs. Imported.

15 H 38021. Net 89.85

TS H 3502L Net 89.85 Extra penlight batteries (4 req.)

32 H 4802 Net ea.


Automatic Film Leading
 CdS Photo Cell Electric Eye
 Built-in Type "A" Filter
 f/1.8 Electro-Zoom Lens

Now, your film finds its own way to trouble-free loading! A new patented mechanism now takes the frustrating work out of film threading. Simply place film on feed spindle, insert leader into film gate, engage auto-matic mechanism and the film threads it-self. Fully coupled automatic CdS exposure self. Fully coupled automatic CdS exposure system computes and sets diaphragm. Powerful electric battery-operated motor drive with Power zoom control. Focuses from 3.5 feet to infinity. Zoom reflex system view-finder with split-image focusing plus adjustable eyepiece. Has shutter release safety lock, remote control, battery tester, film rewind and film counter, manual exposure possible, cable release socket. Comes complete with batteries and pistol grip. Shpg. wt. 6 lbs. imported. wt., 6 lbs. imported. 15 H 3603L Net 149.95 Extra Penlight batteries (4 req.)

Net ea.

DIAL-A-BOUNCE **MOVIE LIGHT**

with camera mounting Bracket



VERNON 18/28 AUTOMATIC 8mm MOVIE CAMERA



Fully Automatic Electric

Eye Electric Drive . . . No Winding

Sharp f/1.8 Lens

Built-in Handle

Remote Control*

An outstanding value in automatic 8 mm movie cameras. Completely new design of rugged die-cast construction houses a fully automatic camera. Fast, sharp f/1.8 13 mm lens does not require focusing. sharp f/1.8 13 mm lens does not require focusing. Built-in automatic electric eye adjusts lens opening from f/1.8 to f/16 according to light conditions. Adjustable for film speeds ASA 10 to 50, Perfect shots every time. Lens opening visible on side window. No rewinding causing you to miss precious "once-in-a-life-time" shots. All-electric drive runs on 4 inexpensive penilght ceils. Shoots up to 20 rolls without a battery change. Run, lock or continuous run release trigger lets you get into your own movies. "And best of all, a remote control (10-ft. cable) is available at extra cost . . . it lets you obtain true candids, natural shots of children and wild life. Imported. wild life. Imported.

15 H 3402L Shpg. wt., 5 lbs.
Remote control Switch and Cable

.. Net 3.98

Penlight cells (4 req.) 32 H 4802 15 H 3403

Net ea.

De Jur "DUO-VISTA" 8mm **PROJECTOR**



Brilliant f/1.2 15-25 zoom lens 2 slow-motion speeds

Built In Viewing Screen

Ing Screen

A new concept in 8mm projection—the
UNIMATIC-DRIVE. Eliminates home movie
flicker and light fail-off in slow motion. Professional movie quality. Features 8 position
controls—forward, reverse, still, off, normal, fast, very slow and slow speeds—built-in
viewing screen (or regular projection at the
twist of a knob), automatic reel to reel
threading, sharp f1.2 zoom lens with 1525mm range. Separate cooling motor for
longer lamp and film life. Positive chain and
gear drive. Room light control and film
trimmer. Shpg. wt., 20 lbs.

Net 129.95 15 H 5202WX

..... Net 129.95

KEYSTONE K-980Z AUTO-THREAD ZOOM PROJECTOR . Fully



Automatic Threading Fast f/1.5

Zoom Lens Tru-Flector Lamp Gives 500-Watt **Brilliance**

9250

Has 6-second automatic film threading matic film threading matic film threading simply insert the leader and the projector does the rast. Fast f/1.5 lens gives needle-sharp picture . . . zooms picture to fit screen from 11 to 20 feet away. Truflector lamp is brighter, cooler than standard 500W lamp. One knob for forward, still, reverse, off, fast rewind. Variable control speeds or slows action . . controls reverse and forward. Includes focusing control, tilt control and room light switch. Die-cast aluminum body and case, fully geared reel arms, 400-ft. reel. Shpg. wt., 20 lbs.

15 W 2201WX Net 22.50

"HOLIDAY" 8mm PROJECTOR



\$5 monthly

Swing-Out Gate—Easy Loading

Coated ¾" f/1.6 Lens

High Intensity Blower
400-ft. Reel Capacity

NEW SLR Interchangeable T-Mount Lenses

Interchangeable lenses designed for use with popular single lens reflex cameras. These lenses fit a wide variety of uses. Wildlife photography, Panoramic scenes, Sporting events, Aerial photography, and hundreds of other applications. Lenses are manufactured raphy, and hundreds of other applications. Lenses are manufactured in different focal lengths with a variety of maximum lens Apertures to deal with a wide range of photographic requirements of professional quality, these lenses are fully hard coated, color corrected and optically tested to insure top-notch resolving power

MM F:2.8 WIOE ANGLE PRESET LENS Perfect for wide angle panoramic shots. Angle of view 63°. Lens has 5 elements. Lens apertures F:2.8-F:16. Focuses on subjects from 36 inches to infinity. Less T mount lens adapter. 15 H 4904 ..

135 MM F:2.8 TELEPHOTO LENS
4 element telephoto lens; angle of view 18°.
Brings distant objects more than 2½ times closer than normal lens. Easily Interchanged with normal lens. F:2.8-F:22. Filter retainer (Series VI) at rear of lens. Less T mount adapter.

15 H 4905 Preset Telephoto Net 42,50 15 H 4906 Auto Type Telephoto .. Net 54,85

200 MM TELEPHOTO LENSES
Professional calibre telephoto lens magnifies distant objects 4X compared to your normal lens. 2 models F:4.5 preset has 8 ft. close focus distance, 4 elements F:3.5 auto type preset has 5 elements 12 foot close focus distance. Both have 12° angle of view and series VI filter retainer ring at rear. Less T mount adapter.

200 mm F:4.5 Telephoto Preset

Net 42.50 200 mm F:3.5 Telephoto Auto Type Net 87.50 15 H 4908

X-PANDER

- **Doubles SLR Focal Lengths**
- No Complicated Calculations Simple Use
- Quick, Easy Installation And Removal

Amazing optical device practically doubles the effective focal length of any of the above lenses. Precision made, attaches directly to your camera body and takes your present lenses without any alteration. Only a single X-Pander is required for all your lenses in the same camera mount. Simple operation, merely open lens diaphragm two "F" stops from indicated aperture when using the X-Pander. No calculations required. Will not alter focusing scale or minimum focusing distance of your camera. Comes complete with leather case and lens hood. Shpg. wt., 8 02s. 15 H 4911 with case Net 18.33

and clear sharp negatives. Lenses are quickly interchangeable by means of precision lens mounts constructed of durable metals, machined for lasting operation. "I mount" system allows complete interchangeability of all lenses to a large assortment of single lens cameras. Lenses are supplied with carrying case and hood, but without lens mount adapter. Necessary adapters, needed to mount these lenses to your SLR are listed on this page. AVG. Shpg. wt. 2 lbs.

300 MM F:5.6 TELEPHOTO PRESET LENS Perfect for taking life size pictures at long distances. Magnifies 6X greater than normal lens. 4 elements, 8° angle of view, minimum focus 12 feet. Series VI filter retainer at

focus 12 feet. Series vi interioristication rear of lens. Less T mount adapter.

Net 52.50

500 MM F:8 TELEPHOTO "CLICK STOP"

2 element click stop telephoto lens brings objects 10X closer than your normal lens. Click stops assure accurate light control. Angle of view 5°, close focusing distance 17 ft. Sky filter built into rear of lens, Series VI filter retainer ring also at rear of lens. Less T mount adapter ring.

15 H 4910 ...

100-200 MM F:5.6 ZOOM PRESET LENS

instantly adjusts to any focal length between 100 mm-200 mm. 7 elements, angle of view 24° (100 mm) —12° (200 mm) Lens opening F:5.6-F:22, Close focusing distance 10 ft. Select the focal length you need with this precision Zoom lens. Less T mount adapter

..... Net 74.95 15 H 4903

T MOUNT LENS ADAPTERS

These easy to use T mounts adapt the accessory lenses listed above to most SLR cameras. Precision made for easy installation, and remova. See table to determine correct adapter for your camera.

15 H 4912 15 H 4913 15 H 4914 Miranda (for own inner thread Mount) EXA, Exa II, Exakta, Tower 32A, Mamiya Reflex 35 Mikon F, Nikkorex F Minolta Reflex SRI, SR2, SR3, SR7

15 H 4915

15 H 4916 15 H 4917 15 H 4918

minotia Reflex SR1, SR2, SR3, SR7
Canonflex
Konica F, FS, FP Reflex
Petri Penta Va, Flex V, Flex 7
Asahi Pentax, Astra 35, Astraflex 35, Contax D, S, Edixa
Reflex, Hexacon, Honeywell Pentax, Pentacon, Prakti-flex, Petri Penta, Praktica, Rival Reflex, Super D, Yash-ica Penta J, J-3 15 H 4919

Shpg. wt., 4 ozs. NET EACH of the above

FRONT FOCUS PHOTO MONOCULAR LENS SET FOR POLAROID CAMERAS



For SLR or Twin-Lens Reflex Cameras

Coated Lens

Ideal For Viewing Sports, Theater

Take-super-telephoto pictures with your single lens or twin-lens reflex camera. The front focus system is specially made for oncamera operation. There is no need to miss those once-in-a-lifetime shots. Provides upright view in ground glass. Increases focal length of your camera lens 6X, 7X or 8X depending on model selected (i.e. 50mm lens plus 8X monocular equals 400mm telephoto). This monocular is also ideal for bird watching, sports events and hunting—wherever lightweight, high powered magnification is needed, Rugged, lightweight construction—weight only 7½ ounces: is only 5 inches long, includes series VI adapter ring and leather case. Shpg. wt, 1 lb. imported.

98 H 7072 6x30 mm

Net 18.85
98 H 7073 7x35 mm

Net 18.95
98 H 7074 8x30 mm

Net 18.95

Net 16.95 Net 18.95 99 H 7074 8x30 mm

Wide Angle and Telephote Lens View Finder for Accurate Composition

An Ideal companion to the Polaroid Camera. Telephoto lens increases the focal length of the lens and results in a 3 times magnification. Wide Angle lens provides a 75% increase of subject area. Each lens has a "conversion band scale." Supplied with slip-on ring adapter, spe-cial electric-type bracket for viewfinder and flash, filter retaining ring, view finder and genuine leather case with shoulder strap. Shpg. wt., 2 lbs.

15 H 4922 For J-66 Net 32.50 15 H 4923 For 100 Net 32.50



POLAROID® CLOSE UP KIT



Focus as close as 6 inches from your subject. Take portraits—small still lifes — do photocopying. Includes 3 snap-on close-up lenses, leather case and built-in tape for accurate focusing. Shpg. wt., 8 ozs.

For all except 110B, 110A, 110, J-33, J-66. J-66 15 H 3001L

REPLACEMENT KIT FOR POLAROID® WINK-LIGHT

Kit contains both battery and bulb for replacement in Polarold WINK-LIGHT. Manufacturer recommends both battery & bulb be replaced together to insure well lighted shots. Shpg. wt., 1 lb. 32 H 4852

THREAD ZOOM PROJECTOR



- · Brilliant-**Powerful**
- f/1.5 15 to 25mm Zoom Lens

New Vernon "88" combines such good fea-tures as a 15 to 25mm f/1.5 zoom lens and a low power Tru-flector lamp which is cooler than and as brilliant as a 500 watt cooler than and as brilliant as a 500 watt lamp. Completely automatic threading assures ease of operation. Cooled by a powerful blower. Controls include focusing, framing, and tilting. Fast power rewind. Bullt-in film cutter. Sturdy die-cast construction. Operates from 100-240 volts 50/60 cps. Low slim modern design. Shpg. wt., 10 lbs. Imported.

15 H 3428 Net 69-95

NEW VERNON 808 SUPER



4"x5" Giant Screen Bright

Viewing This professional quality 8mm movie editor has a fresnel lens screen almost three times the size of the average movie editor. Fresnel lens gives over-all brightness without center hot spots. Editor has convenient frame marker and fine focusing wheel. Rewind arm is geared for speedy rewinding. Large hood shields picture area so editor can be used in a lighted room. Arms fold for easy compact storage. Shgs. wt., 6 lbs. Imported.

15 H 3429

Net 29.95



Includes Butt-Splicer, Quik-S Rewinds and Mounting Board Quik-Splicer, FPS Scale

Complete 8mm splicing and film repair outfit includes butt-type splicer, two post rewinds with self-lubricating Nylon gears mounted on a deluxe hardwood base which has a scene timing scale. Holds reefs with up to 400' film capacity. Steel arms are chrome plated. Shpg. wt., 2 lbs. 14 H 3426

LAFAYETTE ZOOM LENS



 Zoom to Dra-matic Close-Ups! Fill the Screen from 12 to 15' then ZOOM

Coated f/1.5, 15 to 25mm focusable zoom lens fits most popular priced projectors. Converts "Holiday" and "Ultra" into modern, zoom projectors. Adds realism and depth to old "reels." Fills a 30x40" screen at from 12' to 15'—then zooms in for exciting closeups. Show your movies at the size you want—without moving projector or screen. Shpg. wt., 6 ozs. Imported. wt., 6 ozs. 99 H 7103L

Net 6.95

NEW VERNON "88" AUTO- Deluxe 8mm Movie Camera

LAFAYETTE SUPER 8 MOVIE CAMERA

• Fast f/1.9 4-element lens
• Electric drive—no winding
• Enclesed optical viewfinder

A truly modern, versatile, and inexpensive movie camera. Fast f/1.9 4-element lens captures all the exciting action in brilliant color or black and white. Fixed focus lens never needs adjustment because of a change in the distance between camera and subject. Electric motor drive with built-in standard "C" batteries eliminates bothersome hand winding. Just aim and shoot—even beginners get perfect movies every time. Automatic reset footage meter is easily readable. Variable, click-stop, lens aperture opens from f/16 to f/1.9. "Drop-in" spool loading is easy and economical. Exposure 39 H 7180t.

Batteries for show (Common March 1988)

Batteries for above (2 required) 15 H 1601 Carrying case 15 H 3406 Pistol grip handle

TRIPLE-TURRET f/1.8 ELECTRIC EYE CAMERA

Automatic, Cross-Coupled Electric Eye • 3 Quick Change, Turret-Mounted (1.8 Lens • Built-in "A" Conversion and UV Haze Filters • Pistol Grip with Trigger Release • "Combo-View" Finder for Normal, Wide-Angle and Telephote Shooting
You get perfectly exposed movies automatically simply by aligning the needle in the viewfinder. Film speed selector dial adjusts for speeds of ASA 10-40. A quick twist of the turret dials the effect you want; from Normal to Wide-angle or Telephoto for thrilling close ups of distant subjects. The fast (7.1.8 fixed-focused lenses are color-corrected and coated. Etched optical view finder shows exact field for each lens. Economical drop-in spool loading. Includes instructions and pistol grip handle. Imported.

99 H 7178L Shpg. wt., 5 lbs.

Net 29.95
Net 29.95
Everything you need for movie-making and showing fun. You get all this; triple turret

Net 2.95 Everything you need for movie-making and showing fun. You get all this; triple turret—f1.8 Electric Eye Movie Camera, camera case, 500 watt projector, 30"x67 screen. 500 watt bar light with lamp, two 400' reels with storage-cans. Unbeatable for foolproof shooting and showing of indoor and outdoor movies. Shpg. wt., 30 lbs. Net 79.95

NEW DEJURETTE SLIMLINE AUTOMATIC

15 H 3403 Remote control switch and cable 32 H 4802 Penlight cells (2 req.) . Net 3.98 Net ea.

LAFAYETTE AUTOMATIC ELECTRIC EYE

Fast f/1.9 Zeem Lens

Fully Automatic Exposure

Frecision-made 8mm movie camera has built-in electric eye which automatically sets correct exposure for any film (color or black and white) from ASA 10 to ASA 40. Fast, f/1.9 lens zooms from wide-angle, through normal, to telephoto. Picture-window viewfinder zooms with lens. Features Include manual exposure control, single frame exposure (for animated titles, etc.), film counter, cable release socket, sturdy pistol-grip handle for easy trigger action, and fast drop-in spool loading. Shpg. wt., 99 H 7179L

ZOOM MOVIE OUTFIT

A complete zoom movie outfilt with matched components to assure success in taking and showing home movies. The Camera is Lafayette's Zoom f1.9 Auto 8, "Ultra" 500 projector, 30x40" folding screen, Hi-Lite movie gun, 2 sets of 400' reels & cans, zoom camera case. Shpg. wt., 40 lbs. Imported. 15 H 9003

MINOLTA ZOOM 8

 CdS Electric Eye Automatic Exposure TU-Element f/1.8 Rokkor Lens

• CdS Electric Eye Autematic Expesure • TU-Element f/1.8 Rokker Lens • Micromotor Electric Drive
A fine, battery powered, 8mm camera featuring a sensitive cadmium sulfide light meter that automatically sets the right exposure for any film (ASA 10-400), color or black and white. Zoom 8 does the rest. A warning signal shows in the viewfiner in case of insufficient light for perfect exposures. Rokkor f/1.8 lens zooms from wide-angle to telephoto (10-30mm) with the touch of a finger, Filming Speeds: 12, 16 and 24 fps. Phigh-efficiency micro-motor is powered by four inexpensive penlight batteries (included). Mas manual control for special effects, single lens reflex viewfinder for through-the-lens focusing and viewing, built-in, battery level indicator. Spool loading. Shgs. wt., 4 lbs. 15 H 340ft L Imported
Net ea. 13
Net ea. 13 32 H 4802 Repl. Penlight Batteries (4 req.) Net ea.
15 H 3405L Minolta Zoom 8 Case. Shpg. wt., 2 lbs. Net
15 H 3407 Remote Control Switch and Cord. Shpg. wt., 4 oz. Net .13 12.95

YASHICA U-MATIC Cds REFLEX ZOOM

 CdS Automatic Exposure System 3 Filming Speeds
 Electric Motor Drive Trigger Pistol Grip

Trigger Pistol Grip

The U-Matic 8 combines the convenience of automatic CdS electric eye exposure with wind-back and fade controls for lap dissolves and complex trick effects. High speed Yashinon f/1.8 lens zooms from 9mm wide-angle to 28mm telephoto. Parrallex-free reflex viewfinder permits "through-the-lens" viewing. Battery operated motor runs camera at 12, 16 and 24 fps for fast, normal or slow-motion filming. Has ASA film speed dial (10, 16, 25, 32, 40); built-in battery tester; zoom lever; manual exposure control; exposure warning (indicates insufficient light for filming); adjustable eyepiece. Spool loading. Supplied with 16-ft. remote control and switch, trigger pistol grip and four penlight batteries. Shops. wt., 3½ lbs. Imported.

15 H 3804. Rent penlight batteries (4 ren.)

32 H 4802 Repf. penlight batteries (4 req.) Net ea.

.13

FINE MOVIE CAMERAS TO FIT EVERY BUDGET

LAFAYETTE SUPER 8 MOVIE CAMERA



16⁹⁸ 99 H 7180L

TRIPLE-TURRET f/1.8 ELECTRIC EYE



29⁹⁵ 99 H 7178L

NEW! De JURETTE SLIMLINE AUTOMATIC



49⁹⁸ 15 H 5201L \$5,00 WONTHLY

LAFAYETTE AUTOMATIC ELECTRIC EYE CAMERA



MINOLTA ZOOM 8



119⁹⁵
15 H 3401U
AS LITTLE AS
\$6,00 MONTHLY

YASHICA U-MATIC Cds REFLEX-ZOOM 8



99⁹⁵

15 H 3604L \$6.00 MONTHLY



MIRANDA DR 1.9 35MM SLR
AS LITTLE AS 12995
15 H 3703L \$6.00 MONTHLY 129



995 \$8.00 MONTHLY

YASHICA PENTA-J SLR











78B Lafayette Cat. No. 651

Cameras are Available on Easy Pay Plan-See Center Insert A

MIRANDA DR 1.9 35 MM SLR

• Automatic Interchange. 50 MM f1.9 lens • Accuracy of Single Lens Reflex Plus Speed of Range Finder Focusing • Fully Automatic f/1.9 Lens

A complete 35 mm precision single lens reflex comera of outstanding quality. The DR features sharp f/1.9 lens with automatic diaphragm. Closes down to f/16; pentaprism finder for brilliant right-side-up reflex viewing and eye focusing; split-grid rangefinder, threaded and bayonet lens mount accepts a large variety of lenses; instant return mirror; depth of field preview button; single-stroke lever advances film and exposure counter and winds shutter, Focal plane shutter has 1 to 1/500 sec. speeds, FP and Kighs synchronization. Focuses down to 17 inches. With case. Shpg. wt., 5 lbs. Imported. 15 H 3703L

YASHICA PENTA-J SLR

Outstanding 35mm single lens reflex camera has Yashinon 50mm f/2 hard-coated anastigmat lens with convenient screw-in type mount. Features accessory clip for optimal shutter-coupling exposure meter (see below); split-image rangefinder for needle sharp focusing; built-in Penta-Prism and Fresnel lens for brilliant, parallax-free viewing; completely automatic instant-return mirror; fully automatic film winding, 9 shutter speeds, ½ to 1/500 second plus X and B. Complete with carrying case, less exposure meter. Shpg. wt., 3 lbs. Imported.

YASHICA EXPOSURE METER FOR PENTA-J

KOWA "H" AUTOMATIC SLR

Here is a fully automatic single lens reflex 35mm camera. Just set the film speed on the easy to read dial, focus and shoot perfect pictures. Everything is automatic. Provides for easy focusing. Manual over-ride allows you to set lens and shutter for different exposures. An indicator in the viewfinder facilitates its use for automatic exposure control. New minimal movement, trigger film advance is done with the left hand freeing the right hand for steady shutter release. 48mm coated, prominar-type lens gives excellent resolution and color reproduction. 8 shutter speeds to 1/300 sec. with case. M and X flash synch. Shpg. wt., 3 lbs.

MINOLTA HI-MATIC "7" 3-WAY EXPOSURE OPERATION

• Fully Automatic • Cempletely Manual • Semi-Automatic Plus unique on-the-lens electric Features flexible shutter and iris settings. Camera may be set to allow cadmium sulfide electric eye to select the best combination of aperture and speed, Manual operation permits and approach of a sec.—plus 'IB." setting of aperture from f/1.8 to f/22 and shutter from ¼ to 1/200th of a sec.—plus "B," Precision Ribbor 45mm f/1.8 achromatic coated lens. Electric eye is on the lens to measure light accurately—even through filters. Bright double image range finder. Single-stroke film advance with double exposure prevention. Built-in 10 sec. self-timer. ASA range 25-800 fully synchronized with electronic flash. Automatic frame counter. Shgg. wt., 2 lbs. Imported 15 H 3432 Net 94.50

MINOLTA "16 II" SUBMINIATURE CAMERA

• Rokker 3-Element f/2.8 lens • Automatic Film Advance & Shutter Cocking

Sliding camera in and out of built-in case advances film, cocks shutter, counts exposures and prevents double exposure—all automatically, 6 shutter speeds from 1/30 to 1/500 sec. plus B. Click-stop settings. Synchronized for electronic flash and built. Takes regular black and white pictures or color slides that fit any 35 mm projector. Direct viewfinder shows picture exactly as it will appear on film. Lens opening from f/2.8 to f/16. Click-stop settings. Complete with case. Shpg. wt., 1 lb. Net 29.95

FILM FOR "1611"—All are 20-exposure magazines. Shpg. wt., 3 oz. 15 H 3417 Kodak Panatomic X 15 H 3418 Kodak Tri-X Net 15 H 3419 Kodachrome II MINOLTA 16 II Accessories. Avg. Shpg. wt., 6 oz. 15 H 3421 Baby BC Flash with Capacitor and Case 15 H 3422 Bracket for Flash and Tripod Mtg. 1.25 Net Net Net 1.95 15 H 3423 Aux. Lens Set—2 closeup, 1 distance, 1 Y filter 15 H 3424 Color Filter Set—1 ea. 1A, 80A, 81B Net 3.95 Net 3.95

DURST ALL-IN-ONE DARKROOM

e Special "easy-lead" Negative Carrier e Converts to a Copy Camera

Enjoy the thrist of taking and making your own pictures. Enjoy the satisfaction of catching fleeting moments on film and bringing them to exciting life in enlargements. Everything you need is in the Durst darkroom kit—quality subminiature to 2½" sq. Durst 606 Enlarger with 75mm lens, dust cover, set of DURST/KODAK poly-contrast filters, darroom safelight, interval timer, adjustable film developing tank, 4-way paper easel, 2 stainless steel film clips, three 8x10" paper developing trays, graduate, 2 tongs, print squeegee, thermometer, blotter book, 25 sheets 8x10" Kodak printing paper. 1 qt. developer, 1 qt. paper developer, ½ gal. fixer. 75 watt opal enlarging lamp and a complete darkroom guide. Shpg. wt., 45 lbs. 15 & 3499WX With F/4.5-50mm lens Net 159.95

TRANSISTORIZED ELECTRONIC STROBE FLASH

Lightweight & Compact — No Power Pack Needed
 Operates on 4 Economical "Z" Cell Batteries
 Fits any Camera Shoe

Now you can have a high-powered transistorized electronic flash at low cost. Compact and now you can nave a nign-powered transistorized electronic flash at low cost. Compact and featherweight — no power pack is required. Flash duration of 1/2000 sec. for fast pictures, Recycling time: 6-10 seconds; color temperature: 6000° Keivin. Guide number dial for F stop on back. Complete with AC cord. Less batteries. Shpg. wt., 2 lbs. Imported.

89 H 7068

Net 19.85

Batteries for above (4 required).

Net ea.

500 WATT SLIDE PROJECTOR



Automatic Slide Changer Color Corrected 4" f/3.5 lens Holds up to 40 Sildes

500 Watt

Designed and engineered for simplicity of operation, easy of maintenance and long life. 4" color corrected, hard coated f/3.5 life. 4" color corrected, hard coated f/3.5 lens. Sharp, brilliant pictures assured by 500 watt lamp. No slide trays required. Project any 35mm, Bantam, 127, or Instamatic slides. Loads up to 36 slides. Different size slides can be loaded together. Uses standard projection lamp. Compact 5%HX14Lx8½"W. For 105-120 volt 50/60 cycle operation. Shpg. wt., 7½ lbs. 15 H 8401



DELUXE LENTICULAR

• Greater Brilliance **Durable Vinyl Fabric**

Specially-designed, optically-correct lenticular screen is free of glare, sheen and hot spots. Amazing sharpwess and color rendi-tion. Durable vinyl fabric resists fire and fungus. Sturdy chrome tripod legs. Screen is 40x40". Shpg. wt. 12 -bs. 18 H 5005W Net 11.88



LAFAYETTE AG FLASH GUN

Compact, palm size de-pendable B-C operation. Made for the new AG lashbulbs. Fan-type re-2" in diameter when

flector measures 2" in diameter when opened. Shoe fits all standard accessory clips. Features a Computer Dial for determining correct F stop. Testlight, and Bulb Ejector. Complete with cord. Operates on 15V battery (not incl.). Shpg. wt., 8 ozs. se u 7105 importec Net 2.88 15-Volt Battery for above

BOUNCE FLASH BRACKET



Particularly suited to Single-lens Reflex cameras. Permits bounce flash with any clip on Flashgun. Mounts in standard tripod socket. Adjustable length, rotating-swiveling head. Shpg. wt., 6 ozs. Imported. 98 H 7089 Net 1.05

32 H 4802

BATTERY CHARGERS, CONVERTERS and INVERTERS

TRANSISTORIZED POWER CONVERTER

. Small Enough To Mount In Any 12-Volt Car Or Boat

Converts 12 VDC To 117 VAC

 Supplies Voltage For Any Equipment Requiring From 10 to 125 Watts

Rated at 125 watts continuous duty, this fully transistorized, highly efficient converter plugs Into your car's cigarette lighter socket to supply 117 volts AC to operate any equipment requiring 10 to 125 watts including electric shavers, recorders, record players, radio, TV and many others. Has "Power to Spare" for extra years of dependable service. Shop. wt., 5 lbs.

11 H 7301 Net 29.95

2-IN-1 BATTERY CHARGER



End dead battery trouble in your car, boat, truck or tractor. This powerhouse battery charger keeps all 6 and 12 volt batteries fully charged for peak performance even at 40° below freezing. Full 1 amp. "safe" charge rate prevents flacking and plate buckling—same method used by storage battery dealers. Easy to use—plug the line cord into any 110V outlet, connect the two terminals and forget it. Can't overcharge—automatically tapers off. Weided constructed steef. Shpg. wt., 33/2 lbs.

11 H 7802 Net 4.25

PROFESSIONAL 3-AMP. BATTERY CHARGER

For Both 6 and 12 Volts



Approved

For Both 6 and 12 Youx

A professional type 6-12 volt battery charger with automatic reset circuit breaker, Indicator light flashes on when circuit breaker trips. Front panel switch for change-over from 6 to 12 volts. Delivers a tapering charge starting at 3 amps for 6 or 12 volts. Noiseless, alrocoled construction. Oversized components and vented case for troublefree operation. Runs cool even under constant use. 6 ft. charging cables with heavy duty, 25 amp battery clips. Measures 4x6x34". For 105-125 volt, 50-60 cycle AC. Shpg. wt., 5 lbs.

Net 8.95

TRANSISTORIZED 40-50 WATT INVERTER

• Ideal for Salesman, Sportsman, Executive • For Dictating Machines, Razers, Port. Tape Recorders, Etc. Use in Car, Boat or Private Airplane

2 power transistor inverter supplies 40 watts continuous, 50 watts intermittent from 12.6 volt storage battery. Silent operation. Attractively finished green Hammerlold steel case. Epoxy filled to insure longer life. Supplied complete with 3 foot cord and plug for immediate insertion into

CORNELL DUBILIER 12TV12

DC TO AC INVERTER

95

Especially Designed to Power Portable TV Sets with Power Requirements up to 120 watts

Ideal for Automotive, Marine, House Trailers, Campers, etc., as a Source of AC Power Independent of Power

The Model 12TV12 converts 12 volt DC from any 12V storage battery, to 110-120 volt AC at 60 cycles.

Designed primarily for television receivers, tape recorders, phonographs and other frequency sensitive devices, the 12TV12 employs a resonant reed tuning component to assure frequency stability. No loss of B+ in TV brilliance. Will power any TV, ham rig, CB station, or Hi-Fi unit within the 12D/140 watt power requirement rating. Perfect for car or boat.

SPECIFICATIONS **SPECIFICATIONS**

Input: 12 volts @ 12 amperes (full load); Output 120 watts continuous, 140 watts intermittent; RF filtering on both input and output; Finish: Zinc Chromate corrosion resistant undercoat, crinkle paint black bottom and smokerise grey top. 8¾Lx7½wx3¾"H. Wt., 134 lbs. Shpg. wt., 16 lbs.

Net 29.95

Medel MK-3544-5 Mounting Kit for 12TV12—Provides safe, secure mounting to bulkhead, wall, or floor, Supplied with all necessary mounting hardware. Shpg. wt., 2 lbs, 34 H 5502 Net 3.60

COLD-START BOOSTER-CHARGER



Our First Combination Battery Charger and Booster.

- 50 Amp Booster (6 volt)
- 25 Amp Booster (12 volt)
- 10 Amp Charger (6/12 v)

Perfect for starting 6V, 8V, 12V cars. Works as a booster—as a charger. Supplied with heavy copper cables; thermal switch prevents overheating; works up to 200-ft. away from AC power source. Power output: 12V Boost, 25 amps maximum; 6V Boost, 25 amps max; 6/12V Charge, 10 amps tapering to 5 amps max; Power Input: 5 amps max at 117V AC, 60 cycles. Shpg. wt. 942 ibs. 11 H 4001

BATTERY BOOSTER CABLES



As Low As Standard equipment for starting stalled cars, charging batteries, etc. Made with heavy duty, flexible rubber-covered cable.

Rugged copper-clad positive ac-tion grips identified by Black and Red heavy vinyl covered handles. Shog. wt. 3 lbs. 11 H 2901 8 ft. long, set of 2 Net 1.48 11 H 2902 12 ft. long, set of 2 Net 2.25 12 ft. long, 6 gauge copper cable. 11 H 2903 . Net 3.15

Battery Booster Clip only. 11 H 2904C (specify Red or Black) Net .49

INVERT O-CHARGE



Combination Power Inverter and 8 Amp Battery Charger

This dual purpose unit will operate 120 volt equipment from a 12 volt battery or charge a 12 volt battery from a 120 volt source! 175 watts cont., 225 watt intermittent operation; metered input and output; Push button solid state operation; Protective cir-cuit breaker; Operates any AC device within its power limitations. Shpg. wt., 10 lbs. 11 H 3701 Net 38

Y CHARGERS—INVERTERS—ELIMINATORS—LI



ONE CHARGEABLE BATTERY OUTLASTS DOZENS OF CONVENTIONAL BATTERIES

Replaces 2U6, BL-008P and 99 G 9021 Fluid Storage Type Plays About 15 Hours on One Charg-

Battery Recharges Overnight Battery Can Be Used Over and Over Again Complete—Battery Plus Charger

9V Battery complete with charger. Battery 1%x1%"; charger 3%x 1¼x7%". Imported.

NFT 2.69 99 H 9016 Battery and Charger. Shpg. wt., 6 oz. NET 2.69 98 H 6026 Battery Replacement for above, wt., 3 oz. NET 1.29

As little

9-VOLT TRANSISTOR RADIO BATTERY

Replaces RCA VS323, Burgess 2U6, Eveready 216, Zenith Z216, Ray-O-VAC 1604, NEDA 1604. Shpg. wt., 2 oz. Imported. Net ea

of 10

99 H 6021

Net ea., Lots of 10 .20



LAFAYETTE 9-VOLT TRANSISTOR RADIO BATTERY CHARGER AND ELIMINATOR



Charge Battery, Operate Set On AC, or Both **Isolated** Transformer -Shock-Proof

Just plug into any 117-volt AC receptacle and recharge your old 9-volt battery for many hours of extra use; or operate your set indoors without using the battery at all; or you can both charge battery and operate set at the same time. Has 4-position switch for above functions plus off position and pilot light. Size: 4Wx11/4Hx 25/4"D. Imported.

99 H 9021 Shpg. wt., 1 lb. ..

Net 3.45

DYNAMIC BATTERY CHARGER FOR 6-VOLT LANTERN BATTERIES



Keep lantern batteries like new for months—far exceeding their normal life. Pays for itself many times over. Equipped with an isolating step-down power transformer, it is safe from shock hazard. Just connect charger leads to battery binding posts and plug charger into any 117-volt AC outlet. Chart showing chargeable battery types and charging time required is included. Size: 1¼x1¾x2½4".

34 H 4201 Shpg. wt., 34 lb. .

TERADO "DYNAMO" DC TO INVERTER

Convert Your Table Medel Radio to a Car or Boat Radio



Operate any small radio in any 12 volt car, truck, boat or trailer. No installation—just plug into cigar lighter, Needs no outside antenna—table radios will operate on their own built-in antenna. Will also operate your electric shaver or any electric appliance up to 20 watts. Complete with generate condenser and ignition noise suppressor. Measures only 2x2x334". Shpg. wt., 2 lbs.

33 H 5302

Net 8.87

TERADO "QUIK-SHAVE" AC TO DC INVERTER



Any shaver, new or old, gives super performance with QUIK-SHAVE, which changes household AC electricity into jet powered DC. Lengthens shaver life. Up to 88% more cutting power for faster, closer, more comfortable shaves. Plug QUIK-SHAVE into wall outlet, attach shaver cord, and shave twice as fast!

33 H 5301 Shpg. wt., 8 ozs. U.L. Approved Net 3.85

Everything In Electronics For Home, Industry and Laboratory


and EL

The new dry cell battery recharger and eliminator will replenish your supply of flashlight batteries. Recharges "C." "D" and "Z" cell batteries in 2 to 4 hours—keeps battery-operated toys always on the go. It's a battery eliminator too—simply plug into any 110V AC outlet. Delivers 4 to 6 V. DC for "recharge" or "eliminate." Net 4.95 33 H 7701 Shpg, wt., 11/2 lbs.

NEW CHART CHARGE NICKEL-CADMIUM BATTERY CHARGER

o Charges 1 to 10 Cells In Series Up to 250 MA

Designed to meet the demands for Nickel-Cadmium Cells in the industrial and hobby fields. Charges 1 to cells in 10 series and is continuously



34 H 4101

PREE

Net 9.95



BATTERY ELIMINATOR "B"

and CHARGER

Replaces Eveready 416, Burgess UX-45, and RCA VS 318 674/2V B batteries used in Radio Coatrol units and meny portables. Just plug in the AC cord and you can save your battery for outdoor use. Also recharges your battery. 110 volts. 34/2x1x%. Shpg. wt.,, 7 oz. imported. volts. 31/2: 99 H 9092

RADIO TRANSVERTER

Fits all Cars

Converts . For all 9-Voi: Transistor Radios Transistor . Plugs into Cigarette Lighter

Radio to Car Radio "

Now you can avoid the expense of buying a car radio with this new radio transverter. Simple to operate remove 9volt battery from your transistor radio, connect contacts from transverter to battery contacts in the radio, and then plug into the cigarette lighter. Fits a I cars. Shpg. wt., 6 oz. . Net Net 1.47

11 H 4801 For 12-volt Cars ... RECHARGEABLE FLASHLIGHT



Always ready for use-no more batteries to buv. Simply plug into the nearest 110V. A.C. wall outlet—leave overnight—for a comolete recharge, Self contained charger and cells need no service or replacement in normal use. 4x13/4" overall. Shpg. wt., 6 ozs. Imported.

14 H 2102

Net 2.59

Net 85

BIG BEAM LANTERN

Powerful, versatile sealed beam hand lamp. Operates as a lamp, a flashing red beacon or both. The flashing beacon may be positioned up or down. Sealed beam bulb keeps mirrored reflector dust free. 4" chrome-plated steel reflector dust free. 4" chrome-plated steel amphead. Steel weatherornof case with hinged cover and snap catch. Operates on one battery. Shpg. wt., 3 lbs. ... Net 6.98

13 H 7901 Less Battery No. F4H battery, wt., 1½ lbs. 32 H 4869



LAFAYETTE - For The Finest In Car Radio Listening

ALL TRANSISTOR FM-AM **AUTO RADIO**

- Push-pull Hi-Fi Output
- Convenient Under-Dash Installation
- 12-volt, Negative Ground Operation
- AFC for FM Drift-Free Performance
- High Sensitivity for Super Distant Reception on Both AM and FM
- 11 Transistors, 6 Diodes, 1 Thermistor
- Four Stages of I.F. Amplification on FM for Maximum Noise Limiting



only

A fully transistorized AM-FM radio with many Hi-Fi features. Instant play—just turn it on and immediately enjoy either AM or FM listening pleasure. Extremely sensitive for "pulling in" distant stations. A push-pull Mi-Fi output provides 10 watts of peak power which is more than enough to fill your auto with sound. Low battery drain — 1 amp @ 8 watts output. Specs: 11

transistors, 6 diodes, 1 thermistor; tuned circuits-7 on FM, 5 on AM; Sensitivity: 3 μv for 20 db quieting; Speaker-external 3.16 oz. Alnico magnet; for 12-volt, negative ground installations. Dimensions: 61/4" wide x 2%," high x 6%," deep. Shpg. wt., 8 lbs.

.. Net 79.95

ALL-TRANSISTOR MANUAL AUTO RADIO COMPLETE with FREE ANTENNA



- 5 transistors and 2 diodes
- Convenient underdash mounting
- For 12-veit negative ground installations

A fine quality AM radio that utilizes "solid state" construction in a Superheterodyne circuit for trouble-free operation. Finger-tip control to adjust tone as you desire. Also contained is an electronic automatic volume control to keep signals strong and steady. This unit is exclusively hand wired for ruggedness—no printed circuitry. Fits under-dash or in-dash utilizing standard trim plates. Available for 12-volt negative ground installations. Neutral gray-tan baked enamel finish. Overall size: 5½0x6½wx2"H. Shpg. wt., 4½ lbs. 17 H 7405M

ALL-TRANSISTOR PUSH-BUTTON AUTO RADIO with FREE ANTENNA

\$5.00 monthly



- Fits Compactly Under Dash 5 Transistors plus 2 Diodes • Superheterodyne Circuit • 5x7" Speaker
- For 12-volt negative ground installations

This all-transistor push-button AM radio fits all cars requiring 12 volt, negative ground installation. Hand-wired superheterodyne circuit employs 5 transistors and 2 diodes for outstanding reception. Automatic volume control keeps signal strong and steady. Radio mounts neetly under dash. Gray-tan baked enamel finish. Overall size 51/20x61/2Wx2"H. Shpg. wt., 6 lbs.

BLAUPUNKT ALL-TRANSISTOR FM, AM, SW & MB AUTO PORTABLE

 Use It As a Portable—install it in your Car • 4 Bands-FM, AM, Shortwave and Marine Band . Ten Transistors, Four Diodes

Carry it as a portable or install it in your car using an optional easy-to-install adapter that disappears under the dash when not in use. Plays for approx. 300 hours on 6 inexpensive 1½-volt flashlight batteries (not supplied). A built-in ferrite antenna is used for AM reception; a retractable, pivoting telescopic antenna for shortwave/FM reception. Has push/pull output stage and sockets for earphone, tape recorder and record player. Also has a variable tone control for true hi-fi music reproduction. Attractively housed in a black leatherette case. Size: 9½x7½x3½°. 17 H 1515WX Blaupunkt Auto-Portable

Universal Mounting Bracket, with lock, for auto use (6 or 12 volts-reverse polarity) "D" size flashlight battery (6 reg.) for portable use. 32 H 4804

Net 19.00

.13

..... Net ea

RANGER PLAY-MATE 8-TRANSISTOR AUTO/PORTABLE AM RADIO



• The Auto-Radio You Can Enjoy Wherever You Go, Whatever You Do • A Deluxe Car Radio as well as a Powerful Portable Radio • Operates on Auto or Boat's 12-Volt Power Supply, or 4 Penlite Batteries • Locks in Place in Car or Boat—Prevents Theft

The Ranger Pley-Mate plays everywhere, goes anywhere. Insert it in its mounting case and it operates on car or boat 12 voit power supply like any other permanently-installed radio . . slip it out and you have a powerful lightweight portable with a metallic gold finish, powered by its own penlight batteries (not included). Radio locks in place in car or boat, prevents theft. 8 transistors, plus diode plus thermistor super-het circuit with H.F. amplifier. 3½" speaker. For 127 n. 7207

17 H 7407 32 H 4802 Battery For Portable Operation (4 required)

Net 47.50 Net .13

NEW LAFAYETTE TRANSISTORIZED AUTOMOBILE REVERBERATION SOUND SYSTEM

FROM LAFAYETTE ... AUTO REVERBERATION - A 3rd DIMENSION IN SOUND



Made in U.S.A.

The new Lafayette Transistorized Automobile Reverberation sound system consists of the transistorized amplifier chassis with the reverberation unit, under dash control plate with on-off switch, fader control, and interconnecting cables. Includes simple Instructions for connecting the reverb unit to your regular under dash auto speaker, and to a separate rear seat speaker (if your auto does not have a rear seat speaker, see listing of rear seat speakers below. Reverberation is an entirely different approach to sound reproduction. Normal sound reproduction from a single source has a flat, one dimensional effect; with proper sound delay through "REVERBERATION," tones are created with a truly third dimension for concert hall originality. Mounts conveniently in the trunk of your car. For all 12-volt negative ground AM or FM auto radios. Dim: 10½2x1x6". Shpg. wt., 3 lbs.

Net 23,95 The new Lafayette Transistorized Automobile Reverberation sound 17 H 0105

Net 23.95

NEW MOTOROLA FM/AM CAR RADIO

Model FMA100

- FM Response 50-15,000 cycles
- Special Acoustinator Circuit
- 14 Transistors, 7 Diodes
- Push-Pull 8 Watt Audio System
- FM/AM Indicator Light

\$6 monthly



For 12 Volt-Negative

Ground Systems

Fine FM/AM entertainment is combined in one car radio to bring you enjoyable listening on both broadcast bands. Powerful circuitry incorporates 14-transistors plus 7 diodes and 1 thermistor. FM section delivers full frequency response of 50-15,000 cycles through a powerful 8-watt push-pull audio circuit. Push button activated acoustinator circuit minimizes interference in primary signal areas. Low battery drain (.5 amp), instant warm-up and FM/AM indicator light are extra features. Includes full variable tone control, 5x7" Golden Speaker. For 12 Volt-negative ground systems. 7¾Wx2½Hx67%"D. Shpg. wt., 13½ lbs.

17 H 1011 Model FMA100 Net 129.95

MOTOROLA TRANSISTOR MANUAL CAR RADIO for 6 Volt Systems



PLUS FREE **MOUNTING KIT**

SPECIFY MAKE, MODEL AND YEAR OF CAR

universal set designed to fit 6-volt sports Compact. Compact, universal set designed to fit 6-volt sports cars, trucks, boats and older cars. Hand-wired, all-transistor chassis with 7 transistors, 2 diodes, 1 thermistor provides 2 watts undistorted output to built-in 5" Golden-Volce speaker. Features low 1-amp battery drain, automatic gain control, antenna band pass fifter, thumbscrew antenna trimmer, "Instant Play"—No warm-up necessary. Reversible polarity. Size: 67%Wx2½Nx71/4"D. Shpg. wt., 6 lbs.
17 H 1007M Model 414 ... \$5.00 Monthly... Net 39.95

TENNAMATIC" ELECTRIC AUTO ANTENNA

Electrically Raises & Lowers As Low As Automatically

Eliminates **Vandalism**

688

Enables you to operate the antenna at the flip of a switch. No need to get out of car to lower antenna before entering lower antenna before entering garage. Designed to fit most 12 volt cars. Mast extends to 35" and retracts to 1¼". Antenna cable is copper shielded. External parts are plated with chrome. New construction eliminates "motor burn out." Positive 15 lbs. thrust insures "free even in sub zero temperatures. with cable clips. harchets switch

action" Complete with cable, clips, brackets switch and plate, screws, wiring harness and instructions. Shpg. wt., 6 lbs.

REAR MOUNT-18 feet of antenna lead and 20 feet electric harness.

11 H 7102 Net 26.88 FRONT MOUNT—54" of antenna lead and 72" electric harness. Net 26.88

TIRE PRESSURE GAUGE



Helps Maintain Proper Tire Inflation

Low pressure tire gauge (5-50 lbs.) accurately reads air pressure on auto and truck tires. Accurate scale insures proper inflation of tire for longer life, smoother ride. Shockproof; pocket clip. Shpg. wt., 4 oz. Net 89

For Index See Page 3

REAR SEAT SPEAKER KITS FOR TRANSISTORIZED RADIOS



Features Multi-impedance Match For 40, 20, 8 ohms or less
 New Slim Line Construction
 SPEAKER KITS
Complete 6x9" rear seat kit featuring new multi-impedance Slim line 6x9" speaker; chrome grill, 100 ohm Fader control, 40 ohm adapter for Motorola Radios, and a 20 ohm adaptor for Automatic radios. Shpg. wt., 6 lbs.

32 H 2202

Net 4.69


DUAL HI-FI REAR-SEAT SPEAKER KIT



Woofer-Tweeter-Crossover

"Universal" speaker kit includes two Alnico V units—a 5½" woofer and 3" tweeter with electronic crossover network; chrome grille and baffle which fits regular 6x9" cut-out; 3-position plus pre-wired, pre-soldered, switch. Shpg. wt., 4 lbs. 32 H 2212 Net 5.95

SIT-RITE AUTO BACK REST



LOW PRICE

Cool and Comfortable Driving Pillows No Longer Needed

Scientifically designed to give drivers proper back support. Back-rest lessens the danger of back-ache and discomfort from poor driving posture which can lead to driver fatigue, a prime cause of accidents. Constructed with a spring steel frame covered structed with a spring steel frame covered with a sturdy washable woven fabric. Nylon for air circulation—no sticking to seats. cord lacing retains elasticity. Wide mesh Moves driver closer to pedals while eliminating the need for pillows. Fits all cars—no tool installation. Neutral beige to blend with any color. Shpg. wt., 3 lbs.

Net 5.37 Net 5.37 11 H 1801

Lafayette Cat. No. 651 83

LAFAYETTE ELECTRONIC TUNE-UP LAB

Compact, Self-Contained Units

Checks Dwell Angle, Points, Coils, Alternators, Generators, Regulators

Completely Portable Testers

Large, Easy-To-Read Meters


Accurate, Do-It-Yourself Engine Testing

Precise, compact hand-held testers with easy-to-read 21/2" meter receive compact naturated testers with long alligator clip leads. Complete instructions included. Overall dimensions approx. 4x2½x 11/2". COIL TESTER. Tests coils on or off engine. Also checks shorted condensers. Shpg. wt., 1.5 lbs. 11 H 5502

REGULATOR-GENERATOR TESTER. 0-8, 0-16 V. DC ranges for 6 & 12 volt systems with external 1/4 ohm resistor. Shpg. wt., 1.5 lbs. Net 10.88

TACHOMETER. Checks engine rpm, cylinder balance. 2 ranges: 0-1200 rpm, 0-1600 rpm. For 4, 6 and 8 cylinder cars. No jitter. Color coded scale. Shpg. wt., 1.5 lbs.

11 H 5504



OWELL METER. Accurately measures cam angle at all engine speeds. 2 scales. For 4, 6, 8 cylinder engines; 6 or 12 volt. Uses solid state circuitry, Shpg. wt., 1.5 lbs.

ALTERNATOR DIODE AND IGNITION WIRE TESTER. Tests diodes in and out of alternator. Checks windings and ignition wire. Simple to use. Shpg. wt., 1.5 lbs. 11 H 5506 Net 11.59

Complete Tune-up Lab plus case. Includes all 5 Testers.

11 H 5501 Shpg. wt., 8 lbs.

Net 62.50 11 H 5507 Case only. Shpg. wt., 1/2 lb. Net 3.95

Life

Lasts Your Car

TRANSISTORIZED ILLUMINATED **TACHOMETER**



4-6-8 cylinder, 6 or 12 Volt, Neg. or Pos. Ground!

Accurate 0-8,000 RPM Scale

Regular or Transistor Ignition Heavy Chrome Die Cast Case

360 Degree Mounting Adjustment

995 Here is the modern electronic

Here is the modern electronic guide to make your driving more efficient and more fun. Illuminated 3" dial face and electro magnetic meter movement, accurately measures engine speed from 0 to 8000 RPM. Helps reduce gas, oil bills, prevents over speeding and eliminates costly repairs due to improper engine operation. Factory calibrated, no adjustments required. Separate sending unit is a transistorized magnetic amplifier for constant accuracy; easy installation. Universal mounting for above, or below dash or steering column. For regular or transistorized, 6 or 12 volt and negative or positive ground ignition systems. Works with 4, 6 or 8 cylinder cars. Chrome tach head. With clamp. Shpg. Wt., 2 lbs. Works with 4, 1 Shpg. wt., 2 lbs. 11 H 4202

LAFAYETTE ELECTRONIC TRANSISTORIZED IGNITION SYSTEM



Heavy Duty Coil 400:1 Ratio Easily Installed

Incrases Engine Economy
 Pays For Itself
 Greatly Extends Point,

Spark Plug and Condenser

For The Life

6/12-Volt Negative

Ground System

routine replacement of this part unnecessary. More reliable winter starting—battery stays charged. Better coil reliability near-duty coil is designed to run cooler. Gas mileage stays high; timing stays adjusted between check-ups. Installation is accomplished without modifying the engine or vehicle wiring—your conventional ignition system easily restored when you trade your car in. Complete system includes heavy duty 15 amp transistor amplifier with wiring harness, coil resistor and low inductance coil with mounting bracket. Specially designed amplifier chassis gives max. heat dissipation, Shpg. wt., 31/2 ibs.

11 H 0102 6/12-Volt Neg. Gnd.

Point,

TRAVEL-MATE



• Arm Chair Comfort While Driving

Provides more storage space than any glove compartment—plus—the convenience of a multi-purpose arm rest and seat divider. Driver does not have to reach to a distant compartment, and fumble for gloves, maps, glasses, and many other items. Can be transferred from front seat to rear seat in a split second Portable—take it to use at the beach, hatal metal Wachable and scuff-proof with hotel, motel, Washable and scuff-proof with lined interior, 14"Lx7"Hx6"W, All grey color. Shgg, wt., 3 lbs.

Net 4 48

Lafayette HOT CAR-GO



Starts Your Car INSTANTLY

Starts Wet or Cold Motors Instantly Saves Battery and Gasoline • Installs Saves Battery and Gasoline Installs
Easily and Quickly 6 and 12 Volt Cars
Avoid excess wear and tear on your motor
and battery—install Lafayette's Hot Car-Go.
Provides 5 times the normal spark for fast
starting in any weather, and automatically
disconnects when engine is running. Will
not damage plugs or distributor. Simple to
install_instructions included Shop wit. install—instructions included. Shpg. wt., 1 Imported. 99 H 8511

2 WAY CHOKE CONVERSION KIT

Stops Costly Gas Waste and Engine Stalling

Converts Automatic Choke to Manual Control

Gives you finger tip control of your carbure-tor choke for faster starts, maximum gas savings. Dual choke never interferes with normal operation of your automatic choke. No carburetor adjustment necessary. Con-trol bracket screws easily to lip of dash panel. You'll get proper gas mixture, im-proved starting and gas mileage in any kind of weather. of weather. 11 H 2301 Net 1.79

ADJUSTABLE AUTO HEADREST

Fits Any Car Seat

Comfortable Foam Pillow Cushion

 Washable Zippered Cover Avoid auto fatigue with this adjustable headrest. Used by driver or passenger to relieve neck strain—ideal for long or short trips. Completely adjustable for any car or position. Comfortable foam pillow cushions with removable, washable zippered covers. Strong chrome frame fits any car seat. Hold-on-bars are Latex coated. 11 H 3301 Shpg. wt., 3 lbs.

AUTO-BOAT COMPASS

Mounts anywhere on cars-boats-trucks-Mounts anywhere on cats-boats-trucks-tractors-motor-cycles. Non-glare, universal mounting bracket. Most easily compen-sated compass available. Just a twist of the bottom or top knob. Large viewing window and figures for ease of reading. Includes mounting accessories and instructions. Illuminated model includes both 6 and 12-volt bulbs. Shpg. wt., 1 lb. includes

11 H 5801 Non-Illyminated 11 H 5802 Illuminated Model

Net 3.75

Lafayette Cat. No. 651

Take Advantage of Lafayette's Low Auto Accessory Prices

LAFAYETTE DWELL TACHOMETER

Tunes up electronically, any car ever made . Three Dwell Scales

Glant, Easy-to-Read Scale
 Use to Adjust Carburetors

• Giant, Easy-to-Read Scale • Use to Adjust Larouretors

A complete ready-to-use Dwell Meter and Tachometer which will operate on any car ever made. Tests cam Dwell angle and engine RPM on 4, 6 or 8 cylinder cars, 6 or 12 volt right on the engine. Giant, 6½ easy-to-read meter makes it simple for anyone to adjust points which are slightly worn or pitted. Adjusts caraburetors to insure maximum gas economy and quiet engine running. RPM readings are also essential to properly service automatic transmissions. Three dwell angle scales are provided: 0 to 45 degrees, 0-60 degrees, and 0 to 90 degrees. This instrument is suitable for dwell angle adjustment on all foreign and domestic cars. Dual range tachometer 0 to 1000 rpm for precise carburetor adjustments, 0 to 5000 rpm. suitable for making all other tests at high engine speeds.

Completely Wired-Not a Kit!

350

ELECTRO-DIP

Made in U.S.A.

DIPSTICK



AH-000-GAH! HORN

Chrome Plated Bell

A real joy for the sports car en-thusiast. An authentic meter driv-en horn approved as an exact reproduction in sound and appear-

ance by members of antique car, hot rod, and horseless carriage clubs the world over. Chrome plated bell with black wrinkle painted housing.

11 H 3001 6-Volt 11 H 3002 12-Volt Net 10.29 Net 10.29

PRIMETTA

FOR SAFER DRIVING:

- AT NIGHT
- IN RAIN IN SNOW

Net 28.50

IN FOG

NEWLY OEVELOPED OPTICAL FORMULATION



For Fast Cold Weather Starts

Designed to keep crankcase oil warm while your car is turned off for the night. Permits easier starts in cold weather and

faster engine warm-up. Uses about the same amount of electricity as a 100-watt light bulb. Costs only pennies a night to operate. Shpg. wt., 1½ lbs.



COLD-START BOOSTER-CHARGER

Our First Combination Battery Charger and Booster.

50 Amp Booster (6 volt) 25 Amp Booster (12 volt) 10 Amp Charger (6/12 v)

Perfect for starting 6V, 8V. 12V cars, Works as a booster as a charger. Supplied with heavy copper cables; thermal switch prevents overheating; works up to 200-ft. away from AC power source. Power output: 12V Boost, 25 amps maximum; 6V Boost, 50 amps max; 6/12V Charge, 10 amps tapering to 5 amps max. Power Inpot: 5 amps max. at 117V AC. cycles, Shpg. wt., 9½ lbs. H 4001 Net 23.95 11 H 4001



Night driving is safer and easier with Primetta Radar Night Glasses. Scientifically designed to protect the eye from the glare of headlights, street lights, etc. without materially reducing vision. Ideal while driving at night in the rain, fog and snow. The filter lens exclude all ultra violet rays. Designed for 20-20 vision. With heavy, suede-lined leather case. Shop. wt., 6 0z. Net 1.98 11 H 3201

11 H 7601

"Foggles," with case, for over existing glasses. Clip-on 11 H 3202

Net 1.50

AUTO SEAT BELTS



Positive Latching
 Exceeds SAE and GSA Standards

e Exceeds SAE and GSA Standards
Fig. (A) A new engineering concept in auto
seat belts, Side-lock, metal to metal buckle
mechanism for positive safe action. Simple
to unlock even if buckle turns over. Slide
lock and dual grip buckle are formed of aircraft steel—custom chromed with a gold
emblem Insert, A full 90" belt made of
quality, wrinkle-proof material, Pebble weave
webbing comes in 8 colors, Shpg. wt., 2 lbs.
Fig. (B) A quality helt designed of heavy webbing comes in 8 colors, Snpg. wt., 2 los. Fig. (8) A quality belt designed of heavy duty aircraft steel and triple stitched webbing Conventional flip buckle with positive latching and release. Don't let the price fool you, These belts exceed all state. SAE and GSA standards. 8 colors, All hardware provided, Shpg. wt., 2 lbs.

bronnes, amp		
Stock No.(A)	Color	Stock No.(B)
11 H 5701	Black	11 H 5709
11 H 5702	Grey	11 H 5710
11 H 5703	Beige	11 H 5711
11 H 5704	Flame Red	17 H 5712
11 H 5705	Maroon	11 H 5713
11 H 5706	Powder Blue	11 H 5714
11 H 5707	Royal Blue	11 H 5715
11 H 5708	Turquoise	11 H 5716
Net ea. 4.75		Net ea. 2.98

REVOLVING BEACON 685

- Rotates Like a Lighthouse Beacon Signals Help for Miles
- Mounts in
- Suction Saconds

A red warning light that rotates 360 degrees and flashes in all directions. Suction mount holds the beacon firmly in place. Signals for help for miles around; creates a safety zone during a traffic emergency. For use on autos, boats, trucks, docks, etc. For 12 volt use; complete with cigarette lighter adapter nius. Sing. wt. 2 lbs. plug. Shpg. wt., 2 lbs. Net 6.85 11 H 1304

AUTO SEAT BELT RETRACTORS



When Not in Use No Belts Caught in Ocors Keeps Seats Neat


Auto seat belt retractors fit any car Auto seat belt retractors fit any car seat belt — installs quickly on belts without removing them from car. Belts roll up automatically when not in use — cannot catch in doors. Lightweight, stainless steel and aluminum construction. Installs in seconds — no tools necessary. Shpg. wt., ½ lb. 11 H 2403 — Net pair 1.49

TWIN-DICATOR


- Warns cars left and right you wish to turn
- Simple to attach to existing electrical wiring

Chrome plated twin-dicators can be installed almost anyplace on the front fenders of your car. Gives drivers on both sides of you warn-ing of turns and eliminates turn indicator blind spots. Three feet of wire is supplied on each indicator to allow quick and easy installation. Units are also useful as fender guides. Shpg. wt., 1 lb. 11 H 4701

Pair 6.98



AUTOMOTIVE TOOLS AND ACCESSORIES



- 13 piece ½" Drive Socket Set 15 piece ¾" Drive Socket Set 17 piece ¾" Drive Socket Set

Professional quality tool kit. Rugged chrome alloy withstands tough use. Kit contains 15 pc. \(\frac{4}{6} \) drive socket set, 13 pc. \(\frac{1}{2} \) drive socket set, 13 pc. \(\frac{1}{2} \) drive socket set, 13 piece Hex Key Wrench set. Tubular Hack saw, 24 Hack saw blades (10"), 8 piece midget box and open end wrench set, 12 ignition point files, guaranteed to file any tungsten or platinum contact point, keeps ignition points clean for easy starting, ratchet sets each come packed in individual heavy gauge metal box with handle. Box wrenches less results and the sets are the sets and the sets are the sets and the sets are the s heavy gauge metal box with handle. Box wrenches also serve as

- Chrome Alloy Steel Sockets
- Over 100 carefully chosen pieces Steel carrying case with liftout tray

ignition wrench set. Entire kit comes packed in steel tool box (18x6x6¾") with lift out tote tray. Actually 7 different sets packed into one fabulous package. Not a toy kit, these are precision tools that will delight the most competent mechanic. A terrific value for homeowners, craftsmen, do-it-yourselfers, hobbyists etc. Shpg. wt., 23 lbs.

13 H 5554

NEW STEVENS WALDEN 13 Pc. 3/8" DRIVE SOCKET WRENCH SET

- Alloy Steel Seckets Round Head Ratchets Double Chrome Plated Over Nickel

These alloy steel socket wrenches are made in These alloy steel socket wrenches are made in USA for durable use. Chrome plated, professional tools, find thousands of applications in electrical work, autos, shop, household, boats and many others. Kit includes 1 combination spinner connector 36" sq. 1 reversible ratchet, 11/4" set screw key, 3" extension male, 8 sockets 46" to 11/46" sizes increase by 1/46" Will fit standard size parts. Round head design insures grip, ease of operation. Ratchet gives positive control over operation. Turns those wrist breaking jobs into simple tasks. Entire kit comes packed in rugged metal box that will hold sockets neatly. in rugged metal box that will hold sockets neatly. 13 H 5701 Shpg. wt., 3 lbs.



MAGNA-CLOCK with ALARM ONLY

- Pewerful Magnet in Base for Sure-Grip Attachment To Dash Clock Piveted to Swing to Any Position Even on A 80° Surface
- Accurate, Oependable ment with Alarm

A beautifully styled car clock with powerful magnet in the base for sure-grip attachment to any steel surface. Contour-molded plastic case has a convex glass front framed in a beveled, gold-finish metal band. All hands and numerals are luminous. Imported 30-hour movement with alarm is precision-made and is not affected by magnets the made and is not affected by magnet in the base. Easily removed and used whenever you

80. 0110100	01 3 1	LUIUIS.	subil. Mf.	42 ID.
11 H 2205	(Silve	r)		Not 4 95*
11 H 2206	(Blue)			Not 4.05
11 H 2207				
*Plus 10%	FFT	***** *****		Net 4.95"

FLARED "SCAVENGERS"

- · Handsome Styling
- . Mellow Threaty Tone



One piece scavenger pipes built of 18 ga. triple chrome plated steel, Gives your car that "custom" appearance. Designed like a musical instrument to produce a satisfying tone. 4" flared end fits all auto pipes up to 2" in diameter, 3 lengths to choose from. Comes complete with all hardware and lilustrated instructions.

10201000 11120	ractions.		
STOCK NO.	Length	Shpg. wt.	Net
11 H 3003 11 H 3004 11 H 3005	12" 24" 48"	11/2 21/2 5	2.95 4.50 5.80



Oiscennects Battery & Generator Circuits With A Single Switch

With the flip of a single lever protect cars, boats against fires resulting from shorts, battery run down due to appliances unknowingly left on, theft by ignition "jumping" (when mounted in concealed position). (when mounted in concealed position). ing" (when mounted in conceased position). Perfect for cars, boats, heavy equipment. All steel construction, operates on ball bearings for quick, easy operation and rapid reset. Fits 6 or 12 volts. Shpg. wt., 1 lb.

INVERT O-CHARGE



Combination Power Inverter and 8 **Battery Charger**

This dual purpose unit will operate 120 volt equipment from a 12 volt battery or charge a 12 volt battery from a 120 volt source! 175 watts cont., 225 watt intermittent operation; metered input and output; Push button solid state operation; Protective circuit breaker; Operates any AC device within its power limitations. Shpg. wt.. 10 lbs. 11 H 3701



Oefrosts, Oemists, Cools Plugs in Cigarette Lighter Harmless 6" Rubber Blades
 Choice of 6 or 12-volt Models

A practical automotive accessory which keeps windshield free from frost or fog while you drive. High speed 3,000 rpm motor controlled from drivers seat by 2 speed switch. Plugs into cigarette lighter socket for quick easy installation, no wires to attach. Complete with cord; universal swivel joint on sturdy base. Shpg. wt., 2½ lbs.

lbs. 11 H 3401 for 6 volt cars . 11 H 3402 for 12 volt cars


BATTERY CHARGER For both 6 and

12 volts UL Approved A professional type 6-12 volt battery

charger with automatic reset circuit breaker. Indicator light flashes on when circuit breaker trips. Front panel switch for change-over from 6 to 12 volts. Delivers a tapering charge starting at 3 amps for 6 or 12 volts. Noiseless, aircooled construction. Oversized components and vented case for troublefree operation. Oversized components and vented case for troublefree operation. Runs cool even under constant use. 6 ft. charging cables with heavy duty, 25 amp battery clips. Measures 4x6x31/4". For 105-125 volt, 50-60 cycle AC. Shpg. wt., 5 lbs.

1 H 2501





TANK TYPE ENGINE HEATER

Get Fast Summer Starts In Coldest Weather Saves Batteries—Gas—Oil


A thermostatically controlled heater which will solve your hard starting problems in cold weather, Circulates warm water through entire engine. Eliminates battery drain, carbon buildup and high gas consumption during starting and warmup. Easy to install, operates on ordinary AC house current. 850 watt capacity. 110-120 volt AC-DC element. Complete with all fittings except for heater hose. Shpg. wt., 21/2 lbs. 11 G 31D7

Net 9.29

LAFAYETTE ILLUMINATED AMMETER & OIL PRESSURE

GAUGES Complete with Cable and All

Fittings Keep a constant check on the condition and performance of your car's electrical and oil pressure systems. The ammeter calibrated in 60-0-60 scale meas-



11 H 8004 Tee Fitting

Test batteries under load by placing a 200 amp, shunt on battery during a 200 amp. sound on bactery during test. Eliminates guesswork of unloaded testing. 3-color dial reads bad-weak-good. Rugged moulded grip design fits all batteries. Indicates ability of battery to deliver power. Shop. wt., 1½ lbs. Net 4.79 11 H 1707



ELECTRONIC CRUISE CONTROL

Maintains Any Selected Highway Speed

Does Not Affect Braking or Instant Acceleration Increases Gas Mileage By Eliminating Wasteful Speed .

Helps You To Adhere To Posted Speed Limits Sets Fast Idle for Quick Cold-Weather Warm-Up



LAFAYETTE 2-TRANSISTOR ELECTRONIC IGNITION

11 H 5901

SYSTEM

EASY TO INSTALL

● FULL POWER AT HIGH RPM ● ELIMINATES POINT PITTING AND CONDENSER ● EASIER STARTING ESPECI-ALLY IN WINTER ● INCLUDES RELAY FOR HIGH CUR-RENT SWITCHING



This 2-transistor Ign. system will take the needless burden of high current off of your points and deliver a constant high power spark even at speeds exceeding 10,000 RPM. Modern 2-transistor circuit switches and controls the coil primary circuit through a combination amplifier-electronic switch action. Reduces point current to a low value and with proper use extends their life to the life of the car. Carries 100% primary current to a low-inductance design coil delivers their life to the life of the car. Carries 100% primary current to over 20,000 RPM. A special low-inductance design coil delivers constant full voltage at all speeds. Full high spark voltage to over 10,000 RPM. Spark plugs last longer due to complete burning of fuel. Condenser replacement and problems are eliminated because the circuit eliminates the condenser altogether. Switching relay relieves ignition switch drain and loss of power due to long wires. High gas mileage and low timing drift make use very efficient. Transistors are removable and unit is serviceable! System includes double insulated coil, epoxy potted amplifier, ballast, and relay. Shpg. wt., 5 lbs.

11 H 0103 For Negative Ground Systems. Net 24.95 POINT INSULATION KIT: adapts transistor Ign. kits to permit uses with positive ground systems.

with positive ground systems.
0104 Shpg. wt., 3 oz. uses Net 2.50 11 H 0104

INFRA-RED WINDSHIELD DEFROSTER



Cleans Front or Back Windshield in Seconds
 Plugs into Cigarette Lighter
 Suction Cups Mount to Windshield in Seconds

New infra-red electric windshield defroster utilizes the concept of penetrating infra-red instant heat to quickly melt away mist, ice, and snow. You no longer have to wait for car to warm up before cleaning windshield—just plug it into your cigarette lighter, and start defrosting windshield immediately. Complete with 12 foot cable for reaching back windshield. Two suction cups make mounting fast

and easy. Length: 15" Shpg. wt., 1 lb. 11 H 1307

.. Net 2.88



ROTATING "LIGHTHOUSE" BEACON

Rotates Like a Lighthouse Beacon Signals Help for Miles Around Giant Suc-tion Cup for Fast Mounting Battery Operated for Em-ergency Applications 18" Overall Height.

Red warning light rotates and flashes 360 degrees like

and flashes 360 degrees like
a lighthouse beacon. Bright
enough to signal help for
miles around. Creates a safety zone while
changing a flat tire or during a traffic
emergency. For use on autos, boats, trucks,
docks, etc. Suction cup will mount on any
smooth surface. Handy hooks for easy
carrying or hanging up. Powered by three
flashlight batteries. Shpg. wt., 3 lbs.
11 H 1401. Net 4.95 Net 4.95

11 H 1401 Batteries for above (3 required) Net ea. 32 H 4804

MUFFLER "BY-PASS" KIT




- Provides 2 Exhaust "Tones"
- Quiet For City
- Straight thru For Unrestricted Areas

A controlled muffler by-pass kit. Allows you to run with muffler connected for city driving. A dashboard mounted control permits muffler cut-out and straight through exhaust operation when driving in unrestricted areas. Open by-pass reduces back pressure and proopen us-pass reduces back pressure and provides improved efficiency and performance.
Unit complete with all hardware and dash control fittings. Simple to install Fits all cars & trucks with standard exhaust system.
Shgs. wt. 8 lbs.

Not 6 40 Shpg. wt. 11 H 3006





NEW HIGH GAIN ALL CHANNEL*LAFAYETTE VECTOR LOG EXCEPTIONALLY **EFFICIENT LOG-**

PERIODIC VEE DESIGN

Extremely High Gain and Front-to-**Back Ratio**

For Reception of Black and White or Color TV, FM and FM Multiplex


Great Selectivity and Sharpness in Any Location

Flat Response From Lowest to Highest TV Channel

Your choice of six Lafayette LVL models gives you the ideal antenna for your particular needs. Built to last longer and pre-assembled for fast, easy installation. Receives black and white or color TV and FM and FM Multiplex stations with outstanding clarity. Simply select the antenna that will cover your range (up to 175 miles).

1	18 H 0108	50 mile range, 4 elements. Shpg. wt., 4 lbs.	Net	8.79
1	18 H 0109	75 mile range, 6 elements. Shpg. wt., 6 lbs.	Net	12.91
1	18 K 0110	100 mile range, 8 elements. Shpg. wt., 8 lbs.	Net	17.61
1	18 H 0111	125 mile range, 11 elements, Shpg. wt., 11 lbs.	Net	23.45
1	18 H 0112	150 mile range, 15 elements. Shpg. wt., 13 lbs.	Net	29.37
1	18 H 0113	175 mile range, 18 elements. Shpg. wt., 16 lbs.	Net	35.25

FAMOUS COLOR 'TENNA



UP TO 125 MILES OF **POWER FRINGE** RECEPTION

- 19 Electrical Elements
- Engineered for Superior Color & Black and White Reception
- High Gain on All VHF Channels

Twin-driven elements work with carefully tuned, phased and spaced directors and reflectors to extend flat high gain response across entire VHF band. Cuts out ghosts and unwanted signals. Rugged reinforced aluminum elements and brackets stand up under most severe wind and ice loading. 100% pre-assembled for easy installation. Less mast, lead-in. Shpg. wt., 7 lbs.

18 H 0101WX Select a complete antenna installation kit from listing on facing

LAFAYETTE "SUPER HELIX" For Deep Fringe Areas Up To 150 Miles 26 Working Elements for **Extra Sensitivity** · "Goldenized"

Extra-high sensitivity for crisp, clear, snow-free picture in B/W or color, out in deep fringes. Triple-driven collector system combines straight and folded dipole sections into single co-active antenna for Yagl-quality performance. High front-to-back ratios of up to 22 db on low band and up to 28 db on high band screen out ghosts. Entire 1" square boom rigidized by two 1" tubular supports. Less mast and 300-ohm twin line. Shpg. wt., 10 lbs. 18 H 0126W

Net 17.95

FAMOUS SUPER COLOR 'TENNA

UP TO 150 MILES OF EXTRA POWER FRINGE RECEPTION

27 Electrical Elements

Inline Twin-Driver Yagi Design

Deep Fringe Gain on All VHF Channels

Completely Pre-assembled



Delivers the extra picture power needed for crisp, clear pictures in remote areas. Inline twin driven yagi design provides more gain and higher front-to-back ratio. Result: More TV stations, more picture power. Factory preassembled for snap-out assembly. Reinforced gold anodized aluminum construction. Less mast and twin lead. Shpg. wt., 10 lbs.

18 H 0103WX Select a complete antenna installation hit from listing on facing page.

MAXIMUM PERFORMANCE FRINGE ANTENNA

Range to 100 Miles

- 21 Active Elements
- Snap Open Oesign
- Fiberglas Insulators
- Compound Yagi Array GOLD ANODIZED



Field proven design for fringe reception. Gold anodized to combat corrosion. Compound yagi array to "suck-in" signals where other designs fail. "Tension-lok" hardware. Heavy wall tubing throughout. Less Mast. Shpg. wt., 81/2 lbs.

Select a complete antenna installation kit from listing on facing Dage.

TV-FM HI-PASS FILTER



Eliminates Interference in **Antenna Circuits**

HI-pass filter passes all frequencies above 40 mc. Rejects all frequencies below 40 mc. Automatically eliminates electrical disturbances in the antenna circuit. Clears disturbances caused by neon, X-Ray, ignition, appliances, diathermy, short wave, etc. Shgs. wt., 1 lb. Imported.

99 H 4008

LIFELINE COPPERWELD TWIN LEAD

Guarantee: If this deluxe 300 ohm line fails Guarantee: If this deluxe 300 ohm line tails to last the life of your antenna we will replace it at no charge, 20 Gauge Copperweld (steel clad copper) conductors with finest brown polyethylene insulation, Chemically protected against deterioration, Special "waste free" dispenser package, Shg. wt., 344 lbs, Minimum length 100 ft. Net 1 98

34 H 4613 100 ft. package 34 H 4614 K Bulk per ft.

(over 100 ft.) Net .018



Net 11.88

TRI-SET COUPLER

Highly efficient 3 set coupler. For coupling 2 or 3 TV or FM sets to one antenna of any type. No interaction—less than 60 db insertion loss. 40 to 50 db rejection ratio. Shpg. wt., 1 lb. Imported. 99 H 4010

See Our Catalog 650 For Antenna Installation Accessories

ALL CHANNEL'S "RIVIERA" WORLD'S MOST POWERFUL ULTRA-FRINGE VHF-UHF-FM ANTENNA



Guaranteed 200 Mile VHF Reception or Your Money Back

Broadband UHF-VHF and FM, motorless all direction reception

Receives channel 2-83 from all directions without a rotor

All aluminum flip-out assembly

Field tests reception on VHF of up to 200 miles has made possible this unprecedented guarantee. This most powerful ultrafringe antenna may be used for receiving TV channels 2-83 and the FM broadcast frequencies. Perfect for application where color TV or The multiplex signals are extremely weak due to distance from transmitting antenna and to other receiving conditions. Here is an antenna with only one transmission line and to other receiving conditions. Here is an antenna with only one transmission line for all UHF, VHF, and FM stations in all directions within a 200 mile radius without he use of a motorized rotator. The nine position selector switch conveniently connected at the set electronically rotates the antenna beam pattern instantly without physically moving the antenna. Superb gain on channels 2-6 comparable to stacked 10-element single channel yagis; on channels 14-83 comparable to bow-tie reflector. 16½" doweled aluminum elements are 60 inches long. Complete with switch, coupler, 45" stacking bars and 2-7½" angle type most insulators for Polymicalene line listed below. Shop, wt. 10 lbs

below. Shog. wt., 10 lbs.

18 H 1201WX Less Mast
"U-Install-It" kit: Includes Riviera antenna, chimney mount, two five ft. masts, 100
ft. of Polymicalene 4-conductor lead-in wire, 8 stand off insulators and complete

18 H 1202WX Shog, wt., 16 lbs.

Net 27.32



High gain antenna design for the audiophile who seeks perfection in FM reception. Extra elements on this antenna serve to pull in sta tions where others fail. Trouble free operation even under severe weather conditions. The fully automatic snap-lock brackets insure easy, rapid and secure installation. Net ea 5.95 18 H 0149WX Shpg, wt., 3 lbs.

LAFAYETTE ALL-CHANNEL UHF CONVERTER



Makes Your TV Set a Modern 82-Channel Receiver

For Use with Any VHF Set Easy to Install -Easier to

Operate Vernier Tuning

The compact Lafayette low-noise UHF converter will add all UHF channels 14-83 to channel 5 or 6 of your present TV set. Precise tuning with dual-knob Vernier selector. UHF OFF knob for instant selection of UHF or VHF reception. UHF signal light. Maximum signal power with precise 300-ohm input and output impedance. Highly styled, durable metal cabinet. Overall size: 8Wx4Hx41/2"D. For 110-120 wills 60 cms 4C. Shop wh 6 like 120 voits, 60 cps AC. Shpg. wt., 6 lbs. Net 15.95 18 H 0145

ECONOMY UHF ANTENNA

Highest Gain on 70 UHF Channels

 Completely Preassembled
Four bay, UHF bowtie antenna. Exceptionally high (12db) gain — relatively flat across relatively flat across
 . Fully factory assembled. Quickest and easiest to install. Rugged—rigid—corrosion resistant construction. Shpg. wt., 5 lbs. entire spectrum

wt., 5 lbs. 18 H 0142WX

Net 4.50



LAFAYETTE "MULTIPLEX 10" EXTENDED RANGE FM ANTENNA



Ideally suited to Multiplex FM reception. This 10-element, doubledriven, yagi array has the necessary added gain, sensitivity and directivity to compensate for the lack of signal strength, All-aluminum gold anodized construction, Fiberglas insulators, Torsion lock hardware, sure-lock mast clamp, Shpg. wt., 7 lbs. Net 9.88 18 H 0128WX

SPECIAL TV-FM COUPLER **3**87 No Signal Loss

Splits TV and FM signals frequency-wise and without loss to either signal from a common antenna. Gives complete isolation between TV and FM sets. Equipped with 'No-Strip' serrated washers, Indoor mounting on baseboard, in attic or basement; bracket supplied for outdoor mounting to antenna mast. Shpg. wt., 1/4 lb.

Net 3.87 18 H 0141

LAFAYETTE TRANSISTORIZED 4-SET TV/FM BOOSTER

Amplifies Signals for Top Reception on Up to 4 Sets

Easy to Connect and **Economical to Operate**

Can Be Mounted in any

Location, in any Position



Screw-on terminals make wire connections easy. Transistor circuit runs cool, draws little current. Signal strength is boosted 3 to 5 times. Will operate up to 4 TV and or FM sets on the same antenna. Input impedance is matched to antenna impedance. Isolated outputs insure maximum separation. Mount in any convenient lecation where adequate ventilation is provided. Size 43/4Wx11/4Hx31/2"D. For 117 volts, 60 cps AC. Shpg. wt., 1 lb, Imported

Not 14 98 99 H 4011

Net 14.98

"U-INSTALL-IT" KITS

All the items for simple installation. Your choice of an all angle roof mount or chimney mount—lightning arrestor—75 feet of 300 ohm twin lead—screw eyes—mast stand offs and 5 ft. 1¼ 0.D. steel mast. Shpg. wt., 7 lbs.

Net 2.95 18 H 0118W With roof mount With 2-5 ft. masts. Shpg. wt., 10 lbs. Same as 18 H 0118W with chimney mount Same as 18 H 0106W with chimney mount Net 3.55 **18 H 0106W** 18 H 0119W Net 3.25 18 H 0127W Net 3.85 18 H 0120WM Same as 18 H 0118W with aluminum wall bracket 18 H 0121WM Same as 18 H 0106W with aluminum wall bracket Net 2.95

Lafavette Cat. No. 651

Net

Telephones For Intercoms and Private Phone Systems



Designed for real utility in the home and in business. Powerful, solid state circuitry transmits your voice over amazingly long ranges. No current drain between transmission due to separate ranges. No current drain between transmission due to separate push buttons for transmit and receive. Handy location of push buttons facilitate ease of hand-held operation. May be used wherever private telephone communications are desired, Ideal for applications for the home—between rooms, upstairs and downstairs, kitchen, workshop, etc. For industry between offices and warehouse, receptionist and offices, or for interdepartmental needs, etc. Beautifully finished in grey to match any decor. Shpg. wt., 1½ lbs. Imported. Requires 2 batteries listed below. 99 H 9079 Set of two 99 H 9080 Singly 32 H 4802 Battery for above, 2 req. 32 H 3002 Additional 100 ft. roll of 2-cond. wire Net ea. 10.95 Net ea.

DIAL PHONE

Have your own Private Intercom

For Intercoms, Extensions, **Private Systems**

Popular, modern dial phone. Can be used to make complete private systems. Equipment taken from service, reconditioned and ready to work.
Simple 3-wire hook-up. Complete
with handset, dial, bell, induction
coil and connecting cable. General appearance may vary slightly from catalog illustration. Shpg. wt., 8 lbs. 44 H 1801 Net 6.95



30 FT. TELEPHONE EXTENSION CORD

Ideal Extension Cord for Your Telephone Intercom

Use with Dial Phone and Cradle Phone Listed


Add flexibility to your telephone intercom. Now be able to move your telephone intercom from room to room. 30 feet of telephone extension cord with standard 4-pin plug and jack. Color-coded cord to match screw terminals on plug and socket. Imported. 99 H 4540 Extra Phone Jack

Combination male & female telephone plug & phone jack only 100-Ft. 2-Cond. twisted pair—unshielded telephone wire



- Amplifies Telephone To Room Volume 4 Transistors + Varistor
- No Dangling Wires, Pickups To Connect No Warm-Up, Instant Operation

LAFAYETTE TELEPHONE AMPLIFIER



2¼" PM Speaker Several People Can Listen In on Conversation Simultaneously

Battery Operated

An efficient battery operated telephone amplifier which can be applied to and used with any type of telephone. Amplifies incoming voice and projects it through a 2¼" PM speaker. Suction cup on pickup coil attaches easily to telephone and makes permanent installation unnecessary. Volume control (with on-off switch) permits adjustment of volume to appropriate level for up to several people to listen in on conversation at the same time. 4-transistor amplifier is powered by inexpensive, long-lasting 9-volt battery (supplied). Unit is housed in a two-tone ivory and grey high-impact plastic case measuring 3%, wx3.5%hx2%, "D. Shpg. wt., I lb. Imported.

99 H 9085

99 H 6021 Replacement 9V Battery

TELEPHONE OPERATORS HEADSET



Net 1.95

Ideal for Hobbyists, Marine Radio-Telephone Operators, Hams, etc. Leaves Both Hands Free for Operation of Equipment

Headset is lightweight and manufactured to the most exacting standards. All Parts are interchangeable. The Headset consists of the body (Oycoloc), ear and mouthpiece, adjustable headband, for proper fit and maximum comfort, receiver unit, transmitter unit, cord and plug. Shpg. wt., 1 lb. 44 H 6001 Net 19.95

WESTERN ELECTRIC HANDSET with 3-Conductor Coiled Cord



Dependable, rugged Western Electric F-1 Handset. Has countless valuable applica-tions for intercom, private phone, etc. Reconditioned for fool-proof service. Com-

See Our Catalog 650 For Additional Intercoms

TIMERS - PHOTO ELECTRIC RELAY - OUTDOOR LAMPS

INTERMATIC TIMERS A401-4 A211-4

- **Automatically Turns Lights On-**-Discourages Burglars Operates Electrical Appliances with Loads Up To 1875 Watts As Easy To Set As A Clock

13 H 2715

MODEL A211-4 TIME-ALL

Makes practically everything electrical completely automatic. Will handle up to 1875 watts, Turns radio on and off—does not have to be reset each night. Defrosts refrigerator—turns lights on and off
—controls roaster, washing machine, vaporizers, etc. 30 min. minimum on time—23 hours maximum. Easy-to-read 24 hour "day and
night" dial. Operates day after day without attention. Can be controlled manually without automatic reset. For 110 volt 60 cycle AC only. Size: 5x4x21/2". Shpg. wt., 2 lbs.

Net 8.64

MODEL A221-4 TIME-ALL. Similar to A211 except has capacity of 875 watts. Shpg. wt., 2 lbs. 13 H 2716

MODEL A401-4 CLOCK TIMER

Not only tells time, but turns appliances both on and off automatically for periods of 15 minutes to 5½ hours. No installation problem—just plug it in and set. Capacity 1875 watts. 434Wx4½Hx problem—just plug it in and set. Capacity 18/3 watts. 974 11372 21/4"D. For 110V 60 cycle AC. Shpg. wt., 3 lbs. Price includes 13 H 2717

EXTENSION CORD



- Automatic Time Switch & Extension Cord + 3-Way Outlet
- Controls up to 3 Appliances at Same Time
- Reduces Electric Bills

A 3-way combination for every home—an automatic time switch, extension cord, convenient outlet. 0-4 hour time cycle. Easy to operate—plug it into any wall outlet, connect one, two or three devices to be controlled, and turn the knob to the time period desired. At the end of this time period, the electricity is turned off automatically. 6-foot cord. Shpg. wt., 1 lb. two or three



Decorate your lawn with automatic flood lighting. Goes on or off according to natural outdoor light available and is preset to your choice. External switch leg provides instantaneous control of a light cluster (with 1000 watts max. combined). Medium base porcelain socket, cast aluminum housing with heat dissipating fins. Weatherproof. Jointed stem with std. ½" threaded pipe. 6%, LX 2%, WK6%, "D. For 105-130V 50/60 cycles AC. Shpg. Wt., 1 lb. 13 H 2727

YARD 'N PATIO LIGHTER


Photo Electric Lamp Turns On or Off Automatically

A complete photoelectric lamp system, to provide automatic lighting when you want it in your yard or patio. Control unit is completely weather protected. External switch leg provides ir stantaneous control of other lights up to 650 watts combined, includes: 5td. ½" aluminum pipe 13" long, mounting bracket and photo control. Overall length 22" (with reflector), 14" wide (with reflector). For 105-130V 50/60 cycles AC.

Net 12 75

13 H 2728 Shpg. wt., 4 lbs.

LAFAYETTE PHOTO ELECTRONIC RELAY SYSTEM Includes Photo Cell Receiver Plus Electronically Operated Relay Plus Exciter Lamp . . . Efficient



Complete—Ready to Operate—NOT A KIT! Operates Bells, Buzzers and Counters

The Perfect "Guard" for Homes, Stores and Industry Removable Infra-Red Filter For "Invisible-Light" Operation

The Lafayette Photo-Electronic Relay is your key to an inexpensive indoor warning or counting system. Operating on 110-120V AC. R can be used to signal persons entering a room, counting people or merchandise or function as an effective alarm system to warn of intruders. Effective up to 48 feet (without filter, 18 to 20 feet with filter, relay unit has a convenient variable sensitivity control and switch for intermittent alarm operation. Metal case. Size: 41/4Hx3Wx41/2"D. Imported. Net 18.95 99 H 9082 Shpg. wt., 6 lbs.

ACCESSORIES FOR ABOVE

99 H 9023 Electric Bell, 110V AC. Shpg. wt., 2 oz. Net 1.49 99 H 9024 Electric Buzzer, 110V AC. Shpg. wt., 10 oz. Net 1.29 99 H 9011 6-Digit Electric Counter. Shpg. wt., 142 lbs... Net 9.95



1/10 SECOND TIMER

Designed for close timing. Large hand registers 1/10 of a second, up to 30 seconds; small hand reads minutes, up to 15. Start, stop, and continue from crown; Instant zero. 1 Jewel movement. Chromium plated case. Shpg. wt., 8 oz. Imported.

Net 6.90 13 H 3102L

Same as 13 H 3102 (above) except 7 jewels. 13 H 3103L Net 9.33

1/5 SECOND TIMER

Second hand registers 1/5 of a second and completes turn in 60 seconds. Small hand indicates up to 30 minutes. Side slide starts and stops hands. Fast resetting dependable 7-jewel movement. Shpg. wt., 8 oz. Imported.

Same as 13 H 3104 (above) except 1 jewel. 13 H 3105L Net 7.49

APPLIANCE MINDER

Adds Space—Convenience Versatility

Wall or Panel Mounting



Add new space to the new or remodeled kitchen . . . more time for the harried housewife. Simply plug in the coffee-maker, rotisserie, electric frying pan, etc. . . . set the timer up to 12 hours ahead . . . let the appliance minder do the rest. Easily installed in a 4-gang wall box—or surface mounted. Contains two timed outlets (one turns "on," the other turns "off") and two regular outlets. Allows advance planning of meals—go out and return home hours later to a cooked meal. Rated at 15 amps—125 voits AC. UL inspected. Shpg. vt., 1½ bs.

Net 10.99 13 H 8511

FAMOUS LAFAYETTE INTERCOMS

LAFAYETTE 2-STATION TRANSISTORIZED INTERCOM





995 2 UNITS COMPLETE

• Inter-Unit Tone Calling • Beautifully Styled • Battery Operated • Simple Plug-in Connecting cord • Push-Button Operation

A beautifully styled, miniature 2-station intercom that is fully transistorized and operates from one inexpensive 9-volt battery. The system consists of one master and one remote with 66 feet of lightweight interconnecting cord. Plug at each end of cord lets you hook-up system fast — no tools or wiring connection required. Master unit has power on/off/volume control and listen-talk to the master without has push-button for calling only — you can listen or talk to the master without operating any buttons. Master and remote can call each other even when master is switched off — pressing any of the push buttons signals the person at the other end by means of a tone. Each unit is housed in a high-impact plastic case and supplied complete with interconnecting cord and 9-volt battery. Dimensions (each unit): 3Wx134Hx4°D. Shgp. Wt., 1½ lbs. Imported.

Net 9.95

99 H 4526 2-Station Transistorized Intercom
99 H 6021 Extra 9-volt battery
AC power supply and battery charger for above.
44 H 3001 Shpg, wt., 2 lbs.

Net 3.20

LAFAYETTE TRANSISTORIZED INTERCOM SYSTEM

Instant Communications—No Warmup, Heat
 or Hum
 All Push-Button System
 2-Wire Distribution System
 Remote Tone Call & Signal Light
 Can Use up to 3 Remotes

Deluxe intercom system that combines smart styling with high quality performance. All interstation calling is accomplished by handy, functional push-buttons. Remote unit may initiate call by simply depressing "call" switch. Upon doing this, an audio tone is heard at the master unit and also a light appears, showing which remote unit is calling. Master may even be in the "off" position for this function! Master unit has its own volume control with "on-off" switch. No switch is necessary on the remote. Easy hook-up is facilitated by the use of 2-conductor hook-up wire. Comes complete with master control unit, 1-remote unit, batteries and 30 feet of 2 conductor connecting wire. Imported.

Net 19.95

99 H 4531 Net 19.95
Remote stations for above. Imported.
99 H 4542 Net ea. 4.95
Door remote for above. Imported.
99 H 4529 4.95
REPLACEMENT BATTERY
32 H 4801 1½-Volt Battery (4 required) Net ea. 13
32 H 3032 Additional Wire, 100 ft. coil Net .94



Deluxe LAFAYETTE WIRELESS INTERCOM

Lafayette G

2-Station Wireless Intercom System

3250 2 UNITS COMPLETE

Operates from any 117V AC/DC Outlet No Wires to Connect Ideal for Home or Office Add as Many Extra Stations as Desired

Lafayette offers a high quality 2-station wireless intercom. Handsomely styled, these units offer quality performance for home or business use. Each unit features a 3-position bar-control lever: Dictate (for use as "baby sitter," lengthy talking). Talk (has spring return to Listen position), and Listen. No wires to connect—simply plug into any 117V AC/DC outlet. Front panel volume control and pilot light; adjustable squelch control at rear reduces interference during quiet periods. Dependable 3" speaker. Add as many remotes as needed. Shpg. wt., 10 lbs. Imported.

99 H 4547M 2-Station System Net 32.50 Extra Station. Shpg. wt., 5 lbs. Imported.

Take Advantage of Lafayette's Low Intercom Prices

AYETTE RADIO ELECTRO

ILL

IND.

KANS

MAINE

MD.

ATLANTA

COLUMBUS 2611 Lumpkin Rd.

stone Ave.

PEORIA

RANTOUL

512 W. Peachtree N.W.

IDAHO FALLS IDAHO

421 S. Century Blvd. SPRINGFIELD

1363 N. Yellow-

706 Wayne St.

1413 S. 11 St.

INDIANAPOLIS

SIOUX CITY 500 W. 7th St.

MIDWAY 125 E. Main

LEWISTON

NEW ORLEANS 2231 Banks St.

464 Main St.

BALTIMORE

BROCKTON

SPRINGELLID 527 Belmont Ave.

WORCESTER

23 Foster St. ANN ARBOR MICH. 3382 Washtenaw Ave.

BAY CITY 408 E. Midland St.

1326 Broadway

GRAND RAPIDS 7 Burton St., S.E.

IRONWOOD 114 S. Lowell St.

KALAMAZOO

519 Mills St.

315 Hamilton Ave. DETROIT

1115 So. Dort H'way.

BIRMINGHAM

FLINT

BEL-AIR 139 Thomas St. SALISBURY

AYER

131 Lisbon Street ROCKLAND

2014 N. Charles St.

819 Priscilla St.

YER MASS. 45 Groton-Harvard Rd.

Westgate Shoppers Park, Rtes, 27 & 24

4730 E. 10 St.

OVERLAND PARK

7202 W. 79 St. SALINA

314 West Cloud WICHITA 220 W. Harry St. MADISONVILLE

2408 South Main St.

FORT WAYNE II 3101 N. Clinton St.

"ASSOCIATE STORE" DEALER LOCATIONS

Lafayette Radio Electronics "Associate Store" Dealers own and operate their own stores as independent franchised dealers. They establish their own terms and prices, which may vary slightly and do not handle mail orders.

BIRMINGHAM ALA. 9 North 77 St.
FLORENCE
at Shoals Creek HUNTSVILLE
2112 Memorial Pkwy So.
MOBILE 174 So. Ann St.
PHOENIX ARIZONA 4225 N. 7th Ave.
6345 E. B'way
N. LITTLE ROCK ARK. 1920 Pike Ave.
BAKERSFIELD CALIF. 626 Bernard St.
BUENA PARK 6186 Beach Blvd.
CULVER CITY 8553 Washington Blvd.
FRESNO 4510 E. Belmont
SAN CLEMENTE
220-B So. Ola Vista Rd. SAN DIEGO
472 3rd Ave. & Island SAN FRANCISCO
271 9th St. SUNNYVALE 942 W. El Camino Real
VAN NUYS
13630 Sherman Way BRIDGEPORT CONN.
2710 Fairfield Ave. GROTON
565 Long Hill Road
HAMDEN 913 Dixwell Ave.
WATERBURY 386 W. Main St.
NEW CASTLE DEL. 1420 Dupont Blvd. Wilmington Manor
FT. LAUDERDALE FLA.
□ H'way.
GAINESVILLE 101 S. E. 1st St.
JACKSONVILLE 1905 Hendricks Ave.
LAKE WORTH 213 N. Dixie H'way N. MIAMI BEACH
346 NE 16/ 31.
ORLANDO 1225 No. Mills St.
ORLANDO 1225 No. Mills St. PENSACOLA 727 N. Warrington Rd. ST. PETERSBURG
TALLAHASSEE 505 W. Gaines St.
3328 Henderson Bl.
VERO BEACH

nices.	witten	шау	vary	Sitgi
LAN	SING		MI	CH.
POR	T HUI	olme:	s Rd.	
MIN	03 24t NEAP 15 Sou	OLIS	MII	NN.
BILC				SS.
HAT	TIESE 06 Hai	URG		
TUP				
ST.	LOUIS 31 Har	;	Ave.	10.
GRE 21	AT F	ALLS	MQ outh	NT.
OMA			N	EB.
22	REMC 2 Wasi	hingto	30 O.C	H.
	opping ER			
			ve.	
M	Main edical	Hall E	31dg.	
40	NCHE: Bridg	e St.		
Rt	EM e. 28 a URY F	t H'w	ay 9	3 N.J.
11	09 H'V	vay N	0. 35	Ť
50	57 Rte			
Ma	opping	Aanor	ter,	
TRE	NTON Brunsv rcle E			
ALB	UQUE	ROU	E	
	017 Ce	r entral		
79	ANY Centr FALO		e. <u>r</u>	<u>'.Y.</u>
74	7 Maii DEN	ı St.		١
14	W. M	ain St		
POL	3 East	EPS		
10 BOC	5 Duto	hess:	Tpke	
SCH	2 W. A	TAD	Y	
SYR	ACUS	E		
UTI	740 Eri CA			
VES	TAI.	and (1)		
25 Fa	i3 Vest ist	al Pk	-	
WE:	LLSVII	LLE lain S	t.	
	3.		_	

EUGENE 62 W. B'way MEDFORD 1080 S. Riverside PORTLAND 4001 N. Interstate Ave. 131-26 S.E. Powell AKRON 127 No. 7th St. ALLENTOWN 20 N. 7th St. BURNHAM 622 Freedom Ave. DREXEL HILL Rte. 1 and State St. DUNCANSVILLE Main St. ERIE 24th & French St. HARRISBURG 1507-09 North 3rd Street PHILADELPHIA 2546 Cottman Ave. PITTSBURGH 640 Grant St. WILKES-BARRE 115 No. Main St. MILWAUKEE 1840 W. Atkinson AV U.S. POSSESSIONS SAN JUAN U.S. POSSESSIONS SAN JUAN PUERTO RIC The Texas Bidg. 654 Ponce De Leon, Hato Re	and do not nandle mail	orders.
DREXEL HILL Rte. 1 and State St. DUNCANSVILLE Main St. ERIE 24th & French St. HARRISBURG 1507-09 North 3rd Street PHILADELPHIA 2546 Cottman Ave. PITTSBURGH 640 Grant St. WILKES-BARRE 115 No. Main St. WEST V. 809 N. Queen St. WHEELING 1217 Chapline St. GREEN BAY WIS 412 Dousman St. KENOSHA 620-58th St. MILWAUKEE 1840 W. Atkinson AV U.S. POSSESSIONS SAN JUAN PUERTO RIC The Texas Bidg. 654 Ponce De Leon, Hato Re	CHARLOTTE NO. CAR. 1310 N. Independence Blvd. FAYETTEVILLE 2733 Bragg Blvd. MORGANTON 407 So. Sterling St. AKRON 34 North Main CANTON 300 Walnut St. CINCINNATI 606 Walnut St. CLEVELAND 2001 Euclid Ave. COLUMBUS 122 E. Long St. LOGAN 31 E. Main St. PROSPECT Highway 318 SPRINGFIELD 217 N. Belmont STEUBENVILLE 411 Washington St. STRONGSVILLE 14484 Pearl Rd. TOLEDO 5429 Detroit St. ZANESVILLE 925 Linden Ave. OKLAHOMA CITY 3837 N.W. 10 St. EUGENE 62 W. B'way MEDFORD 1080 S. Riverside PORTLAND 4001 N. Interstate Ave. 131-26 S.E. Powell AKRON 217 No. 7th St. ALLENTOWN 20 N. 7th St. BURNHAM	601 W. Market St. PROVIDENCE R. 1023 Chalkstone Ave. COLUMBIA SO. CAI 948 Harden St. GREENVILLE 2109 Augusta Rd. CHATTANOGA TENN 3748 Ringgold Rd. MEMPHIS 1057 N. Watkins St. OAK RIDGE 39 E. Tenn. Ave. AUSTIN 4101 Interregional Hwy. EL PASO 4317 Dyer St. FT. WORTH 3510 "A" Section— E. Lancaster St. HOUSTON 8601 Long Pt. Rd. 6315 So. Park Blvd. LAREDO 1910 San Bernardo LUBBOCK 1722 Ave. H SAN ANTONIO 5090 Blanco Rd. SALT LAKE CITY 147 E. Sixth South— BLACKSBURG Christiansburg Rd. HAMPTON 802 W. Mercury Blvd LYNCHBURG 1624 Park Ave. RICHMOND 3012 W. Broad St. BELLEVUE WASI 10845 N.E. 8 Ave. SEATTLE 1210 First Ave. SPOKANE 5315 N. Market St. TACOMA 8805 Bridgeport Way
127 No. 7th St. ALLENTOWN 20 N. 7th St. BURNHAM 622 Freedom Ave. DREXEL HILL Rte. 1 and State St. DUNCANSVILLE Main St. ERIE 24th & French St. HARRISBURG 1507-09 North 3rd Street PHILADELPHIA 2546 Cottman Ave. PITTSBURGH 640 Grant St. WILKES-BARRE 115 No. Main St. SPOKANE 5315 N. Market St. TACOMA 8805 Bridgeport Way MARTINSBURG 1217 Chapline St. GREEN BAY WIS 412 Dousman St. KENOSHA 620-58th St. MILWAUKEE 1840 W. Atkinson AV U.S. POSSESSIONS SAN JUAN PUERTO RIC The Texas Bidg. 654 Ponce De Leon, Hato Re	14484 Pearl Rd. TOLEDO 5429 Detroit St. ZANESVILLE 925 Linden Ave. OKLAHOMA CITY 3837 N.W. 10 St. EUGENE 62 W. B'way MEDFORD 1080 S. Riverside PORTLAND 4001 N. Interstate Ave. 131-26 S.E. Powell	1722 Ave. H SAN ANTONIO 5090 Blanco Rd. SALT LAKE CITY UTA 147 E. Sixth South BLACKSBURG V/ Christiansburg Rd. HAMPTON 802 W. Mercury Blvd LYNCHBURG 1624 Park Ave. RICHMOND 3012 W. Broad St. BELLEVUE WASI 10845 N.E. 8 Ave. SEATTLE
	127 No. 7th St. ALLENTOWN 20 N. 7th St. BURNHAM 622 Freedom Ave. DREXEL HILL Rte. 1 and State St. DUNCANSVILLE Main St. ERIE 24th & French St. HARRISBURG 1507-09 North 3rd Street PHILADELPHIA 2546 Cottman Ave. PITTSBURGH 640 Grant St. WILKES-BARRE	SPOKANE 5315 N. Market St. TACOMA 8805 Bridgeport Way MARTINSBURG WEST V. 809 N. Queen St. WHEELING 1217 Chapline St. GREEN BAY WIS- 412 Dousman St. KENOSHA 620-58th St. MILW AUKEE 1840 W. Atkinson AV U.S. POSSESSIONS SAN JUAN PUERTO RIC The Texas Bldg. 654 Ponce De Leon,
	e to Own	A Nature

Market St. ENCE R.I. haikstone Ave. BIA SO. CAR. III.E ugusta Rd. NOOGA TENN. inggold Rd. . Watkins St. OGE enn. Ave. nterregional over St. RTH Sectioncaster St. NΓ Long Pt. Rd. So. Park Blvd. an Bernardo K ve. H TONIO llanco Rd. AKE CITY UTAH Sixth South BURG ansburg Rd. ON Mercury Blvd BURG Park Ave. ONC W. Broad St. WASH. N.E. 8 Ave. irst Ave. N. Market St. Bridgeport Way NSBURG WEST VA Queen St. ING Chapline St. BAY WISC. ousman St. 8th St. UKEE V. Atkinson Ave. SSESSIONS AN PUERTO RICO

Would You Like to Own A LECTRONICS "ASSOCIATE STORE"?

EXCLUSIVE FRANCHISES NOW AVAILABLE

Basic Requirements Include:

862 20th Place

- 1. Knowledge of Retailing, or of Radio, Television or Electronics
- 2. Financial Investment of \$10,000 to \$30,000

If you have the basic requirements, and would like complete details without obligation, write for full Information to:

Mr. Robert Laub Lafayette Radio Electronics Corp. Dept. AS-651 111 Jericho Turnpike Syosset, L. I., N. Y. 11791

72 PIECE "POWER SHOP" 3/8" DRILL KIT



A Complete Workshop For Do-It-Yourself Jobs

Drill, Sand, Grinds, Buffs, Saws

Home, Garage, Shop

ONI Y

A complete electric power workshop at Lafayette's typically low price. You can do almost every at-home job with this versatile 72-piece set. Look at what you get: Powerful 3.0 amp. 36" electric drill; 6-pc. power boring set with bits from 36" to 1"; 14-pc. twist drill set with metal index; 29-pc. sanding and polishing set; 7-pc. grind and buff set; 9-pc. 7-size hole saw; 7-pc. countersink and drill saw set; 3-pc. power screwdriver attachment. The 36" drill has 3.0 amp, 110 VAC motor. No-load speed, 1750 rpm; full load speed, 1150 rpm; Special alloy bearings throughout. U.L. approved. Shpg. wt., 10 lbs.

13 N 9005

Net 19.95



NEW RAM ROUTER

13 H 7108

1/4" Cutting Tool Chuck

1/4" Cutting Tool Chuck
Uses Standard Router Bits
20,000 R.P.M.

Light weight for ease in handling. Designed to provide Light weight for ease in handling. Designed to provide heavy duty performance for a variety of woodworking jobs. Rout, Groove, Mortise, Dado, Dovetail, Babbet, and Jointing cuts. Ideal for decorative cuts. Features threaded base with positive lever-locking depth of cut adjustment; veneer cutting guide and wrench included. 1/4" chuck uses standard router bits, 20,000 RPM cutting speed, 1/4 HP 115 volt AC-DC, 3-conductor, 6 ft. cord. Height: 8". Shpg. wt., 5 lbs.

Selection of 4 Most Often Used Router Bits.

4 Piece Router Bit Set. 13 H 7113 Shpg. wt., 1 lb.

RAM "FURY" 1/4" DRILL



SPEEDWAY 41/2" BENCH

GRINDER Die-Cast Aluminum Housing

Ideal for sharpening all workshop, hobby and garden tools—drill bits, planes, knives, chisels, hoes, etc. Base equipped with rubber feet: drilled for bolting to bench or truck. Heavy-duty steel wheel guards; adjustable tool rests; built-in front water cooling tray; castin top parts tray; rear duct exhaust. Bronze alloy bearings. Two 4½x½" wheels (one 40-grit, one 70-grit). 23 amp. 115V, 60-cycle AC motor; no-load speed 3450 rpm. 6-ft. 3-wire cord. Shpg. wt., 10 lbs. 13 H 5309 Less eyeshields Net 14.99

Lafayette's top drill value. ¼" geared chuck drill rated at a full 2.0 amps. U/L approved. ¼" capacity in steel, ½" capacity in steel, ½" capacity in hardwood. 1200 rpm speed under full load, 2000 rpm no load speed. Precision anti-friction bearings. Automatic trigger switch. Specially designed gear train for maximum torque transfer. Dverall length 8". For 115 volts, 25-60 cps AC. Shpg. wt., 13 H 7101

Net 7.88

SPEEDWAY ORBITAL POWER SANDER



Motor-driven power sander for home and shop use. Ideal for rough or finish sanding. Lightweight and easy to handle, it produces perfect finishes every time. Uses 2-pole induction-type burnout-proof motor rated at 1.8 amps. No-load speed is 3450 rpm; push-button witch Special allows of silicons. button switch. Special alloy self-oiling bronze bearings; tefion coated thrust washer and ball bearing on sander drive plate. Sanding area 4½x5½°. Sturdy cast aluminum alloy housings with attractive metallic finish and black crackle trim. 6-ft. 3-wire cord. For 115 volts 60 cne AC coly. Show the 50 cne AC coly. 115 volts, 60 cps AC only. Shpg. wt., 6 lbs.

13 H 5304 Net 11.28 13 H 5305 Lambswool Polishing Pad Net 13 H 5306 18 Sheets Assorted Sandpaper Net

RAM "FURY" 7" HEAVY-**DUTY POWER SAW**



7-Inch Combination Blade

Universal 11/2 hp Motor

Safety Retracting Handle

Heavy Duty 3 Conductor Cord Approved by UL and CSA

A powerful 8 ampere motor provides this big 7" circular saw plenty of reserve power to zip through straight or angle cuts. Cuts vertically to 2½" at 90°, to 2½" at 45°. Features self-lubricating bronze bearings, floating blade guard, safety retracting handle, combination rip and cross-cut blade and 3-wire cord and plug. No load speed, 5000 rpm. Motor is a universal 1½ bp AC-DC 115 volts. UL Approved. Shpg. wt., 15 lbs. 13 H 7103

13 H 7103 Net 19.88 SAW TABLE. Perfect complement to the above Saw. Allows cutting at any angle between 45° and 90°. Complete with miter gauge and rip fence. Shpg. wt., 12 lbs.

13 H 7104 Saw table

UNIVERSAL DRILL PRESS STAND



Adjustable Depth Step

Spring Return Tension Adjustable Cradle Adjustable Depth

Can be used for any ½/4"
pistol grip electric drill.
Features rack and pinion
gear feed, and adjustable
depth stage. 15 to 1 leverage. Drill press
head is ctamped in rigid position. 2½/4"
stroke. Square base is provided with slots
for drill bit and for bolting work to base.
Other features include spring return tension,
fast hand-action, head clamps and adjustable
depth gauge dial. Shpg. wt., 6 lbs.
Net 10.44

14 H 3604

Lafayette Cat. No. 651

See Our Catolog 650 For Workshop Tools and Accessories


54-PIECE SUPER DUTY 3/8" DRILL KIT

• Super Powered 3.0 Amp. 3/8" Drill with Multiple Ball Thrust Bearing, Jacobs Chuck & Key, Micro-Machined Gears, Gleaming Mirror finish

Drill and Practical Accessories Selected for Power and Performance

Everything You Need to Make the TOUGH Jobs EASY

A drill kit deliberately designed to make the tough jobs easy. Big 3.0 amp 36" drill packed with power to spare when you need it! A husky right angle gear drive—can halve or double drill speed! Increase torque or speed to suit your needs. A powerful 12-piece, screw and nut driver set with screw driver bits, Phillips head bit, eight sockets for hex and square nuts and bolts, powerful non-slip clutch. 36" flexible shaft for all your intricate drilling grinding buffing or hobby ible shaft for all your intricate drilling, grinding, buffing or hobby work. 5-pc. Carbide drill set for boring concrete, masonry, t-le, plastic from $\frac{1}{4}$ " to $\frac{1}{2}$ " to $\frac{1}{2}$ " do $\frac{1}{2}$ " do $\frac{1}{2}$ " by 64th in a metal index. All the really needed tools left out of most drill kits. Shpg. wt., 12 lbs.



THOR-SPEEDWAY 3/2" DRILL



"Thermeweld" 3-Amp Motor-that Won't Burn Out!

Get the balance and feel of a ¼" drill— with the power and work capacity of a husky 4sth. Industrially rated to handle really rugged work. Special bronze alloy bearings. rugged work. Special bronze alloy bearings. Precision-geared chuck and key. Noload speed 1750 rpm, full-load about 1150 rpm. Locking trigger switch. Cast aluminum alloy housing. 6-ft. 3-wire cord and plug. UL and CSA approved. 115V., 25-60 cps AC. Shpg. wt., 5 lbs.



PS-120 COMPACT DOUBLE **DUTY NUTDRIVER SET**

convertible set which does compact, more jobs with fewer tools. Special piggy-back "torque amplifier" handle slips over

PS7 DOUBLE DUTY TOOL SET

Complete with remarkable ''piggyback'' torque amplifier. Enclosed in a sturdy, see-through plastic case for easy size identifithrough plastic case for easy size identification. Nut-drivers: hex openings: ¼" and ¼". Screwdrivers, blade sizes: ¾" ¼", ½", #0 Philips, and #1 Philips. Alt tools are 3½" in length. Shpg. wt. ½ lb. 13 H 4622. Net 3.15

SPEEDWAY THOR JIG SAW

 With 3 Assorted **Wood and Metal Cutting Blades**

Enjoy new Jersatility sawing curves, scrolls, straight and rip cuts "THERMOWELD" 3-amp motor cuts 2" in wood, 1/6" in steel. Adjustable plate permits accurate angle cutting to 45° on either side—cuts 2x4's at 45°. Noload speed 3000 strokes per minute; AC/DC positive push-through switch; self-oiling bronze bearings. Auxiliary knob handle; rip guide. Base tilts to 45°. 6-ft., 3-wire cord. Standard 115V. Shpg. wt., 5 lbs.

2 DRAWER TOOL CHEST



- Large-Each Drawer 21/2" Deep Folding Panel Locks Whole Box

A perfect two-drawer chest for the home A perfect (Wo-drawer class for the other craftsman, Sturdy unit features two 2½" deep full size drawers and a top storage area. Completely lockable—folding front panel with tumbler lock firmly secures case. Rust resistant baked enamel finish will endure years of rough punishment. A good start in organizing your own workshop. Finish is Chor-Gray with nickel plated carrying handles on each end of case. Shpg. wt., 12 lbs.

Net 8.90 14 H 8801

GRINDING & POLISHING HEAD

Equipped with double tool rests. Has DuPont equipped with goung tool rests, has burght nylon bearings that insure quiet, smooth running and require little or no lubrication. 2" Pully-universal, for "Y" and round belt. Shaft—36" dia. x 936" long—32-20 thread. 63/2" overall height. Shpg. wt., 7 lbs.

14 H 7602 Net 3.85

VARI-SPEED



Continuous Regulation of Lights & Motors Regulates Speed of Power Tools

Full range solid state speed control with built in automatic circuit breaker. Allows continuous varying speed from max. RPM to min. Also controls light intensity. Fingertip speed control for power tools, home appli-ances and lighting. Handles up to 900 watts. Can be mounted permanently or remain portable. 3 wire receptacle and 6 ft. 3 wire power cord provides maximum safety. Shpg. 12 H 1301

Net 9.95



Power By Any 1/4" Electric Drill Cuts Up To 3" Steel Bars

Driven by any standard 1/4" electric drill. Driven by any standard ¼" electric drill. Can be fastened to bench or attached to a board for portable use. Saws up to 3" steel shafting, pipes, angle irons, etc. constructed of steel with bearing materials at all points of wear. Has built-in vise to hold work. Uses standard 10" blades, works unattended, and produces clean cuts, and will never overload drill motor.

14 H 1401 Shng. wt. 9 lbs. Net 18.95 Net 18.95 14 H 1401 Shpg. wt., 9 lbs.

Lafayette Cat. No. 651 95

SKIL 514 DELUXE JIG SAW with 24 Blades and Case





Lightweight and powerful with true orbital blade action for top cutting speed and efficiency. Exclusive "roller-follower" behind blade supports it to minimize wear and breakage. Powerful motor, rugged helical gears allow wood cuts to 2", soft (non-ferrous) metals up to ½", mild steel to ½". Automatic blower keeps sawdust off line of cut. Has contour grip for greater cutting accuracy. For 115V AC/DC, 2.3 amps. With 24 blades, 3-wire cord, plug, and 2 prong adapter in carrying case. Overall length 8". Shg. wt., 6 lbs. Shpg. wt., 6 lbs. 13 H 6918

Net 22.90

MODEL W-300L REVERSE-O-MATIC



TAPPING

DRILLING NUT ORIVING

REVERSIBLE SCREWDRIVER INCREASES TORQUE

Can be fitted to any electric drill or drill press quickly and easily. Heavy duty industrial type for instant 11 to 1 speed reductrial type for instant 11 to 1 speed reduction. Develops high torque when more power is required for oversize drilling. Easy stop-start action with hand clutch control. Accessories include yankee type — ¾," standard bit — ¾," phillips bit — socket adaptor—adaptable for ½" chuck plus a ¾" female adaptor to fit drill chuck onto unit. Shpg. wt., 1½ lbs.

Net 9 50 14 H 7901

SKIL VARIABLE SPEED DRILLS

Regulate Speed From 0 to 2000 RPM

With Your Trigger Finger No Olais - No Buttons - No Rheostats! Absolute Trigger Speed Centrol

EXCH HEIVE The revolutionary Skil TSC 1/4 inch drill gives you

13 H 6901 Shpg. wt., 4 ibs. Model 569 TSC %" Drill 13 H 6917 Shpg. wt., 4½ ibs. Model 545 TSC ½" Drill 13 H 6919 Shpg. wt., 5 ibs.

Net 33.95 Net 36.50

SKIL RECIPRO SAW With Utility Case And 8 Blades Cuts anything from Thinnest Plastic Sheeting to 6" Logs Exclusive 3-Position Foot—Flush, Stationary, Rocking

Exclusive 4-Position Blade

\$5 monthly



NEW CHASSIS PUNCH SET

Easy-smooth holes in sheet metal
5 sizes: ½", ¾", ¾", 1", 1½"

Five most often needed round hole punches Easily cuts smooth accurate holes for sockets, plugs, controls, panel lights, switches, terminals, and most radio parts. Drive with any wrench or with included T-handle. Punch sizes included are ½", 5%", ¾", 1", 1½". Complete with punches, dies, T drive handle, tapered reamer, fitted case, and instructions. Shgs. wt., 2½ ibs. Imported.

99 H 8024 Net 5.49. Lots of 3 ea. ... 4.94

Net 9.50 NEW RIVET-ALL RIVET KIT





A professional tool which joins virtually anything, metal to metal, plastic to wood, fabric to fabric. Easy to operate, just insert rivet into tool, place in pre-drilled hole and squeeze gun and you have a strong rivet joint. KLIK rivets are strong, neat and permanent. Ideal for Hobbyists, Electronics, Household and Auto repairs. Kit includes Riveter, supply of rivets of various sizes. Extra rivets available at low cost. Shop. wt., 2 lbs.

Net 4.49

13 H 5402 25 Rivets for Work to 1/5" Thick 13 H 5403 20 Rivets for Work to 1/4" Thick 13 H 5404 20 Rivets for Work to 1/2" Thick 13 H 5405 50 Back-up (Reinforcing) Plates Net 4.49 Net .44 Net .44 Net Lafayette Cat. No. 6S1



Net 25.48

A precision tool designed especially for home use. Just dial letters, numbers, symbols—squeeze the embossing handle—pull the cut-off trigger and that's it. Embossing wheel has 44 characters. Prints a crisp white message on durable moisture-resistant tape. Made of heavy duty plastic. Size 6461567M. Shog. wt. 2 lbs. 61/2Lx6"H. Shpg. wt., 2 lbs.

14 H 4101 Embossing tape Magazine for Model M-4. Each contains 144" of 1/4" glossy vinyl tape with adhesive backing. Shpg. wt., 1/4 lb. Net ea..98

14 H 4102 Blue 14 H 4103 Green 14 H 4104 Red 14 H 4105 Clear 14 H 4106 Brown 14 H 4107 Black 14 H 4130 Orange 14 H 4131 Yellow 14 H 4132 Gold

Cloth Printer Kit. Provides a clean, fast and easy way to mark all clothing when used with your Dymo Home Labelmaker. Use directly on clothing or use the iron-on label provided. Shpg. wt., 1/2 lb. Net 4.75

14 H 4109 72 Assort. Iron-On Tapes for above

Take Advantage of Lafayette's Low Tool Prices

TODIS FOR LAB, INDUSTRY AND WORKSHOP



SPECIFICATIONS: Complete 10-in-one machine shop small enough to use on a radio serviceman's bench. Designed as a multi-functional power tool. Converts from horizontal lathe to vertical drill press. The changeover causes no wear or loss of accuracy in precision fit parts. The motor-headstock detaches for use as a portable hand drill, power grinder or buffer. Extra attachments available include a very accurate circular saw, saber and jig saw, flexible shaft, lathe bed power feed, threading attachment, precision collets and cutting tools. Belt drive provides 11 speeds ranging from 900 to 7,200 RPM. Motor can also be controlled by rheostat foot switch or SCR power supply.

Includes 1/10 HP Brush Type fan cooled motor, drill press arm, column and hand lever, face plate, lathe dog, grindstone arbor, tool post, 2 dead centers, 3 jaw universal lathe chuck with reversing jaws, ¼4" Jacobs chuck and key, Allen wrench roughing tool bit, and a spindle return spring, 17½x10½x5¾4" wood chest. 40-page manual. For 115V AC/DC operation, imported.

ATTACHMENTS & ACCESSORIES Model DB 1210 Milling Table. Steel, 5x3" with 2 sets of

Clamps.

14 H 1002 Shpg. wt., 3 lbs.

Net 10.50

Model DB 1010 Clamping Vise. Reach of jaws: 1½".

Mounts on cross slide on Milling table.

14 H 1003 Shpg. wt., 1½ lbs.

Model DB 1130 Teel Kit. Consists of 2 tool bits, 4 drill

bits, grindstone w/cup, single-end cutting key seal cutter, counter sink bit, center drill bit and 2 wood chisels. 14 H 1004 Shpg. wt., 1½ lbs. Model DB 1100 set of 6 tool bits.

Model DB 1100 Set of 6 60 bits. Net 9.50
Model DB 1290 Power Feed Attachment. 1:50 reduction, feed rate of .0008" per revolution.
14 H 1006 Shpg. wt., 7 lbs. Net 19.95
Model DB 1001a 4-Jaw Independent Lathe Chuck.

Capacity 21/4". 14 H 1007 Shpg. wt., 1¼ lbs. Net 22.50 2½" Circular Saw Attachment. 3½x4" table, rip fence, arbor. Max. depth of cut 1/2".

Model DB 1230 Saw. Shpg. wt., 21/2 lbs. Net 9.75 14 H 1008 Model DB 1231 Blade (wood), Shpg. wt., 3 oz.

Net 1.50 14 H 1009 Model DB 1232 Blade (metal). Shpg. wt., 3 oz.

Medel DB 1070 Jig Saw Attachments. Cuts to center of 16° circle. With 12 assorted blades.

14 H 1011 Shpg. wt., 6½ lbs. Net 19.50

Net 19.50



STEEL FRAME WORK BENCH

Includes Tool Rack, Peg Board Back Panel and **Bottom Shelf**

Sturdy, All-Steel Frame Large 24x48" Work Top

13 H 3504WX Shpg. wt., 60 lbs.

A Complete and Serviceable Work Shop

new all-steel frame work bench that is the ultimate A new all-steel frame work bench that is the ultimate in convenience and serviceability. The rigid, all-steel frame is the core of this complete workshop that will last for years. Features a big 24x48" work top of special, heavy-duty, compressed, high-impact board to withstand the roughest use. Matching bottom shelf offers handy storage space. Convenient tool rack with peg board back panel. Base on each leg gives extra support and can be bolted down if desired. Easy-to-assemble. 34½" high. (Tools not included).

x-acto KNIFE CHEST

Handy knife chest comes complete with X-Acto nos. 1, 2, and 5 knives plus 9 assorted extra blades. Chest has a natural wood finish. Shpg. wt., 1 lb. 13 H 7416

x-acto

WOOD CARVING SET



13 H 7421



Professional Quality Throughout All the most often needed tools Oesigned with the Technician in

Each component tool chosen to offer utility and quality. The "ULTRA" kit contains the following: 61/2" insulated side cutters, 5" ronowing: 0-y2 insulated side cutters, 5" insulated chrome plated diagonals, 6" insulated chrome plated long nose, 30-watt soldering iron. 3 offset open-end wrenches covering from ¼" to ½", 5" chrome plated tweezers, shockproof amberoid chuck handle, corea withing hale. tweezers, snockproor amberoid chuck handle, \$\frac{\pmax}{2}\$ screw driver blade, \$\frac{\pmax}{2}\$ screwdriver blade, punch-awl blades, \$\frac{\pmax}{2}\$ recessed screwdriver blade, punch-awl blades, \$\frac{\pmax}{2}\$ with a driver blade, solder and flux. Pliers insulated for 10,000 voits, hand honed cutting edges. Side cutters have beveled nose, diagonals have provisions for wire stripping, long nose has "wrench" grip jaws and cutters. The entire set is nested in a zippered, filted, lined book type carrying case with handle, Measures a scant ing case with handle. Measures a 9x5x2". Shpg. wt., 2½ lbs. Imported. scant

AUTOMATIC SOLDERING Feeds Solder Automatically IRON

Easy, One-Hand Operation Lightweight and Ourable



Features automatic feeding of solder—gives you a "3rd hand." Tip AND solder are placed at exact spot needed. Any required quantity of solder can be automatically fed to the soldering tip by adjusting the feed roller. Tip is made of special alloy for longer service life. Use with standard solder or with special spool listed below, Rated at 30 watts. Operates on 117 volts AC. Shpg. wt., 2 lbs. Imported. 2 lbs. Imported.

99 H B062 99 H 8063 Extra Tip for above

x-acto All purpose POCKET

KNIFE

Net

Extremely handy and completely safe pocket knife. When not in use, blade slides into handle to facilitate easy withdrawal and positive cutting action. Shpg. wt., 4 oz.

Comes in useful vizi-dome container that lets you see where your tools are. 6 gauge blades, 4 regular blades, 2-3 inch blades, No. 5 knife handle (takes all blades). Shpg. wt., 1/2 lb.

x-actoModel Customizing Kit



Basic Tools

... Net 4.95

The customizing kit contains the "basic six" tools needed by indoor auto model enthusiasts who custom build their own racing cars. Contains a #5 knife, razor saw, hand drill, pliers, tweezers, 2 files and a #1 knife. Shpg. wt., ½ lb.

VALUE — Power Tools — **VARIETY**

NEW! Wen 950 Multi-Speed 1/2" Reversible Drill

 Multiple speeds From 340 to 2400 RPM . Powerful 6 Amp., 1/2 HP Burnout-Proof Motor . Double Reduction Gears for Super Torque • UL Industrially



A versatile heavy duty ½" drill to handle big jobs — where great power is required. Quick, easy two-lever control of electronic and gear

reduction speed changes permit efficient use of drill for any type of material or size of hole. All 4 speeds are reversible too with extra safety uouble switch. 6 amp. ½-horsepower motor, 120V AC/DC, 6 ft. 3-wire cord. UL and CSA approved. Size: 11x 8½x3½" (LHW). Die Cast aluminum housing, balanced for construction procession. Shop wit 0.100 per construction of the construction of th tinuous operation. Shpg. wt., 9 lbs. 13 H 6533

NEW! WEN MODEL 450 ALL GUN

THREE HEAT RANGES FROM 25 TO 450 WATTS

 ATR—Automatic Thermal Regulation Gives Controlled Heat Power

Long Reach—Long Life—Heavy Duty Lightweight—Perfect Balance


From Smallest Detail Soldering Jobs to Large Soldering Jobs with ONE Soldering Gun. Through of a superconducting wire in the this new approach to soldering gun design makes possible

heat ranges simply by changing tips — a 2 second operation

ihpg. wt.,	3 lbs. With heavy-duty tip only.		
3 H 6519	Mari	t ea.	9.29
3 H 03ZZ	23-100 Watt tip assembly	Mad	0.0
3 H 0323	AUU-ZUU WAII IIN ASSAMNIV	BJ 4	0.4
3 H 6525	200-450 watt tip assembly Plastic cutter attachment	Net	.91
3 H 6526	Flat Iron Attachment	Net	.42
		HEL	.42

WEN 'SOUPED UP' SABRE SAW MODEL 909





Super-long blade easily cuts through 6x6" lumber. Cuts 4x4" at a 45° angle! Power enough to cut steel plate up to ½" thick—iron pipe up to 2" in diameter. Saw tilts 45°—sole plate always remains flat. Air stream blows dust from line of cut. Includes seven blades for cutting wood—steel—hardboard
— sheet metal — pipe — leather — rubber
— formica, etc. Equipped with rip guide
and circle cutter guide. 8 ft. 3 cond cord
and adapter. 110 watts. 6 amp., AC-DC.
8LX/WX/1/2"H. Shpg. wt., 81/4 lbs. Net 29.37

WEN ELECTRIC HAND PLANE MODEL 930



Souped-up 1.2 H.P. Burnout-Proof Motor • Balanced, Lightweight Polished Aluminum Housing • Industrially Rated for Heavy-Duty Use

Built for years of precision work. Separately adjustable twin cutters; welded burn-out-proof armature; finger control trigger switch. Cutter speed 14,500 R.P.M. Mitre guide plate angle adjusts up to 45°. Guide plate is removable for surface planing. Cutting width 246°; depth adjustable to 1/4." Polished width 24%; depth adjustable to K_6^{**} . Polished aluminum housing with air stream chip ejector. Shoe length 16". 3-wire 8-ft. cord. 13 H 6503 Shpg. wt., 9 lbs. Net each 29.37

WEN 3-INCH BELT SANDER MODEL 910

 Extra-Duty 41/4 Amp Motor Forced Ventilation — Cools Motor and Removes Dust • Compact

Lightweight Ralanced



Provides 850 square feet of abrasive material/minute. Universal self-cooling motor will not overheat. Contour grip, 2 position knob, vibration-free bearings, balancing and lightweight remove fatigue from sanding. Belt changing in seconds. Flush design for close work. Complete gear drive with sealed bearings. Die cast polished aluminum housing. With 3 belts (coarse, medium. fine) and 6 ft. 3 conductor cord. Size: 534/k351/2WX 101/2/"L. For 115 V AC. Shpg. wt., 83/4 lbs. 13 H 6504

WELLER 8200PK EXPERT" SOLDERING KIT



Just the thing for the novice or proplastic utility case can be used to hold other parts or tools. Weller

plastic utility case can be used to noid other parts or tools. Wellet Expert Soldering Kit features the 8200 gun with exclusive tip Grip which assures constant heat. Dual heat feature gives choice of 100 or 140 watts with the pull of the trigger. Accessories include 3 durable soldering tips, tip changing wrench nylon flux brush, soldering aid, and all purpose solder. 13 H 3915 Shpg. wt., 334 lbs.

Net ea. 5.90

WELLER D550PK HEAVY-DUTY SOLDERING KIT

A Professional Heavy Duty soldering
Kit featuring the dual-heat 240/325
watt Weller gun. Everything needed
for hundreds of applications in Hobbies, Shopwork, Household repairs.
ing Tip, Smoothing Tip, Tip Changing Wrench and Instruction Booklet.
Entire kit is enclosed in a high impact plastic case with carrying
handle.

13 H 3918 Shpg. wt., 5 lbs.

Net ea. 8.59

PLASTIC UTILITY CABINETS



LOW AS

Handy, extra strong, one-piece high-impact styrene plastic small parts cabinet.

Stock No. No. of Drawers 13 H 7613 13 H 7614 13 H 7615 Lafayette Cat. No. 651

Drawer Size: 53/4x21/4x11/4".

21/2 lbs.

Shpg. wt. Net 41/2 lbs. 31/2 lbs. 3.99

2.99

1.99

DRAWER PORTABLE LOCKING CABINET 499

> 12 Compact Drawers: 11/4x23/4x53/4" 1 Jumbo Drawer: 21/2×83/4×53/4"

Hinged Door with Lock Clasp. Keyhole slots provided for

hanging. Locking, hinged door provides protection from dust, moisture and theft.

Stock No. 13 H 7621

No. of Cabinet Model Drawers H W 18PA 13

n Ea. 9" 10" 61/2" 53/4 4.99

Net

Tools are Available on Easy Pay Plan-See Center Insert A

EXPERIMENTERS — HOBBYISTS—STUDENTS



SPECTROLINE UV PHILATELITE

IDENTIFY TAGGED STAMPS

A UL approved hand held lightweight lamp of sufficient output of short waves to clearly identify tagged U.S. and foreign stamps. Ground and polished short wave filter provides a narrow band menochromatic light source. Life of bulb is 6000 hours. Convenient on and off switch. Operates on 110V. AC. A 16 page booklet "An introduction to Ultra Violet Fluorescence." 15 H 4511 Shpg. wt., 2 lbs.

SPECTROLINE DUO PHILATELITE

This remarkable unit provides two high-output tubes-one short wave and one long wave—with ballasts and switches permitting in-dependent operation. Long tube life, swivel desk stand, and handle are provided for convenient operation. An informational booklet on Fluorescence is included. Shpg. wt., 4 lbs.

MAGNA-SIGHTER® 3-D BINOCULAR **MAGNIFIER**

- **Leaves Hands Free**
- Reduces Eyestrain
- 3-Dimensional!

A precision optical instrument enabling anyone to do very close work and see it clearly in 3 dimensions. Adjusts to any head size comfortably. No moving parts to replace. Ideal for hobbyists, repairmen, inspectors and technicians. Available in 4 sizes. Shpg. wt., 34 lb.

III3PCCLUIS	allo tee	THE COURSE OF	1110016 111	 Ab.		,
15 H 2001	1.75X, 1	4" Working	Distance	 		7.88
15 H 2002	2.25X, 1	O" Working	Distance			7.88
15 H 2003		8" Working				
15 H 2004	3.5X,	4" Working	Distance		. Net	9.38

PORTABLE ILLUMINATED MAGNIFIER

- EXTREMELY BRIGHT FIELD
- **5X MAGNIFICATION**
- COMPOUND LENS TYPE



A fixed-focus illuminated magnifier—magnifies work 5 times. Field of vision is 2" at 11%" working distance. Magnified area easily accessible through cut out. Invaluable in stamp or coin collecting, photography, entymology—minerology, etc. Excellent map reader. Completely portable—uses two No. 2 cells for power. Weight ¾ lb. Length 8½" overall. Shpg. wt., 1½ lbs. imported

32 H 4804 Battery (2 required)

Net 2.95 Net ea. .13

31/2" STAND MAGNIFIER



Allows free use of both hands-ideal for close tolerance work by engravers, watchmakers, etc. The crystal-clear cross cylinder, magnifying lens rotates a full 360°. The large, colorless, 3½x134" lens mounts in a chromed

STUDENT FOSSIL TEKNIKIT

• Fossils Date Back 475 Million Years

A collection of fossils dating back to the Ordovician era. An ideal collection for Earth-Science students. Contains twenty, one-inch selected specimens of fossil re-mains of invertebrates and plants from seven or more geologic periods. Neatly dis-played, fully identified. An informative handbook is included. Shpg. wt., 1 lb. 15 H 4503



TEKNIKIT VOL.1 MINERAL



- 48 Carefully Selected Specimens
- Named Classified. and Tagged
- Removable for Study

Forty-eight specimens, pre-selected to Il-lustrate cleavage hardness, color, luster, specific gravity, crystal form, etc. Con-tains specimens of ore, organics, fossils, elements, plutonics, oxides, volcanics, hypa-byssals, effusive crystals, common and un-common minerals. Each specimen is tagged and removable from its correspondingly ged and named compartment. Specimens are named as well as classified. An excellent introduction to rock and mineral identification. Handy reference for the advanced "rock hound." Especially useful in the study of mineralogy, petrology, geology, and physio-graphy. Shpg. wt., 1 lb. imported 99 H 7155 Net 2.95

MINERAL TEKNIKIT

VOL. II 48 Additional Specimens

No Two Alike!

Many Uncommon Minerals

Volume II of Lafayette's popular Mineral 'Teknikit.'' Includes specimens of Carbonates, Tantaline, Phosphates, Gemstones, as well as additional Plutonics, Volcanics, Sulphides, Metamorphics, Silicides, Oxides and many others. Specimens are tagged and in marked compartments. The entire collection is indexed for type and classification. Shpg. wt., 1 lb. Imported

99 H 7156 Net 2.95 Special Combination. Buy both volumes and save. You get all 96 specimens. Shpg. wt.,

2 lbs 99 H 7157 Net 4.70

FOSSIL SPECIMENS



• Every Specimen Authenticated • Fessils up to 550 Millien Years Old


A museum study-collection series of genuine fossil specimens up to 550 million years old. Each specimen is packaged with an authentic color reproduction of the fossil as it lived. Factual information and collecting hints included, can open a new world of nature for inquiring minds. wt., per set, 4 oz. SET A. Miocene Shark Teeth, Trilobite and Petrified Wood speci-

mens. B. Dinosaur Bone, SET Sea Urchins and Micro-Fossils specimens.

Set A 15 H 4501 Set B 15 H 4502

Shpg. Net 1.35 Net 1.35

STUDENT RESEARCH Teknikits



- Specially Chosen Specimens Ideal For Nature Students
- Professionally Prepared

Carefully prepared insect and shell speci-mens, chosen for their importance in nature study. Attractively boxed with scientific descriptions. Average shog, wt., ½ lb. per set. Imported

Each set listed below

99 H 7142-4 Swallowtail Butterflies 99 H 7143-6 Pierids 99 H 7144-6 Danaids, Satyrs & Lycaenids 99 H 7145--6 Four-Footed Butterflies 8 Skippers
99 H 7148—Beetles (Sm.) Set of 6
99 H 7147—4 Giant Silkworm Moths
99 H 7148—6 Dragonfiles & Cicadas
99 H 7149—Beetles (Lg.) Set of 6
99 H 7150—Moths Set of 6

99 H 7150—Motifs Set of 6 99 H 7151—Shells (Vol. 1) Set of 25 99 H 7152—Shells (Vol. 2) Set of 12 99 H 7153—Shells (Vol. 3) Set of 11 99 H 7154—Shells (Vol. 4) Set of 12

Lafayette Engine Divided Slide Rules

NEW! LAFAYETTE® VECTORLOGTM SLIDE



The Slide Rule for Communications Engineers and Physicists

SCALE • COMPLETE WITH BELT CARRYING LOOP AND LEATMER CASE
The Lafayette VECTORLOG Slide Rule provides a new concept in scientific calculation, incorporating scales and arrangement designed for quick-easy-manipulation. Twenty-seven (27) scales incorporate the many problems encountered in Electrical Engineering and Physics. The unique P. P', and Q scales allow direct right angle vector addition. No longer are several settings required to obtain right angle vector sums—these scales work in the same manner as the C and O for multiplication. The two Hyperbolic Sine and one Hyperbolic Tangent Scale, the voltage db scale, and the five Log Log scales, provide maximum coverage of these dymanic fields. VECTORLOG is the result of extensive tests for ease of manipulation. Several of these features are: C and O scales on both the front and back of the rule; Sine scales in both degrees and radians, removing the necessity of bothersome conversion of units; A problem-tested location of scales; and adjustment screws to allow variable tension on the slide. Scales include: (FRONT) Tr-1, TR-2, P', P, Q, ST, S-7, S-0, C, O, LIO1, LIO2, LIO3, LII'; (REAR) Sh-1, Sh-2, OF, A, B, CI, CF, Th, C, O, LI3, LI2, db. With instruction book, leather carrying case, and belt carrying loop. Imported
99 H 7102 Shpg. Wt., 1½ lbs.

DELUXE LOG LOG DUPLI DECIMAL

DELUXE LOG LOG DUPLI DECIMAL TRIGONOMETRIC SLIDE RULE




- 25 Scales with 8 Log Log Scales
 Extended Range Avoids "Going Off Scale"
- Extra P Scale Simplifies Computations
- Two Color Scales

10" log dupli decimal trigonometric slide rule contains 25 scales including 8 Log Log Scales. Troublesome end-for-end resetting is eliminated by extensions of C and D scales. Twin set of Log Log scales run from 1.001 to 100,000 and .999 to .00001, enlarging the scale by one scale length each compared with ordinary log log slide rules. Extra features include P scale which enables direct "readout" of cosine value. Scales include LU1, LU2, LU3, DF, CF, CIF, CI, C, D, LL3, LL2, LL1, LL00, L, K, A, B, S, ST, T, C, D, D1, P, and LL0. With instruction book, saddle leather case. Overall length is 14". Imported.

99 H 7055 Shpg. wt., 1½ lbs.

Net 15.95

NEW! DECIMA-DYNE™ SLIDE RULE A Dynamic Reactance Slide Rule




- Automatic 77 Multiplication on OF Scale
- Continuous Resonant Frequency Scale— Simplifies Surge Impedance Calculations

Direct Power Factor Read-out

Simplifies and Speeds Up CRL Calculations

Specially designed to speed up calculations for radio and electrical communication ungineering, for decibel, inductive reactance, capacitive reactance, resonance frequency, surge impedance, etc. capacitive reactance, resonance frequency, surge impedance, etc. Feature scales include: DB—for computation of electric communication circuit; DF and CF—same as D and C scales, except that they are "folded" at π : XC—for computation of capacitive reactance: K1—for computation of inductive reactance: F, and F,—for calculating resonance frequency. The 17 scales are: DB, DF, CF, CIF, CI, C, D, A, XC, XL, K, KI, S, T, F, F,, DI. With instruction book, leather carrying case, belt carrying loop. Imported. Shpg. Wt., 1 lb. 99 H 7128

DECIMA-LOGTM DELUXE 5" LOG LOG DUPLI DECIMAL TRIGONOMETRIC SLIDE RULE



Pocket Version of Lafayette's Most Popular Slide Rule P Scale (Pythagorean) permits direct "readout" of Cosine Values • Includes Leather Case With Pocket Clip • 24 Scales including 8 Log Log Scales

A pocket version of our 10" Log Log Dupli Decimal Trigonometric slide rule. Contains all the scales of the 10" rule except the "ST" scale. Two color scales—positioned for ease in use and rapid calculations. "C" and "D" scales on both sides of the rule. "P" scale for direct, cursor line reading of cosines of angles. Scales—front face: LL1, LL2, LL3, DF, CF, CIF, CI, C, D, LL3, LL2, LL1, Back face: LL0, L, K, A, B, S, T, C, D, DI, LL0, Engine divided rule of laminated, non-hygroscopic bamboo. Complete with instruction book and leather case with pocket clip. Imported.

99 H 7099 Shpg. wt., 8 oz.

NEW Graphos "COLLEGE" SET

A complete college assortment for ruling, technical drawing, and sketching. Orawing ink flows freely and uniformly—producing a well covered and sharply defined line. Lines of over 1000 yards can be accurately drawn with one filling of the pen. No smudges or blots! Set includes pen, black ink cartridge, 6 assorted nibs, and instructions, Housed in a plastic case. Shpg. wt., 8 oz. 15 H 5603

Net 5.98



- Simple As Using A Pencil
- **Professional Results**

LAFAYETTE 5-IN-1 SLIDE TRIANGLE

- Triangle! T-Square! Protractor! Ruler! Caliper! Measures
- Diameter. Width, Angle.
- For Student, Engineer Office, Etc.

The amazing Lafayette slide triangle com-The amazing Latayette Slide triangle combines five instruments in one—triangle, T-square, protractor, ruler and caliper. Use it to measure diameter, thickness, depth, length, angle as well as drawing parallel and vertical lines. Constructed of color-soft, clear, ¾, thick acrylic that is dimensionally and chemically stable. Smooth bevelled edges. Shpg. wt., 5 oz. Imported 59 H 7131

LAFAYETTE DRAFTING SUPPLIES




- Center Wheel Adjustment
- **Professional Quality**
- Made in Germany of nickel plated

Contains 61/6" self-centering compass, one leg knuckle joint with divider, pencil, pen parts and lengthening bar; 61/6" self-centering knuckie joint with divider, pencil, pen parts and lengthening bar; 6½" self-centering divider; spring bow divider 4½", center wheel adjustment with interchangeable needle points; spring bow pencil and spring bow pen, both 4½" with center wheel adjustment and interchangeable needle point; two 5½" ruling pens; extra handle for pen and pencil parts; adjustment tool; lead case and leads: and spare parts kit, all in velvet lined snap closing case. Imported lined snap closing case. Imported Net 6.85

99 H 7003 Shpg. wt., 11/2 lbs. SUPER DRAWING KIT



PORTABLE DRAWING KIT



FRENCH CURVE SET



made of crystal clear plastic .090" thick. Set consists of eight French curves. Excel-lent for perspective, three dimensional drawing and general applications. Shpg. wt., 1/2

lb. 15 H 1425

UTILITY DRAFTING SET

Exceptional Value

Made in Germany of hard rolled, nickel plated brass. All instruments are nested in a fitted, velvet lined case. Contains three side wheel 334" bow instruments—on a divider, one a pencil and one a pen. All have reversible needle point. 51/4" compass with pen and pencil parts—and lengthening bar. 51/4" divider with straightening device. 5" ruling pen. Extra handle for use with pen and pencil parts. Capsule with extra leads. Perfect for schools, labs, industrials. Shpg. wt., 1 lb. Imported. 99 H 7164 Net 3.35

PROFESSIONAL GIANT




• 6" Size with Center Wheel Adjustment Finely Balanced—Prefessional Type

Professional quality utility set in a fitted, velvet lined case. Made in Western Germany of nickel plated brass. 6" glant bow has preferred center wheel adjustment. Makes circles from 46" to over 10" in diameter. Set includes 6" glant bow, interchangeable pen and pencil parts, extra needle for using bow as divider, handle for use with pen and pencil parts, lead, lead box and repair parts. Shpg. wt., 1 lb. Imported.

99 H 7063.

Net 3.50 Net 3.50

draftette PORTABLE DRAFTING MACHINE



Precision instrument

Sketch, design, draw diagrams and schematics like a professional. The new Draftette gives you all the advantages of a portable drafting instrument. One piece aluminum scale features, 2 graduations—top in 16ths and bottom in eighths and fourths, a 360° protractor mounted on a 16x21" drawing and bottom in eighths and fourths, a 360' protractor mounted on a 16x21" drawing board. Draftette can be removed from its board and folded like a jack-knife, to be stored. It is easily attached, to any stiff-backed pad cf paper without screws. Finest satin black anddized aluminum construction. Assembled and ready for use as a T square, triangle or protractor. Perfect for students. Clear vinyl plastic carrying case. Shpg. wt., 21/2 lbs. 15 H 7401

Draftette =12-B Senior with 6x9" scale. 360° protractor on 20x26" drafting board. 15 H 7403 Shpg. wt., 6 lbs. Net 19.95 Draftette =12 Senior less board. Not 15 30 15 H 7404 Shpg. wt., 2 lbs.

LETTERING GUIDE SET



CAPAGED HIS EN JOB STOVETZO" IZ . " 63" 65" 6 To TO

Made of transparent plastic. Simple to use with either sharp pencil or ink. Each has complete alphabet, all numbers plus commonly used signs. Most letters formed with one operation. Set consists of six guides. Sizes 1/6, 1/4, 1/4, 1/4, 1/4, and 1/2". Shpg. wt.,


15 H 1432-Complete Set



Adjustable protractor head clearly marked to 180—easily set and fastened. Transparent arm gives clear full view of subject matter. All plastic—light weight. Adapted for ink ruling. Head fits snugly against board. Shpg. wt., 1/2 ib.

15 H 1426—18" long 15 H 1427—24" long Net 2.10

HARD MAPLE **PANTOGRAPH**




Enlarges • Reproduces!

A 21" adjustable pantograph with 21 different ratios from 1½ to 8. Enlarges, reduces or reproduces drawings, etc. Most rapid, accurate means of reducing or enlarging to scale. Lacquered highly finished bars are 21" long and ¾" wide. Heavy ball bearing standard. Chrome plated hardware, ratio thumb screws and nuts. Complete with lead, accessories and detailed instructions. Shpg. wt., 2 lbs.

15 H 5602 Net 3.75

"draftette" SKETCH KIT



A completely portable drafting drawing machine permanently mounted in a Vinyl binder (self-locking). A weather protected unit, it can be used for sketching, designing, drawing, and drafting. Great for traveling. Contains a precision portable drafting instrument with a 4x6" scale, 180 degree protractor, pad of 50 sbeets, drawing-tracing paper 8½x11", all in one compact binder. Does not require tape or tacks to hold paper in place for use. Only 9½x13X1" in place for use. Only 91/2x13x1". Net 7.80 15 H 7402

Lafayette Cat. No. 651 101

See Our Catalog 650 For Drafting and Drawing Supplies

LAFAYETTE Telescopes and Accessories



EQUATORIAL REFRACTOR

Ultra Precise Helicoid Focusing • 7 Coated Eyepieces Plus Barlow Lens • 76.2 mm Clear Aperture Equatorial Mount • 25x, 42 mm Finder Scope

79-mm hard coated, air-spaced Fraunhofer achromat of 910-mm focal length with 3" clear aperture, focal ratio of f/12 and resolving power of 1.6". Seven coated eyepieces provide magnifications of 227x, 152x, 101x, 73x, 35x, 18x and 25x through viewfinder. Melicoid focusing by means of a massive wheel and helical gear. Finder Scope, with rack and pinion focusing, features a 1.6 inch clear aperture objective of 500-mm focal length. Micro-motion controls with extended flexible shafts and compression locks in all axes. Accesseries include three sunglasses, moon-glass, sun diagonal, two star diagonals, sun projection screen, erecting prism, heavy extensible field tripod, brace, accessory shelf, separate wooden cases for telescope and mount. Shog. wt., 100 lbs. Via EXPRESS ONLY.

RESEARCH QUALITY 3" EQUATORIAL REFRACTOR

• Viewfinder Scope 25X, 42-mm • 910-mm Focal Length • 76.2mm Clear Aperture • Micromotion Controls for Declination and Right Ascension • Resolving Power: 1.6 • Barlow Lens Included Right Ascension • Resolving Power: 1.6 • Barlow Lens Included The objective lens is a 79-mm, hard coated, air spaced Fraunhofer achromat with a clear aperture of 76.2-mm (3"). Focal length 910-mm, focal ratio f/12, resolving power 1.6". Seven coated evepieces prowde magnifications of 227x, 152x, 101x, 73x, 45x, 35x, plus 25x through the viewfinder. Barlow lens add ranges of 454x, 304x, 202x, 146x, 90x, 70x and 50x. Focusing by means of micro-precise rack and pinion drive. The viewfinder scope has a 42-mm (1.6 in. clear aperture) objective —500-mm focal length-rack and pinion focusing —and will accommodate various eyepieces, Finely calibrated hour and declination circles for rapid finding and setting. Body tube of white enameled aluminum. Accessories include three sunglasses, moonglass, two star diagonals, sun diagonal, erecting prism, sun monglass, two star diagonals, sun diagonal, erecting prism, sun projecting screen, extensible field tripod, chain brace, accessory shelf, wooden cabinet. Via EXPRESS ONLY. Imported 99 H 7053WX Shgg. wt., 60 lbs.

Net 189.00



2.4" EQUATORIAL REFRACTOR

 Eyepieces for 160x, 88x, 40x, Barlow Lens gives 320x, 176x, 80x e 800-mm. focal length e 82-mm objective e Micrometion adjustments on both axes e Coated optics throughout e Equatorial mount Objective: Fraunhofer-type achromat, hard coated, 62.5-mm, 800-mm. focal length. Collects about 75 times as much light as the naked eye, capiting names? resolving power 2 seconds, faintest discernible star 10.7 magnitude. Eyepieces are hard-coated Muygenians. 160x (5-mm), 88x (9-mm), 40x 120-mm). Barlow Lens included give ranges of 320x, 176x and 80x. Finder scope is 6X, 30-mm. Tripod head with latitude adjustment. Clamp lever for declination and inclination. Accessories include sun-glass, star diagonal, erecting prism, sun projection screen, field tripod, wooden case. Rack-and-pinion focusing Heavy plating to tripod, wooden case, near the prevent rusting. Imported 99 H 7032WX Shpg, wt., 30 lbs. 99 H 7043L 4-mm. orthoscopic eyepiece for 200x Net 79.50

(400x with Barlow Lens)

Net 8.95

SPOTTING SCOPE



Any Power from 15X to 30X

Any power from 15X to 30X! Ideal for any "Spotting" Need. Pan-head, elevator tripod mount included. Perfect all round scope. Powerful, small lightweight, brilliant viewing. All aluminum and chromed brass. Imported. Shpg. wt., 5 lbs. 99 H 7101

ZOOM MULTI-SCOPE

50 mm Clear Aperture . Any Power From 25X to 80X

A multi-purpose telescope with true zoom action. Use at any magnification from 25X to 80X. Helicoid focusing—the most precise type available—holds scope in focus through type available—holds scope in focus through the entire range of power. Brilliant image at all powers. 50 mm, hard coated, achromatic objective lens. Precisely machined all-metal body. Lightweight—may be hand held or used with tripod supplied. Suitable for astronomical and terrestrial viewing as well as target spotting, nature study, camping or boating, With tripod and sun lens. Imported. Shpg. wt., 5 lbs.

99 N 7161

Net 22.85

10X30mm TELESCOPE with TRIPOD



Portable-Compact-Lightweight

A 10 power, 30mm internal (front) focus telescope that is compact, lightweight and portable—ideal for taking it everywhere you go. Features coated achromatic lenses. Has built-in camera tripod socket. Complete with tripod with rubber-tipped legs that prevent scratching. Imported. 99 H 7071 Shpg. wt., 2 lbs. Net 6.50

LAFAYETTE BINOCULARS

All Lenses Are Coated! Sealed Against Dust & Moisture

Precise design, quality material and expert workmanship. All center focus; adjustable right eye-piece. Leather case, neckstraps included. Imported.

7x35 Popular, versatile, all-purpose binoculars.

99 H 7018 Shpg. wt., 3 lbs. Net 21.95 7x50 Navy style night glasses. Favored for Net 21.95* marine use.

99 H 7016 Shpg. wt., 31/2 lbs. . 20x50 King of the long range. Net 26.751

99 H 7020 Shpg. wt., 41/2 lbs... Net 29.95*

*Add 10% F.E.T.

Wide angle view Fully adjustable

A multi-purpose 7x35mm binocular which is A multi-purpose /x35mm binocular which is especially useful in field studies. Wide angle view allows brilliant and close-up views of sporting events without cutting the image as regular narrow angle binoculars do. Field of view at 1000 yds. is 525 feet! Center focus and right eye adjustment insures perfect focus. All optics are coated. Lined leather case provides protection when not in use. Imported. 99 H 7019

*Add 10% F.E.T.

TRU-ZOOM™

Not a "Vari-Power," One Control Zooms both barrels! • Center Zooms both barrels! • Center Focus, Adjustable Right Eyepiece, plus Single Sychronous Zoom plus S Control!

Sight in subject at 7 power—then Zoom up to 12 power (or any four in between) for closeup viewing. Power 40mm, objective lenses, hard coated actromats. Field of view is 290 feet at 1000 yds. at 12 power (5.5°). Prisms in shock-resistant mounts. Lightweight alloy frame and body. Includes light with the property of the

*Add 10% F.E.T.

4X RIFLESCOPE



- Lightweight—only 6½ ozs.
- Hard Coated Lenses
- Internal Adjustments
- Cross Hair Reticule

Popular, all-around scope for the small game hunter. Bright field, approx. 30 feet at 100 yards. Eye relief distance from 3½ to 4½ inches. Eyepiece diameter, 1" tube diameter 1,4". Hard coated, achromatic lenses reduce glare. Internal windage and elevation adjustments for positive "zero-in." Fine, cross hair reticule pinpoints target. Featherweight weather-resistant precision. rine, cross nair reticure pinpoints target. Featherweight, weather-resistant, precision built. Easy, fast installation with all .22's with grooved receivers, some air rifles. Im-ported. Shpg. wt.. 1 ib.

Net 5.88 99 H 7160

ZOOM OPERA GLASS

 Coated Zoom



Just right for the opera, sporting events, and all around use. Small enough to fit in your pocket. Zooms in subjects. Magnifies 2 to 4 times. Individual focus with master zoom controls. Wide angle view. Neck band and zipper leather case included. Shpg. wt., 1 lb. Imported 99 H 7159 Net 10.95*

*Add 10% F.E.T.



The perfect companion for shooting, hunting and nature fans. Field of view is 85 feet at 1000 yds.! High relative brilliance due to 60mm objective lens. All optics are coated. Equipped with a 11½" tripod and zippered leather carrying case. Exceptionally small and light. Shpg. wt., 3 lbs. Imported.

99 H 7015 Net 16.95

13 H 1602

WEATHER ACCESSORIES

(A) "WINDICATOR" ANEMOMETER

Wind Direction and Velocity on One Dial ● Indicates Velocity from 0 to 100 mph ● New "Gyro" Design Starting Speed 5 mph ● Accuracy for Speed ±S%

A precision velocity/direction system designed to register wind velocity and direction on a single dial. Completely self contained—no outside power source is required. Indicating unit can be wall mounted or set on a desk. The indicator is housed in ahandsome wooden cabinet. 5½x2½x2½x7½m, finished in black and gold. Highly legible dial face 4½x3½m. Two scales for speed, 0 to 25 M.P.H. and 0 to 100 M.P.H. plus third scale for direction. Self contained battery—no drain except when reading wind direction. Simple installation. Complete with 60 ft. of 5 conductor, color coded cable, 1½ volt battery and instructions. Shpg. wt., 15 lbs. Imported.

88 H 9007WX

Net 48.95 cable, 11/2 v 99 H 9007WX

Wired for extended runs. 5 conductor, color coded cable. 32 H 5901 Shpg. wt., 21/2 lbs.

Net per 100 ft. 4.70

(B) INDOOR-OUTDOOR THERMOMETER

Shows inside and outside temperature from the comfort of your room. Single scale for instant comparison. Modern plastic case. 8x24/2x48% long copper capillary tube and bulb. Large numerals and no moving parts. Shpg. wt., 1 lb.

(C) MAXIMUM-MINIMUM THERMOMETER

For weather enthus:asts, gardeners, farmers, etc. Gives three readings at a glance—maximum, minimum and present temperatures. Magnifying lens case for ease of reading. Maintains automatic check on temperature variations. Makes you the local weather expert. Shpg. wt., 1 lb. 13 H 1603

AFAYETTE - MICROSCOPES





(A) 500X "MICRO-MECH" MICROSCOPE

- Built-in Mechanical Stage! 100X-200X-300X-500X
- Quadruple Revolving Turret

For the student — hobbyist - or budding scientist. Featuring a built-in, micro-drive mechanical stage. Permits the micro-movement necessary to properly examine micro objects. Promotes learning through ease of operation. Four achromatic objective lenses giving magnifications of 100X, 200X, 300X and 500X. Complete with wooden carrying case and slides. Imported. 99 H 7035 Shpg. wt., 41/2 lbs.

(B) 900X "ZOOM" MICROSCOPE


- Variable Magnification 100X to 900X with Zeem Action Built-In Substage Illuminator Zeem Ratio 1 to 1.5 for Maximum Resolution


4 Ceated Objectives

An excellent value for the beginning student or hobbyist. Features advanced zoom type micro-optics. Zoom action permits smooth, advanced zoom type micro-optics. Zoom action permits smooth, vibration-free, variable magnification without disturbing stage or specimen. Four hard coated objectives set in a revolving "click stop" turret give magnifications of 100X, 150X, 200X, 300X, 450X, 600X, and 900X. Zoom action permits choosing multiple magnifications without changing eyeplece or objective. The eyepiece zooms smoothly from 10X to 15X. Illuminator operates with batteries or house current, by means of transformer listed below. Round hole disc diaphragm controls illumination. Includes instructions, sample slides and wooden carrying case. Less hatteries imported. Shop slides and wooden carrying case. Less batteries. Imported. Shpg.

specimens 99 H 7110 Shpg. wt., 8 oz. Net 1.80

For BEGINNERS & INTERMEDIATE STUDENTS





(C) 50X STEREO-SCOPE

Stereoscope Binecular Microscope Wide Field—3 Dimension View

Vertically Erect Image

Indispensible for the examination of surface features of gross objects. Excellent hobby aid for the coin and stamp collector. Prismatic, binocular head with interpupillary adjustment. Ground glass stage, 31x234". Heavy modified horseshoe base. Overall height 8". Complete with wooden carrying case. Imported. Shpg. wt., 5 lbs. 99 H 7141 Net 14.95

(D) 80X TO 1200X ZOOM MICROSCOPE

- SOX-1200X Magnification
- Variable Zoom Eyepiece 3-Way Substage Mirror Complete Set of Dissecting Instruments 4 Achrematic Objective Lenses

Constantly variable magnification of 80, 100, 160, 200, 400, 600, 800, and 1200 times. Zoom eyepiece for less specimen adjustment and controlled detail magnification. Excellent dual knob coarse and fine focus control. Stage includes optical condenser and aperture diaphram. Spring loaded rack prevents damaging objective. Substage illuminator-mirror combination for direct, incandescent, or reflected illumination includes 2 prepared sides, 4 blank slides, spatula, scalpel, probe, scissors, tweezers, and magnifying glass. Wooden case with carrying handle. Illuminator operates on penlight cells or house current, by means of 4 transformer. Less batteries. Imported. Shpg. wt. 6 lbs.

Net 19.85

99 H 7140 Zoom Microscope Net 19.95 99 H 7106 Replacement Bulb Net .11 32 H 4802 Battery (2 required) Net ea. .13 TRANSFORMER—Permits use of house current for illumination of Net .11 t ea. .13 zoom microscope. 99 H 7110 Shpg. wt., 8 oz.









E



Net 1.80

A. SLIDE PREPARATION KIT. 30 glass slides, 3x1", in container. Slotted for easy indexing. Includes slide covers and vial of mounting fluid. Shpg. wt., 1 lb. Imported 99 H 7081 Net .98

B. MICROLITE. Provides a bright, evenly lighted field of view. Adjustable for transparent or opaque specimens, direct or indirect illumination. Invaluable where oblique light is necessary. Operates on 110-120 volts AC/OC. Self contained switch, cord and plug. Lamp is 5½" long. Stand is 5½" high. Shpg. wt., 1 lb. Imported.

99 H 7024 Net 2.95

C. HUNTING WITH THE MICROSCOPE. How the microscope works. How to prepare and study cultures—set up a microscope zoo and garden-grow micro organism-perform micro surgery. Profusely illustrated with photographs and drawings. 10 H 6002 Net .89

C. HOW TO DISSECT. Exploring with probe, and scalpel. 128 pages. 82 photos and drawings. Net .89

MICROSCOPY TEKNIKIT. Contains D. MICROSCOPY IRNINII. Contains equipment for collecting — fixing — depending — depending — depending — depending — depending — depending — drying and storing subjects. 24 1x3° sildes. cover slips, labels, tweezers, scalpel, dropper. In fitted case. Shpg. wt., 1 lb. Imported. And YARE 99 H 7088 Net 3.95

MICRO SLIDE PREPARATION TEKNIKIT. Seven dissecting instruments. 3 well slides, 22 blank slides, 25 cover glasses, 25 blank labels, blue stain, mounting fluid, pins and descriptive booklet. Imported. In fitted wooden case. Shpg. wt., 11/2 lbs.

99 H 7098 Net 3.49

E. WELL SLIDE TEKNIKIT. 6 single well slides, 6 double well slides, all 3x1". 20 cover glasses, vial of neutral red solution. Shpg. wt., 8 ozs. Imported. 99 H 7104 Net 1.28

F. MICRO-POLARIZING KIT. A simple, inexr. MICRU-PULANIZING RII. A simple, inexpensive accessory to change any microscope
into a polarizing microscope. Consists of an
Analyzer and a Polarizer. The Analyzer will
fit any microscope eyepiece. The Polarizer
can be placed on or under the stage or between the condenser lens and the stage.
The Polarizer is indexed for polarizing axis.
Supplied with instructions and case. Imported Shop wt 6 ox ported. Shpg. wt., 6 ozs. 99 H 7136

LAFAYETTE PRECISION SCIENTIFIC INSTRUMENTS



1500X SOCIETY STANDARD MICROSCOPE

25X to 1500X in 12 RANGES 4 ACHROMATIC OBJECTIVES IN ROTATING TURRET

VARIABLE SUBSTAGE CONDENSER WITH IRIS DIAPHRAGM STANDARD SOCIETY OPTICS, BOTH OBJECTIVES AND EYEPIECES

RIGID QUALITY CONTROL STANDARDS

PAR FOCAL WITHIN 0.1mm

An unusually fine optical instrument designed especially for precision viewing requiring high magnification with an oil immersion lens. The outstanding features of great range and engineered versatility, optimum clarity and great magnification are usually found in microscopes costing much more.

OPTICAL SPECIFICATIONS: Three Huygenian eyepieces—5x, 10x, 15x, Four achromatic objectives—5x, 10x, 40x, 100x (oil immersion). FOCAL LENGTH: 170 mm, Monoculor. FOCUSING: Coarse focus with adjustable tension. Fine focus vernier adjustment. Par-Focal within ½ rotation of fine focus contro! (0.1 mm) Spring loaded safety device prevents objective going through slide. STAGE: Square stage: 95 mm x 95 mm. Integral mechanical stage, adjustable in any direction. Stage clips. SUBSTAGE: Focusing condenser with variable iris diaphagm. 41 mm plano/concave mirror. Tilting Base. Black and chrome finish. Overall 12" high, 6½" deep, 4½" wide. Includes fitted wood cabinet with lock and key, 3 slides, bottle of redga cil. bottle of cedar oil.

99 H 7134WX Shpg. wt., 111/2 lbs. Imported . Net 89.95

Sample available on approval to universities and industrial laboratories.

Student Research Models-

1200X "RESEARCHER"



- 25X to 1200X in 12 Ranges
- Full Range Fine Focus Adjustment
- Integral Mechanical Stage
- Rotating Diaphragm

Closely parallels the "Society" grade microscope, yet is available at a very low price. Four Huygenian eyepieces: 5X, 10X, 15X, P20X combine with four achromatic objectives: 5X, 10X, 40X, 60X to yield 12 combinations: 25X, 50X, 75X, 100X, 150X, 200X, 300X, 400X, 600X, 800X, 900X, 1200X. Dual knob rack and pinion coarse focusing with tension adjustment for slow motion. Micro-motion fine focusing adjustment. Spring loaded to prevent objective from driving through slide. 85mm x 85mm stage can be moved in any direction, with slide, by 2 knurled screws while looking through the eyepiece. Sub-stage has rotating, 5-position diaphragm and 35mm plano/concave reflecting mirror. Stable horseshoe base. Complete with set of 5 basic dissecting instruments, 10 slides, pack of cover slips, tube of mounting fluid. All in a dovetailed wooden carrying case with handle and four rubber feet. Shpg. wt., 10 lbs. imported.

Net 44.50 99 H 7041

900X "MICROBE HUNTER"

A Microscope featuring GRADE A

Power Range 25X, 50X, 75X, 100X, 150X, 200X, 300X, 400X, 600X, 900X

Full Range Fine Adjustment

Safety Stop on Coarse Adjust-

Made to rigid design specifications— has wide usage in schools, laboratories and law enforcement agencies. All of the most needed features for diversified micro-studies. Power range from 25% to 900% in 12 possible combinations, Geared rack and pinion coarse focusing. Micromotion fine focusing focusing. Micromotion fine focusing—12 complete revolutions. 36mm (plano/concave) mirror. Fixed square stage, 70mm x 80mm. Rotating 5-hole, disciplangm. Three Huygenian eyepieces of 5X, 10X and 15X. Four achromatic objectives of 5X, 10X, 40X and 60X. Oversize base insures stability. Body perfectly balanced at any angle. Complete with upright, wooden carrying case. Shop. wt. 8 lbs. Imported. Net 29.95 99 H 7028

SPECIAL 20X EYEPIECE

Increases the power of our "Microbe Hunter" microscope (above) to 1200X. Highly corrected, fine quality peri-planatic ocular. Shpg. wt., 5 oz. Imported. Net 3.95 99 H 3471

MICROSCOPE MECHANICAL STAGE

WITH GRADUATED SCALES VERNIER TO 1/10th mm

wt., 12 ozs. Imported.

Attaches to any square microscope stage 70 mm x 80 mm or larger. Accommodates slides up to 75 mm x 50 mm. Both lateral slides up to 75 mm x 50 mm. Both lateral and front-to-back movement by rack and pinion. Adjustment scales are graduated in single millimeters with verniers reading to 1/10th mm. Essential accessory for all high magnification examination. Permits relocating any portion of a slide or charting the entire slide. Spring clip automatically accommodates slides of varying dimensions. Shpg. wt 12 ozer Imported.

Net 6.95 Lafayette Cat. No. 651 105

PORTABLE FIELD MICROSCOPE



- Pocket Size—for Field or Lab
 Achromatic—Coated Lenses

Unparalled for "rockhounds" prospectors, coin and stamp collectors, students and coin and stamp collectors, students and hobbyists. Indispensable for examination of gross and opaque subjects. Highly polished, finely machined chromium plated brass tubes, mount and tripod legs. Draw tube permits focusing on objects from flat surface to 134" high. Ideal for rrom rist surface to 14% high. Ideal for inspecting large specimens, small parts, surfaces of large places. Size collapsed is only 436% fully extended 642% less tripod. Includes soft leather case and tripod legs. Shog. wt. 1 lb. Imported. 99 H 7001 Net 5.95



99 H 7087 Microscopes are Available on Easy Pay Plan-See Center Insert A



LAFAYETTE 14" TRANSPARENT CELESTIAL GLOBE

Basic Aid for Students and Teachers of Astronomy NAVIGATORS . AFRONAUTICS . ASTRONAUTICS

- Adjustable Satellite Orbits
- Satellites Travel around Earth Automatically
- Adjustable Sun and Moon
- Adjustable Lunar orbital inclination
- 80 Constellations-including all stars of 1st, 2nd, 3rd and 4th Magnitude
- Similar devices used by the Navy—Air Force—and Marines

The Lafayette Celestial sphere will illustrate how the sky will appear at any hour—on any day—from any point on earth. With it you can tell time by the stars—learn to tell time by the sky—clearly illustrated and help solve navigational problems. Traces the orbits of man made satellites and finds their overhead positions. Sun and moon are positioned by external controls. Artificial satellites automatically circle around the globe. The celestial globe is 14" in diameter with the terrestial globe centered within. The various stars, constellations, and their identifications are permanently molded—not printed-on the celestial sphere. Equipped with horizon ring-time ring-fixed meridian ring-swinging meridian/ring-sun and moon pointers—fixed ecliptic-detachable "planet" indications—universal base—and complete instructions. Shpg. wt., 15 lbs. Imported. complete instructions. Shpg. wt., 15 lbs. Imported.

99 H 9001WX Net 49.50

MICRO PHOTOMETER

- Highly Sensitive Exposure Meter Suitable for use in Astrophotography
- For Photomicrography and Macro-photography



An exceptionally sensitive exposure photometer. Specifically designed for use in laboratory and clinical photomicrography, photomacrography and astro-photography. Sensitivity range in three scales from 0.1cp to 176.4cp. Shutter speed range to 1/5000 sec. Three scale ranges: 0-10, 0-100, and 0-1000. Each scale is subdivided in increments of 50 for maximum accuracy. Applies directly to the eyepiece of the microscope or telescope. Complete with all precessary fittings and instructions. Here design for the second control of th necessary fittings and instructions. Uses 4 penlight cells (not supplied). Shpg. wt., 3 lbs. Imported. 99 H 7130L

32 H 4802 Z batteries, 4 req.

Net 44.95 Net ea. .13 Micro-photography!

Astro-photography! Inexpensive accurate -A200

to use Use any camera/ microscope or cam-era/telescope setup

Photo-record your observations.



Permits the use of any camera—even movie cameras—with practically all microscopes and telescopes. No need to remove the camera lens. Cross hairs are super-imposed on the image for



MICRO-LAB TEKNIKIT ®

A carefully preselected assortment of the most often used lab items for biology, botany, anatomy, zoology, microscopy, etc. Perfectly complements the many inexpensive microscopes already in use. The instruments and accessories are of excellent quality. The cabinet will accommodate any microscope of no more than 8¾x5x3" overall (such as our "BI-OCULAR" and "Micro-Mech") and contains the following accessories: 15 slides, slide labels, slide covers, vial of balsam, dissecting scissors, probe, scalpel, tweezers, spatula, applicator rod, eyedropper, magnifer, 5 test tubes with stoppers, 6 laboratory jars, alcohol burner, polishing cloth. All in fitted drawers. Imported.

99 H 7066 Shpg. wt., 7½ lbs. Net 8.80

99 H 7066 Shpg. wt., 71/2 lbs.

Net 8.80



50X-100X "MAGNI-SCOPE JR."

Direct viewing "projection" microscope affords viewing ease to small groups. The image is projected onto a self contained, translucent glass screen. Finger tip control switches from 50X to 100X. Thumb wheel focus for sharp definition. Projects the full colors present in the slide or specimen. Illumination by means of a battery powered, pre-focused bulb. 2 flashlight batteries (not included). Overall size 4½x3x6½." With bulb and three prepared slides. Imported. 99 H 7113 Shpg. wt., 1½ lbs. Net 5.29 32 H 4804 Batteries (2 req.) Net ea. 13 32 H 4804 Batteries (2 reg.) Net ea.

MICRO-SLIDE TEKNIKIT



Selected Micro-Subjects Professionally Prepared

Carefully prepared slides of universal interest. Cleaned, dissected, embalmed, stained, mounted and covered. Professional size. Set includes 12 prepared slides and slotted, covered box. Shop, wt. 8 oz. Imported.

covered bo	x. Snpg. wt., 8 oz. imi	portea.	
	Parts of Insects		
	Spiders		
	Tiny Creatures		
99 H 7007	Sea Life	Net 1.39	
	Structure of Blood		
99 H 7009	Life cycle of insects	Net 1.39	
99 H 7010	Bacteria	Net 1.79	
99 H 7011	Plankton	Net 1.59	
99 H 7012	Micro-Animals	Net 1.29	
	Micro-Organisms		
*99 H 7014	Substance of Cells	Net .89	

*Set of 6 slides


NEW ARVIN ALL CHANNEL UHF-VHF 12"*PORTABLE T.V.

 Completely Equipped For All Channel UHF-VHF Reception, Channel • Two-Stage High Gain Frame Grid IF Amplification For Super Fringe Area Sensitivity and Performance • Two Speed Transistorized UHF-Tuner With Speed Vernier Orives For Fast, Simplified VHF-Station Selection • 12" Aluminized Picture Tube • Arvin "Memory" VHF Fine Tuning

This modern UHF-VHF TV combines advanced circuitry with the most up to This modern UHF-VHF IV combines advanced circuitry with the incist up to date styling to provide pleasurable TV viewing. High fringe area sensitivity utilizing 2 stages of high gain IF amplification. Automatic Gain Control Circuit assures locked in pictures and constant signal strength despite varying signal conditions. Unique VHF fine tuning system. Adjust picture and sound only once for each station. "Memory" circuit remembers this

NEW ARVIN all channel UHF-VHF 16" portable TV. Same fine features as above except with 16" Aluminized Picture tube. Shpg. wt., 32 lbs.

17 H 2001WX As little As \$ 6.00 Monthly



LIGHTWEIGHT 19-INCH* PORTABLE UHF-VHF TV

• Completely Equipped for All Channel Reception (2-83) • Thin-Line. Brief-Case Styling . 3 Stages Picture IF, 2 Stages Sound IF . Aluminized Picture Tube For Crisp. Brilliant Pictures . Completely **Handwired Chassis**

ONLY 12995 INF-VHE

As Little As \$6.00 monthly

Here is a handsome, lightweight portable TV with slim, brief-case styling that offers a big 19-inch screen and all-channel reception (2-83). The 114", bonded aluminized picture tube provides crisp, brilliant pictures, even in a brightly lit room. Completely hand-wired chassis uses a 17-tube circuit brightly lit room. Completely hand-wired chassis uses a 17-tube circuit with a cascode tuner, adjacent channel traps, and 3 stages of picture IF to assure strong, clear pictures even in outlying areas. Other deluxe features include: front-mounted speaker for best sound, built-in dual telescopic antennas for maximum signal pick-up, illuminated channel dial, jacks for private earphone listening and extension speaker, side-mounted controls, and covenient carrying handle. All tubes are accessible from rear of set. Smartly styled in black with brushed chrome trim. Size: 181-24x1814-14x12"D (overall). For 110-120V, 60 cycles AC. Imported. Shpg. wt., 55 lbs 17 H 1701WX 19" Port, all-channel (2-83) TV Net 129.95




23-INCH* UHF-VHF TV CONSOLETTE

114° Bonded Aluminized Tube For Brilliant Pictures Even In Brightly Lit Rooms
 3 Stages of Picture IF, 2 Stages Sound IF
 Elegant Low-Boy Styling with Slim-line Construction

ONLY 16495 VHF-UHF

As little As \$8.00 Monthly

An elegantly styled TV consolette for all channel reception (2-83). Performance and dependability are built into this 23-inch television receiver which



HEARING AIDS-HEADSETS-SILENT LISTENERS





Only One ounce!

(1) A high quality, completely adjustable, hearing aid which weighs only 2 ounces. Features an advanced 4 transistor circuit, wide range volume control, crystal microphone, magnetic earphone, and a 4 position tone converter control. Three tiny ear plugs and a 3 ft. flexible cord are included. Supplied with leather carrying case, earphone, and battery. Shop wt. 1 lb. Imported

priorie, and battery, oneg, we, a to meported	
99 H 9068L	Net 24.95
32 H 4812 Extra Battery, Burgess Net type	Net .08
99 H 9069 Extra Plug in cord	Net .55
99 H 9070 Extra Earphone	Net 1.59

(2) Good sound intensity and fine tonal reproduction make this an ideal hearing aid. The tiny unit is only 25%x7%x7% inches and weighs less than 1 ounce! Powered by a tiny, long life, mercury cell. A three transistor circuit provides the amount of amplification necessary for many different sound conditions. The large hold down spring clip keeps the hearing aid confirmation in place A special telephone clip keeps the hearing aid comfortably in place. A special telephone circuit provides for clear reception of telephone calls. Supplied with three interchangeable ear plugs, 3-feet of flesh-tinted cord, velvet-tined leather case, mercury cell, and instructions. Shpg. wt., 1 lb. Imported

99 H 9071L 33 H 1101 Extra Battery, Mallory RM625R

Net 22.95 Net



"PRIVATE EAR"



- Remote Control Radio TV/Earphone Adapter
- Operates Up To 2 Speak ers and/or Earphones

Relax in the most comfortable spot in the room and enjoy the benefits of private listening to your TV, radio or phonograph. Connect one or two extension speakers or earphones and control the volume of each separately. 25 foot, flat, flexible extension cord on control unit. Includes earphone control unit and instructions.

99 H 9074 Imported Net 3.29 H 2548 Extra Earphone for "Private Ear" Net .79 Net .39 99 H 2549 10 ft. Earphone Extension Cord

"WHISPER" BONE-CONDUCTION PILLOW SPEAKER

"Sonic Transducer" cannot be heard at a distance



Sound is actually conducted through your pillow and bone to ear. Not just another "pillow this patented device produces the inner speaker," sound vibrations which are heard best when conducted to the inner ear by a solid pathway, rather than air. No danger of disturbing others—even husband or wife asleep in the same bed! 2½" diameter round ivory plastic case is only 56" thick. Supplied jack permits easy plugging into radio or TV. Shpg, wt., 8 oz. Imported. 99 H 9073 Net 2.25

DYNAMIC STEREOPHONIC HEAOPHONES



Magnetic Elements

Lightweight—only 2 ozs.

BINAURAL HEAOPHONES Binaural-Magnetic-6 ohms impedance 99 H 1001 Binaural-Magnetic-5000 ohms impedance 2.35 H 1002 2.45

MONAURAL-MAGNETIC HEAOPHONES Monaural-Magnetic-6 ohms impedance Monaural-Magnetic-5000 ohms impedance

BEHIND-THE-EAR HEARING AID

Flesh Colored Plastic

Self-Contained Miniature Unit-No Cords

Complete with Battery Changer 2 Rechargeable Batteries and Hearing-aid 0

A fine unit combining good performance and very small size. Designed as a light and compact "ear-lobe" hearing aid. All components are contained in the flesh-colored high impact case, which is worn behind the ear. Weighs only ½ of one ounce! Sound travels to the ear through a clear tube. Independent on-off switch and volume control. Operates 8-10 hours on a rechargeable alkali battery and 80-100 hours with a mercury cell. Complete with a handy battery charger

capable of charging cells overnight. Shpg. wt., 1 lb. Imported.

99 H 9072 32 H 1448 Mercury cell for above Net 62.95

REMOTE CONTROL FOR SILENT TV VIEWING Simple to Attach to any TV set or Radio See and hear - Noiselessly -Conveniently

FOR LATE LISTENERS. One or two people can both see and hear the program with the loudspeaker cut off. Tops for enjoying the late-late show

without disturbing the rest of the household or the neighbors.
FOR HARO-OF-HEARING. Hear without turning the set volume so high
that others can't stand the noise. It is possible to listen either with the loudspeaker cut off or, if everyone wants to hear, with the speaker on.

FOR NOISY PROGRAMS view with the speaker off. FOR NORMAL OPERATION it does not affect the regular use of the TV set. It does not have to be disconnected.

REMOTE CONTROL comes complete with 20 ft. of cable so it can be operated comfortably from a distance. Has its own volume control, speaker on-off switch, and two sets of jacks so either 1 or 2 earphones can be connected. Supplied with a miniature dynamic earphone. Highly sensitive and efficient. Complete with 1 earphone with 3 ft. of cord and plug and control box with 20 feet of cable. Only 37/6x2x14/2". Instructions included. Shpg. wt., 3 lbs.

13 H 0901 EXTRA EARPHONE. Shpg. wt., 8 oz. Net .79 99 H 2548

10' EXTENSION CORD for above. 99 H 2549

Net .39



LAFAYETTE HEAO SET

 400 ohm DC Resistance Double Permanent Magnet

A real bargain—the convenience and advantages of earphone listening at an especially low price. This is an extremely efficient, double headset with adjustable headband, for private listening or for greater intelligibility when there are distracting sounds and external noise. 4,000 ohms DC resistance. Has durable permanent magnets, removable earpiece and $3\frac{1}{2}$ feet of catension cord terminated with standard headphone tips. Shop, wt., 12 oz. Imported. 99 H 2504

SUPER POWER DYNAMIC EARPHONE

FOR TRANSISTOR CIRCUITS

Powerful Efficient Magnet

Not to be confused with run-of-the Not to be confused with run-of-the mill earphones. Extra efficient construction and a powerful magnet provides exceptional performance. Ideal solution to the problem of low output in transistor circuits.—it will give delightful performance wherever a high impedance dynamic earphone is required. AC impedance 7000 ohms, DC resistance 1500 ohms. Snap on earpiece. Complete with 3 ft. detabable obusine cost. Shop with 4 accumentations.

tachable plug-in cord. Shpg. wt., 4 oz. Imported.



LAMPS and ELE ACCESSORI ELECTRICAL

CLAMP-TYPE LAFAYETTE DRAFTING LAMP"

AFAYETTE "DAY LIGHT" NEW High Intensity Miniature Lamp

For Factory, Office, Studying, Drafting, Home, Kitchen only

NOTICE

TO CHANGE WITHOUT

ALL PRICES AND SPECIFICATIONS IN THIS CATALOG SUBJECT

delivery. world

details

for

over the free 60 days for de days for de International

to 6

ship w up

Allow up Write to Division



tends ı pro--lo inor acwt.,

12.88



FYING

precision work, features a 5" gnifying glass with a powerful rrounded by a 22 watt shadowent tube. A custom-engineered complete directional mobility-thent knobs insure the proper teadiness for any desired posi-reach, Ideal for assembly, lab-lity control and other detail or assembled form. Shpg. wt.,

less lamp. sembled less lamp ool white lamp

Net ea 2.80

Net 19.95

Net 24.88

TRIC OUTLET



a Outlets Wherever Needed Home, Office, Industry ench or Wall, or Keep Portable

tra outlets, you need this Elec-itrol Center. Has six individual outlets with its own built-in fuse box. Fingertouch control on-off rocker switch with jeweled on-off indicator panel light. Heavy duty line cord for use in the home, office and industry too. Complete with mounting screws for permanent installation on wall or bench, or use it as a portable control center. For 110/120 V AC/DC, 1500 watts, 15 amps. Less fuse. Shpg. wt., 1 lb. imported. 14 H 2103 14 H 2104 Net 4.99 .24

14 H 2104 Box of 5 10-amp fuses Net 13 H 1171 Box of 5 15-amp fuses Net

801 1.09 1.						ZONES			
1.2 3.0 1.00 1.00 1.00 1.40 1.40 1.80 1.	SHIPPING				- 1			P	•
100 100 1,000	WEIGHT		1.2	e ;	4 400	2 C	1 001 40	1 401 to	Dver
Miles Mile	Up to	Local	up to	300	009	1,000	1,400	1,800 Miles	1,800 Miles
29 \$0.40 \$0.45 \$0.46 \$0.52 \$0.59 \$0.66 \$0.72 33 .46 .49 .55 .64 .73 .83 .93 33 .51 .65 .64 .75 .88 1.01 1.13 35 .57 .62 .72 .87 .15 1.38 1.31 39 .68 .75 .88 1.07 1.28 1.50 1.73 41 .73 .81 .90 .13 1.41 1.66 1.96 1.97 43 .78 .87 1.10 1.18 1.41 1.66 1.98 2.11 43 .78 .81 1.00 1.18 1.48 1.78 2.18 43 .78 .10 1.18 1.48 1.78 2.14 2.86 43 .78 .10 1.18 1.41 1.79 2.14 2.84 2.81 .51 1.10 1.18	including			Miles or the fire	7 ounce			itional our	nce
33 346 349 355 364 773 383 393 393 393 351 352 364 775 388 1.01 1.13 393 393 393 395 357 368 369 397 1.15 1.34 1.153 393	10 025.	en 29	ı ا د	\$0.42	5	\$0.52	\$0.59	\$0.66	\$0.72
33 31 35 364 75 88 1.01 1.13 35 57 62 72 87 1.02 1.18 1.34 37 62 .68 .80 .97 1.15 1.34 1.53 39 .68 .75 .88 1.07 1.28 1.50 1.75 41 .78 .81 .90 1.18 1.41 1.66 1.92 42 .83 .93 1.10 1.38 1.56 1.98 2.31 43 .81 .90 1.18 1.48 1.78 2.14 2.48 44 .78 .81 .90 1.18 1.48 1.78 2.14 2.48 45 .83 .93 1.06 1.26 1.99 2.29 2.24 2.8 51 .93 1.12 1.48 1.89 2.25 2.75 3.11 52 .113 1.30 1.56 1.99 2.37 2.50 3.5 53 .128 1.42 1.71 2.20 2.44 2.8 54 .12 1.48 1.89 2.25 2.75 3.11 55 .13 1.30 1.56 1.99 2.37 2.50 3.5 51 .13 1.42 1.79 2.30 2.73 3.36 3.8 52 .13 1.24 1.65 2.30 2.73 3.36 3.8 53 .128 1.48 1.66 2.30 2.73 3.36 3.8 54 .25 .25 .25 3.51 4.0 55 .13 .15 .15 .15 .20 2.61 3.21 3.7 56 .13 .15 .15 .15 .20 2.55 3.51 4.0 57 .17 .25 .10 .10 10 25.00 58 .10 .10 10 25.00 59 .10 .10 10 25.01 50 .10 .10 10 25.01 50 .10 .10 .10 .10 .10 50 .10 .10 .10 .10 .10 50 .10 .10 .10 .10 .10 50 .10 .10 .10 .10 50 .10 .10 .10 .10 .10 50 .10 .10 .10 .10 .10 50 .10 .10 .10 .10 .10 50 .10 .10	3 103.	31	46	.49	.55	.64	.73	83.	.93
35 .57 .62 .72 .87 1.02 1.18 1.34 37 .62 .68 .80 .97 1.15 1.34 1.53 39 .62 .75 .88 1.07 1.28 1.50 1.71 41 .73 .81 .90 1.18 1.41 1.66 1.92 43 .83 .93 1.00 1.18 1.41 1.66 1.92 2.11 47 .88 1.00 1.18 1.48 1.78 2.14 2.42 2.81 49 .93 1.06 1.26 1.58 1.90 2.29 2.74 2.86 2.14 2.86 2.14 2.84 2.84 2.84 2.84 2.84 3.0 3.5 3.1 3.1 3.1 3.1 3.1 3.1 3.1 3.1 3.1 3.1 3.1 3.1 3.2 3.2 3.2 3.2 3.2 3.2 3.2 3.2 3.2 </td <td>) <</td> <td>33</td> <td>2</td> <td>55</td> <td>.64</td> <td>.75</td> <td>88.</td> <td>1.01</td> <td>1.13</td>) <	33	2	55	.64	.75	88.	1.01	1.13
37 .62 .68 .80 .97 1.15 1.34 1.53 39 .68 .75 .88 1.07 1.28 1.50 1.73 41 .73 .81 .90 1.18 1.41 1.66 1.93 43 .78 .81 .90 1.18 1.28 1.53 1.82 2.12 45 .88 1.00 1.18 1.28 1.65 1.98 2.31 47 .88 1.00 1.18 1.48 1.76 2.14 2.82 2.31 49 .93 1.06 1.26 1.58 1.90 2.29 2.14 2.82 2.14 2.82 2.14 2.84 2.84 2.84 2.84 2.84 2.84 2.84 2.84 3.14 2.84 3.14 2.84 3.14 2.84 3.14 2.94 3.14 3.14 3.14 3.14 3.14 3.14 3.14 3.14 3.14 3.14 3.1	1	35	257	.62	.72	.87	1.02	1.18	1.34
1.73	, «	37	62	.68	.80	.97	1.15	1.34	1.53
1.92 1.18 1.41 1.66 1.192 1.182 1.182 2.182 1.182 2.182 1.182 2.182	,	5	89	.75	88.	1.07	1.28	1.50	1.73
43 .78 .87 1.03 1.28 1.53 1.82 2.12 45 .83 .93 1.10 1.38 1.66 1.98 2.31 47 .88 1.00 1.18 1.48 1.78 2.14 2.14 2.33 49 .93 1.06 1.26 1.58 1.90 2.29 2.49 2.86 51 .93 1.06 1.26 1.30 2.02 2.49 2.86 3.06 3.0 53 1.08 1.24 1.48 1.49 2.02 2.44 2.80 3.3 57 1.13 1.30 1.56 1.99 2.25 2.75 3.1 59 1.18 1.41 1.79 2.30 2.49 3.06 3.58 50 1.13 1.24 1.66 2.00 2.49 3.06 3.88 63 1.28 1.29 2.30 2.73 3.36 3.88 65	. 00	41	.73	18.	.90	1.18	1.41	1.66	1.92
45 .83 .93 1.10 1.38 1.66 1.98 2.31 47 .88 1.00 1.18 1.48 1.78 2.14 2.48 49 .93 1.06 1.26 1.58 1.90 2.29 2.69 5.1 .98 1.12 1.31 1.69 2.02 2.44 2.86 5.5 1.08 1.24 1.48 1.89 2.25 2.74 2.60 3.0 5.7 1.13 1.30 1.56 1.99 2.37 2.60 3.0 5.5 1.18 1.36 1.64 2.09 2.49 3.06 3.5 5.6 1.13 1.30 1.79 2.30 2.73 3.66 3.5 6.1 1.28 1.48 1.79 2.30 2.73 3.6 3.8 6.2 1.3 1.4 2.6 2.0 2.61 3.2 4.0 6.2 1.2 7 9 1	0	43	.78	.87	1.03	1.28	1.53	1.82	2.12
47 .88 1.00 1.18 1.48 1.78 2.14 2.48 49 .93 1.06 1.26 1.58 1.90 2.29 2.89 51 .98 1.12 1.13 1.18 1.41 1.99 2.14 2.09 2.74 2.83 53 1.08 1.24 1.48 1.89 2.25 2.75 3.11 57 1.13 1.30 1.56 1.99 2.37 2.90 3.31 59 1.18 1.36 1.79 2.30 2.73 3.06 3.51 3.0 61 1.23 1.42 1.71 2.20 2.61 3.21 3.7 65 1.32 1.56 2.40 2.85 3.51 4.0 65 7 9c 11c 14c 17 65 7c 9c 11c 14c 17 100 2.501 2.500 2.501 2.500	100	45	.83	.93	1.10	1.38	1.86	1.98	2.31
1.06 1.26 1.58 1.90 2.29 2.65	=	47	88	1.00	1.18	1.48	1.78	2.14	2.48
51 .98 1.12 1.33 1.69 2.02 2.44 2.85 53 1.03 1.18 1.41 1.79 2.14 2.60 3.0 55 1.08 1.24 1.48 1.89 2.25 2.75 3.11 57 1.13 1.30 1.56 1.99 2.37 2.90 3.35 59 1.18 1.36 1.64 2.09 2.49 3.06 3.5 61 1.28 1.48 1.79 2.30 2.73 3.21 3.7 62 1.32 1.54 1.66 2.40 2.85 3.51 4.0 65 1.32 1.54 1.66 2.40 2.85 3.51 4.0 66 4c 5c 7c 9c 11c 14c 17 67 7c 9c 11c 14c 17 68 1.79 2.50 2.50 2.50 69 1.70 2.50 2.50 70 1.70 2.50 2.50 70 1.70 2.50 70	12	49	93	1.06	1.26	1.58	1.90	2.29	2.66
1.23 1.03 1.18 1.41 1.79 2.14 2.60 3.0 55 1.08 1.24 1.48 1.89 2.25 2.75 3.11 57 1.13 1.30 1.56 1.99 2.37 2.90 3.31 59 1.18 1.36 1.64 2.09 2.49 3.06 3.5 61 1.23 1.42 1.71 2.20 2.49 3.06 3.5 62 1.28 1.48 1.79 2.30 2.73 3.36 3.8 63 1.28 1.48 1.79 2.30 2.73 3.36 3.8 64 5c 7c 9c 11c 14c 177 65 7c 9c 11c 14c 177 70 70 70 70 70 70 70	13	2	86	1.12	1.33	1.69	2.02	2.44	2.83
55 108 1.24 1.48 1.89 2.25 2.75 311 57 1.13 1.30 1.56 1.99 2.37 2.90 3.31 59 1.18 1.36 1.64 2.09 2.49 3.06 3.51 51 1.23 1.42 1.71 2.20 2.61 3.21 3.7 52 1.28 1.48 1.79 2.30 2.73 3.36 3.81 55 1.32 1.54 1.66 2.40 2.85 3.51 4.0 56 1.32 1.54 1.66 2.40 2.85 3.51 4.0 50 70 90 110 140 170 50 70 90 110 140 170 50 70 70 70 70 50 70 70 70 70 50 70 70 70 70 50 70 70 70 70 50 70 70 70 70 50 70 70 70 50 70 70 70 70 70 70 70 70	14	23	1.03	1.18	1.41	1.79	2.14	2.60	3.01
57 1.13 1.30 1.56 1.99 2.37 2.90 3.31 59 1.18 1.36 1.64 2.09 2.49 3.06 3.51 51 1.23 1.42 1.71 2.20 2.61 3.21 3.7 52 1.28 1.48 1.79 2.30 2.73 3.36 3.81 55 1.32 1.54 1.66 2.40 2.85 3.51 4.00 56 1.32 1.54 1.66 2.40 2.85 3.51 4.00 50 70 9c 11c 14c 177 50 10.01 10.25.00 50 10.01 10.01 50 10.01 10.01 50 10.01 10.01 50 10.01 10.01 50 10.01 10.01 50 10.01 10.01 50 10.01 10.01 50 10.01 10.01 50 10.01 10.01 50 10.01	7 2	25.00	1.08	1.24	1.48	1.89	2.25	2.75	3.18
1.64 2.09 2.49 3.06 3.5.	191	57	1.13	1.30	1.56	1.99	2.37	2.90	3.36
61 1.23 1.42 1.71 2.20 2.61 3.21 3.7 (63 1.28 1.28 1.79 2.30 2.73 3.36 3.8 (65 1.32 1.54 1.66 2.40 2.85 3.51 4.0 (65 1.32 4.6 5.7 7.0 (65 1.32 1.54 1.66 2.40 2.85 3.51 4.0 (65 1.32 1.54 1.66 2.40 2.85 3.51 4.0 (65 1.32 1.32 1.32 1.0.01 10.25.00 (65 1.32 1.0.00 (65 1.32 1.0.01 10.25.00 (65 1.32 1.0.01 10.25.00 (65 1.32 1.0.01 10.25.00 (65 1.32 1.0.01 10.25.00 (65 1.32 1.0.01 10.25.00 (65 1.32 1.0.01 10.25.00 (65 1.32 1.0.01 10.25 1.0.01 10.25 10.00 (65 1.32 1.0.01 10.25 10.00 (65 1.32 1.0.01 10.25 10.00 (65 1.0.01 10.25 10.00 (65 1.0.01 10.25 10.00 (65 1.0.01 10.25 10.00 (65 1.0.01 10.25 10.00 (65 1.0.01 10.25 10.00 (65 1.0.01 10.25 10.00 (65 1.0.01 10.25 10.00 (65 1.0.01 10.25 10.00 (65 1.0.01 10.00 (65 1.0.01 10.00 (65 1.0.01 10.00 (65 1.0.01 10.00 (65 1.0.01	17	50	1.18	1.36	1.64	5.09	2.49	3.06	3.53
63 1.28 1.48 1.79 2.30 2.73 3.36 3.8 (65 1.32 1.54 1.66 2.40 2.85 3.51 4.0 (7.65 1.32 1.54 1.66 2.40 2.85 3.51 4.0 (7.65 1.32 1.54 1.0 (7.65 1.32 1.0 (7.65 1.32 1.0 (7.65 1.32 1.0 (7.65 1.32 1.0 (7.65 1.32 1.0 (7.65 1.32 1.0 (7.65 1.32 1.32 1.0 (7.65 1.32 1.32 1.0 (7.65 1.32 1.32 1.32 1.0 (7.65 1.32 1.32 1.32 1.32 1.0 (7.65 1.32 1.32 1.32 1.32 1.32 1.32 1.32 1.32	- 8	19	1.23	1.42	1.71	2.20	2.61	3.21	3.71
65 1.32 1.54 1.66 2.40 2.85 3.51 4.0 [ED 4c] 4c 5c 7c 9c 11c 14c 177 [FD 4c] 4c 170 [FD 4c] 4c 1	10	63	1.28	1.48	1.79	2.30	2.73	3.36	3.88
FED 4c 5c 7c 9c 11c 14c 177 PARCEL POST HANDLING CHARGES 10.01 to 25.00 10.01 25.00 10.01 25.01 to 50.00	20	9.	1.32	1.54	1.66	2.40	2.85	3.51	4.06
PARCEL POST HANDLING CHARGES .05 .05 .10.01 to 25.00 .10 .25.01 to 50.00	١٣		4c	25	70	96	110	14c	170
	up to 5.00	00	PA				ARGES 25.00 50.00		

SHIPMENTS AIR

etn zone, Fuerto Rico and the Virgin Islands in the 7th zone, All other U.S. possessions and territories in the 8th zone.

rate changes post office

<u>Dadaadaadaadaadaada</u>

in length t APO and Parcel Post limits For fast delivery, you may specify Air Parcel Pock, Air Express or Air Freight, For Air Express Rates see Freight, For Air Express Rates see Your local REA Agent, For Air Freight commercial airport office. Air Parcel Post lir are 70 lbs. in weight, 100" in ler and girth combined, except APO FPO which are 2 lbs. and 20" your nearest

RATES POST PARCEL 1,2,3,

and it works. Has a 1000 watt lamp

load rating which permits it to control not

just one, but several fixtures. A multiple connection extension cord may be used if de-sired. Prowlers are discouraged, and your property is protected with "private eye"

clear plastic case measuring 314x114x1144." Complete with 6-ft, flexible 3-wire cord with adapter plug. For 110-130 volts, 50/60 cps

property is protected with electronic control. Housed

wt., 1 lb.

electronic

Territories, APO's .**83** add .73 add .50 80 per 1b Possessions, 1st lb. .68 For each add extra lb. .48 ZONES AIR

UNITED PARCEL DELIVERY

is serviced by UPS and are to your rates vour area service

via United Parcel Service. This fast, economical service is available from New York to most of the eastern states for parcels up to 50 lbs. and 108 inches in length and girth. 9 SHIPMENTS OUTSIDE C THE UNITED STATES

cent tube In' shatterproof, clear plastic outer tube, gives cool daylight. Stim stylouter tube, gives cool daylight. Slim styling for placing in narrow, confined area. Other features include glare-free shield, vinyl finger-grip handle, vinyl bumper guard, hanging hook, UL approved on-off switch, ballast, 15' 18-ga. UL approved cord. Grease and oil resistant. Overall 17" long. Shpg. wt. 2 lbs.

13 H 2200 Net 6.65 6-Watt Replacement Fluorescent Lamp 12 H 7502 Net 1.60

Net 7.50 For Fastest Service Use Lafayette's Convenient Order Blank

in decorative


Lafayette Cat. No. 651

109

FAMOUS TABLETOP SLOT RACING SETS



HO SCALE 4-LANE RACEWAY SET





High-Speed

Long-Lasting

With 15 Ft. of Track

Enjoy the pleasure of a 4-lane road racing set. Lots of thrills and action. Fun for everyone—young or old. Features the new "Sterling Moss" Thunder Jet 500 motor. With this new engine, the model actually breaks the speed of sound in scale miles per hour.

Set consists of four realistically crafted Thunderjet "500" cars, plastic and metal with rubber tires: four rheostat controls with steering wheels to increase or decrease speed, brakes, reverse and built-in speedometer; 18 voit DC power pack, UL approved. For 110-120v 60 cycle AC. Track Layout about 3 x 3 feet. 12 curved, 12 straight roading sections. Shpg. wt., 9 lbs.





HO SCALE 2 LANE RACING SET

688

Fast Gear Drive Cars

Make 6 Different Exciting Road Courses with this one Set!

ing pier set, guardrail fence set and all necessary hookup wire. Shpg. wt., 8 lbs.





12 H 2301

AUTORAMA "8" OVER 'N UNDER 2 LANE SET

134 Pieces

Two Competition-style Racers

Compete on Big Colorful Roadway

High powered Jaguar XKE racers zoom around a speedy track-up 'n over the jump ramp for spins, thrills. Added realism is provided by an 80 piece accessory kit consisting of a grandstand, starting gate, driver line up board, people and more. Racers are in kit form so you can decorate them with your own colors and numbers just like the real thing. Cars have front end steering. Two rheostat controls have simulated foot pedal speed controls. Powered by UL approved power pack for 110-120 volt 60 AC. Set also includes: 20 curve track, 4 straight, 10 section guard fence, see-saw ramp and 14 piece graduated trestle ramp set. Shog. wt., 10 lbs.

12 H 7202

Net 14.88

1940 Ford Coupe Ready to use, 5¼" long, 12 N 7203 Shpg, wt., ½ lb. Reversing Switch. Makes model cars go forward or back.





12 H 7204 Shpg. wt., 1/2 lb.

X-ACTO PIT KIT

 Designed for **Model Racing Cars**

A must for servicing, repairing and maintaining model raceway cars and track. Contains: small screwdriver, special self-locking tweezers, plastone abrasive, bristle brush, needle file, longnose pliers, X-Acto knife, X-Acto Oiler, and a special track cleaner. Shpg. wt., 1/2 lb.



X-ACTO

MODEL CUSTOMIZING

 All Needed **Basic Tools**

The customizing kit contains the "basic six" tools needed by indoor auto model

The Ideal Christmas Gift—A Lafayette Gift Certificate

110 Lafayette Cat, No. 651



• Drops Bomb in Flight! • Ready-to-Fly • Accurate Scale Model

Famous WWII STUKA. Ready-to-fly, Big green inverted gull wing maneuvers with dive-bombing responsiveness! Canopy section—with antenna mast between, really moves. Molded pilot and rear gunner included. Rear cockpit machine gun swivels. The 4" long plastic "bomb" can be released in flight. Visual fuel gauge permits flight time regulation. Includes .049 Cox Thimble-Drome engine. 23½" gull wing. 18" fuselage. Shpg. wt., 2½ l 14 H 6201 Net 7.49

Super Cub 150

32 H 4868 Ignition Battery #6; wt., 2 lbs. 14 H 6203 Kit: reel, line, hose, etc. and fuel

 New-Improved · Ready-to-Fly

Net Net 2.23

Ready-to-fly version of the famous all-weather CAP patrol plane. New body: closed fuselage

mounts—lighter weight. Famous Baby Bee. 049 1/2A engine; long-life nylon prop; unbreakable spring starter. 171/2" wing span, 12" fuselage. Includes control handle and Dacron lines. 14 H 6204 Shpg. wt., 2 lbs.

14 H 6204 Shpg, wt., 2 lbs. 32 H 4868 Ignition Battery; wt., 2 lbs. 14 H 6203 Kit: Reel, line, hose, etc. and fuel

Net 2.23

SUPER ACCESSORY KITS









line snaps glow fuel finguard filler cap Skylon reel · EVERYTHING YOU NEED FOR POWER MODEL OPERATION

Super Kit for planes: Each accessory thoroughly tested for dependable operation. Includes Skylon reel with Dacron flying lines, finguard, filler cap, stainless steel strainer, line snaps, filler hose, glow plug clip and glow fuel, Less battery. Shpg. wt., 1 lb. 14 H 6203 Net 2.23

P-40 FLYING TIGER



"BIG PLANE" REALISM . "COMBAT" MANEUVERABILITY


. SUPER POWERED SUPERBEE ENGINE

20" WINGSPAN—15" FUSELAGE

Flying scale model of the most famous fighter plane of the past quarter century. From prop spinner to rudder—from wheels to cockpit—every inch a richly detailed P-40 Flying Tiger! Powered by the special Super Bee engine. Most powerful engine of its size loops, wingovers, combat maneuvers, perfect flight control. Hiimpact styrene body—special nylon and vinyl fittings—official insignia—unbreakable spring starter—nylon prop. Includes control handle and Dacron lines. Shpg. wt., 242 lbs.

32 H 4868 Ignition Battery #6. Shpg. wt., 2 lbs. 14 H 6203 Kit: reel, line, hose, etc. and fuel

"WING THING"



Free Flight Powered Flying

Tow-Line Gliding

Sky-High Sailing

Tethered Power Flying

It Flies—It Soars It Spins-It Loops It Glides!

Simple in construction, virtually crash-proof under normal conditions. The "Wing Thing" consists of a flexible plastic wing, 36" long with 52" spread and a light fuselage on which is mounted a powerful Thunderhead engine. You can change flight characteristics to suit yourself by adjusting a counter-weight on the fuselage. "Wing on wing" construction prevents nose dive, provides extra buoyancy. Shpg. wt., 2½ lbs. 12 H 7205

32 H 4868 Ignition Battery; wt., 2 lbs. ... 14 H 6203 Kit: Reel, line, hose, etc. and fuel

Net .84 Net 2.23

Net 9.95

only **995**

NEW! U-2 "SPY PLANE"





It's a secret mission, everything is ready—the camera is loaded, the flight plan set. Whoosh—you're off to high adventure with the huge, silent Model U-2 spy plane. Giant 5 foot wingspan lets it soar like a gilder to 100 feet or more, wings and tail assembly are adjustable for flight control. Pre-set timer snaps shutter, camera takes in-flight photograph of everything below it. Assembles in minutes with only three tables the plane of the part had be about the attention of the part of the plane of the part of the plane of the part of the plane of rubber bands. Plane may be launched by catapult or flown like a kite. Built of rugged plastic. Complete with camera, automatic timer and roll of standard No. 127 black and white film. Camera can be removed and used in ordinary manner. Shpg. wt., 3 lbs

the Air! Giant 5 ft. Wingspan-21/2 ft. Fuselage! Free Flight—Soars like a REAL Glider!
 Control Line—Flies like a Kite!

Take "secret" Pictures from Hundreds of Feet in

SELECTED LAFAYETTE CHRISTMAS GIFTS

Science-Minded Young! Hear Voices a Block Away!

THE BIG EAR



Powerful Transistorized Listening Device

Big 18" Reflector Disk Concentrates Sound Waves into Transistor Unit and Amplifies Them Loud and Clear

Powerful new transistorized listening device. Works on the same principle as the fabulous Missile Tracking Antennas. Pick up sounds too distant for you to hear. Make your own wildlife recordings or carry on long range 2-way communications (using a "Bull Horn"), ideal for experimenters, etc. Complete with sturdy tripod and stethoscope-type earphones. Uses one 9V Battery (not supplied). Shpg. wt., 5 lbs. 13 H 2510

99 H 6021 9V Battery for above

SENSATIONAL LIE-DETECTO MACHINE



An Action Packed Electronic Sensation!

195

- Employs The Same Method As The Famous Polygraph Machine
- Registers Emotions, Feelings and Realisms
- **Absolutely Safe**

Lie-Detecto measures the change in resistance in the skin due to emotional response by means of a special hand-band which detects the amount of perspiration on the skin. Emotions, Feelings and Reactions are registered on an indicator which swings from Start thru Could Be, Are You Kidding, Little Whopper and Big Whopper, depending on the reaction of the person tested. In addition two panel contents provide for Sensitivity and Adjustment. Unit is enclosed in an attractive rugged enclosure of non-breakable Norolon. Supplied with simple instructions and sample questions hand-hand and hattries. simple instructions and sample questions, hand-band and batteries. Shpg. wt., 4 lbs. 13 H 4201

PROJECT-A-SCOPE

Projects Giant Pictures in Color or Black and White- Without Films or **Negatives**

For Lectures — Study — Classroom or just Plain



Handsome projector molded of heat and abuse resistant, hi-impact Mandsome projector molded or neat and abuse resistant, ni-impact plastic for long life. Casts sharp, giant-size enlargements on any white wall or screen in brilliant color or black and white. Simple to operate. Can be used by students, artists, collectors, lecturers and demonstrators. Children can project their favorite comics or story books to amuse themselves and their friends. Uses ordinary household bulbs. U/L approved. 110 volts, AC-DC. Shpg. wt., 2 lbs.
15 th 5.001 For Junior!

ELECTRONIC RIFLE RANGE



A complete rifle range full of action. Target may be placed on tabletop or on stand supplied. Target spins when bullseye is scored.
Authentic-looking, 30-inch rifle shoots a beam of light which actuates target. Develops marksmanship skill. Three ordinary flashlight
batteries required to operate rifle, 4 to operate target. The younger
set will be delighted with this set, while parents can relax without
worrying about accidents. Shpg. wt., 8 lbs.

13 H 4202 (Less batteries)

Net 14.88

Batteries for above 32 H 4804 (7 reg.)

Net ea. .13

EMENEE ENLARG-A-GRAPH



Ideal Gift to Develop Artistic Skills

We'll Send Your Holiday Gift to Any Part of the World



Real Switchboard Action-Lights, Buzzer, Dial Hold Calls—Switch calls—Call to or From All Phones

A Practical Low Cost Intercom System

Great fun for the entire family, practical too, Perfect for play or adult use between living room, kitchen, bedroom, stckroom. Functions like real unit, with 4 plug-ins and 4 signal switches, which ring bell. Operator has own master phone. Call in-switchboard lights up, rings. Operator can receive all incoming calls, can connect phone to phone. Operates on two inexpensive 'D' size flashlight batteries. Complete set includes regular operations dial, message pad, one operators phone and one extension phone. Takes 3 additional extension phones (optional at extra cost). Molded of high impact plastic. Shor, wt. 4 lbs. Shpg. wt., 4 lbs. 13 H 8401 32 H 4804 "D" cells for above Net

for above.

2 req. Net EXTRA PHONES with hanger and wire

13 H 8402 "C" Battery For Extension Phones, 1 each Ea: Net J



Finest model steam engines famous for quality the world over. All engines are ready stocked with "Esbit" dry fuel for initial run. Can be used to operate mechanical models. Imported from Germany. (A) Brass Boiler dia. about 1½ inches. Features Oscillating cylinder. Sturdy firebox housing for Esbit dry fuel. Safety valve. Grooved flywheel. Metal base 6x7 inches. Height including chimney about 7 inches. Spag wt 2 lbs. 7 inches. Shpg. wt., 2 lbs.

(8) Brass boiler stained blue with a diameter $2 \frac{1}{4}$ inches, Features oscillating cylinder. Sturdy firebox for Esbit dry fuel, Safety valve. Steam white, water level indicator and grooved flywheel, Flywheel mounting has railing. Metal base $8\frac{1}{2}\times10^{\circ}$. Height including chimney $9\frac{3}{4}$ Shpg, wt., 3 lbs.

ESBIT DRY FUEL. Package of 20 pellets. Will operate all Fleisch-

man steam engines. Completely safe and non-toxic. Imported from

STEAM ENGINE ACCESSORIES

RAZZLE-DAZZLE WHEEL. A dazzling display of never-ending color. Shpg. wt., 1/2 lb. 12 H 5704 SAUSAGE MACHINE WITH OPERATOR. Watch him make an endless supply of sausages. Shpg. wt., ½ 1b.

Net 3.10 12 H 5705 TRANSMISSION. 7" long; can operate up to 4 models at a time.

Shpg. wt., 1 lb. 12 H 5706

REVELL "Slant-Six" MODEL KIT



Motor Parts Actually Work

Educational Authentic

This Revell motorized plastic 14" scale working model kit of a slant six automotile engine duplicates its full size prototype. The more than 200 individual parts are precise in detail with those of the remarkable engine powering the Valiant and Lancer automobiles. It can be built up and taken down as often as desired. A section of the block can be removed to see the interior parts working. In this motor-minded age the "Slant-Six" makes an ideal kit for any boy or man to own and build, it's fun—and according to educators, its an excellent learning tool. Included is an elaborate educational instruction booklet and a sturdy stand for mounting the engine, Battery operated to provide realistic engine movements. Economical "C" cells are used. Shpg. wt., 242 lbs. 13 H 2005
32 H 4801 Extra "C" cells, 2 required. Net 13

13 H 2005 32 H 4801 Extra "C" cells, 2 required. Net .13



.13 ea.

Net 2,25

....Ea: Net .13

Learn About Optics, Solar Energy Provides Real Stimulus For Further Study Hours of Fun

A wonderful introduction to the fascinating study of physics. Crammed with parts, equipment, apparatus, for hours of endless experimenting in Solar Heat, Optics, Air and Water, Light Blending, Fluid Dynamics pressure and many others. Set includes colorful laboratory manual, radiometer, parabolic reflector, polorizing filters, optical bench, beaker, illuminator, other accessories. Shpg. wt.,



Build An Electromagnetic Crane

Make A Battery Learn About Magnetism

Safety Tested.

Explore the wonders of Electricity, safely. Learn why electricity behaves as it does. Features practical experiments in making a rheostat, battery, using a compass in magnetism research, etc. Endless projects which are educational as well as enjoyable. Safetytested, uses dry cell battery power only. Includes colorful instruction manual. Shpg. wt., 3 lbs.



An all-automatic mechanical action bowling game in your own home! No batteries needed . . . over four foot long alley! The bowler and ball are controlled by the player by the use of levers. You position him to bowl and send the ball down the alley! Automatic pin-spotter picks up the pins standing, sweeps the alley of pins knocked down, lowers and replaces these that were left standing for your next play. All the fun of real bowling with this authentically detalled bowling game. Keep your own score! Instructions and scoring pad included. Keep your owi Shpg. wt., 8 lbs. 13 H 2183

Net 11.88

Hours of exciting fun for all the men in the family. Score with this exciting game that really lets you call the play. Play offense and defense. Your skillful "quarterbacking" makes the football move along the playing field . . as you outplay your opponent . . . and win a real victory. Set contains automatic penalty indicator, first down penalty maker, score board and down maker. Operates on 2 "D" batteries (not included). Shpg. wt., 5 lbs. 12 H 5202 Net 9.98

"D" cell batteries—2 required 32 H 4804

Net each .13



FORMEX "7" MILITARY CASTING SET

Make Your Own Military Toys

Completely Safe
Hours of Do-It-Yourself Fun and Satisfaction
Can Be Reused Countless Times

Now you can make your own military toys with this fascinating new casting set—soldiers, jeeps, cannons, up to 24 figures. Completely safe and simple to operate. Just put the Formex "7" compound into pan on Dyna-Cast Thermal Unit—equipped with regular electric bulb that safely melts the compound ... pour it into the casting moids, dip into the cooling tank, remove the hardened compound and you have realistic, wonderful toys for military maneuvers. Set includes Army Green Formex "7" compound. Shpg. wt., 5 lbs. 12 H 5203

Net 5.69

19-PIECE ROAD RACE SET



- Safe-Battery Operated • 10 Track Sections • 2 "Cross Over" Tracks
- Speedy Aston Martin Flashy Chevrolet Corvette

The best reason why all men are boys at heart. An exciting road race set at an even more exciting price. This 19-piece set consists of: 2 straight tracks, 6 curved tracks, 2 crossover tracks, 1 Aston Martin (with motor), 1 Chevrolet Corvette (with motor), 1 Renault Floride, 4 guard rails, 2 hand controls, 1 pack of track clips. All you need are the batteries. Shpg. wt., 3 ibs. Net 4.88

"D" cell batteries—4 required 32 H 4804 Lafayette Cat. No. 651

114

Net each .13

MAGIC MILL

- Charming Running Water
- Illuminated

Revolving Wheel

Designed for the young railroad

engineer but is equally adapt-

able to many purposes. Log cabin is illuminated and rustic in appearance. The flow of liquid down the chute and over the revolving wheel is set into action by pressing a switch on the side of the mill. Powered by regular flashlight batteries. Perfect for making lovely table contamined describers.

making lovely table center-piece decorations. Shpg. wt., 11/2 lbs Net 3.75 cell battery for above (2 req.) Shpg. wt., 1/4 lb.

Net ea. .13

"MAGIC" WATER PUMP

 Completely Portable Only One Moving Part

A scientific, educational combination of electric motor and water pump. Designed for notice that the pump needs no external connections of pipe or fittings. Uses regular flashlight batteries. Safe—clean—harmless. Loads of fun. Shpg. wt., ½ lb.

14 H 6302

Net 1.69

14 H 6302 "D" cell battery for above. Shpg. wt., 1/4 lb. Net .13

See Our Catalog 650 For Experimenters and Builders Specialties

LAFAYETTE V.T.V.M. WITH 61/2" METER

- Wide Band RMS Measurements on any Waveform from 30 cps to Over 5MC, Without Additional **Probes or Accessories**
- 11 Megohm Input Resistance—Negligible Loading **Effects on DC Circuits**
- Direct Reading DB Scale
 Balanced Push-Pull Amplifier-Isolates and Protects
- Pilot Light Indicates When Unit is *'On"
- Selected 1% Zero Temperature Coefficient Multiplier Resistors for Dependable, Accurate Readings
- Silicon Rectifier in Power Supply Reduces Effects of Heat on Component Values
- ACCURATELY MEASURES AC PEAK-TO-PEAK VOLTAGE, AC RMS VOLTAGE, DC **VOLTAGE AND RESISTANCE**
- GIANT 6½" FULL-VIEW METER WITH EASY-TO-READ TWO-COLOR SCALES

This high quality V.T.V.M. is an indispensable test instrument for the This high quality V.T.V.M. is an indispensable test instrument for the service technician, engineer, or experimenter. It is a highly accurate DC voltmeter, AC voltmeter and ohmmeter employing a glant 6½" easy reading 400 µa meter. With a high input impedance of 11 megneys, the service of 11 megneys, and the volts, while presenting a negligible load to the circuit under test. As a wide band AC voltmeter, it will measure AC peak-to-peak voltages up to 800 on any waveform be it sinusoidal, sawtooth, square or of any other complex form; all this from 30 cps to above 5 Mc—without any accessory probes! AC RMS voltages may be read directly up to 1,500 volts if the waveform is sinusoidal. Resistances can be read directly on the Ohms scale from 0 to 1,000 megohms in 5 verlapping scales. A direct reading scale is calibrated from —10 to overlapping scales. A direct reading scale is calibrated from —10 to +45db (reference 1.73 volts, 6 mw into a 500 ohm line). The meter

NOT A KIT... **FULLY WIRED** AND TESTED

ONLY '

Made in U.S.A.



is isolated from the measuring circuits by a DC amplifier, making it virtually impossible to burn it out. Multiplier resistors are 1% zero temperature coefficient types. Function Selector-selects power off, AC volts, P-P volts, D.C.V. Neg., D.C.V. Positive, Ohms; Range Selector—for 7 voltage and resistance ranges; Ohms Adjust; Balance (cero) Adjustment. There are 3 probes: Common A.C. volts—ohms, and shielded DC volts probe with 1 megohm isolating resistor. Silicon rectifier power supply for 110-120 VAC, 60 cps. Dimensions: 7½Hx 6½Wx5°D. Comes with 1½ volt battery for ohmmeter circuit and complete instructions. Shpg., wt., 7 lbs.

38 H	0101	Above V.T.V.M Ne	26.95
38 H	0103	Accessory RF probe for V.T.V.M Ne	3.95
38 H	1501	Leather Case For V.T.V.M. Ne	2.95

SPECIFICATIONS

OC VOLTMETER RANGES: 0 to 3, 30, 150, 300, 1500 voits. Input resistance: 11 megohms (1 megohm in probe) on all ranges.

A.C. VOLTMETER RMS RANGES: 0 to 3, 30, 150, 300, 1500 voits.
PERAN-TO-PEAK RANGES: 0 to 8, 80, 400, 800 voits, DECIBEL RANGES:

—10 to +5, +6 to +25, +26 to +45 db. Response: 30 cps to above 5 Mc

OHMMETER RANGES: 0 to 1000 megohms in 5 overlapping ranges. ZERO CENTER VOLTMETER RANGES: 0-1.5, 15, 75, 150, 750 volts. TUBES: 1-6211 twin triode balanced meter bridge; 2-9006 peak-topeak rectifiers; silicon rectifier power supply. POWER: 110-120 VAC, 60 cps.

LAFAYETTE COMBINATION SIGNAL GENERATOR AND SIGNAL TRACER

NOT A KIT - FACTORY WIRED AND TESTED

SIGNAL GENERATOR

- Covers From 2S0 KC to 120
- MC in 5 Bands High Stability Electron Coupled Oscillator
- Attenuator For Both RF and Audio Circuits
- Most Used Frequencies Marked on Panel in Color Utilizes New Ruggedized Industrial Types Tubes

SIGNAL TRACER

- · Hi-gain Cascode Pre-amplifier Front Panel Output For VTVM,
 Scope or Phones
 Low Oistortion Triode Output
- Separate R.F. and Audio Signal Probes

Two test instruments in one! The Signal Generator will serve as a full service instrument and the Signal Tracer will follow any signal whether generated by a broadcasting station or injected by the Signal Generator section. When used in combination, with no dependence on outside signals, the unit provides ideal service, for unlike any standard signal tracer, it first injects its own signal then traces that controllable signal to locate the source by standard signal tracing technique. Designed for use with AM, FM, TV and audio circuitry. Features 5 frequency ranges and an attenuator switch to control both the R.F. signal (either modulated or unmodulated) and the 400 cycle audio tone. Front panel output jacks which can be used for oscillioscope, VTVM or earphone connections. Housed in a beautiful crackle finish steel cabinet with a deep etched aluminum panel. Dimensions: 73/x34/34/544/** Complete with 2 probes, Shog, wt. 9 lbs. Dimensions: 71/2x91/2x51/4". Complete with 2 probes. Shpg. wt., 9 lbs.

RANGE: Band A: 250KC to 850KC; B: 850KC-3000KC; C: 3.0MC to 11MC; D: 11MC to 45MC; E: 35MC to 120MC; 400cps audio signal; modulation slide switch, RF/AF attenuator and power switch; Signal output jack; AF input jack. 2 Preamp. output jacks. 4½" alnico 5 speaker. Tubes: 5687, 6350, 6AG5 plus sel. rectifier.



For Additional Test Equipment See Pages 115-120

WORLD FAMOUS LAFAYETTE MULTITESTERS



DELUXE LAFAYETTE 30,000 OHMS PER VOLT MULTITESTER FOR PRECISION MEASUREMENTS

30,000 Ohms per Volt DC, 15,000 Ohms per Volt AC

1% Precision Resistors for High Accuracy

Unique "Buzzer" for Fast Short Tests • 27 Meter Ranges on 2-Color Scale

A deluxe portable Volt-Ohm-Milliammeter with a high order of accuracy. Completely A deluxe portable Volt-Ohm-Milliammeter with a high order of accuracy. Completely wired and portable, it provides wide voltage, current, resistance and db ranges clearly visible on a big 4" meter with 2 color calibrations. Sensitivity is 30,000 ohms-per-volt DC and 15,000 ohms-per-volt AC. All multipliers used are 1% precision resistors for maximum accuracy and years of dependable service. Sensitive 33-micro-amp meter provides full scale readings down to ¼ volt on DC and 0.05 milliamps. Features a unique self-contained buzzer to give you fast in-circuit checks on opens, shorts. Audio output jack with DC blocking capacitor. Handsome, dust proof black plastic case. Complete with leads, batteries. Size: 3¾6Wx6¾4Hx2¾°D. Shpg. wt., 2 lbs. Imported.

99 H 5004 99 H 5005 Pigskin Carrying Case for above

SPECIFICATIONS

Sensitivity: 30,000 ohms/voit OC, 15,000 ohms/voit AC, Ranges: DC voits: 0-.25, 1, 2.5, 10, 25, 100, 250, 500, 1000; AC voits: 0-2.5, 10, 25, 100, 250, 500, 1000. Oirect Current: 0-0.05, 5, 50, 500 ma; 0-12 amps Ohmmeter: 0-60K, 6M, 60 Megohms, Oecibeis: —20 to +56 db. Short Test: Internal Buzzer. Audio Output Jack. Controls: Range Switch, Ohms Adjust. Batteries: 1 type Z cell, 15-voit.



Factory Wired

Deluxe 20,000 Ohms-Per-Volt Multitester

• 20,000 Ohms Per Volt DC-10,000 Ohms Per Volt AC

Measures: 0-1200y OC, 0-1200y AC, 0-10 Megohms, 0-60 µa, 0-600 ma, --20 to +63 db, 200 mmf-0.2 mfd.

Easy visibility is provided by the large 3½" meter with large two color scales. The 40-microampere D'Arsonval meter movement permits a high input resistance on all ranges: 20,000 ohms per volt on DC; 10,000 ohms per volt on AC. 1% tolerance resistors permits the measuring of voltages without unduly loading the circuit, preserving accuracy of readings. Measures 0-0.6, 6, 30, 120, 600, 1200 DC volts, 0-6, 30, 120, 600, 1200 AC volt, Resistance 0-10K, 100K, 1M, 10 Megohms, DC Current 0-60 microamperes, 0-6, 60, 600 milliamperes, —20 to +63 decibels. Features a capacitance measurement range, 200 mmf to 0.2 mfd capacity. Complete with batteries, test leads and operating instructions. Size 5½x3%x1%*D. Shpg. wt. 1½ lbs. imported.

99 H 5006 99 H 5007 Pigskin Carrying Case for above Net 1.95

Net 17.95

20,000 Ohms-Per-Volt Multitester


20,000 Ohms/Volt DC, 10,000 Ohms/Volt AC

1% Precision Resistors

Compact, lightweight, Accurate

Easy-to-Read 3" Meter

SF ECLFICATIONS



SPECIFICATIONS

Sensitivity: 20,000 ohm/volt DC, 10,000 ohms/volt AC. Range DC Volts: 0-3, 30, 60, 300, 600, 3,000V. AC Volts: 0-6, 60, 120, 1,200V. DC Current: 0-60 μA, 0-12, 0-300 ma. Resistance: 0-60K, 0-6 Megohms. Decibels: —20 to +63db. Audio Output Jack. Type "2" 1.5V cell for resistance measurements. This handy pocket multi-tester has every needed range. Ideal for repair and service work on appliances, radio, etc. 40 micro-ampere meter movement permits a high input resistance on all ranges—does not load down circuits while testing. Has a single range/function control for quick, simple operation, plus zero ohms adjust. Supplied with 1½V penlight cell and test leads. Rugged, high impact plastic case. Size 3½x44/2x1". Shpg. wt., 1 lb. Imported.

99 H 5008 99 H 5009 Pigskin Carrying Case for above

Net 1.75



Pocket AC-DC VOM

- Extremely Compact, Measures Only 31/8x21/2x1" Weighs 5 Ozs. 1,000 Ohms Per Volt Sensitivity 1% Precision Resistors Reads: 0-1000 Volts AC-DC, 0-100K Ohms, 0-150 MA

The Lafayette pocket multitester features small physical size, and a wide selection of useful ranges. It can be used for trouble-shooting any type of electronic circuits or electrical appliances such as irons, lamps, radios, television, hi-fi equipment, etc. 1000 ohms per volt sensitivity, and 1% precision resistor components assure accurate, precise readings. Operation is extremely easy, no switching or fidgeting required. Ranges Volts: 0-15-150-1000 AC and DC. Ohms: 0-100K; MA: 0-150. The VOM comes completely wired and tested, and is enclosed in durable plastic case. All accessories including battery are rubber insulated, color coded, flexible tesf leads are supplied. Shgg. wt., 1 ib. Imported.

99 H 5010 AC-DC POCKET VOM

Net 4.95

EXCLUSIVE LAFAYETTE TEST EQUIPMENT



A modern, dependable tube checker designed for fast, accurate testing—the ideal low-cost tube tester for any radio-TV serviceman, experimenter, technician, etc. This outstanding instrument tests most of the tube types employed in Radio, Hi-Fi, Monochrome and Color TV, including the new 12-pin compactrons, nuvistors, T-9's, 7 and 9-pin miniatures—actually tests over 1600 different tubes! A special alligator clip lead is furnished for testing tubes with top caps. Slide switches are employed to connect the various tube elements to their respective test circuits. A 3-position tube slide switch adjust for checking shorted elements, cathode emission and filament continuity. A leakage indicator light glows when an inter-element short or leakage is present in a tube. A power switch turns the unit on and additionally serves to adjust for various AC

LAFAYETTE TUBE TESTER

for HOME, SHOP BENCH or LABORATORY

Packed With Features at A Price You Can Afford

NOT A KIT -COMPLETELY WIRED

 Checks New Compactrons, Nuvistors, New T-9 Types
 7-pln Miniatures, Octals, Lock-In's and 9-pin Miniatures Fast-Setting Slide Switches Covering All Elements of 12-Pin Compactron Tubes • Accurately Checks Over 1600 Oifferent Tubes • Tests for Cathode Emission, Leakage and Shorts plus Filament Continuity • Completely Portable—Weighs Only 6 lbs. • Highly Accurate Country Portable—Weighs Only 6 lbs. • Highly Accurate Country Portable—Weighs Only 6 lbs. • Fighty Accurate Country Portable Country Easy-to-Read Meter with Replace-Good Scale . Slide-Out Tube Chart

OELUXE TUBE TESTER IN CARRYING CASE. Same as our Tube Tester above, but housed in portable wood case with grey vinyl trim. Imported.

99 H 5012

Net 23.95

DELUXE LAFAYETTE 20,000 Ohms-Per-Volt VOM with GIANT 6" Meter

Not a Kit—Completely Wired and Tested



- Glant 6" Full-View Meter
 Expanded Easier-To-Read 2-Color Scale
- 20,000 Ohms-per-volt BC
- 1% Multiplier Resistors
- OC Volts From 0-5000V in 8 Ranges
 AC Volts From 0-5000V in 6 Ranges

A precision VOM with varied ranges for accurate measurement of voltage, current, resistance and decibels. This deluxe VOM gives you accuracy comparable to bench type units, with the added feature of complete portability. Expanded 6" meter scale in red and black gives you top visibility. 50-microamp meter sensitivity provides 20,000 ohms per-volt input resistance on OC and 5,000 ohms per-volt on AC—Wide-range frequency response measures 10 to 100,000 cycles within ± 0.5 db. A single 1.5V battery in the ohmmeter circuit prevents burnout to low current drain devices. All multiplier resistors are 1% precision type. Heavy gauge steel case with high impact plastic panel. Includes test leads, batteries and leather carrying handle. Size 6¼wx7¾kx3½°D. Shg. wt., 4½ lbs. Imported.

SPECIFICATIONS

Sensitivity: 20,000 ohm/volt OC, 5000 ohms/volt AC. Range: AC; 0-5000 volts (in 6 ranges): 2.5, 10, 50, 250, 1000, 5000V: OC; 0-5000 volts (in 8 ranges): 0.25, 1, 2.5, 10, 50, 250, 1000, 5000V: OC Current, 0-10 amps (in 6 ranges); 0-50 \(mu_a\), 1 ma, 10 ma, 100 ma, 500 ma, 10 amps. Ohmmeter: 0-20 megohms (in 3 ranges): 0-2K, 200K, 20M. Decibels: —20 to +50 db. Accuracy: DC; \(\pmu_3\)% Full Scale. AC; \(\pmu_4\)% Full Scale. Resistance: \(\pmu_3\)% Full Scale.

LAFAYETTE RF SIGNAL GENERATOR



• FACTORY CALIBRATED AND TESTED • SIX BANOS: 120 KG - 260 MC

DUAL OUTPUT RF TERMINALS
 SEPARATE VARIABLE AUDIO OUTPUT

DIAL CALIBRATION ±2%
 ETCHED CIRCULAR OIAL - (Vernier Tuned)

A stable, wide-range signal generator engineered to fill the need for an accurate low cost service instrument. The delicate oscillator coils and tuning assembly are factory mounted and adjusted for optimum performance. This top-filght unit can be used for IF-RF alignment, audio signal tracing of TV, FM and AM sets. TV linearity checks and 400 cycle audio testing. In addition, it can serve as a marker generator when used with a suitable sweep generator. Incorporates a large 4½° etched circular dial for easy, accurate frequency adjustments. Provides a fundamental frequency output of 120 KC to 130 MC in 6 bands plus a calibrated harmonic output of 120 mc to 260 MC. The built-in audio oscillator operates at 400 KC with adjustable output to 8 volts. Continuously variable RF attenuator for proper signal attenuation and two plug-la RF output terminals provide a choice of high and low outputs for maximum flexibility. High output and tuning dial calibration of ± 2%. Imported 98 H 5015

SPECIFICATIONS

Full frequency range: 6 Fundamental bands—120-320 Kc 320-1000 Kc. 1-3.5 MC, 3.2-11 MC, 11-38 MC, 36-130 MC; One harmonic band 120-260 MC. Frequency Accuracy: ± 2%. Audie Output: to 8 voits. Large 44% Etched Circular Dial (Vernier tuned) High-Low

RF Output Terminals. Tube Complement: 12BH7A, 6AR5, Selenium Rectifier. Power Requirements: 105-125VAC 50/60 Cps., 12 Watts, Attractive gray wrinkle steel case with leather carrying handle. Complete with test leads. Size: 7Hx101/2Wx53/6"D. Shpg. wt., 9 lbs.

LAFAYETTE SINE/SQUARE WAVE GENERATOR



\$5.00 monthly

• FACTORY CALIBRATED AND TESTED • LOW DISTORTION • FREQUENCY RANGE - SINE WAVE: 20 cps—200 KC IN 4 BANDS; SQUARE WAVE 20-25 KC (Vernier Tuned) • ETCHED CIRCULAR DIAL • FREQUENCY RESPONSE -±1.5DB, 60CPS - 150KC 41/2" VERNIER DIAL

Especially designed for radio-TV servicemen, Hi-Fi fans and students who require a dependable sine and square wave generator at low prices. An outstanding instrument . . . factory wired, tested and calibrated. Among its many applications are square wave testing of audio amplifiers, determining the frequency and transier response of loudspeakers, TV audio circuit testing and many other uses. Quality features and specifications consist of a frequency range of 20 cps to 200,000 cycles in 4 bands. A large easy-to-read and set etched dial (vernier tuned) adds a professional quality touch. Variable attenuator adjusts amplitude of output signal. A full wave power supply is incorporated to provide low distortion and constant output. Factory wiring and calibration insure accuracy of ±3%. Output voltage is 7 volts across a 1 megohm load. Rugged steel cabinet and shock-proof mountings protect components. Complete with instructions and test leads. For 117 V 50/60 cps AC. Size: 10½/Wx7½Hx5¾°D. Shg. Wt., 10 lbs. imported. Shpg. wt., 10 lbs. imported. 99 H 5014 Net 35.95

SPECIFICATIONS

Frequency range: Sine wave; 20-200,000 cps in 4 bands. Square wave—60-30,000 cps. Output Voltage—Sine: 7V RMS: Square 7V P-P. Output Impedance—0-5000 Ohms. Frequency Accuracy: ±3%. Distortion: Less than 2%. Tube

Complement: 1-6BM8, 1-12AT7, 1-6X4, Power requirements: 117V 50/60 cps, 19W. Gray wrinkle steel case with leather carrying handle. Complete with a pair of test leads. Size: 7Hx10½Wx5¾°D. Shpg. wt., 10 ibs.

DELUXE SIGNAL GENERATOR



MACE IN U.S.A.

\$5.00 monthly

 Genometer—7 Signal Generators in one
 RF Signal Generator for FM
 Audio Frequency Generator
 Bar Generator
 Cross Hatch Generator
 Color Dot Pattern Generator **Marker Generator**

A versatile all-inclusive Generator which provides all the outputs for servicing: AM Radio, FM Radio, Amplifiers, Black and White TV, Color TV, SPECIFICATIONS: RF Signal Generator—Provides complete coverage for AM and FM alignment. Generates radio frequencies from 250 KC to 45 MC on fundamentals and from 35 MC to 120 MC on powerful harmonics. Cross Hatch Generator—Will project a cross-hatch pattern on any TV picture tube. The pattern will consist of non-shifting, horizontal and vertical lines interlaced to provide a stable cross-hatch effect. Variable AF Generator—Provides a fixed 400 cycle sine-wave or a variable 300-20,000 cycle peaked wave audio signal. Oat Pattern Generator—The dot pattern projected on any Color TV picture tube enables you to adjust for proper color convergence. Bar Generator—Projects an actual bar pattern of 4-16 horizontal bars or 7-20 vertical bars on any TV receiver screen. Marker Generator—Provides 9 most frequently needed marker points (262 KC, 456 KC. 600 KC, 1000 KC, 1600 KC. 2500 KC, 3.579 MC, 4.5 MC, 10.7 MC). Complete with shielded leads and operating instructions. Size: 10Wx7Hx54/CD, Shgp, wt., 7 lbs. 10Wx7Hx53/4"D. Shpg. wt., 7 lbs. 38 H 1001

Lafayette Is America's One-Stop Electronics Shopping Headquarters

FACTORY ASSEMBLED Ready-to-Use TEST EQUIPMENT LAFAYETTE CAPACITANCE-RESISTANCE ANALYZER

Capacitance Bridge Circuit

Direct Reading Scales

"Magic-Eye" Null Indicator **And Meter**

Measures Electrolytic Power

\$5.00 Monthly

Tests capacitors of all types for value, shorts, opens, leakage, insulation resistance and power factor. Measures resistance from 2 ohms to 200 Megohms. Invaluable for determining the turns and impedance ratios of audio and power transformers. All readings are made directly on expanded easy-to-read etched fial scales. Leakage current and insulation resistance of capacitors are read directly on meter. Bridge circuit accurately measures resistance and capacity. "Magic-eye" indicator permits fast visual results for "null" opens or shorts. Complete with instructions and test leads. For 117V 50/60 cycles AC. Grey wrinkle finish steel with carrying handle. 10½Wx7Mx5¼"D. Shpg. wt.,12 lbs. Imported. 99 H 5017



Capacity Ranges: 20 mmf to $2000~\mu f$ in 4 ranges. Resistance Ranges: 2 ohms to 200 megohms in 4 ranges. Leakage Test: 3-600 volts; Current 0-1 ma; 0-10 ma. Transformer Turns Ratio: 1:1 to 200:1. Transformer Impedance Ratios: 1:1 to



LAFAYETTE DELUXE CRT REJUVENATOR TESTER



\$5.00 Monthly

 Checks and Corrects Each **Gun of Color Tube Separately**

Reiuvenates All TV Picture **Tubes Including Color and** 110° Types

Rapidly checks and corrects black and white and color TV picture tubes including 110° types without removing them from the set. Restores brightness and emission to old CRTs. Determines quality of CRTs by means of an emission test. Large 4½" meter gives legible readings at a glance. Selector switch provides a choice of dual filament voltages of 6.3 V and 12.6 V. Checks and corrects each gun of color tube separately, Repairs Interelement shorts and open circuits. Includes 3 additional tube socket adaptors for 110° deflection type tubes. For 105-125V 60 cycle AC. Handward 131½". Shops. wt., 9 lbs. Imported.

99 N 5018 Deluxe CRT Tester Adapter for 23EP4 picture tube. Shpg. wt., ½ lb. Imported. 99 N 5019

Net 39.50

Net 1.50

CAPACITANCE SUBSTITUTION BOX



A must for the serviceman, experimenter or student. Fast accurate selection of any one of 9 capacitor values from .0001 to 22 MFD. Condensers are porcelain cased tubular type impervious to moisture and are rated at

- 36" Color Coded Test Leads &
- 9 Ranges From .0001 to .22 MFD

600 volts working capacity. 9 capacitance ranges are .0001, .0022, .0047, .01, .C22, .047, .1 plus 22 MFO. Complete with 367 red and black test leads and alligator clips. Size: 434x254x156". Shpg. wt., 142 lbs. 99 H 5020 Imported Net 2.95

RESISTANCE SUBSTITUTION BOX



Ideal for laboratory or service application. Substitute resistance values fast and accurately in trouble shooting circuits where values may have changed. Easy to find bias resistance in experimental vacuum tube or transistor circuits. Slide switch selects two

- 24 Resistance Ratings
- Two Ranges-Low 15-10K Ohms. High 15K-10 Megohms
- 36" Red & Black Test Leads with Alligator Clips

ranges—Low: 15 ohm—10K ohms (1 watt resistors) High: 15K ohm—10 Megohms (1/2 watt resistors). Two rotary switches (12 steps each) selects 24 separate resistances. Size: 43/4x23/6x13/6". Shpg. wt., 11/2 lbs. 99 H 5021 Imported Net 3.95

LAFAYETTE IN-CIRCUIT CAPACITOR CHECKER



- Checks Capacitors in Circuit Magic Eve Indicator
- Wide Range 10 MMF to 2000 MMF

Allows you to check most capacitors from 10 mmf to 2000 mmf for open or shorted conditions without unsoldering. Just connect conditions without unsoldering. Just connect the test leads across the component you wish to test, press the switch and note the eye tube's face for an open or short condition. Checks coupling, by-pass, filter and blocking capacitors. Accurate readings are made in seconds—an Important factor in today's complex electronic equipment. It also indicates capacitor leakage. Tests for opens on capacitors of 10 mmf. or more; for shorts up to 2,000 MF. Shunted by not less than 10 ohms. Complete with test leads and instructions. For 117 VAC. Size: 7% WKSHK4% "D. Shpg. wt., 5 lbs. Imported. 99 H 5022 Net 14,95 99 H 5022

WORLD FAMOUS TEST EQUIPMENT KITS

AFAYETTE TRANSISTOR ANALYZER



6-IN-1 TESTER

IN-CIRCUIT AND OUT-OF-CIR-CUIT TRANSISTOR CHECKER (INCLUDING POWER TYPES)

DIODE AND RECTIFIER CHECKER

SIGNAL GENERATOR BATTERY TESTER

VOLTMETER

MILLIAMMETER

MADE IN U.S.A.

test. This analyzer also checks the condition of diodes and rectifiers. Features a volt-meter which can check up to 12 volts DC and for testing transistor radio batteries. This analyzer can check current drain up to 80

millamperes. Complete with test leads and step-by-step illustrated instructions. Attractive black case and anodized aluminum front panel, 67/ax 53/6x25/6". Shpg. wt., 31/2 lbs. 19 H 0901 Complete Kit

Net 13.50 Extra 1½ volt Battery (2 required) Net ea.

EICO MODEL 427K GENERAL PURPOSE 5" OSCILLOSCOPE KIT

Lafayette's 6-In-1 Transistor Analyzer is a tester capable of testing transistors of all types including power types. The in-circuit test couples the transistor to an oscillator circuit within the tester for an actual performance check. Externally the transistor is checked for leakage on a multi-colored scale and for beta gain in 3 ranges up to 200. Makes trouble shooting transistor radios easy by supplying a 5kc test signal with harmonics for checking the RF, IF, and AF circuits. This signal can also be coupled to an oscilloscope for a visual circuit function



\$7 monthly

Features direct-coupled, push-pull vertical amplifier. Response flat from DC to 500 KC, —6 db @ 1 MC, 4-step plus CAL vertical attenuator. Sensitivity 10 mv p-p or 3.5 mv rms per cm. Horizontal amplifier: flat from 2 cps to 450 KC. Sensitivity 0.5v p-p or 0.18v rms. per cm. Voltage calibrator for peak-topeak measurements. Sweeps 10 cps to 100 KC in 4 ranges. Gun of CRT is mu/metal shielded. For 105-125V, 60 cps AC. Size: 8½x12½x16½%. Shpg. wt., 30 lbs. 38 H 2641WX Model 427 Kit Net 69.95 Model 427. As above, but factory wired. Features direct-coupled, push-pull vertical

EICO MODEL 628K TUBE TESTER KIT



\$5 monthly

Cathode conductance type tube tester features 13 individual lever switches for complete flexibility. Tests 7, 9 and 10 pin miniatures, octal, loctal, 5 and 7 pin nuvisors, novars and compactrons. Pilot light test socket, and VR's and "eye" tubes. Tests for short and open elements. Also tests all color and black and white CRT's with optional adaptor. Protective overload lamp shows transformer overloads and acts as fuse. 3-column roll chart frequently revised for up-to-date data. 4½" meter. With all parts and instructions. For 105-125V 60 cycles AC. Size: 12½Wx9½/kx4½"D. Shpg. wt., 11 lbs. 38 H 2655 Model 628 Kit............ Net 44.95 38 H 2656 As above, factory wired Net 39.95 38 H 2655 Model 628 Kit Net 44.95 38 H 2656 As above, factory wired Net 59.95

EICO MODEL 324K RF SIGNAL GENERATOR KIT



Lafayette Cat. No. 651

For IF-RF alignment, signal tracing and trouble-shooting of TV, FM, AM sets all on fundamentals; marker generator for alignment of new h-f and older i-f TV IF's, Range: 150 kc-145 MC on fundamental: 111-435 MC on calibrated harmonics — ± 1.5% freen calibrated harmonics—

RCA MODEL WV-77EK JUNIOR VOLTOHMYST



This kit makes possible substantial savings in a high quality vacuum-tube voltmeter. Its 28 ranges include 7 DC voltages: 0-1.5, 5, 15, 50, 150, 500, 1500, with ±3% of full scale accuracy and input resistance of 11 megohms: 7rms AC voltages: 0-1.5, 5, 15, 50, 150, 500, 1500, with ±5% of full scale accuracy; 7 peak-to-peak AC voltages: 0-4, 14, 40, 140, 400, 1400, 4000 volts, with 5% accuracy; 7 overlapping ohms ranges from 0.2 ohms to 1000 megohms with center-scale values of 10, 100, 1000, 10K, 10K, 1 meg. and 10 meg. ohms. Other important features include zero center for discriminator alignment; frequency response of 40 cps to 5mc. flat to within ±5% on the 1.5 to 15 voltrms and 4 to 40 volt p-to-p ranges; 1% deposited-carbon resistors; meter electronically protected against burnout. Power requirement is 5 watts at 105-125 v. 50-60 cps AC and VS035 battery. Supplied complete with DC and AC/ohms probes and cables and ground leads, battery, and instruction book.

struction book. 38 H 4602 Shpg. wt., 5½ lbs. Net WV-77E wired and factory-calibrated. Net 29.95 38 H 4603 Net 46.95

RCA MODEL WV-38AK VOLT-OHM MILLIAMMETER KIT



Here is a VOM by RCA that you can get either as a kit or as a factory wired instrument. A must for any kind of electronic servicing. DC voltage has 8 ranges: 0-0.25, 1.0, 2.5, 10, 50, 250, 1000, 5000 volts, with ±3% of full scale accuracy. DC input resistance is 20,000 ohms per volt. AC voltage has 6 ranges: 2.5, 10, 50, 250, 1000, 5000 volts, with ±5% full scale accuracy. Input resistance is 5000 ohms-per-volt. Frequency response, measured full scale accuracy. Input resistance is 5000 ohms-per-volt. Frequency response, measured with reference at 1000 cps is flat within ½ db from 10 cps to 50 KC for 2.5, 10, 50-volt ranges. Resistance from 0-2,000—200,000—20,000,000 ohms in three ranges. DC current has 6 ranges of 1-10-100-500 milliamperes, and 0-10 amps, with full scale accuracy of ±3%. Complete with batteries, ground lead and instruction booklet. Size: 54xx34xx6%".

5¼x3½x6%". 38 N 4804 Shpg. wt., 4 lbs. Net 29.93 WV-38A Completely wired and factory tested. Net 47.95 Model WG-270A Leather Carrying Case for WV-38A(K), 38 H 4806 Shpg. wt., 2 lbs. Net 4.95

DELUXE LAFAYETTE FM COMMUNICATIONS RECEIVERS

MONITOR CALLS FROM STATE. COUNTY AND MUNICIPAL POLICE — FIRE DEPARTMENT — — CIVIL DEFENSE — RAILROADS — TRUCKING — HIGHWAY MAINTENANCE — FORESTRY CONSERVATION - PETROLEUM AND INDUSTRIAL ACTIVITIES



Two deluxe FM communications receivers for the office, home. Excellent sensitivity of 4 µv or less for 20 db quieting and built-in adjustable squelch for dependable all-day monitoring of pount-in adjustable squeich for dependable alt-day monitoring of emergency, commercial, or industrial communications. Both units feature 3 IF stages and fully tuned RF stage. Model HA-52 incorporates 60W4 nuvistor "front-end". A built-in 4" speaker gives clear voice reproduction . . . and as a special feature a front panel phone jack may be used for private listening. Large, easyModel HA-50 30-50 MC Model HA-52 152-174 MC

Variable Squelch

Solid State Power Supply

Extremely Sensitive Circuitry Built-in 4" Speaker

8 Tubes for 10-Tube Performance

Nuvistor Front End*

\$6 monthly

to-read slide rule dial is illuminated for night operation. Housed in attractive blue-grey metal cabinet . . . makes a handsome addition to any home or office. Power requirements: 117 volts AC at 50/60 cps. Size: 11%4x54x736". Shpg. wt., 14 lbs. Imported.

*Model HA-52 Only. 99 H 2525WX Model HA-50 30-50 mc ... 99 H 2526WX Model HA-52 152-174 mc

Net 59.95 Net 59.95

12 LESSON CODE COURSE

12 LESSONS ON A 12" LP RECORD



Learn Morse Code the modern practical way. Supplied with 12 lessons on a non-breakable high quality 33½ rpm long playing record, recorded with code sound to provide further aid. Perfect for home studying. Speed progresses steadily from 3 to 16½ wpm. Complete with sturdy record album and instruction manual. Shpg. wt. 1½ lbs. 11/2 lbs. 40 H 8901 Code Course



TAPEDCODE

Prerecorded magnetic tapes containing complete course in the international Morse Code. The tapes are 7", 1200 ft. and can be played on any standard tape recorder. Playing time 2 hours per tape. Shpg. wt.,

1½ lbs. NOVICE Basic instruction & code 4-8 WPM. 40 H 4901 .. Net 6.35 ADVANCED Code at 9-18 WPM.

40 H 4902

DELUXE LAFAYETTE HA-55 AIRCRAFT RECEIVER

Listen To Aviation Control

Towers and Aircraft





8 Tubes for 11-Tube Performance Two RF Stages with A 6CW4 Nuvistor For High Sensitivity

Solid State Power Supply
Built-in Adjustable Squelch
Illuminated Stide Rule Gial For Night Operation
Built-lin 4" Speaker With Front Panel Phone Jack

Now monitor the exciting frequencies of aircraft communications in your Now monitor the exciting frequencies of aircraft communications in your home or office with this deluxe receiver. The use of multi-purpose tubes gives 11 tube performance offering high sensitivity and selectivity. Two RF stages including a 6CW4 nuvistor really pulls in the stations. A variable squelch adjustable from front panel facilitates absolute quieting. A built-in 4" speaker provides excellent voice reproduction, and a front panel phone jack makes private listening possible. Large, easy-to-read stide rule dial is illuminated for night operation. Attractive buegrey metal cabinet. For 117 volts AC at 50/60 cps. Size 11½6x51/4x73/6". Shpg. wt., 14 ibs. 99 H 2527WX Model HA-55 108-135 Mc Net 59.95

B & W 550A ANTENNA COAXIAL SWITCH



No Loss When Switching Antennas

Lets you instantly select any one of five transmitters, antennas, exciters, receivers, etc., using 52 or 75 ohm line. The switch handles up to 1 kw of modulated power with a maximum crosstalk of —45 db at

30mc. 40 H 1602 Shpg. wt., 2 lbs. Net 8.25 40 H 1603 Model 902-Knob for 550A Net .36 40 H 1604 3818-Dial plate for 550A Net .36

SUPEREX AMATEUR PHONES



Comfortable poly-foam ear cushions. 600 ohm impedance. High sensitivity and crisp, clear reproduction for that hard to read station. Shpg. wt., 2 lbs. 40 H 8501

Net 24.95

TURNER 454X



Engineered for the SSB operator. Wired for PTT, the 454X features two separate switching arrangements—push-to-talk, and a lever-lock switch to hold the mike live. Responses: 300 to 3000 cps. Output level: 48 db. 44 H 7001

Lafayette Cat. No. 651 121

NEW LAFAYETTE DELUXE COMMUNICATIONS RECEIVERS

LAFAYETTE Professional-Quality 8-TUBE AMATEUR COMMUNICATIONS RECEIVER



• 8 Tube Superhet Circuit • 1 RF + 2 IF Stages for High Gain Reception • Easy-to-Read, Illuminated, Slide Rule Dial • Builtin Q-Multiplier for Crowded Phone Operation • Antenna Trimmer for Optimum Performance on All Bands • Calibrated Electrical

Outstanding Bandspread, Selectivity with built-in Q-multiplier, and sensitivity combine to make the HA-230 one of the "hottest" general coverage bandspread receivers we have ever offered. Special filament transformer provides continuous voltage on critical oscillator and mixer stages, maintains frequency stability transformer provides continuous voltage on critical oscillator and mixer stages, maintains frequency stability . . . prolongs tube life . . . faster "warmup." For the crowded amateur bands—illuminated Slide Rule Dial, bandspread with markings every 5 KCS on 80 and 40 meters, every 20 KCS on 20 and 15 meters, and every 50 KCS on 10 -meters, plus an edgewise S-meter. For the SWL—a 0-100 logging scale for "instant reset" to a desired station, an RF Stage with an antenna trimmer for peak performance PLUS 2 IF stages for improved selectivity. Receiver sensitivity—1.0 microvolts for 10 db Signal-to-Noise Ratio. The Built-in BFO can be used to separate CW stations by means of the pitch control, while the Q-multiplier adds the selectivity needed for crowded phone band operation. Front the selectivity needed for crowded phone band operation. Front panel controls: FUNCTION SWITCH, AUDIO GAIN, SELECTIVITY (O-

MODEL HA-230 WIRED

\$8 Monthly

MODEL KT-340 KIT

\$7 Monthly

4 BANDS:

550-1600 Kc 1.6-4.8 Mc

• 4.8-14.5 Mc 10.5-30 Mc

NEW "ALWAYS ON" FILAMENT VOLTAGE FOR MIXER AND OSCILLATOR STAGES FOR FREQUENCY STABILITY

Bandspread on Amateur Bands 80 thru 10 Meters • 0-100 Logging Scale for SWL's • Effective Automatic Noise Limiter • AVC-MVC Selector on Front Panel • Stable Oscillator and BFO for Clear AM CW and SSB Reception

Built-in Edgewise S-Meter

Multiplier), FREQUENCY (BFO), BAND SELECTOR, IF GAIN, TRIMMER, AVC-MVC SWITCH, ANL SWITCH, MAIN TUNING, BANDSPREAD TUNING, and headphone jack, Selectivity—60 db at 10KC, 0.8 KC @ 6db (with Q-multiplier), IF—455KC, Speaker—External PM type (not supplied), 4 or 8 ohms impedance, Audio Output—1.5 Watts, Tubes: 3-6BAG, 2-6BEG, 1-6AV8, 1-6AV6, 1-6AQ5, 1-5Y3. Size—7Hx15Wx 10°D. For 105-120, 60 cps AC, 50 watts, Imported.

99 H 2522WX Shpg, wt., 25 lbs. Net 89.50
99 H 2532 Model HE-48 Matching 3x5" speaker. 4 lbs. Net 7.95

KT-340 SEMI-KIT

This receiver is also available in kit form with all major components and front end premounted and pre-calibrated. Minor components are easily installed, Imported 99 H 2521WX Model KT-340, Semi-Kit

DELUXE LAFAYETTE Professional-Quality 14-TUBE AMATEUR COMMUNICATIONS RECEIVER New!



HA-225

Delivery January 15, 1965

NEW "ALWAYS ON" FILAMENT VOLTAGE FOR MIXER AND OSCILLATOR STAGES FOR FREQUENCY STABILITY!

5 BANDS

150-400 Kc • 1.6-4.8 Mc 10.5-30 Mc • 4.8-14.5 Mc • 48-54 Mc

As Little as \$6 Monthly

Dual Conversion On 6 Meters

And Q-Multiplier Circuits (Can be Used Simultaneously) Crystal Calibrator For Checking Receiver Calibration Markings
 Improved Automatic Noise Limiter
 Voltage Regulated Power Supply

control of HA-225 with a transmitter. Front Panel Controls: AF Gain, RF Gain, 5-Position Function Switch, BFO Frequency, Band Selector, Q-Multiplier Selectivity, Q-Multiplier Frequency, Band Spread Tuning, Main Tuning; Antenna Trimmer, Power On-Off Switch, MVC-AVC Switch, Rec-Send Switch and Headphone jack, IF — 455 KC. Audio Output — 1.5 Watts. Output Impedance — 8 and 500 ohms (speaker not supplied). Tubes: 4-6AQ8. 3-6BA6, 2-6BE6, I-6BL8, I-6AL5, I-6AQ5, I-OA2 plus 6CA4 rectifier. Size: 17Wx7½Hx10°D. Shop. wt. 28 lbs. Imported.

hot supplied. 1-0A2 plus 6CA4 rectifier. Size: Shpg. wt. 28 lbs. Imported.
99 H 2523WX Model HA-225. Less Calibrator Crystal Optional Calibrator Crystal, 100KC, Type HC/13U

40 H 0901L 99 H 2532 Model HE-48 Matching 3x5" speaker, 4 lbs.

• 14-Tube Superheterodyne Circuit • Extra RF Stage, Mixer/ Osc For Dual Conversion On 6 Meters • 1 RF Plus 2 IF Stages For High Gain Reception On All Other Bands . New Product Detector Circuit For Improved SSB Reception • Separate BFD

The HA-225 features full amateur band coverage of 80 through 10 meters plus Marine Beacon Band. Special filament transformer provides continuous filament voltage to oscillator and mixer tubes . . . vides continuous filament voltage to oscillator and mixer tubes . . . maintains critical frequency stability . . prolongs tube life . . . reduces warmup time. Sensitivity is . 5 Microvolt for 10 db s/n ratio. Selectivity is variable from 60 db to 93 db in Q-Multiplier operation with ± 10 KC detuning. Calibrated electrical bandspread on amateur bands 80 thru 10 meters (6 meters is tuned with main tuning controls). Dual conversion on 6 meters provides average of 50 db image rejection. Other features include antenna trimmer for optimum performance on all bands, built-in edgewise "5" meter, special recording jack in rear permits easy connection to tape recorder, remote control socket on the back allows simultaneous

Lafayette Cat. No. 651

Lafayette is Headquarters For the Radio Amateur

NEW! LAFAYETTE 10-80 METER DUAL CONVERSION

AMATEUR RECEIVER Model HA-350 with Mechanical Filter For High Selectivity

s9 monthly

Mechanical Filter for Exceptional Selectivity

Dual Conversion • 12 Tubes

Complete With Crystals For 80, 40, 20, 15 and 10 Meters

Product Detector-Selectable Upper Lower Sideband Reception

100 KC Crystal Calibrator and Crystal BFO


Automatic Noise Limiter . WWV Reception

"S" Meter-Calibrated in "S" Units 1-9 and OB scale to +40 db

HAM BANDS PLUS WWV

3.5-4.0Mc 21.0-21.5Mc 7.0-7.5Mc 28.5-29.1MC 14.0-14.5Mc WWV at 15Mc

MECHANICAL FILTER



Lafayette Deluxe 7-tube SWL Broadcast Receiver



\$6 monthly

Model HA-63 Electrical Bandspread on the 80, 40. 20. 15 and 10 Meter Bands

> A Handsome Feature-Packed Receiver For the Shortwave Listener and Novice

4 BANDS

• 550 kc-1600 kc • 4.8 mc-14.5 mc 1.6 mc-4.8 mc
 10.5 mc-30 mc

 Superhet Circuit; Illuminated "S" Meter • 1.5 Microvolt Sensitivity • 3-Section Tuning Capacitor With Elec- Antenna Trimmer For Optimum trical Bandspread Performance On All Bands • Front Panel AVC-MVC Selecor, ANL and BFO • For Headphones or External Speaker
• AC Transformer Operated • Big Slide Rule Dial

Provides full fingertip coverage of AM broadcast, marine and aeronautical bands, civil defense, WWV, amateur and foreign frequencies. The BFO permits (CW) code reception too. BFO pitch is not variable. Full electrical bandspread on all frequencies with 0-100 logging scale and built in "S' meter assures you of accurate tuning. Superheterodyne circuit includes RF amplifier and three-section tuning gang condenser with separate tuning coils for each band. These provide outstanding selectivity and a sensitivity of 1.5 microvolts. Big silder-rule dial is easy-to-read. Other features are switchable AVC/MVC to reduce blasting or fading; automatic noise limiter (ANL) for maximum noise rejection; and an antenna trimmer control which assures optimum reception on all bands. All controls are conveniently located on front panel. Headphone jack for private listening. An external PM type speaker is required (not supplied). Impedance 4-8 ohms. Beautifully styled in modern steel cabinet. Tubes: (2) 6BA6, (2) 6BE6, (2) 6AV6, (1) 6AR5 plus selenium rectifier. Audio output: 1.5 watts. AC transformer operated. 117 volts 50/60 cycles AC. Size: 13Wx7-4/5Hx10°D. Shpg. wt., 19 lbs. Imported.

99 H 2534WX 99 H 2532 Model HE-48 Matching Speaker



HE-48 SPEAKER

3" x 5" speaker in handsome styled cabinet for Lafayette HE-30, KT-320, HE-80, HA-63, HA-350 receivers, also ideal receiver speaker mate for many other communication receivers. Gives clean audio response. 8 ohm impedance. 734 Hx3½Wx5″D. 4 lbs. Imported. Shpg. wt., 99 H 2532 Net 7.95

Lafayette Cat. No. 651 123

LAFAYETTE AMATEUR STATION ACCESSORIES

STRENGTH METER

LOW. LOW PRICE



Measures SWR, Relative Forward And Reflected Power to 1 KW

Reads Field Strength

A handy 2-in-1 meter for use in the amateur radio station to check transmitters for SWR measurements, Can be left continuously in the circuit for monitoring transmitter outputs, SWR: 1:1 to 3:1; Accuracy ±5 db, 2 to 30 MC; Impedance: 52 Ohms; Antenna: 5-section, collapsible. Comparative RF field strengths can be easily determined with this fine meter. Sensitive 100 micro-ammeter movement with easy to read 2-color dial. Impedance matches 52 Ohm coaxial lines. Attractive arev hammertone aluminum case. Size: A handy 2-in-1 meter for use in the amagrey hammertone aluminum case. Size: 134Wx5%4Hx21/4"D. Shpg. wt., 1 lb. lmported.

99 H 2537 Net 12 95

LAFAYETTE ALL-BAND VERTICAL TUNEABLE 10 TO 80 METERS ANTENNA

Made in U.S.A.

- 10 To 80 Meters
 For Fixed Operation Omni-Directional,
- Vertically Polarized
 Irridite Treated To

1495 Mil Specs

LOW, LOW PRICE

Our best buy multi-band antenna. Can be tuned to any amateur band 10 through 80 meters by a single adjustment. Has amazing efficiency for DX or local conefficiency for DX or local con-tacts. Ground or roof top or tower installation. Can survive winds in excess of 50 mph. Over-all height 18': knocks down to only 5'. Uses 3½'' diameter air wound coil as matching induc-tor. All steel parts irridite treat-ed to Mil Specs. Impedance 52 ohms. Maximum power 1000 watts AM or CW—2 KW PEP. Omni-directional vertically not. Omni-directional, vertically pol-arized, Shpg. wt., 5 lbs. 40 H 0104WX Net 14.95

LAFAYETTE SEMI-AUTOMATIC "BUG"



SUPER SPEED KEY

A quality "Bug" designed for clear, A quality "Bug" designed for clear, easy sending and wide range of speed. 7 adjustments for speed and comfort. Precision-tooled, anti-rust nickel-plated brass and stainless steel operating-parts. Speed adjustable 10 wpm to as high as desired. 1/2" silver contacts; weight scale for reproducible speed settings. 6/26Lx3Wx21/4"H, exclusive of knobs and feet. Shpg. wt., 31/2 lbs. Imported. Imported

Net 9.95

LAFAYETTE "PRECON" AMATEUR PRESELECTOR CONVERTER

The "Precon" is a crystal-controlled dual function unit for the price of one. As a preselector, it can be used ahead of any

receiver to greatly improve gain, image rejection, and sensitivity. Tuned inter-stage circuits and 2 stages of RF amplifi-

cation assures a high signal-to-noise ratio

... As a converter, receiver range can be extended to 30 MC (receiver must tune

\$5.00 Monthly Band Spread

• Crystal Controlled • For 80-40-20-15-10 Meter Bands • As a Converter-Converts Receiver to Dual Conversion Operation • improves Selectivity . Widens

3.5-5.2 MC). Sensitivity and stability are excellent. Antenna trimmer on front panel. 3 crystals are included for 20, 15 and O-meter bands. 52-ohm antenna co-axial connector is built-in. PL-259 connector required for output cable. Attractive modern steel cabinet with 4 rubber feet. Operates on 117 V 50/60 cycles. AC. Size: 10Wx6Hx8"D. Shpg. wt., 10 lbs. Imported. 99 H 2530 Net 49.50

LAFAYETTE 6 and 2 METER VFO

Voltage Regulated For Stability

A Deluxe Self-Powered VFO For 6 and 2 Meters

A high quality variable frequency oscillator designed to operate with modern transmitters using crystal oscillators in the 8-9 Mc region. It provides dependable coverage of both the 6 and 2 meter amateur bands. High electrical stability is achieved by a series-tuned clapp oscillator. OB2 voltage regulator tube protects unit from line voltage variations. Completely self-powered, needs no power from your rig. Uses low-heat half-wave silicon rectifier. Illuminated plexiglass dial is calibrated from 50-54 Mc (6M) and 144-148 Mc (2M). Output voltage is 10-15 V rms. Tubes: 68A6, OB2. Rigid mechanical construction. Complete with 24" low loss coaxial cable. For 117 Volts 50/60 cycles AC. Size: 64/4Wx44/2Hx 4"D. Shpg. wt., 6 lbs. Imported. 4"D. Shpg. wt., 6 lbs. Imported.

NEW! LAFAYETTE DELUXE SELF-POWERED VFO

Covers 80 through 10 Meter Amateur Bands

High Dutput to Drive Any Modern Transmitter

A deluxe variable frequency oscillator providing full coverage of the five bands from 80 to 10 meters. Employs a high "Q" series tuned Clapp oscillator, remarkable for its low drift. A VR tube eliminates fremarkable for its low drift. A VR tube eliminates frequency shift due to variations in line voltage. High output of 10-20 volts is sufficient to drive any modern transmitter. Features large easy-to-read illuminated slide rule dial with smooth tuning drive. Dual output impedance. Low heat silicon diode power supply prevents drain on transmitter power supply. Tubes 6AU6, 6AQ5, 0A2. Size: 61/2WX51/4HX71/2*D. For 117 volts 50/60 cps AC. Shpg. wt., 71/2 lbs. imported. 99 H 2501 Net 34.50



NEW! LAFAYETTE NUVISTOR GRID DIP METER

Complete with All Coils

Nuvistor Oscillator

Compact, True One-Hand Operation

Slim Color-Matched Coils for High Accessibility

Covers 1.7 to 180 MC In 6 Bands

A compact unit designed for easy circuit coupling in hard-to-reach places. Thumb tuning, Sensitive Nuvistor oscillator/de-tector is ideal for checking resonant frequencies of tuned circuits, detecting stray resonant requencies of tuned circuits, detecting stray resonances in transmitters, checking neutralization. Frequency range 1.7 to 180 MC in 6 accurately calibrated ranges. Powered by built-in 117V AC 50/60 cycle transformer power supply with silicon rectifier. Precision plugin coils supplied in protective case. Solid finish aluminum panel, Size: 2¾Wx5½Lx1¾"D. Shpg. wt., 2 lbs. Imported. 99 H 2503



LAFAYETTE QUALITY METERS AND TESTERS

for the CB'er & AMATEUR - Improved Performance - Low, Low Prices

LAFAYETTE MINIATURE ILLUMINATED MODULATION "S" METER



- Combination "S"
 Meter, % Modulation

 Meter and RF Power
 Output Meter
- Accurate D'Arsonval Movement
- Jewel Bearings

295

Highly accurate. Features wide viewing angle and 3-color scale. Front panel zero adjustment. Calibrated scales (1 MA full scale), 0 to 100% modulation, "S" units 0-9, also +10 and +30. Linear full scale markings of 0 to 5. Dimensions: dial face, 15%"; depth 11/4" overall. Supplied with 4 mounting screws and lugs. For 6 or 12 volts. Dust resistant case. Shpg. wt., 8 oz. Imported. 98 N 250?

LAFAYETTE RADIO FIELD INDICATOR



A MUST FOR ALL

 Continuously indicates transmitter autput e Rugged 200 μa meter rovement e Requires no Electricity, Batteries, or Transmitter Connection e Powerful Magnet on Bottom Plate for Meunting on Dashboard or Other Metal Surface

> Our Low, Low Price

675

MAM ANO CB OPERATORS
Checks performance of your marine, mobile or fixed transmitter. Features a 200 μa meter movement with variable sensitivity control. Earphones can be plugged in for an aural check of output. Antenna extends from 3½" to 10¾". Powerful magnet allows easy mounting. Use anywhere . . requires no electricity or batteries. Dimensions: (less antenna) 3½Wx2½Hx2″D. Imported.

99 H 2509 Shpg. wt., 7 oz. Net 6.75 99 H 2515 High output crystal earpiece for above 1.09

LAFAYETTE WAVE-METER for AMATEUR and CITIZENS BAND



• For Amateur and CB Use • Instant Readings of Transmitter RF Output • Requires Ne Power • Compact, Portable, Accurate

6⁷⁵

LAFAYETTE MINIATURE ILLUMINATED "S" METER



- Jeweled Bearings
 Clear Plastic Front
- Accuracy 2% of Full Scale
 High Quality D'Arsonval Movement

OF

Durable wrap-around plastic front panel provides wide-angle readability. Zero adjustment screw on front panel; jewelled bearing movement. Calibrated in "S" units from 0-9 with the scale terminating in +10 and +30 calibrations. Additional full scale calibrations of 0-5 and 0-10 in linear scale divisions. Silvered dials; black numerals and pointers. Illuminating lamp for either 6 or 12 volt operation. 196" dial face; 11/4" overall behind panel. Supplied with mounting screws. Imported. Shops. Wt., 8 oz.

99 H 2513 Net 2.95
See Our Catalog 650 For Additional Electronic Components

SWR BRIDGE AND RF POWER METER

- FIREITEETEE

21⁹⁵

Highly accurate SWR and direct power readings up to 50Mc. The unit may be permanently inserted in the transmission line for SWR and retative power monitoring. For 52 or 75 ohm lines. Insertion loss is negligible. Meter has 50 μ a movement: calibrated directly in watts from 0.15 and in SWR from 1 to 10 IF (reads infinity at full scale) . . . Housed in an attractive grey metal cabinet, 34xx 74xx 234". Sits on 4 rubber feet. Imported.

LAFAYETTE TRANSISTORIZED FIELD STRENGTH METER

 Permits Easy Tune-Up For Maximum Transmitter Output • Earphone Jack to Monitor Audio • Tuned Input from 2.53 to 57 MC

15⁹⁵

Covers 2.530 Mc to 57.000 Mc in 3 bands. Ideal for use with ham, Citizens Band or other transmitters within this frequency range. Enables user to tune his transmitter and antenna for maximum RF output. 200 µa meter is calibrated from 0 to 10. Earphone jack provided. Front panel controls: gain on-off switch, funing, and band selector switch. Battery powered—can be operated anywhere. With telescoping antenna and battery, Imported. Shpg. wt., 2 lbs. 99 H 2510

99 H 2515 Migh output earpiece for above Net 1.99

99 H 2515 High output earpiece for above 32 H 4802 Replacement battery for above

DELUXE LAFAYETTE "S" METER

● New for Hams, SWL's and CB'ers—A Signal Strength Meter Using VTVM Principles ● Easy To Install and Operate ● Magnetic Feet For Mobile Dashboard Mounting ■ Sensitivity and Zero Adjust Controls

Only **8**95



Net

Designed for use with any superheterodyne receiver employing AVC. Meter is calibrated in "S" units from 1 to 9, and in db up to 30db over \$9. Partial peak clipping is provided for noise limiting. Simple installation—B+, filament and ground. It is adaptable to either 6 or 12-volt equipment, and to receivers using 150 ma or 300 ma series string filament systems. Requires 150-200 VDC for B+. Complete with 12AU7 and installation instructions. Imported. Shpg, wt, 2 lbs.

99 H 2512

Net 8.95

ILLUMINATED COMMUNICATIONS "S" METER

- 2 Jewel Movement
- Clear Plastic Front
- Calibrated to S9 + 40 db

395

A quality "S" meter (basic 1 ma, 2 jewel movement) designed to replace many "S" meters used in communications receivers. Clear plastic front measures 236" square and meter fits standard 24" round hole. Perfect for the experimenter and amateur. Complete with mounting screws, instructions for installation and use. For 6 volt or 12 volt operation. Zero adjustment control on front panel. Imported. Shpg. wt., 1 lb.
99 H 2514

Lafayette Cat. No. 651 125

LAFAYETTE MOBILE CITIZEN BAND ANTENNAS

LAFAYETTE ALL STAINLESS STEEL CB MOBILE ANTENNA

THE SCOOP BUY FOR ALL CITIZENS BAND MOBILES



R95

OUTSTANDING **FEATURES**

- 102" Stainless Steel Whip For Optimum 11-Meter Performance
- Heavy-Duty Chrome Plated Stainless Steel Spring
- Chrome Plated Swivel Ball Jointed

Chrome plated swivel mount base designed to be mounted on any surface. Stainless steel spring holds rod in properly adjusted position and prevents rod damage from shocks and blows. Stainless

NEW LAFAYETTE BASE LOADED "AUTO-TOP" CITIZEN BAND ANTENNA

- Automobile rooftop application affords ideal Omnidirectional signal pattern
- Mounts neatly from outside vehicle 34" hole
- Base loaded Phasing Transformer completely weatherproof
- 39" Stainless Steel whip

Only

MADE IN U.S.A.

The new Lafayette Base Loaded "Auto-Top" Citizen-Band antenna offers the CB'er the Ideal omni-directional signal pattern with very low signal to noise. This quality antenna consists of an inconspicuous base loaded, neutral gray weatherproof phasing transformer (only 4" high, and 1" in diameter), a 39" stainless steel whip, and all mounting hardware including complete and simple mounting instruction sheets. Antenna mounts in 34" hole. Comes less cable, Shpg. wt., 2 lbs.
42 H 0120 Net 7.99



Superb Lafayette Fiberglass 48" CENTER LOADED CITIZENS BAND COWL MOUNT ANTENNA

> MADE IN U.S.A.

- Rugged Fiberglass Construction
- Easily Mounts On Cowl or Rear Deck

Lafayette makes antenna news with this ideal center loaded fiberglass antenna—only 48" high but performs like 102" antennas. Designed for cowl mounting, this latest development in mobile antennas provides an excellent radiation pattern. Substitutes for conventional ¼ wave whips as well as base-loaded antennas in the 27 mc band. The four foot whip eliminates the possibility of striking overhead objects. A black plastic covering of whip insures against shorting. Specially designed rocker support assures 8-point grounding and permits mounting up to 35° angle on fender, cowl or rear deck—fits any 1%," to 1¼" mounting hole. Complete with 5 ft. of RG-58/U cable.

NEW! LAFAYETTE "PROFESSIONAL" DOUBLE CHAIN BUMPER MOUNT CB ANTENNA

THE LONG-LIFE BUMPER MOUNT ANTENNA THAT FITS THEM ALL!

· Heavy Outy Double Chain Bumper Mount

Heavy Outy Aluminum Plated Spring
 102" Stainless Steel Whip
 Includes Whip Hold-down Clip

Complete heavy duty double-chain U.S.A. bumper mount assembly. No holes to drill; assembles in minutes. Consists of professional heavy-duty double-chain bumper mount with "2" shaped links, cadmium plated shock abooth links, cadmium plated shock absorb-ing springs that can bend through 90° without damage, 102" stainless steel whip with removable plated steel adapter and whip hold-down gutter clip. Built for long, satisfactory service and performance. Less cable. Shpg. 42 H 0119WX wt., 8 lbs.

Net 15.95



LAFAYETTE CB BUMPER MOUNT ANTENNA WITH STAINLESS STEEL STRAP

- Chrome Plated Bumper Mount with Stainless Steel Strap 102" Stainless Steel Whip, Heavy Outy Chrome Plated
- Stainless Steel Spring

An outstanding Lafayette CB antenna featuring a full-size 102" stainless steel whip and a fully adjustable chrome plated mount with a stainless steel strap which was specially designed to fit most cars. Heavy duty chrome plated stainless steel spring is built for ex-tremely rugged mobile use. Shpg. wt., 3 lbs. Imported 99 H 3032WX Net 8.95



UNIVERSAL LAFAYETTE CITIZENS BAND **AMATEUR SPRING &** SWIVEL BALL-MOUNT BASE

Chrome Plated Swivel Ball Jointed Mount Base Universal Lafayette chrome plated swivel ball

mount base with lug terminals for use with mobile antennas, Can be mounted vertically or horizontally on any surface. With lug terminals for use with mobile antennas. Imported. Shog. wt., 3 lbs. 99 H 3030



Heavy-Duty Chrome Plated Stainless Steel Spring Universal Lafayette Heavy duty chrome plated Stainless steel spring. Provide maximum support for long whips and heavy center-loaded whips. 99 H 3036 Imported. Shpg. wt., 2 lbs. Net 7.90

LAFAYETTE BASE STATION CITIZENS BAND ANTENNAS

FAMOUS LAFAYETTE "STARFIRE V" DELUXE 5 ELEMENT CITIZEN BAND BEAM ANTENNA



Check these outstanding specifications

ELECTRICAL

- GAIN—10db Forward gain
- F-B ratio: —25 db
- V.S.W.R. under 1.5:1 across 27MC hand
- Gamma Matched to 52 ohm Coax Transmission Lines

MECHANICAL

- Boom Length 17'
- Height: 18'6"
- Turning Radius: 8'6"
 Mounts on Masts up to 2"
- Mounts on Masts up to 2" in diameter
- All aluminum construction

The STARFIRE "V" 5 Element vertical beam is one of the most powerful CB antennas ever offered by Lafayette. Tremendous forward gain multiplies your effective radiated power by as much as 10 times. Front-to-back ratio 25 db. V.S.W.R. under 1.5:1. Gamma matched to 52 ohm coax-transmission lines. All aluminum construction for greater weather resistance. Boom length 17 ft. Reflector element (highest 184/2 feet. Mounts on masts up to 2" in diameter. Turning radius 8'6". Vertical wind load 125 lbs. STARFIRE "V" is furnished with complete mounting instructions. Less mast and coax cable. Shpg. wt., 15 lbs.

Net 37.95

NEW LAFAYETTE "RANGE-BOOST"TM END FED 1/2-WAVE CB ANTENNA



Static Clover Leaf

AMAZING PERFORMANCE AT ONLY

19⁹⁵



- 3.75 db True Omni-Directional Gain
- Forward Power Measurement—5 watts
- VSWR—1.17

The "Range-Boost" V2-wave CB base station is the latest addition to Lafayette's famous line of high performance CB antennas. Specially designed anti-static cover-leaf ball drastically reduces receiver noise by continuous dissipation of static discharge. Offers a 3.75 db true omni-directional gain. Forward power measurement: full 5 watts; VSWR is 1.17. Includes a phasing transformer, rubber covered for moisture resistance. Vertical radiator consists of 3 seamless aluminum tube sections topped by a solid aluminum 108" top section. 3 54" radials provide proper transmission line decoupling. Direct ground lightning protection. 50 ohm. 176" over-all length. Accepts PL-259 cable connector. Shgs. wt., 10 lbs. Net 19.95

LAFAYETTE'S "STAR-FIRE" T.M. 3-ELEMENT VERTICAL BEAM CB ANTENNA

16⁹⁵

and Install
Steel Part
to MIL Spe

Completely Precision Tuned and Ready to Assemble and Install

Multiplies Power 8 Timés

Steel Parts Irridite Treated to MIL Specs

An exceptionally high gain, directional antenna system for Citizen's Band communications. It develops a forward gain of 8 db. Front-to-back ratio is 25 db; front-to-side, 40 db. 50 ohm feedline match for maximum efficiency. Comes with bracket for vertical or horizontal mounting. The $144^{\prime\prime}$ O.D. aluminum boom is 8 feet long. $56^{\prime\prime}$ to $76^{\prime\prime}$ O.D. aluminum elements are approximately $1612^{\prime\prime}$ ft. long. All steel hardware is irridite treated to MIL specs. Completely factory pretuned, the "Star-Fire" is furnished with complete instructions. Shgg. wt., 11 lbs.

Deluxe LAFAYETTE GROUND PLANE ANTENNA



The Ideal Antenna For Your CB Gase Station

High Efficiency Ground Plane Antenna

All Aluminum Construction Accepts PL-259 Connector

Accepts PL-259 Connect 1 1 95

Solid aluminum 108" heat-treated radials and radiator. Elements supplied in two 54" lengths joined by threaded coupling nuts. Radials droop for 50 ohm match. Accepts 11/4" tubing RG-58/U cable and PL-259 connector. Shpg. wt., 4 lbs. Imported. Net 11.95

20 FT. COAXIAL CABLE ASSEMBLIES FOR CITIZENS BAND EQUIPMENT

249 (A)

A) These cable assemblies are necessary for connection between Citizens Band Transcoiver and Antenna.

2¹⁵

TYPE A—Consists of 20 ft. RG-58/U cable with PL-259 plus UG-175/U on both ends. Required for Ground Plane and Ccaxial and Mobile Antennas terminating in a coaxial jack. Shpg. wt., 8 oz. 42 H 7001 Type A; 20 ft. length Net 2.49 TYPE 8—Same as type A except one end is terminated with PL-259 plus UG-175/U and other end with universal ring type terminal lugs for mobile antennas. Shpg. wt., 8 oz. RECOMMENDED FOR USE WITH LAFAYETTE ALL STAINLESS STEEL MOBILE ANTENNA ABOVE. 42 H 7002 Type B; 20 ft. length Net 2.15

Lafayette Supplies Fine Citizens Band Equipment at Low Cost

Lafayette Cat. No. 651 127

SELECTED LAFAYETTE CB ANTENNAS AND CRYSTALS

LAFAYETTE CITIZENS BAND WALKIE-TALKIE ANTENNA REPLACEMENT GUIDF

• Fits All Lafayette and many Famous name Walkie-Talkies

Designed for the various Lafayette "Walkie-Talkie" portable CB Transceivers indicated. Will also fit many of the other "Walkie-Talkie" units manufactured by companies other than Lafayette. Check the specs of the antennas listed on the chart below for the antenna best suited to your present "Walkie-Talkie." Average shpg. wt., 1 lb. Imported.

Antenna Stock No.	Sec- tions	Oiam. of Base	Collapsed Length	Extended Length	For Lafayette Walkie-Talkie Models	Net- Ea.
99 H 3008	12	1/2	6	5234	HE-29, HE-29B	1.95
99 H 3037	11	1/2	61/4	541/2	HA-60, HA-61, HE-86, HE-88	1.95
99 H 3038	9	7/4	71/4	5234	HE-75, HE-88	1.95
99 H 3039	11	%6	5¾	50	HE-66, HE-82, HE-83	1.49
99 H 3040	9	3/8	5%	431/4	HA-70	.98
99 H 3041	11	3/6	534	51	HE-29C ·	1.95
99 H 3017	10	₹6	7	58	HA-150	1.95
99 H 3007	" 11	3/6	71/4	6234	HA-300	2.25

LAFAYETTE CHROME PLATED MOBILE BUMPER MOUNT

with Stainless Steel Strap

• Completely Adjustable For Use
With Most Types of Automobile Bumpers

Highly Reliable and Durable!

An outstanding Lafayette mobile Bumper Mount featuring chrome plated mount and stainless steel strap which is completely adjustable for vertical mounting on most types of automobile bumpers. Eliminates need of cumbersome link type chain mounts. Shog. wt., 1½ ibs. 98 H 3035 Imported ... Net 3.95

LAFAYETTE TELESCOPIC C B 395 WHIP ANTENNA

Sturdy, attractive chrome plated whip antenna that telescopes from approx. 45" fully extended to only 15" to facilitate portability and storage. Ideal for shorter distances up to several miles. Has enclosed base loading coil for proper impedance matching. Complete with removable P1-259 conjector that permits direct top, side or rear mounting to transceiver. Imported.

99 H 3015 Shpg. wt., 1 lb. Net 3.95

LOW-COST ECONOMY CB GROUND PLANE ANTENNA



ance in a Citizens Band base station antenna at a truly economical price. Incorporating a special "drooping radial" design for improved impedance characteristics, this excellent ground plane antenna utilizes a 360° polar pattern to provide complete coverage in any direction. Made-to-last construction features a rugged 1 inch diameter radiating element. A double U-bolt arrangement provides the strongest possible mount under the most severe conditions. 42 H 7401WX Shpg. wt., 6 lbs. Net 7.90



BLITZ BUG LIGHTNING PROTECTOR

Designed to fit any standard coaxial cable, the "Blitz Bug" employs the spark gap principle to eliminate static build up on coaxial cables. Provides a constant drain off, reducing chances of a direct lightning strike and in many cases eliminating noise problems. Constructed of 34" O.D. brass by 214" long. Employs one Pt-259 plug and one DKCB connector (takes Pt-259 plug.) Shpg. wt., 1 lb.

3 95

POPULAR CITIZEN BAND TRANSCEIVER CRYSTALS

Our low, low Price

2²⁵



A complete listing of transmitting and receiving crystals for the most popular Citizen Band Transceiver's and Walkie-Taikies on the market today. These crystals are available for any channel from 1 to 23. When ordering be sure to specify stock number and channel

	and the second second		shacily stack namebil	sum cusumel estiled	Net ea. 2.25
MODEL	TRANSMIT RECEIVE	MODEL	STOCK NUMBER TRANSMIT RECEIVE	MODEL	STOCK NUMBER TRANSMIT RECEIVE
Arkay Arvin Mod. 42R99	42 H 4201C 42 H 4233C	Hallicrafters CB-5A Hallmark Duo-Comm.	42 H 4215C 42 H 4227C	Lafayette HE-88,100A	42 H 4204C 42 H 4205C 42 H 4204C 42 H 4205C
Browning S-9 Browning T2700S	42 H 4201C * 42 H 4201C *	Haffmark 212, 512 Hammari HQ105TR	42 H 4201C 42 H 4233C	Lafayette HB111, 200 Lasaile, LA101,	42 H 4701C 42 H 4202C 42 H 4201C 42 H 4233C
Browning 23/9 Cadre C-75	42 H 4212C * 42 H 4223C		42 H 4201C *	Lasaile, LA101-AN Metrotck Starfire	42 H 4201C 42 H 4233C 42 H 4201C 42 H 4211C
Cadre 510, 510A Citifone CD5, CD6,	42 H 4213C 42 H 4224C 42 H 4214C 42 H 4225C	Heath GW-10, 11, 12,	42 H 4201C 42 H 4211C 42 H 4201C 42 H 4211C	Met "Spacestation" Philmore TC-90	42 H 4201C 42 H 4211C 42 H 4201C 42 H 4213C
Citifone CD7 Com Pak 800	42 H 4214C 42 H 4225C 42 H 4201C 42 H 4233C	Heath MW-33		Philmore TC-11, Philmore TC-6-12	42 H 4201C * 42 H 4233C 42 H 4201C *
Daystrom DM34B Demco CB 1A	42 H 4201C 42 H 4211C	Heath GW-30, R220	42 H 4216C *	Poly Comm. PC-11.	42 H 4220C 42 H 4231C
Demco TW110A .Eico 760, 760A	42 H 4218C * 42 H 4210C	Heath GW-31 Int. Exec. 10	42 H 4216C * 42 H 4216C *	Poly Comm. PC-11G, Poly Comm. PC-12G,	42 H 4220C 42 H 4231C 42 H 4220C 42 H 4231C
Eico 770, 771, 772, Eico 777	42 H 4214C 42 H 4210C 42 H 4214C 42 H 4210C	Int. Exec. 100A	42 H 4218C 42 H 4230C 42 H 4218C 42 H 4230C	Poly Comm. PCN-N, Poly Comm. PRO	42 H 4220C 42 H 4231C 42 H 4220C 42 H 4231C
	42 H 4201C 42 H 4233C 42 H 4201C 42 H 4233C	Johnson Mess. III	42 H 4215C 42 H 4235C 42 H 4219C 42 H 4235C	Poly Comm. PC-4 Poly Comm. PC-8	42 H 4220C 42 H 4231C 42 H 4220C 42 H 4231C
Fonet 102B Gen. Rad. MC-1.	42 H 4204C 42 H 4205C 42 H 4201C 42 H 4233C	Knight C-100	42 H 4201C • 42 H 4216C •	Radifon RT101 Regency CBM27	42 H 4201C 42 H 4233C 42 H 4201C
	40 11 40040 40 11 40000		42 H 4201C 42 H 4202C	Sampson T-110A	42 H 4218C •
Gen. Rad. MC-4, MC-5 Gen. Rad. Echo 9	42 H 4201C 42 H 4233C 42 H 4218C 42 H 4233C 42 H 4201C 42 H 4233C	Lafavette HE-15,15B	42 H 4201C 42 H 4202C 42 H 4201C *	Sonar D	42 H 4201C * 42 H 4233C
Globe CB100 Globe CB100A	42 H 4201C 42 H 4226C	Laffite HB-115, 115A Lafayette HE-20, 20A,	42 H 4201C 42 H 4202C	Teirad	42 H 4221C 42 H 4232C 42 H 4201C
	42 H 4204C 42 H 4205C 42 H 4215C 42 H 4227C	Lafayette 43, 90	42 H 4201C 42 H 4202C 42 H 4201C 42 H 4202C 42 H 4201C 42 H 4233C	Utica T, CII	42 H 4201C 42 H 4226C 42 H 4201C 42 H 4226C
Hallicrafters CB-3, Hallicrafters CB-3A,	42 H 4215C 42 H 4227C 42 H 4215C 42 H 4227C	Lafayette 29B, 66, B2	42 H 4201C 42 H 4233C 42 H 4201C 42 H 4233C 42 H 4204C 42 H 4205C	Vocaline ED276.	42 H 4201C * 42 H 4222C * 43 H 4222C *
Hallicrafters CB-5,	42 H 4215C 42 H 4227C		42 H 4204C 42 H 4205C		42 H 4222C * 42 H 4201C *

CITIZEN BAND HEADSETS AND MICROPHONES

NEW! CB SPECIAL SAFETY HEADSET-MICROPHONE



- Keep Both Hands on the Wheel at Ali Times!
- Listen and Talk with Perfect Ease

e LISTER AND TAIK WITH PETTECT EASE
For convenience and safety, the earphone is on the right hand side allowing the mobile operator to hear the traffic. The push-to-talk switch can be held in the hand permitting "both hands on the wheel" driving. No longer are mobile communications unsafe! The microphone is an efficient high impedance, high output, noise cancelling, ceramic type. Impedance of the dynamic earphone is 8 ohms and is housed in a high impact cycolac cup. The headband and earseals are removable permitting cleansing with mild detergents. Easily connects to Lafayette HE-20C, HE-43C, HB-111, and HB-200. Also connects to any other transceiver merely by connecting aerphone in place of speaker and the microphone to the microphone input terminals. Full instructions included, Shpg. wt., 2 lbs.

Net 29.50 Net 29.50

NEW! CB CRADLE HANDSET

• Attach To Side Df Transceiver Or To Car Dashboard

Weight-Actuated Cradle Switch Disconnects Speaker and Connects

Industrial CB - Equip Your Mobile Fleet For Convenient And Private Operation

As Low As 1975







MOUNT ON UNIT

Modernize your present fixed or mobile CB station with this new telephone style handset. Easily attaches to the dashboard, side of unit or even to a wall or panel in fixed station locations. A switch unit or even to a wall or panel in fixed station locations. A switch in the cradle automatically disconnects the speaker when the handset is lifted. This switch also connects the highly-sensitive earpiece element providing no loss in listening time and private—operatoronly, listening. The microphone, a high output ceramic type, is activated by means of a push-button push-to-talk switch on the standard model and a push bar switch on the deluxe model. Easily modified, if desired, so that speaker remains on until mike is activated. Ideal for use in heavy traffic, loud background noise areas, at home, or in the office. Easy to install—just plug into microphone jack and attach two wires to speaker circuit. Unit comes complete with coiled cord between handset and cradle and with standard microphone cable between cradle and CB transceiver. Excellent with Lafavette HE-20C, HB-40O. HB-410A. HB-111. HB-222. HB-333. HE-90. HE-43C, HB-200, HB-400, HB-115A, HB-111, HB-222, HB-333, HE-90, HE-15B. Shpg, wt., 2 lbs.
42 H 6501 Push-Button Actuator type Net 18.75

42 H 6502 Deluxe Push-Bar Type

Net 19.75 Net 21.45

LAFAYETTE CITIZENS BAND PUSH-TO-TALK NOISE CANCELLING CERAMIC MICROPHONE



Lafayette's noise cancelling, high output ceramic push-to-talk microphones are designed to reproduce clean, crisp audio with full modulation with as little clean, crisp audio with full modulation with as little noise pickup as possible. High level, high impedance output. Mooled, tough, gray Cycolac, TM, case assures long life and protection from accidental shock damage. DPDT switch. Wired for standard Relay Switching as used in Lafayette HE-20, 20A, 20B, HE-43, 43A, 43B, HB-11, HB-222, etc, or for Electronic Switching as used in Lafayette HE-20C, HE-90, etc. Size: 2½x7½x35½".
3-conductor coiled cord, 10" retracted, 1 conductor shielded. Complete with hang-up bracket and Amphenoi 91-MPM5L plug attached for Lafayette Transceivers. Shgs, wt., 1 lb. Made in U.S.A.
42 H 0115 For Relay Switching Net 5.88

LAFAYETTE DYNAMIC **CB PUSH-TO-TALK** MICROPHONE



Top quality dynamic microphone. Specifically designed for citizens band and communication transcelvers. High impedance dynamic transducer will not be adversely affected by heat and smooth frequency response of 100 to 11,000 cycles make it most suitable for communications work — indoors or out. Comes with a momentary push-to-talk switch, coiled rubber cable with a 5-prong plug and a convenient hang-up bracket. Shpg. wt., 1


TURNER 350C CB COMMUNICATIONS MIKE



ideal For CB Use With Push-To-Talk Switch

A rugged push-to-talk ceramic microphone wired for relay operation A rugged push-to-talk ceramic microphone wired for relay operation. Extra-tough polystyrene case; hanger button and standard dash bracket are included. Also neoprene coiled cord, 11 inch retracted, 5-ft. extended. Output, —54 db. Response, 80-7000 cps. Dark grey finish. Shpg. wt., 1 lb. Net 5.75

TURNER MODEL 254C CB **PUSH-TO-TALK CERAMIC MIKE**



or Electronic Switching Excellent for Lafayette

Push-to-Talk CB Transceivers



Attractive Ceramic microphone with DPDT push-to-talk switch plus lock switch for fixed station operation. 7' 3 conductor (one shielded) cable. Response 60-8,000 cps. Output level—52 db. Gray hammertone finish with chrome trim 73/4Hx3¾x5¼" base. Shpg. wt., 3 lbs. 44 H 7003 Net 13.82



transistorized dynamic mike that will A transistorized dynamic mise that will match its output and frequency response to your equipment and operational needs, providing increased range, rich modulation and improved audio quality. Impedance 1,000 ohms up. includes colled cable, clip, instructions. Size: 13/aDx41/2"L. Requires 4 Mallory Type RM-312 miniature mercury battery cells. Shpg. wt., 3 lbs.

44 H 3501 Mark I Microphone Mallory RM-312 battery (4 req.) 32 H 4809 Net 33.50

.24

Improve Your CB Performance LAFAYETTE HA-115

AUDIO COMPRESSOR AMPLIFIER FOR CITIZENS BAND TRANSCEIVERS



Made in U.S.A.

only

- For 6 volt, 12 volt or 117 volt Base and Mobile Transceivers
- Illuminated Meter Directly Reads Modulation Percentage
- Printed Circuitry, Advanced
- Works with all Popular CB Units

The audio compressor instantly and automatically increases the "talking power" by increasing the average modulation of CB transmitters. This, however is accomplished without the side effects of over modulation. Final power input remains within the legal 5-watt limit (as per FCC decree) but effective talk power is increased many times. This compressor amplifier is easily connected to CB transceivers operating on either 6 or 12 volts DC or 117 volts AC. Requires very little power for operation hence existing power supplies may be utilized. Comes complete with operating and installation instructions. 3Hx3%wx5"D. Shpg. wt., 2 lbs.

Net 25.95

LAFAYETTE SQUELCHER

Squeich that interference!



- Provides full squelch and noise limiting to most superheterodyne transceivers or receivers
- Vastly improves mobile transceivers when vehicle is in traffic
- Reduces noise from ignition systems and other sources

The Lafayette "Squelcher" noise eliminator was carefully designed to improve reception and reliability in most superheterodyne transceivers or receivers other than those using solid-state detectors. Recommended for the Lafayette NE-20A, HE-20B, HE-20C, HE-30, KT-320, HE-45, HE-45B, ME-90, HB-111, HB-200, and HB-222. Reduces noise from ignition systems and other sources. Quiets receiver when os signal is received. Vastly improves sensitivity of mobile transceivers when operating in traffic. Complete with 2 tubes (6AL5 and 12AX7) and instructions for installation. In satin aluminum with blue gray perforated cover. Furnished with cable. Size 2%,x3%,x44%". 42 H 0904 Shpg. wt., 1¼ lbs.

NEW "QUIETRON"

Transistorized Replacement for your CB Vibrator

- No vibrator Hash
- Longer Life
 Solid State (no moving parts)
 Almost no Mechanical Noise
- **More Efficient**

Marvelous replacement for CB and other vibrators. Eliminates bothersome hum and hash. This two transistor unit is so efficient that it will actually deliver more power out-put than a vibrator. Available in two models. Shpg. wt., 1 lb.

MODEL "N" QUIETRON VIBRATOR REPLACE-MENT where VIB Pin 1 is negative. For the following units; Gonset G11, Lafayette HE-15, Morrow CB 1, 2, 3, Regency CB 27, Johnson 127, 128, 129, Courier 1-M, Intl. Evec. 50, Heath GW-10, Poly-Comm PNC 12 2-12, Arkay SQ9, SQ9W, Dewald TR12, Vocaline FRC 400, 425, and Applico AR 9 425, and Apelco AR 9. 42 H 8202 "N" Quietron

LAFAYETTE AUTO-MARINE ENGINE NOISE SUPPRESSOR KIT



A Must For Mobile CB & Ham Operators
 14 Components Plus Hook-Up Wire

This easily installed kit will effectively sup-Inis easily installed kit will effectively sup-press ignition, generator and voltage regu-lator noise. Consists of 8 spark plug sup-pressors; 1 distributor suppressor; 1 voltage regulator suppressor; 4 coaxial capacitors; shielded cable and braid for wiring filter system. All necessary hardware and instructions for installation are included. Shpg. wt., 2 lbs. 42 H 0905

LAFAYETTE GENERATOR NOISE FILTER • Freq. Range 3-30 mcs • Simple to Install • Maximum Current 25 Amps • Adjustable

Enables quiet receiver op-eration for Citizens Band, Amateur and industrial frequencies. Standard quency range 3-30 mcs.
Maximum current 25 amps.
99 H 6018 Shpg. wt., 1 lb. Imported Net 2.49

AMECO MODEL PV-27 NUVISTOR PREAMPLIFIER

FOR 27 MC

• Over 20 OB Gain

The PV-27 Nuvistor Preamplifier will Improve The PV-27 Nuvistor Preamplifler will improve your gain and noise figure considerably when used ahead of your present citizen band receiver, or transceiver. 2 tuned circuits and a 6DS4 Nuvistor are used for a gain of 20 db and a noise figure of 2.0 db at 27 Mc. Power requirements are 100-150 V. at 8 ma. and 6.3 V. at .135A. Only 2½x3½x7". Shpg. wt.. 2 lbs.
42 H 6901 PV-27 wired & tested ... Net 13.67

B & W 424 LOW PASS FILTER



Designed to effectively reduce TVI-Radiated spurious and other undesirable signals higher than 35 MC are attenuated by at least 60 db—power rating: 100 watts max. Frequency Range: 1.5 to 30 MC, Impedance: 50/75 ohms (reversible) Size: 5x2x134". 42 H 1601 Shpg. wt., 11/2 lbs. Net 8.65

LAFAYETTE ALL-TRANSISTOR CITIZENS "WALKIE-TALKIE" MODEL HA-70A



GREAT FOR: HOME, HUNTING, FISHING, PICNICKING, CYCLING, CAMPING. GOLFING. ETC.

NOT A KIT - COMPLETELY WIRED Great fun for the kids! At a price even they can afford!

3 Transistors

Crystal Transmit

Sensitive Superregenerative Circuit

Our Low, Low Price





You Receive It! Attractive, Neatly Styled Plastic Case—Slip it Into Your Shirt

A great new CB challenge to young and old for countless exciting short range applications. This compact Lafayette Citizens Band Walkie Talkie is a .3-transistor transceiver with crystal control on transmit and with an efficient superregenerative receiver. Super-regenerative has minimum external ignition noise pickup when voice signal is being received. Excellent for camping, picnicking, hunting, fishing, golfing, surveying, cycling, construction and many other applications requiring up to 1/4 mile communications. Has Push-to-Talk Button, On-Off Switch and efficient speaker that is used as speaker and microphone. Complete with built-in telescope antenna, transmitting crystal, one 9-volt battery and plastic carrying case. Size: Approx. 5½x2½x1½f°. Shpg. wt., 1 lb. Imported.

99 H 3011L Model HA-70A

Net ea. 10.95

No Time Wasted in Building-Use This Terrific Little Walkie Talkie As Soon As

2 for 21.00



SOLID STATE

NOISE LIMITER

99 H 6021 Replacement battery for above

Pocket!

CDR AR-22 AUTOMATIC ROTOR FOR CITIZENS BAND

This heavy-duty rotor unit will handle antennas up to 150 lbs. Simply set the control unit pointer to the desired direction, and the antenna will automatically rotate to this position and stop. Perfect for TV, Ham or Citizen Band application. Rotor unit employs 12 heavy duty ball bearings in two 6½" races. Reversible clamps on rotor will take masts from ½" to 2". 0.D. Control unit is marked in compass points. N.S.E.W. NW, NE, SW, and SE. Housed in attractive brown plastic cabinet with rubber feet. For 110-120 volts, 50-60 cps AC. Requires 4 conductor cable. Shpg. wt., 14 lbs.

42 H 8605WX

New Deluxe CDR Model 7R-44 Reter

Deluxe Version of AR-22. Increased rotational torque. 48-ball bearing movement. Finished with famous CDR "HAM-M" Type control box. Dimensionally identical to AR-22. Shpg. wt., 18 bs.

4 conductor cable for AR-22 and TR-44 32 H 8910 100' coil

32 H 8911 less than 100' per ft. over 100' per foot Net

CB to AM **ANTENNA** COUPLER





LAFAYETTE "DUMMY" ANTENNA LOAD FOR CB TRANSCEIVERS

Specially designed network permits any Citizen's band mobile antenna to be used also for broadcast reception. No switching necessary. With SO-299 antenna receptacle, 2 ft. lead with coexial auto plug for broadcast radio connection and 2 ft. lead with PL-259 coaxial plug for transceiver connection. Shpg. wt., ¼ lb.

A 32 only indicate the following and transmitters up to 5 watts. It permits tune-up into a non-radiating element instead of into antenna—in compliance with F.C.C. regulations. Built-in Pl-259 coaxial plug is easily connected and disconnected from equipment. Shpg. wt., 1 lb.
42 H 0902 Net .38

A 52 ohm non-inductive load for testing and

Net 58.75

SUBMINIATURE

For Hams, C#'ers
 Suppresses Noise From Any Type Ignition System, Motors, Atmosphere

The Kolin solid state noise limiter is an extremely effective self-adjusting device, which suppresses impulse noise in your receiver when receiving AM. Small enough to mount directly inside most receivers, it will work on supply voltages of 6 to 220 volts AC or DC. Only 3 connections are required. A switch is used to disable unit in normal quiet areas. Works on all Tube and Hybrid receivers employing a diode detector. All necessary instructions and mounting hardware is supplied. Size: 13/6x 11/4x14/2.

42 H 4510 Shpg. wt., 8 oz. Net 7.95

Lafavette Cat. No. 651 -131

LAFAYETTE 9-TRANSISTOR SUPERHETERODYNE CITIZENS BAND "WALKIE TALKIE" MODEL HE-29C



2 For 49.95

- Transmits & Receives Up to 1.5 Miles
- Crystal Control on Both Transmit &
- Leather Case with Shoulder Strap
- **Push-To-Talk Operation**

Earphone for Personal Listening

Complete portable two-way communications for everyone, everywhere—hunting, fishing, boating, virtually all sports; at work in construction, warehouse, office, farm or for in-plant communications. Receives and transmits up to 1.5 miles under average conditions (no intervening obstructions.) Weighs only 16 ounces and slips into your pocket. Two controls provide fast, efficient operation, on/off volume and push-to-talk. Private monitoring or conversation by means of a special jack and earphone. Telescoping antenna extends 46 inches. Full-transistor circultry employs 9 transistors, 1 diode. Crystal-controlled transmitter section delivers 100 milliwatts of power to the final RF amplifier. Crisp, clear reception furnished by the efficient superheterodyne receiver. Power supplied by 6 penlight batteries with life expectancy of up to 55 hours.

ncy of up to 55 hours.

Housed in black and brushed aluminum metal case with leather carrying case and shoulder strap. With earphone, antenna, batteries and a pair of crystals for the channel of your choice, 6%x2%ex1%". Shpg. wt., 2½ lbs.

•		
99 H 3020CL Model HE-29C Specify Channel	Net	25.95
42 H 4204C Replacement Transmit Crystal, Specify Chang	tal Not	49.95 2.25
42 H 4205C Replacement Receiver Crystal, Specify Changes H 3021 Replacement Earphone for HE-29C	Net	2.25
replacement batteries for HE-29C "Walkie-Talkie," 6 require	ad .	

AC Power Supply
Use in place of batteries for operation on 110 VAC. Shpg. wt., 2 lbs.
99 H 3012 Net

LAFAYETTE 6-TRANSISTOR SUPERHETERODYNE

CB "WALKIE TALKIE" MODEL HA-85







No License Required (FCC Reg. part 15)

- 6 Transistors plus 2 Diodes
- Transmits and Receives up to
- Crystal Controlled Transmit and
- Efficient Superheterodyne Receiver
- Push-to-Talk Operation
- Leather Case with Shoulder
- Earphone for Personal Listening

Ideal for sports, boating, hunting, fishing and construction. Weighs only 15 oz. and is small enough to slip into your pocket. Its ON-OFF Volume Control and efficient Push-to-Talk switch provides easy one-hand operation. Superheterodyne receiver supplies clean reception. Circuit employs 6 transistors and 2 diodes. Transceiver conforms to FCC requirements for 100 milliwatt units. In attractive metal case with leather carrying case and shoulder strap. Complete with earphone for personal listening in addition to built-in speaker, telescoping antenna, 6 penlight batteries and a pair of crystals for the channel of your choice. 676x2%k136". Shpg. wt., 2½ lbs. Imported.

99 H 3013 CL Model HA-85, Specify Channel	
42 H 4204C Replacement Transmit Crystal, Specify Chan	2 for 38.75 nel Net 2.25
42 H 4003C Replacement Receive Crystal, Specify Chan	nel Net 2.25
99 H 3021 Replacement Earphone for HA-85 32 H 4802 Replacement "Z" batteries, 6 required	Net .49
oz ii 1902 Kepiacement & Datteries, 6 required	Net ea13

AC Power Supply

Use in place of batteries for operation on 110 VAC. Shpg. wt., 2 lbs. 99 H 3012

Lafayette 12-Transistor Citizens Band "WALKIE-TALKIE" **Model HE-100 with noise Squelch**



Separate Microphone and Speaker for Better Modulation & Increased Range

 Advanced Walkie-Talkie Design
 Separate Microphone and Speaker for Better Modulation & Increased Range • 12 Transistors, Diode, and Thermistor • Crystal Controlled Transmit and Receive • Superhet Receiver has AVC, Squelch, Push-Pull Audio Output . Optional Plug-in 117 Volt AC Power Pack

A GIGANTIC STEP FORWARD IN THE DESIGN AND PER-FORMANCE OF 100-MW POWER WALKIE-TALKIES!

The use of a separate microphone and speaker results in excellent modulation with greatly improved transmitting range and maximum effective signal intelligibility. Superhet receiver has variable squeich to reduce background noise. 12-transistor advanced design circuit is crystal-controlled for both receive and transmit functions. Sensitivity is better than 1 microvott for 10 db receive and transmit functions. Sensitivity is better than 1 microvolt for 10 db signal-to-noise ratio. Easy-to-use, lightweight . . . carry it anywhere for sports or business. Housed in a rugged hi-impact plastic case. Handy controls include push-to-talk switch, volume and variable squelch. Power is supplied by 8 miniature penlight batteries. To conserve battery power, a 117V AC power pack Is available as an optional plug-in accessory. Complete with leather case, earphone, for private monitoring. 44" telescoping antenna, batteries and crystals for channel 10. Size: 3Wx9Mx234"0. Shpg. wt., 2 lbs. Imported.

Net 39.95 2 for 78.88 99 H 3022L 99 H 3023L Same as HE-100 but specify channel other than 10 (2-23)... Net 39.95 2 for 78.88

CRYSTALS FOR HE-100

42 H 4204C Transmit Crystal only. Specify Frequency. 42 H 4205C Receive Crystal only. Specify Frequency.

AC POWER PACK FOR HE-100

Heavy Outy 117 Volt 60 Cycle AC Power Supply to 12V O.C. Replaces 8 "Z" Cells. Wt. 1 lb. 99 H 3024 REPLACEMENT EARPHONE FOR HE-100 Net .49 99 H 3025

CANADIAN APPROVED HE-100 O.O.T. Approval No. 169361066.

Net 39.95 2 for 78.88

Lafayette 10-Transistor Citizens Band "WALKIE TALKIE" Model HA-60

- Crystal Controlled Superheterodyne Receiver with RF Stage, AVC
- Separate Microphone and Speaker For Better Modulation & Increased Range
- 1 µV Sensitivity For 10 DB S/N Ratio
- 10 Transistors, Diode, Thermistor
- **Crystal Controlled Transmitter**
- Range 1-3 Miles

Ideal for use in business, industry, or personal use. Features automatic volume control and push-pull audio. Separate speaker and microphone provides better modulation and improved transmission range. Simple operation is made possible with sturdy push-to-talk switch and volume control. Earphone is provided for private reception. 44" whip antenna collapses fully when not used. Power is supplied by 8 inexpensive penlight batteries. To conserve battery power, a 117V AC power converter is available as an optional plug-in accessory. Housed in rugged hi-impact plastic case. Complete with leather case, earphone, antenna, batteries and crystals for channel 10. Size: 3Wx9Hx234"D. Shpg. wt., 2 9N 30091

99 H 3009L Net 33.95

OTHER CHANNELS ARE AVAILABLE if desired with any channel other than channel 10 order 99 G 3010L and specify channel (2-23). 99 H 3010L Same as HA-60 but specify channel other than 10 (2-23) Net 33.95 CRYSTALS FOR HA-60 2 for 62.90

42 H 4204C Transmit Crystal only. Specify frequency 42 H 4205C Receive crystal only. Specify frequency.

AC POWER PACK FOR HA-60 99 H 3024 Heavy duty AC power supply Replaces 8 "2" cells. Wt. 1 lb. Net 7.45 99 H 3025 ... REPLACEMENT EARPHONE FOR HA-60 ... Net .49

CANADIAN APPROVED HA-60. 0.0.T. Approval No. 169361073. Net 33.95 2 for 62.90

\$5.00 Monthly 2 FOR 62.90









No License Required (FCC Reg. part 15)

Lafavette Cat. No. 651 133

LAFAYETTE 2-CHANNEL 1-WATT ALL-TRANSISTOR PORTABLE CB TRANSCEIVER

THE SUPER WALKIE-TALKIE ... A NEW CONCEPT IN 2-WAY CB RADIO

DELUXE FEATURES

- Meter for Indicating Battery Strength & Modulation Level. An External Push-to-Talk Dynamic Microphone for Greater Effective Range
- Complete with 2-pair Transmit/Receive Crystals.
- 13-Transistor 5-Diode Circuit.
- **Push-Button Operated**
- Self-Contained Batteries or Powered by External 12-Volt OC Supply. Leightweight—Weighs only 4 lbs.

MODEL **HA-150**

1. EXTERNAL PUSH-TO-TALK OYNAMIC MICROPHONE FOR RELAY SWITCHING 2. CHANNEL SELECTOR

3. SQUELCH

3. SQUELCH
4. AUTOMATIC NOISE LIMITER
5. MODULATION-BATTERY
INDICATOR SWITCH
6. MODULATION-BATTERY
INDICATOR METER
INDICATOR METER
7. POWER ON-OFF/VOLUME
8. TELESCOPING WHIP ANTENNA
6. TELESCOPING W

EXTERNAL BATTERY SOCKET 10. EARPHONE SOCKET

Model HA-150 Ideal for Builders, Contractors, Surveyors, Hunters, Campers, Plant Watchmen, etc.



monthly 2 for 154.95 Here is a fully transistorized 2-way CB radio that offers the portability of a walkie-talkie, yet has features found only on large mobile transceivers. It has full 1-watt RF input . . up to 6-mile range . . . quick-release battery compartment that uses 8 inexpensive flashlight cells for long, heavy-duty service. 4 convenient push buttons give you complete control. It can be used in or out of its leather case . . . as a base station or remote . . carried, or used on a desk, table, car or boat—its uses are virtually unlimited! It has a high-efficiency 59-inch antenna which collapses to 7½ inches. Receiver has high 1 µv sensitivity, push-pull audio, and large 3-inch speaker for clear, full-tone reproduction. The transceiver has plug-in crystals that let you change to any other 2 channels in the Citizens Band—without any circuit retuning or readjustments. Complete with channel 10 and 15 crystals (2 transmit, 2 receive), batteries, push-to-talk dynamic microphone, a leather carrying case, earphone, cord and plug for external battery connections with shoulder strap for 'ansceiver.

Dimensions: 9½Wx2¼4Hx5½"D. Operates from self-contained 12-volt battery pack or 12-volt DC external supply. Imported. Shpg. wt., 7 lbs.

99 H 3014L Replacement batteries for HA-150
32 H 4801 1.5-volt "C" cell (8 required)
42 H 4204C Transmit Crystal. Specify Channel
42 H 4205C Receive Crystal. Specify Channel Set of 2 154.95 REPLACEMENT ANTENNA FOR HA-150 99 H 3017 Antenna 1.95

LAFAYETTE HE-75 1-WATT 13 TRANSISTOR CITIZENS BAND "WALKIE TALKIE"

• 10 Times More Powerful Than 100MW Units-With Far Greater Range • Uses Powerful Silicon Transistors in Output Stage • Crystal-Controlled Receive and Transmit . Automatic Noise Limiter, Squeich AVC . Push-Pull Audio Output . Plug-in Battery Case for Both Penlight and Optional Rechargeable Nickel Cadmium Batteries Meets FCC Requirements for Licensed Operation Part 95.

	Yet	59.95
Rechargeable nickel cadmium battery in sealed compartment	for	118.85
33 H 3018	Net	14.50
42 H 4205C Receive Crystal only. Specify Frequency A 99 H 3019 REPLACEMENT EARPHONE FOR HE-75	Vet Vet Vet	2.25 2.25 .49
CANADIAN APPROVED HE-75 (D.O.T. Approval No. 169361071)	let	59.95

\$6 monthly

2 for 118.95







OTHER CHANNELS ARE AVAILABLE if desired with any channel other than channel 13, order 99 H 3029L and specify channel (1-23)

CB Equipment is Available on Easy Pay Plan-See Center Insert A

NEW LAFAYETTE

2 WATT, 2 CHANNEL CB "WALKIE TALKIE"

Model HA-300

A Compact, Hand-Held 2-Way Radio With All These Features . . .

- Powerful 2 Watts
- 2-Channél Operation
- Self-Contained Rechargeable **Batteries**
- Plug-in Battery Charger
- Provision For External Antenna
- 13 Transistors, 2 Diodes
- Fully Crystal-Controlled
- Lightweight—Weighs Less Than 2½ lbs. Full 2 watts RF input lets you get through off up to 10 mile range over favorable terrain. 2-channel operation. up to 10 mile range over favorable terrain. 2-channel operation—a flip of a switch lets you transfer from one channel to another. Other extras include 2 built-in heavy-duty nickel-cadmium batteries and a plug-in battery charger that enables you to maintain the transceiver's maximum power capabilities at all times. 13 transistors and 2 diodes are used in a fully miniaturized transmitter and receiver, both crystal-controlled for precise, dependable operation. Receiver employs a superheterodyne circuit with 1 RF and 2 IF stages for high sensitivity, push-pull audio for high output and undistorted sound, plus a variable squelch control that silences the receiver on "standby." An automatic gain control circuit prevents overloading on strong signals and maintains uniform sound output. A full-time Automatic Noise Limiting circuit reduces ignition and other electrical noise. Powerful 2-stage transmitter output circuit uses two rugged silicon transistors for greater reliability and longer life. The 10-section, chrome-plated telescopic antenna extends to 56½ inches ard there's



Set of 2 194.95 \$8 Monthly


PRICE INCLUDES

- ✓ Nickel Cadmium Batteries
 - **Battery Charger**
- Earphone

offers

- Crystals for 2 Channels
- Leather Case





also a special receptacle that lets you plug in any existing mobile or ground station antenna for extended range! A push-to-talk bar and thumb-operated volume and squelch controls permit simple, onehand operation.

hand operation.

The HA-300 is equipped with crystals for channels 10 and 15, but may be operated on any two other channels in the Citizens Band by simply changing the plug-in crystals. Supplied complete with 2 self-contained nickel cadmium batteries, 117 volt 50/60 cycle AC operated battery charger, earphone, and leather case with strap. Dimensions: 834x33/2x2". Black metal case with chrome trim and silvered grill. Imported. Shpg. wt., 4½ lbs.

99 H 3006L

Net 99.95

	t of 2						l	let 19	34.95
Fì	TRA CR	YSTALS F	OR HA-3	100					
42	H 4204	C Transm	it cryst	al only.	Speci	fy chan	nel	Net	2.25
42	2 H 4205	C Receive	e crysta	i only. S	pecify	channe	I	Net	2.25
99	H 3019	Replacer	nent ea	rphone	for H	A-300		Net	.49
-									

LAFAYETTE DELUXE "RANGE BOOST" 23-Channel CRYSTAL-CONTROLLED CB TRANSCEIVER



- Made in U.S.A.
- Exceeds FCC Requirement For Spurious and Harmonic
- Includes 2 Section Harmonic Filter to Eliminate TV Interference
- Will Not Become Obsolete-Works with Existing CB **Transceivers**
- Meets All FCC Regulations

\$9 monthly

Model HB-333

Illuminated 'S' Meter Indicates Signal Strength and Relative Power Output Push - to - Talk Noise Cancelling Ceramic Microphone for advanced Electronic Switching Gircuitry Variable Floating Series Gate Noise Limiter

Adjustable Squeich Range Boost ON-OFF Delta Tuning For Increased Crystal Tuning

Accuracy

7. Phone Jack for Phones or External Sceaker
8. Channel Selector
9. PRIVA-COM Selective Call Socket
10. Illuminated Channel Selector Dial
1. Built-in 117 V AC Power Supply With 12
Volts DC Mobile Vibrator Power Supply

Unlike other types of "range boost" circuitry, the Lafayette system maintains the full carrier at all times ensuring excellent audio at maximum range. The modulation density of the audio contained in both sidebands is increased. In addition, the "Range Boost" features continuous crystal-control for both transmit and receive on all 23 channels. Triple crystal Delta tuning ±3 KC of channel center frequency assures accurate station tuning when stations transmit slightly off frequency. Its highly efficient transmitter features: 5 watts plate power input to final (20 Watts PEP) with at least 3.watts power output to the antenna; up to 100% modulation at average speaking level, with "Range Boost." Illuminated D'Arsonval. "S" Meter reads signal strength and relative RF output. Audio output is 3-4 watts into 3x5" pm speaker. An antenna matching adjustment per-3.4 watts into 3x5" pm speaker. An antenna matching adjustment permits resistive antenna loads of 52 or 72 ohms. Has phone jack on front panel for private listening or for remote external speaker. Includes all crystals, efficient noise cancelling microphone, AC & DC cables, and mobile mounting bracket. Includes 2-section harmonic Capies, and mobile mobile mobile for the filter to eliminate TVI. Built-in receptacle accepts Lafayette "Priva-Com" Selective Call unit. Complies with all FCC rules. Dual built-in 117 volt AC, 12 V DC vibrator power supply. Size: 12Wx4½Hx8½D". Shgz. wt., 16 lbs.

42 H 0105WX Net 199.50

HB-333 plus Selective Call Unit. Shpg. wt., 19½ lbs. 42 H 9001WX

Lafayette Cat. No. 651 135

Net 230.75

LAFAYETTE HB-115A PUSH-TO-TALK CITIZENS **BAND TRANSCEIVER**



- 12 Tube Functions, Plus 1-Diode, Plus 2 Silicon Rectifiers
- **B Crystal-Controlled Transmitting Positions**
- Tunable Superheterodyne Receiver Over All 23 Channels

Lafayette's new CB sensation consists of an attractive compact trans-

ceiver with exceptional performance on Class "D" Citizens Band. Two or more HB-115A's will supply you with reliable communications over distances of up to 20 miles or more depending on antenna height and

The HB-115A features 8 crystal-controlled transmitting channels oper-

- Electronic Push-to-Talk Switching
- Push to Talk Ceramic Microphone
- Pi-Network for Maximum Power Output
- External Speaker Earphone Jack on Front Panel
- **Full-Wave Variable Noise Limiter**
- Separate On-Off Power Switch
- Supplied with Channel 14 Transmitting Crystal
- Attractively Styled, Ruggedly Built

\$6.00 MONTHLY MADE IN USA

AC line cord and 6 or 12 volt external mobile power supply. Supplied complete with Channel 14 transmitting crystal, efficient push-to-talk ceramic microphone, and mounting brackets. 6 or 12-volt power supply optional (see below). Size 11½2Wx5Hx6% "D. Shpg. wt. 13 lbs. 42 H 0101WX

ating at the maximum legal input power of 5 watts fully modulated: a pi-network output which matches 30-100 ohm antennas for maximum output; RF stage in transmit and receive sections. The superhetero-POWER SUPPLY: Adapts HB-115A for mobile operation. Complete with cable and mounting flanges. Size 6Wx4Hx41/4"D. Shpg. wt., 4 lbs. 42 H 0102W For 12 Volts Net 11.50 output; RF stage in transmit and receive sections. The supernetero-dyne receiver is tunable on all 23 channels with over 2 watts audio output, has Automatic Volume Control and a very effective fullwave variable Noise Limiter. Features a front panel speaker earphone jack for an extra external speaker or for an earphone or headset for quiet listening: a separate on-off power switch for trouble-free economy 42 H 0103W For 6 Volts Net 11,50

TRANSMITTING CRYSTALS: For any of the 23 channels. 42 H 4201C Specify channel or frequency

ANTENNA: Base-loaded telescoping whip antenna with PL-259 coax connector. For short distance operation. Mounts directly on rear of cabinet. Telescopes to only 15". Shpg. wt., 2 lbs. Imported of operation. The HB-115A has accurate planetary vernier tuning Controls: Tuning, Volume, Variable Noise Limiter, 8-position Crystal Selector and Power indicator. Power receptacle in rear for 115-volt 99 H 3015

LAFAYETTE "PRIVA-COM"™ SELECTIVE CALLER

The "Priva-Com" Selective Caller, when Standby" position, silences the speaker of the transceivers to which it is connected. When the "Priva-Com" call switch is actuated at either "Priva-Com" call switch is actuated at either base or mobile, the transmitted dual tone signal is received by the other "Priva-Com". Its indicato light goes on and the speaker is automaticatly activated. You can now speak or listen to the calling station. The light stays on until manually reset. If the car horn or an external alarm is connected to the "Priva-Com" terminals the received dual-tone signal causes the horn or alarm to sound for 1 second. Both base and mobile stasound for I second, both base and mouter stations can initiate calls and monitor the air at anytime. Cable terminates in plug which mates with Lafayette CB Transceiver. Complete with mounting bracket and instructions. Size 3% Wx 3% Hx51/e"D. Shpg. wt., 31/2 lbs. 42 H 0110

Each Net 32.50 2 for 62.50 *Not recommended for Transceivers with carbon microphones less preamplifiers.

For Quiet Private Communications

Choice of 10 Dual Tone Frequencies Minimizes Interference by Unwanted

Activates car Horn or External Alarm for 1 second If Operator is Away from Equipment

Outstanding Performer with Lafayette HE-20, HE-15, HE-90, HB-111, HB-115, HB-222 & HB-333, as well as with any Push-to-Talk CB Transceiver*

Compatible with Lafayette HA-100 "Priva-Com"

3250 \$5.00 MONTHLY



Net 2.25




NEW! LAFAYETTE DUAL CONVERSION DELUXE CITIZENS BAND TRANSCEIVER MODEL HB-200

-- Illustrious Successor to Famous HE-20C--



- plus 2 Crystal Diodes for 17 Tube **Performance**
- 8-Crystal Receive Positions plus 8-Crystal Transmit Positions plus 23 Channel Tunable Receive
- Spotting Switch for Exact Frequency Location on Tunable Re-

LOOK AT THESE SPARKLING FEATURES



- 1. 13 MC Transmit Crystal for Extra Stability.
 2. Illuminated Meter With 3 Position Switch Indicates "S" Readings, Relative Power Output, and Modulation.
- **Spotting Switch.**
- 4. Dual Cascade Series Gate Noise Limiter.
- Adjustable Squelch.
- Relay Switching Push-To-Talk Ceramic Micro-6.
- 7. Tunable Receive or Crystal Selector Switch.
- Phone Jack for Quiet Listening.
- 9. Illuminated Dial.
- 10. Attractive Styling With Chrome Plated Bezel.11. Supplied With Pair of Transmit/Receive Crystals for Channel 14 plus Crystal for Dual Conversion.
- Hand Wired. Lafayette is Headquarters For the Citizen Band User

- Wired to Accept "PRIVA-COM" Selective Call Unit
- Super Sensitivity-1 Microvolt or
- Built-in 117 Volt AC Power Supply with 12 Volt DC Mobile Transistorized Power Supply

Lafayette advances its leadership in the Citizens Band field with this superb Dual Conversion Deluxe Citizens Band Transceiver. The excellent selectivity and gain of its dual conversion receiver makes the Lafayette HB-200 a natural for efficient fixed and mobile

makes the Lafayette MB-200 a natural for efficient fixed and mobile communications over distances of up to 20 miles or more, depending on the terrain and the height of the antenna.

The 5-watt input highly efficient crystal-controlled transmitter may be operated on any 8 of the 23 channels assigned by the FCC. The dual conversion receiver circuit provides for 8 crystal controlled receiving channels plus a tuneable superheterodyne receiver that covers all 23 assigned channels with a sensitivity of 1 microvolt or less. An adjustable squelch circuit quiets the receiver when no signal is being received. A dual cascade series gate noise limiter effectively reduces ignition, static and unwanted noises. A sensitive Illuminated panel meter is utilized with a 3-position switch to indicate incoming signal strength, relative power output and modulation. The MB-200 also features dependable relay switching; a Spotting Switch for locating exact frequency on tunable receive, and a front tion. The HB-200 also features dependable relay switching; a sportung Switch for locating exact frequency on tunable receive, and a front panel phone jack for quiet listening. It incorporates a Pi-network for matching the output to 30-100 ohm antennas for maximum signal output; input socket on rear of chassis for silent communications between calls when used with Lafayette PRIVACOM selective call unit. A rear mounted low-loss antenna jack accepts PL-259 connector used with dipole, ground plane, rod and direct mounting antennas (listed

Attractively styled low silhouetted transceiver and rugged case with chrome plated bezel.

Complete with bracket handle, efficient Push-to-Talk Ceramic Microphone, pair of transmit and receive Crystals for channel 14 plus crystal for dual conversion, and built-in 117-volt AC Power Supply with 12 volt DC Mobile Transistorized Power Supply. Size: 12x5x 816-70. Shop. wt. 15 lbs.

42 H 0118WX Net	109.50
42 H 4701C 13 MC Transmit Crystal (Specify Channel) Net	2.25 2.25
Direct Plug-In Antenna for Short Oistances, Shpg. wt., 1 lb.	
99 H 3015 Net	3.95

SELECTIVE CALL PACKAGE HB-200 CB Transceiver plus "PRIVA-COM" Selective Call Unit. Net 140.75 42 H 9006WX Shpg. wt., 181/2 lbs.

Lafayette Cat. No. 651 137

NEW! LAFAYETTE Deluxe ALL-TRANSISTOR 5-Watt Dual Conversion CITIZENS BAND TRANSCEIVER HB-500


ONLY 33/4" HIGH

- ✓ 100% Solid-State . . . Full 5-Watt Performance
- ✓ 15 Transistors (11 Silicon Mesa Type), 4 Diodes, 1 Thermistor
- ✓ Small, compact—only 3¾" High
- ✓ Dual conversion superheterodyne receiver
- 12 Crystal Transmit and Receive Positions
- ✓ 23 Channel Tunable Receiver
- ✓ Push-to-talk Dynamic Microphone
- Dependable sealed relay switching
- ✓ Automatic Noise Limiter
- Adjustable squelch
- Requirements.

Requirements.

Lafayette introduces an ingeniously designed 5-watt solid state, dual conversion superheterodyne, CB transceiver. The exciting Lafayette HB-500 packs a real wallop over distances up to 20 miles or more depending on conditions. Its 15 transistors (11 are silicon mesa), 3 diodes, 1 zener diode and 1 thermistor provide instant and cool performance with low current drain.

The 100% modulated 5-watt, crystal-controlled transmitter may be operated on any 12 of the 23 channels. The receiver circuits provide for 12 crystal-controlled channels plus a tuneable superhet receiver that covers all 23 channels with a sensitivity of better than ½ microvolt for 10 db s/m ratio. The receiver employs a specially designed 455KC mechanical filter for 50 db adjacent channel rejection and excellent selectivity. An automatic noise limiter and adjustable squelch circuit assures low noise performance. The receiver terminates in a 3x5" speaker fed by a 2.7 watt push-pull amplifier. Other features include: a spotting switch, illuminated channel selec-Other features include: a spotting switch, illuminated channel selec-



- 1 Adjustable Squelch
- 2 "S" Meter For Indicating Signal Strength
- 3 Spotting Switch For Exact Frequency Location on Tunable Receive
- 4 Illuminated Channel Selector Dial
- 5 Illuminated Receive

- Tuning Dia! 6 Push-To-Talk Dynamic Microphone
- 7 Xtal-Tune Selector Switch 8 Earphone Jack For Private
- Listening 9 Volume Control
- 10 Channel Selector
- 11 Receiver Vernier Tuning

tor and vernier dial tuning, an "S" meter and earphone jack. Complete with mobile mounting bracket, push to talk dynamic microphone, pair of transmit and receive crystals for channel 12 plus a crystal for dual conversion, and a DC cable. Operates on 12 volt pos. or neg. ground. Shpg. wt., 12 lbs. Imported.

99 H 3027WX 12 VDC

99 H 3043C Receive crystal (specify channel) ±.003% Net 2.50 plirect plug-in antenna (shpg. wt., 1 lb.)

98 H 3015

Net 3.95


Medel HB-501 Selid State AC Power Supply
Matching solid state AC power supply for HB-500 for fixed station
operation (at home, business, office). Transceiver rests on power
supply to form an attractive integrated unit. Size 11%x61%x33%". Shpg. wt., 10 lbs. Imported. 99 H 3028W

NEW! LAFAYETTE Deluxe 23 Channel Crystal Controlled Dual Conversion 5 Watt CB TRANSCEIVER MODEL HB-400

- ★ Frequency Synthesized Circuit Provides 23 Crystal - Controlled Transmit & Receive Channels—No Extra Crystals to Buy!
- ★ Push To Talk Microphone & Electronic **Switching**
- ★ Dual Conversion Receiver With 3/10 uv Sensitivity
- * Triple Crystal Delta Tuning Offers "Fine Tuning" of ± 2.5 KC on Receive
- ★ Variable Squelch, Variable Noise Limiter
- Built-in 117V AC & 12V DC Power Supply
- 🛊 "Vari-Tilt" Mounting Bracket for Easy Mobile Installation
- ★ Plug-in Facilities For Lafayette Selective

Call Unit

Efficient, dependable 2-way communications in any fixed or mobile application is assured with this rugged, new 5-watt CB transceiver. A military-type frequency synthesizing circuit makes it possible to transmit and receive over the full range of 23 channels with crystal-controlled accuracy—no extra crystals to buy and install! A zener diode full wave range-Boost circuit increases the average depth of modulation during transmission and thus increases the average power in the sidebands—let's you transmit further within the 5-watt limitation imposed by the FCC! And, the "Range-Boost" system in the HB-400 is fully compatible with existing CB transceivers. Highly efficient circuit design uses 13 tubes (including two nuvistors) and 8 diodes to provide top performance under a wide range of operating conditions. Dual-conversion receiver offers .3 uv sensitivity and low noise, plus excellent adjacent channel rejection. Includes every conditions. Jual-conversion receiver directs 3 of Sensitivity and low noise, plus excellent adjacent channel rejection. Includes every needed feature for optimum reception—crystal-controlled "fine tuning" capability of ±2.5Kc (Delta Tuning), high-efficiency variable



- 1 Illuminated Meter
- 2 Meter Switch
- 3 Speaker
- illuminated channel indicator
- 5 Channel Selector
- 6 Phone Jack

- 7 Delta Tune 8 Range Boost
- 9 Variable squelch
- 10 Volume-on/off
- 11 Variable noise limiter 12 Microphone socket
- 13 Vari-tilt mounting bracket
- 14 Built-in power supply

noise limiter, variable squelch, and Automatic Volume Control. Also included is an illuminated meter which indicates relative RF power output or received signal strength in "S" units. The transmitter is equipped with ceramic push-to-talk microphone and uses reliable electronic transmit-receive switching. Operates in a fixed or mobile location with equal ease . . . has built-in power supply for either 1177 AC or 12V DC. Specially designed "Vari-Tilt" mounting bracket simplifies mobile installation—permits fast removal of the transceiver too! And, there's nothing else to buy—you get all crystals and a built-in vibrator for 12V DC, plus 2 power cables. Measures a compact 12"W x 5"H x 10"D (including controls and plugs at rear). Shpg. wt., 20 lbs. 99 H 3001WX

Model HB-400 plus HA-200 PRIVA-COM Selective Call Unit 40 H 9007WX Shpg. wt., 231/2 lbs.

MODEL **HB-500**

99 H 3027WX

\$7.00 MONTHLY


DESIGNED AND BUILT FOR RELIABILITY

LOW CURRENT DRAIN 350 MA. RECEIVE 850 MA. TRANSMIT



Silicon Mesa Transistors for

Utmost Reliability .003% Tolerance Crystals For Frequency Stability




HIGHLY SELECTIVE MECHANICAL FILTER

With CB channels only 10 Kc apart, selectivity is important! In the HB-500, ultra-sharp selectivity is achieved by means of a true mechanical bandpass filter in the 455 Kc Is section. At 10 Kc on either side or the center frequency, the filter provides 60 db of attenuation.

The filter consists of three sections—an input transducer, a mechanically resonant filter, and an output transducer. The mechanically resonant section consists of six metal disks supported and coupled by a thin rod

ported and coupled by a thin rod. The use of this filter results in an IF bandpass curve which is almost rectangular in shape, with superior "skirt" selectivity.






CONVENTIONAL Average Percent-age of Lower

ADVANCED FULL WAVE "RANGE BOOST" CIRCUIT.

Increases Your Effective Range-Lets You Get Through Where Others Fail!

Want to effectively increase your range? You can—with Range-Boost! A simple turn of a switch on the HB-400 increases the average percentage of modulation and lets your voice cut through QRM and noise to reach further . . . gives you more "talk-power" when you need it—without overmodulating!



LAFAYETTE RADIO **ELECTRONICS** 111 JERICHO TURNPIKE SYOSSET, L.I., N.Y. 11791 5/1/AL BLEN E F 43 4112 HOWEN RD TOLEDO 13 ONTO

BULK RATE U.S. Postage PAID LOUISVILLE KENTUCKY Permit No. 599

IF UNDELIVERABLE DO NOT RETURN



Another outstanding achievement by Lafayette engineers in tape recorder design. The Criterion 1000 records and plays 4-track stereophonic tapes with "ultra" realism through ito own transistorized, preamplifiers, push-pull power amplifiers and matched self-contained high fidelity speakers. Speaker wing panels deflect the sound into the room with the proper stereo separation. Three fingertip selected speeds of 7½, 3¾ and 1½ give you up to 8 hours playing time on a single 7" reel. Positive pushbutton controls coupled to a husky, heavy duty, low silp capacitor-start motor enable smooth tape control with exceptional record-playback characteristics. Pause control, dual volume and tone controls, index counter, separate level meters and an automatic shut-off which electrically and mechanically returns recorder to "stop" position are additional Criterion features. Has 4 inputs for microphones and radio connections plus mike/radio Has 4 inputs for microphones and radio connections plus mike/radio

mixer control and two output jacks for external speakers. Cabinet is genuine teakwood—a modern classic! SPECIF CATIONS. Speeds: 176, 334, 71/2 ips. Frequency Response: ±3 db 50-15,000 cps @ 74/2 ips. ±3 db 50-0,000 cps @ 334 ips. ±3 db 55-5,000 cps @ 176 ips. Motor: 4-pole capacitor-start, Signal-to-Roise ratio: 50 db Wow & Flutter: 0.2% @ 74/2 ips. Rewind Time: 1200 ft. reel, 130 sec. Inputs: 2 microphone, 2 high level. Speakers: 2 6x4 oval; Two external speaker outputs. Power output: 6 watts per channel, Bias & Erase: 80 cc. Reel Size: 7" maximum. With 2 dynemic microphones, cables and 7" take up reel. For 117 volts, 60 cycles AC. 174@WX744Hx12%"D. Shpg. wt., 433/2 lbs. Imported

99 H 1501WX Criterian 1000 Stereo Recorder

28 H 0101

7" reel of 1200 ft. Lafayette recording tape Net 1.59

Net 139.50