

INDEX

—A—

- AM (Amplitude Modulation) (See AM directional arrays, AM nondirectional AM antenna, AM stereo)
- AM Directional Arrays, 2.4-67—92
 - antenna monitor, 2.4-101—102
 - augmented pattern equation, 2.4-89—92
 - detuning and decoupling system, 2.4-102—105
 - filter systems, 2.4-104
 - intermodulation, 2.4-104—106
 - power lines, 2.4-103
 - tower current minimums, 2.4-104
 - tower sectionalization, 2.4-102-103
 - transmitter load, 2.4-105
 - diplexers and multiplexers, 2.4-105—106
 - directional antenna block diagram, 2.4-94
 - field strength, 2.8-217 (See listing)
 - ground system, 2.4-110
 - horizontal RMS field strength (See field strength)
 - insulated tower base impedance, 2.4-64—65
 - maintenance of AM antenna systems, 2.4-109
 - matching networks, 2.4-95—100
 - L networks, 2.4-95—97
 - diagram, 2.4-96—97
 - power divider, 2.4-97—100
 - diagrams, 2.4-98
 - ohms-law divider, 2.4-97
 - simplification, 2.4-99
 - tank-type divider, 2.4-97
 - T networks, 2.4-95
 - multiplication of two tower patterns, 2.4-69
 - mutual-impedance curves, 2.4-76—77
 - pattern shape, 2.4-73
 - space configuration, 2.4-73
 - vector diagram, 2.4-73
 - phasing systems, 2.4-93—94
 - input impedance, 2.4-94
 - radiation patterns, 2.4-94—95
 - VSWR, 2.4-94
 - radiation pattern shape, 2.4-67—69
 - sampling loops, 2.4-101
 - sampling lines, 2.4-101
 - sampling transformers, 2.4-101
 - sampling system, 2.4-101—102
 - soil conductivity, 2.4-113
 - systematization of patterns, 2.4-69—72, 78—88
 - theoretical pattern equation, 2.4-89
 - theoretical self-loop and base radiation resistance, 2.4-76 (See AM proof of performance, partial proof, transmission lines)
- AM Field Strength Measurements (See AM Proof of Performance, Field Strength)
- AM Nondirectional Antenna (See Nondirectional AM Antenna listing)
- AM Proof of Performance, 2.8-217—234
 - antenna monitor system, 2.8-223
 - construction permit, 2.8-219
 - FCC license, 2.8-223—224
 - FCC program test authority, 2.8-219—220
 - measurements, 2.8-219, 221
 - graphical analysis, 2.8-221
 - plotting data, 2.8-221—223
 - partial proof, 2.8-220—221
 - reference proof of performance, 2.8-219
 - regulations, 2.8-225—234
 - special temporary authority, 2.8-223
- AM Stereo, Definition, 3.2-37—38
- Belar AM Stereo, 3.2-53
- Harris linear AM stereo system, 3.2-43—46
 - compatibility with human ear, 3.2-44—45
 - controlled compatibility linear quadrature, 3.2-45—46
 - linear systems, 3.2-44
 - nonlinear systems, 3.2-44
- Kahn-Hazeltine independent sideband system, 3.2-47—51
 - asymmetrical sideband selectivity, 3.2-48—51
 - receiver, 3.2-48
 - transmitting equipment, 3.2-47
- Motorola C-Quam AM stereo system, 3.2-39—42
 - audio performance, 3.2-39
 - audio preemphasis, 3.2-39
 - audio processing, 3.2-39
 - C-Quam, compatible quadrature, 3.2-39—41
 - decoding, 3.2-40—41
 - encoding, 3.2-39—40
 - transmitter, 3.2-39—40
 - heavy modulation, 3.2-41
 - performance, 3.2-41
 - receiver, 3.2-42
 - spectrum, 3.2-39
- PMX AM Stereo, 3.2-55—61
 - broadcast signal equation, 3.2-55
 - characteristics, 3.2-58
 - bandwidth, 3.2-58
 - compatibility, 3.2-58
 - coverage, 3.2-58
 - measurement, 3.2-58
 - performance, 3.2-58
 - sound field disturbances, 3.2-58
 - system implementation, 3.2-55—56
 - synchronous detection, 3.2-58
- AM Transmitters, 3.1-1—36
 - ampliphase, 3.1-9
 - audio phase linearity, 3.1-20—21
 - carrier amplitude regulation (carrier shift), 3.1-19—20
 - carrier frequency generator/exciter, 3.1-13—14
 - characteristics, 3.1-24—25
 - Chireix modulation, 3.1-9
 - diagram, 3.1-9
 - circuitry, 3.1-13
 - Class "B" level anode modulation, 3.1-5
 - diagram, 3.1-6
 - Doherty High Efficiency Linear Amplifier, 3.1-9—10
 - diagram, 3.1-11
 - factory tests, 3.1-18
 - harmonic and spurious output, 3.1-22
 - high level anode modulation, 3.1-5
 - high voltage power supplies, 3.1-17
 - hum and noise, 3.1-19
 - incidental phase modulation(IPM), 3.1-19,24
 - occupied bandwidth, 3.1-21—22
 - operating efficiency and input power, 3.1-22—24
 - outphasing, 3.1-9
 - performance measurements, 3.1-18
 - pulse width high level anode modulation, 3.1-7—9

diagram, 3.1-8
 RF output networks, 3.1-14—16
 RF power amplifier, 3.1-14
 representative transmitters, 3.1-26—36
 shortwave, 3.1-25—26
 stereophonic base/gain equalizer, 3.1-25
 transmitter control and monitoring, 3.1-17
 Advanced Television Systems Committee (ATSC), 1.6-90
 American National Standards Institute (ANSI), 1.6-93
 American Radio Relay League (ARRL), 1.6-93
 Amplitude Modulation (*See* AM)
 Amplitude Measurement, 7.9-185—187
 metering, 7.9-186—187
 peak function, 7.9-186
 peak program (PPM) meter, 7.9-186—187
 true RMS detection, 7.9-186
 volume indicator (VU) meter, 7.9-186—187
 Anchors (*See* Towers)
 Armstrong, Major Edwin H., 3.3-63
 Association for Broadcast Engineering Standards (ABES), 1.6-93
 Association of Federal Communications Consulting Engineers (AFCCE), 1.6-89
 Association of Maximum Service Telecasters (MST), 1.6-90
 Audio, 5.6-107—119
 production, 5.6-118—119
 Audio Console, 5.6-109—113
 Audio Engineering Society (AES), 1.6-93—94
 Audio Measurement, 7.9-185—200
 amplitude measurement, 7.9-185—187
 metering, 7.9-186—187
 peak function, 7.9-186
 peak program (PPM) meter, 7.9-186—187
 true RMS detection, 7.9-186
 volume indicator (VU) meter, 7.9-186—187
 distortion measurement, 7.9-190
 harmonic distortion, 7.9-190
 intermodulation distortion, 7.9-190—196
 total harmonic distortion (THD), 7.9-190
 transient intermodulation distortion (TID), 7.9-190
 wow and flutter, 7.9-193
 frequency analysis, 7.9-187
 real time analyzer (RTA), 7.9-189—190
 fast Fourier transform analyzer, 7.9-190
 parallel analysis, 7.9-189
 swept frequency, 7.9-188—189
 noise measurement, 7.9-196
 CCIR/ARM method, 7.9-197
 Fletcher and Munson, 7.9-197
 NAB A weighting, 7.9-197
 phase measurement, 7.9-198—199
 phase monitoring, 7.9-198—199
 relative program/loudness, 7.9-197—198
 audio program analyzer 7.9-198
 signal to noise ratio, 7.9-197
 telephone noise, 7.9-197
 Audio Processing, 5.6-117
 Augmented Pattern Equation (*See* AM Directional Arrays)
 Automatic Frequency Control (AFC), 3.3-77—78
 phase locked loop AFC, 3.3-77—78
 Automotive Road Information (ARI), 3.4-121

—B—

Base Radiation Resistance, 2.4-76
 Belar AM Stereo (*See* AM Stereo Listing)
 Bessel Function Analysis, 3.4-125
 Bessel Nulls, 3.3-67—68
 Bessel function, 3.3-66—67
 Binary Coded Decimal (BCD), 3.7-200
 Blondel-Ray Relationship, 2.1-7
 Brewster Angle, 2.5-120—121

Broadcast Education Association (BEA), 1.6-94
 Broadcast Facility, 5.1-1—27
 acoustics, 5.1-8—12
 economics, 5.1-9
 examples, 5.1-13—27
 reverb time, 5.1-11
 studio, 5.1-8
 construction, 5.1-2
 economics, 5.1-1—3,9
 budget (form), 5.1-3
 codes, 5.1-2
 planning, 5.1-1—2
 electrical, 5.1-4—7
 engineering, 5.1-2
 mechanical, 5.1-7
 site selection, 5.1-2
 telephones, 5.1-5

—C—

C Band, 4.3-79
 Cameras, television, 5.3-45—72
 afterimage, 5.3-69
 amplitude, 5.3-67
 automatic beam optimization, 5.3-64
 automatic set-up, 5.3-54
 beam current, 5.3-64
 camera tube preamplifier, 5.3-47
 camera types, 5.3-55
 electronic field production (EFP), 5.3-56—57
 electronic news gathering (ENG), 5.3-56
 portable, 5.3-56
 remote control unit, 5.3-56
 sports, 5.3-51
 studio, 5.3-55
 charge coupled device (CCD), 5.3-64
 choice, 5.3-70—72
 deflection system, 5.3-54
 block diagram, 5.3-54
 clock driver, 5.3-54
 encoder, 5.3-52—53
 synchronizing generator, 5.3-52—53
 image enhancer, 5.3-50—52
 image preamplifier, 5.3-47
 imaging device, 5.3-46
 lag, 5.3-68—69
 lead-oxide camera tubes, 5.3-63
 leadicon, 5.3-63
 plumbicon, 5.3-63
 saticon, 5.3-63
 limiting resolution, 5.3-66—67
 measurement, 5.3-66
 Nyquist limit, solid state images, 5.3-65
 optical system, 5.3-45—46, 57—62
 beam splitter, 5.3-46
 filters, 5.3-62—63
 lens, 5.3-45—46
 lens parameters, 5.3-57—60
 angle of view, 5.3-57
 field of view, 5.3-57
 focal length, 5.3-57
 geometric distortion, 5.3-59—60
 longitudinal chromatic variations, 5.3-59
 minimum object difference (MOD), 5.3-60
 modulation transfer function (MTF), 5.3-57
 ramping, 5.3-57
 relative operation, 5.3-57
 uniformity of field, 5.3-59
 vignetting, 5.3-59
 prismatic beam splitter, 5.3-62
 relay type beam splitter, 5.3-62
 performance, 5.3-69

- pixels, 5.3-64
 - power, 5.3-54
 - sensitivity, 5.3-67—68
 - set-up evaluation, 5.3-69—70
 - signal current, 5.3-64
 - system parameters, 5.3-69
 - video processor, 5.3-47
 - x and y alignment, 5.3-63
 - Candella, definition, 2.1-7
 - Cardioid microphone, 5.6-116
 - Cavity Panel Antennas, 2.5-133
 - Chart Recorder, 2.7-211
 - Chireix modulation, 3.1-9
 - diagram, 3.1-9
 - Co-channel Interference, 2.9-247
 - Color Subcarrier, (*See* Color Television Systems, and Multichannel Television Sound)
 - Color Television Standards, 7.1-51—60
 - International Radio Consultative Committee (CCIR), 7.1-51—52
 - monochrome-compatible color television systems, 7.1-52—61
 - National Television System Committee (NTSC), 7.1-52 system, 7.1-54—58
 - Phase Alternation Line (PAL), 7.1-53, 58—60
 - Sequential Couleur Avec Memoire (SECAM), 7.1-53, 61—63
 - Color Television System, 7.1-1—60
 - bandwidth, 7.1-3
 - burst amplitude error, 7.1-26
 - burst phase error, 7.1-25
 - camera alignment, 7.1-40
 - aperture correction, 7.1-42
 - signal to noise, 7.1-41
 - three tube concept, 7.1-41
 - carrier unbalance, 7.1-26—27
 - color encoder, 7.1-37
 - aperture compensation, 7.1-38—40
 - block diagram, 7.1-40
 - functions, 7.1-37
 - waveforms, 7.1-38
 - color errors, 7.1-36—37
 - color fidelity, 7.1-16
 - color frequency standards, 7.1-13
 - color subcarrier, 7.1-8—12
 - color system, 7.1-13
 - block diagram, 7.1-13
 - color variables, 7.1-5
 - displaying colors, 7.1-5—6
 - generating colors, 7.1-5
 - primary colors, 7.1-5
 - compatibility, 7.1-1
 - demodulation, 7.1-25
 - differential phase, 7.1-34—35
 - distortion in transmission system, 7.1-27
 - electronic aspects, 7.1-6
 - band shaping, 7.1-8
 - matrixing, 7.1-7-8
 - envelope delay, 7.1-29—31
 - eye characteristics, 7.1-17—24
 - film chains, 7.1-44
 - frequency interlace, 7.1-12—13
 - fundamentals, 7.1-1
 - gain characteristic, 7.1-27
 - gain stability, 7.1-25
 - incremental gain, 7.1-32—34
 - incremental phase, 7.1-34—35
 - linear transmission system, 7.1-27
 - matrix coefficients, 7.1-36
 - matrixing, 7.1-36
 - modulation, 7.1-25
 - monochrome television system, 7.1-4
 - radiated picture signal, 7.1-4
 - receiver, 7.1-4
 - nonlinearities of transmission systems, 7.1-31
 - phase accuracies, 7.1-36
 - phase characteristic, 7.1-28—29
 - receiver, 7.1-15
 - block diagram, 7.1-14—16
 - resolution, 7.1-3
 - scanning, 7.1-3
 - subcarrier frequency accuracies, 7.1-36
 - subcarrier frequency error, 7.1-27
 - synchronizing, 7.1-3
 - system colorimetry, 7.1-35—36
 - system exponent, 7.1-36
 - transmission characteristics, 7.1-36
 - video unbalance, 7.1-27
 - Color Test Equipment, 7.1-44—48
 - sine-squared pulse and bar, 7.1-45—46
 - stair-step generator, 7.1-45
 - vector scope, 7.1-46
 - vertical interval reference, 7.1-48
 - vertical interval test signal, 7.1-48
 - Communications Act of 1934, 1.1-1
 - Community Antenna Economics, 2.5-135—136
 - Compact Disc Players, 5.6-114
 - Computer Systems (for newsrooms), 7.6-123—157
 - centralized systems, 7.6-139
 - data communication, 7.6-134—138
 - interconnection, 7.6-138—139
 - modems, 7.6-138
 - distributed systems, 7.6-140
 - glossary, 7.6-148—157
 - hardware, 7.6-125
 - hybrid system, 7.6-141
 - installation, 7.6-144—145
 - languages, 7.6-127
 - local area network (LAN), 7.6-140
 - mainframes, 7.6-123—124
 - arithmetic/logic unit, 7.6-123
 - bits, 7.6-123
 - bitwidth, 7.6-124
 - bus, 7.6-124
 - memory, 7.6-124
 - maintenance, 7.6-145—147
 - newswire services, 7.6-137
 - planning, 7.6-141—144
 - programmable read-only memory, 7.6-126
 - security, 7.6-146—147
 - software, 7.6-126
 - terminals, 7.6-132—134
 - Condenser Microphone, 5.6-116
 - Consultant Service, 1.4-67—76
 - services, 1.4-67—70
 - Crossed Dipole Theory, 2.5-133—134
- D—
- D layer, 2.9-236
 - Data Communication, 7.6-134—138
 - dBx™, 5.11-225
 - Department of Agriculture, 1.6-87
 - Department of Commerce 1.6-87
 - National Bureau of Standards, 1.6-87—88
 - Time and Frequency Division, 1.6-87—88
 - WWV, 1.6-87—88
 - WWVB, 1.6-87—88
 - WWVH, 1.6-87—88
 - National Telecommunications and Information Administration, 1.6-88
 - Department of Labor, 1.6-88
 - Occupational Safety and Health Act, 1.6-88
 - Department of the Interior, 1.6-88
 - Bureau of Land Management, 1.6-88
 - Topographic Maps, 1.6-88
 - U.S. Geological Survey, 1.6-88

Department of Transportation, 1.6-88
 Federal Aviation Administration (FAA), 1.6-88

Dielectrics, 2.5-148

Diplexers, 2.4-105—106

Direct Broadcast Satellites (DBS), 1.1-7

Directional Antennas (*See* AM or FM listing)

Directional Microphone, 5.6-116

Distortion Measurement, 7.9-190
 harmonic distortion, 7.9-190
 intermodulation distortion, 7.9-190—196
 total harmonic distortion (THD), 7.9-190
 transient intermodulation distortion (TID), 7.9-190
 wow and flutter, 7.9-193

Distribution Amplifiers, Audio, 5.6-117

Distribution Amplifiers, Pulse, 5.4-79

Distribution Amplifiers, Video, 5.4-77—80

Doherty High Efficiency Linear Amplifier, 3.1-9—10
 diagram, 3.1-11

Dolby A™, 5.11-225

Dolby B™, 5.11-225

Dolby C™, 5.11-225

Dolby Labs™, 5.11-225

Dolby™, 5.11-225

Dummy Loads, 2.5-153

Dynamic Microphone, 5.6-115

—E—

E layer, 2.9-236

Effective Radiated Power (ERP), 2.5-117, 2.6-160—161,
 3.3-80—81
 definition, 2.5-125

Electrical Systems, 7.3-77—91
 efficient energy use, 7.3-91—93
 lagging power factor, 7.3-78—79
 leading power factor, 7.3-78—79
 maintenance, 7.3-94
 motor generator units (MGU), 7.3-85—86
 problems, 7.3-80—84
 assessment, 7.3-81
 measurement, 7.3-81
 suppression, 7.3-84
 processing line filters, 7.3-86—87
 standby power system, 7.3-87—91
 protection, 7.3-88
 transients, 7.3-80
 uninterruptible power systems (UPS), 7.3-86
 utility power system, 7.3-77
 utility company interfacing, 7.3-79—80

Electromagnetic Interference (EMI), 4.4-94

Electronic Field Production (EFP), 5.3-56—57

Electronic Industries Association (EIA), 3.6-185—186, 1.6-90
 Standards, 1.6-90—91

Electronic News Gathering (ENG), (*See* Video Tape Editing,
 1.5-79—81, 6.1-1—8, 6.2-19—27, 6.3-39)

Electrically Erasable Programmable ROM (EEPROM),
 3.7-200

Emergency Broadcasting System, 7.8-167—183
 checklist, 7.8-172—179
 local level, 7.8-172
 station responsibility, 7.8-172
 National Industry Advisory Committee, 7.8-181—183
 operation, 7.8-169
 organization, 7.8-168—169
 state and local level instructions, 7.8-179
 reception, 7.8-180—181
 state level, 7.8-171
 station responsibility, 7.8-171—172
 station responsibility, 7.8-170
 tests, 7.8-170—171

Environmental Protection Agency (EPA), 1.6-89
 National Environmental Protection Act (NEPA), 1.6-89

Equalizers, 5.6-117

—F—

F1 layer, 2.9-237

F2 layer, 2.9-237

FM, (*See* Frequency Modulation, and FM Antennas)

FM Antennas, 2.5-117—153
 antenna gain, 2.5-136—137
 antenna gain, definition, 2.5-125
 antenna site selection, 2.5-128
 beam tilt, 2.5-125—126
 blanketing, 2.5-125
 cavity panel antennas, 2.5-133
 class A station coverage, 2.5-126—127
 class B station coverage, 2.5-127—128
 commercially available antennas, 2.5-130—131
 community antenna economics, 2.5-136
 advantages, 2.5-136
 crossed dipole theory, 2.5-133—134
 directional antennas, 2.5-136
 effective radiated power (ERP), 2.5-117
 definition, 2.5-125
 FCC service contours, 2.5-122
 flat panel antennas, 2.5-133
 transmitter power, 2.5-136—137
 antenna installation on AM towers, 2.5-141—145
 accessory antenna system equipment, 2.5-152
 dummy loads, 2.5-153
 electrical heaters, 2.5-149—150
 FM SCA multiplexing, 2.5-151—152
 FM tower guying, 2.5-141—142
 break up insulators, 2.5-141—142
 effects on antenna, 2.5-141—142
 plastic guys, , 2.5-142 (Table) 2.5-143
 plastic rope, 2.5-142
 porcelain insulators, 2.5-142
 harmonic filters, 2.5-152
 installation procedures, 2.5-146—147
 planning, 2.5-146
 procedure, 2.5-146—147
 receiving and unpacking, 2.5-146
 interference, 2.5-152
 isolation transformers, 2.5-141
 diagram, 2.5-141
 lighting 2.5-151 (*See* listing)
 method, 2.5-145
 pattern optimization, 2.5-143
 pattern service, 2.5-145—146
 diagram, 2.5-145
 protection from icing, 2.5-149—150
 RF switches, 2.5-153
 radomes, 2.5-150—151
 reflectometers, 2.5-153
 spurious frequencies, 2.5-152
 structural considerations, 2.5-147
 antenna polemounting, 2.5-147
 wind loading, 2.5-147
 transmission lines, 2.5-147—148
 diagram, 2.5-148
 dielectrics, 2.5-148
 rigid coax, 2.5-148
 semiflexible coax, 2.5-148
 diagram, 2.5-144
 theory, 2.5-143—144
 (*See* VSWR)

FM signal measurements, 2.5-124—125
 requirements, 2.5-124—125

Fresnel zone clearance, 2.5-121—122
 diagram, 2.5-121
 formula, 2.5-121
 graph, 2.5-121

- general coverage standards, 2.5-123—124
 - high transmitter power ERP myth, 2.5-136
 - null fill 2.5-126
 - panel antennas, 2.5-132—134
 - polarization, 2.5-117—123
 - circular polarization-Cpol, 2.5-117,120,122—123
 - diagrams, 2.5-123
 - cross polarization, 2.5-117
 - elliptical polarization-Epol, 2.5-117
 - horizontal polarization-Hpol, 2.5-117,120
 - vertical polarization-Vpol, 2.5-117,120
 - recommended minimum antenna height, 2.5-122
 - ring stub antenna, 2.5-132
 - series fed antennas, 2.5-131
 - short helix, 2.5-132
 - short helix multi-arm, 2.5-131
 - shunt fed antennas, 2.5-131
 - slanted dipole FM antennas, 2.5-131
 - soil conductivity, 2.5-122
 - station diplexing, 2.5-137—140
 - branched starpoint, 2.5-139—140
 - cavity, 2.5-140
 - constant impedance type, 2.5-139
 - diagram, 2.5-138—139
 - diplexer, definition, 2.5-137—138
 - example, 2.5-140—141
 - twisted ring antenna, 2.5-132
 - wide-band antenna, 2.5-134—136
 - zones, 2.5-124
- FM Propagation, 2.5-118—120
- propagation loss, 2.5-118—119
 - multi-path problems, 2.5-119—120
 - diagram, 2.5-119
 - reflections, 2.5-119—120
 - ground reflections, 2.5-120
 - diagram-2.5-120
- (See Brewster Angle)
- FM SCA Multiplexing, 2.5-151—152
- FM Translators (See translators)
- Fan-Vee Antenna, 2.6-193
- Far field (See Fraunhofer Region)
- Federal Aviation Administration, 1.6-88
- Federal Communications Commission (FCC), 1.1-1—21, 1.6-89
- Code of Federal Regulations, 1.6-89
 - Communications Act of 1934, 1.1-1
 - licensing process, 1.1-5—7
 - application, 1.1-1
 - auxiliary and translator services, 1.1-7
 - direct broadcast satellites (DBS), 1.1-7
 - low power television (LPTV), 1.1-7
 - renewal, 1.1-6—7
 - sales/transfers, 1.1-7
 - steps, 1.1-6—7
 - types of facilities, 1.1-5—6
- structure, 1.1-5
- chart, 1.1-2
 - Common Carrier Bureau (CCB), 1.1-3
 - Field Operations Bureau (FOB), 1.1-3, 1.2-19—21
 - Enforcement Division, 1.2-19—20
 - Engineering Division, 1.2-19—20
 - field facilities, 1.2-20
 - field offices, 1.2-20
 - inspection, 1.2-20—21
 - actions, 1.2-21
 - appeals, 1.2-21
 - element, 1.2-20—21
 - off air monitoring, 1.2-21
 - violations, 1.2-21
 - monitoring stations 1.2-20
 - regional director, 1.2-20
 - Public Service Division, 1.2-19—20
 - Mass Media Bureau (MMB), 1.1-3
 - Audio Services Division, 1.1-3—4
 - AM branch, 1.1-4
 - Auxillary Services Branch, 1.1-4
 - FM Branch, 1.1-4
- Enforcement Division, 1.1-4
- Complaints and Investigations Branch, 1.1-4
 - Equal Employment Opportunity Branch, 1.1-4
 - Fairness/Political Broadcasting Branch, 1.1-4
 - Hearing Branch, 1.1-4
- Policy and Rules Division, 1.1-4—5
- Allocations Branch, 1.1-5
 - Legal Branch, 1.1-5
 - Policy Branch, 1.1-5
 - Technical and International Branch, 1.1-5
- Video Services Division, 1.1-4
- Cable Television Branch, 1.1-4
 - Distribution Service Branch, 1.1-4
 - Low Power Television Branch, 1.1-4
 - Television Branch, 1.1-4
- Office of Administrative Law Judges (ALJ), 1.1-3
- Office of General Counsel (OGC), 1.1-3
- Office of Managing Director (OMD), 1.1-1
- Office of Plans and Policy (OPP), 1.1-3
- Office of Science and Technology, (OST), 1.1-3
- Private Radio Bureau (PRB), 1.1-3
- Review Board (RB), 1.1-3
- FCC Service Contours, 2.5-122
- Fiber Optics, 4.4-93—103
- characteristics, 4.4-95—97
 - advantages, 4.4-93
 - attenuation or loss, 4.4-97
 - disadvantages, 4.4-94
 - dispersion, 4.4-96—97
 - index of refraction, 4.4-95
 - modes, 4.4-96
 - light and fiber characteristics, 4.4-94
 - multimode graded index, 4.4-96
 - multimode step index, 4.4-96
 - optical fibers, 4.4-95
 - single or mono modes step index, 4.4-96
 - types, 4.4-95—96
- video link, 4.4-93—103
- bandwidth, 4.4-93—94
 - digital multiplexing, 4.4-100
 - dimensions, 4.4-94
 - economics, 4.4-94
 - electromagnetic interference (EMI), 4.4-94
 - frequency modulation, 4.4-99
 - installation, 4.4-100—101
 - cable specifications, 4.4-101
 - intensity modulation, 4.4-96
 - loss, 4.4-94
 - modulation technique, 4.4-98
 - multiple video transmission, 4.4-99
 - optical device characteristics, 4.4-97
 - detectors, 4.4-97
 - sources, 4.4-97
 - pulse code modulation (digital), 4.4-99
 - system planning, 4.4-101
 - test equipment, 4.4-102—103
 - transmission techniques, 4.4-98
 - trouble shooting, 4.4-103
 - wavelength division multiplexing, 4.4-99—100
- Field Strength, 2.7-203—216
- AM Proof of Performance, 2.8-217—234
 - analysis of measurement to direct coverage, 2.7-212—213
 - antenna supporting mast, 2.7-211
 - attenuation, 2.4-64
 - chart recorder, 2.7-211
 - coverage measurement, 2.7-204—206
 - definition, 2.4-64
 - emergency procedures, 2.7-214—215
 - equipment principles, 2.7-207
 - FCC measurement method, 2.7-212

- FM field strength, 2.7-203
 - Fresnel zone radius formula, 2.7-206
 - horizontal RMS field strength, 2.4-78
 - inverse distance field, 2.4-64
 - measurement procedures and techniques, 2.7-212—213
 - meters, 2.7-209—210
 - power supplies, 2.7-211
 - precautions, 2.7-215—216
 - propagation, 2.7-207
 - receiving antennas, 2.7-210—211
 - spurious emission, 2.7-207
 - surveys, 2.7-213
 - television field strength, 2.7-203
 - time variation, 2.7-213—214
 - transmitting system evaluation, 2.7-206
 - (See AM Directional Arrays, and FM Antennas)
 - Film, 5.8-137—157
 - audio, 5.8-146—148
 - film density to electronic output, 5.8-138—140
 - low contrast print films, 5.8-138
 - recommended practices, 5.8-149—154
 - scanner, 5.8-140—143
 - slides, 5.8-148—149
 - splicing, 5.8-154—155
 - storage, 5.8-155—157
 - telescopes, 5.8-142—146
 - television pictures 5.8-140
 - Film Chains, 7.1-44
 - telescopes, 5.8-142—146
 - Flat Panel Antennas, 2.5-133
 - Fraunhofer Region (far field), 2.6-157
 - Frequency Analysis, 7.9-187—190
 - real time analyzer (RTA), 7.9-189—190
 - fast Fourier transform analyzer, 7.9-190
 - parallel analysis, 7.9-189
 - swept frequency, 7.9-188—189
 - Frequency Coordination, 1.3-49—62, 4.3-87
 - satellite antenna site selection, 4.3-87
 - aural STL considerations, 1.3-57—59
 - benefits for microwave users, 1.3-61
 - committee formation, 1.3-53—55, 62—64
 - coordination considerations, 1.3-51—52
 - history, 1.3-49—51
 - interference, 1.3-62
 - propagation anomalies, 1.3-59—61
 - television microwave considerations, 1.3-59—61
 - terrain considerations, 1.3-51
 - user density, 1.3-51
 - Frequency Modulation (FM), 3.3-63—111
 - characteristics, 3.3-63—65
 - FCC transmission standards, 3.3-65
 - high fidelity, 3.3-64—65
 - occupied bandwidth, 3.3-64—68
 - reduced noise, 3.3-63—65
 - stereo transmission, 3.3-65
 - subcarrier transmission, 3.3-65
 - combined transmitters, 3.3-98—101
 - filterplexing, 3.3-101—103
 - hybrid combiners, 3.3-99—101
 - hybrid couplers, 3.3-98—99
 - hybrid splitting, 3.3-101
 - installation, 3.3-108
 - maintenance, 3.3-110—111
 - operational measurements, 3.3-103—107
 - asynchronous AM, 3.3-107
 - audio frequency response measurement, 3.3-105
 - audio performance measurement, 3.3-105
 - carrier frequency measurement, 3.3-104
 - FM modulation measurement, 3.3-103—104
 - exciter, 3.3-75-79—80
 - metering, 3.3-79
 - output stage, 3.3-80
 - packaging, 3.3-80
 - field strength, 2.7-203
 - history, 3.3-63
 - logging of transmitter operating parameters, 3.3-104—105
 - power amplifier output circuits, 3.3-88—91
 - folded-half-wavelength cavity, 3.3-89—90
 - output coupling, 3.3-90—91
 - power amplifier cavity, 3.3-88—89
 - power amplifier source impedance, 3.3-91
 - quarter-wavelength cavity, 3.3-89
 - power supplies, 3.3-91
 - polyphase power supplies, 3.3-92
 - single phase power supplies, 3.3-92
 - special power supplies, 3.3-92—93
 - step start, 3.3-93
 - RF intermodulation, 3.3-102—103
 - RF output low-pass filters, 3.3-95—96
 - notch filters, 3.3-96
 - RF power amplifiers, 3.3-80
 - bandwidth considerations, 3.3-81
 - Gysel, 3.3-84
 - intermediate power amplifiers IPA, 3.3-81
 - “N-Way”, 3.3-83—84
 - performance requirements, 3.3-81
 - power output requirements, 3.3-80—81
 - solid state IPA systems, 3.3-83
 - splitter combiner, 3.3-83—84
 - RF power output, 3.3-104
 - signal noise ratio, 3.3-106
 - harmonic distortion, 3.3-106
 - total harmonic distortion (THD), 3.3-106
 - solid state FM transmitters, 3.3-85
 - standing wave ratio-SWR, 3.3-96—97
 - synchronous AM, 3.3-107
 - theory, 3.3-65—68
 - angular modulation, 3.3-65—66
 - Bessel Nulls, 3.3-67—68
 - Bessel function, 3.3-66—67
 - FM sideband structure, 3.3-66—67
 - modulation index equation, 3.3-65
 - phase modulation (PM), 3.3-65
 - theory, 3.3-65—66
 - transmission line power, 3.3-96—98
 - transmitters, 3.3-63—111
 - direct FM, 3.3-75
 - limiting factors, 3.3-71
 - modulator linearity, 3.3-76
 - pre-emphasis, 3.3-72—73
 - RF path, 3.3-71
 - transmitter control systems, 3.3-93—95
 - automatic power control-APC, 3.3-94
 - controller back-up systems, 3.3-94
 - microprocessor control systems, 3.3-94
 - purpose, 3.3-93
 - remote control interfacing, 3.3-95
 - “Turn-Around Loss”, 3.3-102—103
 - transmitter tuning, 3.3-107—108
 - vacuum tube power amplifier circuits, 3.3-85
 - cathode-driven triode amplifiers, 3.3-85
 - grid-driven tetrode and pentode amplifiers, 3.3-86—87
 - grounded grid versus grid-driven tetrode operation, 3.3-86
 - impedance matching into the grid, 3.3-87
 - neutralization, 3.3-88
- Frequency Monitors, 3.8-211—215
- Fresnel, 5.2-43
- Fresnel Zone, 2.5-121—122
 - diagram, 2.5-121
 - formula, 2.5-121
 - graph, 2.5-121
- Fresnel Zone radius Formula, 2.7-206

—G—

Genlock, 5.4-82—84
 Geosynchronous orbit, 4.3-79
 Ground Systems, 2.4-67,110
 grounding, 2.2-23
 (See lightning)

—H—

Harris Linear AM Stereo System (See AM Stereo)

—I—

Illumination Engineering Society of North America (IES), 1.6-44
 Institute of Electrical and Electronic Engineers (IEEE), 1.6-91—92
 Broadcast Technology Society, 1.6-91—92
 standards, 1.6-92
 Instructional Television Fixed Service (ITFS), 7.5-115—122
 Insulated Tower Base Impedance, 2.4-64—65
 Interference
 channel 6/FM antenna problem 2.5-128—129
 alternate locations, 2.5-129
 alternate polarization, 2.5-129
 collocation, 2.5-128—129
 rejection filters, 2.5-129
 FM, 2.5-152
 low power television, 7.4-100—104
 microwave, 4.2-71, 6.2-25—27
 translators, 7.4-100—104
 (See Federal Communications Commission, Frequency Coordination, and satellite systems)
 Interstage Coupling Circuits, 3.3-81—83
 Inverse Distance Field (See Field Strength)
 Ionosphere, 2.9-236

—K—

Kahn-Hazeltine Independent Sideband System (See AM Stereo)
 Klystrons, 3.5-155—162
 cavity tuning, 3.5-157
 efficiency, 3.5-158
 external cavity Klystron tuning, 3.5-158—159
 incidental phase, 3.5-162
 linearity correction, 3.5-162
 magnetic field, 3.5-157
 mod anode, 3.5-156—157
 mod anode pulsing, 3.5-160
 perveance, 3.5-156
 power calibration, 3.5-158
 pulsing, 3.5-160
 RF drive power, 3.5-157—158
 S Klystron visual, 3.5-161—162
 transmission line coupling, 3.5-157
 tuning, 3.5-158
 variable coupler for integral cavity, 3.5-161
 Ku Band, 4.3-79

—L—

Leadicon, 5.3-63
 Lightning protection, 2.3-23—31
 lightning conductor voltage drop (with formula), 2.2-23
 sideflash, definition, 2.2-23—24
 touch voltages, definition, 2.2-23

step voltages, definition, 2.2-23
 surge suppression, 2.2-24—31
 balance line suppressor, 2.2-30
 balance pairs-2.2-30
 components, 2.2-26—27
 gas tubes, 2.2-26
 metal oxide varistors (MOV), 2.2-26—27
 silicon avalanche devices, 2.2-27
 spark gaps, 2.2-26
 criteria, 2.2-26
 equipment suppressor, 2.2-28—29
 diagram, 2.2-28
 low level audio circuits, 2.2-30
 primary suppressor, 2.2-28
 RF circuit protection, 2.2-30
 shielding, 2.2-30—31
 secondary suppressor, 2.2-28
 diagram, 2.2-29
 surge protection, 2.2-29
 single (non-paired) conductors, 2.2-29
 diagram, 2.2-29
 video circuit protection, 2.2-30
 video surge protection, 2.2-30
 Local Area Network (LAN), 7.6-140
 Low Power Television Systems (LPTV), 1.1-7
 (See translators)

—M—

Magnetic Recording, 5.7-121—136, 5.11-217
 (See video tape recording and editing)
 AC bias 5.11-219—221
 optimum bias, 5.11-220—221
 penetration, 5.11-221
 alignment, 5.11-223
 azimuth, 5.11-223
 height, 5.11-223
 meridian, 5.11-223
 mono sum loss, 5.11-225
 speed, 5.11-225
 tape format, 5.11-225
 zenith, 5.11-223
 cleaning, 5.7-122—125
 equalization, 5.11-222—223
 head contour effects, 5.11-223
 history, 5.11-217—218
 maintenance, 5.11-233
 alignment, 5.11-237
 azimuth, 5.11-236
 cleaning, 5.11-236
 demagnetization, 5.11-235
 distortion, 5.11-236
 frequency response, 5.11-236
 head cleaning, 5.11-234
 noise, 5.11-236
 path cleaning, 5.11-235
 performance check, 5.11-236
 phase response, 5.11-236
 test tapes, 5.11-237
 torque, 5.11-236
 wow and flutter, 5.11-236
 operation, 5.7-122—125
 playback process, 5.11-221—222
 gap loss, 5.11-221
 recorded wavelength, 5.11-221
 speed, 5.11-222
 practice, 5.7-122—125
 principles, 5.7-127—136
 self erasure, 5.11-221
 storage, 5.7-125

- system performance, 5.11-225
 - encode-decode system, 5.11-225
 - Dolby A™, 5.11-225
 - Dolby B™, 5.11-225
 - Dolby C™, 5.11-225
 - Dolby Labs™, 5.11-225
 - Dolby™, 5.11-225
 - dBx™, 5.11-225
 - fluxivity, 5.11-225
 - high coecivity, 5.11-225
 - remenance, 5.11-225
 - single-ended noise reduction systems, 5.11-225
 - DNR, 5.11-226
 - Dynafex, 5.11-226
 - modulation noise, 5.11-226
- tape, 5.11-218—219
 - composition, 5.11-218—219
 - type, 5.11-218—219
- tape machine electronics, 5.11-226
 - bias, 5.11-226
 - control, 5.11-228—230
 - equalization, 5.11-226—228
 - flux level, 5.11-233
 - interfacing, 5.11-230
 - audio, 5.11-230
 - remote control, 5.11-230
 - performance, 5.11-231
 - reference level, 5.11-233
- Maintenance
 - towers (*See tower maintenance*), transmitters (*See individual listing*)
- Matching networks, 2.4-95—97
 - L networks, 2.4-95—97
 - diagram, 2.4-96—97
 - power divider, 2.4-97—99
 - diagrams, 2.4-98
 - ohms-law divider, 2.4-97
 - simplification, 2.4-99
 - tank-type divider, 2.4-97
 - T networks, 2.4-95
- Metal Oxide Varistors (MOV), 2.2-26—27
- Medium Wave (*See AM amplitude modulation*)
- Microphones, 5.6-115—116, 5.12-239
 - cardioid microphone, 5.6-116
 - care, 5.12-260
 - condenser microphone, 5.6-116
 - directional microphone, 5.6-116
 - distance, 5.12-249—250
 - acoustic gain devices, 5.12-249—250
 - distant miking, 5.12-250
 - frequency response, 5.12-250
 - shotgun, 5.12-249
 - durability, 5.12-252—253
 - dynamic microphone, 5.6-115
 - dynamic range, 5.12-252
 - frequency response, 5.12-243—244
 - noise problem, 5.12-253—258
 - AC hum, 5.12-255
 - acoustic phase interference, 5.12-255—258
 - acoustic phase cancellation, 5.12-258
 - high-pass filter, 5.12-253
 - popfilter, 5.12-253
 - radio frequency interference (RFI), 5.12-253
 - omnidirectional microphone, 5.6-116
 - output impedance, 5.12-252
 - phantom power, 5.12-242—243
 - polar patterns, 5.12-244
 - bidirectional, 5.12-244
 - cardioid, 5.12-244—248
 - dynamic range, 5.12-244—245
 - headset microphones, 5.12-249
 - inverse square law, 5.12-248—249
 - omnidirectional, 5.12-244—248
 - polar scaling, 5.12-244—245
 - supercardioid, 5.12-244
 - polarity reversal, 5.12-258—259
 - reliability, 5.12-252—253
 - ribbon microphone, 5.6-115
 - sensitivity rating, 5.12-250
 - EIA sensitivity rating, 5.12-251
 - line-level microphones, 5.12-252
 - open circuit output voltage, 5.12-250
 - power level, 5.12-251
 - stereo miking, 5.12-259—260
 - Blumfein technique, 5.12-260
 - mid-side coincident technique (M-S), 5.12-259
- transducer, 5.12-239
 - carbon, 5.12-239
 - condenser, 5.12-242
 - electret, 5.12-242
 - dynamic microphones, small size, 5.12-241
 - dynamic moving coil, 5.12-240—241
 - dynamic ribbon, 5.12-239—240
 - wireless microphone, 6.1-17
- Microwave EFP, 6.2-19
 - airborne considerations, 6.2-25—27
 - frequency considerations, 6.2-19—20
 - receive site, 6.2-20, 24—25
 - remote control, 6.2-25
 - tower, 6.2-20
 - van, 6.2-21—24, 25
 - (*See Frequency Coordination*)
- Microwave ENG, 6.2-19—27
 - van, 6.2-21—24, 25
 - (*See Frequency Coordination*)
- Microwave Systems, 4.2-59—77
 - antenna and wave guide considerations, 4.2-64
 - antenna feeders, 4.2-67
 - antenna systems, 4.2-64—65
 - horns, 4.2-66
 - isotropic antenna, 4.2-65—67
 - omni, 4.2-66
 - parabolas, 4.2-66
 - passive reflectors, 4.2-66
 - FCC licensing, 4.2-77
 - (*See Frequency Coordination*)
 - frequency planning, 4.2-76
 - heterodyne television microwave, 4.2-73
 - passive repeaters, 4.2-68—69
 - repeaters, 4.2-64
 - power, 4.2-75
 - power supplies, 4.2-73
 - receivers, 4.2-71
 - subcarriers, 4.2-74
 - transmitters, 4.2-70
 - K factor, 4.2-61—64
 - clearance requirements, 4.2-61
 - path profiles, 4.2-64
 - path performance, 4.2-59—61
 - free space path loss, 4.2-59—60
 - source of path loss, 4.2-60
- MOV (*See Metal Oxide Varistor*)
- Modems, 7.6-138
- Modulation Monitors, 3.8-211—215
 - calibration, 3.8-215
 - features, 3.8-212—214
 - FCC rules, 3.8-211—212
 - maintenance, 3.8-215
 - monitoring techniques, 3.8-214—215
- Monochrome Television System, 7.1-4
- Motorola C-Quam AM Stereo System (*See AM Stereo*)
- Multichannel Television Sound (BTSC System), 3.6-185
 - Broadcast Television Systems Committee (BTSC), 3.6-185—186
 - objective, 3.6-186
 - companding system, 3.6-189

- amplitude compression, 3.6-190
- fixed preemphasis, 3.6-190
- noise reduction, 3.6-189—190
- separate audio program channel (S.A.P.), 3.6-190
- spectral compression, 3.6-190
- compatibility, 3.6-194
- Electronic Industries Association, 3.6-185—186
- operation, 3.6-194—196
- stereo subcarrier, 3.6-187—188
 - monophonic channel, 3.6-187
 - pilot carrier, 3.6-188
- subcarriers, 3.6-191
 - "Common Mode" phase modulation, 3.6-193
 - incidental carrier phase modulation (ICPM), 3.6-193
 - intercarrier sound receivers, 3.6-193
 - performance specifications, 3.6-191—193
- Multiplexers, 2.4-105—106
- Multiplication Of Two Tower Patterns (*See* AM Directional Arrays)
- Multipoint Distribution Service (MDS), 7.5-115—122
 - antenna, 7.5-120
 - amplifiers, 7.5-120
 - block diagram, 7.5-117
 - down converter/receiver, 7.5-119—121
 - multichannel MDS, 7.5-115
 - RF system, 7.5-115—117
 - repeater, 7.5-119—120
 - response channels, 7.5-121—122
 - transmitters, 7.5-117—118
- Mutual Impedance Curves (AM directional antenna), 2.4-76—77

—N—

- National Association of Broadcasters (NAB), 1.6-91
 - phone list, 1.6-91
 - publications, 1.6-91
- National Bureau of Standards, 1.6-87—88
 - Time and Frequency Division, 1.6-87—88
 - WWV, 1.6-87—88
 - WWVB, 1.6-87—88
 - WWVH, 1.6-87—88
- National Cable Television Association (NCTA), 1.6-91
- National Industry Advisory Committee, 7.8-181—183
- National Labor Relations Board, 1.6-89
 - National Labor Relations Act, 1.6-89
- National Telecommunications and Information Administration (NTIA) 1.6-88
- National Television System Committee system (NTSC), 7.1-52, 54—58
- Nondirectional AM Antennas, 2.4-64—67
 - current and voltage distribution, 2.4-64—65
 - chart and formula, 2.4-64
 - folded conical monopole, 2.4-65—66
 - chart, 2.4-66
 - ground systems, 2.4-67
 - ground towers, shunt fed and folded monopole 2.4-65
 - insulated tower base impedance, 2.4-64—65
 - chart, 2.4-65
 - sectionalized towers, 2.4-66
 - top loading, 2.4-66
 - vertical radiation characteristics, 2.4-64
- Nonionizing Radiation (design consideration), 2.6-157, 163
 - charts, 2.6-164, 2.8-218

—O—

- Occupational Safety and Health Act (OSHA), 1.6-88
- Omnidirectional Microphone, 5.6-116
- Operational Amplifiers, 7.2-69—75
 - active filters, 7.2-73

- equalizers, 7.2-73
- Optical Fibers, 4.4-95

—P—

- PMX AM Stereo (*See* AM Stereo)
- Partial Proof, 2.8-220—221
- Phase Locked Loop AFC, 3.3-77—78
- Phase Modulation (PM), 3.3-65
- Plumbicon, 5.3-63
- Power Systems, (*See* Electrical Systems)
- Propagation, 2.9-235
 - above thirty megahertz, 2.9-241
 - smooth earth conditions, 2.9-241
 - K factor, 2.9-242
 - allocations, 2.9-236
 - beyond line-of-sight conditions, 2.9-242—243
 - coverage areas, 2.9-248—249
 - electromagnetic spectrum, 2.9-235
 - FM, 2.5-118—120
 - propagation loss, 2.5-118—119
 - multi-path problems, 2.5-119—120
 - diagram, 2.5-119
 - reflections, 2.5-119—120
 - ground reflections, 2.5-120
 - diagram-2.5-120
 - (*See* Brewster Angle)
 - free space propagation, 2.9-237—240
 - earth surface, 2.9-238—239
 - plane earth, 2.9-239—240
 - antenna heights, 2.9-239
 - dielectric constants, 2.9-240
 - effects, 2.9-239
 - ground conductivity, 2.9-240
 - horizontal polarization, 2.9-240
 - vertical colorization, 2.9-239
 - medium frequency (AM), 2.9-240
 - ground waves, 2.9-240
 - interference, 2.9-241
 - sky waves, 2.9-240—241
 - ionosphere, 2.9-240
 - solar activity, 2.9-241
 - obstacles, 2.9-243
 - atmospheric refraction, 2.9-247
 - refractive index, 2.9-247
 - buildings, 2.9-246
 - co-channel interference, 2.9-247
 - ducting, 2.9-247
 - hills, 2.9-244—246
 - vegetation, 2.9-246
 - quantifying propagation, 2.9-236
 - D layer, 2.9-236
 - E layer, 2.9-236
 - F1 layer, 2.9-237
 - F2 layer, 2.9-237
 - ionosphere, 2.9-236
 - stratosphere, 2.9-236
 - troposphere, 2.9-236
 - rain attenuation, 2.9-248
 - absorption, 2.9-248
 - (*See* VHF, UHF, AM, FM, Microwave, Satellite, and Frequency Coordination)
- Pulse Code Modulation (digital), 4.4-99

—Q—

- Quadruplex recorders, 5.5-90—91
- Quadruplex Video Tape Recorders, (*See* Video Systems)

—R—

Radar (Weather), 7.7-159
 Radio Electronic News Gathering (RENG), 6.1-1—10
 antenna, 6.1-10
 planning, 6.1-1
 remote pickup unit (RPU), 6.1-5
 wireless microphone, 6.1-17
 wireless systems, 6.1-2—4
 equipment, 6.1-3—4
 RF Circuit Protection (lightning), 2.2-30
 RF Switching, 2.10-251
 diplexers, 2.10-258—261
 Tee diplexer, 2.10-258
 filters, 2.10-253
 band pass filters, 2.10-254—258
 band stop filters, 2.10-254—258
 harmonic filters, 2.10-254
 multiplexer, 2.10-258—261
 patch panels, 2.10-251
 coaxial, 2.10-251
 waveguide, 2.10-251—252
 switches, 2.10-252—253
 manual coaxial switches, 2.10-252
 motorized coaxial switches, 2.10-252—253
 open wire switches, 2.10-253
 waveguide switches, 2.10-253
 transmitter systems, 2.10-261
 alternate main, 2.10-261
 parallel, 2.10-261
 AM, 2.10-262—263
 multi-transmitter different frequencies, 2.10-276—278
 coax system, 2.10-276—278
 shortwave, 2.10-262—263
 UHF, 2.10-271—275
 phaseshifters, 2.10-273—275
 switchless, 2.10-273—275
 VHF, 2.10-263—271
 switchless, 2.10-266—271
 single main, 2.10-261
 Random Access Memory (RAM), 3.7-200
 Read Only Memory (ROM), 3.7-200
 Rectangular Waveguide, 2.3-52—59
 charts and graphs, 2.3-53—58
 Remote Pickup Unit (RPU), 1.3-55—57, 61, 65, 1.5-79—81, 6.1-5
 Ribbon Microphone, 5.6-115
 RS170, 5.4-75

—S—

Safety, 2.1-5—6
 access facilities, 2.1-5—6
 elevator, 2.1-5—6
 ladder, 2.1-5
 stairways, 2.1-6
 transmission line bridges, 2.1-6
 (See lightning protection)
 Sampling loops, 2.4-101
 Satellite Systems, 4.3-79—91
 C Band, 4.3-79
 channeling, 4.3-79—80
 data on blanking interval, 4.3-84
 digital radio, 4.3-84
 earth station components, 4.3-84—87
 antenna, 4.3-84—85
 cassegrain antenna, 4.3-85
 horn antenna, 4.3-85
 multiple beam antenna, 4.3-85
 prime focus antenna, 4.3-84—85
 orthogonal mode transducer (OMT), 4.3-85
 low noise amplifier (LNA), 4.3-86

low noise converter, 4.3-86
 site selection, 4.3-86
 coordination contour, 4.3-87
 frequency coordination, 4.3-87
 interference, 4.3-87—88
 equation, 4.3-87
 FCC licensing, 4.3-88
 installation, 4.3-88—90
 maintenance, 4.3-90—91
 operation, 4.3-90
 frequencies, 4.3-79—80
 frequency division multiplexed/FM (FDM/FM), 4.3-84
 geosynchronous orbit, 4.3-79
 Ku band, 4.3-79
 polarization, 4.3-79—80
 satellite link analysis, 4.3-80
 signal types, 4.3-83
 audio subcarrier, 4.3-83
 data, 4.3-84
 full transponder/FM video, 4.3-83
 half transponder/FM video, 4.3-83
 slow scan video, 4.3-84
 teletext, 4.3-84
 single channel per carrier (SCPC), 4.3-84
 system description, 4.3-79—84
 time division multiplexing (TDM), 4.3-84
 (See Frequency Coordination)
 Saticon, 5.3-63
 Scanner, film, 5.8-142—143
 Scanning, Helical, (See Video Tape Recording)
 Second Audio Program Channel (S.A.P.), 3.6-190
 Security, Transmitter Site, 2.8-218
 Sequential Colour Avec Memoire (SECAM), 7.1-53, 61—63
 Series Fed Antennas, 2.5-131
 Shortwave, 3.1-25—26
 Shunt Fed Antennas, 2.5-131
 Single sideband AM subcarriers, 3.4-130
 Slanted Dipole FM Antennas, 2.5-131
 Slides, 5.8-148—149
 Slow Scan Video, 4.3-84
 Society of Broadcast Engineers, Inc. (SBE), 1.6-92
 certification program 1.6-92
 Society of Motion Picture and Television Engineers (SMPTE), 1.6-92—93
 Recommended Practice RP113-1983 Supervisory Protocol for Digital Control Interface, 5.10-198—216
 SMPTE time code, 5.5-104
 Soil Conductivity, 2.4-113, 2.5-122
 Stand-by power systems, (See electrical systems)
 Standing Wave Ratio (SWR), 3.3-96—97 (See Voltage Standing Wave Ratio)
 Stereophonic FM, 3.4-113—134
 baseband signal, 3.4-116—122
 frequency decoder circuits, 3.4-121
 phase locked loop, 3.4-121
 generators, 3.4-116—122
 performance, 3.4-128—130
 SCA to stereo interference, 3.4-131—134
 time division multiplex (TDM), 3.4-117, 119—121
 transmission standard, 3.4-116
 Stratosphere, 2.9-236
 Studio Lighting, 5.2-29—44
 architectural antenna, 5.2-36—38
 air conditioning, 5.2-37
 distribution, 5.2-37—38
 electrical, 5.2-36—38
 fixtures, 5.2-44
 Fresnel, 5.2-43
 lighting control, 5.2-38—44
 scoops, 5.2-43
 cyclorama, 5.2-34—36
 studio dimensions, 5.2-30
 suspension, 5.2-30—34

- battens, 5.2-32
 - catwalks, 5.2-32
 - fixed grid, 5.2-30—31
 - modular grid, 5.2-34
 - winches, 5.2-32
 - Studio Transmitter Link (STL), 3.7-205
 - Subcarrier, color, 7.1-27—36
 - subcarrier frequency accuracies, 7.1-36
 - subcarrier frequency error, 7.1-27
 - (See Multichannel Television Sound)
 - Subcarrier, FM, 3.4-113—134
 - Bessel function analysis, 3.4-125
 - composite baseband, 3.4-113—115
 - frequency spectrum, 3.4-115
 - glossary of terms, 3.4-113—114
 - history, 3.4-122—133
 - interference, 3.4-123—124
 - modulation limits, 3.4-115
 - operation, 3.4-124—126
 - subsidiary communication authorization (SCA), 3.4-122—133
 - requirements for operation, 3.4-123
 - types, 3.4-124—135
 - automotive road information (ARI), 3.4-121
 - data systems, 3.4-126—128
 - autofrequency shift keying (AFSK), 3.4-126
 - crosstalk, 3.4-134—135
 - data multiplexing, 3.4-128
 - direct data modulation, 3.4-127—128
 - frequency division multiplexing (FDM), 3.4-128
 - frequency shift keying (FSK), 3.4-127
 - guard bands, 3.4-128
 - indirect data modulation, 3.4-126—127
 - interference, 3.4-131—134
 - performance, 3.4-128—130
 - Subsidiary Communication Authorization (SCA), 3.4-122—133
 - Surge Suppression, 2.2-24—31
 - (See lightning)
 - Synchronizing Generator, 5.4-82—85, 7.1-3
 - Synchronizing Waveform, 5.4-75
- T—
- Tape, 5.11-218—219
 - composition, 5.11-218—219
 - type, 5.11-218—219
 - (See Magnetic Recording)
 - Telco (See Telephone Systems)
 - Telecine, (See film chain)
 - Telemetry, 3.7-207 (See Transmitter Control Systems)
 - Telemetry Return Link (TRL), 3.7-205
 - Telephone Systems, 6.4-41
 - access, 6.4-58
 - audio interfacing, 6.4-44—48, 55
 - hybrid, 6.4-45—48
 - QKT, 6.4-44—45
 - voice coupler, 6.4-44—45
 - cellular telephone, 6.4-52
 - digital telephone, 6.4-52
 - frequency shifting, 6.4-50—52
 - line test, 6.4-53—54
 - quality, 6.4-48—50
 - bandwidth, 6.4-49—50
 - processing, 6.4-41
 - satellites, 6.4-57
 - specification, 6.4-56
 - studio-transmitter link (STL), 6.4-53
 - switched network, 6.4-41—42
 - CODEC's, 6.4-41
 - frequency response, 6.4-41
 - phone pairs, 6.4-41
 - regulations, 6.4-42
 - signal to noise ratio, 6.4-42
 - C message weight, 6.4-42
 - subscriber loops, 6.4-41
 - switching circuit, 6.4-43—44
 - "A" leads, 6.4-43
 - HOLD, 6.4-43
 - lamp leads, 6.4-43
 - 25 pair color code, 6.4-44
 - tip/ring, 6.4-43
 - terminal equipment, 6.4-42
 - key systems, 6.4-42—43
 - PBX, 6.4-42—43
 - types of lines, 6.4-56—57
 - Teletext, 4.3-84
 - Television Antennas, 2.6-155—201
 - antenna assembly, 2.6-200
 - antenna design, 2.6-172—173
 - half-wave dipole, 2.6-172—173
 - loop, 2.6-173
 - panels, 2.6-174—176
 - charts, 2.6-174—175
 - slot antenna, 2.6-173—174
 - traveling wave antenna, 2.6-176
 - antenna gain, 2.6-157, 180, 181
 - antenna test, 2.6-198—199
 - azimuth pattern (horizontal plane), 2.6-156—159, 176—180
 - beam tilt, 2.6-162
 - bridge diplexing, 2.6-182
 - charts, 2.6-164
 - circular polarization, 2.6-161—162
 - constant impedance notch diplexer, 2.6-182—184
 - deflection and wind load, 2.6-171
 - economics, 2.6-157—160
 - effective radiated power (ERP), 2.6-160—161
 - elevation pattern, 2.6-158—159
 - feed systems, 2.6-181
 - branching, 2.6-181
 - standing wave feed systems, 2.6-181—182
 - traveling wave, 2.6-182
 - Fraunhofer region (far field), 2.6-157
 - frequency of rotation (formula), 2.6-170
 - graphs, 2.6-165—167
 - horizontal pattern (formula), 2.6-167—168
 - input impedance, 2.6-157, 180—181
 - installation, 2.6-199—200
 - maintenance, 2.6-200—201
 - multichannel television sound diplexer, 2.6-184—186
 - multiple antennas, 2.6-186
 - multiple cavities, 2.6-186
 - nonionizing radiation (design consideration), 2.6-157, 163
 - charts, 2.6-164
 - null fill, 2.6-166
 - pattern, 2.6-164—168, 176—186
 - pattern tests, 2.6-198
 - power capability, 2.6-162—163
 - radiating characteristics, 2.6-158—160
 - refectometer test, 2.6-199
 - systems planning, 2.6-187—188
 - antenna mounting methods, 2.6-186
 - emergency provisions, 2.6-187
 - antenna, 2.6-187
 - RF switching feature, 2.6-187—188
 - standby provisions, 2.6-187
 - transmission lines, 2.6-187
 - layout of transmission lines, 2.6-186—188
 - load location, 2.6-187
 - RF filter networks, 2.6-187
 - transmission line run, 2.6-186—187
 - propagation study, 2.6-186
 - system tests, 2.6-169
 - time domain reflectometers (TDR), 2.6-169
 - transmission line and components, 2.6-169
 - transmitter power, 2.6-157

- types, 2.6-188
 - cloverleaf panel, 2.6-195
 - CPV antenna, 2.6-193—194
 - delta dipole antenna, 2.6-189—190
 - Fan-Vee antenna, 2.6-193
 - pylon circular polarized, 2.6-197
 - pylon-UHF, 2.6-195—196
 - rhombic/butterfly panels, 2.6-193
 - ring panel, 2.6-195
 - slot-director antenna, 2.6-197
 - spiral antenna, 2.6-194
 - TDM antenna, 2.6-194
 - trasar-circular polarized, 2.6-197—198
 - travelling wave antenna, 2.6-190—193
 - UHF antenna linear polarized, 2.6-195
 - VHF circular polarized antenna, 2.6-193
 - VHF super turnstile/batwing, 2.6-188—189
 - wave star (omni), 2.6-196
 - zig-zag, 2.6-196
- uniform field distribution (formula), 2.6-164
- vertical alignment, 2.6-200
- vertical pattern (elevation model), 2.6-157
- vertical patterns, 2.6-164—166
- Voltage Standing Wave Ratio (VSWR), 2.6-168—170
- Television Field Production, 6.3-29—40
 - electronic field production, 6.3-39
 - electronic news gathering, 6.3-39
 - equipment, 6.3-32
 - cameras, 6.3-32—34
 - recorders, 6.3-34—35
 - switching, 6.3-35—38
 - operation, 6.3-38—40
 - microwave considerations, 1.3-59—61
 - (See microwave systems)
- Television Signal Transmission Standards, 4.1-1—50
 - amplitude versus frequency response, 4.1-49
 - audio-video time differential, 4.1-51
 - chrominance-luminance delay in equality, 4.1-18—19
 - chrominance-luminance gain in equality, 4.1-16—17
 - chrominance non-linear gain in distortion, 4.1-24—25
 - chrominance non linear phase distortion, 4.1-26—27
 - chrominance to luminance intermodulation, 4.1-36—37
 - continuity of audio service, 4.1-50
 - crosstalk noise, 4.1-44
 - differential gain, 4.1-32—33
 - differential phase, 4.1-34—35
 - dynamic gain, 4.1-30—31
 - field time wave form distortion, 4.1-10—11
 - gain frequency distortion, 4.1-20—21
 - harmonic distortion, 4.1-49
 - impulsive noise, 4.1-41
 - insertion gain, 4.1-8—9, 50
 - interconnection requirements, 4.1-95
 - line time wave form distortion, 4.1-12—13
 - luminance nonlinear distortion, 4.1-22—23
 - measuring techniques, 4.1-5—7
 - parameters, 4.1-5—7
 - performance, 4.1-5-7
 - performance standards for relay facilities, 4.1-2—3
 - periodic noise, 4.1-42-4-3
 - random noise weighted, 4.1-38—40
 - relative burst gain error, 4.1-47
 - relative burst phase error, 4.1-47
 - short time wave form distortion, 4.1-14—15
 - signal to noise ratio, 4.1-49—50
- Television Transmitters, 3.5-137—183
 - aural exciter, 3.5-149—155
 - BTSC Multichannel Sound System, 3.5-149—150
 - companding, 3.5-151
 - maskings, 3.5-151—152
 - noise, 3.5-151
 - preemphasis, 3.5-152
 - spectral companding, 3.5-152
 - transient protection, 3.5-153
 - transmitter requirements, 3.5-153—155
 - wideband amplitude companding, 3.5-153
 - combining circuits, 3.5-173—177
 - frequency control, 3.5-177—180
 - modulator, 3.5-142—149
 - active group delay equalizer, 3.5-145—146
 - delay compensators, 3.5-143—145
 - IF linearity precorrection, 3.5-147—149
 - passive group delay equalizer, 3.5-145
 - vestigial sideband filter, 3.5-146—147
 - performance measurements, 3.5-180—182
 - principles, 3.5-138—141
 - fields, 3.5-138
 - frames, 3.5-138
 - horizontal interval, 3.5-138—139
 - measurement units, 3.5-138
 - NTSC color transmission system, 3.5-141
 - picture, 3.5-138
 - vertical interval, 3.5-139—140
 - test signals (VITS), 3.5-140
 - RF generator, 3.5-149
 - tetrodes, 3.5-162—173
 - triodes, 3.5-162—173
 - UHF Klystrons, 3.5-155—162
 - cavity tuning, 3.5-157
 - efficiency, 3.5-158
 - external cavity Klystron tuning, 3.5-158—159
 - incidental phase, 3.5-162
 - linearity correction, 3.5-162
 - magnetic field, 3.5-157
 - mod anode, 3.5-156—157
 - mod anode pulsing, 3.5-160
 - perveance, 3.5-156
 - power calibration, 3.5-158
 - pulsing, 3.5-160
 - RF drive power, 3.5-157—158
 - S Klystron visual, 3.5-161—162
 - transmission line coupling, 3.5-157
 - tuning, 3.5-158
 - variable coupler for integral cavity, 3.5-161
 - video processing, 3.5-141—142
 - clamp circuit, 3.5-141—142
 - video precorrection, 3.5-142
 - visual exciter, 3.5-137
- Time Division Multiplex (TDM), 3.4-117, 119—121
 - time division multiplexing, 4.3-84
- Total Harmonic Distortion (THD), 3.3-106
- Towers, 2.1-1—20
 - access facilities, 2.1-5—6
 - elevator, 2.1-5—6
 - ladder, 2.1-5
 - stairways, 2.1-6
 - transmission line bridges, 2.1-6
 - aircraft marking, 2.1-5
 - design standards, 2.1-8—9
 - industry, 2.1-8
 - statutory, 2.1-9
 - finishes 2.1-5
 - corrosion protection, 2.1-1
 - electroplating, 2.1-5
 - flamespraying, 2.1-5
 - hot-dip galvanizing, 2.1-5
 - zinc rich paint, 2.1-5
 - FM antenna installation on AM towers, 2.5-141—145
 - grounded towers, 2.4-65
 - guyed, 2.1-2—3
 - diagram, 2.1-3
 - ice prevention, 2.1-5—6
 - insulated tower base impedance, 2.4-64—65
 - insulators, 2.1-4—5
 - base insulators, 2.1-4
 - guy insulators 2.1-4—5

- sectionalizing insulators, 2.1-4
 - materials, 2.1-3—5
 - guys, 2.1-4
- self-supporting towers, 2.1-1—2
 - chart, 2.1-2
- structures, 2.1-3—4,9—15
 - allowable stresses, 2.1-12—13
 - ice load, 2.1-9—10
 - safety factors, 2.1-12—13
 - seismic loads, 2.1-11
 - temperature changes, 2.1-10—11
 - width restrictions, 2.1-13—15
 - antenna mounting, 2.1-13—14
 - foundation and anchors, 2.1-14—15
 - construction, 2.1-15
 - guy anchors, 2.1-15
 - guyed tower base foundations, 2.1-15
 - self-supporting tower foundations, 2.1-15
 - soil investigation, 2.1-15
 - wind load, 2.1-9
 - chart-2.1-10
- Tower Construction, 2.1-15—17
 - assembly, 2.1-16
 - chart, 2.1-16
 - guy installation, 2.1-17
 - preparation, 2.1-16
 - access, 2.1-16
 - clearing, 2.1-16
 - electrical power, 2.1-16
 - permits, 2.1-16
 - stacking, 2.1-16—17
- Tower Lighting, 2.1-6
 - Blondel-Ray relationship, 2.1-7
 - candella, definition, 2.1-7
 - FAA requirement, 2.1-6—7
 - medium intensity electronic lights, 2.1-7
 - red lights with orange and white paint, 2.1-6—7
- Tower Maintenance, 2.1-17—20
 - structure
 - alignment, 2.1-17—18
 - base insulator, 2.1-19—20
 - condition of paint, 2.1-17
 - connections, 2.1-17
 - corrosion, 2.1-17
 - damage or deformed member, 2.1-17
 - elevator system, 2.1-20
 - lighting system, 2.1-20
 - safety device, 2.1-20
- Translators, 7.4-95—114
 - coverage, 7.4-101—104
 - input signal considerations, 7.4-104
 - antenna stacking, 7.4-105
 - filtering 7.4-105
 - preamplification, 7.4-104—105
 - installation, 7.4-111—113
 - power, 7.4-111—113
 - protection, 7.4-112
 - security, 7.4-112
 - shelter, 7.4-111—112
 - multiple outputs, 7.4-95
 - offset operation, 7.4-114
 - regulatory requirements, 7.4-100—101, 110
 - FM, 7.4-100—101
 - low power television (LPTV) application, 7.4-110
 - television, 7.4-100—101
 - site selection, 7.4-95
 - block diagrams, 7.4-95—99
 - stereo television (BTSC system), 7.4-113
 - Surface Acoustic Wave (SAW), 7.4-113
 - SAW filters, 7.4-113—114
 - transmitting systems, 7.4-105—108
 - antennas 7.4-106
 - combiners 7.4-107—108
 - isolators, 7.4-107—108
 - noise, 7.4-108
 - towers, 7.4-107
 - transmission lines, 7.4-106—107
 - air dielectric, 7.4-106—107
 - foam dielectric, 7.4-107
 - voltage standing wave ratio, 7.4-107—108
- UHF translator, 7.4-108—111
 - amplifier stages, 7.4-110
 - mixing process, 7.4-110
 - output circuitry, 7.4-110
 - specifications, 7.4-111
 - UHF input, 7.4-108
 - VHF input, 7.4-108—110
- Transmission Lines, 2.3-33—62, 2.4-100—101, 110
 - characteristic impedance, 2.4-100
 - coaxial transmission lines, 2.3-33—36
 - graphs, 2.3-34—35
 - dead load, 2.1-13
 - indoor installation considerations, 2.3-51
 - installation-run considerations, 2.3-50—52
 - dimensions, 2.3-52
 - horizontal, 2.3-51
 - vertical, 2.3-50—51
 - jacketing, 2.4-100
 - line losses, 2.4-100
 - line mismatch, 2.4-101
 - moisture (from new line), 2.3-51
 - phase-stabilized line, 2.4-100—101
 - rigid coaxial transmission line, 2.3-40—52
 - features, 2.3-40
 - transmission line section length, 2.3-40
 - charts and graphs, 2.3-41—50
 - formula, 2.3-40
 - reflection, 2.3-40
 - semi-rigid transmission line, 2.3-36
 - chart, 2.3-36—39
 - diagram, 2.3-37—38
 - installation, 2.3-36—40
 - preparation, 2.3-36
 - hanger installation, 2.3-36—39
 - horizontal runs, 2.3-39
 - ice loading, 2.3-36—40
 - ice shields, 2.3-36—40
 - power handling of semi-rigid transmission lines, 2.3-40
 - pressurization, 2.3-40
 - transmission line fittings, 2.4-101
 - wave guides (*See listing*)
 - wind load, 2.1-13
- Transmitter Control Systems, 3.7-197—210
 - AM base currents, 3.7-208
 - analog block diagram, 3.7-199
 - control terminal, 3.7-202—204
 - FCC regulations, 3.7-198—199
 - filament voltage, 3.7-209
 - line voltage, 3.7-209
 - modulation monitors, 3.7-210
 - power supply, 3.7-208
 - RF power input, 3.7-208
 - remote control, 3.7-200—202
 - digital, 3.7-201
 - remote terminal, 3.7-204—205
 - status input, 3.7-209
 - studio transmitter link (STL), 3.7-205
 - telemetry return link (TRL), 3.7-205
 - television monitoring equipment, 3.7-209
 - temperature, 3.7-209
 - terminal communication, 3.7-205—206
 - theory, 3.7-199—200
 - binary coded decimal (BCD), 3.7-200
 - electronically erasable programmable ROM (EEPROM), 3.7-200
 - random access memory (RAM), 3.7-200

- read only memory (ROM), 3.7-200
- tower lights, 3.7-208
- transmitter facility interfacing, 3.7-206—208
 - command, 3.7-207
 - control, 3.7-207
 - metering, 3.7-207
 - plate current, 3.7-207—208
 - plate voltage, 3.7-207
 - telemetry, 3.7-207
- transmitter to studio link (TSL), 3.7-205
- types, 3.7-197—198
- wireless communications, 3.7-206—207
- Transmitter to Studio Link (TSL), 3.7-205
- Troposphere, 2.9-236
- “Turn-Around Loss,” 3.3-102—103
- Turntables, 5.6-113—115

—U—

- U-format, (*See* Video Systems)
- U-matic, (*See* Video Systems)
- UHF, (*See* Klystron)
- Underwriters Laboratories (UL), 1.6-94

—V—

- Vacuum Tube Power Amplifier Circuits, 3.3-85
 - cathode-driven triode amplifiers, 3.3-85
 - grid-driven tetrode and pentode amplifiers, 3.3-86—87
 - grounded grid versus grid-driven tetrode operation, 3.3-86
 - impedance matching into the grid, 3.3-87
 - neutralization, 3.3-88
- Video, 5.4-73
- Video Signal Switching, 5.4-80—82
 - multiple bus switching, 5.4-80—82
 - single bus switchers, 5.4-80
 - switching system control, 5.4-82
- Video Signal Timing, 5.4-82—83
 - genlock, 5.4-83—84
 - timing, 5.4-85—88
- Video Systems
 - editing, (*See* Video Tape Editing)
 - half-inch format, 5.9-165—172
 - features, 5.9-168—170
 - control track, 5.9-168
 - editing features, 5.9-169
 - noise reduction, 5.9-169
 - recorders, 5.9-169
 - time code generator, 5.9-169
 - fundamentals, 5.9-165—166
 - Betacam format, 5.9-165
 - chrominance (C), 5.9-165, 168
 - component recording, 5.9-165—166
 - luminance (Y), 5.9-165, 168
 - MII-format, 5.9-165
 - M format, 5.9-165
 - maintenance, 5.9-170—171
 - cleaning, 5.9-170
 - head degaussing, 5.9-170
 - head drum slip rings, 5.9-170
 - pinchroller, 5.9-170
 - tape path, 5.9-170
 - video heads, 5.9-170
 - head optimization, 5.9-170
 - head replacement, 5.9-170
 - operational check, 5.9-170
 - tension check, 5.9-170
 - test equipment, 5.9-171
 - tools, 5.9-171
 - solder stations, 5.9-171
 - principles, 5.9-166—168

- trouble shooting, 5.9-171—172
 - alignment tape, 5.9-172
 - audio system, 5.9-172
 - control system, 5.9-171
 - power supply, 5.9-172
 - servo system, 5.9-172
 - tape runs, 5.9-171—172
 - tension, 5.9-171
 - threading, 5.9-171
 - video system, 5.9-172
- U-format, 5.9-159—163
 - color, 5.9-159—160
 - chrominance (C), 5.9-159—160
 - luminance (Y), 5.9-159—160
 - NTSC composite video signal, 5.9-160
 - drum, 5.9-159
 - effective drum diameter, 5.9-159
 - electronic switching, 5.9-162
 - helical-scan, 5.9-160—162
 - helix angle, 5.9-159
 - lower drum, 5.9-159
 - maintenance, 5.9-163
 - alignment tape, 5.9-164
 - audio system, 5.9-165
 - cleaning, 5.9-163
 - head degaussing, 5.9-163
 - head drum slip rings, 5.9-163
 - pinch roller, 5.9-163
 - tape path, 5.9-163
 - video heads, 5.9-163
 - control system, 5.9-164
 - head optimization, 5.9-163—164
 - head replacement, 5.9-163—164
 - operational check, 5.9-163
 - power supply, 5.9-165
 - servo system, 5.9-164
 - tape run, 5.9-164
 - tension, 5.9-164
 - tension detector adjustment, 5.9-163
 - threading, 5.9-164
 - troubleshooting, 5.9-164
 - video system, 5.9-165
 - scanner, 5.9-159—160
 - specifications, 5.9-162
 - features, 5.9-162
 - drop-out compensation, 5.9-162
 - dubbing, 5.9-162
 - editing, 5.9-162
 - search, 5.9-162
 - time base correctors, 5.9-162
 - time code generator, 5.9-162
 - SMPTE time code, 5.9-162
 - tracking, 5.9-162
 - track angle, 5.9-159
 - video heads, 5.9-160—162
 - wrap angle, 5.9-159
 - Video Tape Editing, 5.10-175
 - decision list, 5.10-184
 - design considerations, 5.10-194—195
 - disc technology, 5.10-176—178
 - edit commands, 5.10-178-1
 - edit timing, 5.10-178
 - editor control, 5.10-181—184
 - external devices, 5.10-195—197
 - hardware systems, 5.10-184—186
 - interfaces, 5.10-186—194
 - audio mixer, 5.10-192—193
 - audio tape recorder, 5.10-188
 - digital control interface, 5.10-198—215
 - digital video effects, 5.10-191—192
 - tape speed override (TSO), 5.10-187
 - video switcher, 5.10-188—191
 - preview system, 5.10-193—194

time code editing controller, 5.10-179—181
 dialogue, 5.10-181
 SMPTE time-code, 5.10-180, 187—188
 sync error, 5.10-180

Video Tape Recording, 5.5-89—106
 C-format helical recorder, 5.5-91—100
 servo systems, 5.5-96
 capstan, 5.5-96
 tape tension, 5.5-96
 tape transport, 5.5-91—95
 control systems, 5.5-103—104
 disc recorders, 5.5-106
 formats, 5.5-106
 history, 5.5-89—90
 quadruplex recorders, 5.5-90—91
 signal system, 5.5-100—101
 modulation, 5.5-101
 playback, 5.5-101
 SMPTE time code, 5.5-104
 time base correction, 5.5-102—103
 digital time correctors, 5.5-102—103
 video heads, 5.5-96—100
 position, 5.6-96—98
 video tape editing, 5.5-104
 (See Magnetic Recording)

Voltage Standing Wave Ratio (VSWR), 2.6-168—170, 3.3-97
 waveguides, 2.3-61—62
 bandwidth, 2.5-129—130
 intermodulation and AM distortion, 2.5-129—130

—W—

WWV, 1.6-87—88
 WWVB, 1.6-87—88

WWVH, 1.6-87—88

Waveguides, 2.3-51—62
 circular waveguide, 2.3-51—52
 rectangular waveguide, 2.3-52—59
 charts and graphs, 2.3-53—58
 waveguide installation, 2.3-59—62
 hangers, 2.3-59—61
 horizontal, 2.3-59
 installation, 2.3-60
 vertical, 2.3-59
 lateral braces, 2.3-59
 materials, 2.3-59
 pressurization systems, 2.3-61
 storage, 2.3-60
 Teflon probe, 2.3-61—62
 tower top, 2.3-59
 tuners, 2.3-60
 tuning, 2.3-61—62
 VSWR, 2.3-61—62

Weather Radar Systems, 7.7-159—165
 colorizers, 7.7-161
 conventional (noncoherent) Radar, 7.7-160
 dial-up weather Radar data, 7.7-1—65
 Doppler (coherent) Radar, 7.7-160
 Radar (Radio Detection and Ranging), 7.7-159
 history, 7.7-159
 Naval Research Laboratory (NRL), 7.7-159
 principles, 7.7-159
 Radar displays, 7.7-160—161
 digital video integration processor (DVIP), 7.7-160
 plan position indicator (PPI scope), 7.7-160
 range height indicator (RHI scope), 7.7-160
 remoting, 7.7-161
 typical applications, 7.7-162—165

Wide Band Antenna, 2.5-134—136

Wireless Microphone, 6.1-17