


Radio

www.RadioMagOnline.com

A supplement to Radio magazine



PRODUCT

SOURCE



What's
Google
doing with
radio automation?

Google has been redeveloping
SS32 and Maestro from the ground up.
Our new system can be summed up
in just three words...

Progressive. Flexible. Sound.

© Copyright 2007. All rights reserved. Google and Google logo are registered trademarks of Google Inc.

800-726-8877

Visit www.google.com/radioautomation
to find out more.

Come see us at the NAB Radio Show.
September 26 - 28th in Charlotte, NC. Booth # 517.

A Penton Media Publication

Condition your *Signal*

with the New Vorsis® HD-P3

What Is It?


A four-band parametric equalizer feeding a three-band limiter with adjustable crossover points, AGC and selectable filters for FM, AM or streaming audio formats. The HD-P3 includes a variable de-esser, an expander and dual digital outputs (one with user selectable HD latency FM delay), plus high pass, low pass and notch filters, and a signal de-correlator to optimize bass content. All this controlled by an ethernet protocol computer interface that lets you run one or many HD-P3s from your office or internet based locations.

What It's For:

Processing for your new HD signal, improving your existing FM or AM signal chain, preprocessing streaming audio-over-internet, a standalone HD processor or a realtime DJ monitor feed—and finally—a KILLER studio production tool.

What's It Like?

"PERFORMANCE WITH OVERDRIVE"



VORSIS®

It's What's Next in Processing

a division of Wheatstone

Copyright © 2007 by Wheatstone Corporation

ONE

Harris — The ONE choice for end-to-end radio solutions.



ZX™ Series

FM tri-mode transmitters featuring multiple PA modules and power supplies for maximum redundancy. When used with the FlexStar™ HDx Exciter, the ZX™ Series can operate in either digital only or FM/FM-HD. ZX transmitters are available from 500 W to 3500 W.

FlexStar™

HDx Exciter brings HD Radio™ and analog audio to a new level. Featuring real-time adaptive correction for increased power and efficiency and the latest iBiquity platform in HD Radio™ — Engine — HDx Exciter unlocks new revenue streams.

Destiny™ 3DX-50

Highly efficient, medium-wave transmitter, and the latest in the DX™ family of world-class digital AM transmitters. Fully compatible with HD Radio and DRM. Harris AM transmitters are available from 1 kW to 2 MW.

PR&E NetWave™

Modular, network-enabled, high-performance radio broadcast console packed with features that are perfect for small to medium studios. Share all your studio resources throughout the facility with the Harris® VistaMax™ audio management system.

HD Radio is a trademark of iBiquity Digital Corporation.

From AM/FM and HD Radio™ and DRM transmission to program audio transport to consoles to broadcast studios — Harris offers you the best products and systems in the business backed by outstanding customer service.

For more information visit www.broadcast.harris.com/radio, call +1 800 622 0022 or broadcastsales@harris.com.

Harris is the ONE company delivering interoperable workflow solutions across the entire broadcast delivery chain with a single, integrated approach.

Business Operations • Media Management • Newsrooms & Editing • Core Processing • Channel Release • Media Transport • **TRANSMISSION**



assuredcommunications®

Broadcast • Government Systems • RF Comm • Microwave

www.harris.com

PRODUCT SOURCE

THE RADIO PRODUCT SOURCE

The Changing Landscape

Radio broadcasting, especially in the last few years, is changing immensely. What with the introduction of HD Radio, satellite subscription services and webcasting stations on the Internet, let's face it, radio is not exactly what it used to be. But radio will always adapt and evolve with cultural and technological advancements, and now more than ever, the *Radio* magazine Product Source can help guide you along this ever-transforming path.

This year, the Product Source is full of new technologies, new ideas and the tried-and-true. As always, we are bringing you information on products for remote broadcasting in Out and About; production in Portable Production; everything you need for off-site settings in Beyond These Walls; and the latest in literature, because you know we can never stop learning, in Reference Room. But new this year, is the Music Libraries section, with resources to enhance that dull void often called the background. And of course there are our 15 Pick Hits from NAB2007.

We hope that we are a valued resource for your product needs and welcome all feedback. We believe that we have assembled an impressive collection of new products, but if you have a favorite product that we should include or highlight in *Radio* magazine, we'd love to hear from you. Please contact us at radio@penton.com.



**Erin Shipps,
Associate editor**


Special Section Index

Out and About.....	19
Portable Production.....	25
Beyond These Walls.....	27
Reference Room.....	31
Music Libraries.....	35


Radio®

www.RadioMagOnline.com

A supplement to **Radio** magazine




**Comrex
Page 19**



**Belden
Page 25**

PRODUCT SOURCE



**Ledtronics
Page 6**



**Central Music
Company
Page 33**

A Penton Media Publication

Radio®

THE RADIO TECHNOLOGY LEADER

www.RadioMagOnline.com
radio@penton.com

Editor - Chris Scherer, CPBE/CBNT, chris.scherer@penton.com
Technical Editor, RF - John Battison, P.E., john.battison@ohio.net
Associate Editor - Erin Shipps, erin.shipps@penton.com
Senior Art Director - Michael J. Knust, mike.knust@penton.com
Art Director - Robin Metheny, robin.metheny@penton.com
Online Audience Development Manager - Brad Erpelding, brad.erpelding@penton.com

Technical Consultants

Harry C. Martin, Legal
Kevin McNamara, CNE, Computers and Networks
Mark Krieger, CBT, IBOC and Contract Engineering
Russ Berger, Broadcast Acoustics
Donald L. Markley, P.E., Transmission Facilities

Division VP & Group Publisher - Jonathan Chalon, jonathan.chalon@penton.com
Marketing Director - Kirby Asplund, kirby.asplund@penton.com
Marketing Coordinator - Crystal Shires, crystal.shires@penton.com
Vice President of Production - Lisa Parks, lisa.parks@penton.com
Senior Director of Production - Curt Pordes, curt.pordes@penton.com
Group Production Mgr. - Melissa Langstaff, melissa.langstaff@penton.com
Production Coordinator - Liz Stolte, liz.stolte@penton.com
Classified Ad Coordinator - Sarah Maxey, sarah.maxey@penton.com
VP Audience Marketing - Jerry Okabe, jeremy.okabe@penton.com
Audience Marketing Dir. - Barbara Kummer, barbara.kummer@penton.com
Audience Marketing Mgr. - JoAnn DeSmet, joann.desmet@penton.com

MEMBER ORGANIZATIONS

Sustaining Member of:
• Acoustical Society of America
• Audio Engineering Society
• Society of Broadcast Engineers
Member: American Business Media, The Missouri Association of Publishers



missouri association of publications

A PENTON MEDIA PUBLICATION

 **Penton Media**

Penton Media, Inc.
249 West 17th Street
New York, NY 10011

Chief Executive Officer - John French, john.french@penton.com
Chief Financial Officer - Eric Lundberg, eric.lundberg@penton.com
Vice President, General Counsel - Robert Feinberg, robert.feinberg@penton.com

SUBSCRIPTIONS: Free and controlled circulation to qualified subscribers. Non-qualified persons may subscribe at the following rates (Prices subject to change): USA and Canada, 1 year, \$66.00, 2 years, \$116.00, 3 years, \$165.00. Outside the USA and Canada, 1 year, \$83.00, 2 years, \$149.00, 3 years, \$215.00 surface mail (1 year, \$127.00, 2 years, \$237.00, 3 years, \$347.00 airmail delivery). For subscriber services or to order single copies, write to Radio magazine, 2104 Harvell Circle, Bellevue, NE 68005 USA; call 866-505-7173 or 402-505-7173; or visit RadioMagOnline.com.

POSTMASTER: Send address changes to Radio, P.O. Box 2100, Skokie, IL 60076-7800 USA.

ARCHIVES & MICROFORM: This magazine is available for research and retrieval of selected archived articles from leading electronic databases and online search services, including LexisNexis, and Proquest. For microform availability, contact National Archive Publishing Company at 800-521-0600 or 734-761-4700, or search the Serials in Microform listings at napubco.com.

REPRINTS: Contact FosteReprints to purchase quality custom reprints or e-prints of articles appearing in this publication at 866-436-8366 (219-879-8366 outside the U.S. and Canada). Instant reprints and permissions may be purchased directly from our website; look for the RSICopyright tag appended to the end of each article.

PHOTOCOPIES: Authorization to photocopy articles for internal corporate, personal, or instructional use may be obtained from the Copyright Clearance Center (CCC) at 978-750-8400. Obtain further information at copyright.com.

PRIVACY POLICY: Your privacy is a priority to us. For a detailed policy statement about privacy and information dissemination practices related to Penton Media, Inc. products, please visit our website at penton.com.

EDITORIAL and BUSINESS OFFICE: Penton Media, Inc. 9800 Metcalf, Overland Park, KS, 66212; 913-341-1300; RadioMagOnline.com; penton.com.
Copyright 2007, Penton Media, Inc. All Rights Reserved.

Sales Offices

National Sales Manager

Steven Bell

Phone: 913-967-7221; Fax: 913-514-6848
E-mail: steven.bell@penton.com

Europe/UK

Richard Woolley

Phone: +44 1295 278 407
Fax: +44 1295 278 408
E-mail: richard.woolley@btclick.com

Classified Advertising

Joyce Nolan

Phone: 610-701-9993
Fax: 610-701-0580
E-mail: joyce.nolan@penton.com

Online Sales & Marketing

Angie Gates

Phone: 913-967-7516
Fax: 913-514-7516
E-mail: angie.gates@penton.com

List Rental Services


Marie Briganti

Walter Karl
Phone: (845) 732-7054
Fax: (845) 620-1885
marie.briganti@walterkarl.infousa.com

Editorial Reprints

FosteReprints

Phone: (866) 436-8366
(219) 879-8366



Impossible Remote? Nah, You've Got ACCESS.


Meet Another Real-World Super Hero...

Broadcasting a live Phoenix radio program from out to sea would be challenging for even the most seasoned veterans. Not for Attorney and Certified Financial Planner® (and world traveler) Keith DeGreen. Keith is shown here using the Comrex ACCESS Portable as he and his ship, The Global Adventure, approach Koror Harbor In The Republic of Palau—450 miles east of the Philippines and 7,200 miles from Phoenix!

ACCESS delivers mono or stereo over DSL, Cable, Wi-Fi, 3G cellular, satellite, POTS (yep, ACCESS is a full featured POTS codec and works seamlessly with Matrix, Vector and Bluebox)—plus some services you may not have even heard of. Given the challenges of the public Internet, it's no small boast to say that ACCESS will perform in real time over most available IP connections.

Contact Comrex today and find out how ACCESS can make you become a Real-World Super Hero—wherever you are!

Keith has been broadcasting his radio program, a unique mix of personal finance, economics, politics, and real-life "extreme broadcasting" adventure for 19 years. Listen live 5-11AM Sunday mornings AZ time on NewsTalk 550, KFYI, or catch Keith's archived shows, and enjoy the amazing videos, photos and blogs of his open-ended 'round-the-world journey at his website, www.theglobaladventure.com.



ACCESS

Put Comrex On The Line.

COMREX

Toll Free: 800-237-1776 • www.comrex.com • e-mail: info@comrex.com
19 Pine Road, Devens, MA 01434 USA • Tel: 978-784-1776 • Fax: 978-784-1717

Keith DeGreen says:
"Whether I'm a thousand
miles out to sea, visiting
unusual ports of call or
exploring remote
inland places, my
Comrex ACCESS
Portable empowers
me to project a
broadcast-quality signal
back home at anytime
from virtually anywhere."

2007 PRODUCT SOURCE


Cable connector **Neutrik**

EMC-XLR: The EMC-XLR is comprised of three-pole male/female XLR cable connectors with integrated LC-filters, which avoid the RD interference and LF noise. There is also a 360-degree shield contact on the female connector that ensures shielding and chassis contact. This connector can solve problems such as ground loops, RF interference and Pin 1 problems.

732-901-9488; www.neutrik.com
info@neutrikusa.com



Audio software suite **KLZ Innovations**



Audiofile: Use the GPI delay system, mic skimmer, audio logger, silence detector and MP3 streamer/extractor simultaneously on all eight channels with this post-broadcast audio suite. Users can choose from two, four, six or eight channels, each pair configured as stereo or dual mono. MP3-archiving, skimming and streaming is built-in. Remote access is also included via KLZ Webserver technology. Audio is linear 48kHz PCM. GPI delay requires a GPI interface that includes four opto-coupled inputs, eight relay outputs. The interface features a timeline, channel/date tree, skim segments and three players.

800-334-9640; www.klz.com
info@klz.com

Radio test set **Aeroflex**

3920 Radio Test Set: The 3920 features more test capabilities integrated into one system, as well as extended analysis range and file management functions. The 3920 performs all the tests previously capable with the 3901 and 3902, including Tetra mobile station, base station and direct mode test features. An optional 3½ digit DMM function includes the ability to measure AC and DC voltage, current as well as resistance. The 3920 is fully protected against over voltage or current conditions with a front panel fuse. It can export files to USB drives and connect external USB input devices. The 3920 can be used for analyzing high level audio signals including measurements for AF frequency, AF level, sinad, distortion, hum and noise and signal to noise ratio. The 3920 provides RF operation from 10MHz (usable from 100kHz) to 1GHz standard, with OPTO58 providing the ability to go to 2.7GHz.

1-800-843-1553; www.aeroflex.com; info-test@aeroflex.com

Upgrade to remote control system **Davicom/Comlab Telecommunications**



but has a limited number of inputs/outputs (eight metering inputs, 16 status inputs, two audio inputs, eight physical relays and one reach-through serial port), and cannot be expanded. Version 5 of the firmware is daylight-saving time ready for North America, offers bilingual voice and screen capability (supporting Unicode character sets), multiple alarm-call lists (for day/night workshifts, weekends or specific events) and a user-defined log. Configuration and control of Mini-MAC and MAC units is ensured by the included Mac Comm software version 5, which allows customized view screens for each user and site.


418-682-3380; www.davicom.com; info@davicom.com

Next Generation Mini-MAC:

The newest unit shares many features with its big brother, the MAC, and it can also be used to save paper and archive EAS messages. The system runs in the background of any Windows 2000/XP computer. The software generates a warning if planned tests do not occur. One computer can be used to capture and e-mail messages from multiple receivers. Users can automatically publish EAS messages to a website with the Web Ready add-on.

800-833-4459
www.wireready.com
sales@wireready.com

EAS, Wire Service Capture **Wireready**



Alert Ready: This electronic newsroom, EAS alert and wire service capture software allows the user to capture all these events in a personal e-mail account. It stores the needed documentation if the EAS printer fails, and it can also be used to save paper and archive EAS messages. The system runs in the background of any Windows 2000/XP computer. The software generates a warning if planned tests do not occur. One computer can be used to capture and e-mail messages from multiple receivers. Users can automatically publish EAS messages to a website with the Web Ready add-on.

800-833-4459
www.wireready.com
sales@wireready.com

Flash memory audio player **Kowa**


PX10: This player is easy to start: Insert a USB drive and play. Users can store audio by dragging and dropping on the PC screen. The graphical vacuum fluorescent display is bright and clear, showing the counter, level meter and content status. Its triangular-shaped aluminum enclosure makes it strong and lightweight. No moving parts, such as cooling fans and hard disks are used. Users can switch among six pages to access up to 300 audio files. Direct mode allows the user to choose any of the clips assigned to any of the 50 hot keys. A preset mode allows continuous looping.

310-327-1913; www.proaudiokowa.com; pxinfo@proaudiokowa.com

White exit light LED bulb **Ledtronics**

EXL-W series: The EXL-W series white exit light LED bulb is bright, safe and maintenance free. The LED bulbs provide an alternative to the conventional 15T6 or 20T6 incandescent exit sign bulbs. The flame-resistant polycarbonate resin construction of this LED bulb allows for visibility in bright light or smoke. The bulbs offer a solid-state design impervious to shock, vibration, frequent switching and environmental extremes.

800-579-4875; www.ledtronics.com



Audio patch panels **Panel Authority**

Panels: Panel Authority audio patch panels include control and connector panels, stainless and aluminum wall plates, electronic chassis systems, wooden panel mounting systems, aluminum and steel back boxes and panel mounting systems, aluminum rack panels, plain, hinged or vented. Flatorflanged, tapped aluminum rack rails and rack adapters for equipment mounting.

815-838-0488
www.panelauthority.com
preston@panelauthority.com

Traffic scheduling for Windows **Broadcast Software International**

Natural Log: Natural Log interfaces traffic logs and billing with a station's radio automation software. Natural Log is compatible with most computer automation systems, and provides multi-event scheduling, dual product-type protection, user-specified spotset fill sequencing and on-screen log diagnostics.


888-BSI-USA1; www.bsiusa.com; info@bsiusa.com



m!ka MICROPHONE AND MONITOR ARMS

Outstanding design - Yellowtec's new product line for positioning microphones and monitors. m!ka integrates simple and elegant appearance with heavy duty performance.

Combining mic and monitor mounts into one modular system, m!ka helps you restore order to your desktop area.



 **YELLOWTEC**

Heinrich-Hertz-Strasse 1-3
40789 Monheim, Germany
Phone +49-2173-967 315
e-mail: info@yellowtec.com

www.yellowtec.com

2007 PRODUCT SOURCE



PICK HIT

IP audio codec
APT

Worldcast Eclipse:

The Worldcast Eclipse is a multi-interface, multi-algorithm audio codec that offers Ethernet, X.21/V.35 and ISDN

ports providing access to a wide range of networks such as IP, leased line, satellite, microwave and dial-

up. Broadcasters can also choose from coding algorithms such as standard and enhanced Apt-x, MPEG 1/2 Layer II/III, MPEG 4 AAC, G.711 and G.722. The codec is designed with a DSP-based architecture. Enhanced 16- and 24-bit Apt-x are standard.

800-955-APTX; www.aptx.com; info@aptx.com

Internet satellite receiver

Digital Juke Box

Intersat Receiver: The Internet Satellite Receiver will allow radio stations and private air talent to create their own satellite music format with all legal IDs, magic calls, liners, stopsets and more to be fired at the local station level without a satellite receiver or an audio switcher. CD-quality audio and control signals are received over the Internet, which is played back by the Intersat Receiver software on any Windows XP computer. In addition, if the station should lose its Internet connection, the Intersat Receiver will play music from the local hard drive on that station until the Internet connection is reestablished. No spots will be missed, as the computer will play all scheduled spots as well as liners and the legal ID when called for.

888-ONAIR-99
www.digitaljukebox.com
sales@digitaljukebox.com



Cellular remote software module

Tieline Technology

3G: A software upgrade for current users, the Commander G3 and I-mix G3 platforms now deliver live broadcast-quality remotes to the studio via emerging 3G wireless broadband technology. Broadcasters with 3G

broadband enabled cell phones can connect from anywhere they can get reliable wireless 3G coverage and deliver FM-quality mono and stereo audio for remote broadcasts. A 3G broadband connection enables data transfer at download speeds of up to 384kb/s and upload speeds of up to 128kb/s.

888-211-6989; www.tieline.com; sales@tieline.com

Micro monitors

Edirol



MA-10A, MA-10ABK: The MA-10A, MA-10ABK have 10w + 10w stereo amplifiers, two-way bass-reflex enclosures, RCA input connections, are magnetically-shielded, have a frequency range of 45Hz to 35kHz and a nominal input level of 10dBu.

360-594-4273; www.edirol.com
sales@edirol.com

Overhauling a system

Creative Studio Solutions

Documentation Overhauls:

Creative Studio Solutions will send a team of its engineers to a broadcasting facility, where they will trace, re-label and document every wire, connection and piece of equipment. This information will then be entered into studio documentation software, of which the client will receive both a hard copy and CD version. In addition, CSS will make any recommendations regarding the system infrastructure based on their analysis. CSS uses Stardraw Studio documentation software, and a copy of the software is provided to each client at the end of the project.

303-425-5004

www.creativestudiosolutions.com
info@creativestudiosolutions.com

Networked audio system

Wheatstone

Evolution 6:

The E-6 Surface, the E-series Studio Satellite and the E-series Network Switch combine to achieve a cost effective networked audio system. Each studio operates independently yet can share all the sources and mixes through the E-series Network. Switch without traffic limitations, audio latency or machine control delays. The E-6 Surface features event recall, bus-minus and mix-minus and four aux mixes – all with dedicated talkback systems. The E-6 also has four monitor outputs and standard EQ, dynamics, panning and mic processing on all channels (simultaneously). It supports multiple arrays of programmable input channel and master panel switches for customized functions like phone, intercom, salvos or machine commands.

252-638-7000; www.wheatstone.com; sales@wheatstone.com



Microphones

Audio-Technica



UniPoint Series: The re-engineered UniPoint Series includes the Pivot Point connector that allows the cable to exit from either the rear or the bottom of the microphone. This feature is available on most UniPoint boundary mics. In addition, the U891R, U891RW and U891RC boundary mics feature programmable switching plus an LED status indicator. All the mics in the range of hanging, gooseneck, boundary and handheld microphones include Uni-guard RFI shielding, interchangeable elements (cardioid, hypercardioid, omnidirectional and cardioid condenser), 80Hz Unisteep filter to reduce unwanted low frequencies, and a two-stage foam windscreens. There are more than 30 new models in the UniPoint line.

330-686-2600
www.audio-technica.com
sales@atus.com

Twisted pair products

RDL (Radio Design Labs)



Format-A: Format-A twisted pair products send, receive and distribute audio via CAT5 cable.

PICK HIT

Modules are available for

mounting in walls, cabinets and racks. Sending and receiving modules are equipped with connectors and terminal blocks for standard -10dBV unbalanced and +4dBu balanced line levels, and standard microphone levels. Format-A uses one pair for power and three pairs for signals. Sending and receiving modules each use one pair, two pairs or all three pairs for audio signals. Single-pair products allow the installer to select which of the three pairs is used to send or receive the signal. Two-pair products are used for stereo audio. Three-pair products send and receive three separate signals, which may comprise three mono signals or microphone plus stereo line signals.

800-281-2683; www.rdlnet.com
sales@rdlnet.com

USB interface

Henry Engineering



USB Adaptor: The USB Adaptor allows Studiodrive to connect to any PC or laptop computer using USB interface. The USB-Studiodrive produces professional quality digital recording and playback on any PC, and eliminates the need for a soundcard. The adaptor is a plug-in circuit board that mates to the Studiodrive mixer unit. It can be installed in about 30 seconds, and can be retrofitted to any Studiodrive system.

626-355-3656; www.henryeng.com
info@henryeng.com

What will you plug into?

"The PR40 is THE BEST mike I have ever used."

-Art Bell, Coast to Coast

"I suddenly realized that my old studio mics had just become overpriced hammers. These Heil mics blew my mind, but left my budget in great shape."

-Dave Hines, KXUS, Clear Channel

"Nobody ever said anything nice about my voice until I started using th s (PR 40)."

-Leo Laporte, KFI, The Tech Guy

I just put in some of the Heil PR 40's replacing Neumann's and I have to tell you man, that's the best sounding microphone I have ever heard for broadcast. Sure made a believer out of me.

Jay Rose KVEG, Las Vegas


"The Heil PR 30 presents the smoothest and most articulate speech audio from any dynamic microphone I have ever used. Congratulations to the Heil team for bringing large diaphragm dynamics to the marketplace."

-Mike Dorrough, company founder and President,
Dorrough Electronics



www.heilsound.com

2007 PRODUCT SOURCE



HD Radio STL

Nautel

Reliable HD Transport: This system features Clock Packet Tunneling that arranges clock packets to be sent during times when no data packets are using the STL bandwidth, facilitating a more accurate measurement of the STL throughput delay. Data rebalancing ensures continuous operation without

dropout by creating a constant bit-rate stream, reducing instantaneous STL bandwidth requirements. Its automatic E2X start-up sends the initial control packet only once.

207-947-8200; www.nautel.com; info@nautel.com

Grounding wire

Nott Ltd.

Copperweld: Nott now distributes Copperweld grounding wire. This wire has been used by the electric utility industry for many years and just now comes to broadcasting. Standard Copperweld wire is not annealed, making it very springy to deal with. However, their ground wire is annealed and handles just like pure copper wire. It can also be silver soldered like pure copper. Tests indicate erosion may occur at the ends of buried wires, but will go no more than two wire diameters into the metal. In the case of #10 wire, this is less than $\frac{1}{4}$ ". RF current travels only on the outer surface of a wire due to skin effect, so most of the current will be flowing in the copper skin. Bending it into a sharp radius does not cause the copper skin to crack. Wrap it as tight as you like, then silver-solder it.

800-443-0966
www.nottltd.com
ron@nottltd.com



BROADCAST

FM TRANSMITTERS



EM 2000 is a 5000W FM transmitter made up of the EM 25 DIG exciter (or EM 20/30 exciter) and the AM 2000 FM amplifier. AM 2000 includes eight 300W high-efficiency MOSFET technology amplifying modules, fed by 2 independent switching power supplies, which are made to withstand the working conditions. The amplifying modules work independently thanks to a power combining structure that provides high isolation between them.

www.omb.com

OMB AMERICA


factory and laboratories
 phone. (305) 477-0973
 (305) 477-0974
 fax. (305) 477-0611
 3100 NW 72nd. Ave. Unit 112
 MIAMI, Florida 33122 USA

OMB EUROPA

departamento comercial
 teléfono. 902-187878
 fax. 902-187878
 Avda. San Antonio, 41
 CUARTE DE HUERVA
 50410 Zaragoza, ESPAÑA

From September in:

fábrica y laboratorio
 teléfono. 902-187878
 fax. 902-187878
 Pol. Ind. Centrovia C/Paraguay, 6
 LA MUELA
 50196 Zaragoza, ESPAÑA



MT/PLATINUM >1GHz

is a high-performance Studio-to-Transmitter Link. It is made up of the SW MT transmitter externally synthesized in 10MHz sub-bands with a step of 100kHz, and the MR double conversion receiver, that is externally synthesized, too. The MT is microprocessor controlled, and includes LCD display for the visualization of the most relevant transmission parameters (frequency 6-digit), forward and reflected power, modulation level, balanced Mono, Stereo (MPX). The MR receiver has the same visualization system as the transmitter. It includes balanced Mono and Stereo (MPX) outputs. Furthermore, the MT/PLATINUM STL includes a jumper in order to get a proper operation with digital signals.

EM 10000

is a 10000W FM transmitter made up of the EM 250 COMPACT DIG exciter and three control units which combine the power of six AM 2000 FM amplifiers. AM 2000 includes eight 300W high-efficiency MOSFET technology amplifying modules, fed by 2 independent switching power supplies, which are made to withstand the working conditions. The amplifying modules work independently thanks to a power combining structure that provides high isolation between them.



Codec Broadcast Tools

USB Match Tool: The USB Match Tool is a professional USB-to-bi-directional stereo audio codec. It provides professional audio connectivity between the user's professional stereo analog equipment and the PC's USB port. The USB Match Tool is equipped with the Burr Brown Delta Sigma 8x over sampled USB codec that will operate with virtually any audio editing, recording or broadcast automation software at sample rates up to 48kHz and up to 16-bit resolution. The front panel is supplied with input and output trimmers along with a stereo LED input level meter. Plug-in Euroblock screw terminals are provided for the electronically balanced stereo input and outputs. The tool is USB powered by a surge protected internal bi-polar 15Vdc switch-mode power supply affording superior headroom and high-definition audio.

877-250-5575
www.broadcasttools.com
bt@broadcasttools.com

Microphone SE Electronics

SE4: The SE4 mic is a re-modeled SE3, but the chassis has been re-engineered to accept two additional interchangeable capsules: a hypercardioid and an omni. Single and matched pairs of mic and capsule sets are available and shipped in a black aluminum, steel-reinforced flight case. All mics ship with a full-suspension shock mount.



617-623-5581
www.seelectronics.com
usa@sonicdistribution.com

The best
use the best.TM

9000
stations
100
countries


Welcome to the World's largest
broadcast software company



Visit us at www.rcsworks.com or www.prophetsys.com
Email us at best@rcsworks.com

2007 PRODUCT SOURCE

Wireless audio interface
JK Audio



cell phone. It will also connect to other products, such as a laptop, that allows a similar headset connection. Features of the unit include XLR balanced line input and output, and a 9Vdc battery.

800-552-8346; www.jkaudio.com; info@jkaudio.com



Daptor Three: Using Bluetooth wireless technology, this interface connects to the user's cell phone like any other Bluetooth-enabled headset. The interface allows balanced and unbalanced connections to a

Obscenity delay

Eventide

BD600E: The BD600E offers 16 bipolar opto-isolated inputs that may be configured to drive many BD600E functions or as general-purpose delay inputs; 16 open-collector outputs that may be configured to display BD600E status indicators or to pass through delayed versions of the inputs; and an RS-232 output to provide a delayed version of the input for driving a time display or for other control purposes. The BD600E features improved audio performance and expanded obscenity delay capabilities up to 80 seconds. Other features include the exclusive panic function, which stores a .WAV file on a compact flash card to be played when the button is pressed. While the file, which may be a jingle or station ID or

any other message, is played, the delay buffer is rebuilding, allowing programming to play as soon as the jingle has completed.

201-641-1200

www.eventide.com
audio@eventide.com

Arrakis Systems inc.

www.arrakis-systems.com

970-461-0730



Nova-10C
digital console
\$2,795 msrp

Digital Consoles



X-Mixer
digital console
\$5,495 msrp (12 ch)
\$5,995 msrp (14 ch)



On-air Automation
only \$100 per month

...come to our website and see why more stations buy Arrakis Systems !!! New York, L.A., Chicago, Moscow, Paris, Beijing, Nigeria, Baghdad, Jamaica, Tahiti & around the world. With thousands of consoles, studio furniture packages, and on air automation systems sold worldwide since the late 1970s, Arrakis Systems is a world leader in Radio broadcast engineering and manufacturing. Quality, reliability, and value are the hallmark of every Arrakis product



1200 series
analog console
\$2,495 msrp (5 ch)
\$3,795 msrp (10 ch)
\$4,795 msrp (15 ch)

Analog Consoles



12,000 series
analog console
\$4,995 msrp (12 ch)
\$6,195 msrp (18 ch)



6604 Powell St., Loveland, Colorado 80538

Guest control panels

Logitek

GST-22 and GST-23: These guest control panels accompany Logitek's digital audio router and consoles. The GST-22 panel can be dropped into a table cut-out, contains an amplifier and gain control for one pair of headphones and mic on/off and cough buttons. Medium- or high-impedance headphones can be connected to the front or rear of the unit. Audio input may be selected from a list displayed on the panel's LCD screen. The GST-23 keypad, a tabletop box with six buttons, may be programmed for any desired application including playback machine start and intercom functions. The GST-23 connects to the rear of the GST-22 panel. Both products are powered by a small external supply.

800-231-5870

www.logitekaudio.com
info@logitekaudio.com

Offset pyramidal diffuser

Acoustics First



Quadra Pyramid: The Quadra Pyramid presents a low profile with four pyramids creating sixteen angles of reflection on the surface of a single 2'x2' panel. Mounting is designed for wall or ceiling grid. Fire rating is Class 1 (A).

888-765-2900

www.acousticsfirst.com
info@acousticsfirst.com

Wireless Broadband Internet Remotes



"The first time out with the Tieline was a brilliantly simple experience for everyone involved. For lack of a better phrase, the codec just worked."

- Christian Vang
Chief Engineer
Clear Channel St. Louis



"The codecs sounded great. My management was very, very impressed with the demos"

- Grady Jeffreys,
Technical Manager,
Mackay Communications



"The remote was a spectacular success, in no small part thanks to the flawless sound which the Tieline G3 provided over the public Internet"

- Mike Rabey
Chief Engineer
Entercom Indianapolis



100%
*COMREX
POTS
Compatible

Get Free demo codecs delivered to your door Now!!

Tieline®
www.tieline.com

800-950-0750

2007 PRODUCT SOURCE

2007 PRODUCT SOURCE

Remote receiver
Burk Technology



800-255-8090; www.burk.com; sales@burk.com



Watchband:

Delivering station and market monitoring tools to managers, engineers and programming departments, this receiver provides stereo, phase and field intensity data, streaming audio and decoded RBDS to any PC with an Internet connection. Broadcasters can record audio streams for remote playback, as well as log audio metrics for review and analysis. Automatic logging routines allow station-to-station comparisons for the entire market. Logged RBDS data reveals content on market stations.



PC case pullout


Mager Systems

Computer Pull out: This mounting system places the PC in a carriage that completely pulls out of the cabinet or from under a counter top. Once extended, the computer can be rotated 90 degrees in either direction to provide total access to the computer wiring. When installed in a cabinet it is insulated with sound acoustic

treatment, baffling and ventilation. The weight limit on the assembly is 300 lbs. The upper and lower pieces are independent of each

other so there is no rack height limit. The pullout extension is 22" inches. There is no required clearance for the back, however the depth of the equipment and wiring must be factored into the depth of the cabinet.

623-780-0045; www.magersystems.com; mager@magersystems.com



Cat-5 snake cable

Gepco International

CTS4504HDX: This four-channel, heavy-duty Cat-5 snake cable provides four elements of Gepco CT504HDX heavy duty, four-pair Cat-5 UTP cables under an overall jacket. Each element features 24-gauge, solid copper conductors and an inner belt that preserves the critical pair spacing and geometry. For added strength and diameter, each four-pair UTP element has a second TPE jacket that is color-coded for easy identification. The outer jacket is constructed from a rugged TPE compound for durability and flexibility in hostile environments.

800-966-0069; www.gepco.com; gepco@gepco.com

OMNIRAX

BROADCAST FURNITURE

What people are saying about Omnidax...

"Within a short amount of time Omnidax was able to come up with a beautiful concept for our new studios."


"The Omnidax design makes these studios incredible for talent and operators on both sides of the console."

"Our furniture from you not only fit into our budget and timeline, it was very well constructed and looked beautiful. I expect to be outfitting many more facilities with Omnidax..."

"I was impressed with the exceptional care given packaging for shipment. A few very large and potentially fragile components made it cross-country completely unscathed"

"I wholeheartedly recommend Omnidax to everyone."

P. O. Box 1792 Sausalito, CA 94966
800.332.3393 415.332.3392
FAX 415.332.2607
www.omnidax.com info@omnidax.com



The Engineer's Choice!

Multi-stream networked audio processor

Omnia Audio



Omnia 8X: With algorithms modeled after the Omnia.3net, this processor provides eight discrete three-band stereo audio processors in a single, networked box. Its architecture works ahead of any bit-reduced audio coder to reduce artifacts and improve the sound audio destined for HD Radio, Internet and satellite broadcasting. Use it to process headphone feeds where off-air monitoring is not possible; as multi-band level control for remote codecs or on-air telephone systems; to process and send multiple audio streams from a single studio complex to multiple transmitter sites; or on-demand for in-studio musical performances or commercial production applications. The processor uses the Livewire standard over Ethernet.

216-241-3343; www.omniaaudio.com; info@omniaaudio.com

Recording tools for journalists

Technica del Arte

Luci: This software can be loaded on a Pocket PC or Smartphone to provide mpeg recording capability. The screen features large buttons for transport controls, and more than eight hours of recording time is possible with a 256MB memory-card. Product support includes usage if the PDA is lost or damaged by providing a temporary keycode to authorize the software on another device for seven days. The company provides a PHP-script to receive recordings and publish them online immediately.

+31 43 32 19 499; www.technicadelarte.com; sales@technicadelarte.com

Software

Magic Egg Software

Production Order Pro: Organize, track and store production orders, audio files, scripts, and traffic instructions with the industry's first integrated solution for production orders: Production Order Pro by Magic Egg Software.

281-493-4441; www.popro.com
sales@popro.com

Electronics components suppliers

Mouser Electronics



Electronics Components Catalog

Mouser delivers a time-to-market advantage with daily updates and new product additions to its online catalog of 850,000+ products. In addition, Mouser publishes a new 1,900+ page print catalog every 90 days with the newest products added and end-of-life products deleted.

800-992-9943

www.mouser.com
sales@mouser.com

Recorder

Roland

CD-2: The CD-2 records directly to CD or Compact Flash media (2GB capacity) for hours of recording time. Once recorded, audio can be edited, processed and burned to CD. The CD-2 includes a stereo mic or users can plug external mics in via the CD-2's two XLR inputs, complete with phantom power. RCA phono and 1/4" I/O is also provided. A variety of audio effects are available.


800-542-2307

www.rolandus.com



RemoteMix 4

Introducing A Field Mixer That's Outstanding In Its...um...Field



Combining a four-channel field mixer with a four-channel headphone amplifier, a phone-line hybrid, a universal PBX handset interface, a wireless phone interface and Bluetooth® Wireless Technology to connect to cell phones and portables, the RemoteMix 4 is ready to work just about anywhere you are.

Use it as a phone-line hybrid, calling into your studio talk show hybrid. Use it as a front end mixer for your POTS, ISDN or IP codec. Or use it as a combination broadcast/IFB mixer. No matter how you use it, you'll find that it's an incredibly versatile mixer.

Plus... IT SOUNDS GREAT! A soft limiter prevents overdriving the phone line interfaces, while the mixer XLR output is pre-limiter (full range), meaning you have a feed for every need. Bass boost adds a bit of low end before sending the signal down the phone line to provide that "how'd you get it to sound THAT good over POTS lines" nudge. There are convenient 3.5 mm send and receive jacks for recording the show or mixing in your MP3 player.

The RemoteMix 4 can be powered by batteries or the included AC adapter, so you'll never lose a connection – even during a loss in power!

We think we've done our homework with RemoteMix 4. And it'll be in your hands in plenty of time for the fall sports season.

JK Audio
TOOLS FOR SUCCESSFUL RADIO

2007 PRODUCT SOURCE

Guy anchor rod ERI-Electronics Research

Ultra Guy Anchor Rod: This guy anchor features a port to allow non-destructive ultra-sonic testing of



guy anchor integrity, without soil excavation. It's noninvasive because there is no digging and nondestructive because there is no surface damage. No temporary anchors are required. The equipment provides more detail than visual inspection, including detection of stress cracks and internal flaws. The rod is Polyethylene sealed and anticorrosive.

812-925-6000; www.ERlinc.com
sales@ERlinc.com



Codec

Telos Systems

Zephyr/IP: Zephyr/IP uses Agile Connection Technology (ACT) to continuously adapt to network conditions, minimizing the effects of packet loss, varying bandwidth and jitter. ACT's error detection and concealment routines, dynamic buffering and other techniques work together to provide stable IP audio connections. This codec features I/O including AES/EBU, analog and a Livewire Ethernet interface for direct integration with Axia IP-Audio networks as well as LAN, WAN and Wi-Fi networks. Other features include studio-grade 24-bit A/D-D/A converters transmission bit rates from 16kb/s to 256kb/s and a Telos-hosted Z/IP Server service for look-up of and connection to other Zephyr/IP users worldwide.

216-241-7225; www.telos-systems.com; telos-info@telos-systems.com



Interdigital bandpass filters Shively Labs



2604, 2612: These interdigital bandpass filters provide filtering in a footprint less than half the size of conventional bandpass filters. The 2604 is designed for use with transmitters up to 2.5kW and the 2612 for transmitters up to 10kW. Both are manufactured for use in HD Radio applications.

888-SHIVELY
www.shively.com
sales@shively.com

Broadcast media database


BIA Financial Network

Media Access Pro v4.2: The improvements in Media Access ProTM include information on HD Radio, greater functionality and flexibility in the mapping program, expanded technical information on CP data, the addition of low power FMs, more detailed information on radio station audience levels, and user requested custom reports and searches to create customized reports at the click of a button. Version 4.2 also includes predefined searches for CPs and move-ins so the user can quickly know the number of CPs in a market, identify overlapping signals from competing stations and determine when a CP will be a new move-in to a local market.

703-818-2425
www.bia.com
info@bia.com

Broadcast Software

Radio Automation




Simian - radio automation and digital play out system

Instant Audio




Stinger - instant access to 288 'rapid fire' audio files

Digital Cart Player




WaveCart - the original on-screen cart machine

Audio Logging




SkimmerPlus - professional audio logging and skimming

Full PC Systems




Complete PC systems - with hardware and music

Music Library



MusicStore - over 55,000 ready to play (tagged) songs

CD Ripping



Speedy - professional CD to PC ripping and file tagging

Sound Cards



AudioScience - built for broadcast, pro sound cards

Remote Control



Trigger & Relay Devices - for GPI/O & remote control

Broadcast Software International

503 E. 11th Avenue


Eugene, OR 97401 USA

Direct: 541-338-8588

Fax: 541-338-8656

www.bsiusa.com sales@bsiusa.com





**"I demand the best...
the Aphex 230 is
clearly the best."**

- Rick Dees

"My voice is my on air signature. I want it to 'jump' but also be clean, full and natural. Most final on-air processors are cranked to 'stun' and not very kind to voices. With the Aphex voice processor, both my voice and the voice of my sidekick Patti 'Longlegs' Lopez are incredibly open and present, even after going through the station's loudness box."

The Aphex Model 230 Master Voice Channel is a combination of proprietary technologies and the highest quality components. Its performance cannot be duplicated by any other product or combination of products, hardware or software, at any price.

If you demand the best for voice processing, demand the Aphex Model 230.

APHEX
www.aphex.com

© 2007 Aphex Systems. All Rights Reserved.
Designed and manufactured in the USA



2007 PRODUCT SOURCE

FOOTLUNCHI 2007CF

Play-out and production software

Airshift

Airshift Studio: Designed for radio stations with one to five studios, the software is used for all production-related tasks. Workflow starts with the planning process. The station defines its program schedule for each weekday. The template divides each hour of programming to a segment with various attributes: start and end time, name, type and selected music clock. For daily planning, playlists are created for each program containing all the elements needed: music tracks, sounds and commercials. A third-party system, such as music scheduler or traffic system takes care of the scheduling of commercials. A producer finishes production of one item, then places it in the playlist. The publishing phase is where created content is published to the audience. After the program is published, the content used in it is archived or purged.

+35 8 50 365 0577; www.airshift.tv; sales@airshift.tv



Headset with condenser mic

Beyerdynamic



MMX-1: Featuring a closed headphones and cardioid microphone, the unit provides noise cancellation and high-quality speech reproduction, as well as switchable gain of 20dB, which can be activated or deactivated via the PC. No special drivers are required and the MMX-1 can be operated with any standard sound card. The headset has a USB plug and can be connected to each PC via the USB port.

800-293-4463

www.beyerdynamic-usa.com
info@beyerdynamic-usa.com

Turnkey facility

Industrial Acoustics

Modular Studio Systems: The facility includes floating isolation enclosures, electric and HVAC interfaces, integrated lighting systems, integrated tech wiring raceways, interior acoustical treatments and soffits, and interior furnishings. It is all modular, movable and installs in days.

718-931-8000

www.industrialacoustics.com
info@industrialacoustics.com

Masterclock time code generator

ESE



(day of year, hour, minute and second) of time as received via a user-selected NTP server. Several types of time code, as well as a 1PPS signal are generated by the ES-188 and output on the rear panel. These outputs allow the unit to interface with new or existing computers, automation systems and third-party clock systems. The clock features automatic correction for daylight-saving time and a four-hour battery backup. Options include ASCII NTP time-code output, relay contact closure, 220Vac, 12 to 35Vdc power input and UL-approved power supply.

310-322-2136; www.eseweb.com; ESE@eseweb.com

Retrofit adapter

Dialight

D264: The D264 Series retrofit adapter allows for simple retrofit of a new LED beacon to an existing incandescent base, eliminating the need to fully dismantle the old fixture. Remove the top half of the existing incandescent light and the retrofit adapter securely mounts to the existing hinge. Uses a socket-based electrical interface. Other features include rugged cast design, interfaces with most existing fixtures and reduces retrofit time for an LED beacon to a small fraction of what would be required for a complete fixture removal.

800-835-2870; www.dialight.com; info@dialight.com



HD Radio receiver, translator

Fanfare


FP-TRO: With the advent of HD Radio comes the need to provide HD Radio translators and repeaters. Because of the licensing involved with HD Radio, complete demodulation and remodulation of a digital signal can be cost prohibitive. The FP-TRO maintains the signal in the RF domain and converts it to the new frequency, which eliminates the cost of licensing the HD Radio technology used in the translator. The signal is then retransmitted using a Crown Broadcast amplifier.

716-683-5451; www.fanfare.com

custserv@fanfare.com

Status reminder

DM Engineering



Don't Forget: Don't Forget monitors tasks such as switching the local-remote switch or shutting the door on the aux transmitter, and remind the user if the selected action is forgotten before he leaves the site. Don't Forget features six jumper selectable inputs for either N.O. or N.C. conditions, three Opto-Probe LED and visible light sensor inputs, LEDs for each monitored input. One Opto-Probe may be used to monitor a selected LED or light source for applications such as local-remote switches, over modulation LEDs or any other light source desired. Magnetic contact switches are also included for doors or panels that must be closed. Don't Forget can also be used as a fault-alerting system and is easily interfaced with a remote control.

800-249-0487

www.dmengineering.com
info@dmengineering.com

Sound card

Digigram



New From QEI

QEI introduces its new line of low and high power FM Transmitters.

EASY TO OPERATE

EASY TO MAINTAIN

*EASY ON YOUR BUDGET *

Contact us toll free at 800-334-9154 for more information and
special introductory pricing.



D/A Series (500 Watt Model)



Model FMQ30KWC

QEI Corporation
800-334-9154 (toll free sales)
+856-728-2020 (International)
www.qei-broadcast.com (web)
qesisales@qei-broadcast.com (e-mail)

LX6464ES: The LX6464ES combines Digigram's sound card expertise with Ethersound technology. With up to 64 bi-directional PCM linear channels, the LX6464ES is a versatile PCI board that provides an effective way to bridge a wide range of computer audio applications to all channels of a 100Mb/s Ethersound network.

703-875-9100; www.digigram.com
input@digigram.com

OUT AND ABOUT

Useful items to simplify remotes

LXT Lithium-Ion cordless FM/AM radio

Makita



BMR100: LXT Lithium-Ion battery and optimum charging system produces 280 percent total lifetime work with 2x more cycles. It weighs 9.2 lbs, delivers stereo sound from two 3.25" side-firing drivers, is weather-resistant and has a digital backlit display.

800-462-5482; www.makita.com

Vehicle personalization

Roadmaster USA



and Scrolling Rear Deck Message System (Model RRDS100) can personalize a vehicle with messages or ads that scroll on the license plate or in the back window. The scrolling systems come with 99 pre-set words and phrases, including "help me," "slow down," "turning left," "your lights aren't working," "baby on board," and also lets the user program five interchangeable messages up to 120 characters each. Messages can be combined or repeated and the speed and brightness of the LED can be adjusted with the included wireless remote.

800-445-1797

www.roadmasterusa.com

Portable broadcast mixer

JK Audio



Remote Mix 4: A four-channel field mixer and headphone amplifier, this unit is a communications interface that features a phone line hybrid and keypad, a PBX handset interface and a 2.5mm cell phone interface. The portable unit is smaller than a lunch box. Use it as a phone line hybrid, calling into the studio talk show hybrid. Use it as a front end mixer for a POTS, ISDN or IP codec. Features include four XLR mic jacks with phantom power, male XLR clean mixer output and four 1/4" headphone jacks with individual source selectors and level controls. The mixer is powered by dual 9V batteries and/or 100-240Vac external ac power supply.

800-552-8346; www.jkaudio.com
info@jkaudio.com

Hand-held, motorized cable coiler

Kaltman Creations



Cable Coiler: The Cable Coiler offers a fast way to preserve expensive microphone cables. But it's not just for mic cables. It can also be used for lighter weight speaker cable, coax, Cat-5, telephone, fiber optic or rope. Use the high torque motor to coil the cable. Once coiled, just slip the cable off the patent pending spool for instant storage.

678-714-2000

www.kaltmancreationsllc.com
sales@kaltmancreationsllc.com

Portable PA

Yamaha

Stagepas 500: Yamaha's Stagepas 500 portable PA system is a 500W multi-use system that features two 10" speakers and a 10-channel stereo-powered mixer. Each speaker contains a 10" woofer and 1" compression driver, driven by a 250W Class D amplifier. The mixer features balanced XLR connectors, mic/line switches and balanced 1/4" jacks, two-band channel EQ and switchable 24-bit digital reverb. The first two channels feature a compressor/limiter switch that controls dynamics on those inputs.

714-522-9000; www.yamaha.com/proaudio
infostation@yamaha.com



9V speakers

Remote Audio



Speak Easy v2: The Speak Easy v2 operates on a single 9V battery for a full day of typical intermittent use. It will also operate from external 9Vdc-15Vdc on its 2.1mm coaxial power connector. The internal battery is switched out of circuit when plugging in external power, so there is no need to remove the battery when using external power. Both the battery and external circuits are protected against reverse polarity.

615-256-3513; www.remoteaudio.com
info@remoteaudio.com

Portable Stereo IP Codec

Comrex



Access Portable Stereo Bric IP Codec: Access Portable is a compact, handheld unit capable of sending mono, stereo or dual mono audio over POTS, DSL, cable, Wi-Fi, 3G Cellular (EVDO/UMTS), satellite and more. Access is also a fully featured POTS codec able to send and receive 15kHz stereo audio on a single POTS line when connecting to another Access. The codec comes with a seven-hour lithium-ion battery with built-in charger and an integrated Card Bus slot for wireless IP cards and modems.

800-237-1776; www.comrex.com
info@comrex.com

Scrolling Message Systems

The Roadmaster Scrolling Digital License Plate Frame (Model RLPF100)

and Scrolling Rear Deck Message System (Model RRDS100) can personalize a vehicle with messages or ads that scroll on the license plate or in the back window. The scrolling systems come with 99 pre-set words and phrases, including "help me," "slow down," "turning left," "your lights aren't working," "baby on board," and also lets the user program five interchangeable messages up to 120 characters each. Messages can be combined or repeated and the speed and brightness of the LED can be adjusted with the included wireless remote.

800-445-1797

www.roadmasterusa.com

Portable broadcast mixer

JK Audio



Remote Mix 4: A four-channel field mixer and headphone amplifier, this unit is a communications interface that features a phone line hybrid and keypad, a PBX handset interface and a 2.5mm cell phone interface. The portable unit is smaller than a lunch box. Use it as a phone line hybrid, calling into the studio talk show hybrid. Use it as a front end mixer for a POTS, ISDN or IP codec. Features include four XLR mic jacks with phantom power, male XLR clean mixer output and four 1/4" headphone jacks with individual source selectors and level controls. The mixer is powered by dual 9V batteries and/or 100-240Vac external ac power supply.

800-552-8346; www.jkaudio.com
info@jkaudio.com

Veetronix

Touch The Switch Known Around The World

Custom Laser Marking

Retention Leads

RGB Illumination

www.veetronix.com

2007 PRODUCT SOURCE

Telephone hybrid and screener system
Thum + Mahr GmbH/Yellowtec



screener for use in talk shows. The audio connections to the mixing console or audio workstation are equipped with balanced studio level and AES/EBU interfaces. The integrated digital signal processing includes echo cancellation, AGC and expander. Plugging in a telephone handset (or headset) allows off-air screening. In ISDN mode, two callers can be managed simultaneously and switched to air independently. Features include GPI/O with programmable relays and TTL inputs and outputs, a DTMF option to initiate calls, sending DTMF tones over existing connections or decoding incoming DTMF tones as well as an RS-232 interface for external control by a PC running Talkmaster software, or for connection of the B-line Keypad.

+49 2173 967 336
www.yellowtec.com; info@thummahr.de

Yellowtec B-line: B-line combines a POTS and ISDN telephone hybrid with an effective call

Warning enunciator

Alert System

Alert System: PICK HIT 2007

This alert enunciator displays a picture image on a computer monitor. The monitor can be mounted on a wall or a desk. Alert System has 20 screens of picture images. Each of the screens can display a single picture or a picture slide show. A screen is selected by an external closure. A momentary closure switches to the screen the closure occurred. If a continuous closure occurs, the screen that received the closure will remain on until the closure is released. In the event of multiple continuous closures, the screens will rotate in the order of the closures, every five seconds.

817-944-5903



Radio automation application

Mediatron

Radiocube On Air: This system provides support of multiple audio outputs. Multi-format and multi-sampling mixing of these audio formats is possible: MP3,



WMA, WAV, MPEG 2, BWF. Users drag and drop from Windows Explorer to the play list. Separate progress bars provide intro/ramp count up/down. The system offers a built-in prelisten player with loop function. The application supports Direct X plug-ins and provides adjustable pitch for audio outputs (± 50 percent). A dedicated control panel is available.

+49 89-3715645-0
www.meditron.com
info@meditron.com

Innovative FAA Obstruction Lighting Since 1969

LED products

Monitoring Services

High Intensity Systems

- Reduce antenna shut down during sweeps with up to 700ft separation between PC and FH
- FAA/FCC compliance through 24/7/365 monitoring by National Operations Center
- Simplify installation with Flash LED retrofit adapter
- Up to 90% savings on power consumption with conversion to LED technology

FLASH TECHNOLOGY www.flashtechology.com

For more information: info@flashtechology.biz - 1-888-31FLASH

Step up to a Crown

CROWN BROADCAST

- FM Transmitters from 30 watts to 10kW with optional built in audio processor
- FM Translators with built in receivers
- Frequency agile from the front panel
- 3-Year warranty
- Compact—small footprint
- Low power (up to 600 watts) able to now monitor VSWR and control power via remote control.



Current Crown Users—You can take advantage of Crown Broadcast's exclusive unit upgrade program. With this program you will be able to send in your current functioning Crown product and have the unit renewed to like-new condition complete with 2-year warranty. You can also have the units powered up from 30w to 300w and from 100w to 300w. Upgrades are also available for the receiver board and audio processor. This program allows for a long-term investment in your current product without the investment in a new product.

Crown Broadcast IREC, 25166 Leer Drive, Elkhart, IN, 46514 www.crownbroadcast.com ph 866-262-8972

Break-out panels

RAM Broadcast Systems

BP1X24RJ45, BP2X24RJ45: The BP1X24RJ45 features 1RU, 24 bulkhead feed through CAT-5 RJ-45 modules, one large designation strip and front and rear tie bars. The BP2X24RJ45 features 2RU, two rows of 24 bulkhead feed through CAT-5 RJ-45 modules, two large designation strips, and front and rear tie bars.

800-779-7575
www.ramsyscom.com
sales@ramsyscom.com

Washable keyboard
Unotron



Spillseal S5000K: Spillseal keyboard technology provides protection from liquids and dust rated to standard NEMA4X and IP66. It is washable and easy to disinfect, reducing the spread of germs. It is compatible with Windows 95/98/ME/2000/XP with no extra software or set-up.

800-381-5817; www.unotron.com

Digital/analog silence sensor
Danagger Audio Works



the Plan B dead-air prevention device. The Plan B Classic has special features for network repeater applications. It accepts an external closure to inject local audio from the system's internal DVD drive or Compact Flash card and automatically rejoins the network after a break. Like all Plan B models, the Classic will also detect digital or analog program feed failures and provide continuous replacement audio while notifying station personnel via voice remote control. Users can also call the Plan B Classic to monitor program and backup audio, manipulate relays, monitor status inputs, or make emergency phone-to-air announcements. Danagger has included a monitor amplifier with stereo speakers and a headphone jack in the Plan B Classic's sleek 2RU aluminum rack-mount chassis.


800-888-89AUDIO
www.danagger.com
info@danagger.com

Software
Wirecad

Wirecad XL: WireCAD XL is designed for the small facility. It provides a single database with up to 2,000 cables. There is no limit to the number project systems. The tools are there to create functional and physical blocks. Assign system IDs and number cables.

661-253-4370
www.wirecad.com
sales@wirecad.com

Speakers
SLS Loudspeakers



HT400: The HT400 system is composed of four HT6.5S two-way, full-range bookshelf speakers, one HT6.5C dedicated, full-range center channel speaker and one HT6.5W 150W powered subwoofer. The HT6.5S provides a frequency response of 42Hz to 25kHz while the HT6.5C provides 48Hz to 25kHz. Both deliver a frequency response through a 6.5-inch paper composite cone, shielded woofer and the signature Neo3 PDR Ribbon push-pull tweeter with a 2.2kHz crossover point. The HT6.5S weighs 24lbs and is rated for 100W RMS and 200W maximum. The HT6.5C weighs 33 lbs and is rated for 150W RMS and 300W maximum. Both units can be mounted on a stand, shelf or by using a Multimount MM-010 system.

417-883-4549
www.slsloudspeakers.com
sales@slsloudspeakers.com

Plan B Classic:

Danagger Audio Works has announced a new midrange model of the Plan B dead-air prevention device. The Plan B Classic has special features for network repeater applications. It accepts an external closure to inject local audio from the system's internal DVD drive or Compact Flash card and automatically rejoins the network after a break. Like all Plan B models, the Classic will also detect digital or analog program feed failures and provide continuous replacement audio while notifying station personnel via voice remote control. Users can also call the Plan B Classic to monitor program and backup audio, manipulate relays, monitor status inputs, or make emergency phone-to-air announcements. Danagger has included a monitor amplifier with stereo speakers and a headphone jack in the Plan B Classic's sleek 2RU aluminum rack-mount chassis.


Audio processor

Audemat-Aztec

Digiplexer 2/4: This processor is also a full RBDS, digital and stereo encoder. It allows I/O remote control and backup audio.

The processor uses high-speed DSP to create a stereo signal and radio data messages. With the Ethernet connection and the PC software, configuration is possible from anywhere in the world. The processor features real-time clock for RBDS scheduling, two-band audio processing, 2 gigaflops of DSP power, clippers that run at 1.5MHz, LCD screen and Ethernet, USB and RS-232 ports, all in 1RU.

305-249-3110; www.audemat-aztec.com
contact@audemat-aztec.com



WORLD LEADER IN TALKSHOW SYSTEMS

ONE-X-SIX
The perfect multi-line talkshow system for use with up to six phone lines.

TWOx12
Make fast-paced production and high quality conferencing a snap with this 12 line on-air phone system.

Introducing Nx12!
Our most flexible standalone talkshow system...ever. This self-contained 12 line system includes 4 hybrids and is offered with Livewire Audio-over-IP and either analog or AES inputs/outputs. Call for availability.

SERIES 2101
The world's only talkshow system especially designed to meet the challenges of integrating large connected broadcast plants.

CONTROL AS YOU LIKE IT

DESKTOP DIRECTOR
Sophisticated, yet easy-to-use, control stations that make fast-paced production a snap.


CALL CONTROLLER
Simplified and cost effective option for call screening and on-air control.

CONSOLE DIRECTOR
Console + turret mounted accessory controllers put control right at the talent's fingertips. Axia Element users get even tighter integration.

ASSISTANT PRODUCER
This talkshow management system completes your Telos multi-line talkshow system with easy-to-use client/server call screener software that provides vital real-time link between producers and talent.

Telos
AUDIO | NETWORKS

© 2007 TLS Corp. Telos, Axia, One-x-Six, TWOx12, Series 2101, Nx12, Call Controller, Desktop Director, Assistant Producer, Console Director, Livewire and Element TM TLS Corp. All rights reserved.



1.818.840.6749

www.sasaudio.com

ANNIVERSARY
1988-2007

Talk is, as they say, cheap. But when a customer like you has something to say, we sit up and pay close attention. To us, that conversation is golden, a precious commodity.

We know every station, facility and operation is different. So we watch how your staff operates, sit in on the morning shows, work with your engineers and architects. Then we design, build and program your facility with technology appropriate to meet your unique needs and expectations.

The conversation goes like this: You talk. We listen.

From digital routers to console control surfaces, intercommunications to systems integration, SAS provides comprehensive and competitive broadcast engineering solutions. Solutions that are smart, dependable and expandable for all broadcasters—large and small.

Your straight-talk (yeah, both the kudos and the gripes) is the very inspiration behind the innovation of our designs, and the quality of our customer service. For 20 years our unsurpassed, "we got yer back" commitment to client support, and our ever-improving and evolving technologies have delivered to this industry the highest standards of integrity, experience and reliability.



The **Rubicon™** family of digital control surfaces—the favorite of hundreds of major and medium market radio programmers.

So whaddya say? Call us. We're all ears.



**SIERRA
AUTOMATED
SYSTEMS**

20 years of listening. 20 years of innovation.

Look who's talking now.

ABC Air America Bonneville Clear Channel CBS Disney ESPN Moody NPR Pamal Radio One Spanish Broadcasting System Westwood One and more than 1000 major market and smaller radio broadcasters across the country and abroad depend on SAS expertise. Shouldn't you?

2007 PRODUCT SOURCE

Mic preamp
Mackie



on-board DSP matrix mixing, an advanced monitoring/headphone control section with four user assignable headphone outputs, two stereo control room outputs, built-in talkback mic input and remote switching capability. The interface's most innovative feature is an assignable patch bay with advanced DSP capabilities. Users can patch any hardware input, or mix any combination of hardware inputs, to any hardware output. Likewise, any software output can be patched to any hardware destination.

800-898-3211; www.mackie.com; productinfo@mackie.com

Onyx 1200F:

The Onyx 1200F is a 30-by-34 channel, 24-bit/192kHz-capable FireWire audio/MIDI interface that features 12 of Mackie's flagship Onyx preamps,

Nearfield monitor
Dynaudio Acoustics

BM5P: The BM 5P is a passive nearfield monitor that operates within a frequency response of 50Hz to 21kHz, and is equipped with a 170mm (6.9") woofer and 26mm (1") soft dome tweeter. BM 5P uses pure aluminum for the voice.

+45 87-427000; www.dynaudioacoustics.com

Four channel line mixer

Behringer

MX400: This four-channel line mixer yields high sonic quality at all output levels, with ultra low noise 4580 operational amplifiers. It has the same op amps found in its much bigger units, and is well suited as a sub-mixer. Connect the unit's output to a single input on the main mixer. The mixer features 1/4" TS connectors and input level controls for each channel.

877-672-0816; www.behringer.com; support@behringer.de



Sabre designs, manufactures and installs towers to meet your broadcast specifications. We offer everything from custom FM support sections to turnkey AM installations. Committed to customer service, we deliver quality products at competitive prices with the shortest lead times.

Call Sabre today for all your tower needs.

Sabre
Towers & Poles

1-800-369-6690

broadcastsales@sabrecom.com

Rack-mount vertical power strips

APW Mayville

Stanton Power Mount: Power Mount systems carry out the basic function of holding power strips in place, while allowing them to be affixed in virtually any location inside the rack. Power Mount systems offer a 180-degree swivel feature to rotate the power strip during maintenance or integration procedures such as cabling and access to power cords. The entire strip can face the front, middle or back of the cabinet. If power demands increase, more power can be easily added. Use of the system improves overall airflow and enhances equipment cooling since cabling can be taken out of the air path.

800-558-7297
www.stantonracks.com

Audio tone generating software

NCH Swift Sound



Tone Generator: The Tone Generator creates audio test tones, sweeps or noise waveforms using a computer or a PDA handheld. Typical applications include test tone generation for level alignment and calibration and quality control checks.

www.nch.com.au; nch@nch.com.au

Software audio processor

Neural Audio

Neustar SW4.0: This upgrade allows broadcasters to monitor and process multiple digital radio channels HD2, HD3 and HD4 or Internet streams in the same box at a much lower cost per channel than standalone processing, without additional hardware. The NeuStar SW4.0 has been designed to run on any Windows XP computer or server including the HD Importer.

425-814-3200
www.neuralaudio.com
info@neuralaudio.com

SCMS

= **YOUR COMPLETE RADIO SOLUTIONS PROVIDER**

Service and Pricing you can Count On!

1992
1st Fixed IBOC Reception

March 2007
FCC approves HD System

2005
First Live HD Multichannel Broadcast - WFAE

June 2007
SCMS acquires assets of Major Broadcast Equipment Supplier*



We are here for the Long Haul!

Contact SCMS at any of its offices to discuss your broadcast needs Ask for Bob, Ernie, Matt, Mike or Andy at **1-800-438-6040**

Mid-South: 1-877-391-2650 Bob Mayben
Central: 1-731-695-1714 Bernie O'Brien
West Coast: 1-866-673-9267 Doug Tharp
Mid-West: 1-513-899-3036 Mary Schnelle
South-Atlantic: 1-770-632-1295 Art White

North-East: 1-315-623-7655 Jim Peck
South-West: 1-210-775-2725 John Lackness
North Central: 1-513-376-8600 Pam Lefler
Pro Audio: 1-877-640-8205 Ric Goldstein
Latin America: 1-760-650-1427 Lily Massari

SCMS
INC.
www.SCMSInc.com

*Go to www.SCMSInc.com for details
HQ in Pineville, NC

PORTABLE PRODUCTION

Handy gadgets for production on the go



tive electronic equipment from damage caused by line voltage irregularities such as sags, brownouts and overvoltages. The AR-15 Series II reduces line noise by filtering and purifying ac power. The AR-15 regulates an input voltage ranging from 97V to 141V to maintain the 120V output. The unit includes Furman's Linear Filtering Technology to reduce noise. The unit hosts eight outlets on the rear panel and one on the front panel and is housed in 1RU. An LED bargraph meter indicates the input voltage, while a separate LED indicates the output voltage is within an acceptable range.

707-763-1010; www.furmansound.com; info@furmansound.com

Field-deployable Cat 5e cable Belden



Brilliance Catsnake Tactical: Cat 5e UTP cables are AES/EBU-compliant and feature rugged construction. Brilliance CatSnake UTP cables feature Bonded-Pair unshielded twisted pairs with 24 AWG stranded bare copper conductors and polyolefin insulation. To further ensure the durability, portability and re-usability there is a heavy jacket wall version for medium duty use or an upjacketed version for the harshest heavy-duty applications. And, to increase flexibility, the cables offer stranded conductors and matte-finished jackets.

**800-BELDEN1; www.belden.com
info@belden.com**



Firewire audio interface Focusrite Audio Engineering

Saffire LE: The Saffire LE has six inputs and eight outputs (including stereo digital I/O) with comprehensive monitoring and I/O control options. The interface comes bundled with a host of software titles, including FXpansion's BFD ultralite and a demo version of GURU, Novation's classic B-Station soft synth and perhaps most notably, Ableton Live 5 Lite. It also comes with 470 megs of royalty-free loops and samples.

516-249-1399; www.focusrite.com

Digital hand-held recorder M-Audio

Microtrack 24/96: A two-channel digital recorder that records WAV and MP3 files, the unit stores elements to Compact Flash or microdrives. Balanced 1/4" TRS line inputs and 1/8" mic inputs with phantom-powered mic preamps provide flexible input options. Audio can be exported via S/PDIF digital, RCA analog or USB 2.0. An 1/8" headphone output is included. Power is provided by a lithium-ion battery, and the unit can recharge via the computer's USB connection or USB power adapter.

866-657-6434; www.m-audio.com; sales@m-audio.com



Field recording mic Avlex

Superlux E531: Featuring a mid-side configuration, battery powered operation and a 3.5mm stereo mini plug that facilitates integration with a wide range of products; the Superlux E531/BCS microphone makes the ideal recording tool for capturing orchestras, choirs, stage or outdoor venues. The microphone has a cardioid polar pattern for its mid section and a figure-eight polar pattern for the side. It offers the recording engineer 90- or 120-degree coverage patterns at the flip of a switch.

**877-447-9216; www.avlex.com
sales@avlex.com**



Line-level controller A-Designs Audio

ATTY2'D: This multi-channel, passive, line-level controller is the big brother of the ATTY stereo passive line-level controller. Housed in a 1RU chassis, the ATTY2'D features two stereo and two mono channels. All four channels have their own individual mute switches and large, cast aluminum, rotary level controls. A single master mute switch is also located in the center of the front panel for fast termination of audio signal to all channels.

**818-716-4153
www.adesignsaudio.com
sales@adesignsaudio.com**

USB Condenser Mic Marshall Electronics

MXL USB.008: A low-noise, large-diaphragm condenser mic designed for portable recording. No special software or drivers are needed for this USB plug-and-play mic. It features a large 32mm gold diaphragm capsule, a 20Hz to 20kHz frequency response and a three-position analog gain control. The digital section features a 16-bit Delta Sigma A/D converter with sampling rates of 44.1 kHz and 48.1 kHz. The mic ships in a tote bag, which includes a desktop mic stand, stand adaptor, a 10-foot USB cable, windscreens and user's manual.

**800-800-6608; www.mxlmics.com
sales@mxlmics.com**

WATCH FOR THESE MODELS FROM VIOLET DESIGN

hear this THE GLOBE

"The Globe from Violet Design is a pleasantly airy, vintage-sounding microphone, which may have you comparing it to old classic German microphones used on your favorite recordings... The microphone is very beautiful to look at, appointed with rich purple, gold and silver colors that make it look more like some kind of sculpture at first glance..."

The Globe is as close to heaven, as I'll ever hear

...I can't stress it enough, a great sound should inspire the performer or artist to a better performance. The Globe does that."

— Reviewed by Mike Lawson
AppleProAudio.com

Violet DESIGN
visit violetusa.com to learn more

PRODUCT SOURCE

UPCOMING

PCI sound card

Audio Science

ASI6585: The ASI6585 is designed for use in an Axia Livewire IP-audio based radio broadcast automation system. It uses the Livewire protocol to record and play audio streams over a standard Ethernet network. Providing eight play streams mixed to eight stereo outputs and eight record streams fed from eight stereo inputs, the ASI6585 features Audio Science's anything-to-anywhere mixing and routing. Choose from uncompressed PCM, MPEG Layer 2 and MP3 for recording and playback. Compression is handled by an on-board floating point DSP. DSP-based functionality includes MRXT multi-rate mixing technology that allows streams of different sample-rates and formats to be mixed digitally. TSXT time scaling allows compression/expansion of any or all playback streams in real time with no change in pitch.



302-324-5333; www.audioscience.com; sales@audioscience.com

The ASI6585 is designed for use in an Axia Livewire IP-audio based radio broadcast automation system. It uses the Livewire protocol to record and play audio streams over a standard Ethernet network. Providing eight play streams mixed to eight stereo outputs and eight record streams fed from eight stereo inputs, the ASI6585 features Audio Science's anything-to-anywhere mixing and routing. Choose from uncompressed PCM, MPEG Layer 2 and MP3 for recording and playback. Compression is handled by an on-board floating point DSP. DSP-based functionality includes MRXT multi-rate mixing technology that allows streams of different sample-rates and formats to be mixed digitally. TSXT time scaling allows compression/expansion of any or all playback streams in real time with no change in pitch.

302-324-5333; www.audioscience.com; sales@audioscience.com

Server enclosure

Middle Atlantic Products


VMRK: VMRK Series Configured Server Enclosures are manufactured with features that simplify cable, thermal and power management when mounting servers or other data-specific components, and save broadcast integrators valuable time and energy when ordering, installing and servicing components. The enclosures are versatile, full-featured and designed to easily house servers from all of today's leading manufacturers. They are also designed to facilitate passive thermal management with perforated front and split rear doors and a Decora temperature monitoring module for local monitoring; as well as electrical knockouts on rear plates, removable split bottom rear panel, integral gland grommeted cable pass-throughs and a 42-space vertical lacing strip.

973-839-1011; www.middleatlantic.com; sales@middleatlantic.com

VSWR interlock control system

ERI-Electronics Research

VPS-100: The ERI VPS-100 addresses the specific demands of FM master antenna systems requiring multiple contact closures for control. The system provides up to eight simultaneous sets of form C contact closures for multiple transmitter control in the event of an antenna fault. There are also eight form C contact sets available



for individual programming. The VPS-100 can accept samples from an optional directional coupler interface or from third party monitor systems. Relay interface is through industry standard DB25 connectors. The system is part of a family of products developed in collaboration with BDI that can be interconnected by a common bus structure for communication and control of other devices. Some basic features include programmable strike counter interlock control system, LCD display showing status of events, including time/date stamp, complete front panel control and optional network interface for remote access.

812-925-6000; www.ERlinc.com
sales@ERlinc.com

Streaming module for FM Extra

Orban
Opticodec 1010: This software module streams encoded AAC Plus audio from Orban Opticodec-compatible audio servers into the FM Extra encoder and over-the-air to FM Extra-enabled receivers, eliminating transcoding.

480-403-8300; www.orban.com
sales@orban.com

**Measure
and
Display
it with**




142 Sierra Street
El Segundo, CA 90245 USA
Tel: (310) 322-2136
Fax: (310) 322-8127
www.eseweb.com

Acoustic panels Golden Acoustics

Equalizer Squares: These innovative Equalizer Squares are specifically designed to focus on the middle to high frequencies found in most modern office environments. They are designed to be easily installed in existing grid systems, or mounted directly to the wall. They effectively diffuse sound from multiple sources and directions.

248-548-8840
www.goldenacoustics.com

When You Want More Than Just An Antenna



**Full line of HD Radio Accessories:
Circulators, Mask Filters,
Reject Tuners, and
Rigid Components.**



**MASTER FM
DUAL INPUT
HD ANTENNA**



**JSHD DUAL INPUT
HD SIDEMOUNT
ANTENNA**



**RCHA 10dB
HIGH LEVEL
HD INJECTOR**



Your Partner for HD Radio Solutions

JAMPRO ANTENNAS/RF SYSTEMS, INC. • P.O. Box 292880 • Sacramento, CA 92829 USA • Phone (916) 383-1177 • Fax (916) 383-1182 • Toll Free (866) 452-6770 • www.jampro.com

Time is Infinite



Broadcasters have counted on ESE precision master clocks and timing-related products for over 35 years. ESE products accurately synchronize broadcast operations using a choice of GPS, WWV, Modem, Crystal or line frequency for affordable, reliable, perfect time.

Spend a few seconds on www.eseweb.com to discover a vast universe of timing systems that are designed for easy installation, set-up and operation.

BEYOND THESE WALLS

When the work is outside the studio

AES/EBU digital audio monitor Videoquip



DM-1: The DM-1 is a portable monitoring system for AES/EBU digital audio signals. The unit provides a D/A (digital to analog) converter, headphone amplifier and LED display of the incoming sampling frequency (32, 44.1, or 48kHz). Plugging a valid AES/EBU signal into the back of the DM-1 allows headphone monitoring of the signal, with visual status. Any standard headphone from 8 to 600Ω impedance may be used. A front panel level control adjusts the headphone volume.

888-293-1071; www.videoquip.com
vrl@videoquip.com

Head-strap work light Pelican Products

Heads Up Lite 2670 LED: The HeadsUp Lite 2670 LED is a 0.5W, 4.5V, weather-resistant 4.8oz headlamp that gives off 22 lumens of clean brilliant light for up to eight hours while in constant mode. It has a rear intermittent and constant safety beacon, which can be seen for more than half a mile at dusk and flash for more than 20 hours.

800-473-5422; www.pelican.com
sales@pelican.com

Spectrum analyzer, monitor Winradio

WR-G33WSM: A high-performance, low-cost receiver and spectrum analyzer developed for wireless mics and other wireless audio devices. The receiver's frequency range covers all standard wireless mic and other VHF/UHF frequencies used in audio production, including the FM broadcast band and point-to-point communications. Highly sensitive, easy to interface with standard laptops and PCs and optimized to work with short VHF/UHF antennas, the receiver is also simple to install and intuitive to use. The scanning function maps the radio spectrum environment of a particular location to determine available frequencies and allocate wireless mics to the available channels. The entire spectrum environment of each venue can be saved and recalled later, to save time during the next visit. The receiver connects to a PC via the supplied USB cable. The frequency range is: 30Hz to 1,000Hz. It operates on 12Vdc at 600mA.

+61 3 9568 2568

www.winradio.com
helpdesk@winradio.com

Reusable label dispenser Dymo

Rhino 101: The Rhino 101 reusable label dispenser is a refillable, hand-held labeling tool that provides tape, pen, writing surface and cutter into one. While electronic label printing is a fast-growing segment of the market, traditional pen-and-tape labeling remains the method of choice for some, as well as a viable means of temporary labeling in the rough-in phase of installations. The Rhino 101 is available in two packages, one for wire and cable marking (contains self-laminating die cut vinyl labels) and one for general purpose marking (contains continuous flexible nylon labels). It features a large window for writing and viewing, a belt clip and lanyard hook and thumb-driven label advance.

800-426-7827; global.dymo.com

Cable protector Yellow Jacket



AMS: The Yellow Jacket Advanced Modular System (AMS) is a cable protector system designed to grow with a user's needs. The system interfaces with a broad range of existing cable protector systems. Simply add more center sections to protect an additional 5, 50 or more cables, lines or hoses.

626-357-7051
www.yjams.com
sales@yjams.com

Power distribution unit BMF Power



Value Line: Available in eight, 10- or 12-socket configurations, these ac line filters include two- and four-pole EMI noise filtering and provide protection from destructive power line surges. All models include a lighted on/off power switch and resettable circuit breaker. Versions are rated for 15A and 20A capacities with NEMA sockets mounted in a horizontal position to accommodate wall plug-style adapters without blocking the adjacent sockets.

781-792-2720
www.bmfpower.com

Ipod rackmount docking station Raxxess

**RXS-IRDS,
RXS-IRDS2:**




This ipod rackmount docking system is a push/push system: open the docking platform and dock the ipod. The platform closes for a sleek rack appearance. The in-rack IRDS station provides Firewire, USB and audio outputs, and is compatible with all ipod, ipod Mini and ipod Nano products.

800-389-RAXX; www.raxxess.com; info@raxxess.com

Cable pulling tool West Industries

Laserline: Equipped with a laser sighting device, Laserline installs a pull line up to 120' through web trusses, across suspended ceiling systems, under sub-flooring or through any limited access areas. Once a route has been established, aim the Laserline's laser sight at the proposed path for the installation and pull the trigger. A soft projectile pulls a nylon pull line up to 120' to the destination. The unit is machined from aircraft aluminum with an anodized finish. The kit includes CO2 cartridges, 17lb. nylon pull line, nylon darts with a foam tip and a carrying case.

651-458-1500; www.thelaserline.com; info@thelaserline.com



Sign-making software K-Sun

Maxisign v2: Maxisigns V.2 from K-Sun Corporation allows users to design and print professional OSHA mandated and ANSI/ISO compliant safety signs and tags with any PC compatible desktop printer. Enhancements, such as Homeland Security signs and symbols, add to the wide library of safety pictographs, ergonomic, AED and recycling symbols, lockout/tagout formats, IMO signs and ANSI/ISO symbols. Each sign can now be translated into Spanish or Canadian French with the click of a mouse button.

800-622-6312; www.ksun.com; info@ksun.com



Expect MORE From Your AM Transmitter



Armstrong Transmitter X-1000B

1KW HD Radio® ready AM Transmitter for under \$10K

Built with dual hot-swappable 600 Watt RF modules capable of 150% modulation, X-1000E can bring that major market sound to your radio station. Engineered with the latest technological innovations, X-1000B offers high reliability, built-in redundancy and it is HD Radio® ready.

Best of all, our customers tell us that the money they save running the X-1000B pays for itself with

savings in electricity and maintenance costs over an older transmitter...and as a bonus they get exceptional reliability and that major market sound for free.

But, don't take our word for it. Talk to our customers already on-the-air with the X-1000B. Call or email for a users list and decide for yourself why owning this transmitter is a no-brainer.

ARMSTRONG
TRANSMITTER CORPORATION

Tel 315-673-1269 / sales@armstrongtx.com / www.armstrongtx.com

* HD Radio is a registered trademark of iBiquity Digital Corporation.

2007 PRODUCT SOURCE

RF testing equipment
Bird Electronic



multi-octave bandwidth. Bird's load products also deliver more standard VSWR Mismatch values, including 1.10:1, 1.20:1, 1.25:1, 1.30:1, 1.50:1, 1.75:1, 2.00:1, 2.50:1, 3.00:1, 4.00:1 and 5.00:1. The frequency range across the entire series is DC to 1000MHz with N male or female connectors as standard. Bird offers Calibrated Mismatched Loads products in models 2-TMN-(1R10, 25, 30, 50, 75; 2R00; 3R00).

866-695-4569; www.bird-technologies.com; sales@bird-technologies.com

Operate any 3-phase broadcast transmitter from a 1-phase utility supply with the Phasemaster® Rotary Phase Converter

The most reliable alternative to utility 3-phase... AND the least expensive!



- High efficiency output
- Maintenance free operation
- True 3-phase, NOT open-delta
- Approved by all utilities
- Over 1000 TV and radio stations rely on Phasemaster®

Turn any location into a 3-phase site within hours!
Save thousands of dollars on utility line extensions
Recommended by leading transmitter manufacturers

Kay Industries
PHASEMASTER®
Rotary Phase Converters

The World Leaders in Single to Three-Phase Power Conversion
www.kayind.com info@kayind.com

RECEIVERS

OUTSTANDING specifications and pricing on professional quality receivers for **EAS**, monitoring and translators.

The **AFC3** is a three receiver rack mount that is configured to your **EAS** or monitoring specific application. Each receiver has internal frequency selection (PLL) switches, front panel controls and indicators, and rear panel connections.



Price: Approximately \$1,300 (depending on receiver choice)

Select three receivers from our FM or FM/SCA, NOAA Weather, Public Service and/or AM Monitor/Receivers. All receivers are PLL (synthesized) designs using the latest state of the art components and are available as stand alone receivers as well as in AFC3 combinations.

DAYTON INDUSTRIAL CORPORATION

2237 Industrial Blvd., Sarasota, FL 34234 Tel. (941) 351-4454
Email: sales@DaytonIndustrial.com WebSite: www.DaytonIndustrial.com

Quality Receivers Designed and Manufactured in the USA since 1980

Digital recording studio

Korg

D3200: The D3200 provides unique professional features and studio quality audio. Up to 12 tracks can be recorded at once, allowing a complete production to be recorded in a single pass. The D3200 provides up to 32 tracks of digital audio playback at 16- or 24-bit resolution at sample rates of either 44.1 or 48kHz. The D3200 features a flexible 12-bus, 44-channel mixer with up to 69-bit internal processing resolution for incomparable audio quality. Automated mixing lets users record and play back fader, pan and other mixer events. In addition, 100 scene memories provide finely detailed snapshot automation. Eleven 56-bit effects are available simultaneously, utilizing 52 algorithms, including Korg's proprietary REMS modeling technology. 128 preset programs and 128 user locations are provided, as well as an additional 32 user programs within each song. All effects can be easily tweaked and edited using the Knob Matrix.

631-390-6500; www.korg.com



Modulation monitor

Day Sequerra



M2.2R: Based on the popular M2.0, the M2.2R gives broadcasters additional tools to monitor and alarm their HD Radio broadcast transmissions. In addition to the original M2.0 model's basic capabilities, the M2.2R includes six programmable dry, floating alarm relays, RBDS and RF Multipath displays, full FM analog component monitoring including SCA and pilot injection levels and AM noise, a multiplex output for external SCA decoders, Ethernet interface for streaming PAD data or remote control, and Day Sequerra's Remote Dashboard software program, which lets broadcasters remotely tune the unit, alarm key signal parameters and log their data. The new M2.2R also features full time digital audio output, even when tuned to an analog station. The company has rolled their PLM (Performance Loss Module) Option into the M2.2R. This technology employs proprietary heuristic algorithms, which cannot be fooled by pink noise or tones, and will generate alarms when real program silence is detected in HD Radio or analog broadcasts. The M2.2R can also trigger an alarm on loss of RF Carrier, Audio, OFDM Lock, RBDS Stream, PAD Stream,

856-719-9900; www.daysequerra.com; info@daysequerra.com

Coaxial Transfer Switch



case of power loss, the switch will remain in position once power is restored. There is also a manual override that can be performed when ac power is disconnected.

201-767-5380
www.myat.com; sales@myat.com

Pencil condenser microphone

Samson Technologies

CL2: The CL2s are true capacitor microphones that feature a high pass filter and 10dB pad. The mic ships with both cardioid and omni removable elements featuring three micron, gold-sputtered diaphragms with maximum SPLs of 141 and 138dB respectively. The CL2 is ideal for recording or miking orchestral instruments, acoustic guitar, piano, overhead miking of drums and cymbals, vocals and choirs. The mic comes in a durable, lightweight aluminum case with a clip, pop filter, windscreens, shockmount, XLR cable, and the cardioid and omni capsules.

631-784-2200
www.samsontech.com
info@samsontech.com

Analog mixers

Mackie



Onyx 1220, 1620 and 1640: Mackie's Onyx 1220, 1620 and 1640 premium analog mixers incorporate extremely low-noise microphone preamps and circuitry, tremendous durability, many direct instrument inputs with a FireWire option for integration into any computer-based system. They also feature an all-new EQ circuit. Three small-format mixers make up the Onyx line. The Onyx 1220 is a 12-channel (4 mic/line inputs and eight line inputs) mixer with two buses and a three-band Perkins EQ with sweepable midrange. The Onyx 1620 is a 16-channel (8 mic/line inputs and four stereo line inputs) mixer with two buses and a four-band Perkins EQ with dual sweepable midrange. The Onyx 1640 is a 16-channel (16 mono mic/line inputs) mixer with four buses and a four-band Perkins EQ with dual sweepable midrange.

800-898-3211; www.mackie.com; productinfo@mackie.com

Audio processing tool

Symetrix



Deuce 722: The Deuce 722 is designed to solve numerous everyday audio-processing problems. Featuring two inputs and outputs (on XLR and Euroblock connectors), it contains microphone pre-amplification (featuring a Tait front-end with true +48V phantom power), compression, split-band compression, downward expansion, gating, de-essing, AGC, ambient noise compensation, feedback elimination, equalization, mixing, stereo width and balance, delay and more within a single rack space.

425-787-3222; www.symetrixaudio.com; sales@airtoolsaudio.com

Music scheduling software

Broadcast Software International



Natural Music: Natural Music maintains music library databases, generates daily music logs according to pre-set rules and includes interfaces for most computer automation systems. Natural Music features a virtually unlimited number of songs in the library, 1,225 different music categories, drag-and-drop music-log editing, day part and hour circulation rules, including horizontal separation, and an audit log for troubleshooting.

888-BSI-USA1; www.bsiusa.com
info@bsiusa.com



reliability of modern digital signal processing. Due to their compact design, the transmitter occupies a maximum of four height units. All functions are integrated in one box; single frequency network operation is possible.

410-910-7800; www.rohde-schwarz.com; info@rsa.rohde-schwarz.com

Newsroom production

RCS

Prophet Newgen 1.6: This stand-alone newsroom software enables reporters to write newscasts, receive and manipulate wire copy and digitally record, edit and playback audio. This upgraded version includes the added ability to ingest wire services via IP, flexibility to run the News Feeder service on multiple CPUs, moving a media file or story to a new category will update the erase date to reflect the new category's settings, added created date, created user, length and media length columns to the story library, modified e-mail format to send as blind carbon copy, and time and date are now displayed based on regional settings.

914-428-4600; www.rcsworks.com
info@rcsworks.com

Acoustic panels

Realtraps

Corner Mondotrap, Tri-Corner, RFZ: The new Corner Mondotrap is similar to a standard Mondotrap at four inches deep but with beveled sides to nest attractively in a corner and appears only one inch deep. All other dimensions and properties are the same as a standard Mondotrap. The Realtraps Tri-Corner is a triangle-shaped bass trap, also four inches thick, that fits perfectly in tri-corners where two walls meet the ceiling or floor. Like the Corner Mondotrap, the new Tri-Corner appears only 1" thick when installed. At 32" on each side, it has a surface area large enough to tame even very low bass frequencies.

860-210-1870; www.realtraps.com; sales@realtraps.com



Tube transmitter

Harris

HT/HD+: This transmitter, which evolved from the technology of Harris' HT Series of FM transmitters, marks Harris' foray into the HD Radio market with high-power tube-type transmitters. The transmitter will be outfitted with a Flexstar HDX exciter as part of the system. When used with a Flexstar, the transmitter features RTAC digital pre-correction to correct the tetrode tube used in the Harris HT Series of FM transmitters.

800-622-0022

www.broadcast.harris.com; broadcast@harris.com

FM transmitter

Rohde & Schwarz


SR8000: This transmitter is equipped with a digital exciter, provides output power from 100W to 1kW. The digital exciter combines the specs of the analog exciters from the company with the

Talkshow system

Telos Systems

Nx12: The Nx12 provides support for POTS, ISDN and Livewire audio-over-IP technology. This is a self-contained, 12-line system that includes four hybrids. Available with analog or AES inputs/outputs, the system mixes callers down to two separate analog or AES feeds when the built-in outputs are used. Four hybrids remain present. The system includes echo cancellation for VoIP and cell phone callers. With two program-on-hold inputs and two analog or AES outputs, the system is capable of handling the telephone requirements for two stations simultaneously.

216-241-7225; www.telos-systems.com; telos-info@telos-systems.com



specify:

Millenium LIVEWIRE®

For Network Connectivity

Millenium Livewire consoles feature IP audio connectivity AND local studio mixing.

Connect your local studio sources to 12 channels of studio mixing and select facility-wide sources on LCD displays. Radio Systems combines the power of Livewire networking with the functionality of a studio stand-alone console package.

Analog, Digital or Livewire – only Millenium lets you choose.

radio SYSTEMS

Analog and Digital Broadcast Consoles

Radio Systems, Inc. • 601 Heron Drive • Logan Township, NJ 08085
Phone: 856-467-8000 • Fax: 856-467-3044 • www.radiosystems.com

Livewire is a registered trademark of TLS Corp.

2007 PRODUCT SOURCE

FOOTLLOUDER SOURCE



Transmitter

Crown Broadcast

FM600E, FM600R,

FM600T: The FM150 broadcast transmitter offers a frequency agile front panel, SWR metering from remote control and the ability to control output power from a remote control. The FM600 is available in three configurations: The FM600E is a basic exciter with composite input only. The FM600T is a good choice for the lower power broadcaster, with its built-in audio processor and stereo generator. The 20 percent upgrade in power over the company's previous FM500 allows the end user to accommodate date line loss without upgrading to the next higher power Crown unit. The FM600R is the translator option with built-in receiver. With low-loss circuit boards and copper heat spreaders in the RF chain, the unit functions with less heat and improved life span. A robust power supply with switching voltage and power regulators for ac or dc operation allows the FM600 to be used anywhere power can be generated.

800-262-8919

www.crownbroadcast.com; fmsales@irecl.com



Intercom monitor, talk panel

Sierra Automated Systems



ICM-32: Designed for a variety of broadcast communications, the monitor features 32 separate talk/listen channels, each with a two-line/eight-character VFD display; dial-up listen and talk of any router system source or destination; and mixing of multiple sources for listen with independent volume control adjustment. Connectivity is via Internet, local LAN or directly to the SAS 32KD.

818-840-6749; www.sasaudio.com; sales@sasaudio.com

Codec

Broadcast Tools

USB Match Tool: The USB Match Tool is a professional USB-to-bi-directional stereo audio codec. It provides professional audio connectivity between the users professional stereo analog equipment and the PC's USB port. The USB Match Tool is equipped with the Burr Brown Delta Sigma 8x over sampled USB codec that will operate with virtually any audio editing, recording or broadcast automation software at sample rates up to 48kHz and up to 16-bit resolution. The front panel is supplied with input and output trimmers along with a stereo LED input level meter. Plug-in Euroblock screw terminals are provided for the electronically balanced stereo input and outputs. The tool is USB powered by a surge protected internal bi-polar 15Vdc switch-mode power supply affording superior headroom and high-definition audio.

877-250-5575

www.broadcasttools.com
bti@broadcasttools.com

Coverage, Reliability, and HD Radio™ Experience

When Vermont Public Radio installed HD Radio™ at some of the worst weather sites in North America, they chose

Shively Labs® ...again!

WVPR/Mt Ascutney; WNCH/Burke Mtn;
WVPS/Mt Mansfield - Bringing the first
HD Radio™ signals to the Green Mountain State!

P. O. Box 389, 188 Harrison Rd., Bridgton, Maine USA 04009
(207) 647-3327 (888) SHIVELY FAX (207) 647-8273
sales@shively.com www.shively.com

- An Employee-Owned Company -
ISO-9001:2000 Certified

THE NAB
RADIO SHOW
September 26-28, Charlotte
See us at Booth 401

GRAHAM STUDIOS

Quality...Function...Beauty...



Serving Broadcasters for over 23 years

(866) 481-6696 or (970) 225-1956 | www.graham-studios.com

Not just a pretty face...

Engineered for functionality, flexibility, and long lasting beauty.

Custom built or buy off the shelf.

Can reassemble in different configurations.

Easy access for wiring.

Several models to suit your budget.

Precision workmanship guaranteed.

Fully assembled "White Glove" delivery service available.

Nonpenetrating roof mount


Patriot Antenna Systems

Roof mount: The non-penetrating mount is a single or dual tray design and fits both 2" and 2³/₈" fittings. Turning over the center mast allows the switching from one size to another. One side of the mast will accommodate a 2" Az/El cap and the other side will accommodate a 2³/₈" Az/El cap. Assembly is easy and goes together like the previous single-tray models.


800-470-3510; www.sepatriot.com
info@sepatriot.com

REFERENCE ROOM

Selections for your bookshelf reference




Station planning and design book
Elsevier/Focal Press



A Face for Radio: This book explains in easy-to-comprehend language the basic concepts of applicable architectural and interior design elements as guidelines for space planning; building infrastructure; layout schemes for offices and technical facilities; colors, materials, and finishes; lighting and scheduling. The book includes images and plans from leading radio broadcasting facility designers in the U.S. and overseas, budgets and construction schedules for a variety of typical projects, and guidelines to follow for flexible programs that apply to radio stations of all sizes, from major market network affiliates to small independents.

Digital radio reference
Elsevier/Focal Press



The IBOC Handbook: This book outlines the entire digital transmission system for HD Radio. It includes system equations presented in a useful way that retain a clear description of the systems. Included is a history of the technology and the NRSC-5 standard.

Reference book

National Association of Broadcasters


Engineering Handbook, 10th Edition: The NAB Engineering Handbook provides detailed information on virtually every aspect of the broadcast chain, from news gathering, program production and postproduction through master control and distribution links to transmission, antennas, RF propagation, cable and satellite. Hot topics covered include HD Radio, HDTV, 2GHz broadcast auxiliary services, EAS, workflow, metadata, digital asset management, advanced video and audio compression, audio and video over IP, and Internet broadcasting. Basic principles and the latest technologies and issues are all addressed by respected professionals with firsthand experience in the broadcast industry and manufacturing.

Literature

Heil Sound

It All Starts with the Microphone: This primer on mics covers technical aspects to applications and tips that Bob Heil has mastered over his 40 years in professional sound reinforcement and microphone design.

www.heilsound.com



Directional antenna book

Layton Technical Services

Directional Antennas Made Simple: The first edition of *Directional Antennas Made Simple* was published in 1996. The second edition builds on the foundation of the first by reflecting current FCC Rules regulating these systems,


containing additional material suggested by readers of the first edition and having an additional chapter examining and explaining solutions to unusual RF problems encountered in AM radio facilities.

724-942-4054


Radio history book

Random House

Something in the Air: Radio, Rock, and the Revolution that Shaped a Generation is a look at how old media adapts when new media comes along, as well as a trip back to the heyday of Top-40 radio. Marc Fisher, award-winning journalist, Pulitzer Prize finalist and columnist for *The Washington Post*, captures the soul of radio and how it helped shape American culture—the culture which it no longer holds the imagination of—and what the future holds.



Unless noted, these books are available through most book outlets, including the SBE and NAB bookstores.



specify:

**Millenium
DIGITAL.**

For Digital Connectivity

When digital is the requirement—Millenium Digital Consoles are built to provide full digital quality and performance.

With 10 mix-minus outputs, simultaneous analog and digital stereo buses and **FREE** factory digital channel upgrades, Millenium digital consoles are engineered for your digital future.

Analog, Digital or Livewire – only Millenium lets you choose.

radio SYSTEMS •

Analog and Digital Broadcast Consoles

Radio Systems, Inc. • 601 Heron Drive • Logan Township, NJ 08085
Phone: 856-467-8000 • Fax: 856-467-3044 • www.radiosystems.com

2007 PRODUCT SOURCE

Monitoring system and subwoofer



Genelec

8020A, 7050B LSE: The 8020A has been designed for monitoring in difficult listening environments, particularly those characterized by lack of space. The 8020A has a die-cast aluminum Minimum Diffraction Enclosure, which features large internal volumes, curved edges and mechanical strength. Each monitor features a 4" bass driver along with a 3/4" tweeter loaded

into a new Genelec advanced Directivity Control Waveguide. The free field frequency response is 66Hz to 20kHz ($\pm 2.5\text{dB}$). Maximum peak SPL output per pair with music material is 105dB. Bass and treble drivers are each powered by 20W amplifiers. The 7050B subwoofer is a partner to the 8020A for both stereo and surround applications. The 7050B extends the LF response down to 25Hz. This is made possible in such a compact enclosure, thanks to Genelec's patented Laminar Spiral Enclosure (LSE) technology. The 7050B is designed to complement Genelec's 8020A active monitors in stereo and surround applications, and the 8030A in a stereo

508-652-0900; www.genelecsusa.com; genelec.usa@genelec.com



CD/DVD printer

Microboards Technology

PF-2: The PF-2 is a high volume disc printer that helps users create discs at a high speed and with a low cost-per-disc without outsourcing production. The printer is capable of printing 100 discs along with a spindled-output for improved stacking and handling, while still continuing with the ability to print 16.7 million colors at up to 4800 dpi resolution.

**612-470-1848; www.microboards.com
sales@microboards.com**

USB audio interface

Edirol

UA-1X: The UA-1X is a USB audio interface that offers component-quality audio signals to and from a computer. The UA-1X offers sound quality input and output from the computer through RCA jacks. The UA-1X also has an S/PDIF optical output to send digital signals to digital destinations and a headphone jack for direct monitoring of your computer audio and input signals. The UA-1X is ideal for use with laptops and for archiving audio on the computer or playing it back through your home stereo.

**360-594-4273
www.edirol.com
sales@edirol.com**

Your Single Source for Broadcast Solutions

LYNX™ Sidemount FM Antenna for IBOC Operations and Dual Input for Analog

Broadcast Towers and Structural Products

955 Series Low Power FM Band Pass Filter

Standard Rigid Line and MACXLine® Rigid Line with Bellows

Your Source for HELIAX® Coaxial Cable and Elliptical Waveguide System Components and Installation Accessories


ERI is your single source for the broadcast industry's best antennas, filter and combining systems, transmission line and RF components, and towers and structural products. Our professional team of engineers, designers, fabricators, project managers, and installers take pride in contributing to your success by delivering products and services to meet all of your RF and structural needs.

ELECTRONICS RESEARCH, INC. ERI

Visit Online at www.eriinc.com • Call Toll-free at 877 ERI-LINE

Compact FM transmitter

Rohde & Schwarz



NR8200: NR8200 FM transmitters are available for transmit powers of 2.5 to 40kW. Two single transmitters with up to 5kW each can be accommodated in a 19" rack. Even the complete 30kW transmitter requires only 2RU. Exciter standby, (n+1) standby, passive standby, and active dual output stage with manual or automatic switchover can be implemented for the R&S NR8200 transmitter family. Transmitters that are already in the network can be easily integrated in a (n+1) redundancy system.

**410-910-7800
www.rohde-schwarz.com
info@rsa.rohde-schwarz.com**

RBDS encoder

Proline

RDY: This fully digital RDS encoder features full controllable over frontside keypad and display, triple UECP inputs, double pilot inputs and RDS-57Khz output, IP port control, is remote controllable by RDS Database and Managements System or by Load and Control software and operates either as a single encoder or in a UECP or IP network.

**+31 26323 6969
www.proline.nl
info@proline.nl**

MAGER SYSTEMS, INC.
The Best in Sound Furniture

Since 1979 Mager Systems, Inc. has been custom designing and fabricating award winning furniture for the broadcast industry nationwide. We are still the innovators and leaders in solid surface tops and applications which comes with a 10-year warranty. Our complete one-stop-shop includes installation, turnkey prewiring, switches and components, conference rooms, reception desks, and office furniture. Our blending of art form with cutting edge techniques, and a clear understanding of each client's application allows us to produce your showplace tailored to your budget.

Custom Studio Furniture

TEL: 623-780-0045
FAX: 623-780-9860
mager@magersystems.com
www.magersystems.com
Visit our website for more information

HD Radio monitor Day Sequerra



with analog and digital balanced outputs, streaming RS-232 PAD data outputs and six programmable dry, floating contact alarm relays-18 relays, total. Each tuner stores 20 AM and 20 FM presets, decodes HD-1 through HD-8 multicast channels and displays signal strength, multipath, HD Radio PAD data and analog RBDS data. Indicators report HD locked, multicast present, delay bit set and tuner alarm. Audio output is uncompromised with an oversampled D/A converter driving Class-A biased audio outputs. HD Radio stereo separation is better than 90dB, and THD+N is less than 0.005 percent.

856-719-9900; www.daysequerra.com; info@daysequerra.com

AM conductivity software

V-Soft Communications

AM Conductivity v1.0: Version 1.0 of Conductivity for AM radio will automatically identify the correct ground conductivity curves to be used based on the field strength measurements it is provided along a specific radial. Breaks in the conductivity will be plotted on the radial's graph. The program can handle up to five data sets per each radial allowing comparatives; for example, for an omni-directional measurement to a directional measurement. Once given the measurements, Conductivity can construct the actual pattern the station is radiating. Conductivity is a standalone program, or it can be used in tandem with V-Soft Communications' AM-Pro, which will accept direct file input of the ground conductivity break files.

800-743-3684; www.v-soft.com; info@v-soft.com

Audio interfaces

Central Music Company (CME)

U2GKB, U2midi: The U2 USB Cable Interface Series is a series of USB cables with built-in computer interfaces for plug-and-play connection of line- and mic-level audio sources and MIDI keyboards and controllers. The U2GKB is for line-level sources; the U2MIC is for microphone inputs and features +48v phantom power via USB; and the U2MIDI carries 16 channels of MIDI to and from a computer. With a self-contained preamp and real-time monitoring, the U2GKB is designed for easy connection of an instrument to a computer for recording. It features a built-in audio interface with high quality A/D and D/A converters and is USB 2.0 compliant for fast transmission and low-latency recording. The U2GKB has a 1/4" input and a USB output.

www.cme-pro.com; info@cme-pro.com



On-air console Klotz Digital



Decennium: As part of a networkable audio routing system, the Decennium standard console is supplied pre-configured to simplify installation and set up. The console is modular and expandable, and the configuration software allows it to be customized as needed. The Decennium audio engine includes on-board DSP to provide voice processor, parametric six-band EQ and dynamics on each channel. Each channel strip features a rotary encoder with integrated push button and a 16-character display that can be used for source selection and channel-related parameter settings. The control surface is available in 4-, 8-, 12-, 16-, 20- and 24-fader frames.

678-966-9900; www.klotzdigital.com; sales@klotzdigital.com

Utility software DK Technologies

DK-Matrix: DK-Matrix is a PC software package for DK Technologies' MSD600M and PT0660 series of audiometers that allows engineers to set up their meters to suit their needs. Although the audiometers can be configured from the front plate, this new utility software option allows various aspects of the meter to be easily configured from a PC.

**+45 4485 0255; www.dk-technologies.com
info@dk-technologies.com**

M3: The 2RU monitor provides three frequency-selectable AM, FM and HD Radio multicast tuners, each equipped


Acoustic studio foam

Auralex Acoustics

Studiofoam Smartpak:

Auralex Acoustics' Studiofoam SmartPaks are available in several combinations, including 2" and 4" packages consisting of Studiofoam Wedges or Pyramids as well as a pack of LENRD (Low-End Node Reduction Device) bass traps. The 2" Studiofoam Smartpak totals 48 square feet with 12 wedge or pyramid 2'x2' panels per pack. The 4" Studiofoam Smartpak totals 24 square feet with six 2'x2' panels packaged together, and the LENRD Smartpak includes four bass traps. All Smartpaks are available in charcoal, purple and burgundy. Alternate colors and sizes, such as 1" and 3" products, are available via special order in standard packaging. The Performance Series of Roominator Kits are also available using Smartpak technology, including the Project 2, the Pro Plus and the Deluxe Plus Kits.

317-842-2600; www.auralex.com; auralexinfo@auralex.com



specify:

**Millenium
ANALOG**

For Analog Dependability

Millenium Analog Consoles still offer thousands of broadcasters great sounding audio performance.

With solid-state switching, rugged LED-lit keypads and total DC audio control, Millenium Analog Consoles are known for 24-7 reliability. When Analog fits the bill - the best value is Radio Systems Millenium Consoles.

Analog, Digital or Livewire - only Millenium lets you choose.

**radio
SYSTEMS**

Analog and Digital Broadcast Consoles

Radio Systems, Inc. • 601 Heron Drive • Logan Township, NJ 08085
Phone: 856-467-8000 • Fax: 856-467-3044 • www.radiosystems.com

2007 PRODUCT SOURCE



Portable mixer ranges

Soundcraft USA

FX16ii, EFX and MFX: An extension of its multipurpose mixer range, Soundcraft added three new FX models: the FX16ii, EFX and MFX, each featuring no less than 32 Lexicon 24-bit digital effects. The new models use the same AudioDNA processor found in many Lexicon and DigiTech outboard products, including the Lexicon MX500. The FX16ii is useful for on-location audio with 26 inputs, 16 direct outputs, four stereo returns and rotating connector pod, which allows cables to be connected behind the rack. Representing the smallest console in the Soundcraft multipurpose range, the EFX offers a professional solution in a smaller frame size, available in eight- and 12-channel versions.

818-920-3212; www.soundcraft.com; soundcraft-usa@harman.com

LED flashing red obstruction light Farlight



L-864: This LED luminaire was designed to replace incandescent beacon used for obstruction lighting of radio towers. It features 72 Luxeon Star LEDs, has a 45W power consumption, 120/240Vac power source, 2,000 candela peak intensity and can last an estimated 70,000-plus hours. The L-864 is compliant to FAA Advisory Circular 150/5345-43E, FAA Engineering Brief 67, ICAO Annex 14 (Medium Intensity Obstacle Light) and Transport Canada.

310-830-0181
moreinfo@farlight.com

Studio monitors KRK Systems

VXT Series: The VXT Series includes new proprietary woofers and tweeters, a newly designed curved face plate for excellent imaging, a new cabinet design that provides low resonance, improved structural integrity and extended low-end and slotted ports that

greatly reduce port turbulence. KRK engineers started with the functional cabinet design of the flagship monitor, the Expos, E8B to create a very high performance. The use of ABS structural foam as the cabinet material provides excellent damping characteristics and extended low end due to more internal volume. The ABS foam also absorbs shocks so the cabinet is impact resistant. The tweeter's dome is comprised of true silk, as opposed to cloth, which translates to fast transient response, excellent imaging and extended frequency response.

954-316-1500; krksys.com; service@krksys.com

Mixing console Broadcast Tools

Pro Mix 12: The ProMix 12 comes in a small package, but it is loaded with useful features including a mix-minus output, an announce booth output with full duplex talkback, a monaural output, selectable metering and remote starts on all line level stereo input channels. The mixer features 12 input channels including three microphone and nine stereo line sources; stereo program and audition buses, a cue bus, plus built-in mix-minus and mono outputs; and a comprehensive monitor system including an air input and user-programmable muting.

877-250-5575; www.broadcasttools.com; bti@broadcasttools.com

ST350: This lightweight multi-capsule microphone and compact mic-pre/control unit generates surround and stereo simultaneously at balanced line levels. The microphone electronics are capable of driving long cable runs. Control features include high-performance mic preamps with discretely switched 6dB gain steps and composite five-segment LED bargraph for level monitoring. Continuously variable control is offered over the stereo polar patterns from omni to figure-eight with a width control providing mono to wide image stereo. A high-pass filter, switchable M/S output and headphone monitoring are included.

+44 1924 201 089; www.soundfield.com; sales@soundfield.com

Surround microphone Soundfield Research



IP controller Fox Electronics

GPI-100: The GPI-100 is a point-to-point and point-to-multipoint system to transport 12 relay/GPI commands over IP, providing as many as 12 independent switches for equipment at one or more remote site or from a remote back to a primary location. Multiple transmitters and receivers can be interconnected for applications requiring the transport of more than 12 relay/GPI commands or for transport to multiple sites. The GPI-100 configures automatically once connected to the network. Special system application software and updates are downloadable from the company's website. Features include: transmits refresh packets every second, automatic reboot and refresh with loss of IP link and time stamp.

800-604-0301; www.foxelectronics.net; info@foxelectronics.net

Audio receivers

International Datacasting

SFX: The SFX Pro Audio receivers with integrated Datacast XD offer live IP audio decoding plus the ability for time-shift audio file playout for advanced radio networks. The upgraded dual-channel SFX Pro Audio now features MPEG-4 AAC decoding as well as Livewire, which allows the receiver to convey low-delay and high-reliability audio over switched Ethernet.

613-596-4120; www.datacast.com



Mic for female voice AKG

Elle C: Custom-designed for female performers, AKG produced the Elle C live performance vocal microphone. The Elle C features an XLR connector module with 24-carat gold plated pins for optimized connectivity, as well as resistance to corrosion and humidity. Additionally, the mic features a spring steel wire-mesh grill for extreme ruggedness offering reliable control of pops and wind noise. The Elle C features a frequency range of 60 to 20,000Hz.

818-920-3212; www.akgusa.com
akgusa@harman.com



Lavry Black AD 10 and DA 10

www.lavryengineering.com Tel (360) 598-9757

AD 10- 24 bit Analog to Digital Converter

- .0009% THD+N 20Hz-22kHz
- Dynamic Range > 117dB unweighted 20Hz-22kHz
- Dynamic Range > 120dB A-weighted
- XLR +4dBu and TRS -10dBV inputs
- XLR AES/SPDIF and Optical outputs
- Ultra low jitter internal clock 44.1, 48, 88.2, 96 kHz
- Ultra low jitter external clock 32-100 kHz
- Intuitive User Interface for easy operation

DA 10- 24 bit Digital to Analog Converter

- Three digital inputs- XLR/ RCA /Optical
- Digitally controlled ANALOG volume
- Discrete Headphone amplifier
- Crystal mode virtually eliminates jitter
- Includes sample rate conversion
- 44.1, 48, 88.2, 96 kHz Crystal and Narrow mode
- 32-200 kHz Wide mode

See our website for more information on the LavryGold and LavryBlue lines.

5.1 Surround conversion

Fraunhofer Institut

SX Pro: This technology creates 5.1 surround sound from existing stereo content. SX Pro analyzes the audio signal and identifies characteristic sound elements. An intelligent algorithm redistributes these elements to create a natural surround sound listening experience without adding artificial reverberation. The center channel is smoothly integrated without altering the original stereo sound stage. The surround channels consist of the ambience-like sound components of the stereo material.

+49 0 9131 776 340; www.iis.fhg.de

MUSIC LIBRARIES

The music sets the mood

Royalty-free music

Sound Ideas

Music, Sound Effects, Production Elements: Sound Ideas released nine new royalty-free music CDs at NAB2007. The music ranges from wacky comedy music to extreme rock music. The company will also release five new sound effects CDs: Ultimate SFX Collection on Hard Drive, Monsters and Creatures, Ambience IV - Series 14,000, Sci-fi DVD Combo and Extreme Impact DVD Combo. Production Elements Toolkit Vol 3 has new production elements including Dark Ambiences and Elements, Static Swipes, Sweepers, Impact Sweeps and Elements and Transitional Elements.

800-387-3030; www.sound-ideas.com; info@sound-ideas.com

Sound effects downloads

Music 2 Hues

MUSIC 2 HUES

Production Music Library

duction element electronic FX. These categories can be downloaded entirely for one price. The download center also provides all the music from Music 2 Hues' Flagship Series CDs for immediate download. More than 1,000 music tracks and 500 sound effects are offered in the download center.

888-821-7515; www.music2hues.com; info@music2hues.com

sample CDs

Loopmasters




Artist Series: The collections will be produced for a variety of dance genres including house, techno, downbeat, electro, breaks, drum and bass and electronica. Each collection will include Acidised Wav Files, Rex2 Loops and Apple Loops. There will be patches for Halion, Kontakt, Reason NNXT, EXS24, SFZ and Stylus RMX compatibility.

+44 845 094 1460

www.loopmasters.com
info@loopmasters.com

Imaging elements

Noisefuel



High Impact: More than 300 high impact sounds including clangs, rumbles, smacks, thuds, stabs, explosive hits, fast attacks, lasers, flashes and more. CD-Rom includes WAVs and MP3s.

866-252-7788
www.noisefuel.com

Music libraries

Firstcom Music

Chappell, EVO and Gotham: Firstcom.com offers a new line-up of music including rowdy electronic rock from Chappell, a quintessential underscores collection from EVO and Gotham reigns extreme with classic fanfare for action sports and segues into the political season with positively scandalous themes. Set a remote to Firstcom.com and listen to the 20 new releases.

800-858-8880; www.firstcom.com
info@firstcom.com

Music library

Westar Music



Star Trax: Star Trax contains broadcast-length tracks (60s, 30s and stingers) from the Westar Music Library, plus all of the collection's Tags, Bridges, Production Elements and Segues, published in 16-bit/44.1kHz.BVVF format. A complete set of metadata is embedded in the files, ready for use with asset management software. This production music collection is available on 10 DVD ROM discs, and it currently offers more than 5,300 tracks (26.5GB) of professional music and transitions.

866-463-0100

www.westarmusic.com
info@westarmusic.com

Music library

Unique Tracks

High Impact Sound FX Series:

Unique Tracks' High-Impact Sound FX Series collection includes 1,350 effects organized into four volumes.

Volume 1, High-Impact Radio, contains 365 sound effects designed to boost a radio station's promos, sweepers and station IDs. Volume 2 is High-Impact Television. Volume 3 is High-Impact Multimedia for Powerpoint, Flash and Web creators. Volume 4 is High-Impact Game Design.

888-400-2149; www.uniquetracks.com



For Performance Spaces or Production Places

Acoustics First®

Materials to Control Sound and Eliminate Noise™



From practice spaces to professional recording studios, we can help you get the materials you need to fit your application and budget. Our products include acoustical foams, fiberglass panels, diffusers, bass and corner traps, vibration control, acoustical wall fabrics, ceiling tiles, modular enclosures and various other acoustical materials.

Toll Free

I-888-765-2900

Web: <http://www.acousticsfirst.com>

The Best FM-Translator Receiver, Hands Down!

Composite/MPX and L/R audio outputs.

Passes RDS and SCA subcarriers.

**Model 631
\$1390**

Wide/narrow IF bandwidth selection.

Accurate front-panel metering of total-mod, L/R program audio, signal strength and multipath.

Carrier-loss muting and built-in overdeviation protection.

'Tally' outputs for remote alarms of carrier loss and program audio channel loss.



For full technical details, visit

www.inovon.com

Inovonics
1305 Fair Ave • Santa Cruz, CA 95060
TEL: (831) 458-0552 • FAX: (831) 458-0554
www.inovon.com • e-mail: info@inovon.com

A/D & D/A converters Lavry Engineering



Lavry Black series: As a complement to the DA 10 digital-to-analog converter, the AD 10 embodies Lavry's design philosophy of transparency in conversion. Like the DA 10, the AD 10 offers ultra-stable clocking, low THD+N and wide dynamic range. The AD 10 has -10dBV TRS and +4dBu XLR inputs, and clocks externally from 32kHz to 100kHz. Both units operate at fixed sample rates of 44.1kHz, 48kHz, 88.2kHz and 96kHz; the AD 10 on internal crystal, and the DA 10 in crystal mode to virtually eliminate the audible effects of source jitter. The DA 10 also accepts inputs from 32kHz to 200kHz in wide mode. With a discrete headphone amp and digitally controlled analog volume adjustment, the DA 10 offers a straight-wire approach for monitoring digital sources without an external preamp.

360-598-9757; www.lavryengineering.com
sales@lavryengineering.com

Mid-size PA speakers D.A.S. Audio

Reference Series: Consisting of six two-way systems and three subwoofer systems, the Reference series is very versatile. The systems consist of two 12-inch models, two 15-inch models and two double 15-inch models available with 1-and 1.5-inch compression drivers equipped with titanium diaphragms. Included in the range of externally powered products are two subwoofer systems with a single 18-inch bass-reflex configuration and a high power double 18-inch system for use in applications requiring the extra low-frequency power, such as dance clubs and discos. Each cabinet has 12 M10 rigging points so that they can be easily installed using forged steel eyebolts. The rigging points can also be used with the two-piece wall or ceiling "L" brackets as well as the newly incorporated array frame, which permits a horizontal array of up to three RF-12 or RF-15 models. For mobile use, the 12- and 15-inch cabinets include a standard speaker stand/pole

888-DAS-4-USA
www.dasaudio.com; sales@dasaudio.com



NTP clock Masterclock

CLKNTA12: This external NPT source offers accurate legally traceable time. It synchronizes to network time. The unit features self-correction at power up, once each hour and return of NTP after loss. Wireless networking is available and it uses standard Ethernet wiring. The clock provides an internal crystal and clock chip for continuous operation without NTP. Its synchronous motor design runs off ac power line frequency. Encrypted network messages prevent unauthorized tampering of clock configuration, which is saved to non-volatile memory and survives power losses. A network discovery tool provides automatic discovery of NTP clocks attached to the network without changing the PC's networking configuration.

800-940-2248; www.masterclock.com
info@masterclock.com

Forget the Soundcard

GO USB



Dixon Systems NM-250 MKII newsroom mixer is now available with an optional internal USB interface. This eliminates the need for a soundcard and simplifies getting the audio in and out of your favorite software. For more information, visit our web site.

DIXON
Systems

www.dixonsystems.com

Microphones

Hebden Sound

HS3000 series: The HS3000 series is a highly versatile, detachable and fully interchangeable capsule system. It consists of four microphones with Omni (HS3010), Cardioid (HS3020), Hyper-Cardioid (HS3030) and Sub-Cardioid (HS3040) directivity options available singly or as matched stereo pairs. Each microphone is comprehensively tested in-house and comes with a standard 23mm clip and an anti-vibration mount in a lockable studio case. All four polar pattern options can be built around a single pre-amplifier unit and all capsules give a wide frequency range and low noise figures for the discerning audio professional.

+44 (0)114 201 3687; www.hebdensound.com; info@hebdensound.com



Headphone amp, splitter

Boostaroo.com

Boostaroo: The Boostaroo Model T613 is a portable headphone audio amplifier that doubles the available volume of audio players and separates the audio signal into individual stereo channels to drive three separate sets of headphones or speakers. Depending on the ohm rating of headphones, the Boostaroo will increase the volume of the player by 100 percent with no more than a 0.3 percent harmonic distortion. There is no difference in output or frequency response observed when one headphone is plugged in or when three headphones are plugged in. Signal to noise ratio is measured -95dBA from clipping level into a 33Ω resistance.

800-800-4354
www.boostaroo.com
orders@boostaroo.com


Digital mixer

Zaxcom

Deva Mix-12: This device is a control surface for the embedded digital audio mixer of the Deva IV or Deva V location recorders. The mixer provides a three-band shelving EQ with two notch filters and a high-pass filter for each channel, a soft-knee compressor with makeup gain, cross-faded cross points to eliminate clicks or pops, floating point DSP, unlimited routing and Penny and Giles faders. The mixer includes integrated record and stop buttons for the Deva. Each of the 12 fader strips provides access to bus routing and effects for that channel. An LED input meter is provided on each channel strip to augment the Deva's output metering. Three separate talk back buses can be routed to any combination of outputs and internal mix buses.

973-835-5000; www.zaxcom.com
info@zaxcom.com

Power protection MGE UPS Systems



Pulsar MX Frame: This UPS frame accommodates MGE's Pulsar MX 5000 RT power and battery modules for a modular and scalable power protection system. When the Pulsar MX online double-conversion power modules are connected in parallel within the Pulsar MX Frame, the power can be scaled from 5kVA to 10-, 15- or 20kVA power levels within the unit's 16RU frame. The same power and battery sub-modules from MGE standalone UPS units can be used in the frame. Units feature hot-swappable battery and power sub-modules, auto battery-test, switched outlets, multilingual LCD display and power management software. For extended backup time, redundant external battery modules can be added.

800-523-0142; www.mgeups.com
info@mgeups.com

Hideaway surface access

Extron



Hideaway HSA 822MS: The HSA 822MS is a motorized, double-sided, vertically lifting enclosure for inconspicuous computer-video interface and connector access. The enclosure installs at an adjustable height below the tabletop, so a surface matching the tabletop can be used for the cover, making the HSA 822MS nearly invisible in the closed position. The enclosure can be raised and lowered using a contact closure remote control or by pressing on the top surface. The motor is quiet and runs smoothly.

800-633-9876; www.extron.com
support@extron.com



interface VGA output and digital inputs, especially for monitoring multi-channel audio signals and mix outputs.

+49 221 709130; www.rtw.de

Eight-channel monitor RTW Radio-Technische Werkstatten

Digital Monitor 8CH: This digital 8-channel monitor with multi correlation display (phase meters), two-channel audio vectorscope has relevant functions for monitoring level, correlation and volume of digital multi-channel signals. It has a four-fold correlator, AES/EBU status monitor, stopwatch, and a remote control



Professional USB Converter Yellowtec

PUC: PUC is a two-channel self-contained audio interface for use with USB enabled desktop computers or notebooks. The unit is powered through the Universal Serial Bus, so no external power supply is needed. PUC requires no installation of drivers other than those automatically loaded by the host operating system. With the exception of a 1/8-inch headphone jack, audio connections are made via an optional breakout cable, which attaches securely to the PUC via DB25 connector. Electronically balanced analogue audio I/O (0dBFS = +18dBu) is provided through stereo pairs of Neutrik XLRs.

+49 2173 967 336

www.yellowtec.com; info@thummahr.de


Acoustical treatment kits

Media Specialty Resources

Studio Panel SP220, SP 502: Available in six standard colors with an additional 42 optional choices, the new SP220 and SP502 kits come with the same do-it-yourself installation kit included with the higher-priced Studiopanel kits. The point-of-sale package contains all the necessary tools as well as software that allows the end-user to properly place and install each system component for maximum results. The company's innovative larger room kits and various patent-pending acoustic treatment components remain available. The SP502 kit is useful for small- to medium-sized studios. It controls room echo and reflection decay time over a wide range of frequencies. The kit includes five absorber panels and two of the firm's Bazorber panels. The SP220 kit includes two absorber and two diffuser panels.

800-497-2087; www.msr-inc.com; info@msr-inc.com

Audio processor Audemat-Aztec



Silver Audio Processor: The Silver Audio Processor line is a new generation of digital audio processors that can be used to process audio for FM and digital broadcasting such as HD/DAB and Internet streaming. The line uses the latest multi-band DSP technology and includes four- and six-band FM audio processors with dual paths allowing simultaneous processing of FM and digital radio. HD versions, using look-ahead limiters, are also available and dedicated to the process of audio signals that are being fed off into codecs employing bit rate reduction techniques. The six-band FM and HD versions include as a standard the Ariane RMS leveller. This AGC corrects input level variations and also improves consistency. The block can provide stereo enhancement with its matrix mode of operation. The Silver Audio Processor line is provided with many factory and user presets for all music styles and applications. The A/B switching enables instant comparison between current settings and the preset ones.

305-249-3110; www.audemat-aztec.com; contact@audemat-aztec.com



selectable 12- and 24-hour format display with LED indicator, and desktop or optional rackmount.

877-250-5575; www.broadcasttools.com; btibroadcasttools.com

Clock Broadcast Tools

Intellitool: The Intellitool provides GPS or NTP referenced master clock. It features 0.56" six-digit red LED displays, a viewing distance up to 20 feet, automatic daylight-saving time, serial time code output in ESE TC89 or TC90 format with active high output driver, DPST relay time sync outputs, and a built-in GPS receiver.

SMALLER. FASTER. COOLER.

The only thing we didn't change is the price.



Our new 6500 series cards give you greater functionality at the same great price point. They're lead-free and RoHS compliant, too. With powerful DSPs, +24dBu levels, MRX™ multi-rate mixing, SSX™ surround-sound and AudioScience's "anything to anywhere" mixing and routing, our 6500 cards are ready for some serious broadcasting. To learn more, ask your automation VAR, or call +1-302-324-5333.

BUILT FOR BROADCAST

www.audioscience.com

AUDIO SCIENCE
Sound Engineering Since Evolution

Door system

Industrial Acoustics

Sound Control Doors: Each door system, complete with leaf, split-frame seals, hinges and latching hardware, is factory assembled and laboratory tested for performance, alignment, fit and ease of operation prior to shipment. All design changes or material substitutions are fully tested in the lab prior to incorporation. Optional finishes include choices from among 62 types of wood veneers along with paint and metal.

718-931-8000

www.industrialacoustics.com
info@industrialacoustics.com

DIGITAL AUDIO SWITCHING

THE LOGICAL WAY

3-DRX

Automatically switches between two AES Digital Audio signals or a stereo analog signal.
Analyzes digital signal errors (CRC, bit, framing, etc.) and checks for loss of audio on the digital signal. User programmable.

TITUS TECHNOLOGICAL LABORATORIES

800.806.8851 WWW.TITUSLABS.COM

2007 PRODUCT SOURCE



Headphone Alienware

OZMA 7: Alienware's branded headphones, the Ozma 7, comes out of a partnership with German headphone manufacturer Ultrasone AG. The Ozma 7s use Ultrasone's patented S-Logic™ natural surround sound technology and electro-magnetic field emission shielding. The headphones feature technology that produces up to a 40 percent lower dB output (3-4dB) for the same loudness sensation, reducing the risk of hearing loss; a 60 percent reduction in electronic magnetic field radiation; 3.5, 6.3mm screw-on gold-plated plug/adapter; and a frequency response of 10Hz to 25kHz.

1-800-Alienware; www.alienware.com

Green power devices Pulizzi Engineering

RoHS-compliant products: Pulizzi Engineering has achieved compliance to the RoHS Directive standards for the restriction of hazardous substances in electronic equipment. This directive bans placing products on the European Union (EU) market if they surpass allowable levels of lead, cadmium, mercury, hexavalent chromium, polybrominated biphenyl (PBB) and polybrominated diphenyl ether (PBDE) flame retardants. The company now produces 26 RoHS-compliant products.

800-870-2248; www.pulizzi.com; sales@pulizzi.com

Data delivery program Enco Systems

Padapult VS: PADapult was introduced in 2005 as a vehicle to enable broadcasters a means of fully automated or manual delivery of program metadata such as artist and title information as HD Radio Program Service Data, RDS encoders and other information displays. Along with HD Radio's digital audio signal, or Main Audio Program (MAP), there's also a text stream embedded in the carrier wave. This Program Service Data (PSD) consists of metadata and gives land-based stations capabilities similar to satellite radio services. Text scrolls across the front of the receiver's LCD panel. Song and artist information and station ID are standard content, but the PSD can also include traffic and weather updates or other information the station provides—even commercials. Other applications can include traffic, weather and sports updates and provide the advantage of incorporating this information in audio form that does not require the listener to read the information from their radio display.

800-362-6797; www.enco.com; sales@enco.com



Active harmonic filters Staco Energy Products

Stacosine: Stacosine uses power electronics to monitor a non-linear load and dynamically correct every harmonic order from the 2nd to the 31st. Through an injection and cancellation process, the sine wave is restored and distortion is reduced to less than 5 percent THD, meeting stringent IEEE 519 standards. Stacosine technology moves power from the ac source to its dc electronic platform, then back to the ac source rapidly, to cancel harmonics and equalize the sine wave. Designed to operate at levels that continuously adapt to rapid load fluctuations, models are available for 208 to 480 Vac, three-phase installations with an adaptive system frequency of 45/65Hz, and 120/240Vac control power. Equipment ratings are from 25A to 200A. Wall mount or freestanding NEMA 1 enclosures are standard, with NEMA 12 or 3R enclosures available.

937-253-1191; www.stacoenergy.com; sales@stacoenergy.com

The Plan B Classic is your guarantee of delivering uninterrupted audio service. It's three units in one:

- Digital and analog adjustable silence sensor
- Built-in backup audio on CD, DVD, or Compact Flash
- Auto-dialer with clear human voice

FM Extra radio receiver Digital Radio Express

Aruba: The FM Extra Radio Receiver Model Aruba features a new design with a wooden cabinet, built-in hi-fi speaker, tuned port for bass enhancement, improved RF reception specifications, connection for external speaker to use in stereo mode, Headphone output, Digital Optical Output, programmable for Conditional Access and a USB connection.

408-956-8707

www.dreinc.com; contact@dreinc.com

Multipurpose loudspeakers

TCS Audio

TM Series: The TM series of loudspeakers consists of 12 models: the TM10X, TM10XW, TM112, TM112R, TM112W, TM115, TM115R, TM115W, TM206, TM206W, TM215S, and TM215SW. Available in black with handles or white without handles, all TM Series products are finished with a rugged Duratex exterior and feature a foam-backed, powder-coated, 16-gauge perforated steel grill to protect the transducers. The TM112 and TM115 are available in reversed versions for mirror image applications. All TM Series loudspeakers feature Omnimount compatibility or include multiple 3/8"-16 captive nuts for mounting. Models TM10X, TM112, TM115, and TM215S also include pole cups for use on speaker stands or pole-mount applications. The woofers are neodymium coaxial transducers mounted in a vented enclosure.

800-403-4484; www.tcsaudio.com

info@tcsaudio.com



Podcasting service

Zilonis-Prestopod

Prestopod: Designed to be an all-in-one offering to help community and independent radio stations reach a wider audience, this service can quickly create a podcast from an existing online radio program. Prestopod creates and hosts the podcasts, lists them in podcast directories, and reports usage statistics.

360-488-0629

www.prestopod.com

info@prestopod.com

Label printer

K-Sun

Label Shop 2010-PC: K-Sun's LABELShop 2010-PC Printer connects to a laptop or PC with a USB cable and features a very small footprint that fits anywhere on a desk, lab bench or wherever a PC can go. Users can print custom labels with industrial-grade adhesive in 23 different color combinations from 1/6" up to a full 1-inch wide. Special shrink


tube labeling material can also be used in the printer for wire, cable, medical instruments or personal item identification.

800-622-6312; www.ksun.com; info@ksun.com

Cables Belden

Waterdog: The Belden line of New Generation Waterdog Cables includes paired, multi-conductor and coaxial cables that meet the water-resistant standards set by UL 444, UL 13, and the TIA 455-82B Water Filtration Test. The ruggedly constructed cables can be installed indoors or out, above or below ground, making it practical for building management systems to be connected seamlessly - from building to building or, for example, from remote surveillance camera sites to indoor security monitors. The user-friendly Waterdog cables are also ideal for deployment in standard indoor/outdoor building management installations.

800-BELDEN1; www.belden.com; info@belden.com



EAS station multiplexer DM Engineering



Multi Station Relay Adapter:

The Multi Station Relay Adapter (MSRA & MSRA-RM) expands the allowable controlled number of stations from a single Endec to a total of four. It is a microprocessor-based, three-stereo-channel accessory for the Sage-Endec EAS encoder-decoder. All digital commands and EAS audio is supplied by the Endec, and the MSRA interprets

these commands to select the appropriate station or stations for EAS broadcast. The MSRA digital communication with the Endec is via RS232 and the EAS audio for the MSRA is derived from the speaker line output connection of the Endec. A multi-turn, recessed front panel input gain trim potentiometer and individual multi-turn station gain controls are provided for controlling the active stereo distribution amplifier sections having balanced output levels capable of greater than +12dBm into a 600 ohm load impedance.

800-249-0487; www.dmengeering.com; info@dmengineering.com

PAD interface software

Modulation Index

PAD Bridge: Interfacing automation systems and databases to RBDS and digital radio data encoders is a challenge for many stations, and this software provides a bridge between those systems. It can be used to display dynamic program information via RBDS, HD Radio PAD MPS/SPS, Internet streaming players and large-format display signs. One instance of PAD Bridge is used for each program source, and is configured to send data to several different devices or computers. As many as eight instances of PAD Bridge may run on a single computer. PAD Bridge 1.0 runs entirely on the user network without any external server requirements or subscriptions. The software has a one-time license fee per source. The software will parse information directly from most automation systems.

909-860-6760; www.indexcom.com; info@indexcom.com

Microphone preamp

Focusrite Audio Engineering



The preamps feature the same vintage microphone pre-amplifier design as the original ISA 110 module from Focusrite's Forte console. The ISA 828 has eight line inputs, four instrument inputs and an optional eight channel 192kHz ADC. The microphone input stage includes a variable impedance circuit, allowing the user to switch between four carefully selected input impedance settings.

516-249-1399; www.focusrite.com

Digital audio console

AEQ



Arena: This console can monitor all the signals present in the system, as well use the configuration presets in relation to the Swap Page. The dedicated controls for dynamic, EQ, routing and select located above the faders have dual function. In the other mode of operation, these controls turn into send buttons that route the signals to buses, such as master 1, master 2, aux 1 and aux 2. The user may request the on and off controls on top or below the faders. To facilitate easy maintenance, each console offers changeable modules.

800-728-0536

www.aeqbroadcast.com
sales@aeqbroadcast.com

Stereo condenser microphone

Marshall Electronics

MXL 990 USB: The MXL 990 USB stereo condenser microphone features two gold diaphragm capsules in an X/Y stereo configuration. The MXL 990 connects directly to a computer without the need for external mic preamps. The microphone features twin gold sputtered capsules (20 mm each) and this pressure-gradient stereo condenser microphone features a 20Hz to 20kHz frequency response. The digital section of the microphone features a 16-bit Delta Sigma A/D converter with sampling rates of 44.1kHz and 48kHz.

800-800-6608; www.mxlmics.com; sales@mxlmics.com



Multimedia work environment

Forecast Consoles

Soho: The Soho signature series is built with Masterail technology. It offers cable power and management, side cars (rack mount or drawer), additional monitor arms and toolbars, additional speak pods, equipment turrets and a console equipment wedge.


800-735-2070; www.forecast-consoles.com
info@forecast-consoles.com

Protocol translator, controller

Kramer Electronics

FC-5: The FC-5 is a protocol translator designed to make an RS-232-controlled machine compatible with other RS-232-based protocols. Because the FC-5 will work with any RS-232 controllable product and can convert RS-232 commands to contact closure and relay control signals, it will also make system integration of various components such as screens and drapes easier. The translator comes pre-configured with two serial translation tables, a generic serial switcher control protocol to Kramer's Protocol 2000 and the Sierra Video Systems' serial protocol to Kramer's Protocol 2000. The FC-5 can be programmed to work with up to four translation tables, each with up to 256 commands.

888-275-6311; www.kramerelectronics.com
info@kramerelectronics.com



Coaxial Dynamics

A CDI INDUSTRIES, INC. COMPANY
Specialists in RF Test Equipment & Components



Visit Us at
NAB/Las
Vegas
Booth #
N6315

Coaxial Dynamics (a CDI Industries, Inc. Company)
6800 Lake Alman Drive • Middleburg Hts, OH 44130
Phone: 440-243-1100 Toll Free: 800-COAXIAL Fax: 440-243-1100
sales@coaxial.com • www.coaxial.com

When is Dad coming home?

Workplace safety is a growing concern in today's changing industry. RSI can help you make it home to the people that matter most to you, your family.

With years of real world experience, RSI's qualified instructors have taught FF safety to hundreds of industry workers. Protect yourself, protect your employees. Let RSI help you to develop a workplace where everyone makes it home.



RSI: The Original University based telecomm safety services provider.

888-830-5648
www.rsicorp.com
Visit us at PCIA booth 111



2007 PRODUCT SOURCE

2007 PRODUCT SOURCE

GALLERY

2007 PRODUCT SOURCE

AM Antenna Solutions

Reach Farther, Sound Better!



Directional Antenna Systems

LBA is your trusted supplier for IBOC-ready AM antenna systems. For over 40 years we have been designing and manufacturing reliable *Directional Antenna Systems, ATU's, Multiplexers, Combiners, Cellular/PCS Colocation Isolators, and RF Components* for all power levels.

Choose an LBA system and join thousands of satisfied broadcasters in the US and worldwide!


LBA can also design, manage, install and finance your complete RF project. Please call us for a free technical consultation!



Diplexer/Triplexer Systems



RF Components



High-Power Antenna Tuning Units



IBOC PHASE ROTATORS AVAILABLE!

Factory Dealer For:







SINCE 1963

LBA Technology, Inc.

3400 Tupper Drive, Greenville, NC 27834
800-522-4464 / 252-757-0279 Fax: 252-752-9155
Contact Jerry Brown: jbrown@LBAGroup.com

www.LBAGroup.com

SONIFEX

Manufacturers of Audio Broadcast Equipment

Stop seeing red. Start seeing Redbox

RB-DA6: 1 of the first 5 Redboxes launched in 1999. Now part of over 40 units that make up the redbox range.

Only The Best
Redbox - Designed and manufactured to the highest specifications

- Interfaces • Headphone Distribution Amplifiers
- Audio Distribution Amplifiers • Digital Audio Converters
- Matching Converters • Microphone Amplifiers & Limiters
- Mixers & Source Selectors • Stereo To Mono Converters
- Synchronizers, Delays & Silence Detectors

Visit our website for details: www.sonifex.co.uk







T: 207 773 2424
E: Info@Independentaudio.com
www.independentaudio.com

Investigator V3 FM

Now included:
3-second USGS Terrain Block Level census data The Antenna Structure Registry Database One set of National Geographic TOPO! Maps

Things are no longer locked together. With multiple monitors, move the job control, station table, and other tool boxes to one screen then, expand the map to full size on another. The map is now a resizable rectangle.

It is easier than ever to keep your clients informed or to create your FCC engineering exhibits. Just create the contours and show the cities put some labels and arrows on to identify everything, save map to clipboard, and paste it into your word processing program. You can also export the contours as KML files to display on Google Earth.

Our White/Gray tool is the latest development in the program. We try to give our clients the tools they need and have requested.



rfSoftware, Inc.
Innovative engineering tools
alex@www.rfsoftware.com



Radiocube

352-367-1700

This is a small ad for a **GREAT RADIO AUTOMATION SOFTWARE** with a small price, too!

Get your free demo today: www.radiocube.com

We beat the competition.

Software for Station Operators and DJ's

Transcom Corporation

Fine Used AM & FM Transmitters
Authorized Representatives for all major equipment manufacturers

<p>USED FM TRANSMITTERS</p> <table border="0" style="width: 100%; border-collapse: collapse;"> <tr><td>1 KW</td><td>2007</td><td>Crown FM1000A (new)</td></tr> <tr><td>1 KW</td><td>2007</td><td>Crown FM1000E (new)</td></tr> <tr><td>1 KW</td><td>2001</td><td>Harris Quest 1</td></tr> <tr><td>2 KW</td><td>1999</td><td>Crown FM2000A</td></tr> <tr><td>7 KW</td><td>2002</td><td>Harris Z16 IBOC</td></tr> <tr><td>7+ KW</td><td>2005</td><td>Harris Z16 HOS IBOC</td></tr> <tr><td>10 KW</td><td>2001</td><td>Henry 10,000D-95</td></tr> <tr><td>20 KW</td><td>1985</td><td>Harris FM20K</td></tr> <tr><td>20 KW</td><td>1989</td><td>QEI FMQ 20,000B</td></tr> <tr><td>25 KW</td><td>1990</td><td>Continental 816R-3B</td></tr> <tr><td>25 KW</td><td>1980</td><td>Harris FM25K</td></tr> <tr><td>35 KW</td><td>1987</td><td>Harris FM35K</td></tr> <tr><td>50 KW</td><td>1982</td><td>Harris Combiner w/auto exciter-transmitter switcher</td></tr> </table>	1 KW	2007	Crown FM1000A (new)	1 KW	2007	Crown FM1000E (new)	1 KW	2001	Harris Quest 1	2 KW	1999	Crown FM2000A	7 KW	2002	Harris Z16 IBOC	7+ KW	2005	Harris Z16 HOS IBOC	10 KW	2001	Henry 10,000D-95	20 KW	1985	Harris FM20K	20 KW	1989	QEI FMQ 20,000B	25 KW	1990	Continental 816R-3B	25 KW	1980	Harris FM25K	35 KW	1987	Harris FM35K	50 KW	1982	Harris Combiner w/auto exciter-transmitter switcher	<p>EXCITERS</p> <p>*New* 20 and 30 W synthesized exciters Used 2004 Harris Digit 2nd Generation</p> <p>NEW TV TRANSMITTERS</p> <p>Special Discount Pricing On: VHF and UHF TV Antennas (10W to 10KW) TV STL</p> <p>USED TV TRANSMITTERS</p> <p>1 KW UHF Axcerra 832A, CH 28</p> <p>USED AM TRANSMITTERS</p> <p>2.5 KW 1986 Harris SX2.5A-single phase 5 KW 1974 Continental 315F 5 KW 1982 Harris MW5A 5 KW 1987 Harris MW5B 5 KW 1988 Harris SX5A-single phase 10 KW 1985 Continental 316F 50 KW 1985 Continental 317 C2</p>
1 KW	2007	Crown FM1000A (new)																																						
1 KW	2007	Crown FM1000E (new)																																						
1 KW	2001	Harris Quest 1																																						
2 KW	1999	Crown FM2000A																																						
7 KW	2002	Harris Z16 IBOC																																						
7+ KW	2005	Harris Z16 HOS IBOC																																						
10 KW	2001	Henry 10,000D-95																																						
20 KW	1985	Harris FM20K																																						
20 KW	1989	QEI FMQ 20,000B																																						
25 KW	1990	Continental 816R-3B																																						
25 KW	1980	Harris FM25K																																						
35 KW	1987	Harris FM35K																																						
50 KW	1982	Harris Combiner w/auto exciter-transmitter switcher																																						

Please visit our web site, www.fmamtv.com, for current listings or CALL US FOR A QUOTE!

2655 Philmont Ave. Suite 200, Huntingdon Valley, PA 19006
800-441-8454 215-938-7304 Fax: 215-938-7361

USE THE COUPON BELOW AND
SAVE 10% ON YOUR NEXT ORDER!

Freeland Products, Inc.
Rebuilder of Quality Tubes Since 1940

www.freelandproducts.com
75412 Highway 25, Covington, LA 70435
800-624-7626 * 985-893-1243 * Fax 985-892-7323

E-mail freeland-inc.com@freeland-inc.com

Are you looking for ways to cut your engineering budget, while maintaining the highest quality for your station?

We offer a great warranty, quick service and technical support for our customers 24/7. We can bank your rebuilt tube too, until you need it, just ask.

We have a LARGE stock of commonly used tubes ready to ship. If you're in a hurry we can ship from stock. Call 800-624-7626 for more information!

Take 10% off the cost of your next Rebuilt Transmitter Tube.
~coupon copies are not VALID~
This original coupon MUST accompany the used tube when sending for rebuild.

FCC Certified FM Stereo Transmitters

GET ON-THE-AIR. STAY ON-THE-AIR!

- ✓ 50W RF output continuous duty!
- ✓ Auto protect, auto soft fail, auto restore!
- ✓ Automatic battery backup!
- ✓ Digital display of all parameters!
- ✓ Simple to install!

What's the bottom line? To stay on the air! The PX50 was designed with that in mind! Auto monitoring of all parameters, with automatic power reduction and restore on VSWR and temperature errors! No more down time AND no more trips to the tower site! Plus the PX50 is FCC Certified under parts 2, 73, & 74 (PFPX50) and Industry Canada approved (IC: 4318A-PX50) so you never have to worry about non compliance! Make your life easy with the PX50 from Ramsey!

THE ORIGINAL... "STATION-IN-A-BOX"

Since the introduction of our "Station-In-A-Box" hundreds have been put in service worldwide! From temporary locations, rapid deployment installations, to emergency broadcast facilities, there is no quicker way to get on the air!


RAMSEY ELECTRONICS, LLC
590 Fishers Station Drive, Victor, NY 14564
800-446-2295 • 585-924-4560
www.ramseybroadcast.com

40

2007 Radio Product Source

www.RadioMagOnline.com

Broadcast Engineering Propagation Software



Professional software packages for FCC applications and predicting coverage.

- Create stunning "real-world" coverage maps and interference studies using Longley-Rice, TIREM, ITU-R P.1546-1, PTP, FCC and others with Probe 3™
- Search FM channels under spacings and contour protection using FMCommander™
- Prepare AM skywave and groundwave allocations studies and map FCC contour coverage using AM-Pro 2™
- Plot STL paths and coverage over 3D terrain with Terrain-3D™



The leader in broadcast engineering consulting software.

www.v-soft.com 800 743-3684

Remote Broadcast Solutions!!!



MiCTel - Mic/Line to Telephone Interface

- ▷ Outputs & Inputs for telephone handset, cellular phone or balanced line level at up to +10dEm.
- ▷ Operates up to 36+ hours on two 9V alkaline batteries.
- ▷ High quality, user-switchable, internal limiter prevents clipping.
- ▷ External power input with silent, auto-switching battery backup.

▷ Individual gain controls for send, receive and headphones levels.

CircuitWerkes, Inc.
352-335-6555
2805 NW 6th Street,
Gainesville, Florida 32601, USA



TelTap - Pocket-Sized Manual Telephone Coupler

- ▷ Can be used as a phone tap or a passive manual telephone coupler.
- ▷ Send or receive telephone audio.
- ▷ Mute Switch disconnects all audio to or from the phone line, but leaves the TelTap connected.
- ▷ Compact size & low cost makes the TelTap a great remote kit addition for main or backup capabilities.

Get info on these & other great remote products at www.circuitwerkes.com



DO WE HAVE A FLASHER FOR YOU!
NO, NOT THAT ONE,
THIS ONE!
INTRODUCING THE STUDIO
HOT LINE SERIES

THE FIRST PHONE FLASHER, ALERT AND DOOR INDICATOR SYSTEMS THAT ARE DESIGNED EXCLUSIVELY FOR BROADCASTERS, WITH THE FOLLOWING FEATURES:

- * Distinctive color multiple ultra-brite wide angle LED flashers and distinctive audible alerts for both phone, alert or door
- * Single line stand-alone units and multi-line systems available with up to 12 lines in and up to 5 display indicator modules
- * Audible alerts muted by contact closure or logic low
- * Driving voltage output provided for the DME Solid State Relay Pack for lighting incandescent lamps
- * Adjustable volume for audible alerts (Off-Low-High)

FOR MORE INFORMATION, PRICING, ETC. ABOUT THESE AND OTHER INNOVATIVE PRODUCTS FOR THE BROADCASTER PLEASE VISIT OUR WEBSITE AT:

WWW.DMENGINEERING.COM
805-987-7881 800-249-0487

Ram Broadcast Systems
builds studios for most of North America's major networks, group stations, and news organizations. Ram offers comprehensive studio design, fabrication, systems-integration, and custom furniture. Put Ram's 35 years of experience to work for you!

RAM Broadcast Systems
www.ramsyscom.com
800.779.7575

More ways to access the Radio Technology Leader

Each month in print




Every day online



Via e-mail



With a podcast



2007 PRODUCT SOURCE

2007 PRODUCT SOURCE

Radio newsroom software can make your web site look a lot better

Web publishing can be as easy as sending an email.

Have the best web site in your market.



wjbc.com kpbs.org Regent
wfir960.com 580wdbo.com
wsmiradio.com Emmis Cox
kbkw.com mix96.net
hoosieragtoday.com
kiow.com ktlo.com
knzafm.com kcnzam.com
wsjm.com kuaz.org wif.org
750kerr.com Mid-West Family
networkindiana.com
mnnradio.com & many more!

- Use the news & sports you just aired - publish text, audio & video all in one step
- Eliminate tedious cut & paste submission forms
- Non-proprietary - compatible with your existing web servers, ISP and CMS
- Revamp your existing sites or start from scratch
- Great for podcasting, RSS, school closings & more
- Newsroom & web publishing software info:
wireready.com/webready
wireready.com/newsready
- Solutions start as low as \$1495

(800) 833 4459
sales@wireready.com

The Ultimate IBOC Receiver/Translator

Designed to accommodate "full envelope" baseband signals (IBOC and analog), Fanfare's new age receiver/translator, the TRO, is fully self-contained and does not require an IBOC exciter. In fact, it arrives ready for full deployment under all existing FM modulation forms.

Along with the savings in not requiring a proprietary exciter, the TRO-1 offers considerable versatility. Installation is simplified, requiring only connection to the receiving antenna and a linearized PA. Operational settings are via the front panel control center or by RS232 serial data I/O.

At the heart of the TRO design and what makes it work is patented NTP-based technology, which enables the TRO's unique method of translation. In effect, this NTP-based process removes noise from consideration by establishing a noise floor that is well below normal measure. Such significant noise reduction manifests itself in significantly increased sensitivity and adjacent noise rejection.



P.O. Box 386 Lancaster NY 14086

Website "www.fanfare.com"

1-800-268-8637

FAX - 866-791-7443

Email "proinfo@fanfare.com"

Emergency Warning & Community Messaging using your FM station with free RDS equipment.

Available today!



Call us for more information

viaRadio
Radio Data Systems

Specializing in RDS/RBDS solutions

ViaRadio Corporation
(321) 242-0001
www.viaradio.com
Info@viaradio.com

from MILLIWATTS to KILOWATTS™

Transmitting & Audio Tubes
Semiconductors

Taylor
Eimac
Amperex
MA/Com

Immediate Shipment from Stock

Motorola
Toshiba
Thompson
Mitsubishi

• Se Habla Español • We Export

760-744-0700 • 800-737-2787
Fax: 760-744-1943

www.rfparts.com

E-mail:
rfp@rfparts.com



3801 La Plata Hwy
Farmington, NM 87401
Phone 505-327-5646
Fax 505-325-1142

Folded Unipole

Antennas



Detuning Systems



Gilastat Lightning Dissipation Systems



Nello Towers

Radian/Rohn Towers

www.nottltd.com
info@nottltd.com

ADVERTISER INDEX

This index is a service to readers. Every effort is made to ensure accuracy, but Radio magazine cannot assume responsibility for errors or omissions.

Advertiser's Name	Page Number	Advertiser Hotline	Advertiser Website	Advertiser's Name	Page Number	Advertiser Hotline	Advertiser Website
Acoustics First	35	888-765-2900	www.acousticsfirst.com	Mager Systems	32	623-780-0045	www.magersystems.com
Aphex Systems	17	818-767-2929	www.aphex.com	Mediatron	40	800-779-7575	www.mediatron.com
Armstrong Transmitter Corp.	27	315-673-1269	www.armstrongtx.com	Mooretronix	42	800-300-0733	www.mooretronix.com
Arrakis Systems	12	970-224-2248	www.arrakis-systems.com	Nott Ltd.	42	505-327-5646	www.nottltd.com
AudioScience	37	302-324-5333	www.audioscience.com	OMB America	10	305-477-0973	www.omb.com
Broadcast Software International	16	888-BSIUSA1	www.bsiusa.com	Omnirax	14	415-332-3392	www.omnirax.com
Circuit Werkes	41	352-335-6555	www.circuitwerkes.com	Qei Corporation	18	800-334-9154	www.qei-broadcast.com
Coaxial Dynamics	39	440-243-1100	www.coaxial.com	Radio Systems	29, 31	856-467-8000	www.radiosystems.com
Comrex	5	978-784-1717	www.comrex.com	Ram Broadcast Systems	41	847-487-7575	www.ramsyscom.com
Crown Broadcast/IREC	20	866-262-8972	www.crownbroadcast.com	Ramsey Electronics	40	800-446-2295	www.ramseyelectronics.com
Danagger Audio Works	38	888-892-8346	www.danagger.com	RCS/Prophet Systems	11	877-774-1010	www.prophetsys.com
Dayton Industrial	28	941-351-4454	www.daytonindustrial.com	RF Parts	42	800-737-2787	www.rfparts.com
Dixon	36	416-261-3773	www.dixonsystems.com	RF Software	40	352-367-1700	www.rfsoftware.com
DM Engineering	41	800-249-0487	www.dmengineering.com	RSI	39	888-830-5648	www.rsicorp.com
ERI-Electronics Research	32	812-925-6000	www.ERlinc.com	SabreCommunications	24	800-369-6690	www.sabrecom.com
ESE	26	310-322-2136	www.eseweb.com	SCMS, Inc.	24	800-438-6040	www.scmsinc.com
Fanfare FM	42	800-26-TUNER	www.fanfare.com	Shively Labs	30	888-SHIVELY	www.shively.com
Flash Technology	20	888-313-5274	www.flashtechology.com	Sierra Automated Systems	22, 23	818-840-6749	www.sasaudio.com
Freeland Products	40	800-624-7626	www.freelandproducts.com	Sonifex	40	207-773-2424	www.independentaudio.com
Full Compass	25	800-356-5844	www.fullcompass.com	Telos Systems	21	216-241-7225	www.telos-systems.com
Google	1	888-438-7268	www.google.com/ads/asaudio	Tieline Technology	13	888-211-6989	www.tieline.com
Graham Studios	30	866-481-6696	www.graham-studios.com	Titus Technology Labs	37	800-806-8851	www.tituslabs.com
Harris Corp. Broadcast Div.	3	800-622-0022	www.broadcast.harris.com	Transcom Corp.	40	800-441-8454	www.fmamtv.com
Heil Sound	9	618-257-3000	www.heilsound.com	VeeTronix	19	800-445-0007	www.veetronix.com
Inovonics	35	831-458-0552	www.inovonics.com	Via Radio	42	321-242-0001	www.viaradio.com
Jampro	26	866-452-6770	www.jampro.com	V-Soft Communications	41	800-743-3684	www.v-soft.com
JK Audio	15	800-552-8346	www.jkaudio.com	Wheatstone	2, 43, 44	252-638-7000	www.wheatstone.com
Kay Industries	28	800-348-5257	www.kayind.com	WireReady	42	800-833-4459	www.wireready.com
Lavry Engineering	34	360-598-9757	www.lavryengineering.com	Yellowtec	7	+49-2173-967-315	www.yellowtec.com
LBA Technology	40	800-522-4464	www.lbagroup.com				

This Little Unit



Can Do **BIG** Things!

Our new AP-3 is the perfect HD Processor:



SETTING UP FOR HD RADIO?

The Vorsis AP-3 digital processor is the ideal tool to shape your sound exactly the way you want it — cleanly and efficiently.

Built around a multi-band compressor with complementary AGC, the AP-3 replaces a whole rack of dedicated units. VORSIS pre-conditions your signal (HPF, LPF, notch filter, de-esser, expander), then let's you apply 3-band AGC/compression and 4-band parametric EQ (signal chain reversible) before going through a final stage zero-overshoot peak limiter.

With real-time spectrum density readouts and full metering, our included PC graphic interface software makes operation of the AP-3 direct and easy, offering complete control of all audio parameters, presets, monitor functions, system settings and security—all through a single RJ-45 ethernet connection that lets you control one or many AP-3 units.

TAILOR THAT SOUND

VORSIS®

THE TOOLS HAVE CHANGED...



BUT THE MISSION REMAINS THE SAME

Today's audio control surface has evolved to a very high degree. Yesterday's wish list is today's feature set: total router integration, routable audio and logic, total show recall, and a complete set of DSP audio processing are under the hood of this G7...

All in a package of stainless steel and aluminum designed for years of 24/7 service, with a familiar look and feel that will *help your talent make years of great radio.*

Networked audio requires a higher level of expertise, experience and resources. Benefit from all three with **WHEATSTONE!**

WE MAKE THE GOOD STUFF

 **Wheatstone**