

The New Models

So many new tape recorders have been introduced this season that it has been impossible to describe them all fully when they first appeared. In this regular feature, we shall provide photographs and full specifications of models which have recently made their bow.



TRIX "COMET"

A popular priced recorder with the new Garrard magazine-loading tape feature.

Manufacturer's Specifications

Price: 35 gns. Deck: Garrard "Bichette."
Speed: $3\frac{1}{2}$ ips. Rewind speed: 45 seconds.
Recording sense: half track, left to right.
Frequency response: 30—10,000 cps.
Wow and flutter: Better than 0.2 and 0.05 per cent.
Signal-to-noise ration: —50 dB.
Output: 3 watts. Weight: 24 lb.
Size: $14\frac{1}{2}$ x $13\frac{1}{2}$ x 8 in. Max. spool size: 4 in., in cassette.
Speaker: 7 x 4 in. elliptical. Microphone: crystal.
Other facilities: Superimposition, magic eye, tone control, inputs for microphone, radio/gram, extension speaker sockets, can be used as a straight-through amplifier.

TRIX ELECTRICAL COMPANY LTD., 1-5, MAPLE PLACE, LONDON, W.1.

LEE PRODUCTS TR 400

Another inexpensive and compact machine using the B.S.R. Monardeck.

Manufacturer's Specifications

Price: 26 guineas. Deck: B.S.R. Monardeck.
Speed: $3\frac{1}{2}$ ips. Rewind speed: 3 minutes.
Recording sense: normal half track, left to right.
Frequency response: 80-8,000 cps.
Output: $2\frac{1}{2}$ watts. Weight 17 lb.
Size: 14 x $11\frac{1}{2}$ x 6 in. Max. spool size: $5\frac{1}{2}$ in.
Speaker: 8 x $2\frac{1}{2}$ in slot.
Microphone: crystal.
Other facilities. Monitoring, magic eye, separate bass/treble controls, inputs for mic, radio/gram, can be used as a straight through amplifier.

LEE PRODUCTS (GREAT BRITAIN) LTD.,
ELPICO HOUSE, LONGFORD STREET, N.W.1.



FIDELITY ARGYLL

An all British-constructed machine with a wide range of facilities.

Manufacturer's Specifications

Price: 29 guineas. Deck: B.S.R. Monardeck.
Speed: $3\frac{1}{2}$ ips. Rewind speed: 3 minutes (850 ft.).
Recording sense: normal half track, left to right.
Frequency response: 60-10,000 cps.
Signal-to-noise ratio: 50 dB down.
Wow and flutter: total .4 per cent R.M.S.
Output: 4 watts. Weight: 22 lb.
Size: 17 x $13\frac{1}{2}$ x $7\frac{1}{2}$ in. Maximum spool size $5\frac{1}{2}$ in.
Speaker: 7 x 4 in., high flux.
Microphone: high gain crystal.
Other facilities: Superimposition, monitoring, mixing, tone control, input sockets for mic, radio/gram, output socket for extension loudspeaker, safety erase lock, can be used as a straight through amplifier, storage place included for microphone, mains lead and two spare reels of tape.

FIDELITY RADIO LTD., 11-13, BLECHYNDEN STREET, W.11.

